# Boulevard Central District

**Modernizing Planning and Zoning**
**in Amherst's Major Commercial Center**
**to Encourage Revitalization**

## Supplemental Draft Generic Environmental Impact Statement

## Town of Amherst

***Prepared for:***

*Town of Amherst*
*Municipal Building*
*5583 Main Street*
*Williamsville, NY 14221*

***Prepared by:***

*2200 Main Place Tower*
*Buffalo, NY 14202-3722*

*SDGEIS Acceptance: _____*
*Pubic Hearing: _____*
*Comment period deadline: _____*

# Boulevard Central District

## Modernizing Planning and Zoning in Amherst's Major Commercial Center to Encourage Revitalization

## Supplemental Draft Generic Environmental Impact Statement

**Town of Amherst**
**Erie County, New York**


**Lead Agency:**
**Town of Amherst Town Board**
5583 Main Street
Williamsville, NY 14221

**Contact Person:**
**Daniel Howard, AICP**
Planning Director
(716) 631-7051

**Prepared by:**
**CHA Consulting, Inc.**
2200 Main Place Tower
Buffalo, NY 14202-3722
CHA FILE 088431

**Contact Person:**
**Christopher R. Einstein**
Principal Planner
(518) 453-4505

**Assisted by:**

**Town of Amherst Planning Dept**
5583 Main Street
Williamsville, NY 14221

**Land Use & Zoning**
Kimberly Amplement, Senior Planner
Roberta Rappoccio, Associate Planner

**Town of Amherst Engineering Dept**
1100 N Forest Road
Williamsville, NY 14221

**Sewer**
Jeffrey Burroughs, Town Engineer

**Water**
Brian Armstrong, Engineering Services Administrator

**C&S Companies**
141 Elm Street, Suite 100
Buffalo, NY 14203

**Traffic**
Kelsey Wessel, Managing Engineer

**Greater Buffalo Niagara Regional Transportation Council**
438 Main St, #503
Buffalo, NY 14202

**SECTION** **PAGE #**

**EXECUTIVE SUMMARY** ..... ***ES-1***

**1.0 INTRODUCTION** ..... **1-1**
- 1.1 Project Location and Project Setting ..... 1-2
- 1.2 Project History ..... 1-4
- 1.3 The State Environmental Quality Review Act Process (SEQRA) ..... 1-5

**2.0 PROJECT DESCRIPTION** ..... **2-1**
- 2.1 Project Purpose and Need ..... 2-1
- 2.2 Study Area Planning ..... 2-3
- 2.3 2025 Projected Growth Redevelopment Scenario ..... 2-8

**3.0 ENVIRONMENTAL SETTING, POTENTIAL IMPACTS & MITIGATION** ..... **3-1**
- 3.1 Transportation ..... 3-1
- 3.2 Utilities ..... 3-23
- 3.3 Unavoidable Adverse Impacts ..... 3-45

**4.0 ALTERNATIVES** ..... **4-1**
- 4.1 Alternative 1: Maximum Buildout Scenario ..... 4-1
- 4.2 Alternative 2: High Growth 20-Year Redevelopment Scenario ..... 4-2
- 4.3 Alternative 3: 2020 Projected Growth Redevelopment Scenario ..... 4-2
- 4.4 Alternative 4: 2025 Projected Growth Redevelopment Scenario ..... 4-2
- 4.5 No-Action Alternative ..... 4-2

**5.0 IRREVERSIBLE & IRRETRIEVABLE COMMITMENT OF RESOURCES** ..... **5-1**

**6.0 USE AND CONSERVATION OF ENERGY** ..... **6-1**

**7.0 FUTURE SEQR ACTIONS** ..... **7-1**

**8.0 REFERENCES** ..... **8-1**

**APPENDICIES**
- Appendix A SEQR Documentation
- Appendix B Land Use and Zoning Documentation
- Appendix C Traffic Data
- Appendix D Water & Sewer Data

## LIST OF MAPS

Page #
Map 1.1-1 BCD Study Area ..... 1-3
Map 2.3-1 TAZ Boundaries ..... 2-11
Map 2.3-2 Reducing the Analysis Area ..... 2-15
Map 2.3-3 Potential Redevelopment Areas ..... 2-16
Map 2.3-4 Existing Land Uses ..... 2-19
Map 2.3-5 Projected Future Land Uses ..... 2-20
Map 2.3-6 Projected Number of Stories ..... 2-21
Map 2.3-7 Existing Zoning ..... 2-22
Map 2.3-8 Projected Future Zoning ..... 2-23
Map 3.1-1 Study Corridors ..... 3-2
Map 3.1-2 Functional Classifications ..... 3-5
Map 3.1-3 Study Area Intersections ..... 3-6
Map 3.1-4 Pedestrian and Bicycle Accommodations ..... 3-8
Map 3.1-5 Public Transit ..... 3-9
Map 3.1-6 Collisions ..... 3-12

## LIST OF TABLES

Page #
Table 2.3-1 Growth Projections Comparison ..... 2-28
Table 3.1-1 Study Corridors ..... 3-3
Table 3.1-2 Intersection LOS Criteria ..... 3-10
Table 3.1-3 Boulevard Central District TAZ Growth Projections ..... 3-15
Table 3.1-4 Estimated Mitigation Improvement Costs ..... 3-19 & 3-20
Table 3.1-5 Threshold Analysis for Improvements ..... 3-21
Table 3.1-6 Public/Private Share Costs ..... 3-22
Table 3.2-1 Historical SSO Volumes ..... 3-24
Table 3.2-2 Measurements at Sewer Meter Locations ..... 3-28
Table 3.2-3 Simulated Water Pressures in Study Area ..... 3-32
Table 3.2-4 Simulated Available Fire Flows in Study Area ..... 3-33
Table 3.2-5 Mitigation Costs ..... 3-35
Table 3.2-6 Selected Sewer Segment Capacities ..... 3-36
Table 3.2-7 Baseline Sewer Mitigation Costs ..... 3-42

## LIST OF FIGURES

Page #
Figure 2.2-1 Urban Renewal Area ..... 2-5
Figure 3.2-1 West Side Interceptor Sewersheds ..... 3-26
Figure 3.2-2 Flows and Capacities of Primary Interceptors ..... 3-27
Figure 3.2-3 Mini-System Analysis Overview ..... 3-29
Figure 3.2-4 Location of Cast Iron Mains to be Replaced for Mitigation ..... 3-34

# EXECUTIVE SUMMARY

## Project Description

The Town's current Boulevard Central District Generic Environmental Impact Statement (BCD GEIS) was prepared in late 2019 and adopted in January 2020. The document specifies that the GEIS may be supplemented or updated pursuant to 6 NYCRR Part 617.10(d) of SEQR which states *"Generic EISs and their findings should set forth specific conditions of criteria under which future actions will be undertaken or approved, including requirements for any subsequent SEQR compliance. This may include thresholds and criteria for supplemental EISs to reflect specific significant impacts, such as site-specific impacts, that were not adequately addressed or analyzed in the generic EIS."*

A variety of changes have occurred over the past several years that signal a need to reevaluate the BCD GEIS, the most significant of which are the assumptions leading to the projection of land use, zoning, and the type and magnitude of development. This in turn requires a reevaluation of potential impacts and corresponding mitigation with a Supplemental GEIS.

The Boulevard Central District is an approximately 1,264-acre portion of the Town of Amherst, bounded on the east and north by the Interstate 290 (I-290), the west by Niagara Falls Boulevard and on the south by Sheridan Drive, as well as including properties immediately to the south of Sheridan Drive (Study Area). In 2020, the Town adopted the Boulevard Central District GEIS and Statement of Findings that evaluated the cumulative impacts of growth within the Study Area for a Projected Growth Redevelopment Scenario, based on new mixed-use zoning. Although the Study Area is generally built out, it includes numerous underutilized sites, representing a significant opportunity for redevelopment and reinvestment.

Several significant trends and recent studies have emerged and conditions have changed since 2019-2020, when the Town's BCD GEIS was prepared and adopted. These changes have influenced the Town's decision to revise its land use growth assumptions and prepare this 2025 Supplemental GEIS. These trends are discussed in detail in Section 2.0 of the SDGEIS and are summarized as:

- A decline in office space demand that emerged post-COVID with more work-from-home opportunities
- An increase in medical office demand
- Continued influence on E-commerce that has diminished demand for retail space
- An increase in light industrial demand, especially for warehousing and logistics
- An increase in rental housing demand
- Rising construction costs and interest rates
- More selective bank financing

Other factors affecting the amount and distribution of growth within the BCD include:

- Discrepancies between the final zoning and the assumptions used in the original GEIS, particularly the mixed-use zoning
- Focused vision for the BCD through an Action Plan adopted in 2021 that led to refined development projections
- Designation of the Boulevard Mall and some surrounding properties as an Urban Renewal Area and the creation of an Urban Renewal Plan in 2022
- Completion of a Strategic Economic Development Plan in 2023 with identified opportunity sites
- Infrastructure improvements to address sewer capacity issues
- Recently proposed or constructed projects that are inconsistent with the intended zoning and are not to the scale anticipated in the original GEIS

## Zoning

The Town approved the application and mapping of mixed-use zoning districts in December 2020 for the majority of non-residential parcels within the BCD. However, some areas in the original GEIS that were anticipated to be rezoned to mixed-use districts were not. With recent experience using the provisions of the mixed-use districts, the Town has found the utilization of these districts to be a bit challenging and is currently in the process of proposing changes to these districts. The Town has also not seen the higher density redevelopment in the BCD that was anticipated with the adoption of the mixed-use districts. Based on these factors along with discussions with the development community, proposed changes to the land use and zoning projections were necessary to facilitate future redevelopment of the BCD.

## Growth Projection

Growth projections have to be associated with a growth period. Consistent with the original GEIS, a 20-year timeframe was used and it was determined that the Supplemental GEIS would incorporate a new 20-year period as opposed to using the remaining 15 years of the original GEIS.

Growth was distributed over the study area in order to evaluate the potential impacts on the BCD. This is accomplished through the work undertaken by the Town to investigate growth trends, developable and re-developable lands within the study area, and zoning. However, to analyze growth by geographic areas, the Town continued to use Traffic Analysis Zones (TAZ), consistent with the original GEIS.

Undertaking a process of detailed land use analysis, the Town Planning Department reduced the area of potential redevelopment based first on the elimination of areas (primarily residential) that are unlikely to be redeveloped over time and further reduced this developable area based on what could reasonably be expected to redevelop over the next 20 years. This reduced the overall acreage of potential developable land from the initial study area of 1,264 acres down to approximately 265 acres. See Section 2.0 for graphics illustrating the potential developable areas within the BCD.

Commercial growth (office & retail) within the BCD was projected through a thorough analysis process, considering several factors. A building analysis was conducted to determine the likelihood of a building to remain and those to be completely redeveloped over the 20-year growth period. A land use and zoning analysis was conducted to determine the likely future land uses for the areas likely to be redeveloped. The existing zoning provides the maximum development potential through bulk regulations, particularly lot coverage and number of stories. Building use composition (percent of retail vs. office) is an often difficult assessment and has changed since the original GEIS with declining demand for office space and increasing vacancy rates following the COVID-19 pandemic.

Future residential growth was based on the following assumptions and analysis:

- The continued, but diminished, growth of student housing to serve the 30,000 students at the University of Buffalo (UB);
- A larger residential component as part of the commercial redevelopment within the BCD;
- Town-wide growth rate of 2 percent for housing;
- Growing trend towards siting multi-family and mixed-use projects within regional commercial areas and where the size and scale of such buildings are more amenable to neighboring properties; and
- The development community's increasing incorporation of upper-floor housing in commercial projects to ensure project viability.

Based on the new commercial and residential growth assumptions, the following thresholds for the Projected Growth Redevelopment Scenario were modified and established for the new 20-year planning period.

***2019***

- 5,000 Housing Units
- 1,900,000 SF Commercial Retail
- 1,100,000 SF Commercial Office

***2025***

- 4,921 Housing Units
- 2,258,676 SF Commercial Retail
- 303,268 SF Commercial Office

## Evaluation of Potential Impacts and Mitigation

### Land Use and Zoning

Because the new assumptions in the 2025 Projected Growth Redevelopment Scenario regarding the land use and mixed-use zoning is expected to result in an overall decrease in the redevelopment potential compared to the current zoning, no significant adverse land use impacts are anticipated as a result of this action.

The Study Area is one of the densest sections of Amherst that has historically seen a great deal of commercial development. It is recognized that the intensity of uses in this area will likely continue. The Town wishes to see new growth occur in a much more sustainable and desirable manner and hopes the mixed-use zoning will provide this flexibility in design that supports more walkable, integrated development. This development is much more likely to be compatible with surrounding neighborhoods along with generating economic growth in the Town.

This potential also exists under some of the other zoning districts in the Town's Zoning Code, but would probably be much less sustainable with the continuation of the existing patterns of development and redevelopment (repurposing strip plazas and big box retail with large surface parking areas). The specific implications of increased density within the Study Area over current conditions are discussed under each of the impact topics. The mixed-use zoning districts promote diverse commercial and residential uses and reduce the vacant and underutilized properties with redevelopment that is respectful of the surrounding residential neighborhoods by providing buffers, as well as connections between neighborhoods, commercial areas, and public spaces that should have a beneficial impact on mobility and overall quality of life.

### Transportation

The results of the intersection analyses show that the overall operations of most of the Study Area intersections are at Level of Service (LOS D) or better during the AM and PM peak hours for

the Existing and Planned Conditions. These operations are consistent with local and regional mobility objectives. The exceptions are as follows:

**Existing Condition**

| | |
|---|---|
| Niagara Falls Boulevard and Sheridan Drive | PM – LOS E |
| Maple Road and Sweet Home Road | PM – LOS E |

The same capacity analysis methodology used to evaluate the Existing Condition was also used to project the Planned Condition to assess the ability of the road network to carry the estimated trips associated with the proposed growth without any improvements to the network. The results of these analyses show that the changes in traffic volume and circulation patterns associated with the 2025 Projected Growth Redevelopment Scenario will have an impact resulting in an overall LOS E or F operations at the following intersections in the Planned Condition.

**Planned Condition**

| | |
|---|---|
| Maple Road and Sweet Home Road | PM – LOS E |

Under the Planned Condition and without mitigation, the LOS at the intersection of Niagara Falls Boulevard at Sheridan Drive improved from E to D during the PM peak hour. Adjustments in traffic volumes also impact adjacent intersections and street segments which resulted in shifting arrival patterns at intersections due to a change in vehicle headway. The change in arrival patterns has a cascading impact within the study area network most focused on directly connected streets and intersections resulting in improvements to LOS movements without any roadway improvements applied.

Mitigation measures offset a project's traffic impacts by employing geometric, operational and other techniques to accommodate the traffic from a proposed project. The following improvements have been identified:

**Corridor Improvements:**

Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive

- Adaptive signal control

Ridge Lea Road/ North Bailey Avenue: Niagara Falls Boulevard to Maple Road

- Widen from a 3-lane cross section to a 5-lane cross section

Bowmart Parkway: Maple Road to Meyer Road

- Resurfacing

Sheridan Drive: Niagara Falls Boulevard to Millersport Highway

- Revised signal timings and coordination

**Intersection Improvements:**

Maple Road and Sweet Home Road

- Updated signal timings including exclusive left turns and improved yellow/red times
- Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out)
- Adjust the northbound approach – Northbound right turn lane changes to right and through lane
- Adjust signal timing

Sheridan Drive and Sweet Home Road

- Updated timings including exclusive left turns and improved yellow/red times
- Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out), and bicycle boxes
- Adjust signal timing, cycle length too long even considering it is a part of a coordinated network, including leading pedestrian and bicycle intervals

North Bailey Avenue, Emerson Drive and Amsterdam Avenue

- Convert to a single lane roundabout

Conceptual layouts of these improvements are provided in Appendix C.

This program of improvements will maintain LOS D or better operations at all of the studied intersections in the Planned Condition during the PM and Saturday peak hours, except at the Maple Road/Sweet Home Road intersection as noted above. Most intersection approaches will also operate at LOS D or better, but there will be some approaches and/or individua movements that will operate at LOS E or F. These operations are consistent with the Existing Condition.

These proposed improvements limit the need to create large intersections which is consistent with local objectives for maintaining/enhancing community character. Other improvement options that could be considered include access management strategies, providing additional multi-modal infrastructure, and leveraging ITS technology where possible to maximize efficiency within the existing road infrastructure. The mitigation strategies should also be reevaluated if/when a future transit expansion is implemented by NFTA.

## Utilities

### Water

The growth under the 2025 Projected Growth Redevelopment Scenario would add approximately 0.93 million gallons per day (MGD) under average conditions and 2.29 MGD under peak demand conditions (calculated by applying the peak factor of 2.46 from the Ball Pump Station). When combined with the existing demand of the Study Area, the future average day water demand is 1.90 MGD, and the future peak water demand is 4.69 MGD.

The increased water demand associated with the 2025 Projected Growth Redevelopment Scenario will strain the capacity of the existing distribution system in the Study Area, especially during peak periods. The future simulated water pressure drops by 8 psi during peak periods; the minimum pressure in the Study Area drops by 14 psi. The mean available fire flow drops by about 500 gpm under the future peak scenario.

In order to maintain the quality of water service as it exists today, and to mitigate the impacts of the 2025 Projected Growth Redevelopment Scenario, the aging cast iron water mains should be replaced in the Study Area. With the cast iron mains replaced, the simulated water pressure rises to 85 psi under peak conditions and mean available fire flow is equal to current. The recommended mitigation action would involve the replacement of approximately 52,000 linear feet of water main, ranging in size from 6 inches to 16 inches in diameter.

### Sewer

The growth under the 2025 Projected Growth Redevelopment Scenario would add approximately 0.93 MGD of sewer flow under average conditions, and 3.46 MGD under peak demand conditions. The calculated average peaking factor is approximately 3.33.

There is generally sufficient capacity in the interceptor sewer systems to transmit existing and proposed flow (with the exception of the West Side Interceptor). Because the existing West Side Interceptor is significantly over capacity between Maple Road and Chestnut Ridge Road (at the Hartford Relief sewer) during wet weather events, one of the following alternative mitigation measures must be undertaken to minimize surcharge conditions and guard against future Sanitary Sewer Overflows (SSOs):

- Alternative #1 - Additional Infiltration & Inflow (I&I) work to reduce wet weather flows;
- Alternative #2 - Construction of a replacement parallel West Side Interceptor to remove the West Side Interceptor bottleneck; or
- Alternative #3 - Construction of a pump station to divert flows from the West Side Interceptor to another interceptor with spare capacity.

In addition, the following baseline alternatives must be undertaken to create local sewer capacity for the redevelopment of the Boulevard Mall corridor:

- Stabilize and reline the Niagara Falls Boulevard sanitary sewer system.
- Reline the 24-inch RCP from Ridge Lea Road to Chestnut Ridge Road (under the I-290).
- Replace 310 linear feet of 24-inch sewer with 30-inch sewer on Chestnut Ridge Road, from the West Side interceptor to the collector manhole.
- Reline the sewer on Willowridge Drive to the Willowridge pump station, reline the remaining Ridge Lea Sewer south of the I-290, reline the sewer on Chestnut Ridge Road from the I-290 to the collector manhole, and also rehabilitate the remining manholes in the mini-system.
- Construct an 18-inch "spine" sanitary sewer on North Bailey Avenue, to collect sewage from the BCD to the east of North Bailey Ave.
- Construction of wet weather flow capacity improvements at the Water Pollution Control Facility (WPCF).

**Stormwater**

Certain size storm events are known to cause localized flooding problems in the Study Area. Due to the age of the majority of existing development in the Study Area, there is little to no stormwater storage provided. In order to help relieve the localized flooding problems, the Town of Amherst should add more stringent requirements for new and/or re-development projects to achieve additional storage volume for post-construction stormwater management. The Town should require applicants to meet one or more of the following requirements in the Town Stormwater Management Plan to increase the additional storage volume and help mitigate the existing localized flooding issues.

- Mitigate the proposed conditions peak flows to match the existing conditions peak flows with a 10% escalation factor to account for climate change (according to Section 3.2.3.1 of the NYSDOT Bridge Manual (2017).
- Use a median curve number (CN) value when computing the existing conditions runoff rates (i.e. use 50% runoff rate from existing land cover and 50% runoff rate from prior to any development such as woods or meadow).
- Mitigate all proposed stormwater runoff peak rates to match the existing 10-year storm peak including the proposed 100-year storm peak.

## Recreation and Open Space

The land use pattern derived from the mixed-use zoning coupled with the target demographics for the multi-family residential component of the Projected Growth Redevelopment Scenario point to a limited need for outdoor recreational opportunities such as parks and playgrounds.

However, incorporation of civic spaces throughout the mixed-use portion of the Study Area is highly recommended to meet Town goals within these districts. The need for parks and other open space will be monitored as development and the associated demographics unfold for the Study Area.

**Community Services**

Increased development and population over the 20-year planning period could affect the ability to provide emergency services through the existing volunteer base and equipment. Mitigation will include planning and coordination with all involved emergency service providers along with some potential for capital investments for equipment. This is generally addressed through the taxing districts; however, cooperation and coordination, along with public education, are essential to make sure structures, residents and workers are safe. The ability to continue to serve the Study Area with an all-volunteer force requires continuous evaluation and assessment as demands grow.

**Cultural Resources**

No significant impacts to historic resources in the Town are anticipated as a result of the Projected Growth Redevelopment Scenario. The northern portion of the Alberta Drive Historic District (National Register eligible) is located adjacent to the southern boundary of the Study Area. It is separated from the Study Area by Eggert Road and is therefore unlikely to be significantly impacted by any future redevelopment activities within the Study Area.

## Alternatives / Scenarios

In order to address the SEQR action that is the subject of this SDGEIS, it was necessary to compare the alternative build-out scenarios for the Study Area under the mixed-use zoning with that of the No Action (existing zoning) Scenario, as well as to compare various growth projections over the 20-year planning period.

The **No-Action Scenario** differs significantly from that evaluated in the 2020 GEIS because at that time the Town elected to move forward with mixed-use zoning and implemented the GEIS. Therefore, the No-Action alternative would involve keeping the current zoning and land use decisions as they are today. This alternative has been rejected by the Town for two important reasons. First, in some areas of the BCD the rezoned lands are inconsistent with the proposed redevelopment projects, requiring applicants to undergo rezoning for their projects to be approved. Second, the development projections for office and retail under the 2020 GEIS appear to be significantly inconsistent with current trends and the result could be unintended increases in impacts to infrastructure not presently accounted for in the GEIS.

The full development potential of the Study Area under the mixed-use zoning was considered in the **Maximum Build-Out Scenario** alternative and was determined by maximizing the number of blocks and the number of building floors, resulting in approximately 11.3 million gross square feet of commercial (retail and office) and nearly 38,000 residential units. This is a very significant amount of development that would take several decades to achieve and does not take into consideration development constraints that might be present within each block, including parking needs for the type of development.

Assuming the combination of incentives, attractiveness of the proposed land use, and demand for student housing spur a high rate of growth within the Study Area, the **High Growth 20-year Development Scenario** would add approximately 5 million gross square feet of commercial space and 11,700 new residential units might be realized within 20 years. Based on current development trends and the pace of redevelopment within the BCD, this scenario is too aggressive and unlikely. When considering the traffic impacts and magnitude of mitigation for the 2025 Projected Growth Redevelopment Scenario, it is clear that a high growth scenario will not be an acceptable situation, at least as it can be envisioned today.

The **2020 Projected Growth Redevelopment Scenario** (subject of the original GEIS impact evaluation) was derived from the new mixed-use zoning, the commercial growth projections from the *2016 Town of Amherst Economic Study*, and local demand for student housing. This alternative is viewed as being more realistic within the 20-year planning period, resulting in 3 million gross square feet of commercial and 5,000 new residential units. The primary difference between this redevelopment growth scenario and the one presented in this SDGEIS is the percentage of office to commercial space.

The cumulative effects of COVID, current development trends and developer preferences, and considerable planning efforts in the BCD since the adoption of the 2020 GEIS have led to the **2025 Projected Growth Redevelopment Scenario**. The result was a significant reduction in anticipated office growth with a significant increase in retail development, but overall the commercial growth projection only changed by about 400,000 gsf for the next 20 years, dropping from approximately 3 million gsf to approximately 2.6 million gsf. Nevertheless, the shift from commercial to retail prompted the need to re-evaluate the potential cumulative impacts.

## Future SEQR Actions

Part 617.10 of the State Environmental Quality review regulations (SEQR) states, in part, that *"Generic EIS's and their findings should set forth specific conditions or criteria under which future*

*actions will be undertaken or approved, including requirements for any subsequent SEQR compliance. This may include thresholds and criteria for supplemental EIS's to reflect specific significant impacts, such as site specific impacts that were not adequately addressed or analyzed in the generic EIS."*

*"No further SEQR compliance is required if a subsequent site specific action will be carried out in conformance with the conditions and thresholds established for such actions in the generic EIS or its findings statement."*

To satisfy these requirements, future development within the Study Area should generally be consistent with the scale and density of the 2025 Projected Growth Development Scenario as presented and evaluated in this SDGEIS and be consistent with criteria to be specified in the Statement of Findings. Failure to provide the appropriate mitigation for potential adverse impacts would require future SEQR action.

# SECTION 1.0

# INTRODUCTION

On January 6, 2020, the Town of Amherst Town Board adopted the Statement of Findings for the Boulevard Central District Generic Environmental Impact Statement (BCD GEIS) to address future growth and redevelopment of the Town of Amherst Boulevard Central District, an approximately 1,264-acre area of the Town that includes several parcels of underutilized land within the Town's federally designated Opportunity Zone and parcels immediately south of Sheridan Drive as illustrated on Map 1.1-1. The Town envisioned significant changes to this area, such as converting aging shopping centers and other large commercial retail sites to mixed-use retail/office/residential "live, work, play" developments and neighborhoods. Several development scenarios were evaluated for the Study Area based on the proposed land use and new mixed-use zoning. Consideration of the scenarios and growth trends led to the identification of a likely revitalization alternative for the study area. The cumulative environmental impacts of this alternative were evaluated through the BCD GEIS pursuant to the State Environmental Quality Review Act (SEQRA) regulations (6 NYCRR 617).

A variety of changes to economic and social/work practices have occurred over the past several years that signaled a need to reevaluate the BCD GEIS and the assumptions made to inform land use and zoning projections of future development, their associated impacts, and corresponding mitigation costs. These changes have influenced the Town's decision to revise its land use assumptions and prepare this 2025 Supplemental GEIS, referred to as the BCD Supplemental Draft GEIS (BCD SDGEIS). These trends are discussed in detail in Section 2.0 of the SDGEIS and are summarized below:

- A decline in office space demand that emerged post-COVID with more work-from-home opportunities
- An increase in medical office demand
- Continued influence of E-commerce that has diminished demand for retail space
- An increase in light industrial demand, especially for warehousing and logistics
- An increase in rental housing demand
- Rising construction costs and interest rates
- More selective bank financing

Other factors affecting the amount and distribution of growth within the BCD include:

- Discrepancies between the final zoning and the assumptions used in the original GEIS, particularly the mixed-use zoning districts
- Focused vision for the BCD through an Action Plan adopted in 2021 that led to refined development projections
- Designation of the Boulevard Mall and some surrounding properties as an Urban Renewal Area and the creation of an Urban Renewal Plan in 2022
- Completion of a Strategic Economic Development Plan in 2023 with identified opportunity sites
- Infrastructure improvements to address sewer capacity issues
- Recently proposed or constructed projects that are inconsistent with the intended zoning and are not to the scale anticipated in the original GEIS


As a Supplemental GEIS, the environmental issues will focus on those original environmental topics that will most likely be affected by the changes in land use and density. The remaining environmental issues discussed in the previous Draft and Final GEIS and the conclusions provided for these issues in the Statement of Findings have not changed.

## 1.1 Project Location and Project Setting

The BCD SDGEIS Study Area is located in the western portion of the Town of Amherst and remains the same as that originally delineated in the original BCD GEIS. Niagara Falls Boulevard forms the western boundary of the Study Area and is also the municipal boundary with the Town of Tonawanda. The southern boundary is generally Sheridan Drive, but also includes some parcels fronting along the south side of Sheridan Drive. Interstate-290 (I-290) forms the eastern and northern boundaries of the Study Area, creating a triangle. Exceptionally good access from major roads fostered both the residential and commercial growth of this area.

The Study Area is illustrated on Map 1.1-1, along with the boundaries of the Federal Opportunity Zone. The Opportunity Zone (Census Tract 92) follows Niagara Falls Boulevard, Sheridan Drive, and the I-290, with a small area to the north of I-290. The intent of establishing the Study Area was to include the majority of commercial properties within this area of Town. For this reason, the commercial properties south of Sheridan Drive were included even though they are not within the Opportunity Zone.

**MAP 1.1-1 – STUDY AREA BOUNDARY**



Adjacent land uses along Niagara Falls Boulevard and Sheridan Drive consist primarily of commercial retail fronting on these roads with mostly older, established single-family residential neighborhoods adjacent to the commercial uses. North and east of the Study Area is a mix of commercial, single and multi-family residential, and institutional uses. The most significant use in this area is the State University of New York at Buffalo (UB) North Campus. The I-290 creates a separation between the Study Area and these uses to the north and east.

Land use within the Study Area is primarily commercial retail that includes many underutilized parcels located along Maple Road in the central portion of the Study Area.

## 1.2 Project History

Federal Opportunity Zones were established in 2017 as a provision of the Tax Cuts and Jobs Act. Opportunity Zones provide tax incentives to encourage investment in low income, undercapitalized communities. The "zones" were nominated by the governors of each state and were officially designated by the U.S. Treasury Department. In 2018, New York State designated the Study Area (minus the properties south of Sheridan Drive) as a Federal Opportunity Zone. Concurrently with this action, the Town of Amherst updated its Comprehensive Plan and included policies and new commercial/mixed-use land use designations to provide guidance for redeveloping the underutilized, mostly commercial retail sites within the Study Area. To identify and understand the cumulative impacts of redevelopment and implementation of these new policies and provide guidance within the Opportunity Zone, the Town elected to prepare a Generic Environmental Impact Statement (GEIS) through the SEQR process to provide a comprehensive process to better plan for future infrastructure needs and community services. However, since the GEIS was adopted and implemented, development trends have changed due to the influences of COVID, changes in market conditions, new planning efforts within the BCD, and preferences of the development community. These factors have required a re-evaluation of the land use and zoning in specific portions of the Study Area.

Other studies and plans were completed for the BCD following the 2020 adoption of new zoning and the GEIS. In 2021, a focused vision for the BCD was created through an Action Plan that led to refined development projections for specific opportunity sites. Subsequently, in 2022, the Boulevard Mall and some surrounding properties were designated as an Urban Renewal Area and an associated Urban Renewal Plan was adopted by the Town. In September 2023, the Town completed a Strategic Economic Development Plan that, among other important findings, recommended targeting industries such as healthcare services and medical tourism, professional services and information technologies, and manufacturing.

# 1.3 THE STATE ENVIRONMENTAL QUALITY REVIEW ACT (SEQRA) PROCESS

The State Environmental Quality Review Act (SEQRA) provides the opportunity for a Lead Agency to prepare a Supplemental Generic Environmental Impact Statement "…limited to the specific significant adverse environmental impacts not addressed or inadequately addressed in the EIS that arise from:

(a) changes proposed for the project;
(b) newly discovered information; or
(c) a change in circumstances related to the project" (6NYCRR 617.9(a)(7)).

For the Boulevard Central District GEIS, the need for this SDGEIS is based on the refined development projections for the Study Area dictated by changes in land use and density, as well as redistribution of development within the Study Area that impacts traffic analysis, and major infrastructure projects that impact the water and sewer capital improvement plans and associated mitigation costs. These changes were determined by the Lead Agency to be significant enough to require new studies of the Town's infrastructure within the Study Area and a re-evaluation of the cumulative impacts and required mitigation.

The SEQRA regulations further state that a supplemental GEIS must be subject to the full procedural requirements for preparation of a GEIS except that scoping is not required. Future implementation (development) of the Revised 2025 Projected Growth Redevelopment Scenario for the Boulevard Central District is considered a Type 1 action under SEQR (6NYCRR Part 617.5). The Town of Amherst Town Board has completed a Coordinated Review of the project to reestablish lead agency as required under SEQRA Part 617.6. The Town Board declared itself lead agency by resolution on __[date]_____. The list of involved agencies and potential permitting or approving agencies is indicated below.

The Town Board determined the SDGEIS adequate for public review on ___[date]_____. A SEQR Public Hearing before the Town Board on the SDGEIS is scheduled for ___[date]_____. The public comment period is anticipated to close on ___[date]_____. The SDGEIS is posted for public access on the Town's website.

Future site-specific projects in the Study Area will be guided by the thresholds and recommendations identified in the Draft and Final SGEIS and the associated Statement of Findings. Projects that meet the parameters established in the Statement of Findings will require no further review under SEQR. However, specific project documentation will need to be provided

in order for the Planning Board and Planning staff to appropriately evaluate each project against the SGEIS impact and mitigation findings and thresholds. Projects that exceed the thresholds evaluated or otherwise do not meet the requirements outlined in the SGEIS and Statement of Findings will require further review under SEQR, as determined by the reviewing board (in most cases, the Planning Board).

## List of Potential Permitting/Approving Agencies

Approvals and permits for specific developments will be obtained during Town review of specific projects within the Study Area. The following agencies will likely have review or approval authority over new actions within the Study Area:

Town of Amherst Town Board - Lead Agency

- Adoption of SEQR Findings
- Adoption of future zoning district amendments

Town of Amherst Planning Board

- Review and approval of future redevelopment projects (site plans and subdivisions)

New York State Department of Environmental Conservation (NYSDEC) Region 9

- State Pollutant Discharge Elimination System permit (SPDES)
- Section 401 Water Quality Certification
- Article 24 Freshwater Wetland permits
- Sewer improvements

New York State Department of Transportation (NYSDOT)

- Projects affecting state roads

Erie County Water Authority

- Water system improvements

Erie County Department of Public Works – Highway Division

- Projects affecting County roads

US Army Corps of Engineers (USACE)

- Nationwide Permits or Individual Section 10/404 permits depending on need to impact streams and wetlands within the Study Area.

NYS Office of Parks, Recreation and Historic Preservation (NYSOPRHP)-interested

- Consultation required under Section 106 of the National Historic Preservation Act and Section 14.09 of the NYS Historic Preservation Act

There are several other local, regional and state agencies that may become involved in future projects through consultation or potential future funding sources. The intent of this GEIS is to identify and coordinate with those agencies that are known at this time to potentially have some involvement or interest in future redevelopment of the Study Area. Others may be identified during the course of this SEQR process or during the 20-year planning period covered by this SDGEIS.

# SECTION 2.0

# PROJECT DESCRIPTION

## 2.1 Project Purpose and Need

The Town of Amherst is proposing updates to the land use assumptions and development projections within the Boulevard Central District (BCD) GEIS Study Area to address current development trends and new concepts for the redevelopment of the Boulevard Mall. The Town has determined that these changes will alter the geographic distribution of impacts on the Study Area, likely requiring revisions to the capital improvement plans for water and sewer infrastructure and affecting traffic volumes and patterns such that new traffic impacts must be considered. Furthermore, the measures required to mitigate the potential cumulative impacts of growth and redevelopment within the Study Area also need to be determined along with corresponding updates to the mitigation cost tables.

The original BCD GEIS and Statement of Findings were adopted by the Town of Amherst Town Board on January 6, 2020. This enabled a new streamlined process for addressing development and redevelopment within the GEIS Study Area whereby projects that are subject to SEQRA (Type I or Unlisted Actions) could forego the normal SEQRA process if they met the thresholds and procedures established in the GEIS. In essence, if a project aligns with the GEIS development projections, its cumulative impacts have already been assessed and mitigation measures were identified. Therefore, the remaining step for the developer is simply to calculate their fair share in the mitigation cost, which is accomplished by providing details on square footage of commercial growth, number of residential units (if applicable), number of additional employees (if applicable) and trip generation to address traffic impacts. All these metrics relate back to the impact assessment and the fair share calculations for mitigation.

However, the above is all predicated on a growth scenario developed for the GEIS for the selected period of time (effective period of the GEIS). In communities with established zoning and development patterns, it is not difficult to establish a highly predictable growth scenario. Within Amherst's Boulevard Central District, the development projections are based on amended mixed use zoning designed to attract developers and reimagine an area of Town where some of the

uses (e.g. Boulevard Mall) are no longer desirable, leading to disinvestment. While the new zoning that comprises the Town's Projected Growth Redevelopment Scenario within the Study Area remains a valid tool for promoting a more sustainable form of development, it requires modifications to reflect changes in market demand, especially as it relates to the office/retail mix, and flexibility desired by developers.

The 2020 GEIS SEQR action involved the implementation and application of new mixed-use zoning districts for the commercial areas of the approximately 1,260-acre Boulevard Central District, bounded on the east and north by the I-290, the west by Niagara Falls Boulevard and on the south by Sheridan Drive, as well as including properties immediately to the south of Sheridan Drive (Study Area). In addition, the Town elected to evaluate the cumulative impacts of likely growth within this Study Area under the mixed-use zoning through the preparation of a Generic Environmental Impact Statement (GEIS). Although the Study Area is generally built out, it contains many underutilized sites that present a significant opportunity for redevelopment and reinvestment.

Historically this area has seen a great deal of commercial development and investment. More recently, however, it has experienced declining activity due to the evolution of more preferred or desirable commercial land use patterns, changing market trends and new technologies. These new patterns and trends have impacted the quality of the commercial and business development including the overall appearance and function of the area.

The Town recognized that continuing on the same path in regard to land use, zoning and design standards would constrain the Town's ability to take full advantage of its designated Federal Opportunity Zone, a program established by Congress in 2017 to promote investment and drive economic growth in low-income or economically disadvantaged communities.

With the goal to encourage the improvements and investments necessary to promote the creation of mixed-use retail/office/residential "live, work, play" neighborhoods, the Town adopted several amendments to its Comprehensive Plan and new mixed-use zoning districts. Consideration of growth trends and application of the new mixed-use zoning was used to model and evaluate land use scenarios and to identify a Projected Growth Redevelopment Scenario for the Study Area.

This Supplemental Draft GEIS (SDGEIS) for the BCD study area evaluates the potential benefits and impacts of the mixed-use zoning amendments and other recent land use decisions within the Study Area under the associated Revised 2025 Projected Growth Redevelopment Scenario. The

GEIS's core purpose remains unchanged: to enable the Town and other agencies to assess the cumulative environmental impacts of the projected development and estimate the scope of potential improvements and other mitigation measures necessary to accommodate future growth. The scope of issues is reflective of those most affected by the revised development projections, specifically water, sewer, and traffic.

Mitigation costs will continue to be used and updated based on the revised redevelopment projections to address certain impacts, such as traffic and sanitary sewer, to provide greater equity in the redevelopment process. Understanding the cumulative impacts of growth allows the costs of using and improving public services to be more equitably shared across all new development within the Study Area. The calculation of mitigation costs include, as appropriate, the public share of the cost of improvements, recognizing that existing development also contributes to the impacts.

## 2.2 Study Area Planning

The Town of Amherst has a long history of land use planning that began in the 1950s. Since then, the Town's Comprehensive Plans have been amended several times (1961, 1968, 1975, 2007, 2015, 2017), most recently in 2020. These amendments were prepared to position the Town to plan for its growth under evolving trends and major initiatives, e.g. the decision to build the UB North Campus in the Town. Recent trends in commercial/retail business have affected essential land use demand and forms of development. As a result of a comprehensive plan review process conducted in 2014, the Town recognized a need to amend its Plan and zoning for commercial land uses. Information about the Town's planning history can be found on its website at www.amherst.ny.us.

Since 2019 the Town has prepared several studies and initiatives that provide new information and guidance for land use, zoning, market conditions, infrastructure needs and more in the BCD. Recent development projects built or proposed in the Town also reflect recent trends and conditions, discussed further in Section 2.3 below. All of these influence the 2025 SGEIS land use and zoning assumptions and resulting demographic projections that are summarized below.

Mixed-Use Zoning: The Town adopted new Mixed-Use districts into its Zoning Code (Chapter 203) in September 2019, before the original BCD GEIS was finalized. When the GEIS was adopted in January 2020, the Town had yet to formally map the mixed-use districts throughout the Town, including within the BCD. The future zoning identified in the original GEIS included the mixed-use districts for analytical purposes, but was based on what the Town assumed may be rezoned in

the BCD in the future. In December 2020, the Town Board formally adopted a resolution designating/mapping mixed-use zoning for a majority of commercial properties within the BCD.


Upon formal rezoning of properties in the BCD, some inconsistencies between the future zoning assumed in the GEIS and the actual zoning assigned to properties emerged. Projected future land development for some rezoned properties that were assumed to be mixed-use had to be adjusted, as they were not rezoned to a mixed-use district and are not likely to be in the future. As a result, some 2019 land use and zoning assumptions no longer apply. For example, Northtown Automotive properties on Sheridan Drive were assumed to be rezoned to mixed-use and projected accordingly in the GEIS; however, the Town ultimately decided not to initiate rezoning of this area and it remains zoned General Business (GB), Motor Service (MS) and Multi-Family Residential (MFR-5). Future changes to Section 5A of the Town's Zoning Code, containing the mixed-use districts, may also influence future rezonings in the Study Area.

Boulevard Central District Action Plan: The Town adopted an Action Plan in 2021 for the BCD to establish and communicate its vision for the BCD area. The Town and its consultant met with property owners, outside agencies, residents, and other stakeholders to understand the potential for new development in the BCD. The Town's vision and goals for this area, as stated in the Action Plan, were incorporated into the Comprehensive Plan as a new Focal Planning Area (described in Chapter 10). The Action Plan includes an illustrative plan for a long-term vision of what a vibrant, interconnected, and mixed-use environment could look like. Conceptual redevelopment renderings demonstrate how the community's vision would revitalize and transform the suburban style development sites into prosperous, walkable centers by applying provisions of the new mixed-use zoning districts. Additionally, new street networks framed by building frontages create an environment with smaller, walkable blocks to provide interconnectivity. Public open spaces such as parks and community gathering spaces are also integrated into the overall pattern of development. Redevelopment site yield calculations (residential and commercial) were prepared based on the visualizations and the provisions of the mixed-use zoning districts. These calculations provide improved projections of future development resulting from the application of the zoning to sites such as the Boulevard Mall, Maple Ridge Plaza and the shopping center at Sheridan Drive and Sweet Home Road.

Boulevard Mall Redevelopment: On June 27, 2022, the Town Board passed a resolution designating a portion of the BCD as an Urban Renewal Area (see Figure 2.2-1) and for the Town Board to act as the Amherst Urban Renewal Agency (AURA). The Urban Renewal Area includes approximately 195 acres and 60 parcels, including the Boulevard Mall. The Mall has been continually declining due to changing national and regional shopping trends, leading to the loss

of businesses, high vacancy rates, and diminishing property value. The impetus for defining an Urban Renewal Area was to spur redevelopment, increase the tax base, and provide amenities, businesses and transportation options to existing residents, while also creating a place to attract new residents and visitors.

**FIGURE 2.2-1: Urban Renewal Area**




On October 24, 2022, the Town Board approved the Boulevard Central District Urban Renewal Plan to provide guidelines and a framework for the potential redevelopment of certain blighted properties within the Urban Renewal Area. Also on this date, the Town Board passed a resolution to use its powers of condemnation in accordance with the provisions of NYS Eminent Domain Procedure Law (EDPL) to acquire some of these properties, specifically the Boulevard Mall and some immediately adjacent properties. On January 30, 2023, the Town Board adopted the

determination and findings and brief synopsis in connection with the acquisition of the properties pursuant to Article 2 of the EDPL. The Town may issue Article 4 of the EDPL to vest/acquire property at a later date.

The Town continues to work towards redevelopment of the Boulevard Mall site. There have been efforts to work with current property owners to form a redevelopment plan that achieves the Town's vision of a walkable, mixed-use environment for new residents and visitors. The Town has also had several conversations with developers regarding the potential for retail, office, hospitality and housing on the site. Additional planning and design continues, all of which informs projected future growth in the Mall area.

Strategic Economic Development Plan (SEDP): The Town completed a Strategic Economic Development Plan (SEDP) in September 2023 that provides *"a strategic approach for promoting long-term sustainable economic growth resulting from greater returns on local investment, improved job creation and retention, increases in per capita income and property values, enhancements in the local tax base, and strengthened regional networks."* Significant findings include: (1) future real estate investments will primarily be redevelopment/infill development initiatives; and (2) encouraging and developing live-work-recreate activity centers can be a valuable tool to attract workers

The SEDP identifies industries for the Town to target – these include healthcare services and medical tourism, professional services and information technologies, and manufacturing. The SEDP also reviewed various opportunity development sites, including the Boulevard Mall area. For this area, the SEDP states that *"existing and projected market trends demonstrate that workers prefer to live and work in a pedestrian-friendly built environment, abundant with vibrant retail amenities. The area lends itself to supporting this environment, especially given the available redevelopment opportunities and abundance of underutilized parking lots."* The Boulevard submarket office vacancy rate of 12.1% combined with the lack of office demand suggests that the 2019 office use projection in the original GEIS should be adjusted. As a result, the revised growth projections in this SDGEIS account for predominant retail use, some residential, and limited office uses.

Infrastructure Improvements: In late 2023, Empire State Development (ESD) approved a $31 million funding agreement to construct improvements to the Town's West Side Sewer Interceptor and sewers along North Bailey Avenue. This large infrastructure investment will enable the Town to address overflow and infiltration issues along with improving the peak flow holding capacity in the current sewer shed, serving the BCD. In the current GEIS, the West Side

Interceptor is identified as a sewer mitigation project. The Town also considered what additional improvements to the area's sewer system are necessary to include as part of the BCD SDGEIS due to recent development and capital needs that may have changed.

Recently Proposed or Constructed Development Projects: Since 2019 a variety of mixed-use development/redevelopment projects have been proposed and/or constructed throughout the Town. Many have not occurred within the BCD, likely due to higher land values, demolition costs for existing buildings/infill development, and availability of vacant land outside the area. Projects within the BCD have typically included standalone retail and shopping center uses that have included repurposing or additions to existing buildings and/or replacement in-kind of building footprints.

Select developers have continued to show a preference for the Town's legacy Shopping Center (SC) zoning district in the BCD, as several areas that were re-zoned to mixed-use districts in 2020 have been rezoned back to other commercial districts. These re-zonings are likely due to developers' familiarity with the established districts, the lack of familiarity with the new requirements in the mixed-use districts, the need for a variety of variances, and the types of land uses and spaces tenants are seeking. These large commercial areas include The Boulevard Plaza at Niagara Falls Boulevard and Ridge Lea Road and the former University at Buffalo Ridge Lea Campus located along the eastern side of North Bailey Avenue next to the I-290; both have been rezoned back to SC.

Recently proposed and/or constructed mixed-use projects have experienced a change in the mix of land uses within buildings. Only a few years ago, as the original GEIS was being developed, the Town was still seeing a strong market for retail and even office spaces occupying the entirety of first floor mixed-use buildings. One example includes a mixed-use project constructed in 2018 at 6770-6790 Main Street, zoned General Business (GB) and Multi-Family Residential 5 (MFR-5). It was constructed with two 3-story buildings with approximately 18,700 gross square feet of first floor office uses and 24 apartments (31,640 gross square feet) on the second and third floors. This ratio created a building use composition of 37% office and 63% residential.

Today, there has been a shift in need for residential/rental units on the first floor of mixed-use buildings, replacing the demand for office space and some retail space. The majority of mixed-use buildings proposed within the Town now contain smaller retail and/or restaurant spaces on the first floor, with the majority of the rest of the building (including some of the first floor) consisting of multi-family units (see Mixed-Use Site Plan Precedents Exhibit in Appendix B). Some examples include:

1. 5226 & 5228 Main Street: A mixed-use building near the Village of Williamsville consisting of approximately 10,930 square feet of first floor commercial (50% designated for retail and 50% designated for restaurant space) and 30 apartments (33,504 gross square feet) on floors two through four. This creates a building use composition of 25% commercial and 75% residential.

2. 1720, 1740 & 1760 Maple Road: A mixed-use development near Ayer Road consisting of a variety of buildings, most of which are purely residential. The one mixed-use building on the site contains approximately 9,715 square feet of commercial space on the first floor but also includes two apartment units on the first floor with apartments on the second through fourth floors (32 units, 54,860 gross square feet). This creates a building use composition of 18% commercial and 82% residential.

3. 6812, 6814 & 6832 Main Street and 29 & 37 Tennyson Terrace: A mixed-use building consisting of approximately 13,500 square feet of first floor commercial uses (29% office, 37% retail and 33% restaurant) and 34 apartments (49,379 gross square feet) on floors two through five. This creates a building composition of 21% commercial and 79% residential.

These recent land development projects support a change in the building use composition (ratio) assumptions originally used in the GEIS, shifting away from mostly retail and office uses to smaller percentages of retail and the majority of the building as residential. Therefore, the Town has revised the land use growth assumptions and demographic projections that form the basis of development impacts and mitigation measures reflecting this shift in the BCD SDGEIS.

## 2.3 2025 Projected Growth Redevelopment Scenario

The process and assumptions for establishing the 2025 Projected Growth Redevelopment Scenario for the BCD SDGEIS has benefitted from considerable planning efforts in the BCD, as discussed in Section 2.2, as well as the emergence of new trends and other factors leading to more in-depth investigations and analysis. The process, methodology, and ultimately the revised projections, are described in this section.

In consideration of the changing market conditions, emerging trends, recent Town projects and studies, and recent development projects, the Town reevaluated the land use assumptions and demographic projections supporting the BCD SDGEIS. The following describes the timeframe,


geographic definition, analytical factors, and assumptions utilized to assign land use growth and demographic projections that form the basis for redevelopment/growth and the associated impacts.

Growth Period: A 20-year time period was derived to project growth in the BCD and to identify impacts and mitigation. The projected new residential units and new non-residential square footage were derived for each time period and assigned to individual Traffic Analysis Zones (TAZ) for analytical and reporting purposes.

Geographic Definition: Real Property Information System (RPIS) parcel-based map data for Amherst and both AutoCAD and ArcGIS software were used to inventory and assess the geography of the area. The BCD SDGEIS comprises approximately 1,264 acres of land generally located within a triangular shaped area bounded by Niagara Falls Boulevard, Sheridan Drive and the I-290, comprising the Town's largest commercial district (see Map 2.3-1).

The BCD Study Area was disaggregated into smaller areas called Traffic Analysis Zones (TAZ), also shown on Map 2.3-1. The TAZ boundaries are maintained by the region's Metropolitan Planning Organization (MPO), the Greater Buffalo Niagara Regional Transportation Council (GBNRTC), and have remained unchanged since the original GEIS was prepared in 2019. A TAZ is an area delineated by state and/or local transportation agencies and often used for tabulating transportation-related data, especially journey-to-work and place-of-work statistics and origin-destination studies. A TAZ usually consists of one or more census blocks, block groups, or census tracts. The GBNRTC utilizes TAZs to analyze and report future growth projections (population, employment and households) and to support traffic modeling. Use of the TAZs provides the Town an established geography with regularly updated demographic forecasts that enables sub-area traffic analyses that can be compared with regional travel forecasts. The Town is utilizing the TAZ boundaries for analytical purposes and to remain consistent with the original GEIS and GBNRTC traffic modeling efforts.

**MAP 2.3-1 – TAZ Boundaries**



*Analysis:* In order to be consistent, Town staff employed the same methods used for the original DGEIS again for the SDGEIS, which involved both quantitative and qualitative measurements. The quantitative data used and applied to the Study Area included real property parcel data (i.e. area, land use), aerial imagery, building footprints (polygons) and vacancy rates, existing land uses and zoning, parking demand, and site plan development applications (pending or completed). These data provide a quantifiable reference to assess existing conditions. Qualitative data were also used, including discussions with larger stakeholders/ businesses/landowners on future development plans, and emerging land use trends in the Town.


Professional staff from the Planning Department collaborated to consider the Study Area and form new assumptions to derive the demographic and development projections (see Town Land Use Analysis Notes Exhibit in Appendix B). A key assumption was that it is unlikely that all of the land area, consisting of 1,264 acres, will redevelop within the projected 20-year growth period due to a variety of factors as explained previously. A majority of the BCD is developed and there are few vacant lands to consider for new development; however, there are lands that could be considered underutilized with potential for future redevelopment. Underutilized land is defined as developable land that contains buildings and/or structures that may potentially be redeveloped or converted into another "higher and better" use such as residential or mixed-use. A portion or all of a parcel of land may be considered underutilized if the existing development is no longer economically viable. Examples of underutilized land include vacant and older buildings, and associated parking lots which are evident throughout the Boulevard Mall property, Maple Ridge Plaza and others.

The assumptions now reflect a "reduction" of the overall redevelopment area to concentrate future growth into smaller more focused areas. To designate these more focused growth areas, Town staff conducted a land use analysis to determine where redevelopment is most likely to occur. Some general land uses were excluded from the analysis including the majority of single-family residences, open spaces, infrastructure rights-of-way (roadways) and civic spaces, totaling approximately 596 acres. With these exclusions, the geographic area was reduced from the entire 1,264 acres down to the majority of non-residential land totaling approximately 668 acres – this is what was used as a starting point for growth projections (see Map 2.3-2).

The 668 acres used for analysis were then further reduced into higher probability growth areas, called Potential Redevelopment Areas, based on a variety of factors; these areas comprise an approximate total of 265 acres. The progression showing the reduction in overall redevelopment area is shown in Map 2.3-2 (the method for further reduction is explained in more detail in the Analytical Factors section).


**MAP 2.3-2: Reducing the Analysis Area**

## BCD Study Area





**1,264 Acres**

## Land Use Analysis Areas





**668 Acres**

## Potential Redevelopment Areas




**265 Acres**

**MAP 2.3-3: Potential Redevelopment Areas**



These Potential Redevelopment Areas, or underutilized areas of land with the most potential for growth, were disaggregated into 31 smaller areas (see Map 2.3-3, red areas). The Potential Redevelopment Areas were used as the geographic basis to derive growth assumptions for the SDGEIS (see a full list of detailed projections for each Potential Redevelopment Area in the Growth Projections Summary Table by TAZ Exhibit in Appendix B). Each TAZ may contain multiple Potential Redevelopment Areas featuring their own assumptions and projections. Factors 1-5 discussed in the Analytical Factors section below were applied to these Potential Redevelopment Areas to derive new zoning, land use and demographic projections for the SDGEIS.

## Analytical Factors

The following is an analysis of the major factors considered for the updated growth projections proposed for the BCD. These include a building analysis, land use and zoning assumptions, building/lot coverages, building use composition and population, housing and commercial growth.

Analysis Factor 1 - Building Analysis: Within each TAZ, individual buildings were evaluated based on their existing use, age, longstanding tenancy or occupancy, vacancy, and an opportunity for reuse or repurposing for future uses. Based on these building factors, Town staff assumed that some buildings would remain unchanged over the 20-year growth period and others would be removed. Those buildings identified to remain, and in most instances their related development elements (parking, stormwater, etc.), were not factored into the future projections. Existing building footprints that are identified to remain were taken from aerial imagery and submitted site plans. These are shown in black in Map 2.3-3. Buildings identified to be removed entirely in the future due to their high likelihood of redevelopment are within red areas designated on Map 2.3-3.

Analysis Factor 2 – Projected Land Use: The Town's Comprehensive Plan designates the future land uses in the BCD as primarily commercial and mixed-use, as illustrated in Figure 6 (the Conceptual Land Use Plan) in the Comprehensive Plan. There are a few exceptions, such as existing residential areas, community facilities, Sweet Home Middle School, and small pockets of commercial office (existing land uses can be found on Map 2.3-4), but these generally fall outside of the identified Potential Redevelopment Areas. The Comprehensive Plan identifies the BCD as a Suburban Center, described as the most intensive forms of commercial and mixed-use development in Amherst. The form and scale of development is accommodated on large parcel sizes and is generally adjacent to major roadways that exist there. This can result in more density and taller buildings, some reaching as high as eight (8) stories. The BCD is also a Focal Planning Area in the Comprehensive Plan, supporting the type of mixed-use development the Town desires and is likely to see in the BCD.


The Town has determined that the identified Potential Redevelopment Areas will include future growth over the 20-year planning period in a variety of land uses with Commercial, Residential, and Mixed-Use, with a small amount of Office, as most likely. Projections of future land uses within the Potential Redevelopment Areas were based on a variety of factors, including consideration of data and information from the recent studies and plans discussed in Section 2.2. To assign future land uses in the Potential Redevelopment Areas, the Town examined their surrounding context and scale, existing uses, and the identified buildings to remain, along with considering input from developers and existing property owners about future site plans and uses. The future projected land uses are shown in Map 2.3-5.

The future projected land uses were assumed to have a certain number of stories based on surrounding context and scale, and underlying zoning districts that currently exist or could likely be applied in the future (e.g. Retail is likely to be 1 or 2 stories, Residential would likely be 3 or 5 stories, and Mixed-Use could be either 5 or 8 stories). Generally, the number of stories projected for each land use (see Map 2.3-6) was maximized to determine the land use growth assumptions in the Potential Redevelopment Areas (housing and population growth estimates are described in Analytical Factor 6).


Analysis Factor 3 - Zoning: The Town approved the application and mapping of mixed-use zoning districts in December 2020 for the majority of non-residential parcels within the BCD (see Map 2.3-7 for existing zoning). Some areas in the original GEIS anticipated to be rezoned to mixed-use districts were not, most notably many of the Motor Service District (MS) parcels. In the original GEIS, the Town assumed mixed-use zoning to determine the potential redevelopment, with higher building heights (majority of areas at five (5) stories) and requirements for additional new block and street networks. With recent experience using the provisions of the mixed-use districts, the Town found that utilization by developers of these districts is challenging, especially requirements for new streets and blocks. Many areas zoned as Center (CTR), Deep Corridor (DC) or Shallow Corridor (SC) have multiple owners and land rights that are difficult to merge or consolidate into larger areas; this creates the need for variance requests and hinders creation of larger block and street networks with infill development.

The Town is currently working to amend some of the mixed-use district provisions, with possible removal or consolidation of districts, along with some changes to other existing commercial districts located within the BCD. The approach for the SDGEIS was to focus on the Potential Redevelopment Areas generally based on the current zoning districts in those areas and the projected changes to the zoning (see Map 2.3-8 for Projected Future Zoning). Some areas may still include the mixed-use districts but may also include other zoning districts such as GB, SC, OB, and MFR-5. Zoning is a key component for growth projections as it establishes maximum


**MAP 2.3-4: Existing Land Uses**




**MAP 2.3-5: Projected Future Land Uses**




**MAP 2.3-6: Projected Number of Stories**



**MAP 2.3-7: Existing Zoning**



**MAP 2.3-8: Projected Future Zoning**



height/number of stories, uses within a building, and required parking. This helps to calculate the total use of the parcel in terms of the number of units or square footage of buildings that could be constructed on a site/in a Potential Redevelopment Area.

Analysis Factor 4 – Building/Lot Coverage: Consideration of the future land uses delimited in Map 2.3-5 required an assumption of building/lot coverage percentage for each land use. Building/lot coverage is a combination of the size of a building and the amount of space required to accommodate associated parking areas and infrastructure needs such as storm drainage. Building/lot coverage depends on the intensity of the future land use. Larger buildings with more residential units, larger floor areas or more stories would require larger areas for parking and therefore result in less available land for building footprints. For the purposes of the projections in the SDGEIS, it was assumed that a residential unit requires 1 parking space and the size of the parking space plus the related facilities is approximately 320 square feet.

Building/lot coverages for the future land uses were derived from consideration of several similar development projects and site plans constructed/proposed within the Town; some of these projects were described previously. An additional consideration was that building/lot coverage for areas identified as Mixed-Use (Map 2.3-5, pink areas) would feature new streets and smaller block networks, as required in the Center zoning districts. In these Mixed-Use areas, more lot coverage would be necessary for new roadway infrastructure, further diminishing developable space. Using these factors and considerations, the following building/lot coverage assumptions (see Growth Projections Summary Table by TAZ Exhibit in Appendix B for details) were established for the assigned land uses identified in Map 2.3-6:

- Retail (1 story) – 30% building/lot coverage
- Retail (2 story) – 30% building/lot coverage
- Residential (3 story) – 25% building/lot coverage
- Residential (5 story) – 25% building/lot coverage
- Mixed-Use (5 story) – 20% building/lot coverage
- Mixed-Use (8 story) – 15% building/lot coverage

Analysis Factor 5 – Building Use Composition: The original GEIS assumed the composition of a non-residential building as 60% retail and 40% office. Due to the changing economic conditions and development trends discussed previously, precipitated by such conditions as the COVID-19 pandemic, online shopping, increased construction costs and interest rates, and bank financing issues, it is likely that this composition is no longer realistic. As previously noted and summarized above, the Town examined a variety of mixed-use development projects either recently constructed or currently proposed to understand current building use composition ratios (see Mixed-Use Site Plan Precedents Exhibit in Appendix B).

Based on these examples, the Town derived an updated ratio for building use composition using an approximate average of the various compositions from the constructed/proposed buildings: 80% of uses in mixed-use buildings are residential and the remaining 20% of uses are defined as non-residential. The 20% non-residential uses are generally located on the first floor and can contain a variety of uses such as retail, restaurants, offices, services, entertainment, technology, light industrial or flex space. Traditional office space demand has declined in Amherst since COVID, with vacancy rates at approximately 12%, similar to those observed state-wide. Office demand continues to decline in the short-term; however, the Town assumed that demand for new office space, particularly with regards to services, will experience increased demand within denser mixed-use developments in the future. Of the 20% of non-residential uses proposed, 5% of the share was designated for new office uses, and 15% for new retail use. The 80% residential uses were applied to upper floors. For residential uses, the average unit size was assumed to be 1,400 square feet; this size was divided into the overall projected residential floor area to derive a total number of new housing units feasible within a proposed building.

Analysis Factor 6 – Population, Housing and Commercial Growth: A traditional approach to monitoring growth in a community is through consideration of data for population, number of new housing units and new commercial growth over time. This data can provide valuable information on trends occurring in a community. Population data collected from the US Decennial Census, American Community Survey (ACS), and GBNRTC population projections, indicate Amherst's population has grown steadily since 2000. Census population counts over the previous decade grew from 122,366 persons in 2010 to 129,595 persons in 2020. Similarly, ACS population estimates for the past 5 years increased from 126,078 persons in 2019 to 131,063 persons in 2023, resulting in an overall average growth rate for Amherst of approximately 4.7%. In addition, the GBNRTC demographic projections for the BCD area (by TAZs) also predict a slow but steady increase in population from 7,356 persons in 2024 to 7,891 persons projected by 2050, with an average projected growth rate of 2.3% over the next 20+ years (see Demographic Projections Chart Exhibit in Appendix B).

Housing growth estimates and overall bedroom-size breakdowns were derived by utilizing Town planning and building permit data for the period 2019-2023. Analysis of rezoning, subdivision and site plan approvals, with subsequent review of constructed projects, found an overall town-wide housing unit growth rate of 3%. Further focusing on the building permit data for multifamily stand-alone or mixed-use housing units, the growth rate was 2%, or 1,111 units over the same 5-year timeframe (2019-2023). This 2% housing unit growth rate is consistent with the proposed future land uses and overall housing unit build-out of roughly 4,400 units over 20-years.

Housing growth estimates are based on Town-wide data, but these estimates were deemed applicable to the BCD alone given factors such as (1) Town's current efforts to foster redevelopment in older-commercial areas in the BCD, (2) the growing trend towards siting multi-family and mixed-use projects within regional commercial areas and where the size and scale of such buildings are more amenable to neighboring properties, and (3) the development community's increasing incorporation of upper-floor housing in commercial projects to ensure project viability.

Much of the commercial growth estimate for the BCD was also derived from the residential development data analysis. The residential development data indicates that within regional commercial corridors developers are increasingly proposing mixed-use projects that rely on first floor commercial and at least 3 to 4 stories of upper-story residential. In addition, more and more upper-story residential is necessary to improve overall commercial project viability given the strong housing demand, lack of housing stock available in Amherst, and the built-in customer base it can provide. Therefore, staff applied 1 to 2 story retail to high-value commercial real estate on major intensive commercial roadways where those factors matter to rental rates and applied mixed-use building development potential to areas adjacent to commercial uses, but requiring residential components to improve project viability.

**Study Area Growth Projections**

Table 2.3-1 shows growth projections from the original GEIS and those derived by the Town for the 2025 Projected Growth Redevelopment Scenario. The number of total new residential units and retail and office space anticipated to be added to the Study Area is identified for each TAZ (refer to Map 2.3-1 for TAZ locations)**.** For the 2025 Projected Growth Redevelopment Scenario, the following totals/thresholds were established for the new 20-year planning period (percentage distributions within each TAZ can be found in Maps B1, B2 and B3 in Appendix B):

- 4,921 Housing Units
- 2,258,676 SF Commercial Retail
- 303,268 SF Commercial Office

## Table 2.3-1: Growth Projections Comparison

**2019 (DGEIS)**

**2025 (SDGEIS)**

| | | TRAFFIC ANALYSIS ZONE (TAZ) BOUNDARIES | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Date** | **Proposed Land Use** | **668** | **676** | **677** | **678** | **679** | **680** | **681** | **682** | **683** | **684** | **686** | **687** | **688** | **699** | **701** | **702** | **705** | **708** | **709** | **Totals** |
| **2019 (DGEIS)** | Total Dwelling Units | 0 | 200 | 500 | 1140 | 180 | 180 | 50 | 1700 | 150 | 50 | 115 | 205 | 75 | 20 | 0 | 75 | 300 | 35 | 25 | **5,000** |
| **2025 (SDGEIS)** | Total Dwelling Units | 0 | 78 | 494 | 1,140 | 0 | 43 | 50 | 1,551 | 269 | 50 | 115 | 385 | 118 | 20 | 0 | 200 | 320 | 90 | 0 | **4,921** |

| **Date** | **Proposed Land Use** | **668** | **676** | **677** | **678** | **679** | **680** | **681** | **682** | **683** | **684** | **686** | **687** | **688** | **699** | **701** | **702** | **705** | **708** | **709** | **Totals** |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **2019 (DGEIS)** | Total Retail (SF) | 0 | 440,000 | 200,000 | 100,000 | 310,000 | 30,000 | 40,000 | 190,000 | 125,000 | 100,000 | 24,000 | 30,000 | 47,000 | 70,000 | 20,000 | 4,000 | 100,000 | 42,000 | 6,000 | 1,878,000 |
| **2019 (DGEIS)** | Total Office (SF) | 0 | 290,000 | 100,000 | 35,000 | 10,000 | 20,000 | 25,000 | 127,000 | 85,000 | 70,000 | 20,000 | 92,000 | 40,000 | 60,000 | 18,000 | 2,000 | 75,000 | 29,000 | 6,000 | 1,104,000 |
| | | | | | | | | | | | | | | | | | | | | **TOTAL SQUARE FEET (2019 DGEIS)** | **2,982,000** |

| **Date** | **Proposed Land Use** | **668** | **676** | **677** | **678** | **679** | **680** | **681** | **682** | **683** | **684** | **686** | **687** | **688** | **699** | **701** | **702** | **705** | **708** | **709** | **Totals** |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **2025 (SDGEIS)** | Total Retail (SF) | 0 | 82,062 | 109,678 | 299,265 | 310,159 | 28,622 | 65,350 | 831,015 | 51,799 | 13,875 | 69,845 | 0 | 147,657 | 7,000 | 0 | 52,500 | 84,000 | 31,394 | 74,456 | 2,258,676 |
| **2025 (SDGEIS)** | Total Office (SF) | 0 | 0 | 0 | 99,755 | 0 | 0 | 0 | 158,013 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17,500 | 28,000 | 0 | 0 | 303,268 |
| | | | | | | | | | | | | | | | | | | | | **TOTAL SQUARE FEET (2025 SDGEIS)** | **2,561,944** |

# SECTION 3.0

# ENVIRONMENTAL SETTING, POTENTIAL IMPACTS & MITIGATION

## 3.1 Transportation

### 3.1.1 Existing Conditions

**Regional and Local Context**

The SGEIS Study Area is located in the southwest portion of the Town of Amherst which is part of the Buffalo-Niagara metropolitan region. The Study Area is near the UB North Campus; downtown Buffalo is about 10 miles to the west. The site is easily accessible to the Buffalo-Niagara International Airport located about 10 miles to the southeast.


**Transportation Infrastructure and Site Access**

The Study Area is generally bounded by the following roadways: I-290, Niagara Falls Boulevard (US Route 62) and Sheridan Drive (NY Route 324). Access to/from I-290 is available at Niagara Falls Boulevard (Interchange 3), Millersport Highway (Interchange 5), and Sheridan Drive (Interchange 6). Other roadways in the Study Area that provide regional access to/from the Study Area and are functionally classified as Principal Arterials include Maple Road, Eggert Road, and Bailey Avenue. Minor arterials and local streets within the Study Area that provide connections to the regional network include: Ridge Lea Road, North Bailey Avenue, The Boulevard (Consumer Square Plaza) access drive, Romney Drive, Meyer Road, Alberta Drive, and Almeda Avenue. Map 3.1-1 shows the primary roadway corridors in the Study Area.

***Roadway Network***

The Study Area is served by a network of local, county, and state-maintained roadways. The principal study corridors and their maintenance jurisdiction are shown in Map 3.1-1 and in Table 3.1-1:

**MAP 3.1-1 – Study Corridors**



| Table 3.1-1: Study Corridors | | |
|---|---|---|
| **Roadway** | **Segment** | **Jurisdiction** |
| Niagara Falls Boulevard (US 62) | Eggert Road to I-290 Interchange 3 | New York State |
| Sheridan Drive (SR 324) | Eggert Rd to I-290 Interchange 6 | New York State |
| Maple Road (CR 192) | Niagara Falls Boulevard to Millersport Highway | Erie County |
| Bailey Avenue (US 62) | Eggert Road to Sheridan Drive | Erie County |
| North Bailey Avenue | Sheridan Drive to Ridge Lea Road | Town of Amherst |
| Ridge Lea Road | Bailey Avenue to Niagara Falls Boulevard | Town of Amherst |
| Millersport Highway (SR 263) | Sheridan Drive to Maple Road | New York State |
| Sweet Home Road (SR952T) | Sheridan Drive to Maple Road | Erie County |
| Eggert Road | Sheridan Drive to Millersport Highway | Erie County |
| Alberta Drive | Eggert Road to Maple Road | Town of Amherst |
| I-290 | Interchange #3 (US 62) | New York State |

Regional north/south access to the Study Area is provided via Niagara Falls Boulevard (US Route 62). Niagara Falls Boulevard is a principal arterial and part of the National Highway System. In the Study Area, Niagara Falls Boulevard features three travel lanes in each direction, a center median, and auxiliary turn lanes at major intersections. The posted speed limit on this roadway in the Study Area is 40 miles per hour (mph).

Regional east/west access to the Study Area is provided via Sheridan Drive (SR 324). Sheridan Drive is also a principal arterial and part of the National Highway System. In the Study Area, Sheridan Drive features three travel lanes in each direction with a center median and auxiliary turn lanes at major intersections. The posted speed limit is 40 mph.

Millersport Highway (SR 263) is a principal arterial that traverses the Study Area in a southwest-to-northeast orientation east of the Study Area. This roadway provides access to the UB North Campus as well as an interchange access with I-290. Between Sheridan Drive and the UB Campus, Millersport Highway features two travel lanes in each direction. The intersection of Millersport Highway and Maple Road is a half-diamond/partial cloverleaf interchange configuration. The posted speed limit is 45 mph between Maple Road and the I-290 interchange, and 35 mph between there and Sheridan Drive.

Sweet Home Road runs north/south through the Study Area. The segment from Sheridan Drive to Maple Road is a two-lane local County Road. North of Maple Road, Sweet Home Road is a state-owned roadway (SR 952T) with two travel lanes in each direction and a center lane for left turns. The state-owned segment is classified as a minor arterial. The posted speed limit is 35 mph on the County segment and 45 mph on the state-owned segment.

Maple Road (CR 192) is an east/west road through the Study Area. West of Niagara Falls Boulevard (in the Town of Tonawanda), it is Brighton Road and is classified as a minor arterial. East of Niagara Falls Boulevard (Town of Amherst), it is Maple Road and is classified as a principal arterial. From Niagara Falls Boulevard to North Bailey Avenue, Maple Road features three travel lanes in the westbound direction and two lanes in the eastbound direction with a two way left turn lane and exclusive turn lanes at intersections. In the eastbound direction, there is a curb lane for right-turns into property access drives and at street intersections. Maple Road transitions from three lanes to two lanes east of Bowmart Parkway in the westbound direction, with the center two-way left-turn lane maintained throughout these segments. The speed limit on Maple Road is 45 mph.

North Bailey Avenue is a north/south minor arterial that extends from Sheridan Drive to Ridge Lea Road. North Bailey Avenue is a two-lane road from Sheridan Drive to Maple Road, with auxiliary turn lanes at these two intersections and at the Wegman's signalized driveway. North of Maple Road, North Bailey Avenue also provides a center lane for left turns at intersections and driveways. The posted speed limit is 35 mph.

Ridge Lea Road is an east/west road that extends between Niagara Falls Boulevard and North Bailey Avenue and is functionally classified as a minor arterial. The segment of Ridge Lea Road from Niagara Falls Boulevard to the shopping plaza access, provides two eastbound lanes and one westbound lane (with auxiliary turn lanes at the approach to Niagara Falls Boulevard). From the plaza access to North Bailey Avenue, it is a two-lane road. The posted speed limit is 35 mph.


Alberta Drive is a 4-lane local road that extends north/south through the Study Area from Maple Road to Eggert Road. The speed limit on Alberta Drive is 35 mph.

Meyer Road is an east/west local road that begins at Niagara Falls Boulevard and continues east through the intersection with North Bailey Ave, terminating at a dead end just west of I-290. Meyer Road is a 2-lane road. The speed limit on Meyer Road is 30 mph.

These study roadways and their functional classifications are shown on Map 3.1-2[1]. See the footnoted link for additional information about the functional classification of roadways.

[1] Functional Classifications Source: https://www.dot.ny.gov/gisapps/functional-class-maps


**MAP 3.1-2 – Functional Classifications**



***Intersections***

The key intersections within the study area that were included for detailed analysis are shown in Map 3.1-3 and in Appendix C. All but four of the studied intersections are controlled by traffic signals. The 5-legged intersection of North Bailey Avenue and Emerson Drive/Amsterdam Avenue is presently controlled by stop signs on all approaches. This intersection was studied in August 2014 for potential improvements to address traffic safety and operational concerns. The study identified a recommended improvement option to reconstruct the intersection as a roundabout. Map 3.1-3 also shows the locations of other signalized intersections within the Study Area which were not evaluated for the SGEIS.

**MAP 3.1-3 – Study Area Intersections**




***Pedestrian and Bicycle Accommodations***

Map 3.1-4 shows the location of sidewalks and bike accommodations within the Study Area. In general, sidewalks are provided on one or both sides of all the study roadways, except for the following:

- Meyer Road east of North Bailey Avenue
- Bowmart Parkway
- Maple Road from Corporate Parkway to Flint Road
- Millersport Highway from Flint Road to the intersecting northern study limit

Pedestrian crosswalks and pedestrian-activated crossing signals are provided at all the signalized study intersections.

Millersport Highway is part of NYS Bike Route 517, which is a signed, on-road bicycle route that extends 90 miles from the Pennsylvania border near Jamestown to the Hamlet of Olcott in Niagara County. However, there are no design treatments or signing that enhance the bicyclist accommodation. On-road bike lanes are provided on both sides of Sweet Home Road from Eggert Road north to the UB North Campus.


***Transit***

Public transit services within the Study Area are provided by the Niagara Frontier Transportation Authority (NFTA). These services include Fixed bus routes and Paratransit. The fixed bus route service routes and stop locations in the Study Area are shown on Map 3.1-5 and additional service characteristics for these transit routes are shown in Appendix C. Bus stops in the Study Area are designated by an NFTA route sign. There are no bus shelters or other rider amenities at these stops.


The University at Buffalo also provides students, staff and faculty with transportation through a bus/shuttle to off-campus destinations. Based on the Spring 2025 Semester schedule, the university bus (the Stampede) which serves the North and South Campus, has stops including Tops Market, Wegmans, Walmart, Target, and the Boulevard Mall from the Campus.

The NFTA is in the planning process for an expansion of the Metro Rail network to extend Light Rail Transit (LRT) service through the Study Area. Because that planning process is ongoing, the transportation analysis for the Study Area SGEIS does not consider the impacts and benefits of this potential future enhancement of the transit system.

**MAP 3.1-4 – Pedestrian and Bicycle Accommodations**



**MAP 3.1-5 – Public Transit**



## Traffic Operations – Existing and Planned Conditions

Vehicular traffic operations at the study intersections were analyzed using the existing condition Synchro model developed for the study area based on the applicable procedures of the Highway Capacity Manual, published by the Transportation Research Board. The Synchro model was developed using the previous GEIS synchro model as a base and updating it with the most current conditions such as updated signal timings, etc. The current signal timing information and lane configuration were coordinated with the Town of Amherst and NYSDOT prior to conducting any existing or planned analysis.

Traffic operations are generally described in terms of a Level of Service ranking system. For intersection operations, Level-of-Service (LOS) is a qualitative expression of mobility based on the amount of control delay. LOS A represents very good conditions with little or no delay and LOS F generally represents very poor operations with high levels of delay. The LOS thresholds for signalized and unsignalized intersections are provided in Table 3.1-2.

The results of the intersection analyses show that the overall operations of most of the Study Area intersections are at LOS D or better during the PM and SAT peak hours for the Existing and Planned conditions. These operations are consistent with local and regional mobility objectives. The exceptions are as follows:

**Table 3.1-2: Intersection LOS Criteria**

| LOS Threshold | Unsignalized Control Delay per Vehicle (sec) | Signalized Control Delay per Vehicle (sec) |
|---|---|---|
| **A** | ≤ 10 | ≤ 10 |
| **B** | > 10 and ≤ 15 | > 10 and ≤ 20 |
| **C** | > 15 and ≤ 25 | > 20 and ≤ 35 |
| **D** | > 25 and ≤ 35 | > 35 and ≤ 55 |
| **E** | > 35 and ≤ 50 | > 55 and ≤ 80 |
| **F** | > 50 | > 80 |

Existing Conditions

Niagara Falls Boulevard and Sheridan Drive: PM – LOS E
Maple Road at Sweet Home Road: PM – LOS E

It is noted that although the overall intersection operations at the other study intersections are consistent with typically acceptable performance objectives, many of the study intersections have individual lane groups that operate with longer delays and lower LOS (E-F). These conditions are typically associated with lower volume turn movements and the delay is a function of the

long cycle lengths used to process the signal phasing, but in some cases the longer delays also occur on through movements. Summary Tables showing the capacity analysis results are provided in the Appendix C.

## Crash Analysis

Vehicle crash history data was obtained from NYSDOT's Crash Location and Engineering Analysis Repository (CLEAR) system for a three-year period from May 2021 to May 2024 for the Study Area. The crash data showed a total of 1,032 crashes reported to have occurred within the Study Area over the three-year period. A collision summary is shown on Map 3.1-6. There were no fatalities in the Study Area. About 65% of the crashes were property damage only and 35% were non-fatal injury crashes.

There were a total of 23 crashes throughout the Study Area involving pedestrians and bicyclists (15 pedestrian, 8 bicycle) during the study period, accounting for 2.2% of the total. Most of these crashes occurred at signalized intersections where there are crosswalks and pedestrian signals. The locations of these vehicular crashes with pedestrians/bicyclists are shown on Map 3.1-6.

Inspection of the collision data showed that 592 of the crashes occurred at intersections within the Study Area and 440 occurred on the various roadway segments between the study intersections.


The severity distribution of the intersection crashes is consistent with the general overall characteristics of all crashes in the Study Area: 65% property damage only and 35% non-fatal injury crashes. It should be noted that the locations with higher crash frequency also are typically higher-volume intersections.

Intersection crash distribution by manner of collision is detailed in Appendix C. The most common collision types at the intersections were rear end (45%) and left turn (15%) crashes. Overtaking crashes accounted for another 15% of the total.

The study intersections within the project area having the highest number of crashes over the three-year analysis period are listed below. These intersections are also some of the higher volume intersections in the Study Area:

- Maple Road at Sweet Home Road (58 crashes)
- Sheridan Drive at Millersport Highway (50 crashes)
- Niagara Falls Boulevard at Ridge Lea Road (49 crashes)
- Maple Road at North Bailey Avenue (45 crashes)

**MAP 3.1-6 – Collisions**



- Niagara Falls Boulevard at Maple Road and Brighton Road (44 crashes)
- Sheridan Drive at Bailey Avenue (37 crashes)
- Sheridan Drive at Sweet Home Road (33 crashes)
- Niagara Falls Boulevard at Romney Road (30 crashes)
- Niagara Falls Boulevard at Sheridan Drive (30 crashes)
- Sheridan Drive at Alberta Drive (23 crashes)
- Maple Road at Alberta Drive (17 crashes)

Two intersections in particular had a significantly high number of crashes (>50 crash), Maple Road at Sweet Home Road and Sheridan Drive at Millersport Highway. The majority of the crashes were rear ends with a listed cause of following too closely and driver inattention. Congestion increases the chances of rear ends with unexpected stops and increased driver frustration. The second typical crash for Maple Road at Sweet Home Road was left turn. These can be caused by disregarding traffic signals, driver inattention /distraction or failing to yield the right of way, which is noted in the crash reports as the primary cause. The signal operates on permissive and protective left turns for all approaches.

### 3.1.2 Potential Impacts & Mitigation

The potential transportation impacts associated with redevelopment within the Study Area result from changes in the amount of traffic generated by the proposed land uses, changes in travel patterns and travel mode, and their effect on traffic operations.

**Trip Generation**

The changes in trip generation associated with redevelopment within the Study Area were estimated by using GBNRTC's Regional Transportation Demand Model (TDM). These estimates considered the trip characteristics associated with the various land use types and densities contemplated within each TAZ, and the underlying considerations of local and regional socio-economic, demographic and travel mode characteristics. Projected development within the Study Area consists of the mix of uses described in Table 3.1-3.

The regional model analyzed the PM three-hour peak period for street segments that are federal aid eligible, this means some local streets were not accounted changes. To account for increases and decreases on each roadway segment during the Saturday peak hour, the PM regional model scenario was used as it is expected to have similar origin and destination patterns with the PM peak. A percentage change in traffic volumes between the base model and the model with the Project Growth Redevelopment Scenario volumes during the PM peak period were determined.

The streets with a high percentage increase in volumes were Alberta Drive, Niagara Falls Boulevard, Maple Road, North Bailey Avenue, and Sheridan Drive. To complete the analysis segment growth was translated to intersection turning movement volumes using a factoring procedure to determine impacts to intersections.

### Trip Distribution and Assignment

To determine future traffic volumes and routes, the percent change of road segments from the GBNRTC model comparing existing and proposed conditions was used to determine the significance of road segment increases and or decreases. Individual intersection turning movements were then determined by comparing the ratio of turning movements between existing condition and proposed conditions. This ratio was used to apply volume differences to the planned model turning movements. To validate the projected traffic volumes, TAZ's which resulted in a 5% or greater of the total area growth were considered a significant increase in future volumes and therefore routes to and from those TAZ's within the Study Area were reviewed to compare the increased growth and ensure an increase in traffic volumes was captured on those routes to and from the major development TAZ's. See Map 2.3-1 in Section 2 for a map of TAZ Boundaries.

Overall distribution of vehicles entering and exiting the study area were also identified to verify increases in traffic volumes. Main access points to the study area include the following intersections:

- Niagara Falls Boulevard at Ridge Lea Road/Koeing Road
- Niagara Falls Boulevard at Maple Road
- Niagara Falls Boulevard at Sheridan Drive
- Maple Road at Millersport Highway
- Sheridan Drive at Millersport Highway
- Eggert Road at Bailey Avenue

From these major access points into and out of the study area, traffic was distributed based on level of road segment increases in traffic that were reported from the regional model, as well as the increases in each TAZ based on growth from new development.

| Table 3.1-3: Boulevard Central District TAZ Growth Projections | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **TAZ** | **Amherst BCD Projections** | | | **Amherst BCD Projections with Land Use Changes to Population & Employment** | | | | |
| | **Total Units** | **Retail SF** | **Office SF** | **Population** | **Retail Emp*** | **Office Emp*** | **Total Pop & Emp Growth** | **Percentage of Growth** |
| **668** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0% |
| **676** | 78 | 82,062 | 0 | 108 | 234 | 0 | 343 | 2% |
| **677** | 494 | 109,678 | 0 | 756 | 313 | 0 | 1,069 | **6%** |
| **678** | 1,140 | 299,265 | 99,755 | 2,394 | 855 | 570 | 3,819 | **22%** |
| **679** | 0 | 310,159 | 0 | 0 | 886 | 0 | 886 | **5%** |
| **680** | 43 | 28,622 | 0 | 74 | 82 | 0 | 155 | 1% |
| **681** | 50 | 65,350 | 0 | 115 | 187 | 0 | 301 | 2% |
| **682** | 1,551 | 831,015 | 158,013 | 2,389 | 2,374 | 903 | 5,666 | **33%** |
| **683** | 269 | 51,799 | 0 | 422 | 148 | 0 | 570 | 3% |
| **684** | 50 | 13,875 | 0 | 125 | 40 | 0 | 165 | 1% |
| **686** | 115 | 69,845 | 0 | 265 | 200 | 0 | 464 | 3% |
| **687** | 385 | 0 | 0 | 905 | 0 | 0 | 905 | **5%** |
| **688** | 118 | 147,657 | 0 | 283 | 422 | 0 | 705 | 4% |
| **699** | 20 | 7,000 | 0 | 45 | 20 | 0 | 65 | 0% |
| **701** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0% |
| **702** | 200 | 52,500 | 17,500 | 384 | 150 | 100 | 634 | 4% |
| **705** | 320 | 84,000 | 28,000 | 602 | 240 | 160 | 1,002 | **6%** |
| **708** | 90 | 31,394 | 0 | 189 | 90 | 0 | 279 | 2% |
| **709** | 0 | 74,456 | 0 | 0 | 213 | 0 | 213 | 1% |

*Town of Amherst Economic Study (2016)
350 sq ft per retail employee
175 sq ft per office employee

## Traffic Operations – Planned Condition

The same capacity analysis methodology used for the Existing Condition was used for the Planned Condition to assess the ability of the road network to carry the estimated trips associated with the proposed project without any improvements to the network. The results of these analyses show that the changes in traffic volume and circulation patterns associated with the 2025 Projected Growth Redevelopment Scenario will have an impact resulting in an overall LOS E or F operations at the following intersections in the Planned Condition.

| Planned Condition | |
|---|---|
| Maple Road and Sweet Home Road: | PM - LOS E |

Under the Planned Condition and without mitigation, the LOS at the intersection of Niagara Falls Boulevard at Sheridan Drive improved from E to D during the PM peak hour. Adjustments in traffic volumes also impact adjacent intersections and street segments which resulted in shifting arrival patterns at intersections due to a change in vehicle headway. The change in arrival patterns has a cascading impact within the study area network most focused on directly connected streets and intersections resulting in improvements to LOS movements without any roadway improvements applied.

## Mitigation Measures

Mitigation measures offset a project's traffic impacts by employing geometric, operational and other techniques to accommodate the traffic from a proposed project. The following improvements have been identified:

**Corridor Improvements:**

Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive

- Adaptive signal control

Ridge Lea Road/ North Bailey Avenue: Niagara Falls Boulevard to Maple Road

- Widen from a 3-lane cross section to a 5-lane cross section

Bowmart Parkway: Maple Road to Meyer Road

- Resurfacing

Sheridan Drive: Niagara Falls Boulevard to Millersport Highway

- Revised signal timings and coordination

**Intersection Improvements:**

Maple Road and Sweet Home Road

- Updated signal timings including exclusive left turns and improved yellow/red times
- Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out)
- Adjust the northbound approach – Northbound right turn lane changes to right and through lane
- Adjust signal timing

Sheridan Drive and Sweet Home Road

- Updated timings including exclusive left turns and improved yellow/red times
- Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out), and bicycle boxes

- Adjust signal timing, cycle length too long even considering it is a part of a coordinated network, including leading pedestrian and bicycle intervals

North Bailey Avenue, Emerson Drive and Amsterdam Avenue

- Convert to a single lane roundabout

Conceptual layouts of these improvements are provided in Appendix C.

This program of improvements will maintain LOS D or better operations at all of the studied intersections in the planned condition during the PM and Saturday peak hours, except at the Maple Road/Sweet Home Road intersection as noted above. Most intersection approaches will also operate at LOS D or better, but there will be some approaches and/or individual movements that will operate at LOS E or F. These operations are consistent with the Existing Condition.
These proposed improvements limit the need to create large intersections which is consistent with local objectives for maintaining/enhancing community character. Other improvement options that could be considered include access management strategies, providing additional multi-modal infrastructure, and leveraging ITS technology where possible to maximize efficiency within the existing road infrastructure. The mitigation strategies should also be reevaluated if/when a future transit expansion is implemented by NFTA.

## Mitigation Improvement Costs

Cost estimates for the transportation improvements identified above were developed to reflect current and future construction costs. These cost estimates include considerations for design, construction, and construction administration/inspection. Design and construction administration/inspection costs were based on a percentage of the construction cost, consistent with applicable guidelines for federal-aid projects. Mitigation costs were calculated based on a development's percentage consumption of new peak-hour, peak-direction traffic capacity by roadway segment or intersection, and the cost by link or node of creating that capacity. Costs are split into two shares; a public share, and a private share of proportional costs.

The improvement costs shown in Table 3.1-4 are presented based on Year 2025 costs and escalated to a Year 2030 and Year 2035 cost basis. As shown, the total estimated cost of transportation improvements to address the identified future traffic mobility/congestion issues for the Projected Growth Redevelopment Scenario assessment of growth potential is $39.5 million (2030 cost basis).

## Funding Considerations

It cannot be assumed that funding for the transportation improvements described previously will be funded exclusively with private or public finances. In addition to mitigating the traffic impacts

of the Study Area redevelopment, the improvements will have a public benefit by improving mobility and safety. Consequently, a public/private sharing of the costs of the new transportation infrastructure may be appropriate. Mitigation costs are calculated based on a development's percentage consumption of new peak-hour, peak-direction traffic capacity by roadway segment or intersection, and the cost by link or node of creating that capacity.

***Public Share***

The public share will incorporate costs considering the following:

- Existing and background growth
- New traffic to and from residential locations within the Study Area
- Existing and new traffic to and from public institutions (e.g. University at Buffalo)
- The amount of additional reserve capacity created (reserve capacity can be expected to be minimal, even after implementation of planned improvements)
- Safety improvements
- Costs may be covered under State or Federal grant funding, and supported by NYSDOT, Erie County Department of Public Works, and the Town, but there is no guarantee and it depends on the available funding.

***Private Share***

The private share will incorporate costs considering the following:

- Existing and new traffic to and from commercial properties in the Study Area
- New residential traffic in the Study Area

See Appendix C – Mitigation Objectives for more information on the process.

There are existing streets and intersections which have capacity to accommodate additional traffic volumes but they are not operating at full potential based on inefficiencies with the traffic signal network, or the infrastructure, such as a road surface in poor condition making it a less appealing route. Some of these streets and intersections provide direct access through a public street to new development areas and relieve congestion from parallel routes which are at capacity. Costs for these locations were not based on providing additional capacity, but how much of the remaining capacity that anticipated development traffic will be using (see Table 3.1-5 for more detail).

| Table 3.1-4: Estimated Mitigation Improvements and Costs | | | | | |
|---|---|---|---|---|---|
| **Location** | **Improvements** | | **Estimated Cost** | | |
| | | | **2025 Cost** | **2030 Cost** | **2035 Cost** |
| **Corridor Improvements** | | | | | |
| Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive | Adaptive signal control using ITS technology | Design | $21,750 | $26,250 | $29,250 |
| | | Construction | $145,000 | $175,000 | $194,900 |
| | | Construction CS/CI | $14,500 | $17,500 | $19,500 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | ***Total Cost*** | ***$181,250*** | ***$218,750*** | ***$243,650*** |
| Ridge Lea Road/N Bailey Avenue: Niagara Falls Boulevard to Maple Road | Add a travel lane in each direction with turn lanes at intersections | Design | $3,157,150 | $3,660,000 | $4,242,950 |
| | | Construction | $21,047,650 | $24,400,000 | $28,286,300 |
| | | Construction CS/CI | $2,104,800 | $2,440,000 | $2,828,650 |
| | | ROW Acquisition | TBD | TBD | TBD |
| | | ***Total Cost*** | ***$26,309,600*** | ***$30,500,000*** | ***$35,579,000*** |
| Bowmart Parkway: Maple Road to Meyer Road | Resurfacing | Design | $32,250 | $38,250 | $43,350 |
| | | Construction | $215,000 | $255,000 | $288,950 |
| | | Construction CS/CI | $21,500 | $25,500 | $28,900 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | ***Total Cost*** | ***$268,750*** | ***$318,750*** | ***$361,200*** |
| Sheridan Drive: Niagara Falls Boulevard to Millersport Highway | Revised signal timings and coordination | Design | $1,200 | $1,400 | $1,650 |
| | | Construction | $8,000 | $9,300 | $10,750 |
| | | Construction CS/CI | $800 | $1,000 | $1,100 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | ***Total Cost*** | ***$10,000*** | ***$11,700*** | ***$13,500*** |
| **Intersection Improvements** | | | | | |
| Maple Road at Sweet Home Road | • Updated timings including exclusive left turns and improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out)<br>• Adjust the northbound approach – NB right turn lane changes to right and through lane | Design | $12,150 | $15,150 | $16,330 |
| | | Construction | $81,000 | $101,000 | $108,850 |
| | | Construction CS/CI | $8,100 | $10,100 | $10,900 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | ***Total Cost*** | ***$101,250*** | ***$126,250*** | ***$136,050*** |

**table continued on next page*

| Table 3.1-4: Estimated Mitigation Improvement Costs (continued) | | | | | |
|---|---|---|---|---|---|
| Sheridan Drive at Sweet Home Road | • Updated timings including exclusive left turns and improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out), and bicycle boxes<br>• Adjust signal timing, cycle length too long even considering it is a part of a coordinated network, including leading pedestrian and bicycle intervals | Design | $12,150 | $15,150 | $16,330 |
| | | Construction | $81,000 | $101,000 | $108,850 |
| | | Construction CS/CI | $8,100 | $10,100 | $10,900 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | ***Total Cost*** | ***$101,250*** | ***$126,250*** | ***$136,050*** |
| Emerson Drive at N Bailey Avenue | Convert to a roundabout | Design | $291,750 | $338,250 | $392,100 |
| | | Construction | $1,945,000 | $2,255,000 | $2,613,950 |
| | | Construction CS/CI | $194,500 | $225,500 | $261,400 |
| | | ROW Acquisition | TBD | TBD | TBD |
| | | ***Total Cost*** | ***$2,431,250*** | ***$2,818,750*** | ***$3,267,450*** |
| **Total Mitigation Improvement Costs** | | | **$29,403,350** | **$34,120,450** | **$39,520,250** |

A detailed breakdown including the justification for each cost share of improvements can be found in Appendix C.

Not included in these transportation improvements are site access improvements that are required to mitigate the direct impact of any individual development, i.e. traffic signals, turn lanes into driveways, access roads, and any treatments beyond what is outlined in this document. Site access improvements are still required to be implemented by the developer as part of site plan approval.

The basic methodology considers existing traffic volumes, future development and non-development volumes and the amount of additional reserve capacity created by the transportation improvements to identify a basis for allocating public and private shares for funding the improvement(s). This approach in assessing transportation mitigation costs has been successfully used for several GEIS areas in the Capital Region of New York State. Based on the number of trips anticipated with the private share percentage of each mitigation project, the mitigation share per trip is $1,130. Table 3.1-6 provides a summary of the cost shares associated with each improvement location. Additional information on the cost breakdown is included in the Mitigation Memo in Appendix C.

| Table 3.1-5: Threshold Analysis for Improvements | | | | | |
|---|---|---|---|---|---|
| | PM Peak Hour Traffic (vph) | | LOS D Threshold | | |
| | Existing (2025) Volume | Planned Demand Volume | Maximum Volume* | Volumes that Could be Accommodated | % Cost of Private Share Improvements |
| **Street Segments** | | | | | |
| Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive | | | | | |
| | 3,700 | 4,300 | 3,700 | 0 | 0% |
| | w/adaptive signal control | | 4,300 | - | 100% |
| Ridge Lea Road/N Bailey Avenue: Niagara Falls Boulevard to Maple Road | | | | | |
| | 1,660 | 2,090 | 1,680 | 20 | - |
| | w/ 4 lane cross section | | 2,500 | 820 | 35% |
| Bowmart Parkway: Maple Road to Meyer Road | | | | | |
| | 434 | 560 | 1,680 | 1,120 | - |
| | w/upgrades | | 1,680 | 1,120 | 10% |
| Sheridan Drive: Niagara Falls Boulevard to Millersport Highway | | | | | |
| | 2,600 | 2,850 | 2,600 | 250 | 0% |
| | w/ coordinated network | | 2,850 | - | 100% |
| **Intersections** | | | | | |
| Maple Road at Sweet Home Road | | | | | |
| | 3,093 | 4,637 | 3,436 | 343 | - |
| | w/ lane and timing changes | | 5,040 | - | 21% |
| Sheridan Drive at Sweet Home Road | | | | | |
| | 2,897 | 3,187 | 2,897 | 0 | - |
| | w/timing changes | | 3,400 | 213 | 57% |
| N Bailey Avenue at Emerson Drive & Amsterdam Avenue (Stop Controlled) | | | | | |
| | 1,225 | 1,390 | - | - | - |
| | roundabout | | - | - | 0% |

*The assumptions in this table are based on the principles discussed in the 2010 Highway Capacity Manual that provides planning level engineering estimates for capacity. This is for a base condition and may vary per location depending on number of access points, speed, driver behavior, truck percentage, signal timings and spacing, etc. Values were also checked in Synchro running an arterial LOS analysis since each road has unique site condition impacting capacity.

Mitigation costs per trip are recommended to be collected based on the 2030 public/private share costs, which is the median year from existing and long-term improvements. Development, growth, and determining needs for mitigation projects based on the traffic demands created from development will not be known or needed until a future date. Collecting funds based on existing dollars will result in a lack of resources to appropriately fund projects in future dollars, while collecting funds too far in advance may result in an excess of funds for necessary improvements. The Town will need the flexibility to apply projects, and therefore funding, as development projects become tangible and changing traffic volumes and patterns can be mitigated.

| Table 3.1-6: Public/Private Share Costs | | |
|---|---|---|
| **Project** | **Private Share Cost (2030)** | **Public Share Cost (2030)** |
| Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive | $218,750 | - |
| Ridge Lea Road: Niagara Falls Boulevard to N Bailey Avenue/Maple Rd | $10,675,000 | $19,825,000 |
| Bowmart Parkway: Maple Road to Meyer Road | $31,880 | $286,880 |
| Sheridan Drive: Niagara Falls Boulevard to Millersport Highway | $11,700 | $0 |
| Maple Road at Sweet Home Road | $26,520 | $99,740 |
| Sheridan Drive at Sweet Home Road | $71,960 | $54,290 |
| N Bailey Avenue at Emerson Drive & Amsterdam Avenue | $0 | $2,818,750 |
| ***Total*** | ***$11,035,810*** | ***$23,084,660*** |

# 3.2 Utilities

## 3.2.1 Existing Conditions

### Water

Water for the Study Area is provided by the Erie County Water Authority (ECWA) through a lease-manage arrangement. The ECWA is responsible for customer service, billing, meter reading, and routine maintenance, but the Town is responsible for capital improvements. There are a few small areas on the southern edge of the Study Area that are in direct-service water supply areas, that are owned and operated by ECWA.

The ECWA utilizes two water treatment plants, the Van De Water Treatment Plant and the Sturgeon Point Water Treatment Plant. Water for the Study Area is provided from the former, via a 48-inch precast concrete cylindrical pipe (PCCP) that conveys water to the Ball Pump Station, located just north of I-290 on Sweet Home Road. The nearest elevated storage tank is located near the intersection of I-90 and I-290, approximately 2.1 miles south of the Study Area. According to ECWA, the zone of influence for this tank does not extend far enough north to affect pressures within the Study Area.

The Ball Pump Station distributes water to the northern service areas of the ECWA, including Amherst and the entirety of the Study Area. The station has four pumps and a combined capacity of 71 million gallons per day (MGD). The historical average day and peak hourly flow for the Ball Pump Station is 17.0 MGD and 41.75 MGD, respectively. This results in a calculated peak factor of 2.46.

The Study Area is serviced by water mains ranging in size from 6 inches to 16 inches in diameter. The area between Maple Road and Sheridan Drive is predominantly served by cast iron water mains. Most of these mains were installed in the 1950's and 1960's, although a few segments date back to the 1930's. Ductile iron pipe is present generally among the single-family residential areas near Sweet Home Road, as well as along Niagara Falls Boulevard north of Maple Road. A PVC water main is present in the Study Area north of Maple Road. There are also a few records of asbestos concrete (ACP) water main in the Study Area.

The Town provided billing records for the water meters within the Study Area. Where billing records were not available, usage was estimated based on the *New York State Design Standards for Intermediate Sized Wastewater Treatment Systems,* assuming 110 gpd per bedroom (3BR) for single family homes, and 0.1 gpd/sf for commercial properties. The current Study Area average

day water usage is approximately 0.97 MGD. Using the peak factor from the Ball Pump Station, the current peak water usage is approximately 2.39 MGD.

### Sewer

The Town of Amherst owns and operates a publicly owned treatment works (POTW) under State Pollutant Discharge Elimination System (SPDES) Permit # NY-0025950. The POTW consists of a separate sanitary sewer system and an Advanced Water Pollution Control Facility (AWPCF). The AWPCF is located on Tonawanda Creek Road and is permitted for 48 MGD with a discharge to Tonawanda Creek.

The existing sanitary sewer collection system includes 550 miles of sewer mains, ranging in size from 6 to 96 inches in diameter. Pipe materials vary, with the majority being constructed of clay tile, concrete (RCP and ACP), and PVC.

The sanitary sewer system in the Town is of varied age and physical condition. A significant percentage of the system was constructed from 1920 to 1960; the majority of pipe laid during those years was clay tile pipe. Significant work has occurred over the past 25 years to document the condition, clean, and stabilize structurally failing pipe.

In 2006, the Town of Amherst was given an Order on Consent, which required mitigation of its sanitary sewer overflow (SSO) points. As a condition of that Order, the Town submitted an Engineer's Report detailing work that would be necessary to mitigate the four remaining SSOs. To date, all of the projects within that report have been completed, and two of the four SSOs have been eliminated.

The two remaining SSOs are at the intersections of North Drive & Eggert Road, and at the intersection of Capen Drive & Oxford Road. In addition, a third, infrequently used SSO location was reported to the NYSDEC in 2018. That SSO location is at North Ivyhurst Road & Sheridan Drive. The volumes of SSOs reported to the NYSDEC are shown in Table 3.2-1 below.

**Table 3.2-1: Historical SSO Volumes**

| Year | North Dr & Eggert Road (gal) | Capen Dr & Oxford Rd (gal) | N. Ivyhurst Rd & Sheridan Dr (gal) |
|---|---|---|---|
| 2018 | 593,350 | 709,650 | 412,500 |
| 2019 | 240,096 | 231,418 | 0 |
| 2020 | 31,701 | 33,000 | 0 |
| 2021 | 144,562 | 167,026 | 243,750 |
| 2022 | 502,200 | 277,776 | 0 |
| 2023 | 0 | 0 | 0 |
| 2024 | 98,992 | 175,510 | 281,250 |

As a condition of the Town's most recent SPDES permit, the Town has authored a NYSDEC approved Capacity Management Operations and Maintenance (CMOM) document which formally details the maintenance procedures, reporting, recordkeeping and monitoring requirements for the sanitary sewer network. As part of the CMOM plan, the Town was required to prepare and execute a town-wide mini-system study plan (Sanitary Sewer Evaluation Study – SSES). The mini-system study plan requires an annual sewershed analysis with recommendations for following year improvements, focusing on the removal of inflow and infiltration (I&I) sources in the respective sewershed. The goal of the CMOM plan is to work through all of the Town's system, on a sewershed basis. The mini-system study consists of fieldwork to document average & peak flows and to determine I&I sources (through smoke testing, CCTV work and manhole inspections), with the goal of reducing wet weather flows and eliminating remaining SSOs and improving services.


The Town's AWPCF was constructed in the mid to late 1970s. The construction of the AWPCF supplanted the Town's original treatment plant, on North Forest Road. Flows at the AWPCF vary from an average of 26 to 28 MGD, to peak wet weather flows in excess of 120 MGD.

The Town's AWPCF was also operating under an Order on Consent. In 2012, the AWPCF violated its effluent permit limits for ultimate oxygen demand. A byproduct of that Order led to a study that prioritized $35 million in capital improvement projects. The last of these projects have recently been completed. In addition, considering the age of the facility and continually tightening regulations and codes, there is an ongoing backlog of capital projects that must be undertaken over the next decade to improve the reliability and effectiveness of the AWPCF.

There are multiple sewersheds that convey sewage from the Opportunity Zone to the AWPCF via the West Side Interceptor (Figure 3.2-1). The sewersheds that are tributary to the West Side Interceptor include approximately 220 miles of sewer main, ranging in size from 8 to 60 inches in diameter.

In general, the West Side Interceptor collects sewage from the oldest areas of the Town (including the Village of Williamsville) and conveys it along the I-290 ROW to an easement running north-south from Chestnut Ridge Road to the Peanut Line Interceptor.


**FIGURE 3.2-1: West Side Interceptor Sewersheds**




The West Side Interceptor is located in the vicinity of the Opportunity Zone and is a 54- to 66-inch reinforced concrete pipe. The segment of the West Side Interceptor extends from the Hartford Relief Sewer at Maple Road to Chestnut Ridge Road is frequently over capacity during rain events due to I&I. The capacity of the interceptor at this location is approximately 38.5 MGD. Although the average flow is 11.3 MGD and the peak daily flow is 13.9 MGD, the wet weather flow (corresponding to a 2-year, 6-hour storm event) is approximately 56.7 MGD, which exceeds the capacity.

Due to these capacity limitations, the West Side Interceptor surcharges at levels above 10 feet near Sheridan Drive, adjacent to the I-290. This surcharge creates a backwater effect throughout the system and is a primary cause of the SSO at North Ivyhurst and Sheridan Drive. The capacities and flows at various segments along the West Side Interceptor and other primary mains nearby are shown in Figure 3.2-2.

**FIGURE 3.2-2: Flows and Capacities of Primary Interceptors**



***Prior Initiatives***

In 2014, the Town of Amherst constructed a flow diversion point from the existing connection chamber/manhole of the West Side Interceptor/Chestnut Ridge sanitary sewer. The flow diversion consists of a 21-inch pipe with the invert matching the crown of the 60-inch West Side Interceptor at the connection point. The diversion is piped to the existing dead end 24-inch sewer running east along Chestnut Ridge Road to the Sweet Home Road Interceptor. The diversion flow rate varies based on the surcharge elevation and the position of the end of pipe gate control valve. Past metering results have shown a peak flow of 5 MGD diverted from the West Side Interceptor to the Sweet Home Road Interceptor with the flow control gate 100% open.

***Current Initiatives***

The Town, in its continual effort to plan for future developments and to improve its sanitary sewer system, has developed a sewer interceptor model (using the EPA modeling engine SWMM), and has completed a mini-system analysis of the sewershed that contains the Boulevard Mall. One of the goals of the modeling effort was to determine if construction of a wet weather relief pump station, to transfer flow from the bottle-necked portion of the West Side Interceptor to the Peanut Line Interceptor, would be a feasible method to manage the surcharge conditions. This concept will be explored further in the Impacts and Mitigation section.

The Town continues to evaluate the sewesheds that service the Boulevard Central District. In 2019, the Town embarked on a review of capacities and existing wastewater flows in the BCD via performance of a mini-system study. The first task associated with the performance of a mini-system study was the mapping of the mini-system, followed by the siting and deployment of temporary flow meters, as shown in Figure 3.2-3. For this particular mini-system, temporary flow meters were deployed from March 5 to June 30, 2019. A summary of the results of the flow metering are found in Table 3.2-2.

**Table 3.2-2: Measurements at Sewer Meter Locations**

| Segment | Size & Material; Pipe Capacity | Avg Flow | Peak Flow | Maximum Water Surface Elevation |
|---|---|---|---|---|
| Meter #1 Maple Rd @ Mall | 10 inch VTP; 0.73 MGD | 0.23 MGD | 0.80 MGD | 45 inches |
| Meter 2 Niagara Falls Blvd & Maple Rd | 12 inch ACP; 1.10 MGD | 0.26 MGD | 1.36 MGD | 27 inches |
| Meter 3 Niagara Falls Blvd & Consumer Sq | 12 inch ACP; 1.10 MGD | 0.59 MGD | 1.43 MGD | -- |
| Meter 4 Chestnut Ridge Rd | 24 inch RCP; 3.85 MGD | 0.65 MGD | 1.60 MGD | 18 inches |

**FIGURE 3.2-3: Mini-System Analysis Overview**




Based on Table 3.2-2, the existing sewers in the Boulevard Mall area (Meters 1, 2, & 3) are over capacity during peak flow conditions. These segments are over 50 years old. Furthermore, the existing sewer mains are constructed with fragile materials (VTP, ACP) and are installed within heavily trafficked corridors. Therefore, it was anticipated that a significant portion of the network identified in the mini-system map would have to be reconstructed and rehabilitated during the normal course of Town capital planning.

In addition, it is important to note that approximately 60% of the estimated peak flow from the Opportunity Zone will be generated by the redevelopment within this mini-system, which connects just downstream of the most capacity constrained section of the West Side Interceptor

(the segment from Maple Road to Chestnut Ridge Road). Other than the capacity issues described above and the backwater effect of the West Side Interceptor, there are no other known capacity deficiencies in the Opportunity Zone sewershed.

### Stormwater

The Town of Amherst is currently a member of the Western New York Stormwater Coalition as well as a regulated Municipal Separate Storm Sewer Systems (MS4) community in Erie County.

The Town has developed a Stormwater Management Plan (March 2018) in compliance with the New York State Pollutant Discharge Elimination System (SPDES) General Permit for Stormwater Discharges from MS4s (GP-0-24-001). The goal of the plan is to provide stormwater runoff control and prevent pollutants discharging from storm sewers to the waterbodies of the United States to meet the requirements of the Phase II regulations of the federal Clean Water Act. The objective of this plan is to reduce the amount of pollutants in stormwater runoff to the "maximum extent practicable" with six program elements and Minimum Control Measures:

- Public Education and Outreach
- Public Involvement and Participation
- Illicit Discharge Detention and Elimination
- Construction Site Runoff Control
- Post Construction Stormwater Management
- Pollution Prevention and Good Housekeeping for Municipal Operations

For each Minimum Control Measure and Best Management Practice (BMP) described in the plan, the Town's responsibilities are clearly defined. Some components of the required work are provided through the collective efforts of the Western New York Stormwater Coalition, while the remaining work is provided by the Town of Amherst and has been adopted into the Local Law in August 2007, as amended.

The Town has one stormwater drainage management district. Stormwater in the Town is managed through a series of open ditches, closed pipes, detention ponds and creeks. Stormwater management is a concern to many residences, with particular focus on localized flooding resulting from rain events and water quality impacts of stormwater runoff. There are also concerns about the receiving waters from this area (Ellicott Creek) and the tributaries to the creek. The existing closed storm conveyance systems were originally designed to convey up to the 10-year storm event.

Localized flooding is an issue within the Study Area. The Town keeps records of flooding and sewer back-up complaints, many of which are noted within the residential areas of the Study

Area. A well-known location for periodic flooding during storm events is the Maple Road and Niagara Falls Boulevard intersection.

**Energy & Communications Services**

Electric service is provided to the Study Area by National Grid. National Fuel provides gas service. Communication services, including television and internet, are provided by Verizon (multiple carriers for wireless service) and Spectrum.

## 3.2.2 Potential Impacts & Mitigation

**Water**

Future water demand for the Study Area under the 2025 Projected Growth Redevelopment Scenario was calculated by applying the unit flow rates from *Design Standards* to the number of projected residential units and commercial building area. Specifically, the following parameters were used to calculate flow for the Redevelopment Scenario:

- 2/3rd of the dwelling units assumed to be 2 bedroom at 110 gpd/bedroom
- 1/3rd of the dwelling units assumed to be 1 bedroom, at 110 gpd/bedroom
- Retail and office are estimated at 0.1 gpd/SF
- A 20% reduction in flow was applied to all values for water saving fixtures
- Peak water flow was calculated by applying the Ball Pump Station peak factor (2.46)

The growth under the 2025 Projected Growth Redevelopment Scenario would add approximately 0.93 million gallons per day (MGD) under average conditions and 2.29 MGD under peak demand conditions (calculated by applying the peak factor of 2.46 from the Ball Pump Station). When combined with the existing demand of the Study Area, the future average day water demand is 1.90 MGD, and the future peak water demand is 4.69 MGD.

In order to evaluate the impacts to the water system, a skeletonized hydraulic model was constructed of the Study Area. The model was built using water main data provided by ECWA and water meter billing records provided by the Town. The water meter records were spatially linked to parcel data, which was then imported into the model to provide an accurate distribution of flow. Future demand multipliers were applied according to the growth projected for a given Transportation Analysis Zone (TAZ).

The Study Area model was calibrated using hydrant flow test records provided by ECWA by adjusting the internal pipe roughness factors (C-factor) until simulated conditions matched measured conditions. In the calibrated model, cast iron water mains have C-factors ranging from

70-85. Cast iron water mains tend to become tuberculated with age, resulting in rougher internal surfaces, reduced diameter, and higher friction losses. Ductile iron pipe can also become rougher with age; therefore, DIP older than 20 years were assigned a C-factor of 110, and newer than 20 years had a C-factor of 120. Plastic pipe, such as PVC, tends not to deteriorate internal roughness, so these mains were assigned a C-factor of 140.

Model scenarios were created to compare simulated pressures under the following conditions:

- Current Average Demand
- Current Peak Demand
- Future Average Demand
- Future Peak Demand

Table 3.2-3 provides a summary of the simulated pressures in the Study Area under each scenario.

**Table 3.2-3: Simulated Water Pressures in Study Area**

| Scenario | Min (psi) | Max (psi) | Mean (psi) |
|---|---|---|---|
| Current Average | 88 | 101 | 93 |
| Current Peak | 87 | 98 | 91 |
| Future Average | 87 | 99 | 92 |
| Future Peak | 73 | 94 | 83 |
| Future Peak w/Mitigation | 77 | 94 | 85 |

Available fire flow was also used as a metric to establish the overall capacity of the distribution system in the Study Area. Hydraulic models can be used to iteratively ramp up demand at a specific junction, while monitoring pressure system-wide to ensure no other junctions drop below 20 psi (the minimum recommended operating pressure). This process is repeated for every junction in a given area. The available fire flow simulations were performed using peak demand conditions for conservative comparisons. NFPA 291, *Recommended Practice for Fire Flow Testing and Marking of Hydrants,* categorizes hydrants based on available fire flow:

- Class AA: 1500+ gpm
- Class A: 1000 – 1500 gpm
- Class B: 500 – 1000 gpm
- Class C: < 500 gpm

The results of the simulated available fire flow in the Study Area are provided in Table 3.2-4.

| Table 3.2-4: Simulated Available Fire Flows in Study Area | | | |
|---|---|---|---|
| **Scenario** | **Min (gpm)** | **Max (gpm)** | **Mean (gpm)** |
| Current Peak | 1,100 | 5,000+ | 3,400 |
| Future Peak | 920 | 5,000+ | 2,900 |
| Future Peak w/Mitigation | 1,300 | 5,000+ | 3,400 |

Although the Ball Pump Station has sufficient excess capacity, the increased water demand associated with the Projected Growth Redevelopment Scenario will strain the capacity of the existing distribution system in the Study Area, especially during peak periods. The future simulated water pressure drops by 8 psi during peak periods; the minimum pressure in the Study Area drops by 14 psi. The mean available fire flow drops by about 500 gpm under the future peak scenario.


In order to maintain the quality of water service as it exists today and to mitigate the impacts of the 2025 Projected Growth Redevelopment Scenario, the aging cast iron water mains should be replaced in the Study Area. With the cast iron mains replaced, the simulated water pressure rises to 85 psi under peak conditions and average available fire flow in the Study Area would be equal to current.

The recommended mitigation action would involve the replacement of approximately 52,000 linear feet of water main, ranging in size from 6 inches to 16 inches in diameter. Approximately 12,500 feet of the cast iron pipe is located in areas that would be directly redeveloped in the Study Area and would need to be replaced regardless of size or condition; replacement of these mains will be categorized as the private share of the mitigation.

The remainder of the pipes are located either in entirely residential neighborhoods, which are not expected to have significant growth under the Projected Growth Redevelopment Scenario, (nor are they located along major thoroughfares). These mains provide water service to areas both inside and outside the Study Area. Replacement of these mains would be necessary for smooth water system operation under the redevelopment scenario, but the surrounding areas would also benefit from these pipes being replaced. Therefore, these mains will be categorized as the public share of the mitigation. These mains are displayed in Figure 3.2-4.

The breakdown of pipe lengths and cost sharing is provided in Table 3.2-5. The costs for water main replacement are estimated based on historical bid pricing for the area. The costs are inclusive of associated work required, such as traffic control, excavation, backfill, restoration, materials, hydrants, and service reconnections.

**FIGURE 3.2-4: Location of Cast Iron Mains to be Replaced for Mitigation**




The water mitigation costs have been updated using the Engineering News-Record Construction Cost Index (ENRCCI) methodology as presented in the Traffic Mitigation section of this chapter. As such, the estimated costs from 2019 have been adjusted to 2025 costs using the ENRCCI Index. Future adjustments of mitigation costs will be set upon a predetermined schedule (e.g., every three years or similar) to allow for the capture of incremental mitigation costs due to price volatility into the future.

The Water Mitigation Costs are shown in Table 3.2-5. The developer share of the Water Mitigation Costs are summarized using a cost per flow (gallon-per-day) basis. The Mitigation Costs are calculated using the average gallon per day flow, which are calculated according to the per-unit hydraulic loading rates provided in Table B-3 of the *New York State Design Standards for*

*Intermediate Sized Wastewater Treatment Systems* (2014). In this case, the growth under the Projected Growth Redevelopment Scenario would add an average of 930,000 gpd (0.93 MGD).

| Table 3.2-5: Mitigation Costs | | | | | |
|---|---|---|---|---|---|
| | | Developer Share | | Public Share | |
| Item | 2024 Unit Cost | Length (ft) | 2024 Cost | Length (ft) | 2024 Cost |
| 8" DIP | $271 | 12,500 | $ 3,383,400 | 30,100 | $ 8,147,300 |
| 12" DIP | $331 | - | - | 6,800 | $ 2,249,600 |
| 16" DIP | $361 | - | - | 2,500 | $ 902,300 |
| | | | | | |
| **Total** | | 12,500 | $ 3,383,400 | 39,400 | $ 11,299,200 |
| | | | | | |
| **Mitigation Cost per Average Flow GPD** | | **$ 3.64 / GPD** | | | |

## Sewer

Future sewer flows for the Study Area under the Projected Growth Redevelopment Scenario were calculated in the same manner as water, by applying the unit flow rates from *Design Standards* to the number of projected residential units and commercial building area. However, it is noted that the peak flow for sewer uses is a population-based method, stipulated in *Recommended Standards for Wastewater Facilities* ("Ten States Standards").

Specifically, the following parameters were used to calculate flow for the Redevelopment Scenario:

- 2/3rd of the dwelling units assumed to be 2 bedroom at 110 gpd/bedroom
- 1/3rd of the dwelling units assumed to be 1 bedroom, at 110 gpd/bedroom
- Retail and office are estimated at 0.1 gpd/SF
- A 20% reduction in flow was applied to all values for water saving fixtures
- Peak sewer flow estimates are derived from the formula used in the Ten States Standards (per TAZ):
    - $Peak\ Factor = \frac{18+\sqrt{P}}{4+\sqrt{P}}$, where *P* is population in thousands
    - Population (per TAZ) is calculated by taking the total average sewer flow estimate (including residential & retail/office), divided by 100 gpd/capita

The growth under the 2025 Projected Growth Redevelopment Scenario would add approximately 0.93 MGD of sewer flow under average conditions, and 3.46 MGD under peak demand conditions. The calculated average peaking factor is approximately 3.33.

As presented in the previous section, sewage flows from the Opportunity Zone ultimately discharge to the West Side Interceptor. The majority of the flow (60%) will be transmitted to the interceptor via a new spine sewer along North Bailey Road, and to a lesser extent, to the Niagara Falls Boulevard collector sewers. Smaller volumes of flow will be transmitted via the Hartford Relief sewer and the Sheridan Drive sewers. A breakdown of wastewater flows by tributary area is provided in Appendix D.

The capacities of the segments are shown in the following Table 3.2-6, along with modeled hydraulic conditions under the current and future 2025 Projected Growth Redevelopment Scenario:

**Table 3.2-6: Selected Sewer Segment Capacities**

| Segment | Size & Material; Pipe Capacity | Current Peak Flow | Future Peak Flow (Redevelopment) | Excess Capacity |
|---|---|---|---|---|
| Ridge Lea Road | 24 inch RCP; 3.85 MGD | 1.60 MGD | 3.30 MGD | 0.15 MGD |
| Hartford Relief Sewer at West Side Interceptor | 48 inch RCP; 24.5 MGD | 19.90 MGD | 20.8MGD | 3.30 MGD |
| West Side Interceptor at I-290 | 54 inch RCP; 36.5 MGD | 36.8 MGD | 37.31 MGD | - 0.81 MGD |
| West Side Interceptor at Hartford Relief Sewer | 54 inch RCP; 38.5 MGD | 56.7 MGD | 60.2 MGD | -21.70 MGD |

As shown above, there is generally sufficient capacity in the interceptor sewer systems to transmit existing and proposed flow (with the exception of the West Side Interceptor). Because the existing West Side Interceptor is significantly over capacity between Maple Road and Chestnut Ridge Road (at the Hartford Relief sewer) during wet weather events, one of the following alternative mitigation measures must be undertaken to minimize surcharge conditions and guard against future SSOs:

- Alternative #1 - Additional I&I work to reduce wet weather flows;
- Alternative #2 - Construction of a replacement parallel West Side Interceptor to remove the West Side Interceptor bottleneck; or
- Alternative #3 - Construction of a pump station to divert flows from the West Side Interceptor to another interceptor with spare capacity.

The alternatives listed above were identified to mitigate the increased sanitary sewage flow from the 2025 Projected Growth Redevelopment Scenario. It is important to note that the Town is committed to reducing wet weather flows throughout the system and that I&I mitigation work will continue for many years beyond the scope of this project and GEIS. These alternatives were studied by the Town in 2021 and are summarized later in this section.

In addition, the following baseline alternatives must be undertaken to create local sewer capacity for the redevelopment of the Boulevard Mall corridor:

- Stabilize and reline the Niagara Falls Boulevard sanitary sewer system:
    - Over the past three years, the Town has completed the rehabilitation (CIPP) of the Niagara Falls Boulevard sewers, north of Maple Road (Maple Road to 1641 Niagara Falls Boulevard and Ridge Lea Road to Willowridge Drive). Most of the rehabilitation included cured in place pipe (CIPP) lining and limited replacement of some of the sewer mains.
    - During the winter of 2022-2023, a portion of the system, from 1641 Niagara Falls Boulevard to Ridge Lea Road, collapsed and had to be replaced. Reconstruction of this segment was challenging and illustrated the difficulties that the Town would encounter if a full-scale pipe replacement project on Niagara Falls Boulevard were to proceed. In light of the challenges, the Town is instead constructing a "parallel" 21-inch sanitary sewer on North Bailey Avenue, from Maple Road to Ridge Lea Road.
    - The project costs for lining were $118,580, and the replacement 15-inch sewer cost was $404,000.
    - In addition, the sewer on Niagara Falls Boulevard from Ridge Lea to Willowridge Drive was relined (as this sewer serves as an overflow for this mini-system), for a cost of $168,860.

- Reline the 24-inch RCP from Ridge Lea Road to Chestnut Ridge Road (under the I-290):
    - This work was completed in 2024 at a project cost of $54,820.

- Replace 310 linear feet of 24-inch sewer with 30-inch sewer on Chestnut Ridge Road, from the West Side interceptor to the collector manhole.
    - This receives flow from the Willowridge neighborhood and the Boulevard Mall corridor (under the I290).
    - The estimated project cost is $950,000.

- Reline the sewer on Willowridge Drive to the Willowridge pump station, reline the remaining Ridge Lea Sewer south of the I-290, reline the sewer on Chestnut Ridge Road

from the I-290 to the collector manhole, and also rehabilitate the remining manholes in the mini-system.
    - The estimated project cost is $557,260.

- Construct an 18-inch "spine" sanitary sewer on North Bailey Avenue, to collect sewage from the BCD to the east of North Bailey Ave.
    - The Town completed this project, which will provide surcharge relief of the Niagara Falls Boulevard sewer, as well as provide additional capacity for redevelopment in the Boulevard Mall corridor.
    - The project cost was $3,331,000.

- Construction of wet weather flow capacity improvements at the AWPCF.
    - This project would include clarifier capacity enhancements, consisting of circumferential baffles and energy dissipation inlet structures.
    - The estimated project cost is $5,000,000.

The above baseline measures are necessary to increase and preserve capacity in the Boulevard Mall corridor. The preservation of capacity (via CIPP lining and rehabilitation projects) will also help stabilize fragile and aging pipe materials like ACP and RCP.

***Sanitary Sewer Mitigation***

Baseline Mitigation

The Town has an existing local law, which states the Town of Amherst is required (and obligated per NYSDEC) to reduce the infiltration and inflow (I&I) of water into the sewage system on a 4:1 ratio (i.e. 4 gpd of I&I to every 1 gpd of peak sewage flow) ratio for each new sewer connection above 2,500 gallons/day into the Town's AWPCF. I&I removal is calculated on a gallons-per-minute (gpm) basis and charged at four times the peak flow, at a rate of $250 per gpm. This program will be required for all projects in the BCD.

The baseline mitigation will also consist of contributions to the incremental sewer improvements on Niagara Falls Boulevard, the spine sewer construction on North Bailey Road, and improvements to handle excess wet weather flows at the advanced water pollution control facility. The projects and work are necessary to stabilize the sanitary sewers and create capacity in the Boulevard Mall development corridor as well as help to mitigate additional peak flow capacity issues at the treatment plant.

The baseline mitigation projects, along with developer share percentages, are as follows:

- I&I Removal
  - Requirement of new developments
  - Calculated at four times the peak flow, at a rate of $250 per gpm

- Niagara Falls Boulevard Sewer Rehab
  - Niagara Falls Blvd (Maple Road to 1641 Niagara Falls Boulevard), I-290 crossing, and Niagara Falls Blvd (Ridge Lea Road to Willowridge Drive), completed 2022-2024.
  - Approximately 2.1 MGD new peak flow in BCD sewersheds tributary to Chestnut Ridge Rd, with 4 MGD capacity
  - Private Share = $\frac{2.1\ MGD}{4\ MGD} = 53\%$

- Niagara Falls Boulevard Sewer Replacement
  - Replacement of 15" SS from 1641 Niagara Falls Boulevard to Ridge Lea Stub, completed 2023
  - Provides approximately 1 MGD capacity for BCD projects; pipe capacity is 2 MGD.
  - Private Share = $\frac{1\ MGD}{2\ MGD} = 50\%$

- Overflow (Relief Sewer) Rehab
  - Willowridge Drive (Niagara Falls Blvd to pump station), Chestnut Ridge Road (I-290 crossing to Chest Ridge replacement), and manhole rehabilitation
  - Approximately 2.1 MGD new peak flow in BCD sewersheds tributary to Chestnut Ridge Rd, with 4 MGD capacity
  - Private Share = $\frac{2.1\ MGD}{4\ MGD} = 53\%$

- Chestnut Ridge Sewer Replacement
  - Replacement of 310 linear feet of 24-inch with 30-inch sanitary sewer
  - Approximately 2.1 MGD new peak flow in BCD sewersheds tributary to Chestnut Ridge Rd, with 4 MGD capacity
  - Private Share = $\frac{2.1\ MGD}{4\ MGD} = 53\%$

- North Bailey 18-inch Spine Sewer
  - New 18-inch sewer from Boulevard Mall parcel to Ridge Lea Road, completed 2025.
  - Only required for redevelopment of Boulevard Mall district
  - Private Share = 100%

- AWPCF Improvements
  - Hydraulic Improvements to Clarifiers

- Approximately 3.5 MGD new peak flow in all BCD sewersheds, with 15 MGD capacity
- Private Share = $\frac{3.46\ MGD}{15\ MGD} = 23\%$

In addition to the baseline mitigation projects, one of the three alternatives will also need to be implemented, as presented below.

Alternative #1: Additional I&I Work to Reduce Wet Weather Flows

Under this alternative, the Town would collect sufficient mitigation funds to implement enough I&I improvements, in the form of rehabilitation of existing assets, to offset the 3.5 MGD of additional flow associated with the Projected Growth Redevelopment Scenario. Due to the unpredictable nature of I&I without detailed study, it is difficult to determine exactly how much rehabilitation work would be necessary to achieve this offset.

The Town's sanitary sewer consultant (GHD Engineering) evaluated the feasibility of this option and estimated a cost of approximately $49 million for lining, spot repairs, and bypass pumping on the publicly owned sewer system. In addition, additional rehabilitation work on the private side laterals would also be required, for an additional cost of up to $70 million. Therefore, this alternative was determined to be infeasible.

Alternative #2: Construction of a Replacement Parallel West Side Interceptor to Remove the West Side Interceptor Bottleneck

Under this alternative, the Town would construct a parallel West Side Interceptor from the Hartford Relief Sewer to Chestnut Ridge Road. GHD Engineering estimated that this alternative would cost $82 million. Although this alternative is likely to require less operations and maintenance when compared to a diversion pump station, the capital cost is unreasonable. Furthermore, the construction would be extremely complex due to the physical barriers (Maple Road, I-290) separating the upstream and downstream terminus points of the interceptor. Therefore, this alternative was determined to be infeasible.

Alternative #3: Construction of a pump station to divert flows from the West Side Interceptor to Another Interceptor with Spare Capacity

Under this alternative, the Town would construct a diversion pump station and forcemain to bypass the bottleneck in the West Side Interceptor. The forcemain would discharge to the underutilized Peanut Line Interceptor. The conceptual size of the pump station is estimated at 15 MGD, which would require a 24-inch diameter forcemain. The pump station would be used to actively manage the flows in the West Side Interceptor with the goal of minimizing the surcharge for wet weather events (anything larger than a 2-year, 6-hour storm). The preconstruction

estimate of this project is $36 million. This alternative was determined to be the most cost effective and feasible option.

Since the Projected Growth Redevelopment Scenario would add approximately 3.46 MGD of peak flow within a 15 MGD capacity pump station, the developer share cost of this alternative is 23%.

The Town was successful in obtaining a $31 million grant from the NYS Empire State Development. The remaining project cost is approximately $5 million; therefore, the private funded portion of the project is estimated to be $1.15 million.

***Mitigation Costs Summary***

The Sewer Mitigation Costs are shown in Table 3.2-7. The developer share of the Sewer Mitigation Costs are summarized using a cost per flow (gallon-per-day) basis. The growth under the Projected Growth Redevelopment Scenario would add approximately 0.93 MGD of sewer flow under average conditions, and 3.46 MGD under peak demand conditions (the calculated average peaking factor across all TAZ blocks is approximately 3.33).

The Mitigation Costs are calculated using the peak gallon per day flow, which is calculated according to the per-unit hydraulic loading rates provided in Table B-3 of the *New York State Design Standards for Intermediate Sized Wastewater Treatment Systems* (2014). The peaking factor is calculated from population in accordance with the Ten States Standards. It is noted that the I&I Removal is assessed by the Town at $250/gpm (at 4 times the peak flow); the Private Share cost for this item is determined from that rate in Table 3.2-7, which is used to determine the equivalent Mitigation Fee that is shown (of $0.69/gpd). The remainder of the Private Share costs are similarly determined by applying the Flow Proportional Share to the Capital Cost, and the mitigation fees are calculated by dividing the Private Share cost by the peak flow in gallons per day.

| Table 3.2-7: Baseline Sewer Mitigation Costs | | | | | |
|---|---|---|---|---|---|
| **Mitigation** | **Capital Cost** | **Flow Proportional Share** | **Mitigation Fee** | **Developer Share** | **Public Share** |
| I&I Removal | N/A | 100% | $0.69/gpd | $ 2,402,778 | N/A |
| NFB Sewer Rehab | $ 342,260 | 53% | $0.05/gpd | $ 181,398 | $ 160,862 |
| NFB Sewer Replacement | $ 404,000 | 50% | $0.06/gpd | $ 202,000 | $ 202,000 |
| Overflow (Relief Sewer) Rehab | $ 557,260 | 53% | $0.09/gpd | $ 295,348 | $ 261,912 |
| Chestnut Ridge Sewer Replacement | $ 950,000 | 100% | $0.27/gpd | $ 950,000 | N/A |
| North Bailey 18" Spine Sewer | $3,331,000 | 100% | $0.96/gpd | $ 3,331,000 | N/A |
| AWPCF Improvements | $5,000,000 | 23% | $0.33/gpd | $ 1,150,000 | $ 3,850,000 |
| West Side Interceptor Diversion PS and FM | $ 5,000,000 | 23% | $0.33/gpd | $ 1,150,000 | $ 3,850,000 |
| **Total** | **$16,185,214** | **-** | **$2.78/gpd** | **$ 7,860,440** | **$ 8,327,774** |

## Stormwater

The design of stormwater facilities for the proposed project must meet the requirements of the New York State DEC State Pollution Discharge Elimination System (SPDES), General Permit for Stormwater Discharges from Construction Activity (GP-0-24-001), and guidelines listed in the New York State Stormwater Management Design Manual (July 2024) or the General Permit manual in effect at the time of a proposed project. In accordance with the New York State DEC regulatory guidelines, new development and/or redevelopment projects with land disturbance of 1-acre or more shall not cause an increase in stormwater peak flows greater than the existing condition peak flows for the 1-, 10-, and 100-year 24-hour storm events. In addition, the proposed projects will be required to provide treatment water quality volume, minimum runoff reduction volume, and adequate stormwater drainage system to convey runoff to prevent flooding problems.

The Town of Amherst Stormwater Management Plan (March 2018) section 2.3 has identified Ellicott Creek and its tributaries as 303(d) impaired waterbodies for phosphorus and silt and sediment. The plan should include a requirement for new and/or redevelopment projects to

design post construction stormwater management practices to provide water quality volume calculated based on the 1-year, 24-hour storm (not the 90% rainfall) according to Chapter 10 of the NYS Stormwater Management Design Manual. This requires applicants to provide more water quality volume treatment for their proposed projects within the Study Area.

Furthermore, in order to help relieve the localized flooding problems, the Town of Amherst should also add more stringent requirements for new and/or re-development projects to achieve additional storage volume for post construction stormwater management. The Town should require applicants to meet one or more of the following requirements in the Town Stormwater Management Plan.

The following options will help increase the additional storage volume and help mitigate the existing localized flooding issues:

- Mitigate the proposed conditions peak flows to match the existing conditions peak flows with 10% escalation factor to account for climate change (according to Section 3.2.3.1 of the NYSDOT Bridge Manual (2017)).
- Use a median curve number (CN) value when computing the existing conditions runoff rates (i.e. use 50% runoff rate from existing land cover and 50% runoff rate from prior to any development such as woods or meadow).
- Mitigate all proposed stormwater runoff peak rates to match the existing 10-year storm peak including the proposed 100-year storm peak.

In accordance with the New York State DEC regulatory guidelines, new development and/or redevelopment projects will also be required to provide treatment for minumim runoff reduction volume (RRv) and evaluate the potential use of green infrastructure techniques and practices on site. Applicants must provide infiltration tests in accordance with Appendix D of the New York State Stormwater Management Design Manual. Soils test results will be reviewed and evaluated to idenitifly potential green infrastructure techniques such as those listed below. These stormwater management practices will also help reduce the amount of runoff needed for storage and help mitigate the existing drainage issues within the Study Area.

- Underground storage systems (with or without infiltration)
- Bioretention basins
- Rain gardens
- Dry or vegetated swales
- Green roofs (extensive or intensive)
- Porous pavement (or pavers)

The required green infrastructure techniques and practices will be determined by the Town of Amherst when it reviews specific development proposals. These techniques shall be incorporated in the Stormwater Pollution Prevention Plan (SWPPP) and any final design site plans.

### Energy & Communications Services

The results of this section have not changed since the original GEIS. It remains reasonable to conclude that given the developed conditions of the area, sufficient energy and communications services are available. Additionally, since these are private, for-profit providers, although regulated, future demand will likely warrant infrastructure and capacity improvements as necessary.

# 3.3 Unavoidable Adverse Impacts

In the process of evaluating the environmental impacts of projects, the extent to which the impacts can be mitigated through project design considerations or other specific actions may be limited or in some cases unavailable. This results in unavoidable impacts. Since beneficial impacts would typically not need to be mitigated, the focus of this section is on unavoidable adverse impacts. The primary mitigation for the cumulative impacts of growth is planning and coordination to ensure that the required services are in place and that specific studies are complete to address specific concerns. As a result, some unavoidable, site-specific adverse impacts will not be discovered until specific projects are evaluated. These impacts will be evaluated against the thresholds identified in the GEIS and Findings Statement to determine significance and whether or not additional evaluation through SEQR is warranted.

## 3.3.1 Transportation

The build condition for the 2025 Projected Growth Redevelopment Scenario will result in diminished conditions and the failure of various intersections and road segments. Mitigation measures have been identified that would improve intersection function and widen some road segments in order to return traffic movements to an acceptable level of service. These mitigation measures would occur over time as specific projects are proposed. In general, increased development leads to increased traffic that can cause delays and create a less desirable pedestrian environment. Significant efforts have been made to identify how the Study Area will grow and where, which led to a number of mitigation measures that when implemented should allow the road system to function well. The Town will continue to monitor growth/redevelopment to determine where resources should be used to prevent unavoidable adverse impacts. The potential future extension of the light rail system from Buffalo to UB could also create both concerns and opportunities and the progression of planning for this system will also be carefully monitored.

## 3.3.2 Utilities

The water and sewer demand for the 2025 Projected Growth Redevelopment Scenario has been identified along with the required improvements to the infrastructure that serves as the mitigation to provide adequate service. The 2025 Projected Growth Redevelopment Scenario will not be limited by the utilities. The unavoidable impact of the infrastructure improvements is the cost that must be borne by both the public and the development community. By distributing

these costs over all future development identified in this GEIS, the costs to individuals (taxpayers and developers) is fairly distributed and mitigated.

# SECTION 4.0

# ALTERNATIVES

Environmental Impact Statements (EIS) require the evaluation of a range of potential alternatives including an evaluation of a No Action alternative. The action addressed in this Supplemental SEQR process includes the modification/amendment of the Projected Growth Redevelopment Scenario to address some new realities and preferences in the commercial market in Amherst and particularly within the BCD. The primary alternatives evaluated in this section consider the different densities of development that can occur under the current mixed-use zoning.

The extension of the light rail system from Buffalo to the UB North Campus remains a potential future development scenario that may have some significant transportation implications. Since this proposal is still in the early planning stages, it was determined that it would not be included as a factor in the impact evaluation for the 2020 GEIS or this Supplemental GEIS. When/if this project moves forward, the environmental impacts related to the transit expansion project will need to be fully addressed during the SEQRA/NEPA review of that action.

## 4.1 Alternative 1: Maximum Build-Out Scenario

The Maximum Build-Out Scenario represents the maximum development potential of the Study Area under the Town's current commercial and mixed-use zoning. This is achieved by maximizing the number of blocks and the number of floors in each zone. Although there have been some revisions within the extent of the mixed-use zoning in the BCD since the 2020 GEIS, overall the buildout projections will be similar, at approximately 11 million gross square feet of commercial (retail and office) and nearly 38,000 residential units. This is a very significant amount of development that would take several decades to achieve and does not take into consideration development constraints that might be present within each block, including parking needs for the type of development.

It is difficult to predict what impacts this development scenario might impose upon the community and infrastructure. Certainly, without any improvements or planning for infrastructure there would be significant impacts on traffic, stormwater and localized flooding, sewer and water service, and a number of community services. What is unknown is if there are any constraints to the systems that would preclude this level of development. Another factor to consider is that technology, changes in transportation, availability of resources, and changing

land use patterns, as well as public opinion, could completely modify such development potential over this build-out period. To put this in perspective, comprehensive plans are typically reviewed on a 5-10-year basis and completely overhauled by year 20. This level of growth would be expected to exceed the 20-year planning horizon.

## 4.2 Alternative 2: High Growth 20-Year Redevelopment Scenario

Assuming the combination of incentives, attractiveness of the proposed land use, and demand for student housing spur a high rate of growth within the Study Area, approximately 5 million gross square feet of commercial space and 11,700 new residential units might be realized within 20 years. Based on current development trends and the pace of redevelopment within the BCD, this scenario is too aggressive and unlikely. When considering the traffic impacts and magnitude of mitigation for the 2024 Projected Growth Redevelopment Scenario, it is clear that a high growth scenario will not be an acceptable situation, at least as it can be envisioned today.

## 4.3 Alternative 3: 2020 Projected Growth Redevelopment Scenario

This alternative was chosen as the preferred redevelopment scenario for the Study Area in the 2020 BCD GEIS. It was found to be consistent with the growth projections identified by the Delta Economic Report (2016), resulting in 3 million gross square feet (gsf) of commercial and 5,000 new residential units over a 20-year planning period. The primary difference between this redevelopment growth scenario and the one presented in this SDGEIS is the percentage of office and commercial space, as detailed in SDGEIS Section 2.0 and as summarized in Section 4.4 below.

## 4.4 Alternative 4: 2025 Projected Growth Redevelopment Scenario

As discussed in SDGEIS Section 2.0, the cumulative effects of COVID, current development trends and developer preferences, and considerable planning efforts in the BCD since the adoption of the 2020 GEIS, have led to the re-evaluation of the BCD redevelopment potential both in terms of quantity (sf, units) of development and the type of development. The result was a significant reduction in anticipated office growth with a significant increase in retail development, but overall the commercial growth projection only changed by about 400,000 gsf for the next 20 years, dropping from approximately 3 million gsf to approximately 2.6 million gsf. Nevertheless, the shift from commercial to retail prompted the need to re-evaluate the potential cumulative impacts.

## 4.5 No-Action Alternative

The No-Action alternative differs significantly from that evaluated in the 2020 GEIS because at that time the Town elected to move forward with mixed-use zoning and implemented the GEIS. Therefore, the No-Action alternative would involve keeping the current zoning and land use

decisions as they are today. This alternative has been rejected by the Town for two important reasons. First, in some areas of the BCD the rezoned lands are inconsistent with the proposed redevelopment projects, requiring applicants to undergo rezoning for their projects to be approved. Rejecting these projects to remain consistent with the new zoning could delay redevelopment of these areas. The redevelopment plan evaluated in this SDGEIS is consistent with current development trends and will facilitate redevelopment of the BCD. Second, the development projections for office and retail under the 2020 GEIS appear to be significantly inconsistent with current trends and the result could be unintended increases in impacts to infrastructure not presently accounted for in the GEIS.

# SECTION 5.0

# IRREVERSIBLE & IRRETRIEVABLE COMMITMENT OF RESOURCES

Development of the 2025 Projected Growth Redevelopment Scenario would result in the irreversible and irretrievable commitment of a variety of resources.

Construction of structures, related site improvements and infrastructure would require the consumption of building materials, equipment, energy, and human resources. These resources would be consumed during construction and operation. Based on previous and on-going development within the vicinity of the Study Area, it is assumed that sufficient construction materials, equipment and labor force is available to satisfy the demands of the 2025 Projected Growth Redevelopment Scenario, especially over the 20-year planning period. The availability of utilities (such as sewer, water, electricity, and natural gas) also appears to be sufficient to support the development potential with some capital improvements. Municipal services, such as solid waste disposal, police, and emergency services would also be required and can be more sensitive to significant changes over a short period of time. However, it is anticipated that the projected timeframe for development will be sufficient to adequately plan for these services.

This project will have a significant beneficial impact on land and environmental/ecological resources by focusing development and reinvestment within previously developed and underutilized land within the Town of Amherst. In any given year, only a certain amount of growth will occur town-wide. By encouraging and facilitating this growth within areas designated for redevelopment, there will be increased support of the Town tax base by increasing the value of these properties, more opportunities for jobs and economic growth, additional housing opportunities, and less pressure on undeveloped areas of the Town.

# SECTION 6.0

# USE AND CONSERVATION OF ENERGY

Any construction related to redevelopment within the Study Area will be required to conform to the New York State (NYS) Building Construction Code and applicable sections of the NYS Energy Conservation Construction Code. As specific projects move forward, specific methods to reduce and conserve energy consumption will be evaluated in more detail. Green building design, construction, operations, and maintenance measures will be considered and implemented as practicable in each redevelopment plan.

During construction and installation activities, Best Management Practices will be required such as:

- Limiting the idling of equipment and vehicles.
- Use of more energy-efficient equipment during construction and maintenance
- Continued regular inspection and maintenance of construction equipment.
- Construction scheduling to allow for efficient installation of project components and reduced down time between tasks or phases.

Internal circulation, including roadways and sidewalks, will be designed to provide efficient connections between the various site elements and promote a highly walkable area.

As required under the mixed-use zoning, the installation of electric vehicle charging stations will encourage the use of energy efficient electric cars. The number and location will be based on the specific projects proposed including site and parking demand, as well as any available information regarding numbers of electric vehicles in use in Western NY. Nearby public transportation, including NFTA buses and the potential future light rail extension from Buffalo, can all work together to reduce the use of fossil fuels.

The use of rooftop solar arrays would reduce the consumption of non-renewable energy for heating, cooling and electricity.

The use of landscaping to shade parking areas and sidewalks will reduce the “heat island effect” that results from large, paved areas.

The NYS Energy Conservation code addresses elements such as heating and cooling systems, hot water systems, electrical systems, construction material, equipment specifications and building sealing and insulation. Energy Star and New York Energy Smart programs encourage the use of energy conserving appliances, materials, technologies and building techniques and would reduce the overall long- term energy consumption of projects within the Study Area.

In general, by focusing and facilitating redevelopment of the BCD there will be significant energy savings for the Town by concentrating development in a previously developed area that is served by public transportation, is a hub for retail development, supports an existing residential community and offers opportunities for highly desired higher density multi-family development within a mixed-use area. This approach will result in new construction providing modern, energy efficient buildings, located near a major university with the potential for future transit linkages between destinations within the BCD and to other areas of the Town.

# SECTION 7.0

# FUTURE SEQR ACTIONS

Each project proposed for the Study Area will be evaluated against the thresholds and recommendations included in this Supplemental GEIS and the Findings Statement to determine if further SEQR action is required. The Findings and the details of studies provided in the Draft and Final Supplemental GEIS documents will provide guidance for evaluating consistency with SEQR. These are the development guidelines for future development in the Study Area and will be readily available to the public and the development community.

When projects in the Study Area are submitted to the Town and determined to be subject to SEQR, the Planning Department will review the Environmental Assessment Form (EAF) and the Town's GEIS Compliance Checklist to determine consistency with, or deviation from, the GEIS and the Findings Statement. If the impact thresholds identified in this GEIS are exceeded, the action may require further review under SEQR. For example, an action that is inconsistent with the zoning and the intended land use pattern for the Study Area would be subject to further SEQR review. In other cases, adoption of a Negative Declaration (determination of no significant adverse impact) may be sufficient to satisfy SEQR requirements. This determination must be made by the Town prior to the issuance of any discretionary land use approvals for the proposed development.

The following scenarios put forth in Section 617.10(c) & (d) of the SEQR regulations summarize the mechanism for reviewing future actions:

A. If the Town determines that the proposed action is in conformance with the conditions and thresholds in the Final SGEIS or the Findings Statement, then no further environmental review pursuant to SEQR will be required;

B. If the Town determines that the proposed action is adequately addressed in the Final SGEIS, but is not addressed or not adequately addressed in the Findings Statement, then an amended Findings Statement must be prepared;

C. If the Town determines that the proposed action was not addressed, or was not adequately addressed, in the Final SGEIS, but it will not result in any significant environmental impacts, then a negative declaration must be prepared; or

D. If the Town determines that the proposed action was not addressed, or was not adequately addressed, in the Final SGEIS, and the action may have one or more significant adverse environmental impacts, then a supplement to the Final SGEIS must be prepared.

# SECTION 8.0

# REFERENCES

US Census Bureau. "American Community Survey (ACS)". May 14, 2019. https://www.census.gov/programs-surveys/acs (2017 data).

Erie County Office of GIS. Fire District Data, July 2019.

Greater Buffalo Niagara Regional Transportation Council. "Census Tract Traffic Analysis Zones Data 2015 and 2050". https://www.gbnrtc.org/.

Greater Buffalo Niagara Regional Transportation Council. GBNRTC Online Bicycle Map: GBNRTC Online Bicycle Map

Highway Capacity Manual, 6th Edition, Transportation Research Board, 2016.

Highway Capacity Manual, 7th Edition, Transportation Research Board, 2022.

Intensive Level Historic Resources Survey of Selected Resources in the Town of Amherst, September 2017. Prepared for Town of Amherst Historic Preservation Commission by Clinton Brown Company Architecture, PC. https://www.amherst.ny.us/pdf/committees/additional/historic/2017_intensive_level_survey/220211_01_cover.pdf

National Cooperative Highway Research Program Report 765: Analytical Travel Forecasting Approaches for Project-level Planning and Design, Transportation Research Board, 2014.

New York State Department of Environmental Conservation, Division of Water. "New York State Design Standards for Intermediate Sized Wastewater Treatment Systems". March 5, 2014.

New York State Department of Transportation. CLEAR Crash Data Viewer: NYSDOT CLEAR Crash Data Viewer

New York State Department of Transportation. Roadway Functional Classification: https://www.dot.ny.gov/gisapps/functional-class-maps.

New York State Department of Transportation, Safety Program Management and Coordination Bureau. https://www.dot.ny.gov/divisions/operating/osss/highway/accident-rates.

New York State Department of Transportation. Traffic Data Viewer: https://www.dot.ny.gov/tdv.

New York State Office of Parks, Recreation and Historic Preservation, Historic Preservation Office Cultural Resource Information System, https://cris.parks.ny.gov/, July 2019.

Niagara Frontier Transportation Authority. "Amherst-Buffalo Corridor Light Rail Extension, Traffic Analysis Methodology". July 2, 2018.

Niagara Frontier Transportation Authority. Metro System Interactive Map: Winter 2025 System Map - Remix

Town of Amherst Bicentennial Comprehensive Plan prepared by Wallace Roberts & Todd, LLC, and URS Corporation and Economic Research Associates. December 11, 2017.

Town of Amherst Recreation and Parks Master Plan, April 2018. Prepared by Green play LLC, Weston & Sampson and RRC Associates. (Accessed April 17, 2024). https://www.amherst.ny.us/pdf/youthrec/180608_parks_rec_master_plan.pdf

United States Department of Housing and Urban Development, Office of Policy Development and Research. *Comprehensive Housing Market Analysis. Buffalo-Cheektowaga-Niagara Falls, New York.* July 1, 2017.

United States Department of Transportation, Program and Organizational Transportation Systems Center Research and Innovative Technology Administration. "FHWA Scenario Planning Guidebook, 2011", prepared for Office of Planning Federal Highway Administration.

United States Department of Agriculture, Natural Resources Conservation Service. Web Soil Survey "Hydrologic Soil Groups-Erie County, New York". July 2, 2019. https://websoilsurvey.sc.egov.usda.gov/App/WebSoilSurvey.aspx

Town of Amherst Stormwater Plan. Town of Amherst Engineering Department. March 2018 (Accessed April 17, 2024). https://www.amherst.ny.us/pdf/engineering/environmental/180611_stormwater_plan_2018.pdf

Town of Amherst Economic Study. Amherst, NY November 9, 2016. Prepared by Delta Associates. https://www.amherst.ny.us/pdf/planning/161109_economic_study.pdf

Town of Amherst Code. Accessed May 8, 2024. https://ecode360.com/AM0003#13385536

Town of Amherst Mixed Use Zoning, Adopted September 3, 2019. (Accessed April 17, 2024). https://www.amherst.ny.us/pdf/planning/compplan/zcrc/191002_zoning_mixed_use_code_adopted.pdf

Town of Amherst and Erie County GIS Data. Parcel, Building Footprint and Geospatial Data Information. Received from Erie County November 2021.

Town of Amherst Planning Department. Growth Projections. June 19, 2019. (Revised April/May 2024)

Town of Amherst. *Strategic Economic Development Plan Amherst, NY*. September 2023. Prepared for the Town of Amherst. Prepared by RKG Associates, Inc. https://share.amherst.ny.us/docman/doc_files_list.php?hash=exeytk2elq529idesboe46nxe

Sustainable Cities and Society. Volume 75, December 2021, 103356. Space Ratio: A Measure of Density Potentials in the Built Environment. Liam Thomas Bolton. Accessed January 30, 2024. https://www.sciencedirect.com/science/article/abs/pii/S2210670721006314?via%3Dihub

1. American Planning Association. *PAS Report 111.* Accessed February 28, 2024. *https://www.planning.org/pas/reports/report111.htm*.

Internal Revenue Service. Opportunity Zones**.** IRS Website. Accessed February 29, 2024. *https://www.irs.gov/credits-deductions/businesses/opportunity-zones#:~:text=Opportunity%20Zones%20are%20an%20economic,providing%20tax%20benefits%20to%20investors*.

Town of Newbury. *Floor Area Ratio and Lot Coverage Compliance Checklist*. Accessed February 29, 2024. *https://www.townofnewbury.org/sites/g/files/vyhlif951/f/uploads/far_lot_cov_checklist_0.pdf*

EASI. Transportation Analysis Zones. Accessed February 29, 2024. https://www.easidemographics.com/trshelp/html/traffic_analysis_zone.htm#:~:text=A%20traffic%20analysis%20zone%20(TAZ,block%20groups%2C%20or%20census%20tracts.

Town of Amherst. *Town of Amherst Boulevard Central District Modernizing Planning and Zoning in Amherst's Major Commercial Corridor Statement of Findings Draft and Final Generic Environmental Impact Statement*. Prepared by CHA. Adopted by the Town Board January 6, 2020. (Accessed April 17, 2024). https://www.amherst.ny.us/content/projects.php?dept_id=dept_15&proj_id=proj_08&neworder=02

Town of Amherst, NY. *Boulevard Central District Action Plan Town of Amherst, NY. June 3, 2021*. Prepared by Dover, Kohl & Partners, town planning with Nelson Nygaard Consulting Associates. Accessed April 17, 2024. https://www.amherst.ny.us/pdf/planning/bcd/210726_final_bcd_action_plan.pdf

Time Saver Standards for Landscape Architecture. Design and Construction Data. Second Edition. 1998. Prepared by Charles W. Harris and Nicholas T. Dines.

American Planning Association. Planning and Urban Design Standards. 2006. Prepared/Published by John Wiley & Sons, Inc.

American Planning Association. *People Over Parking.* Accessed May 8, 2024. https://www.planning.org/planning/2018/oct/peopleoverparking/.

PAS Report 214. *Parking in Residential Areas*. Prepared by Gail Ornstein. September 1966. Accessed May 8, 2024. https://www.planning.org/pas/reports/report214.htm.

Franklin Street. Commercial Real Estate, Capital Insurance, Leasing and Management. https://franklinst.com/how-large-is-a-parking-space/

Janover Commercial Real Estate Loans. *Parking Ratio in Commercial Real Estate*. Accessed May 8, 2024. https://www.commercialrealestate.loans/commercial-real-estate-glossary/parking-ratio/

CBRE Upstate NY. Data https://www.cbre.com/offices/affiliates/upstate-new-york

Newmark. Hybrid Workspace Strategies. *Hybrid Workplace Models: Establishing the Future for the Office.* March 10, 2021. https://www.nmrk.com/perspectives/category/hybrid-workplace-strategies

Town of Colonie Final Generic Environment Impact Statement Airport Area. Prepared by Clough, Harbour & Associates Engineers & Planners. February 1991.

# APPENDIX A

## SEQR DOCUMENTATION

LEAD AGENCY RESOLUTION

**Amherst Town Board**
5583 Main Street
Williamsville, NY 14221
**www.amherst.ny.us**

Francina J. Spoth
Town Clerk

Meeting: 05/11/26 03:00 PM
Department: Planning
Initiated by: **Dan Howard**
Co-Sponsored by:

DOC ID: 31844 **RESOLUTION 2026-417** **ADOPTED**

# Boulevard Central District Supplemental Generic Environmental Impact Statement (Bcd Sgeis)

Purpose: Re-establishment of SEQR Lead Agency and Preparation of a Supplemental Generic Environmental Impact Statement (SGEIS)

**WHEREAS,** the Town Board previously assumed Lead Agency status pursuant to the State Environmental Quality Review Act (SEQRA) for the preparation of a Generic Environmental Impact Statement (GEIS) for the Boulevard Central District (BCD), and following public review, adopted a Statement of Findings pursuant to 6 NYCRR Part 617.11 of SEQR on January 6, 2020; and

**WHEREAS,** subsequent to the adoption of the GEIS, the Town Board determined that changes in development conditions, new information, and/or proposed modifications to the original action warrant the preparation of a Supplemental Generic Environmental Impact Statement (SGEIS) in accordance with 6 NYCRR §617.9(a)(7); and

**WHEREAS,** the Town Board desires to re-establish itself as Lead Agency for the environmental review of the proposed supplemental action to ensure a coordinated and comprehensive review under SEQRA; and

**WHEREAS,** the Town Board has identified all involved and interested agencies and has provided notice of its intent to serve again as Lead Agency; and

**WHEREAS**, no other involved agency has objected to the Town Board serving again as Lead Agency;

**NOW, THEREFORE, BE IT RESOLVED,** that the Town Board hereby re-establishes itself as Lead Agency for the purposes of conducting a coordinated environmental review of the preparation of a SGEIS pursuant to SEQRA; and

**BE IT FURTHER RESOLVED**, that the Town Board directs that the SGEIS be prepared by the Planning Department in accordance with the requirements of 6 NYCRR Part 617, including but not limited to public review and consideration of environmental impacts, alternatives, and mitigation measures.

**5/11/2026**
A motion to approve was made by Supervisor Lavin, seconded by Councilmember Davis and unanimously approved 5-0.

**FINANCIAL IMPACT:**

None

| | |
|---|---|
| **RESULT:** | **ADOPTED [UNANIMOUS]** |
| **MOVER:** | Shawn Lavin, Supervisor |
| **SECONDER:** | John B. Davis, Councilmember |
| **AYES:** | Lavin, Marinucci, Szukala, Davis, Kavanaugh |

Amherst

*Town of Amherst Planning Department* *Erie County, New York*

Shawn A. Lavin
Supervisor

Daniel C. Howard, A
Planning Directo

Daniel J. Ulatowski, A
Assistant Planning Dir

# MEMORANDUM

**TO:** Honorable Town Board

**FROM:** Daniel C. Howard, AICP, Planning Director DCH

**DATE:** May 6, 2026

**SUBJECT:** Boulevard Central District Supplemental Generic Environmental Impact Statement (BCD SGEIS)

Honorable Members:

The Town's current Boulevard Central District (BCD) Generic Environmental Impact Statement (GEIS) was prepared in late 2019 and adopted in January 2020, over five years ago. The intent of the BCD GEIS was to reimagine and redevelop the Town's larger commercial area in a comprehensive manner by encouraging mixed-use development and increased density, maximizing economic investment and tax revenue, improving vehicular and pedestrian mobility and safety, investing in aged infrastructure systems, and protecting and enhancing surrounding residential neighborhoods.

The GEIS was an environmental analysis prepared under the State Environmental Quality Review (SEQR) process that identified broad environmental impacts and mitigation measures associated with plans, programs or multiple actions in a geographic area. It is an effective tool to plan for future growth as it addresses impacts on both the natural and built environment, providing the opportunity to mitigate these impacts through good planning, capital improvement plans, and more equitable distribution of costs.

The BCD GEIS Study Area is bounded generally by Niagara Falls Boulevard on the west, the Interstate 290 (I-290) on the north and east, and Sheridan Drive properties immediately south of Sheridan Drive to the south. It includes a mix of commercial, retail, office and residential uses. There are few undeveloped properties and while the residential component consists of established and stable neighborhoods, many of the non-residential properties could benefit from reinvestment and redevelopment.

The GEIS may be supplemented or updated pursuant to 6 NYCRR Part 617.10(d) of SEQR which states *"Generic EISs and their findings should set forth specific conditions of criteria under which future actions will be undertaken or approved, including requirements for any subsequent SEQR compliance. This may include thresholds and criteria for supplemental EISs to reflect specific significant impacts, such as site-specific impacts, that were not adequately addressed or analyzed in the generic EIS."*

Attachment: TB Memo - SGEIS (RES-2026-417 : Bcd Sgeis)

A variety of changes have occurred over the past several years that signal a need to reevaluate the GEIS and the initial assumptions made to better inform land use and zoning projections of future development, its associated impacts, and corresponding mitigation costs. The Town has reviewed the original methodology, factors and assumptions and determined that these have changed to a degree that warrants a Supplemental GEIS (SGEIS) with new demographic projections and land use growth assumptions. Changes in impacts to utility and transportation systems along with their related mitigation projects are also being examined.

The Town Board acted as Lead Agency under SEQR for the original GEIS, and should appropriately act again as Lead Agency for the SGEIS. The Planning Department has identified all involved and interested agencies and has provided notice of its intent to serve again as Lead Agency. A coordinated review process resulted in no objections from other agencies in this regard. The attached resolution re-establishes the Town as Lead Agency and directs the Planning Department to prepare the SGEIS in accordance with the requirements of 6 NYCRR Part 617 of SEQR.

Please contact me with any questions or concerns.

Attachment: TB Memo - SGEIS (RES-2026-417 : Bcd Sgeis)

*X:\Special_Projects\Boulevard Central District\GEIS\GEIS Supplemental 2026\Town Board Materials\TB Memo - SGEIS Lead Agency 5-11-26.docx*

# APPENDIX B

## LAND USE AND ZONING

MIXED-USE SITE PLAN PRECEDENTS.....AB-2
TOWN LAND USE ANALYSIS NOTES.....AB-31
GROWTH PROJECTIONS SUMMARY TABLE BY TAZ.....AB-39
DEMOGRAPHIC PROJECTIONS CHART.....AB-47
MAP B1 – PERCENTAGE OF NEW RESIDENTIAL.....AB-48
MAP B2 – PERCENTAGE OF NEW RETAIL.....AB-49
MAP B3 – PERCENTAGE OF NEW OFFICE.....AB-50

# APPENDIX B


**MIXED-USE SITE PLAN PRECEDENTS**


# Mixed-Use Site Plan Precedents

| ADDRESS | ZONING | ACREAGE | BUILDING COVERAGE | USES & PERCENTAGES |
|---|---|---|---|---|
| 5226 & 5228 Main Street (proposed) | TI-4 | 1.1 acres<br>47,916 sq. ft. | 10,930 sq. ft.<br>0.25 acres<br>22.8% | 10,930 sq. ft. or 24.6% commercial<br>33,504 sq. ft. or 75.4% residential |
| 1720, 1740 & 1760 Maple Road (to be constructed) | DC-5 | 5.18 acres<br>225,640.8 sq. ft. | 51,889.2 sq. ft.<br>1.19 acres<br>23% | 9,715 sq. ft. or 17.7% commercial<br>45,145 sq. ft. or 82.3% residential |
| 6812, 6814 & 6832 Main Street and 29 & 37 Tennyson Ter (proposed) | GB & MFR-5 | 2.23 acres<br>97,138.8 sq. ft. | 17,772 sq. ft.<br>0.41 acres<br>18.3% | 13,500 sq. ft. or 21% commercial<br>49,379 sq. ft. or 79% residential |
| 6770-6790 Main Street | GB, R-3 & MFR-5 | 2.6 acres<br>113,256 sq. ft. | 22,370 sq. ft.<br>0.51 acres<br>19.8% | 18,770 sq. ft. or 37.2% office<br>31,640 sq. ft. or 62.8% residential |
| 6842 & 6846 Main Street (in construction) | DC-5 | 2.58 acres<br>112,384.8 sq. ft. | 31,301.8 sq. ft.<br>0.72 acres<br>27.9% | 6,876 sq. ft. or 8.4% commercial (4.2% office)<br>75,124 sq. ft. or 91.6% residential |
| 5949 & 5951 Main Street and 21 Richfield Rd | GB & R-3 (MU Village) | 1.68 acres<br>73,180.8 sq. ft | 20,640 sq. ft.<br>0.47 acres<br>28.2% | 18,600 sq. ft. or 33.3% commercial<br>37,200 sq. ft. or 66.6% residential |
| 5877 Main Street (Village) (in construction) | MU (Village) | 1.63 acres<br>71,002.8 sq. ft. | 15,000 sq. ft.<br>0.34 acres<br>21.1% | 15,000 sq. ft. or 25% commercial<br>45,000 sq. ft. or 75% residential |
| 4548-4564 Main Street & 17 Fruehauf Ave & 22 Chateau Terrace (in construction) | TI-2.5 | 0.93 acres<br>40,510.8 sq. ft. | 12,000 sq. ft.<br>0.28 acres<br>29.6% | 6,657 sq. ft. or 10.6% commercial<br>56,204 sq. ft. or 89.4% residential |
| 315 Campbell Blvd | NB | 2.25 acres<br>98,010 sq. ft. | 19,120.4 sq. ft.<br>0.44 acres<br>19.5% | 2,200 sq. ft. or 5.8% commercial<br>35,821 sq. ft. or 94.2% residential |
| 1185 Sweet Home Road | GB, MFR-6 and NCD-LC | 12.9 acres<br>561,924 sq. ft. | 46,500 sq. ft.<br>1.1 acres<br>8.2%<br>*just MU buildings | 10,454 sq. ft. or 4.4% commercial<br>226,906 sq. ft. or 95.6% residential |


## 5226 & 5228 Main Street (SP-2023-14) (proposed)

- Zoned TI-4
- 1.1 acres = 47,916 sq. ft.
  - **Building coverage on site = 10,930 sq. ft. or 0.25 acres or 22.8%**
- 1 building, 4 stories
  - 1st floor commercial – 10,930 sq. ft. (50% restaurant, 50% retail)
  - 2nd – 4th floors of residential
    - 10 apartments per floor (3 floors) = 30 apartments
    - 11,168 sq. ft. per floor (3 floors) = 33,504 sq. ft.
- **TOTAL SQUARE FOOTAGE: 44,434 sq. ft.**
  - **10,930 sq. ft. or 24.6% commercial**
  - **33,504 sq. ft. or 75.4% residential**







2nd - 4th Floors





1st Floor

## 1720, 1740 & 1760 Maple Road (SP-2023-06) (to be constructed)


- Zoned DC-5
- 5.18 acres (1720 (0.92 acres), 1740 (0.16 acres) & 1760 (4.1 acres)) = 225,640.8 sq. ft.
    - **Building coverage on site (all buildings) = 21,205 + 13,715 + 6,609.6 + 6,609.6 + 4,830 = 51,889.2 sq. ft. or 1.19 acres or 23%**
- 6 buildings
    - Building #1 – 4 story residential
        - 75 units, 84,820 sq. ft.
    - **Building #2 – 4 story mixed-use**
        - **1st floor commercial**
        - **32 units, 54,860 sq. ft.**
    - Building #3 – 2 story townhomes with attached garages
        - 5 units
    - Building #4 – 2 story townhomes with attached garages
        - 6 units, approximately 12,139.2 sq. ft.
    - Buildings #5 & #6 – Garages A & B
        - 20 total spaces (10 spaces each), 4,830 sq. ft. (2,415 sq. ft. each)
- **TOTAL SQUARE FOOTAGE OF BUILDING #2 (Mixed-Use): 54,860 sq. ft.**
    - **9,715 sq. ft. or 17.7% commercial**
    - **45,145 sq. ft. or 82.3% residential**


CORE STREET
LOCAL STREET
BUILDING #1
PROPOSED 4-STORY RESIDENTIAL
75-UNIT BLDG.
(84,820 GSF)
BUILDING #2
PROPOSED 4-STORY MIXED USE
32-UNIT BLDG.
(54,860 GSF)
PROPOSED 2-STORY TOWNHOUSE 'A'
W/ ATTACHED GARAGES
(5 UNITS)
PROPOSED 2-STORY TOWNHOUSE 'B'
W/ ATTACHED GARAGES
(6 UNITS)
GARAGE A (10 SPACES)
GARAGE B (10 SPACES)
GARAGE C (10 SPACES)
STORMWATER MANAGEMENT AREA
OUTDOOR AMENITY SPACE (0.15 AC.)
OUTDOOR AMENITY SPACE (0.11 AC.)
BENCH
A/C UNITS, TYP.
PATIO, TYP.
EXIST TREE PIT, TYP.
15" SANITARY SEWER EASEMENT TO THE TOWN OF AMHERST PER LIBER 6852 DEEDS P.262
EXCEPTION PER LIBER 7437 DEEDS PAGE 592
EXCEPTION PER LIBER 7327 DEEDS PAGE 371
EXCEPTION TO ERIE COUNTY PER LIBER 7350 DEEDS PAGE 457
FORMER NORTH LINE OF ROAD AS 66' WIDE ROAD
TOPSOIL AND SEED AREAS OF REMOVED CURB CUT/PAVEMENT, TYP.
CURB FLUSH WITH EX. PAVEMENT, CURB GRADUALLY TAPERS 1 INCH
OFFSET CURB TO AVOID EX. DRAINAGE STRUCTURE
560'
710.34'
269.29'
579.52'
100' DEED
100.18' MEAS.
135.00'
105.00'
700.00'
5.0'
FLARE, TYP.
8 SPACES
16 SPACES
Blacktop

**BUILDING #2 FLOOR PLANS**





1 A-101 Level 1 - Floor Plan
1/8" = 1'-0"






1 A-102 Second Floor Plan
1/8" = 1'-0"


## 6812, 6814 & 6832 Main Street and 29 & 37 Tennyson Ter (SP-2024-03) (proposed)

- Zoned GB & MFR-5
- 2.23 acres (6812 (0.28 acres), 6814 (0.44 acres), 6832 (0.41 acres), 29 (0.63 acres) 37 (0.47 acres) = 97,138.8 sq. ft.
  - **Building coverage on site = 17,772 sq. ft. or 0.41 acres or 18.3%**
- 3 buildings (total 67,151 sq. ft.)
  - **Building #1 - 4/5 story mixed-use**
    - **14,748 sq. ft. footprint**
    - **1st floor - 13,500 sq. ft. commercial (29% office, 37% retail, 33% restaurant)**
    - **2nd – 5th floors – 49,379 sq. ft. residential (34 units)**
  - Buildings #2 & #3 – Garages A & B
    - 12 total spaces (6 spaces each), 3,024 sq. ft. (1,512 sq. ft. each)
- **TOTAL SQUARE FOOTAGE OF BUILDING #1 (Mixed-Use): 64,127 sq. ft.**
  - **13,500 sq. ft. or 21% commercial**
  - **49,379 sq. ft. or 79% residential**











## 6770-6790 Main Street (SP-2017-18B)


- Zoned GB, R-3 and MFR-5
- 2.6 acres (6770 (0.6 acres), 6790 (2 acres)) = 113,256 sq. ft.
    - **Building coverage on site = 22,370 sq. ft. or 0.51 acres or 19.8%**
- 5 buildings
    - **Building #1 (6790 Main) – 2/3 story mixed-use (29,665 sq. ft.)**
        - **1st floor – 11,855 sq. ft. office**
        - **2nd floor – 11,712 sq. ft. residential (8 units)**
        - **3rd floor – 6,098 sq. ft. residential (4 units)**
    - **Building #2 (6770 Main) – 3 story mixed-use (20,745 sq. ft.)**
        - **1st floor – 6,915 sq. ft. office**
        - **2nd floor – 6,915 sq. ft. residential (6 units)**
        - **3rd floor – 6,915 sq. ft. residential (6 units)**
    - Buildings #3, #4 & #5 – Garages
        - 15 total spaces (5 spaces in 3 buildings), 3,600 sq. ft. (1,200 sq. ft. each)
- **TOTAL SQUARE FOOTAGE OF BUILDINGS #1 & #2 (Mixed-Use): 50,410 sq. ft.**
    - **18,770 sq. ft. or 37.2% office**
    - **31,640 sq. ft. or 62.8% residential**



33 CAESAR BOULEVARD
(ZONED R-3)
220.00'
PROPOSED GARAGE
(5) 11' x 20' UNITS
PROPOSED GARAGE
(5) 12' x 20' UNITS
PROPOSED GARAGE
(5) 12' x 20' UNITS
MFR-5
GB
R-3
GB
CAESAR BOULEVARD
(60' WIDE)
TENNYSON TERRACE
(50' WIDE)
6770 MAIN STREET
3-STORY MIXED USE BUILDING
1ST FLOOR - RETAIL
2ND & 3RD FLOOR - RESIDENTIAL
AT-GRADE
CONCRETE
PATIO
6790 MAIN STREET
2-STORY MIXED USE BUILDING
1ST FLOOR - RETAIL
2ND FLOOR - RESIDENTIAL
3-STORY MIXED USE BUILDING
1ST FLOOR - RETAIL
2ND & 3RD FLOOR - RESIDENTIAL
MAIN STREET
(99' WIDE)

## 6842 & 6846 Main Street (SP-2021-27) (in construction)


- Zoned DC-5
- 2.58 acres = 112,384.8 sq. ft.
    - **Building coverage on site = 31,301.8 sq. ft. or 0.72 acres or 27.9%**
- 4 buildings
    - **Building #1 - 4 story mixed-use**
        - **20,500 sq. ft. footprint**
        - **1st floor – 6,876 sq. ft. commercial (3,436 sq. ft. retail, 3,436 office), 14 units (13,624 sq. ft.)**
        - **2nd – 3th floors – 41,000 sq. ft. residential (32 units, 16 per floor, 20,500 sq. ft. per floor)**
        - **4th floor – 15 units, 20,500 sq. ft.**
    - Building #2 – 2 story townhomes with attached garages
        - 6 units, 12,716 sq. ft. (6,358 sq. ft. each floor)
    - Building #3 & #4 – Garages
        - 19 total spaces (10 spaces in one (2,356.8 sq. ft.), 9 spaces in other (2,087 sq. ft.)), 4,443.8 sq. ft. total
- **TOTAL SQUARE FOOTAGE OF BUILDING #1 (Mixed-Use): 82,000 sq. ft.**
    - **6,876 sq. ft. or 8.4% commercial (4.2% office)**
    - **75,124 sq. ft. or 91.6% residential**


MAIN (90' WIDE) STREET (N.Y.S. ROUTE 5)
RPZ ENCLOSURE
LIMIT OF VINYL FENCE
PROPOSED GROUND SIGN
TWO-WAY ACCESS
TWO-WAY ACCESS
OUTDOOR AMENITY SPACE (0.1± AC)
GATE
10 CAR GARAGE 113.58'
9 CAR GARAGE 100.58'
A/C UNIT, TYP.
COVERED PATIO, TYP.
PROPOSED 2-STORY TOWNHOUSES W/ ATTACHED GARAGES (6 UNITS)
LIMIT OF VINYL FENCE
FUTURE ROAD CONNECTION
EV PARKING
5' PEDESTRIAN ZONE
6' CURB ZONE
5'x6' TREE PIT, TYP.
PATIO, TYP.
PROPOSED 4-STORY MIXED USE BUILDING
20,500± GSF FOOTPRINT
1ST FLOOR (6,872± SF COMMERCIAL, 14 APTS)
2ND - 3RD FLOORS (16 APTS/FLR)
4TH FLOOR (15 APTS)
1ST FLOOR COMMERCIAL
PATIO, TYP.
6846 MAIN STREET ZONED GB
6848 MAIN STREET ZONED GB
0 MAIN STREET ZONED GB
7300 TRANSIT ROAD ZONED GB
7350 TRANSIT RD ZONED GB
EX. DUMPSTER TO BE RELOCATED TO PROPOSED DUMPSTER ENCLOSURE
TWO-WAY ACCESS DRIVEWAY CONNECTION
OUTDOOR AMENITY SPACE (0.08± AC)
TWO-WAY EMERGENCY ACCESS DRIVEWAY CONNECTION
RELOCATE EX. BANK SIGN, COORD. WITH OWNER
EX. SANITARY SEWER EASEMENT TO TOWN OF AMHERST



Retail
114
Lobby
113
Vestibule
112
Elec.
116
Stair B
115
Unit Type 4
111
Unit Type 2
110
Unit Type 3
109
Unit Type 2
108
Unit Type 9
107
Unit Type 6
104
Unit Type 7
103
Unit Type 3
102
Unit Type 2
101
Unit Type 9
100
Corridor
106
Level 1 - Floor Plan
1
A-101
3/32" = 1'-0"




Level 2 - Floor Plan




1 A-104 Level 4 - Floor Plan
3/32" = 1'-0"





1 A-101 T Level 1
1/8" = 1'-0"

N

## 5949 & 5951 Main Street and 21 Richfield Rd (SP-2014-15)


- Zoned GB & R-3 (and MU Village zoning)
- 1.68 acres = 73,180.8 sq. ft.
    - **Building coverage on site = 20,640 sq. ft. or 0.47 acres or 28.2%**
- 2 buildings
    - **Building #1 - 3 story mixed-use**
        - **1st floor – 18,600 sq. ft. commercial**
        - **2nd & 3rd floors – 37,200 sq. ft. residential (20 units)**
    - Building #2 – Garages
        - 8 spaces, 2,040 sq. ft.
- **TOTAL SQUARE FOOTAGE OF BUILDING #1 (Mixed-Use): 55,800 sq. ft.**
    - **18,600 sq. ft. or 33.3% commercial**
    - **37,200 sq. ft. or 66.6% residential**




Apartment 1
1052 sqft
Apartment 2
1401 sqft
Apartment 3
1401 sqft
Apartment 4
1550 sqft
Apartment 5
1212 sqft
Apartment 6
1580 sqft
Apartment 7
1511 sqft
Apartment 8
1504 sqft
Apartment 9
1530 sqft
Apartment 10
1428 sqft


## 5877 Main Street (Village) (in construction)

- Zoned MU (Village zoning)
- 1.63 acres = 71,002.8 sq. ft.
    - **Building coverage on site = 15,000 sq. ft. or 0.34 acres or 21.1%**
- 4 story mixed-use
    - **1st floor – 15,000 sq. ft. commercial (50% spa)**
    - **2nd - 4th floors – 45,000 sq. ft. residential (28 units)**
- **TOTAL SQUARE FOOTAGE OF BUILDING: 60,000 sq. ft.**
    - **15,000 sq. ft. or 25% commercial**
    - **45,000 sq. ft. or 75% residential**




## 4548-4564 Main Street & 17 Fruehauf Ave & 22 Chateau Terrace (SP-2022-11) (in construction)

- Zoned TI-2.5
- 0.93 acres = 40,510.8 sq. ft.
    - **Building coverage on site = approximately 12,000 sq. ft. or 0.28 acres or 29.6%**
- **2.5 story mixed-use (3.5 with grade change)**
    - **56,204 sq. ft. of residential throughout**
    - **1st floor – 6,657 sq. ft. commercial (2 restaurants) and 6 units**
    - **2nd floor – 20 units**
    - **3rd floor – 18 units**
- **TOTAL SQUARE FOOTAGE OF BUILDING: 62,861 sq. ft.**
    - **6,657 sq. ft. or 10.6% commercial**
    - **56,204 sq. ft. or 89.4% residential**




## 315 Campbell Blvd (SP-2019-01A)


- Zoned NB
- 2.25 acres = 98,010 sq. ft.
    - **Building coverage on site = 19,120.4 sq. ft. or 0.44 acres or 19.5%**
- 2 buildings
    - **Building #1 - 2.5 story mixed-use**
        - **1st floor – 2,200 sq. ft. office/retail and 12 units (14,328.4 sq. ft.) = 16,528.4 sq. ft.**
        - **2nd floor – 14,328.4 sq. ft. residential (12 units)**
        - **3rd floor – 7,164.2 sq. ft. residential (6 units)**
    - Building #2 – Garage
        - 9 spaces, 2,592 sq. ft.
- **TOTAL SQUARE FOOTAGE OF BUILDING: 38,021 sq. ft.**
    - **2,200 sq. ft. or 5.8% commercial**
    - **35,821 sq. ft. or 94.2% residential**


LIMIT OF FENCE
JURISDICTIONAL WETLAND TO BE IMPACTED (0.02 AC)
PROPOSED 2 1/2-STORY APARTMENT BUILDING - 30 UNITS (30' MEDIAN HEIGHT)
(12) APTS 1ST FLOOR
(12) APTS 2ND FLOOR
(6) APTS 3RD FLOOR
1-STORY OFFICE/ RETAIL SPACE 2,200 SF
PATIO
5'x8' CONCRETE PATIO, TYP.
A/C UNIT, TYP.
PERMANENT OPEN SPACE LIMIT
STORM WATER MANAGEMENT AREA
PERMANENT OPEN SPACE
9 CAR GARAGE
SIGN
10' SIDE SETBACK
30' FRONT SETBACK
20' FRONT SETBACK
3' HIGH MASONRY WALL IN 20LF SECTIONS, TYP.
76'± PROPOSED CURBCUT
@ L=387' DEED L=421.22' MEAS.
@ 266' DEED 263.94' MEAS.
@ 323' DEED 322.90' MEAS.
414.48' DEED
ZONED NB
ZONED NCD-2

## 1185 Sweet Home (SP-2018-19)


- Zoned GB, MFR-6 and NCD-LC
- 12.9 acres = 561,924 sq. ft.
    - **Building coverage (of mixed-use buildings) = approximately 46,500 sq. ft. or 1.1 acres or 8.2%**
- 19 buildings (196 total residential units, 97 units in mixed-use buildings #1 & #2)
    - **Building #1 – 5 story mixed-use (approximately 120,264 gross sq. ft.)**
        - **1st floor – 7,564 sq. ft. commercial, 7 units (total approximately 23,100 sq. ft.)**
        - **2nd – 5th floors – approximately 97,164 sq. ft. residential (24,291 sq. ft. per floor), 48 units (12 units each floor)**
    - **Building #2 – 4 story mixed-use (approximately 117,096 gross sq. ft.)**
        - **1st floor – 2,890 sq. ft. commercial, 3 units (total approximately 23,400 sq. ft.)**
        - **2nd - 4th floors – approximately 93,696 sq. ft. residential (23,400 sq. ft. per floor), 39 units (13 units each floor)**
    - Buildings #3 - #18 – 3 story residential buildings (99 4-bedroom units)
        - #3, #4, #15, #16 – 7 units each
        - #5, #6, #8, #10, #12, #14, #17, #18 – 6 units each
        - #7 – 8 units
        - #9, #11, #13 – 5 units
    - Maintenance Building
        - 1,300 sq. ft.
- **TOTAL SQUARE FOOTAGE OF BUILDINGS #1 & #2: 237,360 sq. ft.**
    - **10,454 sq. ft. or 4.4% commercial**
    - **226,906 sq. ft. or 95.6% residential**


SITE PLAN
SCALE: 1"=60'
N
PROPOSED STOP SIGN
PROPOSED STOP BAR & CROSSWALK
315.00'
200.00'
173.00'
146.02'
SWEET HOME ROAD
© Cannina Wood Morris PC





**PODIUM LEVEL FLOOR PLAN (L1)**


**BUILDING #1 GROUND FLOOR PLAN**




**BUILDING #1 UPPER FLOOR PLAN**



**BUILDING #2 GROUND FLOOR PLAN**



**BUILDING #2 UPPER FLOOR PLAN**




TYPICAL FLOOR

# APPENDIX B

**TOWN LAND USE ANALYSIS NOTES**

# Town Land Use Analysis Notes

**TAZ 668**

- 2019 Units: 0
- 2024 Units: 0
- 2019 Commercial – Retail SF: 0
- 2019 Commercial – Office SF: 0
- 2024 Commercial - Retail SF: 0
- 2024 Commercial – Office SF: 0
- TAZ to remain unchanged – only a very small portion of the TAZ is within the BCD GEIS boundary and that portion contains no developable land as it is part of the I-290 right-of-way

**TAZ 676**

- 2019 Units: 200
- 2024 Units: 78
- 2019 Commercial – Retail SF: 440,000
- 2019 Commercial – Office SF: 290,000
- 2024 Commercial – Retail SF: 82,062
- 2024 Commercial – Office SF : 0
- The shopping center known as Consumer Square/The Boulevard is likely to remain largely unchanged over the 20 year growth period, with the exception of some infill of the parking area with liner buildings similar in size and location to existing buildings along the central drive aisle. These would likely be 1-story buildings with smaller retail and/or restaurant space
- The residential area to the north of Ridge Lea Road is assumed to be suitable for redevelopment into a mix of uses due to its proximity to the shopping center to the south and the I-290 to the north, and its location away from single-family residential uses

**TAZ 677**

- 2019 Units: 500
- 2024 Units: 494
- 2019 Commercial – Retail SF: 200,000
- 2019 Commercial – Office SF: 100,000
- 2024 Commercial – Retail SF: 109,678
- 2024 Commercial – Office SF: 0

- The area north of the Boulevard Towers Apartments has the potential to add additional housing units in a larger underutilized open area/green space
- The area just east of the Meyer Pointe Senior Apartments has the potential to redevelop, with commercial along the Niagara Falls Boulevard frontage and more residential, possibly similar in use with either senior or market rate apartments, adjacent to the existing senior apartments.
- The area east of Premier Wine & Spirits and west of Tops Friendly Markets, between Meyer Road and Maple Road, has the potential to redevelop with commercial uses along Maple Road and residential along Meyer Road to mirror the Boulevard Towers Apartments to the north
- Some of the only remaining single-family homes and smaller vacant lands along Meyer Road closer to North Bailey Avenue have the potential to be developed as a mix of uses

**TAZ 678**

- 2019 Units: 1,140
- 2024 Units: 1,140
- 2019 Commercial – Retail SF: 100,000
- 2019 Commercial – Office SF: 35,000
- 2024 Commercial - Retail SF: 299,265
- 2024 Commercial – Office SF: 99,755
- There is a large potential for larger scale mixed-use in the majority of this TAZ
- The area between Maple Road, Sweet Home Road and the I-290 is isolated from single-family residential and contains an older office building and Motel6 that could either be converted to more housing or entirely demolished to become mixed-use buildings
- The Maple Ridge Plaza is largely underutilized with large parking areas and high turnover or vacancy rates within the existing plaza. There is interest from the property owners to infill outparcels or entirely redesign the plaza using the mixed-use zoning districts.
- The corner of North Bailey Avenue and Maple Road, extending east to the Sweet Home Middle School property, is another location with high turnover in tenants (especially in the larger buildings towards Meyer Road) and is a large area that has the potential to transform into a mixed-use center utilizing the mixed-use districts.

**TAZ 679**

- 2019 Units: 180
- 2024 Units: 0
- 2019 Commercial – Retail SF: 310,000
- 2019 Commercial – Office SF: 10,000
- 2024 Commercial - Retail SF: 310,159

- 2024 Commercial – Office SF: 0
- This area was rezoned using the mixed-use zoning districts back in 2020 but has recently been reverted back to Shopping Center (SC) zoning
- A redevelopment project was recently approved for this site, containing a large footprint Costco with related fueling station, a 2-story Dick's Sporting Goods store, and a warehouse for operations related to Delta Sonic. The KeyBank building is slated to remain but adding approximately 600 employees relocated from a different KeyBank facility, which necessitated a recent parking expansion project.
- The warehouse portion of the approved project may change in the near future, with either more commercial or entertainment uses; as such, the Town identified the southern portion of this TAZ to have potential for redevelopment with different commercial uses in the future

**TAZ 680**

- 2019 Units: 180
- 2024 Units: 43
- 2019 Commercial – Retail SF: 30,000
- 2019 Commercial – Office SF: 20,000
- 2024 Commercial – Retail SF: 28,622
- 2024 Commercial – Office SF: 0
- This TAZ consists mainly of residential uses, except for uses along Sheridan Drive
- There is slight mixed-use redevelopment potential (either housing or retail/commercial) at the corner of Sheridan Drive and Alberta Drive as the area contains older office buildings

**TAZ 681**

- 2019 Units: 50
- 2024 Units: 50
- 2019 Commercial – Retail SF: 40,000
- 2019 Commercial – Office SF: 25,000
- 2024 Commercial - Retail SF: 65,350
- 2024 Commercial – Office SF: 0
- It is assumed that the Wegmans building and related parking area to the south will remain within the 20 year growth period.
- The current Ashley Furniture store at the southern end of the TAZ has the potential for mixed-use redevelopment, either with commercial mirroring redevelopment in the Boulevard Mall TAZ to the west or along the drive aisle in the center of the parcel, with either upper story housing or town homes for transitions to the adjacent residential neighborhoods.

**TAZ 682**

- 2019 Units: 1,700
- 2024 Units: 1,551
- 2019 Commercial – Retail SF: 190,000
- 2019 Commercial – Office SF: 127,000
- 2024 Commercial - Retail SF: 831,015
- 2024 Commercial – Office SF: 158,013
- This TAZ contains the Boulevard Mall and large retail shopping plazas to the south which contain the most redevelopment potential within the BCD.
- The Boulevard Central District Urban Renewal Plan, adopted in 2022, outlines community goals and objectives that direct the outcomes the Town is seeking in the redevelopment of the Mall site and larger Urban Renewal Area. The proposed future land uses outlined in Figure 3 reflect these goals and objectives and balance the various interests on site, and include:
- Higher-density mixed-uses applied to a larger portion of the TAZ than currently zoned in order to meet housing and economic development goals.
- Frontages along the major roadways (Niagara Falls Boulevard, Maple Road and Sheridan Drive) are assumed to remain a majority of commercial uses at about 1-2 stories in height.
- Focus on more vertical mixed-uses further east into the Boulevard Mall and shopping plaza sites, as the eastern roads that perimeter the TAZ are less intensive than Maple Road and Niagara Falls Boulevard, and more favorable to residential environments.
- The shopping plaza to the south of the Mall site is large and currently contains vacant big box stores, giving the potential for mixed-use center redevelopment, continuing the Mall vision further south.
- The TAZ estimates reflect anticipated full build-out within the 20 year timeframe, as the Town is actively driving redevelopment of the site.

**TAZ 683**

- 2019 Units: 150
- 2024 Units: 269
- 2019 Commercial – Retail SF: 125,000
- 2019 Commercial – Office SF: 85,000
- 2024 Commercial - Retail SF: 51,799
- 2024 Commercial – Office SF: 0
- It is assumed that the majority of this TAZ will remain unchanged and continue to operate one of the region's largest car dealerships (Northtown Automotive) within the 20-year growth period.
- A small area north of Hartford Road containing a few single-family homes and two-unit/duplex buildings, adjacent to the Shaarey Zedek Apartments, could redevelop to

include more housing units in a larger multi-family building/complex or could be utilized by Northtown as well.

**TAZ 684**

- 2019 Units: 50
- 2024 Units: 50
- 2019 Commercial – Retail SF: 100,000
- 2019 Commercial – Office SF: 70,000
- 2024 Commercial - Retail SF: 13,875
- 2024 Commercial – Office SF: 0
- The majority of this TAZ contains a single-family neighborhood except for the frontage along Sheridan Drive between North Bailey Avenue and Sweet Home Road
- Walmart is likely to remain, although could change over to more warehousing/distribution if in-store shopping continues to decline in favor of online shopping, reducing the need for some of the parking
- The plaza at the corner of Sheridan and Sweet Home that extends along the Sheridan frontage has the potential to redevelop into a mix of uses.

**TAZ 686**

- 2019 Units: 115
- 2024 Units: 115
- 2019 Commercial – Retail SF: 24,000
- 2019 Commercial – Office SF: 20,000
- 2024 Commercial - Retail SF: 69,845
- 2024 Commercial – Office SF: 0
- The majority of this TAZ contains a single-family home neighborhood except for frontages along Sheridan Drive and Millersport Highway which have some limited potential for additional commercial/mixed-use redevelopment, specifically with the older office and motor service uses on Sheridan Drive, the larger City Mattress building at the corner of Sheridan and Millersport, and the Homewood Suites by Hilton on Millersport near the I-290 ramp.

**TAZ 687**

- 2019 Units: 205
- 2024 Units: 385
- 2019 Commercial – Retail SF: 30,000
- 2019 Commercial – Office SF: 92,000
- 2024 Commercial - Retail SF: 0

- 2024 Commercial – Office SF: 0
- Although currently not zoned mixed-use, portions of the University Corporate Centre Office Park, accessed off of Maple Road and adjacent to the I-290, could host infill residential or office.
- It is assumed that St. Leo's Church and School and the Town's Eggertsville Community Park will remain over the 20-year growth period. If it were to redevelop, it would include more civic or community space and would not contribute more units of commercial square footage.

**TAZ 688**

- 2019 Units: 75
- 2024 Units: 118
- 2019 Commercial – Retail SF: 47,000
- 2019 Commercial – Office SF: 40,000
- 2024 Commercial - Retail SF: 147,657
- 2024 Commercial – Office SF: 0
- The majority of this TAZ contains a single-family neighborhood except for frontage along Maple Road
- It is assumed that the area at the corner of Maple Road and North Bailey Avenue will continue to have a majority of commercial land uses, with potential for some of the office buildings to convert to commercial uses.
- The frontage on Maple Road east of Hillcrest Drive has older buildings that have seen some turnover and vacancy in recent years and could redevelop to include smaller multi-family residential buildings to buffer single-family homes to the south.

**TAZ 699**

- 2019 Units: 20
- 2024 Units: 20
- 2019 Commercial – Retail SF: 70,000
- 2019 Commercial – Office SF: 60,000
- 2024 Commercial - Retail SF: 7,000
- 2024 Commercial – Office SF: 0
- The BCD GEIS contains only a smaller portion of this TAZ at the corner of Harlem Road and Sheridan Drive at the I-290
- It is assumed that the existing office buildings could be redeveloped into a mix of uses on this site, with retail on the bottom and residential above.

**TAZ 701**

- 2019 Units: 0
- 2024 Units: 0
- 2019 Commercial – Retail SF: 20,000
- 2019 Commercial – Office SF: 18,000
- 2024 Commercial - Retail SF: 0
- 2024 Commercial – Office SF: 0
- The only areas in this TAZ contained in the BCD GEIS boundary are the shallow parcels along Sheridan Drive and at the corner of Millersport Highway
- The Town is assuming that because of the shallowness of these parcels, the buildings will be reused or repurposed in their current states for similar commercial or office uses, causing no change in residential units or commercial/office square footage within this TAZ.

**TAZ 702**

- 2019 Units: 75
- 2024 Units: 200
- 2019 Commercial – Retail SF: 4,000
- 2019 Commercial – Office SF: 2,000
- 2024 Commercial - Retail SF: 52,500
- 2024 Commercial – Office SF: 17,500
- The corner of Bailey Avenue and Sheridan Drive has the potential to redevelop with a mix of uses – the Rite Aid store is closing and there are some smaller commercial buildings that could be redeveloped
- It is proposed that there could be additional commercial square footage in this area of the TAZ than what was projected in 2019 (up to 10,000 SF)

**TAZ 705**

- 2019 Units: 300
- 2024 Units: 320
- 2019 Commercial – Retail SF: 100,000
- 2019 Commercial – Office SF: 75,000
- 2024 Commercial - Retail SF: 84,000
- 2024 Commercial – Office SF: 28,000
- This TAZ has potential for redevelopment with a mix of uses, particularly the area at Eggert Road, Bailey Avenue and Sheridan Drive where marginal, older buildings exist. Although an At Home retail store recently utilized an existing building in this area, it is likely it could vacate this site within the 20-year growth period. This area could host a majority of housing with retail on the first floor.

**TAZ 708**

- 2019 Units: 35
- 2024 Units: 90
- 2019 Commercial – Retail SF: 42,000
- 2019 Commercial – Office SF: 29,000
- 2024 Commercial – Retail SF: 31,394
- 2024 Commercial – Office SF: 0
- The only site the Town sees as having potential to redevelop in this TAZ is the area along Sheridan Drive that contains the current Ethan Allen store and Sheridan Family Restaurant, which could contain a mix of uses, likely office space, to compliment neighboring medical uses with some upper floor residential as well.

**TAZ 709**

- 2019 Units: 25
- 2024 Units: 0
- 2019 Commercial – Retail SF: 6,000
- 2019 Commercial – Office SF: 6,000
- 2024 Commercial - Retail SF: 74,456
- 2024 Commercial – Office SF: 0
- The BCD GEIS contains only a smaller portion of this TAZ along Sheridan Drive
- The Town assumes that because of the shallow parcels, there will be little redevelopment potential except for reutilization and repurposing of existing buildings with similar uses. An exception is the small area near Millersport Highway that includes Public Storage, which the Town anticipates expanding with second story storage space.

# APPENDIX B

**GROWTH PROJECTIONS SUMMARY TABLE BY TAZ**

# Growth Assumptions Summary Table by TAZ

## OVERALL SUMMARY: VARIABLES & ASSUMPTIONS

| | | | | | |
|---|---|---|---|---|---|
| TAZ | 19 | | Traffic Analysis Zone (Smaller Geographic Areas in Study Area) | | |
| BCD Study Area Boundary | 55,059,840 | SF | (Horizontal) | 1264 | AC |
| Conceptual Land Use Area | 29,117,208 | SF | (Horizontal) | 668 | AC |
| Potential Redevelopment Area | 11,552,849 | SF | (Horizontal) | 265 | AC |
| Building Coverage Area | 2,757,261 | SF | (Horizontal) | 63.3 | AC |
| Total Building SF | 9,437,669 | SF | (includes exterior wall for entire building) | | |
| Building Coverage (1st floor) | 15-30% | | (%) varies based on Land Use | | |
| Vertical Height | varies | | (# of stories - MU, SC, OB, CS, GB, MS, RD, CF) | | |
| Per Unit | 1400 | | SF per Dwelling Unit | | |
| **Commercial Ratio** | | | | | |
| Office Ratio | 0-5% | | | | |
| Retail Ratio | 95-100% | | | | |
| **Mixed Use Ratio** | | | | | |
| Residential Ratio | 80% | | | | |
| Retail Ratio | 15-20% | | | | |
| Office Ratio | 0-5% | | | | |

*The data, variables and factors used to derive the growth assumptions is organized by TAZ. The Potential Redevelopment Areas are broken down into sub areas numbered #1-31 and correspond to the polygons in the Town exhibits/maps.*

| TAZ 668 | | | | |
|---|---|---|---|---|
| | Variable | Assumption | Value | Unit of Measure |
| | **Sub Area (N/A)** | | 0 | |
| | Building Coverage (1st Floor) | | 0 | |
| | Zoning Applied | | CF | |
| | Total Building SF | | 0 | (n/a) |

| TAZ 676 Potential Redevelopment Area | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| | **Sub Area 1** | | | 182,710 | SF | |
| COMMERCIAL | Building Coverage (1st Floor) | 30% | 0.3 | 54,813 | SF | Consumer's Square |
| | Zoning Applied (Height) | | 1 | SC | # of Stories | |
| | Total Building SF | | | 54,813 | SF | |
| | | 0% | 1 | 54,813 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 54,813 | SF | |

| | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| | **Sub Area 2** | | | 113,536 | SF | |
| MIXED-USE/RESIDENTIAL | Building Coverage (1st Floor) | 15% | 0.15 | 17,030 | SF | Consumer's Square |
| | Zoning Applied (Height) | | 8 | CTR-8 | # of Stories | |
| | Total Building SF | | | 136,243 | SF | |
| | | 0% | 1 | 136,243 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 108,995 | SF | |
| | Retail | 20% | 0.2 | 27,249 | SF | |
| | Total Units | | | 78 | Dwelling Units | |

| TAZ 677 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| | **Sub Area 3a & b** | | | 269,270 | SF | |
| COMMERCIAL | Building Coverage (1st Floor) | 30% | 0.3 | 80,781 | SF | Burlington Plaza/Tops |
| | Zoning Applied (Height) | | 1 | SC, RD, MS | # of Stories | |
| | Total Building SF | | | 80,781 | SF | |
| | | 0% | 1 | 80,781 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 80,781 | SF | |

| | | | | | | |
|---|---|---|---|---|---|---|
| **RESIDENTIAL** | Variable | Assumption | | Value | Unit of Measure | Burlington Plaza/Tops |
| | **Sub Area 4a, b & c** | | | 460,473 | SF | |
| | Building Coverage (1st Floor) | 25% | 0.25 | 115,118 | SF | |
| | Zoning Applied | | 5 | MFR-5 | # of Stories | |
| | Total Building SF | | | 575,591 | SF | |
| | | 0% | 1 | 575,591 | Total Bldg SF (used for modeling) | |
| | Units | | | 411 | Dwelling Units | |

| | | | | | | |
|---|---|---|---|---|---|---|
| **MIXED-USE/RESIDENTIAL** | Variable | Assumption | | Value | Unit of Measure | Burlington Plaza/Tops |
| | **Sub Area 5a & b** | | | 144,487 | SF | |
| | Building Coverage (1st Floor) | 20% | 0.2 | 28,897 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 144,487 | SF | |
| | | 0% | 1 | 144,487 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 115,590 | SF | |
| | Retail | 20% | 0.2 | 28,897 | SF | |
| | Total Units | | | 83 | Dwelling Units | |

| **TAZ 678 Potential Redevelopment Areas** | | | | | | |
|---|---|---|---|---|---|---|
| **COMMERCIAL** | | | | | Unit of Measure | School / AMC Plaza |
| | **Sub Area (N/A)** | | | 0 | SF | |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | CS, GB, MS, SC | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 5% | 0.05 | 0 | SF | |
| | Retail | 95% | 0.95 | 0 | SF | |

| | | | | | | |
|---|---|---|---|---|---|---|
| **MIXED-USERESIDENTIAL** | Variable | Assumption | | Value | Unit of Measure | School / AMC Plaza |
| | **Sub Area 6a, b & c** | | | 1,995,100 | SF | |
| | Building Coverage (1st Floor) | 20% | 0.2 | 399,020 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 1,995,100 | SF | |
| | | 0% | 1 | 1,995,100 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 1,596,080 | SF | |
| | Retail | 15% | 0.15 | 299,265 | SF | |
| | Office | 5% | 0.05 | 99,755 | SF | |
| | Units | | | 1,140 | Dwelling Units | |

| **TAZ 679 Potential Redevelopment Areas** | | | | | | |
|---|---|---|---|---|---|---|
| **COMMERCIAL** | Variable | Assumption | | Value | Unit of Measure | Ridge Lea / Costco |
| | **Sub Area 7** | | | 1,033,863 | SF | |
| | Building Coverage (1st Floor) | 30% | 0.3 | 310,159 | SF | |
| | Zoning Applied (Height) | | 1 | SC, GI, RD | # of Stories | |
| | Total Building SF | | | 310,159 | SF | |
| | | 0% | 1 | 310,159 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 310,159 | SF | |

| | | | | | | |
|---|---|---|---|---|---|---|
| **RESIDENTIAL** | Variable | Assumption | | Value | Unit of Measure | Ridge Lea / Costco |
| | **Sub Area (N/A)** | | | 0 | SF | |
| | Building Coverage (1st Floor) | 25% | 0.25 | 0 | SF | |
| | Zoning Applied (Height) | | 5 | MFR-5 | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Units | | | 0 | Dwelling Units | |

| **TAZ 680 Potential Redevelopment Areas** | | | | | | |
|---|---|---|---|---|---|---|
| **COMMERCIAL** | Variable | Assumption | | Value | Unit of Measure | Emerson Apartments |
| | **Sub Area 8** | | | 45,334 | SF | |
| | Building Coverage (1st Floor) | 30% | 0.3 | 13,600 | SF | |
| | Zoning Applied (Height) | | 1 | MIXED-USE | # of Stories | |
| | Total Building SF | | | 13,600 | SF | |
| | | 0% | 1 | 13,600 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 13,600 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 9** | | | 75,108 | SF | Emerson Apartments |
| | Building Coverage (1st Floor) | 20% | 0.2 | 15,022 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 75,108 | SF | |
| | | 0% | 1 | 75,108 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 60,086 | SF | |
| | Retail | 20% | 0.2 | 15,022 | SF | |
| | Units | | | 43 | Dwelling Units | |

| TAZ 681 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area 10** | | | 159,166 | SF | Wegmans |
| | Building Coverage (1st Floor) | 30% | 0.3 | 47,750 | SF | |
| | Zoning Applied (Height) | | 1 | MIXED-USE | # of Stories | |
| | Total Building SF | | | 47,750 | SF | |
| | | 0% | 1 | 47,750 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 47,750 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 11** | | | 88,000 | SF | Wegmans |
| | Building Coverage (1st Floor) | 20% | 0.2 | 17,600 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 88,000 | SF | |
| | | 0% | 1 | 88,000 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 70,400 | SF | |
| | Retail | 20% | 0.2 | 17,600 | SF | |
| | Units | | | 50 | Dwelling Units | |

| TAZ 682 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area 12a & b** | | | 1,487,399 | SF | Boulevard Mall |
| | Building Coverage (1st Floor) | 30% | 0.3 | 446,220 | SF | |
| | Zoning Applied (Height) | | 1 | GB/SC/MS | # of Stories | |
| | Total Building SF | | | 446,220 | SF | |
| | | 0% | 1 | 446,220 | Total Bldg SF (used for modeling) | |
| | Office | 5% | 0.05 | 22,311 | SF | |
| | Retail | 95% | 0.95 | 423,909 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 13** | | | 643,027 | SF | Boulevard Mall |
| | Building Coverage (1st Floor) | 20% | 0.2 | 128,605 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 643,027 | SF | |
| | | 0% | 1 | 643,027 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 514,422 | SF | |
| | Retail | 15% | 0.15 | 96,454 | SF | |
| | Office | 5% | 0.05 | 32,151 | SF | |
| | Units | | | 367 | Dwelling Units | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 14** | | | 710,166 | SF | Boulevard Mall |
| | Building Coverage (1st Floor) | 15% | 0.15 | 106,525 | SF | |
| | Zoning Applied (Height) | | 8 | CTR-8 | # of Stories | |
| | Total Building SF | | | 852,199 | SF | |
| | | 0% | 1 | 852,199 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 681,759 | SF | |
| | Retail | 15% | 0.15 | 127,830 | SF | |
| | Office | 5% | 0.05 | 42,610 | SF | |
| | Units | | | 487 | Dwelling Units | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 15a & b** | | | 708,528 | SF | Boulevard Mall |
| | Building Coverage (1st Floor) | 20% | 0.2 | 141,706 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 708,528 | SF | |
| | | 0% | 1 | 708,528 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 566,822 | SF | |
| | Retail | 15% | 0.15 | 106,279 | SF | |
| | Office | 5% | 0.05 | 35,426 | SF | |
| | Units | | | 405 | Dwelling Units | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 16** | | | 425,239 | SF | Boulevard Mall |
| | Building Coverage (1st Floor) | 15% | 0.15 | 63,786 | SF | |
| | Zoning Applied (Height) | | 8 | CTR-8 | # of Stories | |
| | Total Building SF | | | 510,287 | SF | |
| | | 0% | 1 | 510,287 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 408,229 | SF | |
| | Retail | 15% | 0.15 | 76,543 | SF | |
| | Office | 5% | 0.05 | 25,514 | SF | |
| | Units | | | 292 | Dwelling Units | |

**TAZ 683 Potential Redevelopment Areas**

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| COMMERCIAL | **Sub Area (N/A)** | | | 0 | SF | Northtown Dealer |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | MS | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 0 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| RESIDENTIAL | **Sub Area 17** | | | 225,076 | SF | Northtown Dealer |
| | Building Coverage (1st Floor) | 25% | 0.25 | 56,269 | SF | |
| | Zoning Applied (Height) | | 3 | MFR-5 | # of Stories | |
| | Total Building SF | | | 168,807 | SF | |
| | | 0% | 1 | 168,807 | Total Bldg SF (used for modeling) | |
| | Units | | | 121 | Dwelling Units | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 18** | | | 215,828 | SF | Northtown Dealer |
| | Building Coverage (1st Floor) | 15% | 0.15 | 32,374 | SF | |
| | Zoning Applied (Height) | | 8 | CTR-8 | # of Stories | |
| | Total Building SF | | | 258,994 | SF | |
| | | 0% | 1 | 258,994 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 207,195 | SF | |
| | Retail | 20% | 0.2 | 51,799 | SF | |
| | Units | | | 148 | Dwelling Units | |

**TAZ 684 Potential Redevelopment Areas**

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| COMMERCIAL | **Sub Area (N/A)** | | | 0 | SF | Walmart / Residential |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | MS, GB | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 0 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 19** | | | 55,500 | SF | Walmart / Residential |
| | Building Coverage (1st Floor) | 25% | 0.25 | 13,875 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 69,375 | SF | |
| | | 0% | 1 | 69,375 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 55,500 | SF | |
| | Retail | 20% | 0.2 | 13,875 | SF | |
| | Units | | | 50 | Dwelling Units | |

| TAZ 686 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area 20** | | | 170,734 | SF | Sheridan Dr / Neighborhood |
| | Building Coverage (1st Floor) | 30% | 0.3 | 51,220 | SF | |
| | Zoning Applied (Height) | | 1 | GB, MS, CF | # of Stories | |
| | Total Building SF | | | 51,220 | SF | |
| | | 0% | 1 | 51,220 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 51,220 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| RESIDENTIAL | **Sub Area 21** | | | 115,312 | SF | Sheridan Dr / Neigh. |
| | Building Coverage (1st Floor) | 25% | 0.25 | 28,828 | SF | |
| | Zoning Applied (Height) | | 3 | MFR-5 | # of Stories | |
| | Total Building SF | | | 86,484 | SF | |
| | | 0% | 1 | 86,484 | Total Bldg SF (used for modeling) | |
| | Units | | | 62 | Dwelling Units | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 22** | | | 74,500 | SF | Sheridan Dr / Neigh. |
| | Building Coverage (1st Floor) | 25% | 0.25 | 18,625 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 93,125 | SF | |
| | | 0% | 1 | 93,125 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 74,500 | SF | |
| | Retail | 20% | 0.2 | 18,625 | SF | |
| | Units | | | 53 | Dwelling Units | |

| TAZ 687 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area (N/A)** | | | 0 | SF | St. Leo's / Uniland |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | OB, MS, CF | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 0 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| RESIDENTIAL | **Sub Area 23** | | | 14,384 | SF | St. Leo's / Uniland |
| | Building Coverage (1st Floor) | 25% | 0.25 | 3,596 | SF | |
| | Zoning Applied (Height) | | 3 | MFR-5 | # of Stories | |
| | Total Building SF | | | 10,788 | SF | |
| | | 0% | 1 | 10,788 | Total Bldg SF (used for modeling) | |
| | Units | | | 8 | Dwelling Units | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| RESIDENTIAL | **Sub Area 24a, b & c** | | | 422,427 | SF | St. Leo's / Uniland |
| | Building Coverage (1st Floor) | 25% | 0.25 | 105,607 | SF | |
| | Zoning Applied (Height) | | 5 | MFR-5 | # of Stories | |
| | Total Building SF | | | 528,034 | SF | |
| | | 0% | 1 | 528,034 | Total Bldg SF (used for modeling) | |
| | Units | | | 377 | Dwelling Units | |

| TAZ 688 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area 25** | | | 492,189 | SF | Maple Rd / Office |
| | Building Coverage (1st Floor) | 30% | 0.3 | 147,657 | SF | |
| | Zoning Applied (Height) | | 1 | OB, MS | # of Stories | |
| | Total Building SF | | | 147,657 | SF | |
| | | 0% | 1 | 147,657 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 147,657 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| RESIDENTIAL | **Sub Area 26** | | | 219,824 | SF | Maple Rd / Office |
| | Building Coverage (1st Floor) | 25% | 0.25 | 54,956 | SF | |
| | Zoning Applied (Height) | | 3 | MFR-5 | # of Stories | |
| | Total Building SF | | | 164,868 | SF | |
| | | 0% | 1 | 164,868 | Total Bldg SF (used for modeling) | |
| | Units | | | 118 | Dwelling Units | |

| TAZ 699 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area (N/A)** | | | 0 | SF | former UB MD |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | MIXED-USE | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 0 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| MIXED-USE/RESIDENTIAL | **Sub Area 27** | | | 28,000 | SF | former UB MD |
| | Building Coverage (1st Floor) | 25% | 0.25 | 7,000 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 35,000 | SF | |
| | | 0% | 1 | 35,000 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 28,000 | SF | |
| | Retail | 20% | 0.2 | 7,000 | SF | |
| | Units | | | 20 | Dwelling Units | |

| TAZ 701 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area (N/A)** | | | 0 | SF | Sheridan Dr. / Walgreens |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | MS, CF | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 0 | SF | |

| | Variable | Assumption | | Value | Unit of Measure | |
|---|---|---|---|---|---|---|
| RESIDENTIAL | **Sub Area (N/A)** | | | 0 | SF | Sheridan Dr. / Walgreens |
| | Building Coverage (1st Floor) | 25% | 0.25 | 0 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Units | | | 0 | Dwelling Units | |

| TAZ 702 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| | Variable | Assumption | | Value | Unit of Measure | |
| COMMERCIAL | **Sub Area (N/A)** | | | 0 | SF | Sheridan Dr. / Pure Hockey |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 5% | 0.05 | 0 | SF | |
| | Retail | 95% | 0.95 | 0 | SF | |

| MIXED-USE/RESIDENTIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Pure Hockey |
|---|---|---|---|---|---|---|
| | **Sub Area 28** | | | 280,000 | SF | |
| | Building Coverage (1st Floor) | 25% | 0.25 | 70,000 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 350,000 | SF | |
| | | 0% | 1 | 350,000 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 280,000 | SF | |
| | Retail | 15% | 0.15 | 52,500 | SF | |
| | Office | 5% | 0.05 | 17,500 | SF | |
| | Units | | | 200 | Dwelling Units | |

| TAZ 705 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| COMMERCIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Wholefoods |
| | **Sub Area (N/A)** | | | 0 | SF | |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | MS, GB | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 5% | 0.05 | 0 | SF | |
| | Retail | 95% | 0.95 | 0 | SF | |

| MIXED-USE/RESIDENTIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Wholefoods |
|---|---|---|---|---|---|---|
| | **Sub Area 29** | | | 448,000 | SF | |
| | Building Coverage (1st Floor) | 25% | 0.25 | 112,000 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 560,000 | SF | |
| | | 0% | 1 | 560,000 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 448,000 | SF | |
| | Retail | 15% | 0.15 | 84,000 | SF | |
| | Office | 5% | 0.05 | 28,000 | SF | |
| | Units | | | 320 | Dwelling Units | |

| TAZ 708 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| COMMERCIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Harlem Rd. |
| | **Sub Area (N/A)** | | | 0 | SF | |
| | Building Coverage (1st Floor) | 30% | 0.3 | 0 | SF | |
| | Zoning Applied (Height) | | 1 | OB, GB | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 0 | SF | |

| MIXED-USE/RESIDENTIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Harlem Rd. |
|---|---|---|---|---|---|---|
| | **Sub Area 30** | | | 125,575 | SF | |
| | Building Coverage (1st Floor) | 25% | 0.25 | 31,394 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 156,969 | SF | |
| | | 0% | 1 | 156,969 | Total Bldg SF (used for modeling) | |
| | Residential | 80% | 0.8 | 125,575 | SF | |
| | Retail | 20% | 0.2 | 31,394 | SF | |
| | Units | | | 90 | Dwelling Units | |

| TAZ 709 Potential Redevelopment Areas | | | | | | |
|---|---|---|---|---|---|---|
| COMMERCIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Duff's |
| | **Sub Area 31** | | | 124,094 | SF | |
| | Building Coverage (1st Floor) | 30% | 0.3 | 37,228 | SF | |
| | Zoning Applied (Height) | | 2 | MS, CS | # of Stories | |
| | Total Building SF | | | 74,456 | SF | |
| | | 0% | 1 | 74,456 | Total Bldg SF (used for modeling) | |
| | Office | 0% | 0 | 0 | SF | |
| | Retail | 100% | 1 | 74,456 | SF | |

| RESIDENTIAL | Variable | Assumption | | Value | Unit of Measure | Sheridan Dr. / Duff's |
|---|---|---|---|---|---|---|
| | **Sub Area (N/A)** | | | 0 | SF | |
| | Building Coverage (1st Floor) | 25% | 0.25 | 0 | SF | |
| | Zoning Applied (Height) | | 5 | CTR-5 | # of Stories | |
| | Total Building SF | | | 0 | SF | |
| | | 0% | 1 | 0 | Total Bldg SF (used for modeling) | |
| | Units | | | 0 | Dwelling Units | |

# APPENDIX B

**DEMOGRAPHIC PROJECTIONS CHART**

# Demographic Projections Chart

| TAZ | GBNRTC 2020 Base (Data) | | | | Town BCD Growth Assumptions (2025) | | | BCD Growth Assumptions to Pop & Emp | | | GBNRTC 2020 TAZ with BCD Projections | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | *Population* | *Avg HH Size* | *Retail Emp* | *Office Emp* | *Total Units* | *Retail SF* | *Office SF* | *Population* | *Retail Emp** | *Office Emp** | *Population* | *Retail Emp* | *Office Emp* |
| 668 | 1 | 4.00 | 92 | 261 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 92 | 261 |
| 676 | 262 | 1.39 | 653 | 347 | 78 | 82,062 | 0 | 108 | 234 | 0 | 370 | 887 | 347 |
| 677 | 765 | 1.53 | 745 | 395 | 494 | 109,678 | 0 | 756 | 313 | 0 | 1,521 | 1,058 | 395 |
| 678 | 21 | 2.10 | 470 | 333 | 1,140 | 299,265 | 99,755 | 2,394 | 855 | 570 | 2,415 | 1,325 | 903 |
| 679 | 18 | 2.12 | 442 | 235 | 0 | 310,159 | 0 | 0 | 886 | 0 | 18 | 1,328 | 235 |
| 680 | 519 | 1.71 | 257 | 49 | 43 | 28,622 | 0 | 74 | 82 | 0 | 593 | 339 | 49 |
| 681 | 0 | 2.29 | 189 | 101 | 50 | 65,350 | 0 | 115 | 187 | 0 | 115 | 376 | 101 |
| 682 | 287 | 1.54 | 1,473 | 280 | 1,551 | 831,015 | 158,013 | 2,389 | 2,374 | 903 | 2,676 | 3,847 | 1,183 |
| 683 | 240 | 1.57 | 261 | 726 | 269 | 51,799 | 0 | 422 | 148 | 0 | 662 | 409 | 726 |
| 684 | 633 | 2.50 | 105 | 83 | 50 | 13,875 | 0 | 125 | 40 | 0 | 758 | 145 | 83 |
| 686 | 875 | 2.30 | 108 | 294 | 115 | 69,845 | 0 | 265 | 200 | 0 | 1,140 | 308 | 294 |
| 687 | 172 | 2.35 | 77 | 139 | 385 | 0 | 0 | 905 | 0 | 0 | 1,077 | 77 | 139 |
| 688 | 480 | 2.40 | 138 | 73 | 118 | 147,657 | 0 | 283 | 422 | 0 | 763 | 560 | 73 |
| 699 | 684 | 2.26 | 27 | 161 | 20 | 7,000 | 0 | 45 | 20 | 0 | 729 | 47 | 161 |
| 701 | 976 | 2.21 | 128 | 55 | 0 | 0 | 0 | 0 | 0 | 0 | 976 | 128 | 55 |
| 702 | 359 | 1.92 | 172 | 76 | 200 | 52,500 | 17,500 | 384 | 150 | 100 | 743 | 322 | 176 |
| 705 | 53 | 1.88 | 198 | 536 | 320 | 84,000 | 28,000 | 602 | 240 | 160 | 655 | 438 | 696 |
| 708 | 174 | 2.10 | 55 | 108 | 90 | 31,394 | 0 | 189 | 90 | 0 | 363 | 145 | 108 |
| 709 | 837 | 2.28 | 108 | 51 | 0 | 74,456 | 0 | 0 | 213 | 0 | 837 | 321 | 51 |

| GBNRTC 2020 Base Numbers by TAZ (Baseline Data/Unit of Measurement) | Town Land Use Growth Assumptions (redevelopment) | Conversion of Town Growth Assumption to GBNRTC Units of Measure | Final Result & Output Data Used for Traffic Model |
|---|---|---|---|

**Notes**:

** Town of Amherst Economic Study (2016)*


*350 sq ft per retail employee*

*175 sq ft per office employee*


# APPENDIX B

**MAPS**


# Map B1 – Percentage of New Residential



# Map B2 – Percentage of New Retail



# Map B3 – Percentage of New Office



# APPENDIX C

## TRAFFIC DATA

ADDITIONAL TRANSPORTATION DATA

TECHNICAL MEMO 1 – INVENTORY OF EXISTING CONDITIONS

TECHNICAL MEMO 2 – SUMMARY OF PLANNED CONDITIONS

MITIGATION OBJECTIVES

CONCEPTUAL LAYOUTS OF MITIGATION MEASURES

# APPENDIX C

## ADDITIONAL TRANSPORTATION DATA

# Additional Transportation Data

## Intersections

| Intersections Studied | | |
|---|---|---|
| **Corridor** | **Intersecting Street** | **Intersection Control** |
| Niagara Falls Boulevard | • WB I-290 Ramps | Signal |
| | • EB I-290 Ramps | Signal |
| | • Ridge Lea Road | Signal |
| | • The Boulevard Plaza | Signal |
| | • Romney Road | Signal |
| | • Meyer Road | Stop Sign |
| | • Maple Road/Brighton Road | Signal |
| | • Boulevard Mall Access | Signal |
| | • Treadwell Road | Signal |
| | • Sheridan Drive | Signal |
| | • Eggert Road | Signal |
| Sheridan Drive | • Eggert Road | Signal |
| | • Alberta Drive | Signal |
| | • Bailey Avenue/North Bailey Avenue | Signal |
| | • Sweet Home Road | Signal |
| | • Millersport Highway | Signal |
| Eggert Road | • Alberta Drive | Signal |
| | • Bailey Avenue | Signal |
| Maple Road | • Alberta Drive | Signal |
| | • North Bailey Avenue | Signal |
| | • Bowmart Parkway | Signal |
| | • Hillcrest Drive | Signal |
| | • Sweet Home Road | Signal |
| | • Millersport Highway SB Ramps | Signal |
| | • Millersport Highway NB Ramps | Signal |
| North Bailey Avenue | • Romney Road | Stop Sign (To be Signal) |
| | • Southern Shopping (Best Buy Entrance) | Stop Sign (To be Signal) |
| | • Emerson Drive/Amsterdam Avenue | All-Way Stop Signs |
| | • Meyer Road | Signal |
| Meyer Road | • Bowmart Parkway | Stop Sign |

## Transit

| NFTA Bus Service | | | | |
|---|---|---|---|---|
| **Route No.** | **Route Name** | **Route** | **Service Hours** | **Average Weekday Headways** |
| 34 | Niagara Falls Boulevard | University LRT Station (University at Buffalo South Campus) to Amherst Development Park | 6 a.m. to 9:30 p.m. | 30 min (peak)<br>60 min (off-peak) |
| 35 | Sheridan | Blackrock Riverside Transit Hub to University at Buffalo Amherst Campus | 5:45 a.m. to 10:00 p.m. | 30 min (peak)<br>60 min (off-peak) |
| 44 | Lockport | University LRT Station (University at Buffalo South Campus) to Lockport | 6:15 a.m. to 11:00 p.m. | 45 min (peak)<br>60-90 min (off-peak) |
| 49 | East Amherst | University LRT Station (University at Buffalo South Campus) to Eastern Hills Mall | 7:15a.m. to 4:30p.m. | 60-90 min |

## Traffic Volumes

Traffic volume data was compiled from several sources, including the New York State Department of Transportation (NYSDOT) Traffic Data Viewer, Greater Buffalo Niagara Regional Transportation Council (GBNRTC) Transportation Data Management System, New York State Department of Transportation (NYSDOT), and the Town of Amherst Engineering Department (see table on the following page). Turning movement data was collected at the study area intersections through a combination of hired contractors, Town of Amherst Miovision cameras, and NYSDOT Miovision cameras. The weekday PM data was collected on Thursday February 2, 2023, October 26, 2023, and November 16, 2023 from 3:00 PM to 6:00 PM. The Saturday midday count data was collected on Saturday February 4, 2023, October, 28, 2023, and November 18, 2023 from 12:00 PM to 3:00 PM. Turning movement counts were collected during similar months when school and the University at Buffalo were in session.

The study area is primarily retail in nature, which sees heavy peaks during winter months and the holiday season. Historical traffic data was reviewed from Miovision cameras and the NYS Traffic Data Viewer to verify peak traffic months. Since traffic data was taken during peak periods in the area, no adjustments were made to the data. GBNRTC was consulted about growth in the area and if a compounded growth rate would be applied to bring traffic counts to the existing/current year (2025). There is stagnant growth in the area and therefore no growth rate was applied to bring counts to the current year.

| 2024 AADT Volumes | | |
|---|---|---|
| **Road** | **Segment** | **AADT[1]** |
| Niagara Falls Boulevard | I-290 Interchange to Maple Road | 30,297 |
| | Maple Road to Sheridan Drive | 26,011 |
| Sheridan Drive | Niagara Falls Boulevard to Bailey Avenue | 19,915 |
| | Bailey Avenue to Sweet Home Road | 25,400 |
| | Sweet Home Road to Millersport Highway | 25,651 |
| Millersport Highway | Sheridan Drive to I-290 Interchange | 22,779 |
| | I-290 Interchange to Flint Road | 34,329 |
| | Flint Road to Maple Road | 29,099 |
| Maple Road | Niagara Falls Boulevard to Bailey Avenue | 17,009 |
| | Bailey Avenue to Sweet Home Road | 23,079 |
| | Sweet Home Road to Millersport Highway | 20,985 |
| Bailey Avenue | Eggert Road to Sheridan Drive | 11,640 |
| North Bailey Avenue | Sheridan Drive to Emerson Drive | 10,407 |
| | Emerson Drive to Maple Road | 11,508 |
| | Maple Road to Ridge Lea Road | 14,954 |
| Eggert Road | Sheridan Drive to North Bailey Avenue | 9,173 |
| | North Bailey Avenue to Millersport Highway | 8,788 |
| Sweet Home Road | Sheridan Drive to Maple Road | 12,540* |
| | Maple Road to Rensch Road | 16,501 |
| Ridge Lea Road | Niagara Falls Boulevard to Lowe's Store west driveway | 13,662 |
| | Lowe's Store west driveway to North Bailey Avenue | 8,529 |
| Alberta Drive | Sheridan Drive to Maple Road | 7,100* |
| I-290 Interchange 3 | NB to EB On Ramp | 6,034 |
| | SB to EB On Ramp | 7,949 |
| | EB to NB Off Ramp | 3,887 |
| | EB to SB Off Ramp | 4,804 |
| | NB to WB On Ramp | 4,507 |
| | SB to WB On Ramp | 4,624 |
| | WB Off Ramp | 13,227 |

[1] AADT = Annual Average Daily Traffic (vehicles per day)

*estimated from peak hour data

*Annual Average Daily Traffic (AADT) volumes were gathered from the NYS Traffic Data Viewer. The most recent available AADT volumes on the NYS Traffic Data Viewer are estimated counts for the most recent year of 2024. These (2024) AADT volumes on the study roadways are shown in Table 3.1-4.*

The Planned Condition for traffic volumes is the future redevelopment scenario. Since growth is expected to be stagnant outside of the land use and zoning changes, the future redevelopment scenario is not tied to a specific horizon year and is therefore referred to as the planned condition. Traffic volumes for the Planned Condition were estimated using data outputs of GBNRTC's regional Travel Demand Model (TDM). Without considering the Planned Condition, the Town of Amherst is projected to maintain a general status quo condition, i.e. negligible changes

to traffic and growth. The following are descriptions for each of the models used and considered to determine forecasted traffic volumes in the Study Area:

- GBNRTC Base Travel Demand Model: GBNRTC's base model is a 2020 calibrated model for this study area consisting of 18 Traffic Analysis Zones (TAZs). This includes the base highway network of streets within the federal aid highway system.

- GBNRTC Forecasted Travel Demand Model: GBNRTC's forecasted model is a 2050 model that includes all known development and projects with a planning year of 2050. This model includes the NFTA light rail extension through the Town of Amherst to the UB Campus. This model was not used as a part of this project because it provided more conservative traffic volumes compared to the existing base model, partly in due to the light rail extension expected to decrease the dependency on single occupancy vehicles in the area.


- GBNRTC Projected Growth Development Model: This model was created by GBNRTC using the GBNRTC base travel demand model and adjusting existing land use and zoning to incorporate future land use changes for new population, retail employment, and office employment.

- Existing Condition Model: Synchro 12 model encompassing major intersections and road segments within the study area. This model is populated with existing traffic count data, geometry, signal timings, and phasings that were requested by signal owners and field verified. This model is used to determine the existing capacity, delay, and queueing at intersections.
- Planned Condition Model: Synchro 12 model encompassing major intersections and road segments within the study area. This model is populated with projected traffic volumes from the GBNRTC Project Growth Development Model with existing geometry, signal timings, and phasings.

- Planned Condition Model with Mitigation: Synchro 12 model encompassing major intersections and road segments within the study area. This model is populated with projected traffic volumes from the GBNRTC Project Growth Development Model and identified mitigation including updated signal timings and coordination, geometry, and other mitigation techniques.

The base travel demand model and the projected growth development model were compared to obtain the percent difference for peak hour periods. The percent difference was applied to existing traffic counts to obtain traffic data for the Planned Condition (see the figure on the following page).

**Traffic Volume Generation Process**




## Process to Determine Public and Private Shares for Mitigation Projects

1. **Determine Benefited Area:** The benefited areas are delineated by the boundaries established for the Study Area. The parcels internal to this boundary area have been identified as the primary beneficiaries of the construction of the identified mitigation improvements. The general public at large and external parcels will be considered secondary beneficiaries to the mitigation improvement projects. These external parcels are considered background traffic generators and are therefore the responsibility of the public share.

2. **Calculate Costs of Improved Facilities:** The cost of each planned roadway improvement includes design, construction, and supervision expressed in projected dollars. Construction, engineering, and management costs will be indexed according to NYSDOT's construction price trends. Costs for highway maintenance, renewal, or reconstruction are excluded from the cost basis to be shared; these will be the responsibility of the roadway jurisdictional owner.

   Site access improvements are those that are required to mitigate the direct impact of any individual development. Examples of site improvements are additional turning lanes, traffic signals, or other traffic control devices beyond those outlined as a part of this GEIS. Other site access improvements may include but are not limited to access roads, sidewalks, lighting, raised medians, landscaping, and other treatments not specific in this GEIS. These are implemented by the private developers.

3. **Determine Available Capacity:** *Available Capacity* is defined as the existing unused capacity plus either the additional one-way peak direction capacity of the reconstructed/new facilities or total approach capacity for intersections. Capacity values were calculated based on guidelines in the Highway Capacity Manual, using base threshold volumes to maintain a LOS D or better at a planning level basis. For intersections, capacity can be difficult to measure as similar to an urban street, there are many factors that impact capacity including signal timings, detection, queues, peak hour factor, etc. Therefore, the intersection capacity utilization tool in Synchro was used for each intersection, which determines the amount of available capacity.

4. **Calculate Available Capacity Consumed:** The amount of available capacity used by traffic generated by the proposed project is calculated by dividing the development projected trips for the Study Area by the total available capacity for improvement projects.

5. **Calculate Development Cost Share:** Development cost share is based on the amount of available capacity consumed by PM peak hour trips generated by projected new development. Mitigation costs are calculated for new trips only.

$$\textit{Private Share} = \textit{Cost} \times \frac{\textit{Additional Development Trips}}{\textit{(Total New Trips + Additional Reserve Capacity)}}$$

$$\textit{Public Share} = \textit{Cost} \times \frac{\textit{(New Non-Development Trips + Additional Reserve Capacity)}}{\textit{(Total New Trips + Additional Reserve Capacity)}}$$

## Justification for Each Cost Share of Improvements

Niagara Falls Boulevard from Ridge Lea Road to Sheridan Drive

This street segment is expected to operate under planned development at an arterial LOSE for northbound during the PM and Saturday peaks, the existing level of service for northbound is an E. Urban street LOS is based on travel speed as a percentage of base free-flow speed. There are many variables which impact the capacity and LOS of an urban street including signal timings and spacing, exclusive turn lanes and phasing at intersections, the peak hour factor, facility length, access points, etc. In addition, determining the capacity of an adaptive signal-controlled network is difficult in the planning process, it is better measured in the field once implemented. Therefore, it can be reasonably assumed that the adaptive signal control would be able to accommodate the increase in traffic volumes but reserve capacity for public benefit would be difficult to determine. The private share of these improvements is based on the number of planned trips expected to use Niagara Falls Boulevard and there would be no additional reserve capacity for public benefit.

Ridge Lea Road/N Bailey Avenue from Niagara Falls Boulevard to Maple Road

Segments of this road are expected to operate at an arterial LOS E, with the existing road approaching capacity volumes.

Bowmart Parkway from Maple Road to Meyer Road

Bowmart Parkway has capacity to accommodate existing and planned volumes; however, this will provide direct access to planned development with an extension of Bowmart Parkway north of Meyer Road. Bowmart Parkway could help relieve congestion from North Bailey Avenue, including the N Bailey Avenue at Maple Road intersection. Private share costs are based on the private/public share mitigation cost formulas.

Sheridan Drive from Niagara Falls Boulevard to Millersport Highway

Sheridan Drive is currently operating at a LOS D (westbound) and E (eastbound) during the PM peak. Some segments between intersections will experience a LOS E and F. It is assumed that any additional traffic volumes will degrade the arterial level of service to below a D and further degrade to LOS E for the eastbound direction. The private share of these improvements is based on the number of planned trips expected to use Sheridan Drive divided by the reserve capacity that is of public benefit.

# APPENDIX C

## TECHNICAL MEMO 1 – INVENTORY OF EXISTING CONDITIONS

# Technical Memo 1 – Inventory of Existing Conditions

Traffic Impact Study: Town of Amherst Boulevard Central District

## Background

This technical memo is an inventory of existing conditions for the transportation network within the Town of Amherst Boulevard Central District (BCD). The Town of Amherst BCD is the study area for this project which is approximately 1,260 acres of land bounded by the Interstate 290 (I-290), Niagara Falls Boulevard, and Sheridan Drive. The Town of Amherst completed a GEIS for this study area in 2019 evaluating the cumulative impacts of growth for adopting mixed-use zoning districts.

The GEIS is going through an update revising the land use plan and therefore impacting proposed traffic generated by development. Since it has been more than 3 years since traffic data was collected, an updated inventory of existing conditions including traffic counts and crashes within the study area was completed. This technical memorandum reports the results of an inventory of existing conditions for the GEIS update.

## Study Area

The study area for the traffic impact study will be that of the Amherst Boulevard Central District with some extended limits. The Amherst BCD is generally bound by Niagara Falls Boulevard to the west, Sheridan Drive to the south and I-290 to the north and east. The traffic study area will incorporate road segments and intersections further east to incorporate Millersport Highway and further north to include both I-290 ramps. The limits of the traffic study area compared to the Amherst BCD area are extended because it incorporates major intersections that are a point of entry and exit to Amherst BCD area. The study area is a mix of commercial and residential zoning and is a highly trafficked retail area. It is located near the UB North Campus approximately ten miles from downtown Buffalo.

## Roadway Network

The study area includes a network of Town, County, and State roadways. Primary access to the study area is provided by Niagara Falls Boulevard from the north and south, and Maple Road and Sheridan Drive from the east and west. The primary roadways within the study area are listed in Table 1.

Table 1: Primary Study Roadways

| Roadway | Segment | Jurisdiction | Functional Classification | AADT* |
|---|---|---|---|---|
| I-290 | Interchange 3 Eastbound<br>Interchange 3 Westbound | NYSDOT Region 5 | Principal Arterial Interstate | 109,548 |
| Millersport Highway (NYS Route 263) | Maple Rd to Sheridan Dr | NYSDOT Region 5 | Principal Arterial | 25,099 |

Table 1 Continued: Primary Study Roadways

| Roadway | Segment | Jurisdiction | Functional Classification | AADT* |
|---|---|---|---|---|
| Niagara Falls Boulevard (US Route 62) | I-290 WB Interchange to Eggert Rd | NYSDOT Region 5 | Principal Arterial | 30,297 |
| Sheridan Drive (NYS Route 324) | Eggert Rd to Millersport Hwy | NYSDOT Region 5 | Principal Arterial | 25,400 |
| Eggert Road | Sheridan Dr to Bailey Ave | Erie County | Minor Arterial | 9,173 |
| Maple Road | Niagara Falls Blvd to Millersport Hwy | Erie County | Principal Arterial | 23,079 |
| Sweet Home Road | Maple Rd to Sheridan Dr | Erie County | Local | 12,540 |
| Alberta Drive | Maple Rd to Eggert Rd | Town of Amherst | Local | 7,100 |
| North Bailey Avenue/Bailey Avenue | Ridge Lea Rd to Eggert Rd | Town of Amherst | Minor Arterial | 14,954 |
| Bowmart Parkway | Meyer Rd to Maple Rd | Town of Amherst | Local | 3,039 |
| Meyer Road | Niagara Falls Blvd to Bowmart Pkwy | Town of Amherst | Local | 3,440 |
| Ridge Lea Road | Niagara Falls Blvd to North Bailey Ave | Town of Amherst | Minor Arterial | 13,662 |
| Romney Road | Niagara Falls Blvd to North Bailey Ave | Town of Amherst | Local | 6,770 |

*Counts estimated in 2024

*Interstate-290* is a southeast/northwest road that acts as the border to north and east within the study area. The I-290 with interchanges connects to the Boulevard Central District study area at Niagara Falls Boulevard and Millersport Highway. The I-290 is classified as a principal arterial interstate. It is a six-lane divided freeway and has multiple exit and entrance ramps within the study area. The posted speed limit is 55 mph.

*Millersport Highway (NYS Route 263)* is a northeast/southwest highway that provides access to the UB North Campus and several intersecting arterials. It is classified as a principal arterial road and Millersport Highway is a four-lane road with a two-way center turn lane and auxiliary turning lanes in the study area. The connection to Maple Road from Millersport Highway is a partial clover leaf/diamond interchange. Interchange access from Millersport Highway is provided to I-290. The posted speed limit is 45 mph north of the I-290 interchange and 35 mph south of the I-290 interchange.

*Niagara Falls Boulevard (US Route 62)* is the main north/south access and acts as the western border to the study area. The properties along Niagara Falls Boulevard are primarily retail/commercial. Niagara Falls Boulevard is a principal arterial and a part of the National Highway System. Niagara Falls Boulevard is a six-lane divided highway with auxiliary turning lanes at major intersections. The posted speed limit is 40 mph.

*Sheridan Drive (NYS Route 324)* is an east/west road that is a main access and acts as the southern border to the study area. It is classified as a principal arterial highway. Sheridan Drive is a six-lane road with three lanes

in each direction and auxiliary turn lanes at the major intersections. The road has center medians with greenery. The posted speed limit is 40 mph.

*Maple Road* is an east/west roadway and is a major access route into the study area. The properties along Maple Road are primarily commercial/retail, along with a middle school. Maple Road is a principal arterial. Maple Road is a five-lane roadway between Niagara Falls Boulevard and North Bailey Avenue. Maple Road is a four-lane roadway east of Niagara Falls Boulevard. Maple Road has a two way left turn lane between Niagara Falls Boulevard and Sweet Home Road with auxiliary right turn lanes at multiple locations for driveways and major intersections. The posted speed is 45 mph.

*Eggert Road* is a northwest/southeast roadway classified as a minor arterial. Eggert Road is a four-lane roadway with auxiliary turn lanes at the intersection with Niagara Falls Boulevard. The posted speed limit is 35 mph.

*North Bailey Avenue* is a north/south road in the study area and is parallel to Niagara Falls Boulevard. North Bailey Avenue extends from Ridge Lea Road to Sheridan Drive and extends beyond Sheridan Drive as Bailey Avenue. North Bailey Avenue is a principal arterial. North Bailey Avenue is a two-lane road with a two-way center turn lane between Ridge Lea Road and Sheridan Drive. North Bailey Avenue shifts to a four-lane road with a two-way center turn lane at the Sheridan Driver intersection then changes back to a two-lane road south of Eggert Road. The posted speed limit is 35 mph.

*Ridge Lea Road* is an east/west road between Niagara Falls Boulevard and North Bailey Avenue. Ridge Lea Road is a minor arterial roadway. Ridge Lea Road serves as a connection for vehicles coming from the north on Niagara Falls Boulevard to North Bailey Avenue. Ridge Lea Road is a two-lane road with auxiliary turning lanes at the intersection with Niagara Falls Boulevard and the Boulevard Plaza driveway. In the segment between Niagara Falls Boulevard and the Consumer Plaza driveway there are two eastbound lanes. The posted speed is 35 mph.

*Romney Road* is an east/west road between Niagara Falls Boulevard and North Bailey Avenue. Romney Road is classified as a local road. It is a two-lane road with left turning lanes at intersections and right turn lanes at driveways. The posted speed limit is 30 mph.

*Meyer Road* is an east/west road between Niagara Falls Boulevard to just past Bowmart Parkway where it dead ends. Meyer Road is classified as a local road. Meyer Road is a two-lane roadway without auxiliary turn lanes. The posted speed limits is 30 mph.

*Alberta Drive* is a north/south roadway that runs parallel to Niagara Falls Boulevard. Alberta Drive is classified as a local road. Between Maple Road and Sheridan Drive, Alberta Drive is a four-lane road. South of Sheridan Drive, Alberta Drive changes to a two-lane roadway. The posted speed limit is 35 mph.

*Bowmart Parkway* is a north/south road between Meyer Road and Maple Road. Bowmart Parkway is classified as a local road. Bowmart parkway is a two-lane road with a left turn lane at the intersection with Maple Road. There is no posted speed limit on Bowmart Parkway; the assumed speed limit is 30 mph.

*Sweet Home Road* is a north/south road through the Boulevard Central District. Sweet Home Road is a four-lane highway and is classified as a minor arterial north of Maple Road. South of Maple Road, Sweet Home Road is a local two-lane roadway. Sweet Home Road has auxiliary turn lanes at the major intersections in the study area. The posted speed limit is 45 mph north of Maple Road and 35 mph south of Maple Road.

Table 2 describes the intersection control at each major intersection in the study area.

Table 2: Study Intersections

| Intersection | | Intersection Control |
|---|---|---|
| 1. | Niagara Falls Boulevard at WB I-290 Ramps | Signalized |
| 2. | Niagara Falls Boulevard at EB I-290 Ramps | Signalized/Slip Ramp |
| 3. | Niagara Falls Boulevard at Ridge Lea Road | Signalized |
| 4. | Niagara Falls Boulevard at Consumer Square | Signalized |
| 5. | Niagara Falls Boulevard at Romney Road | Signalized |
| 6. | Niagara Falls Boulevard at Meyer Road | Stop Control |
| 7. | Niagara Falls Boulevard at Maple Road & Brighton Road | Signalized |
| 8. | Niagara Falls Boulevard at Boulevard Mall Driveway | Signalized |
| 9. | Niagara Falls Boulevard at Tredwell Road | Signalized |
| 10. | Niagara Falls Boulevard at Sheridan Drive | Signalized |
| 11. | Niagara Falls Boulevard at Eggert Road | Signalized |
| 12. | Maple Road at Alberta Drive | Signalized |
| 13. | Maple Road at North Bailey Avenue | Signalized |
| 14. | Maple Road at Bowmart Parkway | Signalized |
| 15. | Maple Road at Hillcrest Drive | Signalized |
| 16. | Maple Road at Sweet Home Road | Signalized |
| 17. | Maple Road at Millersport Hwy Ramps SB | Signalized |
| 18. | Maple Road at Millersport Hwy Ramps NB | Signalized |
| 19. | Sheridan Drive at Eggert Road | Signalized |
| 20. | Sheridan Drive at Alberta Drive | Signalized |
| 21. | Sheridan Drive at Bailey Avenue | Signalized |
| 22. | Sheridan Drive at Sweet Home Road | Signalized |
| 23. | Sheridan Drive at Millersport Highway | Signalized |
| 24. | Eggert Road at Alberta Drive | Signalized |
| 25. | Eggert Road at Bailey Avenue | Signalized |
| 26. | North Bailey Avenue at Romney Road | Stop Control |
| 27. | North Bailey Avenue at Meyer Road | Signalized |
| 28. | Bailey Avenue at Emerson Drive | Stop Control |
| 29. | Bowmart Parkway at Meyer Road | Stop Control |

## Pedestrian Conditions

The pedestrian accommodations in the study area include sidewalks on at least one side of the road for all study roadways with the exceptions of

- Meyer Road east of N Bailey Avenue
- Bowmart Parkway
- Maple Road from Corporate Parkway to Flint Road
- Millersport Highway from Flint Road to the intersecting northern study limit.

All study area signalized intersections have pedestrian accommodations that include crosswalks and pedestrian signals. See Figure 1 for the Pedestrian and Bicycle Infrastructure Map prepared for the Town of Amherst on the Boulevard Central District development.

## Bicycle Conditions

Sweet Home Road is the only road with bicycle accommodations within the study area, which are striped on-street bicycle lanes. Millersport Highway is a designated bicycle route, but there are currently no exclusive or marked shared bicycle accommodations. The study area is a highly commercial location. Existing bicycle use is low in the area based on count data. See Figure 1 for the Pedestrian and Bicycle Infrastructure Map.

## Transit Conditions

There are 5 NFTA transit routes within the study area and 68 transit route stops. Three of the five NFTA transit routes operate every day of the week, the other two routes operate only on weekdays. The University at Buffalo also provides students, staff, and faculty with transportation through a bus/shuttle to off-campus destinations that are nearby shopping locations. Based on the Spring 2025 Semester schedule, the university bus, the stampede, has stops for different locations depending on the day of the week. Stops include Tops, Wegmans, Walmart, Target, and the Boulevard Mall from the campus. See Figure 2 for the Transit Map.

## Access Management

The Boulevard Central District is heavily developed with commercial and retail properties. There are many driveways on the main arterials in the study area like Niagara Falls Boulevard, Maple Road, and Sheridan Drive. Excessive vehicular access points to parcels from high volume roadways can cause additional crashes, limits on roadway capacity and longer travel times for motorists from the unpredictable entry and exit of vehicles from driveways.

Figure 1: Pedestrian and Bicycle Infrastructure Map




Figure 2: Transit Map



# Capacity Analysis Methodology

**Intersections**

The study intersections were analyzed using SYNCHRO 12[1], which is a computer program that implements the methods presented in the 7th Edition Highway Capacity Manual[2]. SYNCHRO determines the Level of Service (LOS), which is measured in terms of time Delay (seconds).

> Delay is a quantitative measure stated in terms of the control delay per vehicle for a 15-minute analysis period expressed in time (seconds). It is a qualitative measure of driver discomfort, frustration, fuel consumption and lost travel time.
> Level of Service criteria are stated in terms of the control delay (stated above) per vehicle and ranges from "A" to "F". Level of Service A is representative of a movement that is free flowing with minimal delay, while LOS F generally represents long delays. LOS D is generally considered acceptable in urban environments.

The ranges of delay for each level of service, as contained in the 7th Edition Highway Capacity Manual, are shown in Table 3.

Table 3: Intersection Level of Service Criteria

| Level of Service (LOS) | Unsignalized Intersections | Signalized Intersections | |
|---|---|---|---|
| | Delay (sec) | Delay (sec) | v/c ratio* |
| A | 0-10 | 0-10 | <1.0 |
| B | > 10-15 | > 10-20 | <1.0 |
| C | > 15-25 | > 20-35 | <1.0 |
| D | > 25-35 | > 35-55 | <1.0 |
| E | > 35-50 | > 55-80 | <1.0 |
| F | over 50 | over 80 | ≥1.0 |

* If the volume to capacity ratio is 1.0 or greater, the LOS is F

**Intersection Analysis**

Turning movement counts (TMCs) were collected at the study area intersections through a combination of turning movements collected by Quality Counts, Town of Amherst Miovision cameras, and NYSDOT Miovision cameras. The weekday PM data was collected on Thursday February 2, 2023, October 26, 2023, and November 16, 2023 from 3:00 PM to 6:00 PM. The Saturday midday count data was collected on Saturday February 4, 2023, October, 28, 2023, and November 18, 2023 from 12:00 PM to 3:00 PM. The study area

[1] Synchro Studio 12, Traffic Signal Optimization and Simulation Modeling Software, Version 12, Trafficware Corporation, Albany, California, 2023.
[2] Highway Capacity Manual, Transportation Research Board, National Research Council, Washington D.C., 2022.

weekday afternoon peak hour is 4:30 PM to 5:30 PM and the Saturday midday peak hour is 1:30 PM to 2:30 PM. Refer to Figure 3 in Appendix A for existing turning movement volumes. The turning movement counts had no adjustment factors applied to them. They were collected during similar months when schools and the University were in session. Counts were compared to previous counts taken at the study intersections, and they were similar not requiring any adjustments. The study area is primarily retail seeing heavy peaks during the winter months and holiday season.

Intersections along Niagara Falls Boulevard are a part of a coordinated traffic signal network. Coordinated traffic signal networks manage the progression of traffic on the mainline by increasing traffic flow and therefore decreasing congestion. Since a coordinated network prioritizes the mainline, side street approaches and mainline exclusive turning movements typically experience longer delays and lower levels of service. The existing condition results indicate that Niagara Falls Boulevard through movements are operating with acceptable levels of service of D or better, while the side street and mainline exclusive turning movements are experiencing longer delays, which is typical for a coordinated network. In addition, the values for delay are based on Synchro's Delay Method, which has more favorable results for shorter cycle lengths, while Niagara Falls Boulevard is on a cycle length of 180 seconds, which is the upper limit of recommended cycle lengths according to the Synchro Manual. Table 4 highlights the results of the level of service analysis for existing conditions.

Table 4: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| Niagara Falls Boulevard at I-290 Westbound Ramps (Signalized) | | | | | | | |
| Eastbound | *Left* | D (41.2) | 0.04 | 14 | D (43.2) | 0.06 | 18 |
| | *Right* | A (0.1) | 0.02 | 0 | A (7.5) | 0.04 | 16 |
| Westbound | *Left* | **E (72.1)** | **0.82** | **594** | **E (72.0)** | **0.80** | **541** |
| | *Thru* | **E (63.7)** | **0.82** | **550** | **E (69.1)** | **0.82** | **535** |
| | *Right* | **E (61.4)** | **0.80** | **511** | **E (59.1)** | **0.76** | **447** |
| Northbound | *Thru* | B (17.5) | 0.39 | 340 | C (21.2) | 0.39 | 363 |
| | *Right* | A (3.0) | 0.36 | 51 | A (5.3) | 0.37 | 99 |
| Southbound | *Thru/Right* | B (19.6) | 0.45 | 402 | B (19.7) | 0.52 | 500 |
| | *Intersection* | C (30.4) | - | - | C (30.4) | - | - |

*lowercase letters signify the HCM 6th edition Stop Control methodology was used
a: level-of-service
b: delay is measured in seconds
c: volume to capacity ratio
d: 95th queue length, measured in feet (queue length of stop-controlled intersections measured in number of vehicles)
m footnote on queue indicates that volume is metered by an upstream signal
# footnote on queue indicated that the volume modeled exceeds capacity

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at I-290 Eastbound Ramps (Signalized)** | | | | | | | |
| Eastbound | *Right* | **E (66.3)** | **0.79** | **292** | D (49.0) | 0.65 | 428 |
| Westbound | *Right* | A (0.4) | 0.26 | 0 | A (0.2) | 0.15 | 0 |
| Northbound | *Thru/Right* | A (0.1) | 0.25 | 0 | A (0.8) | 0.41 | 0 |
| Southbound | *Thru* | A (7.5) | 0.34 | 154 | C (27.9) | 0.53 | 573 |
| | *Right* | A (1.5) | 0.39 | 13 | A (7.1) | 0.48 | 61 |
| | *Intersection* | B (10.3) | - | - | B (16.2) | - | - |
| **Niagara Falls Boulevard at Ridge Lea Road (Signalized)** | | | | | | | |
| Eastbound | *Left* | **E (66.4)** | **0.50** | **187** | **E (56.7)** | **0.39** | **178** |
| | *Thru/Right* | D (53.8) | 0.21 | 120 | D (50.4) | 0.21 | 147 |
| Westbound | *Left/Thru* | **F (107.2)** | **0.71** | **170** | **E (73.0)** | **0.35** | **167** |
| | *Right* | D (38.3) | 0.67 | 351 | C (22.1) | 0.50 | 319 |
| Northbound | *Left* | **F (96.0)** | **0.35** | **m59** | **F (105.0)** | **0.49** | **m103** |
| | *Thru/Right* | B (12.4) | 0.47 | 85 | C (28.6) | 0.79 | 113 |
| Southbound | *Left* | **F (83.6)** | **0.83** | **371** | **E (78.1)** | **0.61** | **463** |
| | *Thru/Right* | A (9.1) | 0.36 | 204 | B (12.1) | 0.43 | 227 |
| | *Intersection* | C (32.6) | - | - | C (33.3) | - | - |
| **Niagara Falls Boulevard at Consumer Plaza (Signalized)** | | | | | | | |
| Eastbound | *Left/Thru* | **E (67.7)** | **0.22** | **60** | **F (174.1)** | **0.82** | **#103** |
| | *Right* | A (0.1) | 0.03 | 0 | A (0.8) | 0.10 | 0 |
| Westbound | *Left/Thru* | **E (67.1)** | **0.44** | **207** | **F (96.9)** | **0.82** | **296** |
| | *Right* | A (9.0) | 0.42 | 75 | A (9.8) | 0.54 | 82 |
| Northbound | *Left* | **F (93.2)** | **0.20** | **m40** | **F (124.6)** | **0.32** | **m70** |
| | *Thru* | **E (56.9)** | **0.56** | **480** | D (44.9) | 0.53 | 516 |
| | *Right* | B (11.7) | 0.18 | m107 | A (9.6) | 0.17 | 24 |
| Southbound | *Left* | **F (94.3)** | **0.81** | **250** | **F (83.4)** | **0.72** | **#491** |
| | *Thru/Right* | B (16.7) | 0.40 | 313 | A (7.4) | 0.39 | 258 |
| | *Intersection* | D (39.4) | - | - | C (34.8) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at Romney Road (Signalized)** | | | | | | | |
| Eastbound | *Left/Thru* | **F (345.3)** | **1.54** | **#288** | **F (158.2)** | **1.04** | **#265** |
| | *Right* | A (0.5) | 0.08 | 0 | A (0.8) | 0.09 | 4 |
| Westbound | *Left* | **F (110.8)** | **0.84** | **234** | **F (117.4)** | **0.94** | **304** |
| | *Thru/Right* | **F (84.4)** | **0.85** | **320** | **E (65.5)** | **0.77** | **333** |
| Northbound | *Left* | **F (81.6)** | **0.38** | **76** | **F (84.2)** | **0.53** | **115** |
| | *Thru* | C (25.9) | 0.24 | 312 | D (39.5) | 0.30 | 394 |
| | *Right* | B (13.6) | 0.05 | 46 | C (23.3) | 0.17 | 150 |
| Southbound | *Left* | **F (118.5)** | **0.77** | **264** | **F (108.2)** | **0.82** | **352** |
| | *Thru/Right* | A (2.5) | 0.25 | 26 | A (6.8) | 0.28 | 124 |
| | *Intersection* | D (49.7) | - | - | D (46.5) | - | - |
| **Niagara Falls Boulevard at Meyer Road (Unsignalized)** | | | | | | | |
| Eastbound | *Left/Thru/Right* | c (17.6) | 0.05 | 0.1 | **f (83.7)** | **0.29** | **1** |
| Westbound | *Left/Thru/Right* | d (31.9) | 0.24 | 0.9 | **f (119.0)** | **0.78** | **4.1** |
| Northbound | *Left* | b (11.6) | 0.00 | 0 | c (15.3) | 0.0 | 0 |
| Southbound | *Left* | c (18.0) | 0.20 | 0.8 | d (27.2) | 0.36 | 1.6 |
| | *Intersection* | n/a | | | n/a | | |
| **Niagara Falls Boulevard at Maple Road and Brighton Road (Signalized)** | | | | | | | |
| Eastbound | *Left* | **E (55.8)** | **0.55** | **186** | D (54.4) | 0.54 | 197 |
| | *Thru/Right* | **F (89.2)** | **0.79** | **245** | **F (88.8)** | **0.80** | **260** |
| Westbound | *Left* | **F (79.3)** | **0.88** | **#384** | **E (75.3)** | **0.86** | **#357** |
| | *Thru* | **E (74.1)** | **0.63** | **287** | **E (70.8)** | **0.52** | **236** |
| | *Right* | B (10.5) | 0.52 | 86 | B (10.6) | 0.54 | 88 |
| Northbound | *Left* | **F (102.0)** | **0.61** | **146** | **F (101.4)** | **0.58** | **130** |
| | *Thru* | C (31.3) | 0.35 | 298 | C (34.5) | 0.44 | 385 |
| | *Right* | A (4.1) | 0.26 | 57 | A (4.2) | 0.29 | 60 |
| Southbound | *Left* | **F (101.9)** | **0.74** | **208** | **F (93.9)** | **0.76** | **198** |
| | *Thru/Right* | B (17.5) | 0.34 | 167 | C (21.7) | 0.37 | 224 |
| | *Intersection* | D (45.5) | - | - | D (45.8) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| Niagara Falls Boulevard at Boulevard Mall Driveway (Signalized) | | | | | | | |
| Eastbound | *Left/Thru/Right* | B (16.7) | 0.05 | 14 | B (17.8) | 0.12 | 24 |
| Westbound | *Left* | C (21.7) | 0.09 | 26 | C (25.8) | 0.15 | 34 |
| | *Thru/Right* | B (12.4) | 0.12 | 22 | B (13.2) | 0.17 | 28 |
| Northbound | *Left* | C (22.9) | 0.04 | 14 | C (26.4) | 0.04 | 13 |
| | *Thru/Right* | A (7.7) | 0.31 | 126 | B (10.4) | 0.40 | 154 |
| Southbound | *Left* | C (22.1) | 0.15 | 34 | C (25.6) | 0.24 | 51 |
| | *Thru/Right* | A (5.5) | 0.31 | 129 | A (5.8) | 0.31 | 121 |
| | *Intersection* | A (7.2) | - | - | A (9.1) | - | - |
| Niagara Falls Boulevard at Treadwell Road (Signalized) | | | | | | | |
| Eastbound | *Left/Thru/Right* | C (20.1) | 0.19 | 49 | B (19.1) | 0.19 | 48 |
| Westbound | *Left* | C (26.3) | 0.17 | 48 | C (23.5) | 0.13 | 38 |
| | *Thru/Right* | B (15.0) | 0.10 | 28 | B (12.4) | 0.14 | 33 |
| Northbound | *Left* | D (37.1) | 0.21 | 62 | C (33.1) | 0.24 | 71 |
| | *Thru/Right* | B (10.7) | 0.31 | 246 | B (11.8) | 0.38 | 242 |
| Southbound | *Left* | D (35.4) | 0.11 | 37 | C (34.8) | 0.14 | 44 |
| | *Thru/Right* | B (13.8) | 0.40 | 269 | B (14.4) | 0.41 | 248 |
| | *Intersection* | B (13.5) | - | - | B (14.0) | - | - |
| Niagara Falls Boulevard at Sheridan Drive (Signalized) | | | | | | | |
| Eastbound | *Left* | **F (96.7)** | **0.81** | **268** | **F (90.3)** | **0.76** | **274** |
| | *Thru/Right* | **E (73.0)** | **0.67** | **330** | **E (67.0)** | **0.54** | **280** |
| Westbound | *Left* | **F (97.6)** | **0.79** | **238** | **F (98.6)** | **0.75** | **200** |
| | *Thru* | **E (78.1)** | **0.76** | **359** | **E (79.2)** | **0.75** | **339** |
| | *Right* | A (0.5) | 0.10 | 0 | A (0.8) | 0.14 | 0 |
| Northbound | *Thru/Right* | B (19.6) | 0.27 | 62 | C (22.5) | 0.29 | 122 |
| Southbound | *Left* | **F (99.4)** | **0.71** | **171** | **F (98.6)** | **0.76** | **208** |
| | *Thru* | C (23.2) | 0.33 | 315 | C (22.2) | 0.26 | 242 |
| | *Right* | A (2.9) | 0.34 | 56 | A (2.9) | 0.36 | 57 |
| | *Intersection* | **E (55.3)** | - | - | D (54.1) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at Eggert Road (Signalized)** | | | | | | | |
| Eastbound | *Thru* | **E (79.6)** | **0.53** | **197** | **F (88.0)** | **0.59** | **174** |
| | *Right* | B (14.3) | 0.48 | 83 | B (16.1) | 0.50 | 73 |
| Westbound | *Left* | **F (82.4)** | **0.39** | **99** | **F (104.1)** | **0.57** | **115** |
| | *Thru/Right* | **F (86.4)** | **0.77** | **284** | **F (85.7)** | **0.75** | **205** |
| Northbound | *Left* | **F (109.1)** | **0.80** | **275** | **F (110.8)** | **0.74** | **207** |
| | *Thru/Right* | C (24.3) | 0.27 | 255 | B (18.8) | 0.27 | 239 |
| Southbound | *Left* | D (36.5) | 0.30 | 124 | **E (61.2)** | **0.30** | **130** |
| | *Thru/Right* | B (13.4) | 0.36 | 315 | A (3.9) | 0.30 | 264 |
| *Intersection* | | D (40.4) | - | - | D (35.1) | - | - |
| **Maple Road at Alberta Drive (Signalized)** | | | | | | | |
| Eastbound | *Left* | B (12.6) | 0.08 | 23 | B (12.4) | 0.13 | 36 |
| | *Thru* | C (26.4) | 0.59 | 170 | C (25.5) | 0.58 | 166 |
| | *Right* | A (6.4) | 0.34 | 47 | A (6.3) | 0.36 | 48 |
| Westbound | *Left* | B (15.2) | 0.41 | 98 | B (15.1) | 0.43 | 103 |
| | *Thru/Right* | B (18.0) | 0.43 | 187 | B (19.1) | 0.38 | 152 |
| Northbound | *Left* | B (18.2) | 0.46 | 124 | C (20.3) | 0.55 | 140 |
| | *Thru/Right* | B (12.6) | 0.32 | 104 | B (11.3) | 0.37 | 106 |
| Southbound | *Left* | B (14.1) | 0.05 | 16 | B (13.9) | 0.04 | 14 |
| | *Thru/Right* | B (14.9) | 0.24 | 51 | B (18.7) | 0.31 | 61 |
| *Intersection* | | B (18.1) | - | - | B (18.2) | - | - |
| **Maple Road at N Bailey Avenue (Signalized)** | | | | | | | |
| Eastbound | *Left* | C (23.2) | 0.34 | 57 | C (25.9) | 0.45 | 89 |
| | *Thru* | D (38.4) | 0.67 | 242 | D (42.7) | 0.69 | 240 |
| | *Right* | A (0.3) | 0.08 | 0 | A (0.7) | 0.15 | 0 |
| Westbound | *Left* | C (25.2) | 0.59 | 150 | C (26.0) | 0.56 | 154 |
| | *Thru/Right* | C (29.2) | 0.68 | 288 | C (33.6) | 0.72 | 249 |
| Northbound | *Left* | B (20.0) | 0.22 | 60 | B (18.2) | 0.28 | 78 |
| | *Thru* | D (43.5) | 0.75 | 341 | D (48.4) | 0.77 | 335 |
| | *Right* | A (1.9) | 0.25 | 10 | A (1.7) | 0.26 | 6 |
| Southbound | *Left* | **E (61.0)** | **0.92** | **#317** | C (23.6) | 0.64 | 200 |
| | *Thru* | D (37.5) | 0.65 | 348 | C (32.9) | 0.61 | 359 |
| | *Right* | A (0.7) | 0.19 | 0 | A (3.1) | 0.21 | 28 |
| *Intersection* | | C (32.7) | - | - | C (30.8) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| Maple Road at Bowmart Parkway (Signalized) | | | | | | | |
| Eastbound | *Left* | A (6.8) | 0.30 | 32 | C (31.9) | 0.37 | 83 |
| | *Thru* | A (6.0) | 0.37 | 125 | A (6.6) | 0.40 | 133 |
| Westbound | *Thru/Right* | B (14.0) | 0.60 | 250 | B (15.6) | 0.62 | 198 |
| Southbound | *Left* | C (34.0) | 0.58 | 162 | C (30.2) | 0.56 | 149 |
| | *Right* | A (8.3) | 0.24 | 37 | A (0.9) | 0.12 | 11 |
| *Intersection* | | B (12.5) | - | - | B (13.4) | - | - |
| Maple Road at Hillcrest Drive (Signalized) | | | | | | | |
| Eastbound | *Left/Thru/Right* | A (8.0) | 0.45 | 228 | A (4.6) | 0.37 | 182 |
| Westbound | *Left* | C (20.9) | 0.06 | 24 | C (20.2) | 0.04 | 13 |
| | *Thru/Right* | A (7.0) | 0.62 | 200 | A (2.7) | 0.41 | 115 |
| Northbound | *Left/Thru/Right* | A (9.5) | 0.22 | 33 | A (4.6) | 0.10 | 12 |
| Southbound | *Left* | C (21.7) | 0.11 | 31 | A (0.0) | 0.00 | 0 |
| | *Thru/Right* | A (0.0) | 0.01 | 0 | B (16.7) | 0.16 | 6 |
| *Intersection* | | A (7.7) | - | - | A (3.7) | - | - |
| Maple Road at Sweet Home Road (Signalized) | | | | | | | |
| Eastbound | *Left* | **E (55.7)** | **0.83** | **336** | C (22.7) | 0.65 | 228 |
| | *Thru* | D (37.6) | 0.44 | 331 | C (23.2) | 0.32 | 251 |
| | *Right* | A (2.4) | 0.12 | 17 | A (0.4) | 0.09 | 3 |
| Westbound | *Left* | C (26.7) | 0.50 | 109 | B (14.1) | 0.17 | 34 |
| | *Thru* | D (48.8) | 0.78 | #666 | C (31.9) | 0.47 | 370 |
| | *Right* | B (10.8) | 0.37 | 80 | A (3.6) | 0.13 | 27 |
| Northbound | *Left* | D (40.3) | 0.51 | 110 | D (37.7) | 0.40 | 97 |
| | *Thru* | **E (63.6)** | **0.72** | **457** | **E (65.5)** | **0.72** | **283** |
| | *Right* | A (3.3) | 0.23 | 23 | A (0.9) | 0.17 | 0 |
| Southbound | *Left* | D (42.9) | 0.64 | 192 | D (43.1) | 0.57 | 146 |
| | *Thru* | **E (69.5)** | **0.85** | **#653** | **E (62.9)** | **0.72** | **306** |
| | *Right* | B (19.7) | 0.72 | 291 | A (8.6) | 0.60 | 83 |
| *Intersection* | | D (41.5) | - | - | C (29.8) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Maple Road at Millersport Highway West (Signalized)** | | | | | | | |
| Eastbound | *Left* | A (0.9) | 0.03 | m2 | A (0.4) | 0.02 | m1 |
| | *Thru* | A (0.9) | 0.27 | 28 | A (1.1) | 0.23 | 10 |
| Westbound | *Thru* | A (3.0) | 0.31 | 108 | A (1.2) | 0.24 | 17 |
| | *Right* | A (0.2) | 0.15 | 0 | A (0.2) | 0.12 | 0 |
| Southbound | *Left* | **E (74.0)** | **0.29** | **80** | **E (65.1)** | **0.15** | **37** |
| | *Right* | C (21.5) | 0.58 | 78 | C (22.8) | 0.58 | 60 |
| *Intersection* | | A (4.3) | - | - | A (3.0) | - | - |
| **Maple Road at Millersport Highway East (Signalized)** | | | | | | | |
| Eastbound | *Left* | C (34.4) | 0.48 | 138 | A (1.8) | 0.14 | 9 |
| | *Thru* | C (23.0) | 0.46 | 457 | A (1.1) | 0.20 | 26 |
| Westbound | *Thru/Right* | C (24.4) | 0.56 | 488 | A (4.6) | 0.31 | 178 |
| Northbound | *Left* | C (32.3) | 0.36 | 72 | D (54.9) | 0.21 | 65 |
| | *Thru/Right* | **E (62.3)** | **0.36** | **#690** | C (33.2) | 0.85 | 179 |
| *Intersection* | | C (32.5) | - | - | A (9.9) | - | - |
| **Sheridan Drive at Eggert Road (Signalized)** | | | | | | | |
| Eastbound | *Left* | C (27.2) | 0.29 | 47 | C (29.8) | 0.41 | 73 |
| | *Thru* | C (21.1) | 0.42 | 169 | C (20.5) | 0.45 | 188 |
| | *Right* | A (3.9) | 0.25 | 41 | A (3.5) | 0.22 | 34 |
| Westbound | *Thru/Right* | C (22.5) | 0.56 | 229 | C (20.6) | 0.51 | 210 |
| South eastbound | *Left/Thru/Right* | D (46.5) | 0.77 | #191 | D (40.2) | 0.58 | 126 |
| North westbound | *Left/Thru/Right* | D (41.9) | 0.66 | 151 | D (39.7) | 0.63 | 141 |
| *Intersection* | | C (26.9) | - | - | C (24.1) | - | - |
| **Sheridan Drive at Alberta Drive (Signalized)** | | | | | | | |
| Eastbound | *Left* | **F (86.3)** | **0.73** | **237** | **F (85.7)** | **0.77** | **269** |
| | *Thru/Right* | B (16.0) | 0.24 | 193 | C (20.6) | 0.33 | 262 |
| Westbound | *Left* | **F (102.4)** | **0.52** | **m126** | **F (103.4)** | **0.57** | **m142** |
| | *Thru/Right* | A (9.4) | 0.40 | 94 | B (11.4) | 0.44 | 102 |
| Northbound | *Left/Thru/Right* | **E (75.2)** | **0.58** | **98** | **E (76.7)** | **0.71** | **144** |
| Southbound | *Left* | **E (56.9)** | **0.48** | **174** | D (52.4) | 0.47 | 165 |
| | *Thru/Right* | **E (55.5)** | **0.69** | **306** | **E (56.6)** | **0.75** | **374** |
| *Intersection* | | C (28.8) | - | - | C (33.2) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Sheridan Drive at Bailey Avenue (Signalized)** | | | | | | | |
| Eastbound | *Left* | **F (105.8)** | **0.69** | **219** | **F (104.9)** | **0.77** | **320** |
| | *Thru/Right* | B (20.0) | 0.33 | 128 | C (21.9) | 0.38 | 144 |
| Westbound | *Left* | **F (123.3)** | **0.68** | **215** | **F (108.1)** | **0.73** | **172** |
| | *Thru/Right* | B (10.3) | 0.43 | 75 | C (25.6) | 0.50 | 434 |
| Northbound | *Left* | D (46.3) | 0.43 | 115 | D (43.9) | 0.43 | 121 |
| | *Thru/Right* | **E (71.7)** | **0.79** | **295** | **E (72.5)** | **0.79** | **286** |
| Southbound | *Left* | D (50.1) | 0.54 | 138 | D (51.5) | 0.64 | 185 |
| | *Thru/Right* | **E (63.5)** | **0.68** | **263** | **E (60.1)** | **0.62** | **254** |
| *Intersection* | | D (39.7) | - | - | D (45.8) | - | - |
| **Sheridan Drive at Sweet Home Road (Signalized)** | | | | | | | |
| Eastbound | *Left* | **E (76.6)** | **0.64** | **257** | **E (58.1)** | **0.60** | **268** |
| | *Thru/Right* | D (43.3) | 0.33 | 367 | C (34.5) | 0.29 | 332 |
| Westbound | *Left* | **F (86.2)** | **0.54** | **125** | **F (84.3)** | **0.43** | **92** |
| | *Thru/Right* | D (38.1) | 0.53 | 413 | C (33.8) | 0.43 | 334 |
| Northbound | *Left* | D (51.9) | 0.15 | 52 | **E (62.8)** | **0.22** | **65** |
| | *Thru/Right* | **E (79.5)** | **0.84** | **399** | **F (83.6)** | **0.76** | **274** |
| Southbound | *Left* | D (42.9) | 0.46 | 113 | D (49.0) | 0.48 | 147 |
| | *Thru/Right* | D (48.1) | 0.65 | 396 | D (46.0) | 0.55 | 289 |
| *Intersection* | | D (48.8) | - | - | D (42.7) | - | - |
| **Sheridan Drive at Millersport Highway (Signalized)** | | | | | | | |
| Eastbound | *Left* | **E (57.4)** | **0.72** | **#318** | D (45.4) | 0.66 | 260 |
| | *Thru/Right* | D (36.8) | 0.50 | 234 | C (26.7) | 0.39 | 180 |
| Westbound | *Left* | **E (58.5)** | **0.63** | **203** | D (47.9) | 0.42 | 116 |
| | *Thru/Right* | D (43.4) | 0.70 | 272 | D (37.9) | 0.65 | 200 |
| Northbound | *Left* | C (24.2) | 0.17 | 43 | C (22.6) | 0.16 | 50 |
| | *Thru* | D (38.8) | 0.48 | 205 | D (40.7) | 0.62 | 190 |
| | *Right* | A (7.8) | 0.26 | 49 | A (7.0) | 0.27 | 36 |
| Southbound | *Left* | C (24.5) | 0.27 | 86 | C (23.6) | 0.29 | 81 |
| | *Thru* | D (39.9) | 0.68 | 354 | C (33.8) | 0.41 | 161 |
| | *Right* | A (5.9) | 0.45 | 68 | A (7.0) | 0.47 | 67 |
| *Intersection* | | D (37.4) | - | - | C (31.4) | - | - |

Table 4 Continued: Intersection LOS Analysis of Existing Conditions

| Approach | | Weekday PM | | | Saturday Midday | | |
|---|---|---|---|---|---|---|---|
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Eggert Road at Alberta Drive (Signalized)** | | | | | | | |
| Eastbound | *Left/Thru/Right* | A (5.0) | 0.20 | 40 | A (6.3) | 0.27 | 39 |
| Westbound | *Left/Thru/Right* | A (4.8) | 0.21 | 43 | A (5.8) | 0.22 | 32 |
| Northbound | *Left/Thru/Right* | B (13.2) | 0.07 | 20 | A (9.3) | 0.07 | 14 |
| Southbound | *Left/Thru/Right* | B (12.8) | 0.32 | 49 | B (11.1) | 0.37 | 42 |
| | *Intersection* | A (6.1) | - | - | A (7.0) | - | - |
| **Eggert Road at Bailey Avenue (Signalized)** | | | | | | | |
| Eastbound | *Left/Thru/Right* | B (16.6) | 0.48 | 104 | B (16.5) | 0.45 | 87 |
| Westbound | *Left/Thru/Right* | B (17.0) | 0.53 | 114 | B (15.7) | 0.53 | 100 |
| Northbound | *Left* | A (7.8) | 0.22 | 43 | A (7.1) | 0.16 | 32 |
| | *Thru/Right* | C (20.1) | 0.65 | 213 | C (20.1) | 0.66 | 209 |
| Southbound | *Left* | A (8.6) | 0.29 | 46 | A (8.6) | 0.32 | 48 |
| | *Thru/Right* | B (13.0) | 0.32 | 83 | B (11.5) | 0.28 | 80 |
| | *Intersection* | B (15.7) | - | - | B (15.1) | - | - |
| **N Bailey Avenue at Romney Road (Unsignalized)** | | | | | | | |
| Eastbound | *Left* | **e (49.1)** | **0.20** | **0.7** | **f (85.6)** | **0.41** | **1.6** |
| | *Right* | c (16.5) | 0.40 | 1.9 | c (24.3) | 0.59 | 3.8 |
| Northbound | *Left* | a (9.3) | 0.15 | 0.5 | b (10.2) | 0.22 | 0.9 |
| | *Intersection* | n/a | | | n/a | | |
| **N Bailey Avenue at Meyer Road (Signalized)** | | | | | | | |
| Eastbound | *Left/Thru/Right* | C (25.4) | 0.57 | 131 | C (26.0) | 0.52 | 125 |
| Westbound | *Left/Thru* | B (19.8) | 0.08 | 32 | C (23.8) | 0.06 | 26 |
| | *Right* | A (6.5) | 0.28 | 38 | A (8.1) | 0.28 | 41 |
| Northbound | *Left* | A (7.0) | 0.10 | 17 | A (6.5) | 0.11 | 15 |
| | *Thru/Right* | B (11.0) | 0.62 | 279 | A (9.7) | 0.60 | 265 |
| Southbound | *Left* | A (9.2) | 0.28 | 46 | A (6.6) | 0.17 | 27 |
| | *Thru/Right* | B (12.4) | 0.68 | 326 | B (13.5) | 0.76 | 399 |
| | *Intersection* | B (12.7) | - | - | B (12.7) | - | - |
| **Bowmart Parkway at Meyer Road (Unsignalized)** | | | | | | | |
| Westbound | *Left* | a (7.6) | 0.01 | 0 | a (7.5) | 0.00 | 0 |
| Northbound | *Left* | a (9.9) | 0.18 | 0.6 | a (9.7) | 0.16 | 0.6 |
| | *Intersection* | n/a | | | n/a | | |

The majority of intersections are operating overall at acceptable levels of service (D or better). The only intersection currently experiencing an overall LOS of E or F is Niagara Falls Boulevard at Sheridan Drive. This is a high-volume intersection of US Route 62 and NY State Route 324. The movements experiencing a LOS E or F at this intersection include eastbound left and through/right, westbound left and through, and southbound left.

There are many intersections with movements experiencing a LOS E or F. The majority of these movements are left turn lanes. Lower levels of service are common on exclusive turn lanes as most of the green time at signals is given to the major through movements to move large volumes of traffic, creating delay on the lower demand movements. Movements experiencing a LOS E or F are listed below. See Appendix A, Figures 4 and 5 for intersection level of service maps for the Weekday PM and Saturday Midday peaks respectively.

Movements:

- Niagara Falls Boulevard at I-290 Westbound Ramps westbound left, through, and right.
- Niagara Falls Boulevard at I-290 Eastbound Ramps westbound right.
- Niagara Falls Boulevard at Ridge Lea Road eastbound left, westbound left, northbound left, southbound left.
- Niagara Falls Boulevard at Consumer Plaza Drive eastbound left/through, westbound left/through, northbound left and through.
- Niagara Falls Boulevard at Romney Road eastbound left/through, westbound left and through/right, northbound left, southbound left.
- Niagara Falls Boulevard at Meyer Road eastbound left/through/right and westbound left/through/right.
- Niagara Falls Boulevard at Maple Road and Brighton Road eastbound left and through/right, westbound left and through, northbound left, southbound left.
- Niagara Falls Boulevard at Sheridan Drive eastbound left and through/right, westbound left and through, and southbound left.
- Niagara Falls Boulevard at Eggert Road eastbound through, westbound left and through/right, northbound left, and southbound left.
- Maple Road at N Bailey Avenue southbound left.
- Maple Road at Home Sweet Road eastbound left, northbound through, and southbound through.
- Maple Road at Millersport Highway West southbound left.
- Maple Road at Millersport Highway East northbound through/right.
- Sheridan Drive at Alberta Drive eastbound left, westbound left, northbound left/through/right, and southbound left and through/right.
- Sheridan Drive at Bailey Avenue eastbound left, westbound left, northbound through/right, and southbound through/right.
- Sheridan Drive at Sweet Home Road eastbound left, westbound left, and northbound left and through/right.
- Sheridan Drive at Millersport Highway eastbound left and westbound left.
- North Bailey at Romney Road eastbound left.

## Crash Analysis

A crash analysis was completed for the study area intersections and road segments. There was a total of 1,032 crashes within the study area over a three-year period from May 2021 through May 2024. The most common type of crash within the study area was rear end, with a total of 423 out of 1,032 crashes (40%). Then next most common types were left turn and overtaking with a combined total of 180 crashes (30%). Detailed crash analyses are provided in Appendix B. There were 15 crashes with a pedestrian and 8 crashes with a bicyclist. All of the pedestrian and bicyclist crashes resulted in an injury. There were no fatalities.

A total of 592 crashes occurred at the study intersections and 440 crashes occurred along roadway segments. Table 5 and Table 6 are a summary of the predominant crash types and severity at each intersection. Crash maps within the study area are provided in Appendix B. See Figure 6 for a crash heat map.

Intersections that had a more concentrated number of crashes over the analysis period included the following:

- Maple Road at Sweet Home Road (58 crashes)
- Sheridan Drive at Millersport Highway (50 crashes)
- Niagara Falls Boulevard at Ridge Lea Road (49 crashes)
- Maple Road at North Bailey Avenue (45 crashes)
- Niagara Falls Boulevard at Maple Road and Brighton Road (44 crashes)
- Sheridan Drive at Bailey Avenue (37 crashes)
- Sheridan Drive at Sweet Home Road (33 crashes)
- Niagara Falls Boulevard at Romney Road (30 crashes)
- Niagara Falls Boulevard at Sheridan Drive (30 crashes)
- Sheridan Drive at Alberta Drive (23 crashes)
- Maple Road at Alberta Drive (17 crashes)

Two intersections in particular had a significantly high number of crashes (>50 crash), Maple Road at Sweet Home Road and Sheridan Drive at Millersport Highway. The majority of the crashes were rear ends with a listed cause of following too closely and driver inattention. Congestion increases the chances of rear ends with unexpected stops and increased driver frustration. The second typical crash for Maple Road at Sweet Home Road was left turn. These can be caused by disregarding traffic signals, driver inattention /distraction or failing to yield the right of way, which is noted in the crash reports as the primary cause. The signal operates on permissive and protective left turns for all approaches. Crash diagrams can be found in Appendix B.

Figure 6: Crash Heat Map




Table 5: Intersection Crash Types

| Intersection Name | Less Severe | | | | | Severe | | | | | Total Crashes |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | Rear End | Overtaking | Sideswipe | Right Turn | Total | Right Angle | Left Turn | Head On | Pedestrian Bicyclist | Total | |
| Maple Rd at Sweet Home Road | 31 | 4 | 7 | 2 | 44 | 1 | 13 | 0 | 0 | 14 | 58 |
| Sheridan Dr at Millersport Hwy | 27 | 10 | 4 | 4 | 45 | 2 | 3 | 0 | 0 | 5 | 50 |
| Niagara Falls Blvd at Ridge Lea Road | 16 | 12 | 4 | 3 | 35 | 1 | 9 | 0 | 4 | 14 | 49 |
| Maple Rd at North Bailey Ave | 21 | 5 | 2 | 2 | 30 | 2 | 12 | 1 | 0 | 15 | 45 |
| Niagara Falls Blvd at Maple Rd & Brighton Rd | 26 | 6 | 3 | 0 | 35 | 2 | 6 | 0 | 1 | 9 | 44 |
| Sheridan Dr at Bailey Ave | 15 | 7 | 4 | 0 | 26 | 8 | 3 | 0 | 0 | 11 | 37 |
| Sheridan Dr at Sweet Home Rd | 12 | 3 | 0 | 3 | 18 | 7 | 6 | 1 | 1 | 15 | 33 |
| Niagara Falls Blvd at Romney Rd | 16 | 4 | 1 | 3 | 24 | 1 | 3 | 1 | 1 | 6 | 30 |
| Niagara Falls Blvd at Sheridan Dr | 14 | 4 | 1 | 3 | 22 | 1 | 5 | 0 | 2 | 8 | 30 |
| Sheridan Dr at Alberta Dr | 10 | 4 | 0 | 1 | 15 | 6 | 1 | 0 | 1 | 8 | 23 |
| Maple Rd at Alberta Dr | 8 | 1 | 0 | 0 | 9 | 3 | 4 | 0 | 1 | 8 | 17 |
| Niagara Falls Blvd at Eggert Rd | 9 | 3 | 1 | 0 | 13 | 3 | 0 | 0 | 0 | 3 | 16 |
| North Bailey Ave at Meyer Rd | 6 | 1 | 2 | 1 | 10 | 3 | 3 | 0 | 0 | 6 | 16 |
| Eggert Rd at Bailey Ave | 3 | 2 | 2 | 2 | 9 | 2 | 3 | 0 | 1 | 6 | 15 |
| Maple Rd at Bowmart Pkwy | 4 | 4 | 0 | 1 | 9 | 2 | 3 | 0 | 0 | 5 | 14 |
| Sheridan Dr at Eggert Rd | 3 | 5 | 1 | 0 | 9 | 1 | 2 | 0 | 1 | 4 | 13 |
| Niagara Falls Blvd at Consumer Square | 7 | 2 | 0 | 0 | 9 | 1 | 2 | 0 | 0 | 3 | 12 |
| Maple Rd at Hillcrest Dr | 3 | 3 | 2 | 0 | 8 | 1 | 3 | 0 | 0 | 4 | 12 |
| Niagara Falls Blvd at WB I-290 Ramps | 5 | 1 | 0 | 2 | 8 | 1 | 1 | 1 | 0 | 3 | 11 |
| Niagara Falls Blvd at Meyer Rd | 2 | 2 | 0 | 2 | 6 | 0 | 5 | 0 | 0 | 5 | 11 |
| Bailey Ave at Emerson Dr | 2 | 0 | 1 | 0 | 3 | 8 | 0 | 0 | 0 | 8 | 11 |
| Niagara Falls Blvd at Tredwell Rd | 8 | 0 | 0 | 0 | 8 | 2 | 0 | 0 | 0 | 2 | 10 |
| Niagara Falls Blvd at EB I-290 Ramps | 6 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 6 |
| Niagara Falls Blvd at Boulevard Mall Driveway | 5 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 5 |
| Maple Rd at Millersport Hwy Ramps NB | 4 | 0 | 0 | 1 | 5 | 0 | 0 | 0 | 0 | 0 | 5 |
| Eggert Rd at Alberta Dr | 2 | 1 | 0 | 0 | 3 | 1 | 1 | 0 | 0 | 2 | 5 |
| North Bailey Ave at Alberta Dr | 1 | 0 | 0 | 0 | 1 | 0 | 4 | 0 | 0 | 4 | 5 |
| Bowmart Pkwy at Meyer Rd | 2 | 1 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 2 | 5 |
| Maple Rd at Millersport Hwy Ramps SB | 2 | 1 | 0 | 1 | 4 | 0 | 0 | 0 | 0 | 0 | 4 |
| Total | 270 | 86 | 35 | 31 | 422 | 59 | 94 | 4 | 13 | 169 | 592 |

Table 6: Intersection Crash Severity

| Intersection Name | Property Damage | Injury | Fatal | Total Crashes |
|---|---|---|---|---|
| Niagara Falls Blvd at WB I-290 Ramps | 7 | 4 | 0 | 11 |
| Niagara Falls Blvd at EB I-290 Ramps | 3 | 3 | 0 | 6 |
| Niagara Falls Blvd at Ridge Lea Road | 31 | 18 | 0 | 49 |
| Niagara Falls Blvd at Consumer Square | 8 | 4 | 0 | 12 |
| Niagara Falls Blvd at Romney Rd | 24 | 6 | 0 | 30 |
| Niagara Falls Blvd at Meyer Rd | 7 | 4 | 0 | 11 |
| Niagara Falls Blvd at Maple Rd & Brighton Rd | 29 | 15 | 0 | 44 |
| Niagara Falls Blvd at Boulevard Mall Driveway | 2 | 3 | 0 | 5 |
| Niagara Falls Blvd at Tredwell Rd | 5 | 5 | 0 | 10 |
| Niagara Falls Blvd at Sheridan Dr | 19 | 11 | 0 | 30 |
| Niagara Falls Blvd at Eggert Rd | 11 | 5 | 0 | 16 |
| Maple Rd at Alberta Dr | 12 | 5 | 0 | 17 |
| Maple Rd at North Bailey Ave | 36 | 9 | 0 | 45 |
| Maple Rd at Bowmart Pkwy | 8 | 6 | 0 | 14 |
| Maple Rd at Hillcrest Dr | 7 | 5 | 0 | 12 |
| Maple Rd at Sweet Home Road | 32 | 26 | 0 | 58 |
| Maple Rd at Millersport Hwy Ramps SB | 3 | 1 | 0 | 4 |
| Maple Rd at Millersport Hwy Ramps NB | 3 | 2 | 0 | 5 |
| Sheridan Dr at Eggert Rd | 6 | 7 | 0 | 13 |
| Sheridan Dr at Alberta Dr | 11 | 12 | 0 | 23 |
| Sheridan Dr at Bailey Ave | 26 | 11 | 0 | 37 |
| Sheridan Dr at Sweet Home Rd | 18 | 15 | 0 | 33 |
| Sheridan Dr at Millersport Hwy | 38 | 12 | 0 | 50 |
| Eggert Rd at Alberta Dr | 3 | 2 | 0 | 5 |
| Eggert Rd at Bailey Ave | 10 | 5 | 0 | 15 |
| North Bailey Ave at Alberta Dr | 5 | 0 | 0 | 5 |
| North Bailey Ave at Meyer Rd | 12 | 4 | 0 | 16 |
| Bailey Ave at Emerson Dr | 8 | 3 | 0 | 11 |
| Bowmart Pkwy at Meyer Rd | 5 | 0 | 0 | 5 |
| Total | 389 | 203 | 0 | 592 |

# APPENDIX C

## TECHNICAL MEMO 2 – SUMMARY OF PLANNED CONDITIONS

# Technical Memo 2 – Summary of Planned Conditions

Traffic Impact Study: Town of Amherst Boulevard Central District

## Background

This technical memo is a summary of planned conditions due to a change in the Town's land use plan, for the transportation network within the Town of Amherst Boulevard Central District (BCD). This planned condition analysis builds off the existing conditions report model and analysis results that were presented in Technical Memo 1. The planned conditions analysis considers the anticipated growth within the transportation network based on the Town's planned land use projections for the area. This technical memorandum presents the results of the planned conditions analysis for the GEIS update.

## Planned Land Use and Growth

A land use program was developed for the Amherst Boulevard Central District and provided by the Town of Amherst. To determine the impacts of the planned land use program on the transportation network, planned land uses were correlated to Traffic Analysis Zones (TAZ). Each TAZ had a projected increase in population, retail employment, and office employment based on the potential development corresponding to land uses. Expected population and employee growth were based on the number of planned residential units and the square footage of retail and office facilities. The Greater Buffalo Niagara Regional Transportation (GBNRTC) was engaged to determine the origin and destination of travel within the study area using their regional transportation model. The regional model has known background development and growth programmed into it. The Town of Amherst planned land use projections were added to the regional model according to the anticipated type of development growth within each TAZ, and the model determined increases and decreases on major routes/street segments within the transportation system in the study area. The regional model which was altered to include changes in the projected land use in the BCD area is referred to as the Projected Growth Development Model.

The regional model analyzed the and PM three-hour peak periods for street segments. The regional model only has the PM peak, the future land use program induced the most significant impacts to the PM and Saturday peaks. To account for increases and decreases on each segment during the Saturday peak hour, the PM regional model scenario was used, as it is expected to have similar origin and destination patterns to the PM peak. Figure 1 in Appendix A is a map showing the percentage change in traffic volumes between the base model and the model with the Amherst BCD forecast volumes during the PM peak period. Streets with a high percentage increase in volumes were Alberta Drive, Niagara Falls Boulevard, Maple Road, North Bailey Avenue, and Sheridan Drive. To complete the analysis segment growth was translated to intersection turning movement volumes to determine impacts to intersections.

To determine vehicle routes, the percentage increases and decreases of street segments by comparing the base regional model to the Projected Growth Model were applied to the planned condition Synchro model. The turning movements were determined by using the ratios of the Projected Growth Development Model and applying those to the planned condition Synchro model. To check the road segment and turning


movement changes for the planned condition, a percentage of growth in each TAZ was calculated and compared to the expected overall growth of the Amherst Boulevard Central District. A summary of the projections and growth percentages are given in Table 1, any TAZ with 5% or greater of the total area growth was considered a significant increase in future volumes and was included as one a major growth TAZ. The six identified TAZs with 5% or greater of the total area growth were used to project trip distribution to and from the study area, see Figure 2 for a map of the TAZs.

Table 1: Amherst Boulevard Central District TAZ Growth Projections

| TAZ | Amherst BCD Projections (2026) | | | Amherst BCD Projections to Pop & Emp | | | | |
|---|---|---|---|---|---|---|---|---|
| | Total Units | Retail SF | Office SF | Population | Retail Emp* | Office Emp* | Total Pop & Emp Growth | Percentage of Growth |
| 668 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0% |
| 676 | 78 | 82,062 | 0 | 108 | 234 | 0 | 343 | 2% |
| 677 | 494 | 109,678 | 0 | 756 | 313 | 0 | 1069 | **6%** |
| 678 | 1,140 | 299,265 | 99,755 | 2394 | 855 | 570 | 3819 | **22%** |
| 679 | 0 | 310,159 | 0 | 0 | 886 | 0 | 886 | **5%** |
| 680 | 43 | 28,622 | 0 | 74 | 82 | 0 | 155 | 1% |
| 681 | 50 | 65,350 | 0 | 115 | 187 | 0 | 301 | 2% |
| 682 | 1,551 | 831,015 | 158,013 | 2389 | 2374 | 903 | 5666 | **33%** |
| 683 | 269 | 51,799 | 0 | 422 | 148 | 0 | 570 | 3% |
| 684 | 50 | 13,875 | 0 | 125 | 40 | 0 | 165 | 1% |
| 686 | 115 | 69,845 | 0 | 265 | 200 | 0 | 464 | 3% |
| 687 | 385 | 0 | 0 | 905 | 0 | 0 | 905 | **5%** |
| 688 | 118 | 147,657 | 0 | 283 | 422 | 0 | 705 | 4% |
| 699 | 20 | 7,000 | 0 | 45 | 20 | 0 | 65 | 0% |
| 701 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0% |
| 702 | 200 | 52,500 | 17,500 | 384 | 150 | 100 | 634 | 4% |
| 705 | 320 | 84,000 | 28,000 | 602 | 240 | 160 | 1002 | **6%** |
| 708 | 90 | 31,394 | 0 | 189 | 90 | 0 | 279 | 2% |
| 709 | 0 | 74,456 | 0 | 0 | 213 | 0 | 213 | 1% |

* Town of Amherst Economic Study (2016)
350 sq ft per retail employee
175 sq ft per office employee

Figure 2: TAZ Growth Changes



## Trip Distribution


Trip distribution assumptions were based on the TAZ growth and the roadway segment percent changes provided by the regional model. Road segment changes were applied to the planned condition Synchro model based on the changes from the regional model. Turning movement ratios were also applied to the planned condition model. For verification of trip distribution, the main access points of entering and exiting the study area were identified. Main access points to the study area include the following intersections:

- Niagara Falls Boulevard at Ridge Lea Road/Koeing Road
- Niagara Falls Boulevard at Maple Road
- Niagara Falls Boulevard at Sheridan Drive
- Maple Road at Millersport Highway
- Sheridan Drive at Millersport Highway
- Eggert Road at Bailey Avenue

From these major access points into and out of the study area, traffic was distributed based on level of segment increases in traffic that were reported from the regional model, as well as the increases in each TAZ based on growth from new development. Projected turning movement volumes were not balanced between intersections because driveway locations for developments will not be determined until site plan review for each impending development. Therefore, turning movement volumes distributed to a street segment may have been dissolved or generated within a segment based on the assumption they entered or exited to an existing or future driveway within that street segment.

Appendix A Figure 3 shows the existing turning movement volumes collected in 2023. Figure 4 in Appendix A displays the segment growth calculated from existing volumes and the growth rates provided by GBNRTC. In Appendix A Figure 5 shows the turning movement distribution percentages at each intersection and Figure 6 shows the turning movement distribution volumes. Figure 7 shows the overall planned conditions for the intersection analysis.

Figure 7: Planned Conditions Turning Movement Diagram



# Capacity Analysis Methodology

**Intersections**

The study intersections were analyzed using SYNCHRO 12[1], which is a computer program that implements the methods presented in the 7th Edition Highway Capacity Manual[2]. SYNCHRO determines the Level of Service (LOS), which is measured in terms of time Delay (seconds).

> Delay is a quantitative measure stated in terms of the control delay per vehicle for a 15-minute analysis period expressed in time (seconds). It is a qualitative measure of driver discomfort, frustration, fuel consumption and lost travel time.
> Level of Service criteria are stated in terms of the control delay (stated above) per vehicle and ranges from "A" to "F". Level of Service A is representative of a movement that is free flowing with minimal delay, while LOS F generally represents long delays. LOS D is generally considered acceptable in urban environments.

The ranges of delay for each level of service, as contained in the 7th Edition Highway Capacity Manual, are shown in Table 2.

Table 2: Intersection Level of Service Criteria

| Level of Service (LOS) | Unsignalized Intersections | Signalized Intersections | |
|---|---|---|---|
| | Delay (sec) | Delay (sec) | v/c ratio* |
| A | 0-10 | 0-10 | <1.0 |
| B | > 10-15 | > 10-20 | <1.0 |
| C | > 15-25 | > 20-35 | <1.0 |
| D | > 25-35 | > 35-55 | <1.0 |
| E | > 35-50 | > 55-80 | <1.0 |
| F | over 50 | over 80 | ≥1.0 |

* If the volume to capacity ratio is 1.0 or greater, the LOS is F

The projected growth volumes distributed through the transportation network based on the Town's projected growth were added to the existing traffic volumes to complete an intersection capacity analysis. The results of the planned land use capacity analysis are compared to existing conditions and displayed in Table 3.

[1] Synchro Studio 12, Traffic Signal Optimization and Simulation Modeling Software, Version 12, Trafficware Corporation, Albany, California, 2023.
[2] Highway Capacity Manual, Transportation Research Board, National Research Council, Washington D.C., 2022.

Table 3: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at I-290 Westbound Ramps (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | D (41.2) | 0.04 | 14 | D (43.2) | 0.06 | 18 | D (40.8) | 0.04 | 14 | D (42.1) | 0.05 | 18 |
| | *Right* | A (0.1) | 0.02 | 0 | A (7.5) | 0.04 | 16 | A (0.1) | 0.02 | 0 | A (7.4) | 0.04 | 16 |
| Westbound | *Left* | **E (72.1)** | **0.82** | **594** | **E (72.0)** | **0.80** | **541** | **E (71.9)** | **0.83** | **625** | **E (71.4)** | **0.81** | **576** |
| | *Thru* | **E (63.7)** | **0.82** | **550** | **E (69.1)** | **0.82** | **535** | **E (66.5)** | **0.84** | **595** | **E (70.1)** | **0.83** | **575** |
| | *Right* | **E (61.4)** | **0.80** | **511** | **E (59.1)** | **0.76** | **447** | **E (63.5)** | **0.82** | **547** | **E (60.9)** | **0.77** | **485** |
| Northbound | *Thru* | B (17.5) | 0.39 | 340 | C (21.2) | 0.39 | 363 | B (19.3) | 0.42 | 354 | C (23.0) | 0.41 | 389 |
| | *Right* | A (3.0) | 0.36 | 51 | A (5.3) | 0.37 | 99 | A (3.3) | 0.38 | 59 | A (5.5) | 0.39 | 102 |
| Southbound | *Thru/Right* | B (19.6) | 0.45 | 402 | B (19.7) | 0.52 | 500 | C (20.6) | 0.47 | 412 | C (21.0) | 0.53 | 514 |
| | *Intersection* | C (30.4) | - | - | C (30.4) | - | - | C (31.7) | - | - | C (31.7) | - | - |
| **Niagara Falls Boulevard at I-290 Eastbound Ramps (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Right* | **E (66.3)** | **0.79** | **292** | D (49.0) | 0.65 | 428 | **E (68.2)** | **0.81** | **352** | **E (56.9)** | **0.76** | **534** |
| Westbound | *Right* | A (0.4) | 0.26 | 0 | A (0.2) | 0.15 | 0 | A (0.4) | 0.26 | 0 | A (0.1) | 0.15 | 0 |
| Northbound | *Thru/Right* | A (0.1) | 0.25 | 0 | A (0.8) | 0.41 | 0 | A (0.1) | 0.25 | 0 | A (0.3) | 0.46 | 0 |
| Southbound | *Thru* | A (7.5) | 0.34 | 154 | C (27.9) | 0.53 | 573 | B (10.3) | 0.38 | 243 | C (28.9) | 0.56 | 627 |
| | *Right* | A (1.5) | 0.39 | 13 | A (7.1) | 0.48 | 61 | A (2.3) | 0.41 | 29 | A (7.8) | 0.57 | 137 |
| | *Intersection* | B (10.3) | - | - | B (16.2) | - | - | B (12.6) | - | - | B (17.7) | - | - |

*lowercase letters signify the HCM 6th edition Stop Control methodology was used

a: level-of-service

b: delay is measured in seconds

c: volume to capacity ratio

d: 95th queue length, measured in feet (queue length of stop controlled intersections measured in number of vehicles

m footnote on queue indicates that volume is metered by an upstream signal

# footnote on queue indicated that the volume modeled exceeds capacity

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at Ridge Lea Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | **E (66.4)** | **0.50** | **187** | **E (56.7)** | **0.39** | **178** | **E (62.0)** | **0.51** | **186** | **E (58.9)** | **0.46** | **178** |
| | *Thru/Right* | D (53.8) | 0.21 | 120 | D (50.4) | 0.21 | 147 | D (49.4) | 0.18 | 119 | D (50.4) | 0.20 | 147 |
| Westbound | *Left/Thru* | **F (107.2)** | **0.71** | **170** | **E (73.0)** | **0.35** | **167** | **F (120.2)** | **0.89** | **#325** | **F (87.8)** | **0.68** | **#304** |
| | *Right* | D (38.3) | 0.67 | 351 | C (22.1) | 0.50 | 319 | D (35.5) | 0.68 | 456 | C (26.8) | 0.60 | 443 |
| Northbound | *Left* | **F (96.0)** | **0.35** | **m59** | **F (105.0)** | **0.49** | **m103** | **F (99.4)** | **0.35** | **m53** | **F (103.9)** | **0.48** | **m93** |
| | *Thru/Right* | B (12.4) | 0.47 | 85 | C (28.6) | 0.79 | 113 | B (12.8) | 0.65 | 88 | C (30.5) | 0.90 | 128 |
| Southbound | *Left* | **F (83.6)** | **0.83** | **371** | **E (78.1)** | **0.61** | **463** | **E (72.0)** | **0.86** | **468** | **F (87.9)** | **0.75** | **575** |
| | *Thru/Right* | A (9.1) | 0.36 | 204 | B (12.1) | 0.43 | 227 | B (11.6) | 0.43 | 247 | B (11.9) | 0.49 | 253 |
| *Intersection* | | C (32.6) | - | - | C (33.3) | - | - | C (32.7) | - | - | D (37.6) | - | - |
| **Niagara Falls Boulevard at Consumer Plaza (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru* | **E (67.7)** | **0.22** | **60** | **F (174.1)** | **0.82** | **#103** | **E (67.7)** | **0.22** | **60** | **F (174.1)** | **0.81** | **#103** |
| | *Right* | A (0.1) | 0.03 | 0 | A (0.8) | 0.10 | 0 | A (0.1) | 0.03 | 0 | A (0.7) | 0.09 | 0 |
| Westbound | *Left/Thru* | **E (67.1)** | **0.44** | **207** | **F (96.9)** | **0.82** | **296** | **E (67.1)** | **0.44** | **207** | **F (96.9)** | **0.81** | **296** |
| | *Right* | A (9.0) | 0.42 | 75 | A (9.8) | 0.54 | 82 | A (9.0) | 0.42 | 75 | A (9.8) | 0.54 | 82 |
| Northbound | *Left* | **F (93.2)** | **0.20** | **m40** | **F (124.6)** | **0.32** | **m70** | **F (111.4)** | **0.20** | **m0** | **F (122.3)** | **0.32** | **m68** |
| | *Thru* | **E (56.9)** | **0.56** | **480** | D (44.9) | 0.53 | 516 | **E (55.9)** | **0.64** | **547** | D (41.0) | 0.61 | 590 |
| | *Right* | B (11.7) | 0.18 | m107 | A (9.6) | 0.17 | 24 | B (9.1) | 0.18 | m76 | A (5.2) | 0.17 | m13 |
| Southbound | *Left* | **F (94.3)** | **0.81** | **250** | **F (83.4)** | **0.72** | **#491** | **F (95.8)** | **0.81** | **m253** | **F (80.8)** | **0.72** | **#477** |
| | *Thru/Right* | B (16.7) | 0.40 | 313 | A (7.4) | 0.39 | 258 | B (16.7) | 0.46 | 350 | A (8.3) | 0.45 | 324 |
| *Intersection* | | D (39.4) | - | - | C (34.8) | - | - | D (38.8) | - | - | C (32.5) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at Romney Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru* | F (345.3) | 1.54 | #288 | F (158.2) | 1.04 | #265 | F (372.5) | 1.60 | #291 | F (130.7) | 0.94 | #249 |
| | *Right* | A (0.5) | 0.08 | 0 | A (0.8) | 0.09 | 4 | A (0.5) | 0.07 | 0 | A (0.7) | 0.08 | 3 |
| Westbound | *Left* | F (110.8) | 0.84 | 234 | F (117.4) | 0.94 | 304 | F (109.5) | 0.86 | m254 | F (109.4) | 0.92 | m336 |
| | *Thru/Right* | F (84.4) | 0.85 | 320 | E (65.5) | 0.77 | 333 | F (82.3) | 0.86 | m340 | E (62.2) | 0.77 | 363 |
| Northbound | *Left* | F (81.6) | 0.38 | 76 | F (84.2) | 0.53 | 115 | E (78.1) | 0.38 | m73 | F (81.2) | 0.53 | 116 |
| | *Thru* | C (25.9) | 0.24 | 312 | D (39.5) | 0.30 | 394 | D (36.1) | 0.28 | 394 | D (51.2) | 0.36 | 462 |
| | *Right* | B (13.6) | 0.05 | 46 | C (23.3) | 0.17 | 150 | C (21.1) | 0.06 | 67 | C (31.7) | 0.19 | 172 |
| Southbound | *Left* | F (118.5) | 0.77 | 264 | F (108.2) | 0.82 | 352 | F (117.6) | 0.79 | 294 | F (112.7) | 0.83 | 391 |
| | *Thru/Right* | A (2.5) | 0.25 | 26 | A (6.8) | 0.28 | 124 | A (2.6) | 0.28 | 36 | A (8.5) | 0.33 | 140 |
| *Intersection* | | D (49.7) | - | - | D (46.5) | - | - | D (51.0) | - | - | D (48.7) | - | - |
| **Niagara Falls Boulevard at Meyer Road (Unsignalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | c (17.6) | 0.05 | 0.1 | f (83.7) | 0.29 | 1 | c (21.5) | 0.06 | 0.2 | f (147.7) | 0.78 | 1.5 |
| Westbound | *Left/Thru/Right* | d (31.9) | 0.24 | 0.9 | f (119.0) | 0.78 | 4.1 | f (609.8) | 1.97 | 11 | f (3958.5) | 23.0 | 22.4 |
| Northbound | *Left* | b (11.6) | 0.00 | 0 | c (15.3) | 0.0 | 0 | b (12.3) | 0.00 | 0 | c (16.5) | 0.003 | 0 |
| Southbound | *Left* | c (18.0) | 0.20 | 0.8 | d (27.2) | 0.36 | 1.6 | d (25.5) | 0.35 | 1.5 | f (50.8) | 0.62 | 3.5 |
| *Intersection* | | n/a | | | n/a | | | n/a | | | n/a | | |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| Niagara Falls Boulevard at Maple Road and Brighton Road (Signalized) | | | | | | | | | | | | | |
| Eastbound | *Left* | **E (55.8)** | **0.55** | **186** | D (54.4) | 0.54 | 197 | D (53.1) | 0.59 | 209 | D (51.0) | 0.56 | 222 |
| | *Thru/Right* | **F (89.2)** | **0.79** | **245** | **F (88.8)** | **0.80** | **260** | **F (86.6)** | **0.83** | **296** | **F (86.3)** | **0.83** | **314** |
| Westbound | *Left* | **F (79.3)** | **0.88** | **#384** | **E (75.3)** | **0.86** | **#357** | **F (119.2)** | **1.08** | **#593** | **F (107.6)** | **1.03** | **#545** |
| | *Thru* | **E (74.1)** | **0.63** | **287** | **E (70.8)** | **0.52** | **236** | **E (70.0)** | **0.59** | **295** | **E (66.7)** | **0.48** | **241** |
| | *Right* | B (10.5) | 0.52 | 86 | B (10.6) | 0.54 | 88 | B (10.5) | 0.55 | 99 | B (13.0) | 0.57 | 122 |
| Northbound | *Left* | **F (102.0)** | **0.61** | **146** | **F (101.4)** | **0.58** | **130** | **F (97.0)** | **0.66** | **195** | **F (98.0)** | **0.66** | **189** |
| | *Thru* | C (31.3) | 0.35 | 298 | C (34.5) | 0.44 | 385 | D (37.3) | 0.43 | 361 | D (41.6) | 0.53 | 468 |
| | *Right* | A (4.1) | 0.26 | 57 | A (4.2) | 0.29 | 60 | A (4.6) | 0.33 | 64 | A (6.8) | 0.36 | 98 |
| Southbound | *Left* | **F (101.9)** | **0.74** | **208** | **F (93.9)** | **0.76** | **198** | **F (105.4)** | **0.77** | **243** | **F (97.4)** | **0.79** | **227** |
| | *Thru/Right* | B (17.5) | 0.34 | 167 | C (21.7) | 0.37 | 224 | C (20.7) | 0.43 | 185 | C (27.0) | 0.46 | 256 |
| | *Intersection* | D (45.5) | - | - | D (45.8) | - | - | D (51.2) | - | - | D (50.8) | - | - |
| Niagara Falls Boulevard at Boulevard Mall Driveway | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | B (16.7) | 0.05 | 14 | B (17.8) | 0.12 | 24 | B (19.8) | 0.05 | 16 | C (20.4) | 0.11 | 28 |
| Westbound | *Left* | C (21.7) | 0.09 | 26 | C (25.8) | 0.15 | 34 | C (32.0) | 0.38 | 75 | D (37.0) | 0.42 | 90 |
| | *Thru/Right* | B (12.4) | 0.12 | 22 | B (13.2) | 0.17 | 28 | B (10.6) | 0.27 | 39 | B (11.6) | 0.31 | 46 |
| Northbound | *Left* | C (22.9) | 0.04 | 14 | C (26.4) | 0.04 | 13 | C (32.5) | 0.06 | 18 | D (37.4) | 0.05 | 17 |
| | *Thru/Right* | A (7.7) | 0.31 | 126 | B (10.4) | 0.40 | 154 | B (14.7) | 0.54 | 198 | B (16.9) | 0.61 | 247 |
| Southbound | *Left* | C (22.1) | 0.15 | 34 | C (25.6) | 0.24 | 51 | C (31.2) | 0.37 | 86 | D (35.7) | 0.43 | 109 |
| | *Thru/Right* | A (5.5) | 0.31 | 129 | A (5.8) | 0.31 | 121 | A (7.5) | 0.41 | 175 | A (6.9) | 0.36 | 168 |
| | *Intersection* | A (7.2) | - | - | A (9.1) | - | - | B (12.4) | - | - | B (14.0) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at Treadwell Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | C (20.1) | 0.19 | 49 | B (19.1) | 0.19 | 48 | C (21.9) | 0.18 | 53 | C (24.6) | 0.20 | 58 |
| Westbound | *Left* | C (26.3) | 0.17 | 48 | C (23.5) | 0.13 | 38 | C (32.4) | 0.37 | 99 | C (34.3) | 0.35 | 98 |
| | *Thru/Right* | B (15.0) | 0.10 | 28 | B (12.4) | 0.14 | 33 | B (10.7) | 0.23 | 44 | B (11.2) | 0.28 | 51 |
| Northbound | *Left* | D (37.1) | 0.21 | 62 | C (33.1) | 0.24 | 71 | D (42.5) | 0.25 | 65 | D (43.4) | 0.30 | 82 |
| | *Thru/Right* | B (10.7) | 0.31 | 246 | B (11.8) | 0.38 | 242 | B (17.9) | 0.52 | 287 | B (17.0) | 0.54 | 313 |
| Southbound | *Left* | D (35.4) | 0.11 | 37 | C (34.8) | 0.14 | 44 | D (41.0) | 0.36 | 103 | D (42.6) | 0.38 | 109 |
| | *Thru/Right* | B (13.8) | 0.40 | 269 | B (14.4) | 0.41 | 248 | B (15.2) | 0.50 | 307 | B (15.6) | 0.49 | 282 |
| | *Intersection* | B (13.5) | - | - | B (14.0) | - | - | B (18.0) | - | - | B (18.2) | - | - |
| **Niagara Falls Boulevard at Sheridan Drive (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | **F (96.7)** | **0.81** | **268** | **F (90.3)** | **0.76** | **274** | **F (95.7)** | **0.83** | **301** | **F (86.5)** | **0.79** | **344** |
| | *Thru/Right* | **E (73.0)** | **0.67** | **330** | **E (67.0)** | **0.54** | **280** | **E (70.2)** | **0.64** | **329** | **E (61.0)** | **0.47** | **272** |
| Westbound | *Left* | **F (97.6)** | **0.79** | **238** | **F (98.6)** | **0.75** | **200** | **F (97.2)** | **0.80** | **253** | **F (98.4)** | **0.76** | **214** |
| | *Thru* | **E (78.1)** | **0.76** | **359** | **E (79.2)** | **0.75** | **339** | **E (77.2)** | **0.76** | **367** | **E (78.6)** | **0.75** | **347** |
| | *Right* | A (0.5) | 0.10 | 0 | A (0.8) | 0.14 | 0 | A (0.8) | 0.15 | 0 | A (1.0) | 0.18 | 0 |
| Northbound | *Thru/Right* | B (19.6) | 0.27 | 62 | C (22.5) | 0.29 | 122 | C (20.9) | 0.32 | 76 | C (27.7) | 0.37 | 330 |
| Southbound | *Left* | **F (99.4)** | **0.71** | **171** | **F (98.6)** | **0.76** | **208** | **F (99.2)** | **0.73** | **179** | **F (98.4)** | **0.76** | **216** |
| | *Thru* | C (23.2) | 0.33 | 315 | C (22.2) | 0.26 | 242 | C (26.7) | 0.40 | 406 | C (27.5) | 0.33 | 329 |
| | *Right* | A (2.9) | 0.34 | 56 | A (2.9) | 0.36 | 57 | A (3.2) | 0.42 | 63 | A (4.4) | 0.44 | 98 |
| | *Intersection* | **E (55.3)** | - | - | D (54.1) | - | - | D (53.4) | - | - | D (53.3) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Niagara Falls Boulevard at Eggert Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Thru* | **E (79.6)** | **0.53** | **197** | **F (88.0)** | **0.59** | **174** | **E (78.2)** | **0.51** | **195** | **F (86.3)** | **0.56** | **172** |
| | *Right* | B (14.3) | 0.48 | 83 | B (16.1) | 0.50 | 73 | B (13.9) | 0.47 | 82 | B (15.5) | 0.49 | 72 |
| Westbound | *Left* | **F (82.4)** | **0.39** | **99** | **F (104.1)** | **0.57** | **115** | **F (80.3)** | **0.37** | **99** | **F (99.6)** | **0.54** | **114** |
| | *Thru/Right* | **F (86.4)** | **0.77** | **284** | **F (85.7)** | **0.75** | **205** | **F (84.8)** | **0.78** | **294** | **F (81.8)** | **0.75** | **208** |
| Northbound | *Left* | **F (109.1)** | **0.80** | **275** | **F (110.8)** | **0.74** | **207** | **F (109.1)** | **0.80** | **275** | **F (110.8)** | **0.73** | **207** |
| | *Thru/Right* | C (24.3) | 0.27 | 255 | B (18.8) | 0.27 | 239 | C (26.2) | 0.30 | 285 | C (20.4) | 0.29 | 269 |
| Southbound | *Left* | D (36.5) | 0.30 | 124 | **E (61.2)** | **0.30** | **130** | D (38.4) | 0.33 | 161 | **E (70.8)** | **0.34** | **189** |
| | *Thru/Right* | B (13.4) | 0.36 | 315 | A (3.9) | 0.30 | 264 | B (13.0) | 0.43 | 410 | A (3.2) | 0.35 | 156 |
| | *Intersection* | D (40.4) | - | - | D (35.1) | - | - | D (39.0) | - | - | C (33.7) | - | - |
| **Maple Road at Alberta Drive (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | B (12.6) | 0.08 | 23 | B (12.4) | 0.13 | 36 | B (12.3) | 0.09 | 22 | B (24.9) | 0.14 | 35 |
| | *Thru* | C (26.4) | 0.59 | 170 | C (25.5) | 0.58 | 166 | C (27.2) | 0.65 | 203 | C (17.1) | 0.63 | 200 |
| | *Right* | A (6.4) | 0.34 | 47 | A (6.3) | 0.36 | 48 | A (5.8) | 0.38 | 50 | A (17.1) | 0.39 | 51 |
| Westbound | *Left* | B (15.2) | 0.41 | 98 | B (15.1) | 0.43 | 103 | C (30.4) | 0.79 | #248 | C (30.7) | 0.76 | #258 |
| | *Thru/Right* | B (18.0) | 0.43 | 187 | B (19.1) | 0.38 | 152 | B (17.9) | 0.48 | 223 | B (25.3) | 0.42 | 182 |
| Northbound | *Left* | B (18.2) | 0.46 | 124 | C (20.3) | 0.55 | 140 | C (22.9) | 0.60 | 163 | C (22.3) | 0.70 | 184 |
| | *Thru/Right* | B (12.6) | 0.32 | 104 | B (11.3) | 0.37 | 106 | B (13.2) | 0.50 | 153 | B (20.8) | 0.55 | 157 |
| Southbound | *Left* | B (14.1) | 0.05 | 16 | B (13.9) | 0.04 | 14 | B (15.3) | 0.05 | 17 | B (15.7) | 0.04 | 15 |
| | *Thru/Right* | B (14.9) | 0.24 | 51 | B (18.7) | 0.31 | 61 | B (15.7) | 0.25 | 53 | B (10.4) | 0.32 | 63 |
| | *Intersection* | B (18.1) | - | - | B (18.2) | - | - | C (20.2) | - | - | C (20.4) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Maple Road at N Bailey Avenue (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | C (23.2) | 0.34 | 57 | C (25.9) | 0.45 | 89 | D (35.1) | 0.60 | #113 | D (38.4) | 0.67 | #162 |
| | *Thru* | D (38.4) | 0.67 | 242 | D (42.7) | 0.69 | 240 | D (44.1) | 0.77 | 338 | D (53.1) | 0.85 | #363 |
| | *Right* | A (0.3) | 0.08 | 0 | A (0.7) | 0.15 | 0 | A (0.4) | 0.12 | 0 | A (0.8) | 0.19 | 0 |
| Westbound | *Left* | C (25.2) | 0.59 | 150 | C (26.0) | 0.56 | 154 | D (36.2) | 0.74 | 212 | D (36.2) | 0.72 | 204 |
| | *Thru/Right* | C (29.2) | 0.68 | 288 | C (33.6) | 0.72 | 249 | C (34.6) | 0.81 | 369 | D (38.4) | 0.80 | 320 |
| Northbound | *Left* | B (20.0) | 0.22 | 60 | B (18.2) | 0.28 | 78 | C (26.8) | 0.43 | 91 | C (22.4) | 0.45 | 100 |
| | *Thru* | D (43.5) | 0.75 | 341 | D (48.4) | 0.77 | 335 | D (52.4) | 0.83 | #437 | **E (55.9)** | **0.83** | **#415** |
| | *Right* | A (1.9) | 0.25 | 10 | A (1.7) | 0.26 | 6 | A (2.3) | 0.26 | 15 | A (2.1) | 0.27 | 12 |
| Southbound | *Left* | **E (61.0)** | **0.92** | **#317** | C (23.6) | 0.64 | 200 | **F (160.1)** | **1.23** | **#386** | D (35.6) | 0.78 | #279 |
| | *Thru* | D (37.5) | 0.65 | 348 | C (32.9) | 0.61 | 359 | D (51.3) | 0.82 | #439 | D (39.8) | 0.72 | 403 |
| | *Right* | A (0.7) | 0.19 | 0 | A (3.1) | 0.21 | 28 | A (4.4) | 0.31 | 38 | A (8.2) | 0.33 | 74 |
| *Intersection* | | C (32.7) | - | - | C (30.8) | - | - | D (46.0) | - | - | D (37.9) | - | - |
| **Maple Road at Bowmart Parkway (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | A (6.8) | 0.30 | 32 | C (31.9) | 0.37 | 83 | B (11.7) | 0.40 | 56 | D (41.8) | 0.48 | 111 |
| | *Thru* | A (6.0) | 0.37 | 125 | A (6.6) | 0.40 | 133 | A (6.8) | 0.42 | 157 | A (7.8) | 0.47 | 175 |
| Westbound | *Thru/Right* | B (14.0) | 0.60 | 250 | B (15.6) | 0.62 | 198 | B (16.9) | 0.70 | 320 | B (17.5) | 0.66 | 256 |
| Southbound | *Left* | C (34.0) | 0.58 | 162 | C (30.2) | 0.56 | 149 | D (44.2) | 0.69 | #259 | D (35.9) | 0.63 | 209 |
| | *Right* | A (8.3) | 0.24 | 37 | A (0.9) | 0.12 | 11 | A (8.9) | 0.27 | 46 | A (0.6) | 0.13 | 11 |
| *Intersection* | | B (12.5) | - | - | B (13.4) | - | - | B (15.4) | - | - | B (15.7) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Maple Road at Hillcrest Drive (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | A (8.0) | 0.45 | 228 | A (4.6) | 0.37 | 182 | B (10.3) | 0.53 | 285 | A (4.7) | 0.41 | 223 |
| Westbound | *Left* | C (20.9) | 0.06 | 24 | C (20.2) | 0.04 | 13 | C (25.7) | 0.06 | 26 | C (22.3) | 0.03 | 14 |
| | *Thru/Right* | A (7.0) | 0.62 | 200 | A (2.7) | 0.41 | 115 | A (7.6) | 0.70 | 292 | A (2.9) | 0.48 | 151 |
| Northbound | *Left/Thru/Right* | A (9.5) | 0.22 | 33 | A (4.6) | 0.10 | 12 | B (11.0) | 0.24 | 34 | A (4.6) | 0.10 | 13 |
| Southbound | *Left* | C (21.7) | 0.11 | 31 | A (0.0) | 0.00 | 0 | C (25.7) | 0.10 | 33 | A (0.0) | 0.00 | 0 |
| | *Thru/Right* | A (0.0) | 0.01 | 0 | B (16.7) | 0.16 | 6 | A (0.0) | 0.01 | 0 | B (18.3) | 0.01 | 7 |
| | *Intersection* | A (7.7) | - | - | A (3.7) | - | - | A (9.0) | - | - | A (3.8) | - | - |
| **Maple Road at Sweet Home Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | **E (55.7)** | **0.83** | **336** | C (22.7) | 0.65 | 228 | **E (77.7)** | **0.94** | **#507** | D (38.8) | 0.81 | #408 |
| | *Thru* | D (37.6) | 0.44 | 331 | C (23.2) | 0.32 | 251 | D (42.4) | 0.57 | 421 | C (27.4) | 0.42 | 322 |
| | *Right* | A (2.4) | 0.12 | 17 | A (0.4) | 0.09 | 3 | A (3.9) | 0.15 | 29 | A (1.3) | 0.11 | 11 |
| Westbound | *Left* | C (26.7) | 0.50 | 109 | B (14.1) | 0.17 | 34 | D (42.8) | 0.67 | 170 | B (17.2) | 0.25 | 42 |
| | *Thru* | D (48.8) | 0.78 | #666 | C (31.9) | 0.47 | 370 | **F (108.2)** | **1.10** | **#862** | D (42.6) | 0.65 | 424 |
| | *Right* | B (10.8) | 0.37 | 80 | A (3.6) | 0.13 | 27 | B (16.5) | 0.51 | 145 | A (4.7) | 0.19 | 37 |
| Northbound | *Left* | D (40.3) | 0.51 | 110 | D (37.7) | 0.40 | 97 | D (45.2) | 0.62 | 132 | D (37.2) | 0.44 | 111 |
| | *Thru* | **E (63.6)** | **0.72** | **457** | **E (65.5)** | **0.72** | **283** | **E (70.6)** | **0.82** | **#566** | **E (66.6)** | **0.76** | **329** |
| | *Right* | A (3.3) | 0.23 | 23 | A (0.9) | 0.17 | 0 | A (8.3) | 0.30 | 63 | A (1.1) | 0.22 | 0 |
| Southbound | *Left* | D (42.9) | 0.64 | 192 | D (43.1) | 0.57 | 146 | **E (60.8)** | **0.85** | **#313** | D (49.2) | 0.71 | 178 |
| | *Thru* | **E (69.5)** | **0.85** | **#653** | **E (62.9)** | **0.72** | **306** | **E (73.2)** | **0.89** | **#757** | **E (61.1)** | **0.71** | **334** |
| | *Right* | B (19.7) | 0.72 | 291 | A (8.6) | 0.60 | 83 | C (27.6) | 0.84 | #493 | B (11.3) | 0.67 | 130 |
| | *Intersection* | D (41.5) | - | - | C (29.8) | - | - | **E (60.4)** | - | - | C (34.7) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Maple Road at Millersport Highway West (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | A (0.9) | 0.03 | m2 | A (0.4) | 0.02 | m1 | A (1.4) | 0.11 | m6 | A (0.5) | 0.06 | m2 |
| | *Thru* | A (0.9) | 0.27 | 28 | A (1.1) | 0.23 | 10 | A (1.1) | 0.28 | 37 | A (1.0) | 0.23 | 11 |
| Westbound | *Thru* | A (3.0) | 0.31 | 108 | A (1.2) | 0.24 | 17 | A (3.0) | 0.33 | 133 | A (1.1) | 0.25 | 18 |
| | *Right* | A (0.2) | 0.15 | 0 | A (0.2) | 0.12 | 0 | A (0.2) | 0.15 | 0 | A (0.1) | 0.11 | 0 |
| Southbound | *Left* | **E (74.0)** | **0.29** | **80** | **E (65.1)** | **0.15** | **37** | **E (74.9)** | **0.31** | **78** | **E (64.9)** | **0.15** | **36** |
| | *Right* | C (21.5) | 0.58 | 78 | C (22.8) | 0.58 | 60 | D (39.7) | 0.71 | 121 | C (22.7) | 0.59 | 62 |
| | *Intersection* | A (4.3) | - | - | A (3.0) | - | - | A (5.6) | - | - | A (2.9) | - | - |
| **Maple Road at Millersport Highway East (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | C (34.4) | 0.48 | 138 | A (1.8) | 0.14 | 9 | D (36.1) | 0.52 | 120 | A (2.2) | 0.14 | 11 |
| | *Thru* | C (23.0) | 0.46 | 457 | A (1.1) | 0.20 | 26 | C (21.3) | 0.48 | 467 | A (1.4) | 0.20 | 35 |
| Westbound | *Thru/Right* | C (24.4) | 0.56 | 488 | A (4.6) | 0.31 | 178 | C (25.2) | 0.58 | 517 | A (5.1) | 0.32 | 196 |
| Northbound | *Left* | C (32.3) | 0.36 | 72 | D (54.9) | 0.21 | 65 | C (32.1) | 0.09 | 72 | D (53.1) | 0.18 | 64 |
| | *Thru/Right* | **E (62.3)** | **0.36** | **#690** | C (33.2) | 0.85 | 179 | **E (63.4)** | **0.93** | **#722** | D (35.7) | 0.85 | 195 |
| | *Intersection* | C (32.5) | - | - | A (9.9) | - | - | C (32.3) | - | - | B (10.5) | - | - |
| **Sheridan Drive at Eggert Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | C (27.2) | 0.29 | 47 | C (29.8) | 0.41 | 73 | C (32.0) | 0.36 | 52 | D (35.4) | 0.47 | #84 |
| | *Thru* | C (21.1) | 0.42 | 169 | C (20.5) | 0.45 | 188 | C (21.4) | 0.44 | 183 | C (20.7) | 0.47 | 204 |
| | *Right* | A (3.9) | 0.25 | 41 | A (3.5) | 0.22 | 34 | A (3.9) | 0.25 | 41 | A (3.5) | 0.21 | 34 |
| Westbound | *Thru/Right* | C (22.5) | 0.56 | 229 | C (20.6) | 0.51 | 210 | C (23.4) | 0.61 | 261 | C (21.3) | 0.55 | 238 |
| South eastbound | *Left/Thru/Right* | D (46.5) | 0.77 | #191 | D (40.2) | 0.58 | 126 | D (42.2) | 0.66 | 151 | D (40.1) | 0.63 | 141 |
| North westbound | *Left/Thru/Right* | D (41.9) | 0.66 | 151 | D (39.7) | 0.63 | 141 | D (47.1) | 0.77 | #191 | D (40.6) | 0.58 | 126 |
| | *Intersection* | C (26.9) | - | - | C (24.1) | - | - | C (27.2) | - | - | C (24.5) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Sheridan Drive at Alberta Drive (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | F (86.3) | 0.73 | 237 | F (85.7) | 0.77 | 269 | F (85.7) | 0.76 | 261 | F (85.0) | 0.78 | 296 |
| | *Thru/Right* | B (16.0) | 0.24 | 193 | C (20.6) | 0.33 | 262 | B (19.4) | 0.26 | 204 | C (24.8) | 0.36 | 261 |
| Westbound | *Left* | F (102.4) | 0.52 | m126 | F (103.4) | 0.57 | m142 | F (101.7) | 0.52 | m124 | F (107.4) | 0.57 | m139 |
| | *Thru/Right* | A (9.4) | 0.40 | 94 | B (11.4) | 0.44 | 102 | B (13.1) | 0.51 | 123 | B (17.9) | 0.57 | 256 |
| Northbound | *Left/Thru/Right* | E (75.2) | 0.58 | 98 | E (76.7) | 0.71 | 144 | E (75.4) | 0.58 | 98 | E (75.3) | 0.69 | 143 |
| Southbound | *Left* | E (56.9) | 0.48 | 174 | D (52.4) | 0.47 | 165 | E (57.4) | 0.64 | 279 | D (54.0) | 0.65 | 292 |
| | *Thru/Right* | E (55.5) | 0.69 | 306 | E (56.6) | 0.75 | 374 | D (50.2) | 0.70 | 366 | D (48.9) | 0.68 | 406 |
| | *Intersection* | C (28.8) | - | - | C (33.2) | - | - | C (31.5) | - | - | D (36.1) | - | - |
| **Sheridan Drive at Bailey Avenue (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | F (105.8) | 0.69 | 219 | F (104.9) | 0.77 | 320 | F (98.1) | 0.72 | 245 | F (98.3) | 0.82 | #406 |
| | *Thru/Right* | B (20.0) | 0.33 | 128 | C (21.9) | 0.38 | 144 | C (24.7) | 0.38 | 173 | C (26.7) | 0.45 | 192 |
| Westbound | *Left* | F (123.3) | 0.68 | 215 | F (108.1) | 0.73 | 172 | F (117.2) | 0.71 | 219 | F (108.7) | 0.75 | 220 |
| | *Thru/Right* | B (10.3) | 0.43 | 75 | C (25.6) | 0.50 | 434 | B (13.6) | 0.51 | 459 | C (26.2) | 0.57 | 460 |
| Northbound | *Left* | D (46.3) | 0.43 | 115 | D (43.9) | 0.43 | 121 | D (46.6) | 0.51 | 131 | D (43.9) | 0.51 | 136 |
| | *Thru/Right* | E (71.7) | 0.79 | 295 | E (72.5) | 0.79 | 286 | E (70.5) | 0.81 | 320 | E (71.1) | 0.80 | 313 |
| Southbound | *Left* | D (50.1) | 0.54 | 138 | D (51.5) | 0.64 | 185 | D (50.3) | 0.61 | 156 | D (51.8) | 0.70 | 204 |
| | *Thru/Right* | E (63.5) | 0.68 | 263 | E (60.1) | 0.62 | 254 | E (63.1) | 0.73 | 300 | E (59.2) | 0.67 | 295 |
| | *Intersection* | D (39.7) | - | - | D (45.8) | - | - | D (41.9) | - | - | D (47.0) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Sheridan Drive at Sweet Home Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | **E (76.6)** | **0.64** | **257** | **E (58.1)** | **0.60** | **268** | **E (75.7)** | **0.15** | **#386** | D (54.7) | 0.58 | 304 |
| | *Thru/Right* | D (43.3) | 0.33 | 367 | C (34.5) | 0.29 | 332 | D (46.1) | 0.46 | 391 | D (37.8) | 0.31 | 362 |
| Westbound | *Left* | **F (86.2)** | **0.54** | **125** | **F (84.3)** | **0.43** | **92** | **F (86.2)** | **0.07** | **125** | **F (84.3)** | **0.43** | **92** |
| | *Thru/Right* | D (38.1) | 0.53 | 413 | C (33.8) | 0.43 | 334 | D (42.3) | 0.38 | 454 | D (39.6) | 0.54 | 412 |
| Northbound | *Left* | D (51.9) | 0.15 | 52 | **E (62.8)** | **0.22** | **65** | D (52.3) | 0.20 | 53 | **E (62.9)** | **0.22** | **65** |
| | *Thru/Right* | **E (79.5)** | **0.84** | **399** | **F (83.6)** | **0.76** | **274** | **F (81.4)** | **0.20** | **407** | **F (83.6)** | **0.76** | **274** |
| Southbound | *Left* | D (42.9) | 0.46 | 113 | D (49.0) | 0.48 | 147 | D (44.1) | 0.35 | 154 | D (48.5) | 0.54 | 179 |
| | *Thru/Right* | D (48.1) | 0.65 | 396 | D (46.0) | 0.55 | 289 | D (45.4) | 0.35 | 406 | D (43.3) | 0.55 | 293 |
| | *Intersection* | D (48.8) | - | - | D (42.7) | - | - | D (50.4) | - | - | D (45.0) | - | - |
| **Sheridan Drive at Millersport Highway (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | **E (57.4)** | **0.72** | **#318** | D (45.4) | 0.66 | 260 | **E (59.9)** | **0.74** | **#355** | D (46.3) | 0.67 | #279 |
| | *Thru/Right* | D (36.8) | 0.50 | 234 | C (26.7) | 0.39 | 180 | D (37.7) | 0.56 | 279 | C (26.8) | 0.42 | 205 |
| Westbound | *Left* | **E (58.5)** | **0.63** | **203** | D (47.9) | 0.42 | 116 | **E (61.5)** | **0.65** | **209** | D (49.1) | 0.42 | 116 |
| | *Thru/Right* | D (43.4) | 0.70 | 272 | D (37.9) | 0.65 | 200 | D (44.4) | 0.72 | 296 | D (38.4) | 0.66 | 214 |
| Northbound | *Left* | C (24.2) | 0.17 | 43 | C (22.6) | 0.16 | 50 | C (25.8) | 0.20 | 49 | C (23.4) | 0.18 | 56 |
| | *Thru* | D (38.8) | 0.48 | 205 | D (40.7) | 0.62 | 190 | D (40.3) | 0.48 | 212 | D (41.8) | 0.62 | 192 |
| | *Right* | A (7.8) | 0.26 | 49 | A (7.0) | 0.27 | 36 | A (7.9) | 0.26 | 50 | A (6.9) | 0.27 | 36 |
| Southbound | *Left* | C (24.5) | 0.27 | 86 | C (23.6) | 0.29 | 81 | C (25.7) | 0.27 | 89 | C (24.5) | 0.29 | 83 |
| | *Thru* | D (39.9) | 0.68 | 354 | C (33.8) | 0.41 | 161 | D (42.1) | 0.69 | 372 | D (35.1) | 0.42 | 166 |
| | *Right* | A (5.9) | 0.45 | 68 | A (7.0) | 0.47 | 67 | A (6.3) | 0.51 | 78 | A (7.2) | 0.52 | 74 |
| | *Intersection* | D (37.4) | - | - | C (31.4) | - | - | D (38.4) | - | - | C (31.7) | - | - |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **Eggert Road at Alberta Drive (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | A (5.0) | 0.20 | 40 | A (6.3) | 0.27 | 39 | A (5.0) | 0.21 | 42 | A (6.3) | 0.28 | 42 |
| Westbound | *Left/Thru/Right* | A (4.8) | 0.21 | 43 | A (5.8) | 0.22 | 32 | A (4.9) | 0.22 | 45 | A (5.7) | 0.22 | 34 |
| Northbound | *Left/Thru/Right* | B (13.2) | 0.07 | 20 | A (9.3) | 0.07 | 14 | B (13.2) | 0.07 | 20 | A (9.3) | 0.07 | 15 |
| Southbound | *Left/Thru/Right* | B (12.8) | 0.32 | 49 | B (11.1) | 0.37 | 42 | B (12.8) | 0.32 | 49 | B (11.2) | 0.36 | 42 |
| | *Intersection* | A (6.1) | - | - | A (7.0) | - | - | A (6.1) | - | - | A (7.0) | - | - |
| **Eggert Road at Bailey Avenue (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | B (16.6) | 0.48 | 104 | B (16.5) | 0.45 | 87 | B (17.1) | 0.51 | 114 | B (17.1) | 0.48 | 94 |
| Westbound | *Left/Thru/Right* | B (17.0) | 0.53 | 114 | B (15.7) | 0.53 | 100 | B (18.0) | 0.53 | 123 | B (16.9) | 0.54 | 107 |
| Northbound | *Left* | A (7.8) | 0.22 | 43 | A (7.1) | 0.16 | 32 | A (7.9) | 0.24 | 46 | A (7.1) | 0.19 | 35 |
| | *Thru/Right* | C (20.1) | 0.65 | 213 | C (20.1) | 0.66 | 209 | C (20.9) | 0.69 | 243 | C (20.3) | 0.68 | 235 |
| Southbound | *Left* | A (8.6) | 0.29 | 46 | A (8.6) | 0.32 | 48 | A (8.6) | 0.30 | 46 | A (8.7) | 0.33 | 47 |
| | *Thru/Right* | B (13.0) | 0.32 | 83 | B (11.5) | 0.28 | 80 | B (13.2) | 0.35 | 97 | B (12.7) | 0.34 | 93 |
| | *Intersection* | B (15.7) | - | - | B (15.1) | - | - | B (16.2) | - | - | B (15.8) | - | - |
| **N Bailey Avenue at Romney Road (Unsignalized)** | | | | | | | | | | | | | |
| Eastbound | *Left* | **e (49.1)** | **0.20** | **0.7** | **f (85.6)** | **0.41** | **1.6** | **f (179.9)** | **0.62** | **2.3** | **f (535.9)** | **1.39** | **4.4** |
| | *Right* | c (16.5) | 0.40 | 1.9 | c (24.3) | 0.59 | 3.8 | d (26.8) | 0.59 | 3.7 | **f (72.2)** | **0.93** | **9.2** |
| Northbound | *Left* | a (9.3) | 0.15 | 0.5 | b (10.2) | 0.22 | 0.9 | b (10.9) | 0.26 | 1.1 | b (13.0) | 0.37 | 1.7 |
| | *Intersection* | n/a | | | n/a | | | n/a | | | n/a | | |

Table 3 Continued: Intersection LOS Analysis of Existing vs. Planned Land Use Conditions

| Approach | | Existing Condition | | | | | | Planned Condition | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Weekday PM | | | Saturday Midday | | | Weekday PM | | | Saturday Midday | | |
| | | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue | LOS[a] (Delay)[b] | V/C[c] | Queue[d] | LOS (Delay) | V/C | Queue |
| **N Bailey Avenue at Meyer Road (Signalized)** | | | | | | | | | | | | | |
| Eastbound | *Left/Thru/Right* | C (25.4) | 0.57 | 131 | C (26.0) | 0.52 | 125 | D (46.3) | 0.78 | #251 | D (47.2) | 0.76 | #213 |
| Westbound | *Left/Thru* | B (19.8) | 0.08 | 32 | C (23.8) | 0.06 | 26 | C (28.3) | 0.13 | 54 | C (29.1) | 0.10 | 40 |
| | *Right* | A (6.5) | 0.28 | 38 | A (8.1) | 0.28 | 41 | A (7.5) | 0.33 | 48 | A (7.8) | 0.31 | 45 |
| Northbound | *Left* | A (7.0) | 0.10 | 17 | A (6.5) | 0.11 | 15 | C (23.3) | 0.47 | 58 | D (41.0) | 0.58 | #85 |
| | *Thru/Right* | B (11.0) | 0.62 | 279 | A (9.7) | 0.60 | 265 | B (12.1) | 0.66 | 341 | B (11.0) | 0.63 | 347 |
| Southbound | *Left* | A (9.2) | 0.28 | 46 | A (6.6) | 0.17 | 27 | B (13.9) | 0.47 | 82 | B (11.0) | 0.38 | 69 |
| | *Thru/Right* | B (12.4) | 0.68 | 326 | B (13.5) | 0.76 | 399 | C (22.4) | 0.88 | #651 | C (28.8) | 0.93 | #905 |
| | *Intersection* | B (12.7) | - | - | B (12.7) | - | - | C (20.4) | - | - | C (23.2) | - | - |
| **Bowmart Parkway at Meyer Road (Unsignalized)** | | | | | | | | | | | | | |
| Westbound | *Left* | a (7.6) | 0.01 | 0 | a (7.5) | 0.00 | 0 | a (7.7) | 0.02 | 0.1 | a (7.7) | 0.016 | 0.1 |
| Northbound | *Left* | a (9.9) | 0.18 | 0.6 | a (9.7) | 0.16 | 0.6 | b (11.3) | 0.28 | 1.2 | b (11.0) | 0.25 | 1 |
| | *Intersection* | n/a | | | n/a | | | n/a | | | n/a | | |

The majority of intersections are expected to operate at an overall acceptable level of service (D or better) with the growth volumes applied. Under existing conditions, the only intersection experiencing an overall LOS of E or F is Niagara Falls Boulevard at Sheridan Drive. Under planned conditions without mitigation the LOS at the intersection of Niagara Falls Boulevard at Sheridan Drive improved from E to D during the PM peak, while the overall LOS decreased from D to E at the intersection of Maple Road and Sweet Home Road during the PM peak. Movement level of service maps for the planned condition during the PM and Saturday peaks are in Appendix A, Figures 8 & 9.

**Degradation in LOS**

Changes in LOS for intersections and movements that have a change of delay resulting in a degradation of LOS (i.e. from a LOS D to a LOS E) resulting in a projected LOS E or worse from the existing condition to the planned condition are listed below. Also see Figure 10 for a diagram of the movements with a degradation in LOS.

Niagara Falls Boulevard at I-290 Eastbound Ramps
- Eastbound right in the Saturday Midday Peak from LOS D to LOS E

Niagara Falls Boulevard at Ridge Lea Road
- Westbound left/through in the Saturday Midday Peak from LOS E to LOS F
- Southbound left in the Saturday Midday Peak from LOS E to LOS F
- Overall intersection level of service in the Saturday Midday Peak from LOS C to LOS D

Niagara Falls Boulevard at Meyer Road
- Westbound left/through/right in the PM Peak from LOS d to LOS f
- Southbound left in the Saturday Midday Peak from LOS d to LOS f

Niagara Falls Boulevard at Maple Road and Brighton Road
- Westbound left in the Saturday Midday Peak from LOS E to LOS F


Maple Road at N Bailey Avenue
- Northbound through in the Saturday Midday Peak from LOS D to LOS E
- Southbound left in the Weekday PM Peak from LOS E to LOS F
- Overall Intersection level of service in the PM and Saturday Midday Peaks from LOS C to LOS D

Maple Road at Sweet Home Road
- Westbound through in the PM Peak from LOS D to LOS F
- Southbound left in the PM Peak from LOS D to LOS E
- Overall Intersection level of service in the PM Peak from LOS D to LOS E

Sheridan Drive at Sweet Home Road
- Northbound through/right in the PM Peak from LOS E to LOS F

N Bailey Avenue at Romney Road
- Eastbound left in the PM Peak from LOS e to LOS f
- Eastbound right in the Saturday Midday Peak from LOS c to LOS f

Figure 10: Degradation in Level of Service Map




## Improvement in LOS

Several intersection movements throughout the study area show an improvement in delay from the existing to planned scenario even though the traffic volumes either stayed the same or increased. The planned scenario differs from existing conditions due to changing traffic volumes and distribution. Adjustments in the traffic volumes impact adjacent intersections and street segments resulting from shifting arrival patterns at intersections due to a change in vehicle headway. The change in arrival patterns has a cascading impact within the study area network most focused on directly connected streets and intersections especially. These impacts to connected street and intersections result in improvements to LOS movements without any roadway improvements applied.

For coordinated signal networks, the platoon of traffic in Synchro is equally distributed from upstream traffic signals across the green time. Changes in traffic volumes at intersections in a coordinated network impacts the coordination factor or effectiveness of the existing offsets and timings. For the build scenario, the offsets and timings remain the same; these may result in positive distribution of changes to traffic volumes arriving from upstream intersections improving the delay and level of service.

Protected left turns at some intersections also experience an improvement in LOS with no changes or experience an increase in left turn volumes. One of the limitations to the methodologies for calculating delay is analyzing left turn pockets. If through movement vehicles have queues blocking the left turn lane, the delay for that left turn lane will not accurately be reflected because the demand is not represented in the delay output. At these left turn pocket locations, the queue in the build condition now exceeds the length of the turn pocket, which may restrict some left turning vehicles from reaching the turn pocket during each cycle.

Intersections that experienced an improvement to level of service in one or more movements are as follows:

- Niagara Falls Boulevard at Ridge Lea Road
- Niagara Falls Boulevard at Romney Road
- Niagara Falls Boulevard at Maple Road and Brighton Road
- Niagara Falls Boulevard at Sheridan Drive
- Niagara Falls Boulevard at Eggert Road
- Sheridan Drive at Alberta Drive
- Sheridan Drive at Sweet Home Road

## Mitigation

Mitigation will be explored further in future analyses; however, mitigation is recommended at the following locations due to either overall or movement level of service E or F, an increase in traffic volumes at a location impacting operations, and a high number of crashes and crash severity:

Street Segments

- Niagara Falls Boulevard from Ridge Lea Road to Sheridan Drive
- Ridge Lea Road/North Bailey Avenue from Niagara Falls Boulevard to Maple Road
- Bowmart Parkway from Maple Road to Meyer Road
- Sheridan Drive from Niagara Falls Boulevard to Millersport Highway

Intersections

- Maple Road at N Bailey Avenue
- Maple Road at Sweet Home Road
- Sheridan Drive at Sweet Home Road
- Emerson Drive at North Bailey Avenue

**Street Segments**

Niagara Falls Boulevard from Ridge Lea Road to Sheridan Drive

Niagara Falls Boulevard is a major arterial in Amherst carrying large volumes of traffic. Niagara Falls Boulevard currently operates on a coordinated signal network and is three travel lanes in each direction with turn lanes at intersections. To improve operations along Niagara Falls Boulevard, ITS technology should be explored such as adaptive signal control. Adaptive signal control responds to fluctuating traffic demand and patterns by adjusting signal timings to ease traffic congestion. This mitigation strategy would improve traffic flow without building additional lanes and infrastructure to increase capacity.

Ridge Lea Road/North Bailey Avenue from Niagara Falls Boulevard to Maple Road

Ridge Lea Road/North Bailey Avenue in this section is approaching capacity under existing conditions based on daily traffic volumes. This section is currently one lane in each direction with a two way left turn lane/exclusive turn lane at intersections. This segment is going through improvements to accommodate imminent development at Amherst Commerce Park of DICK'S House of Sport and a Costco with fueling stations. There will be two traffic signals installed at the intersections of Romney Road and the Best Buy Driveway. Additional capacity will be needed to accommodate the traffic volumes from the development as well as more available capacity at the traffic signals for through movements.

Bowmart Parkway from Maple Road to Meyer Road

A private road is being constructed across from where Bowmart Parkway currently ends at Meyer Road, which will provide access to the newly constructed Amherst Commerce Park. This direct access to eminent development is expected to make Bowmart Parkway a more attractive route for trips originating from and going to the southeast. Bowmart Parkway as a direct route to this development may relieve some of the congestion from parallel routes such as North Bailey Avenue. Bowmart Parkway is a single lane in each direction and currently has enough capacity for existing conditions with plenty of reserve capacity. The current pavement surface is in poor condition, basic maintenance to Bowmart Parkway would make this a more appealing route providing direct access to trip generating attractions.

Sheridan Drive from Niagara Falls Boulevard to Millersport Highway

Sheridan Drive is a major east-west arterial that carries large volumes of traffic. Sheridan Drive is a six-lane road with three lanes in each direction and exclusive turn lanes at intersections. The cycle lengths at traffic signals on Sheridan Drive are very long creating excessive delay. Sheridan Drive could benefit from operating on a coordinated network with update signal timings.

**Intersections**

Maple Road at Sweet Home Road

Maple Road at Sweet Home Road is currently approaching capacity under existing conditions and has injury crashes and severe crash types. This intersection will also experience an increase in traffic volumes due to the planned development. This intersection should be investigated for mitigation to provide capacity and safety improvements.

Sheridan Drive at Sweet Home Road

This intersection currently has multiple movements with a LOS E or F and has injury crashes and severe crash types. There is available capacity at the intersection, but timings should be revised, and the intersection should be investigated for safety improvements.


Emerson Drive at North Bailey Avenue

This is a 5-legged intersection with all approaches operating under stop control. In prior studies, this intersection has been recommended for conversion to a roundabout to improve safety and operations. This recommendation was identified in the previous GEIS. It is recommended to continue with the previously identified mitigation to convert this intersection to a roundabout.

Maple Road at North Bailey Avenue

This intersection was recently awarded Congestion Mitigation and Air Quality (CMAQ) to make capacity improvements. In addition to a need for improved capacity, this intersection also experiences a high frequency of severe crash types. Capacity and safety improvements should be investigated.

Figure 11: Mitigation Map



# APPENDIX C

## MITIGATION OBJECTIVES

# Mitigation Objectives

Mitigation is recommended at street segments and intersections throughout the Boulevard Central District (BCD) due to capacity, efficiency, or safety constraints. These constraints are sometimes present in existing conditions and expected to be exasperated by future traffic demands due to development, or are a need to be addressed in the future condition once development has been established. Recommended improvements primarily focus on improvements to capacity, efficiency, and safety.

## Capacity

There are existing locations throughout the BCD Area that are already approaching or have reached capacity, which is primarily controlled by the ability of the physical infrastructure to accommodate traffic demands. To increase capacity, mitigation will depend on whether the infrastructure is an intersection or road segment. For signalized intersections, capacity can be increased by additional lanes at the intersection or by installing congestion management technology such as adaptive signal timings. For road segments, an increase in capacity is typically limited to increasing the number of travel lanes, and/or also providing turn lanes to remove turning vehicles from through traffic. There are a number of other methods to help improve capacity such as restricting left turns, changing intersection control, and providing additional multimodal options to reduce dependency on single occupancy vehicles, etc.


## Efficiency

There are locations throughout the BCD area where there is available capacity within the physical infrastructure to accommodate the demand, but the level of service is poor with higher delays due to the inefficiencies of a traffic signal or signal network. Improvements can be made to reduce delay through updated timings, network coordination, and signal detection technology.

## Safety

There are existing locations that have a high number of crashes, and/or severe crash types. Existing crashes should be mitigated since additional traffic or growth will add to the number of conflicts, potentially compounding an existing safety deficiency. Many of these countermeasures for mitigation projects were identified as broad scale treatments in the Greater Buffalo Niagara Regional Transportation Council (GBNRTC) Roadway All-user Crash Elimination (RACE) Plan. Countermeasures include updated clearance times, adding backplates to signal heads, enhanced pavement markings, and no turn on red signage.

**Figure 1: Mitigation Map**




# Proposed Mitigation Projects

A table of proposed mitigation projects is on the next page with further explanation of existing and/or future needs to be addressed and recommended improvements to mitigate those needs. Additional information is provided on adaptive signal timings following the mitigation table.

| Boulevard Central District Mitigation Concepts | | | | | |
|---|---|---|---|---|---|
| Location | | Existing and/or Future Build Needs to Address | Jurisdiction | Recommended Improvements | Improvement Results |
| Segments | Niagara Falls Boulevard:<br>Ridge Lea Road to Sheridan Drive | • Efficiency: Side streets and exclusive turn lanes have long delays and poor levels of service to accommodate heavy northbound and southbound traffic volumes on Niagara Falls Boulevard.<br>• Safety: There are a high number of crashes, including pedestrians and bicyclists, at signalized intersections, including NFB at Ridge Lea Road, Romney Road, Maple Road, and Sheridan Drive. | NYSDOT | • Adaptive Signal Control | • Improved traffic flow and performance measures during peak and off-peak periods.<br>• Reduced delay for side streets and auxiliary turns.<br>• Improved pedestrian and bicycle crossing times through detection with the ability to extend crossing times when peds/bicycles detected in the crosswalks. |
| | Ridge Lea Road/North Bailey Avenue:<br>Niagara Falls Boulevard to Maple Road | • Capacity: N Bailey Avenue is approaching capacity under existing conditions based on ATR data collected in February 2023. Counts show a daily volume of approximately 17,000 vehicles per day, and peak hourly volumes of 1,400 vehicles per hour. Traffic will increase with planned development including Costco with fueling stations and Dick's House of Sport | Town of Amherst | • Widen from one-lane in each direction with turn lanes, to two-lanes in each direction with turn lanes | • Additional capacity to accommodate future traffic due to development in the area. |
| | Bowmart Parkway:<br>Maple Road to Meyer Road | • Pavement Surface: A private road is being constructed across from where Bowmart Parkway currently ends at Meyer Road, which will provide access to the newly constructed Amherst Commerce Park. This direct access to Amherst Commerce Park will potentially make Bowmart Parkway a more appealing route for trips originating from and going to the southeast. Bowmart Parkway has enough capacity, but has a pavement surface in poor condition. | Town of Amherst | • Resurfacing | • Bowmart Parkway as an alternative route could alleviate some traffic from North Bailey Avenue and congestion at the signalized intersection of North Bailey Avenue and Meyers Road, which is already at capacity. |
| | Sheridan Drive:<br>Niagara Falls Boulevard to Millersport Highway | • Efficiency: Cycle lengths are currently long (160 seconds) with poor LOS and increasing delay on side streets and left turn movements. | NYSDOT | • Revised signal timings and coordination. | • Improved traffic flow and performance measures<br>• Reduced delay for side streets and auxiliary turns. |
| Intersections | North Bailey Avenue<br>at Maple Road | • Capacity: Under future conditions, left turns and the North Bailey Avenue approaches are expected to experience long delays and poor levels of service due to the expected increase in traffic due to planned nearby development along North Bailey Avenue.<br>• Safety: High frequency of left turn crashes with a high number of total crashes. Traffic signals operate with protected/permissive left turns. Operating as protected lefts only impacts capacity and level of service. | Town of Amherst | *Improvements are to be completed under an existing CMAQ Project.*<br>• Updated timings including exclusive left turns, improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out)<br>• Installation of a second southbound left turn lane<br>• Possible traffic signal replacement for widening | • Additional capacity to accommodate future left turn volumes southbound on North Bailey Avenue<br>• Improved safety through clearance times and traffic signal intersection countermeasures |


| Boulevard Central District Mitigation Concepts | | | | | |
|---|---|---|---|---|---|
| Location | | Existing and/or Future Build Needs to Address | Jurisdiction | Recommended Improvements | Improvement Results |
| Intersections | Maple Road<br>at Sweet Home Road | • Capacty and Efficiency: Multiple movements under the existing conditions have a LOS E including NB through, SB through, and EB left. Deteriorating LOS is expected in future conditions with additional traffic. In future conditions the intersection is expected to be over capacity.<br>• Safety: This intersection has the highest number of crashes in the study area. Most crashes are rear ends with the second most common being left turn. | NYSDOT | • Updated timings including exclusive left turns and improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out)<br>• Adjust the northbound approach – NB right turn lane changes to right and through lane<br>• Adjust signal timing | • Increase capacity northbound/southbound/EB lefts<br>• Improved safety through clearance times and traffic signal intersection countermeasures |
| | Sheridan Drive<br>at Sweet Home Road | • Capacty and Efficiency: Multiple movements under the existing conditions have a LOS E or F including NB through, EB left, and WB left. Deteriorating LOS is expected in future conditions with additional traffic.<br>• Safety: This intersection has a high number of severe type crashes compared to others in the study area. Outside of rear ends, the predominant crash types are right angles and left turns. There was also a bicycle hit, Sweet Home Road is a bicycle route. | NYSDOT | • Updated timings including exclusive left turns and improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out), and bicycle boxes<br>• Adjust signal timing, cycle length too long even considering it is a part of a coordinated network, including leading pedestrian and bicycle intervals | • Improved LOS for turning movements.<br>• Improved efficiency and reduced delay with improved signal timings and coordination<br>• Improved pedestrian and bicycle safety |
| | Emerson Drive<br>at North Bailey Avenue | • Efficiency: Northbound and southbound approaches experience long queues and delays (up to 20 vehicles) during peak hour. Future development is anticipated to increase volumes on the northbound and southbound approaches of North Bailey Avenue. | Town of Amherst | • Convert to roundabout | • Improved efficiency and flow through the intersection, serving the higher demand movements of northbound and southbound.<br>• Improved safety with less conflict points. |

## Adaptive Signal Control Technology

Adaptive signal control (ASCT) is an advanced traffic signal system that adjusts signal timings in real time based on current traffic conditions. Unlike fixed-time or actuated signals that operate using pre-programmed timing plans, ASCT systems continuously monitor traffic volumes, queues, and flow patterns to dynamically adjust green times, cycle lengths and signal coordination across multiple intersections in a corridor. ASCT supports multi-mobility demands to respond to vehicles, peds, bike, and buses. The goal of adaptive signal control is to reduce congestion, stops, delay emissions, and to improve travel time by responding to actual traffic patterns instead of relying on pre-fixed timing schedules. The more intersections and data that ASCT has to utilize, the better the performance. ASCT responds strongly to special events and traffic pattern anomalies. ASCT performs best during off-peak peak periods and is less effective with at capacity roadways during peak periods.

Implementation of adaptive signal control systems typically begins with evaluation and data collection to establish baseline performance. Installation of upgraded signal controllers, detection hardware and a reliable communication infrastructure may be necessary to implement adaptive signal control systems. Adaptive signal control software can then be installed, and a burn in period of several weeks to collect and analyze data to build a baseline. Then the next steps involve calibration and fine-tuning of minimum green times, coordination, and logic rules to meet the objectives for the corridor network. This is effective in comparing before/after comparisons and system performance. There is no impact to existing transit signal priority (TSP) or emergency vehicle priority (EVP) systems.

Niagara Falls Boulevard, Maple Road and Sweet Homes Road in the Town of Amherst have existing Miovision signal detection cameras installed. Miovision's TrafficLink platform (now called Miovision One) can be integrated with the SURTRAC adaptive signal control system because there is already a video detection camera system, real time traffic data, and cloud connectivity available. SURTRAC is a decentralized system that involves software level integration rather than major hardware changes. However additional hardware to expand the effectiveness can include advanced detection cameras. The SURTRAC system is modular and cloud-connected, adaptive operations can be implemented quickly, minimizing installation costs and disruption. Estimated costs are a one-time purchase of $8,950 per intersection and optional $2,000 per intersection for maintenance and support.



# Mitigation

## Mitigation Measures

Mitigation measures were identified to offset the impacts of anticipated traffic resulting from a land use and development plan. These mitigation measures reflect estimates in trip generation assuming full build out of the BCD area, based on the Town's updated land use and zoning projections. The identified intersection of Maple Road at N Bailey Avenue is already being progressed as a funded project through the Congestion Mitigation and Air Quality (CMAQ) program to improve capacity. Therefore, this intersection is not included as a part of mitigation costs.

Street Segments

- Niagara Falls Boulevard from Ridge Lea Road to Sheridan Drive
- Ridge Lea Road from Niagara Falls Boulevard to N Bailey Avenue
- Bowmart Parkway: Maple Road to Meyer Road
- Sheridan Drive: Niagara Falls Boulevard to Millersport Highway

Intersections

- Maple Road at Sweet Home Road
- Sheridan Drive at Sweet Home Road
- Emerson Drive at N Bailey Avenue
- Maple Road at N Bailey Avenue

Table 1 contains updated cost estimates for the identified mitigation above. For planning purposes, mitigation projects are assumed to occur over the short (5 year horizon) and mid-term (10 year horizon). There are many factors that would be considered on which and when projects are to be implemented. This will depend on when, where, and the type of development that occurs, which cannot be predicted. Therefore, the cost of mitigation projects will use the midpoint (5-year time frame). To determine future costs, a 3% compounded inflation rate was used for each project, which is the standard inflation rate used by the NYSDOT to project future costs on projects at the design approval stage. Inflation rates for construction consider increased prices of materials, supply-chain constraints, and an increased cost for skilled labor. Costs developed assume public works projects that require prevailing wages. Trip and cost estimates are approximate and may not reflect how development actually occurs over time, therefore it is recommended to review and update the fee and schedule periodically as development occurs.

Table 1: Estimated Mitigation Improvement and Associated Costs

| Location | Improvements | | Estimated Cost | | |
|---|---|---|---|---|---|
| | | | 2025 Cost | 2030 Cost | 2035 Cost |
| Corridor Improvements | | | | | |
| Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive | Adaptive signal control using ITS technology | Design | $21,750 | $26,250 | $29,250 |
| | | Construction | $145,000 | $175,000 | $194,900 |
| | | Construction CS/CI | $14,500 | $17,500 | $19,500 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | *Total Cost* | *$181,250* | *$218,750* | *$243,650* |
| Ridge Lea Road/N Bailey Avenue: Niagara Falls Boulevard to Maple Road | Add a travel lane in each direction with turn lanes at intersections | Design | $3,157,150 | $3,660,000 | $4,242,950 |
| | | Construction | $21,047,650 | $24,400,000 | $28,286,300 |
| | | Construction CS/CI | $2,104,800 | $2,440,000 | $2,828,650 |
| | | ROW Acquisition | TBD | TBD | TBD |
| | | *Total Cost* | *$26,309,600* | *$30,500,000* | *$35,579,000* |
| Bowmart Parkway: Maple Road to Meyer Road | Resurfacing | Design | $32,250 | $38,250 | $43,350 |
| | | Construction | $215,000 | $255,000 | $288,950 |
| | | Construction CS/CI | $21,500 | $25,500 | $28,900 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | *Total Cost* | *$268,750* | *$318,750* | *$361,200* |
| Sheridan Drive: Niagara Falls Boulevard to Millersport Highway | Revised signal timings and coordination | Design | $1,200 | $1,400 | $1,650 |
| | | Construction | $8,000 | $9,300 | $10,750 |
| | | Construction CS/CI | $800 | $1,000 | $1,100 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | *Total Cost* | *$10,000* | *$11,700* | *$13,500* |

Table 1 Continued: Estimated Mitigation Improvement and Associated Costs

| Location | Improvements | | Estimated Cost | | |
|---|---|---|---|---|---|
| | | | 2025 Cost | 2030 Cost | 2035 Cost |
| Intersection Improvements | | | | | |
| Maple Road at Sweet Home Road | • Updated timings including exclusive left turns and improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out)<br>• Adjust the northbound approach – NB right turn lane changes to right and through lane | Design | $12,150 | $15,150 | $16,330 |
| | | Construction | $81,000 | $101,000 | $108,850 |
| | | Construction CS/CI | $8,100 | $10,100 | $10,900 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | *Total Cost* | ***$101,250*** | ***$126,250*** | ***$136,050*** |
| Sheridan Drive at Sweet Home Road | • Updated timings including exclusive left turns and improved yellow/red times<br>• Installation of safety improvements including backplates, enhanced pavement markings, No Turn on Red signs (Overhead Blank-Out), and bicycle boxes<br>• Adjust signal timing, cycle length too long even considering it is a part of a coordinated network, including leading pedestrian and bicycle intervals | Design | $12,150 | $15,150 | $16,330 |
| | | Construction | $81,000 | $101,000 | $108,850 |
| | | Construction CS/CI | $8,100 | $10,100 | $10,900 |
| | | ROW Acquisition | N/A | N/A | N/A |
| | | *Total Cost* | ***$101,250*** | ***$126,250*** | ***$136,050*** |
| Emerson Drive at N Bailey Avenue | Convert to a roundabout | Design | $291,750 | $338,250 | $392,100 |
| | | Construction | $1,945,000 | $2,255,000 | $2,613,950 |
| | | Construction CS/CI | $194,500 | $225,500 | $261,400 |
| | | ROW Acquisition | TBD | TBD | TBD |
| | | *Total Cost* | ***$2,431,250*** | ***$2,818,750*** | ***$3,267,450*** |
| Total Mitigation Improvement Costs | | | $29,403,350 | $34,120,450 | $39,520,250 |

## Mitigation Cost Program

Mitigation measures were developed through land use assumptions and projections in the GEIS. The NYS SEQR is the legal basis to determine each development's contribution towards transportation improvements to mitigate congestion, safety deficiencies, and other adverse impacts from proposed development. This may also alleviate the need for individual traffic impact studies for each proposed development within the Study Area, but a trip generation analysis/traffic impact analysis would be needed to determine site access improvements and private contributions towards the mitigation cost share. Not included in these transportation improvements are site access improvements that are required to mitigate the direct impact of any individual development, i.e. traffic signals, turn lanes into driveways, access roads, and any treatments beyond what is outlined in this document. Site access improvements are still required to be implemented by the developer as part of site plan approval.

Mitigation costs are calculated based on a development's percentage consumption of new peak-hour, peak-direction traffic capacity by roadway segment or intersection, and the cost by link or node of creating that capacity. Costs are split into two shares; a public share, and a private share of proportional costs.

*Public Share*
The public share will incorporate costs considering the following:

- existing and background growth
- new traffic to and from residential locations within the Study Area
- existing and new traffic to and from public institutions (e.g. University at Buffalo)
- the amount of additional reserve capacity created (reserve capacity can be expected to be minimal, even after implementation of planned improvements)
- safety improvements
- costs may be covered under State or Federal grant funding, and supported by NYSDOT, Erie County Department of Public Works, and the Town

*Private Share*
The private share will incorporate costs considering the following:

- existing and new traffic to and from commercial properties in the Study Area
- new residential traffic in the Study Area

The following process was used for determining the public and private shares for transportation mitigation improvement projects:

1) Determine Benefited Area: The benefited areas are delineated by the boundaries established for the Study Area. The parcels internal to this boundary area have been identified as the primary beneficiaries of the construction of the identified mitigation improvements. Exceptions include parcels located within the study area that are pre-existing to the implementation of mitigation improvements. If parcels are redeveloped and incorporated as a part of the proposed roadway network, the formula should incorporate and charge such a parcel for their cost-share. The general public at large and

external parcels will be considered secondary beneficiaries to the mitigation improvement projects. These external parcels are considered background traffic generators and are therefore the responsibility of the public share.

2) Calculate Costs of Improved Facilities: The cost of each planned roadway improvement includes design, construction, and supervision expressed in projected dollars. Construction, engineering, and management costs will be indexed according to NYSDOT's construction price trends. Costs for highway maintenance, renewal, or reconstruction are excluded from the cost basis to be shared; these will be the responsibility of the roadway jurisdictional owner.

   Site access improvements are those that are required to mitigate the direct impact of any individual development. Examples of site improvements are additional turning lanes, traffic signals, or other traffic control devices beyond those outlined as a part of this GEIS. Other site access improvements may include but are not limited to access roads, sidewalks, lighting, raised medians, landscaping, and other treatments not specific in this GEIS. These are implemented by the private developers.

3) Determine Available Capacity: *Available Capacity* is defined as the existing unused capacity from Tables 5 and 6, plus either the additional one-way peak direction capacity of the reconstructed/new facilities or total approach capacity for intersections. Capacity values were calculated based on guidelines in the Highway Capacity Manual, using base threshold volumes to maintain a LOS D or better at a planning level basis. For intersections, capacity can be difficult to measure as similar to an urban street, there are many factors that impact capacity including signal timings, detection, queues, peak hour factor, etc. Therefore, the intersection capacity utilization tool in Synchro was used for each intersection, which determines the amount of available capacity.

4) Calculate Available Capacity Consumed: The amount of available capacity used by traffic generated by the proposed project is calculated by dividing the development projected trips for the Study Area by the total available capacity for improvement projects.

5) Calculate Development Cost Share: Development cost share is based on the amount of available capacity consumed by PM peak hour trips generated by projected new development. Mitigation costs are calculated for new trips only.

$$\text{Private Share} = \text{Cost} \times \frac{\text{Additional Development Trips}}{(\text{Total New Trips} + \text{Additional Reserve Capacity})}$$

$$\text{Public Share} = \text{Cost} \times \frac{(\text{New Non-Development Trips} + \text{Additional Reserve Capacity})}{(\text{Total New Trips} + \text{Additional Reserve Capacity})}$$

There are existing streets and intersections which have capacity to accommodate additional traffic volumes but they are not operating at full potential based on inefficiencies with the traffic signal network, or the infrastructure, such as the road surface is in poor condition making it a less appealing

route. Some of these streets and intersections provide direct access through a public street to new development areas and relieve congestion from parallel routes which are at capacity.

Table 2: Threshold Analysis for Improvements

| | PM Peak Hour Traffic (vph) | | LOS D Threshold | | |
|---|---|---|---|---|---|
| | Existing (2025) Volume | Planned Demand Volume | Maximum Volume* | Volumes that Could be Accommodated | % Cost of Private Share Improvements |
| Street Segments | | | | | |
| *Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive* | | | | | |
| | 3,700 | 4,300 | 3,700 | 0 | 0% |
| | w/adaptive signal control | | 4,300 | - | 100% |
| *Ridge Lea Road/N Bailey Avenue: Niagara Falls Boulevard to Maple Road* | | | | | |
| | 1,660 | 2,090 | 1,680 | 20 | - |
| | w/ 4 lane cross section | | 2,500 | 820 | 35% |
| *Bowmart Parkway: Maple Road to Meyer Road* | | | | | |
| | 434 | 560 | 1,680 | 1,120 | - |
| | w/upgrades | | 1,680 | 1,120 | 10% |
| *Sheridan Drive: Niagara Falls Boulevard to Millersport Highway* | | | | | |
| | 2,600 | 2,850 | 2,600 | 250 | 0% |
| | w/ coordinated network | | 2,850 | - | 100% |
| Intersections | | | | | |
| *Maple Road at Sweet Home Road* | | | | | |
| | 3,093 | 4,637 | 3,436 | 343 | - |
| | w/ lane and timing changes | | 5,040 | - | 21% |
| *Sheridan Drive at Sweet Home Road* | | | | | |
| | 2,897 | 3,187 | 2,897 | 0 | - |
| | w/timing changes | | 3,400 | 213 | 57% |
| *N Bailey Avenue at Emerson Drive & Amsterdam Avenue (Stop Controlled)* | | | | | |
| | 1,225 | 1,390 | - | - | - |
| | roundabout | | - | - | 0% |

*The assumptions in this table are based on the principles of the 2010 Highway Capacity Manual which provides planning level engineering estimates for capacity. This is for a base condition and may vary per location depending on number of access points, speed, driver behavior, truck percentage, signal timings and spacing, etc. Values were also checked in Synchro running an arterial LOS analysis since each road has unique site condition impacting capacity.

Niagara Falls Boulevard from Ridge Lea Road to Sheridan Drive

This street segment is expected to operate under planned development at an arterial LOSE for northbound during the PM and Saturday peaks, the existing level of service for northbound is an E. Urban street LOS is based on travel speed as a percentage of base free-flow speed. There are many variables which impact the capacity and LOS of an urban street including signal timings and spacing, exclusive turn lanes and phasing at intersections, the peak hour factor, facility length, access points, etc. In addition, determining the capacity of

an adaptive signal-controlled network is difficult in the planning process, it is better measured in the field once implemented. Therefore it can be reasonably assumed that the adaptive signal control would be able to accommodate the increase in traffic volumes but reserve capacity for public benefit would be difficult to determine. The private share of these improvements is based on the number of planned trips expected to use Niagara Falls Boulevard and there would be no additional reserve capacity for public benefit.

Ridge Lea Road/N Bailey Avenue from Niagara Falls Boulevard to Maple Road

Segments of this road are expected to operate at an arterial LOS E, with the existing road approaching capacity volumes.

Bowmart Parkway from Maple Road to Meyer Road

Bowmart Parkway has capacity to accommodate existing and planned volumes; however, this will provide direct access to planned development with an extension of Bowmart Parkway north of Meyer Road. Bowmart Parkway could help relieve congestion from N Bailey Avenue, including the N Bailey Avenue at Maple Road intersection. Private share costs are based on the private/public share mitigation cost formulas.

Sheridan Drive from Niagara Falls Boulevard to Millersport Highway

Sheridan Drive is currently operating at a LOS D (westbound) and E (eastbound) during the PM peak. Some segments between intersections will experience a LOS E and F. It is assumed that any additional traffic volumes will degrade the arterial level of service to below a D and further degrade the LOS E for the eastbound direction. The private share of these improvements is based on the number of planned trips expected to use Sheridan Drive divided by the reserve capacity that is of public benefit.

The private share of these improvements is based on the number of planned trips expected to use Niagara Falls Boulevard and there would be no additional reserve capacity for public benefit.

## Trip Generation

The number of expected trips generated from the land use and zoning projections for the entire study area was determined using the Trip Generation Manual for the PM peak. The PM peak was chosen because it has the most data associated with trip generation for the multiple types of proposed developments.

The proposed land use plan was used to estimate the increase in trips into the study area. Each TAZ had trips estimated on a high level based on the planned development and type, assumptions were made for specific land use codes that correlate to the Trip Generation Manual for housing types, retail, and office space. The following are land use codes that were used and applied tailored to each TAZ.

| Residential | Retail | Office |
|---|---|---|
| 220: Multi-family (Low Rise) | 820: Shopping Center > 150k SF | 710: General Office Building |
| 221: Multi-family (Mid Rise) | 821: Shopping Plaza (40k-150l SF) | |
| | 822: Strip Retail Plaza (<40k SF) | |

The change in land use, which typically leads to an increase in development, was converted to planned trips which is shown in Table 3 below.

Table 3: TAZ Trip Generation

| TAZ | Residential | | | Commercial - Retail | | | Commercial - Office | | | Total Trips |
|---|---|---|---|---|---|---|---|---|---|---|
| | *Land Use* | *Units* | *PM Trips* | *Land Use* | *Retail (SF)* | *PM Trips* | *Land Use* | *Office (SF)* | *PM Trips* | |
| 668 | N/A | 0 | 0 | N/A | 0 | 0 | N/A | 0 | 0 | 0 |
| 676 | 221 | 78 | 31 | 821 | 82,062 | 748 | N/A | 0 | 0 | 779 |
| 677 | 221 | 494 | 193 | 821 | 109,678 | 960 | N/A | 0 | 0 | 1,153 |
| 678 | 221 | 1140 | 445 | 820 | 299,265 | 1243 | 710 | 99,755 | 166 | 1,853 |
| 679 | N/A | 0 | 0 | 820 | 310,159 | 1275 | N/A | 0 | 0 | 1,275 |
| 680 | 221 | 43 | 17 | 822 | 28,622 | 164 | N/A | 0 | 0 | 181 |
| 681 | 221 | 50 | 20 | 821 | 65,350 | 620 | N/A | 0 | 0 | 640 |
| 682 | 221 | 1551 | 605 | 820 | 831,015 | 2592 | 710 | 158,013 | 243 | 3,440 |
| 683 | 221 | 269 | 105 | 821 | 51,799 | 516 | N/A | 0 | 0 | 621 |
| 684 | 221 | 50 | 20 | 822 | 13,875 | 98 | N/A | 0 | 0 | 118 |
| 686 | 220 | 115 | 70 | 821 | 69,845 | 655 | N/A | 0 | 0 | 725 |
| 687 | 221 | 385 | 150 | N/A | 0 | 0 | N/A | 0 | 0 | 150 |
| 688 | 220 | 118 | 71 | 821 | 147,657 | 1251 | N/A | 0 | 0 | 1,323 |
| 699 | 220 | 20 | 29 | 822 | 7,000 | 60 | N/A | 0 | 0 | 90 |
| 701 | N/A | 0 | 0 | N/A | 0 | 0 | N/A | 0 | 0 | 0 |
| 702 | 221 | 200 | 78 | 821 | 52,500 | 522 | 710 | 17,500 | 39 | 639 |
| 705 | 221 | 320 | 125 | 821 | 84,000 | 763 | 710 | 28,000 | 58 | 946 |
| 708 | 221 | 90 | 35 | 822 | 31,394 | 175 | N/A | 0 | 0 | 211 |
| 709 | N/A | 0 | 0 | 821 | 74,456 | 690 | N/A | 0 | 0 | 690 |
| | | Total Trips | 1,996 | | | 12,333 | | | 505 | 14,835 |

The following table is a breakdown of the expected trips by land use type.

Table 4: Proposed PM Peak Hour Trips by Land Use Type for the Study Area

| Land Use | PM Peak Trips |
|---|---|
| Residential Housing | 1,996 |
| Retail | 12,333 |
| Office | 505 |
| *Total* | *14,835* |

The land use plan focuses on providing mixed-use development. Mixed-use developments typically have some portion of trips beginning and ending within the mixed-use development. An internal capture rate is applied to not double count trips on the external road system when some trips are visiting multiple locations within the mixed-use development either by driving or walking. The mixed-use development in the land use plan typically consists of retail/commercial establishments mixed with rental housing. In addition, retail and commercial trips are typically not all new trips, many are pass-by trips meaning those vehicles are already on route and stop by at a retail or commercial establishment on their existing route. Retail has an average pass-by rate of 29%. Therefore, a pass-by rate of 29% was applied to the retail trips only to obtain a new trip total for the area.

Table 5: Total Proposed PM Peak Hour Trips for the Study Area

| Land Use | PM Peak Trips |
|---|---|
| Residential Housing | 1,996 |
| Retail | 12,333 |
| Office | 505 |
| 10% internal capture | -1,484 |
| 29% pass-by rate (for retail) | -3,577 |
| *Total* | *9,773* |

Based on the number of trips anticipated with the private share percentage of each mitigation project, the mitigation cost per trip is **$1,130.**

Table 6: Private Share versus Public Share Costs

| Project | Private Share Cost (2030) | Public Share Cost (2030) |
|---|---|---|
| Niagara Falls Boulevard: Ridge Lea Road to Sheridan Drive | $218,750 | - |
| Ridge Lea Road: Niagara Falls Boulevard to N Bailey Avenue | $10,675,000 | $19,825,000 |
| Bowmart Parkway: Maple Road to Meyer Road | $31,880 | $286,880 |
| Sheridan Drive: Niagara Falls Boulevard to Millersport Highway | $11,700 | - |
| Maple Road at Sweet Home Road | $26,520 | $99,740 |
| Sheridan Drive at Sweet Home Road | $71,960 | $54,290 |
| N Bailey Avenue at Emerson Drive & Amsterdam Avenue | $0 | $2,818,750 |
| *Total* | *$11,035,810* | *$23,084,660* |

## Costs Contribution Determination for New Developments

A process is outlined below for determining the cost share each development will contribute towards the transportation mitigation improvements based on a cost per trip generated. The process includes:

1) Proposed Development Assumptions: Information about the proposed development is sent to the Town of Amherst to review, this will include an accompanying traffic study. The Town will determine if the proposal contains enough information for a review. Information should include development location, type, size, and layout, as well as a site plan showing ingress and egress connections to existing streets. The traffic study should be an abbreviated version which includes trip generation and methodology, trip distribution, and an existing and build capacity/operational analysis of an appropriate study area mutually delimited with the Town with consideration of anticipated trips and distribution.

    a) Review Development Trips: The trip generation of the proposed development would be calculated to determine mitigation cost. The trip generation should be calculated using the methodology established by the *Institute of Transportation Engineers* in the most recent edition of the ***Trip Generation Manual***. The output of this step is trip ends, which is trips entering and exiting the proposed development during the PM peak hour.

    *Pass-By Trips:* For developments that are identified in the ITE Trip Generation Manual that must account for pass-by trips such as gas stations, banks, service stations, etc. this can be used when appropriate. A pass-by trip is defined as traffic passing the site on the street that contains direct access to the development, this is not to be mistook for a diverted trip. The pass-by adjustment rate is to be based on the ITE Trip Generation Manual, or surveys conducted by a qualified engineer or planner with industry standard accepted methodology and agreed upon by the Town.

    *Redevelopment:* For redevelopments, the trip generation rate is adjusted for traffic generated by the previous development, ***if*** that development was in operation during the traffic data collection for the GEIS (2022). The credit should be based on traffic counts compiled for the former land use, if available. If actual traffic data is not available, then the credit will be based on trips calculated from the ITE Trip Generation Manual.


    b) Distribute Trips: Trips generated from the development will be distributed to the adjacent roadway to determine if access improvements may be required.

2) Once the number of trips has been determined, the defined cost per trip will be applied to the development as a contribution for public transportation mitigation improvements.

# APPENDIX C

## CONCEPTUAL LAYOUTS OF MITIGATION MEASURES

# RIDGE LEA ROAD/NORTH BAILEY AVENUE NIAGARA FALLS BOULEVARD TO MAPLE ROAD




50 0 50 100 150 200'

1" = 100'

C&S COMPANIES®
C&S Engineers, Inc.
141 Elm Street, Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

## TRANSPORTATION IMPROVEMENT CONCEPT LAYOUT

BOULEVARD CENTRAL DISTRICT
GENERIC ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENTAL
TOWN OF AMHERST, ERIE COUNTY, NEW YORK

FIGURE 1

DATE: AUGUST 2025

C&S PROJECT NO.: H22.007.001

Copyright ©

# RIDGE LEA ROAD/NORTH BAILEY AVENUE NIAGARA FALLS BOULEVARD TO MAPLE ROAD




C&S COMPANIES®
C&S Engineers, Inc.
141 Elm Street, Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

## TRANSPORTATION IMPROVEMENT CONCEPT LAYOUT

BOULEVARD CENTRAL DISTRICT
GENERIC ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENTAL
TOWN OF AMHERST, ERIE COUNTY, NEW YORK


**FIGURE 2**

DATE: AUGUST 2025

C&S PROJECT NO.: H22.007.001

Copyright ©

# RIDGE LEA ROAD/NORTH BAILEY AVENUE NIAGARA FALLS BOULEVARD TO MAPLE ROAD




50 0 50 100 150 200'

1" = 100'

C&S COMPANIES®

C&S Engineers, Inc.
141 Elm Street, Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

## TRANSPORTATION IMPROVEMENT CONCEPT LAYOUT

BOULEVARD CENTRAL DISTRICT
GENERIC ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENTAL
TOWN OF AMHERST, ERIE COUNTY, NEW YORK


FIGURE 3

DATE: AUGUST 2025

C&S PROJECT NO.: H22.007.001

Copyright ©

# RIDGE LEA ROAD/NORTH BAILEY AVENUE NIAGARA FALLS BOULEVARD TO MAPLE ROAD




50 0 50 100 150 200'

1" = 100'

C&S COMPANIES®
C&S Engineers, Inc.
141 Elm Street, Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

## TRANSPORTATION IMPROVEMENT CONCEPT LAYOUT

BOULEVARD CENTRAL DISTRICT
GENERIC ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENTAL
TOWN OF AMHERST, ERIE COUNTY, NEW YORK

FIGURE 4

DATE: AUGUST 2025

C&S PROJECT NO.: H22.007.001

Copyright ©

# MAPLE ROAD AT SWEET HOME ROAD




50 0 50 100 150 200'

1" = 100'

C&S COMPANIES®
C&S Engineers, Inc.
141 Elm Street, Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

## TRANSPORTATION IMPROVEMENT CONCEPT LAYOUT

BOULEVARD CENTRAL DISTRICT
GENERIC ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENTAL
TOWN OF AMHERST, ERIE COUNTY, NEW YORK

FIGURE 5

DATE: AUGUST 2025

C&S PROJECT NO.: H22.007.001

Copyright ©

# SHERIDAN DRIVE AT SWEET HOME ROAD




50 0 50 100 150 200'

1" = 100'

C&S COMPANIES®
C&S Engineers, Inc.
141 Elm Street, Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

## TRANSPORTATION IMPROVEMENT CONCEPT LAYOUT

BOULEVARD CENTRAL DISTRICT
GENERIC ENVIRONMENTAL IMPACT STATEMENT SUPPLEMENTAL
TOWN OF AMHERST, ERIE COUNTY, NEW YORK

FIGURE 6

DATE: AUGUST 2025

C&S PROJECT NO.: H22.007.001

Copyright ©

# Existing Conditions Memo
# Appendix A – Figures



Ridge Lea Rd
Romney Rd
Meyer Rd
Maple Rd
Niagara Falls Blvd
N Bailey Ave
Bowmart Pkwy
Alberta Dr
Sweet Home Rd
Millersport Hwy
Sheridan Dr
Eggert Rd
Bailey Ave
Legend
Sidewalks
None
One Side
Both Sides
Bike Infrastructure
Road with Bike Lanes
NYS Bike Route
Off-Road Path
Signalized Intersection
Stop Controlled Intersection
Traffic Study Boundary
Boulevard Central District (BCD) Boundary
0 0.1 0.2 0.4 Miles

Figure 1





Ridge Lea Rd
Romney Rd
Meyer Rd
Maple Rd
N Bailey Ave
Bowmart Pkwy
Niagara Falls Blvd
Alberta Dr
Sweet Home Rd
Millersport Hwy
Sheridan Dr
Eggert Rd
Bailey Ave
Legend
Bus Stop Location
NFTA Bus Routes
Traffic Study Boundary
Boulevard Central District (BCD) Boundary
0 0.1 0.2 0.4 Miles

Figure 2





| | | | |
|---|---|---|---|
| C&S COMPANIES® | Boulevard Central Distict - GEIS Update<br>TOWN OF AMHERST, ERIE COUNTY, NEW YORK<br>Project No. H22.007.005 Date: Apr-25 | **Legend**<br>AM Peak Hour: N/A<br>PM Peak Hour: 4:30 - 5:30 PM<br>SAT Peak Hour: (1:30 - 2:30 PM)<br>Signalized:<br>Stop Controlled:<br>Roundabout:<br>Thru Movement:<br>Right Turn Movement:<br>Left Turn Movement | **Figure 3**<br>2023 Existing Conditions<br>Peak Hour Volumes |




## Level of Service Map: Existing Conditions PM Peak

Traffic Impact Study: Town of Amherst Boulevard Central District
Town of Amherst, Erie County, New York

Figure 4





# Level of Service Map: Existing Conditions SAT Peak

Traffic Impact Study: Town of Amherst Boulevard Central District
Town of Amherst, Erie County, New York

Figure 5

# Planned Conditions Memo
# Appendix A – Figures




Boulevard Central District
Percent Change in PM Peak Period Modeled Volume
2020 Base vs 2020 Base with BCD Forecast
GBNRTC Travel Demand Model 2020 Base Year
Prepared by GBNRTC, November 2024

Figure 1





TAZ: 668
TAZ: 676
TAZ: 679
TAZ: 677
TAZ: 678
N Bailey Ave
Niagara Falls Blvd
Maple Rd
TAZ: 688
TAZ: 687
TAZ: 681
TAZ: 682
TAZ: 680
TAZ: 684
TAZ: 686
Sweet Home Rd
Millersport Hwy
TAZ: 683
Sheridan Dr
TAZ: 705
TAZ: 702
Eggert Rd
TAZ: 701
TAZ: 708
TAZ: 709
TAZ: 699
Legend
TAZ Percent (%) Development Volume Growth
Less than 5%
5%
6%
22%
33%
Traffic Study Boundary
Boulevard Central District (BCD) Boundary
0
0.15
0.3
0.6 Miles


Figure 2





| | | | |
|---|---|---|---|
| C&S COMPANIES® | Boulevard Central Distict - GEIS Update<br>TOWN OF AMHERST, ERIE COUNTY, NEW YORK<br>Project No. H22.007.005 Date: Apr-25 | **Legend**<br>AM Peak Hour: N/A<br>PM Peak Hour: 4:30 - 5:30 PM<br>SAT Peak Hour: (1:30 - 2:30 PM)<br>Signalized:<br>Stop Controlled:<br>Roundabout:<br>Thru Movement:<br>Right Turn Movement:<br>Left Turn Movement | **Figure 3**<br>2023 Existing Conditions<br>Peak Hour Volumes |





| | | | |
|---|---|---|---|
| C&S COMPANIES® | Boulevard Central Distict - GEIS Update<br>TOWN OF AMHERST, ERIE COUNTY, NEW YORK<br>Project No. H22.007.005 Date: Apr-25 | **Legend**<br>AM Peak Hour: N/A<br>PM Peak Hour: 4:30 - 5:30 PM<br>SAT Peak Hour: (1:30 - 2:30 PM)<br>Signalized:<br>Stop Controlled:<br>Roundabout:<br>Thru Movement:<br>Right Turn Movement:<br>Left Turn Movement | **Figure 4**<br>Segment<br>Growth Volumes |





| | | | |
|---|---|---|---|
| C&S COMPANIES® | Boulevard Central Distict - GEIS Update<br>TOWN OF AMHERST, ERIE COUNTY, NEW YORK<br>Project No. H22.007.005 Date: Apr-25 | **Legend**<br>AM Peak Hour: N/A<br>PM Peak Hour: 4:30 - 5:30 PM<br>SAT Peak Hour: (1:30 - 2:30 PM)<br>Signalized: Stop Controlled: Roundabout:<br>Thru Movement: Right Turn Movement: Left Turn Movement: | **Figure 5**<br>Distribution Split Percentages |




| | | | |
|---|---|---|---|
| C&S COMPANIES® | Boulevard Central Distict - GEIS Update<br>TOWN OF AMHERST, ERIE COUNTY, NEW YORK<br>Project No. H22.007.005 Date: Apr-25 | **Legend**<br>AM Peak Hour: N/A<br>PM Peak Hour: 4:30 - 5:30 PM<br>SAT Peak Hour: (1:30 - 2:30 PM)<br>Signalized:<br>Stop Controlled:<br>Roundabout:<br>Thru Movement:<br>Right Turn Movement:<br>Left Turn Movement | **Figure 6**<br>Intersection<br>Growth Volumes |





| | | | |
|---|---|---|---|
| C&S COMPANIES® | Boulevard Central Distict - GEIS Update<br>TOWN OF AMHERST, ERIE COUNTY, NEW YORK<br>Project No. H22.007.005 Date: Apr-25 | **Legend**<br>AM Peak Hour: N/A<br>PM Peak Hour: 4:30 - 5:30 PM<br>SAT Peak Hour: (1:30 - 2:30 PM)<br>Signalized:<br>Stop Controlled:<br>Roundabout:<br>Thru Movement:<br>Right Turn Movement:<br>Left Turn Movement | **Figure 7**<br>Planned Conditions<br>Peak Hour Volumes |




# Level of Service Map: Planned Conditions PM Peak

Traffic Impact Study: Town of Amherst Boulevard Central District
Town of Amherst, Erie County, New York


Figure 8




# Level of Service Map: Planned Conditions SAT Peak

Traffic Impact Study: Town of Amherst Boulevard Central District
Town of Amherst, Erie County, New York

Figure 9




# Degradation in Level of Service Map: PM Peak & SAT Peak

Traffic Impact Study: Town of Amherst Boulevard Central District
Town of Amherst, Erie County, New York

Figure 10




# Mitigation Map

Traffic Impact Study: Town of Amherst Boulevard Central District
Town of Amherst, Erie County, New York

Figure 11



Ridge Lea Rd
Romney Rd
Meyer Rd
N Bailey Ave
Bowmart Pkwy
Maple Rd
Niagara Falls Blvd
Alberta Dr
Sweet Home Rd
Millersport Hwy
Sheridan Dr
Eggert Rd
Bailey Ave
Legend
Collision Density
Low
High
Traffic Study Boundary
Boulevard Central District (BCD) Boundary
Vehicle Collision with Pedestrian
Vehicle Collision with Bicyclist
0 0.1 0.2 0.4 Miles

Figure 6

# Appendix B – Collision Data

**Crash Level Details**

| Case Number | X Coordinate | Y Coordinate | Crash Date | Crash Time | Case Year | Collision Type | Crash Severity | Crash Type | Light Conditions | Road Characteristics | Road Surface Conditions | Traffic Control | Traffic Way | Weather Conditions | Max Injury in Crash | Apparent Contributing Factor |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 38871509 | 189011.25 | 4766863.69 | 5/31/2021 | 10:25 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38871510 | 188425.0657 | 4768032.134 | 5/31/2021 | 1:33 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38871512 | 189858.48 | 4766811.31 | 5/31/2021 | 12:28 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38876317 | 188749.0898 | 4766878.276 | 6/3/2021 | 2:28 PM | 2021 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38881529 | 188427.4768 | 4768077.791 | 6/7/2021 | 12:04 AM | 2021 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(UNKNOWN,UNKNOWN) |
| 38883966 | 188569.2978 | 4768053.07 | 6/9/2021 | 12:31 PM | 2021 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH TREE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 38885359 | 189033.7304 | 4765971.024 | 6/9/2021 | 5:20 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(CELL PHONE (HAND HELD),DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38888038 | 189002.5469 | 4765350.334 | 6/8/2021 | 3:35 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38889485 | 189049.5833 | 4765689.68 | 6/11/2021 | 10:00 AM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(UNKNOWN,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38891620 | 188726.51 | 4765728.74 | 6/14/2021 | 5:50 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38891624 | 189018.0882 | 4765358.999 | 6/15/2021 | 11:16 AM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38893909 | 188689.2864 | 4768063.538 | 6/13/2021 | 11:45 AM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38894540 | 188428.2436 | 4768093.011 | 6/17/2021 | 3:36 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) / V5:(NOT APPLICABLE,NOT APPLICABLE) |
| 38896128 | 190961.7754 | 4766519.369 | 6/17/2021 | 4:17 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | OTHER | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38896926 | 188485.4118 | 4768059.483 | 6/19/2021 | 12:38 PM | 2021 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38896929 | 188460.5131 | 4768486.002 | 6/19/2021 | 1:48 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38897516 | 188744.0366 | 4768044.894 | 6/20/2021 | 12:19 PM | 2021 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38906531 | 188440.6939 | 4768077.191 | 6/7/2021 | 12:04 AM | 2021 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(DRIVER INATTENTION,NOT ENTERED) |
| 38906533 | 190845.4525 | 4766798.447 | 6/25/2021 | 6:42 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38907481 | 190838.4 | 4766825.93 | 6/26/2021 | 10:22 PM | 2021 | HEAD ON | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38916307 | 188306.78 | 4766160.2 | 7/3/2021 | 1:59 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38916953 | 188578.7527 | 4768052.576 | 7/5/2021 | 6:04 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | TWO-WAY,NOT DIVIDED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38927596 | 188462.03 | 4768514.94 | 7/12/2021 | 12:08 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38928659 | 188376.97 | 4766899.12 | 6/15/2021 | 6:15 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 38929028 | 189018.4 | 4765678.29 | 7/13/2021 | 1:03 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38929031 | 189858.48 | 4766811.31 | 7/12/2021 | 7:11 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38929033 | 188375.9398 | 4766883.915 | 7/13/2021 | 2:29 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38930697 | 188369.8221 | 4767086.513 | 7/14/2021 | 9:15 AM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | UNKNOWN | NONE | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,AGGRESSIVE DRIVING/ROAD RAGE) / V2:(AGGRESSIVE DRIVING/ROAD RAGE,NOT APPLICABLE) |
| 38938629 | 189228.36 | 4766851.93 | 7/14/2021 | 11:31 AM | 2021 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,UNPROTECTED | CLOUDY | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 38939770 | 188709.07 | 4765465.65 | 7/15/2021 | 12:16 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38943717 | 188326.35 | 4766431.76 | 7/20/2021 | 11:57 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38945734 | 189518.8593 | 4765724.173 | 7/9/2021 | 4:16 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38947668 | 189018.4 | 4765678.29 | 7/20/2021 | 5:50 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38871509 | 189011.25 | 4766863.69 | 5/31/2021 | 10:25 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38949124 | 189512.93 | 4765618.602 | 7/21/2021 | 7:52 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38952198 | 190946.82 | 4766542.14 | 7/28/2021 | 12:32 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND GRADE | DRY | NONE | NOT ENTERED | CLEAR | | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38954570 | 191137.12 | 4766817.45 | 8/1/2021 | 1:50 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38955555 | 189851.7652 | 4766797.637 | 7/31/2021 | 7:08 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38958491 | 188403.6752 | 4766897.273 | 8/3/2021 | 1:13 PM | 2021 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38959884 | 189241.4238 | 4767216.358 | 8/4/2021 | 8:11 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(UNSAFE SPEED,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38961123 | 188444.3045 | 4768102.118 | 7/19/2021 | 12:03 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 38962539 | 190967.26 | 4766528.08 | 8/6/2021 | 12:42 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,UNSAFE SPEED) / V2:(DRIVER INATTENTION,NOT APPLICABLE) |
| 38964625 | 188358.1 | 4766900.87 | 8/7/2021 | 4:23 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38964725 | 189018.4 | 4765678.29 | 8/8/2021 | 12:51 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38965537 | 188322.51 | 4766175.29 | 8/9/2021 | 2:07 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38969876 | 189011.25 | 4766863.69 | 8/13/2021 | 4:25 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38969886 | 189980.48 | 4766806.33 | 8/13/2021 | 11:51 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38970176 | 189518.47 | 4765713.68 | 8/9/2021 | 6:25 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NO PASSING ZONE | NOT ENTERED | CLEAR | | V1:(EATING OR DRINKING,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 38970981 | 189031.12 | 4767182.2 | 8/10/2021 | 6:20 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38975060 | 188353.4467 | 4766602.842 | 8/17/2021 | 8:28 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38976600 | 189513.5 | 4765618.53 | 8/16/2021 | 1:36 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38976613 | 188338.0463 | 4766902.552 | 8/13/2021 | 9:40 PM | 2021 | BICYCLIST | INJURY | COLLISION WITH BICYCLIST | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(NOT APPLICABLE,NOT APPLICABLE) |
| 38976669 | 190949.8033 | 4766528.722 | 8/17/2021 | 5:12 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38979901 | 190967.26 | 4766528.08 | 8/19/2021 | 3:17 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TURNING IMPROPER,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38979907 | 189017.49 | 4765347.34 | 8/20/2021 | 9:59 AM | 2021 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | DRY | MAINTENANCE WORK AREA | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(UNSAFE SPEED,PASSING OR LANE USAGE IMPROPERLY) |
| 38980805 | 188808.9179 | 4766859.414 | 8/13/2021 | 7:40 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAWN | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38982728 | 190238.28 | 4765545.61 | 8/23/2021 | 8:07 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38982739 | 188742.21 | 4765982.22 | 8/23/2021 | 1:28 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38982754 | 188422.1275 | 4767717.694 | 8/22/2021 | 3:15 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38985917 | 188280.1394 | 4765767.328 | 8/24/2021 | 3:45 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38985919 | 190238.28 | 4765545.61 | 8/2/2021 | 4:26 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38985950 | 188365.1864 | 4766738.621 | 8/25/2021 | 10:34 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38995813 | 188358.1 | 4766900.87 | 8/31/2021 | 9:47 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38995912 | 188957.9006 | 4765685.77 | 8/26/2021 | 4:15 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38997616 | 190238.28 | 4765545.61 | 9/1/2021 | 10:15 AM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 38998638 | 188371.07 | 4767103.06 | 9/2/2021 | 6:58 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38999379 | 190331.09 | 4765668.06 | 9/3/2021 | 7:58 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38999382 | 190226.55 | 4765530.23 | 9/4/2021 | 7:07 AM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAWN | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 38999388 | 189011.25 | 4766863.69 | 9/4/2021 | 12:25 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39001459 | 189019.33 | 4765693.39 | 9/6/2021 | 1:48 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39002611 | 188426.71 | 4768062.57 | 9/7/2021 | 12:27 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39002631 | 190238.28 | 4765545.61 | 9/7/2021 | 6:57 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,CELL PHONE (HANDS FREE)) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39002647 | 189011.25 | 4766863.69 | 9/6/2021 | 8:23 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39003951 | 188742.21 | 4765982.22 | 9/8/2021 | 8:41 AM | 2021 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) |
| 39003954 | 188376.97 | 4766899.12 | 9/8/2021 | 7:55 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39005144 | 188442.611 | 4768339.18 | 9/9/2021 | 2:20 PM | 2021 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(UNKNOWN,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPL

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39006527 | 188282.82 | 4765652.11 | 9/10/2021 | 1:22 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39007425 | 189347.6613 | 4766844.596 | 9/7/2021 | 4:00 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(BACKING UNSAFELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39007428 | 190954.98 | 4766536.54 | 9/10/2021 | 6:26 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39014972 | 190971.8412 | 4766561.932 | 9/8/2021 | 12:37 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39017442 | 190238.28 | 4765545.61 | 9/15/2021 | 8:54 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39017443 | 191307.08 | 4766812.67 | 9/16/2021 | 7:32 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(UNSAFE LANE CHANGE,GLARE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39018430 | 189389.35 | 4766841.83 | 9/17/2021 | 9:15 AM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39018447 | 188429.9766 | 4767856.632 | 9/17/2021 | 2:00 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNSAFE SPEED,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39019190 | 188296.28 | 4765784.38 | 9/18/2021 | 3:22 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(ALCOHOL INVOLVEMENT,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39020349 | 188725.61 | 4765714.2 | 9/11/2021 | 5:38 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39020490 | 189882.4855 | 4766806.156 | 9/17/2021 | 6:46 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39020647 | 188980.8148 | 4766865.342 | 9/19/2021 | 10:34 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39021979 | 190238.28 | 4765545.61 | 9/18/2021 | 12:34 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39023487 | 191120.6247 | 4766792.373 | 9/20/2021 | 3:50 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39024746 | 189015.5156 | 4765632.661 | 9/22/2021 | 2:28 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39025924 | 189018.4 | 4765678.29 | 9/22/2021 | 8:32 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39027816 | 188352.8492 | 4766595.287 | 9/25/2021 | 1:40 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39028546 | 189860.7354 | 4766816.973 | 9/26/2021 | 4:13 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39029747 | 188438.3212 | 4768031.534 | 9/23/2021 | 12:47 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39030538 | 188416.97 | 4767626.4 | 9/27/2021 | 1:25 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39030559 | 188416.97 | 4767626.4 | 9/27/2021 | 1:50 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39032282 | 188424.3803 | 4767757.571 | 9/28/2021 | 1:04 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39032283 | 189858.48 | 4766811.31 | 9/27/2021 | 3:05 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39032291 | 190967.26 | 4766528.08 | 9/27/2021 | 11:57 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39036061 | 191175.22 | 4766873.175 | 9/30/2021 | 12:43 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39036062 | 190997.133 | 4766600.019 | 9/29/2021 | 3:33 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39036067 | 191042.8817 | 4766671.334 | 9/29/2021 | 3:38 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39037118 | 188407.5077 | 4767465.744 | 10/1/2021 | 2:26 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(TURNING IMPROPER,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39037123 | 189513.5 | 4765618.53 | 10/1/2021 | 10:18 AM | 2021 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39037834 | 189242.3 | 4767022.02 | 10/1/2021 | 10:07 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39038273 | 188437.82 | 4766895.518 | 9/25/2021 | 3:24 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39040812 | 189020.9623 | 4765754.314 | 10/3/2021 | 1:05 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39040813 | 189523.7279 | 4765631.684 | 10/4/2021 | 11:13 AM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39044094 | 188281.23 | 4765785.74 | 10/2/2021 | 10:55 AM | 2021 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,DIVIDED,UNPROTECTED | CLEAR | | V1:(VIEW OBSTRUCTED/LIMITED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39044097 | 188365.1864 | 4766738.621 | 10/6/2021 | 1:03 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39044103 | 188626.7169 | 4767599.568 | 10/6/2021 | 12:22 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39045509 | 188270.29 | 4765658.69 | 9/23/2021 | 6:38 AM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39046336 | 189018.6556 | 4766954.829 | 10/8/2021 | 12:11 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39046414 | 189067.9943 | 4766859.861 | 10/7/2021 | 3:55 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39047227 | 188809.94 | 4766874.62 | 10/8/2021 | 6:13 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,GLARE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39049056 | 189858.48 | 4766811.31 | 10/11/2021 | 5:46 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39049057 | 189518.8593 | 4765724.173 | 10/7/2021 | 10:58 AM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,DIVIDED,UNPROTECTED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39052321 | 191175.22 | 4766873.175 | 10/12/2021 | 3:35 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(REACTION TO OTHER UNINVOLVED VEHICL,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39055428 | 189665.119 | 4766596.067 | 10/14/2021 | 5:39 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39056395 | 189011.25 | 4766863.69 | 10/16/2021 | 3:21 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39057128 | 189238.8 | 4766851.34 | 10/17/2021 | 2:49 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39057130 | 188415.1779 | 4767595.973 | 10/17/2021 | 11:51 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39058684 | 188358.1 | 4766900.87 | 9/21/2021 | 9:05 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39059254 | 188548.3813 | 4768055.07 | 10/17/2021 | 5:28 PM | 2021 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO KEEP RIGHT,LOST CONSCIOUSNESS) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39060921 | 188531.045 | 4768056.742 | 10/19/2021 | 9:29 AM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,NOT DIVIDED | CLEAR | | V1:(PASSING OR LANE USAGE IMPROPERLY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39066169 | 190459.43 | 4765840.66 | 10/21/2021 | 8:30 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(REACTION TO OTHER UNINVOLVED VEHICL,PAVEMENT SLIPPERY) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39066175 | 188378.7074 | 4766929.55 | 10/22/2021 | 7:30 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39067003 | 188376.97 | 4766899.12 | 10/22/2021 | 7:08 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TURNING IMPROPER,UNKNOWN) / V2:(UNKNOWN,NOT APPLICABLE) |
| 39070558 | 189389.35 | 4766841.83 | 10/24/2021 | 7:13 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | A - SERIOUS INJURY | V1:(UNKNOWN,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 39070560 | 190774.1914 | 4766270.399 | 10/25/2021 | 8:37 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39073594 | 191085.7346 | 4766739.439 | 10/12/2021 | 3:39 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39073852 | 189514.06 | 4765632.86 | 10/19/2021 | 5:15 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | UNKNOWN | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39074250 | 188401.99 | 4767631.09 | 10/26/2021 | 12:26 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | RAIN | | V1:(DRIVER INATTENTION,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39074319 | 189031.12 | 4767182.2 | 10/27/2021 | 5:23 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39077300 | 189887.16 | 4766805.89 | 10/15/2021 | 5:55 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(FOLLOWING TOO CLOSELY,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39077304 | 190954.98 | 4766536.54 | 10/5/2021 | 5:23 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39077308 | 188998.0331 | 4766661.512 | 10/29/2021 | 3:15 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39078189 | 189812.7771 | 4766812.517 | 10/30/2021 | 3:54 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39083046 | 188438.9318 | 4768044.454 | 10/31/2021 | 1:39 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39086580 | 189017.51 | 4766325.63 | 11/3/2021 | 7:45 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39089414 | 188809.3342 | 4766865.496 | 11/5/2021 | 12:59 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39089468 | 189017.51 | 4766325.63 | 10/20/2021 | 8:30 AM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39089479 | 189141.3675 | 4766856.232 | 11/5/2021 | 1:18 PM | 2021 | RIGHT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39089481 | 188341.9331 | 4766442.4 | 11/5/2021 | 5:00 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39089496 | 188951.0638 | 4766866.958 | 11/4/2021 | 10:31 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39090013 | 189228.36 | 4766851.93 | 11/7/2021 | 9:37 AM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39091993 | 188340.8396 | 4766427.09 | 11/8/2021 | 11:53 AM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39093975 | 189571.78 | 4766535.62 | 11/8/2021 | 11:54 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39093985 | 189000.8026 | 4766707.148 | 11/8/2021 | 5:25 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39094073 | 189543.4503 | 4766130.074 | 11/8/2021 | 3:20 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39095262 | 188596.9549 | 4766887.259 | 11/9/2021 | 2:17 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39097063 | 189010.649 | 4766856.094 | 11/11/2021 | 2:38 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(PASSING OR LANE USAGE IMPROP

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39106622 | 190238.28 | 4765545.61 | 11/13/2021 | 10:12 AM | 2021 | SIDESWIPE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | C - POSSIBLE INJURY | V1:(TURNING IMPROPER,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39108066 | 188426.71 | 4768062.57 | 11/17/2021 | 11:15 AM | 2021 | BICYCLIST | PROPERTY DAMAGE | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,FAILURE TO YIELD RIGHT OF WAY) |
| 39108198 | 189028.7645 | 4767127.777 | 11/17/2021 | 5:06 PM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39109286 | 190238.28 | 4765545.61 | 11/19/2021 | 1:14 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39109289 | 188358.1 | 4766900.87 | 11/19/2021 | 5:56 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39109292 | 188387.8307 | 4767391.47 | 11/14/2021 | 12:24 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39110284 | 189011.25 | 4766863.69 | 11/20/2021 | 4:42 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39115904 | 189887.16 | 4766805.89 | 11/22/2021 | 6:34 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39116910 | 190838.4 | 4766825.93 | 11/21/2021 | 3:38 AM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39116917 | 189228.36 | 4766851.93 | 11/24/2021 | 6:56 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39118704 | 188997.11 | 4766646.3 | 11/28/2021 | 2:03 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | TWO-WAY,DIVIDED,UNPROTECTED | SNOW | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39122877 | 188101.19 | 4765776.47 | 11/10/2021 | 11:55 AM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39125114 | 189858.48 | 4766811.31 | 11/29/2021 | 9:19 PM | 2021 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39125119 | 190253.2278 | 4765542.852 | 11/22/2021 | 5:40 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39126939 | 188439.76 | 4768061.98 | 11/27/2021 | 7:42 PM | 2021 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39128514 | 190968.2261 | 4766529.625 | 12/2/2021 | 10:54 AM | 2021 | HEAD ON | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39128519 | 190400.7871 | 4765763.465 | 12/2/2021 | 2:29 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(UNSAFE LANE CHANGE,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39132052 | 188406.3446 | 4767445.997 | 12/4/2021 | 3:14 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39138264 | 190887.5632 | 4766434.959 | 12/8/2021 | 6:57 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD UNLIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39138364 | 189870.6928 | 4766839.219 | 12/8/2021 | 3:38 PM | 2021 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39141491 | 188435.3358 | 4767968.362 | 12/10/2021 | 10:05 AM | 2021 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39147946 | 189018.4 | 4765678.29 | 12/14/2021 | 2:26 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39147948 | 188498.7113 | 4766892.625 | 12/5/2021 | 12:14 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NO PASSING ZONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39150998 | 189019.4111 | 4765385.593 | 12/16/2021 | 3:36 PM | 2021 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNKNOWN,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 39151001 | 188991.8489 | 4766564.176 | 12/15/2021 | 1:02 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39151002 | 189818.3 | 4766716.19 | 12/16/2021 | 1:39 PM | 2021 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39151837 | 188340.8975 | 4766427.895 | 12/16/2021 | 1:08 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) |
| 39151839 | 188432.5658 | 4767909.75 | 12/17/2021 | 8:34 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(BACKING UNSAFELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39154184 | 189033.24 | 4765963.42 | 12/18/2021 | 2:31 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39155497 | 188214.44 | 4765695.51 | 12/3/2021 | 5:15 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39158285 | 189016.1729 | 4766924.451 | 12/21/2021 | 12:41 PM | 2021 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,VIEW OBSTRUCTED/LIMITED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39158315 | 189005.163 | 4766864.02 | 12/19/2021 | 10:18 PM | 2021 | HEAD ON | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(BACKING UNSAFELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39159744 | 189274.159 | 4767263.783 | 12/20/2021 | 7:15 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39162002 | 189855.5991 | 4766805.938 | 12/23/2021 | 10:30 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39162003 | 188430.1298 | 4767859.346 | 12/23/2021 | 6:22 PM | 2021 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | | V1:(UNSAFE LANE CHANGE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39165705 | 188854.1321 | 4765713.524 | 12/26/2021 | 11:07 AM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39168254 | 189521.4825 | 4765785.071 | 12/8/2021 | 3:34 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) / V3:(NOT ENTERED,NOT ENTERED) |
| 39168751 | 189858.48 | 4766811.31 | 12/27/2021 | 7:00 PM | 2021 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39171494 | 189018.4 | 4765678.29 | 12/30/2021 | 5:40 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39172950 | 188376.5993 | 4766893.035 | 1/1/2022 | 4:05 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:(ALCOHOL INVOLVEMENT,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39174002 | 188333.8339 | 4766330.846 | 1/2/2022 | 8:44 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | SNOW/ICE | NONE | NOT ENTERED | SNOW | | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39175279 | 188416.97 | 4767626.4 | 1/1/2022 | 7:42 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39175706 | 188758.0082 | 4766877.74 | 12/23/2021 | 12:00 PM | 2021 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | UNKNOWN | TRAFFIC SIGNAL | NOT ENTERED | SLEET/HAIL/FREEZING RAIN | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39177696 | 188327.7267 | 4766903.418 | 12/30/2021 | 5:12 PM | 2021 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39178577 | 188950.3797 | 4766866.995 | 1/5/2022 | 10:31 AM | 2022 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39178580 | 190954.98 | 4766536.54 | 1/4/2022 | 2:55 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNSAFE SPEED,OUTSIDE CAR DISTRACTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39178594 | 188294 | 4765687 | 1/4/2022 | 4:00 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39179883 | 188341.3382 | 4766426.889 | 1/6/2022 | 4:00 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | C - POSSIBLE INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39180630 | 188518.7521 | 4766891.672 | 1/5/2022 | 4:23 PM | 2022 | SIDESWIPE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | A - SERIOUS INJURY | V1:(LOST CONSCIOUSNESS,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39180647 | 190870.6499 | 4766410.991 | 1/4/2022 | 2:37 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39180816 | 188523.9671 | 4766891.423 | 1/1/2022 | 1:40 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39181482 | 190886.6435 | 4766812.576 | 1/8/2022 | 11:28 AM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(TURNING IMPROPER,NOT APPLICABLE) |
| 39183004 | 189238.8 | 4766851.34 | 1/8/2022 | 6:42 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39183006 | 189514.06 | 4765632.86 | 1/8/2022 | 4:43 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,FAILURE TO YIELD RIGHT OF WAY) / V2:(DRIVER INATTENTION,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39186360 | 188416.97 | 4767626.4 | 1/11/2022 | 8:56 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(PRESCRIPTION MEDICATION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39192439 | 188997.11 | 4766646.3 | 1/16/2022 | 9:42 AM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39192440 | 189033.24 | 4765963.42 | 1/15/2022 | 9:06 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | | V1:(PASSING OR LANE USAGE IMPROPERLY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39192998 | 188281.23 | 4765785.74 | 1/3/2022 | 7:50 PM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39196942 | 188474.0616 | 4767607.309 | 1/19/2022 | 6:17 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39196989 | 189706.3774 | 4766820.245 | 1/19/2022 | 7:53 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:(ALCOHOL INVOLVEMENT,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39198499 | 189072.0751 | 4766859.659 | 1/20/2022 | 11:14 AM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39199384 | 189419.7608 | 4766839.777 | 1/21/2022 | 2:28 PM | 2022 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39200276 | 190938.152 | 4766511.126 | 1/22/2022 | 7:39 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(UNKNOWN,UNKNOWN) / V2:(UNKNOWN,UNKNOWN) |
| 39201507 | 189036.995 | 4766284.27 | 1/23/2022 | 9:30 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | SNOW/ICE | STOP SIGN | NOT ENTERED | SNOW | | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39201514 | 190437.4862 | 4765811.774 | 1/22/2022 | 3:20 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39203359 | 188358.1 | 4766900.87 | 1/8/2022 | 6:45 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39203426 | 188726.51 | 4765728.74 | 1/24/2022 | 8:49 AM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39203427 | 188408.0095 | 4767474.264 | 1/24/2022 | 4:00 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39203429 | 188726.9994 | 4765983.166 | 1/24/2022 | 6:00 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD UNLIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | | V1:(FOLLOWING TOO CLOSELY,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39204992 | 188574.3553 | 4767602.158 | 1/25/2022 | 12:30 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,VIEW OBSTRUCTED/LIMITED) / V2:(VIEW OBSTRUCTED/LIMITED,NOT APPLICABLE) |
| 39204999 | 188710.7682 | 4768046.411 | 1/25/2022 | 1:14 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | TWO-WAY,NOT DIVIDED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39205005 | 188574.3553 | 4767602.158 | 1/25/2022 | 12:57 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,VIEW OBSTRUCTED/LIMITED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39207848 | 190846.48 | 4766825.68 | 1/26/2022 | 5:40 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39207851 | 190331.09 | 4765668.06 | 1/26/2022 | 3:52 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39208741 | 188468.2656 | 4766894.071 | 1/28/2022 | 1:30 PM | 2022 | SIDESWIPE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39211143 | 189019.33 | 4765693.39 | 1/29/2022 | 8:55 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39211782 | 188322.51 | 4766175.29 | 1/29/2022 | 5:40 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE |

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39213888 | 188718.6646 | 4766880.104 | 2/1/2022 | 6:17 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39213889 | 191005.5636 | 4766612.715 | 1/31/2022 | 3:43 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39217289 | 189197.6657 | 4765671.589 | 2/3/2022 | 11:54 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | | V1:(PAVEMENT SLIPPERY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39217295 | 189514.06 | 4765632.86 | 1/25/2022 | 4:18 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39218233 | 189513.5 | 4765618.53 | 2/3/2022 | 9:15 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39218246 | 188426.71 | 4768062.57 | 2/4/2022 | 4:30 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39221078 | 188415.1779 | 4767595.973 | 2/5/2022 | 11:09 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39222329 | 190215.8271 | 4765515.415 | 1/25/2022 | 4:30 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39222458 | 189033.5296 | 4765676.459 | 2/7/2022 | 1:13 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39223738 | 189228.36 | 4766851.93 | 2/7/2022 | 4:23 PM | 2022 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FOLLOWING TOO CLOSELY,PAVEMENT SLIPPERY) / V2:(UNKNOWN,UNKNOWN) |
| 39223739 | 188413.3858 | 4767565.545 | 2/7/2022 | 6:45 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39225479 | 188358.1 | 4766900.87 | 2/9/2022 | 8:46 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(NOT ENTERED,NOT ENTERED) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT ENTERED) |
| 39227893 | 190967.26 | 4766528.08 | 2/11/2022 | 9:05 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39227896 | 191152.86 | 4766816.96 | 2/11/2022 | 1:49 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNKNOWN,UNKNOWN) / V2:(UNKNOWN,UNKNOWN) |
| 39227900 | 188726.51 | 4765728.74 | 2/11/2022 | 7:21 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39228827 | 188461.7166 | 4768508.962 | 2/12/2022 | 12:54 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39231980 | 189228.36 | 4766851.93 | 2/14/2022 | 2:04 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39232997 | 189858.48 | 4766811.31 | 2/2/2022 | 12:00 AM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39233252 | 189023.3828 | 4767024.156 | 2/14/2022 | 2:30 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39233260 | 189031.12 | 4767182.2 | 2/15/2022 | 12:37 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39233262 | 188282.82 | 4765652.11 | 2/15/2022 | 6:22 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAWN | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(TURNING IMPROPER,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39234640 | 190954.98 | 4766536.54 | 2/16/2022 | 6:00 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39237545 | 188282.82 | 4765652.11 | 2/18/2022 | 7:05 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39239869 | 188401.99 | 4767631.09 | 2/13/2022 | 7:00 PM | 2022 | HEAD ON | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39242370 | 188416.97 | 4767626.4 | 2/21/2022 | 2:43 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39243628 | 190838.4 | 4766825.93 | 2/23/2022 | 12:04 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FOLLOWING TOO CLOSELY,CELL PHONE (HAND HELD)) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39243632 | 191005.5636 | 4766612.715 | 2/23/2022 | 5:17 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39243637 | 189022.9274 | 4767015.634 | 2/23/2022 | 7:06 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | YIELD SIGN | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39245089 | 189832.5957 | 4766756.13 | 2/24/2022 | 11:00 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(PASSING OR LANE USAGE IMPROPERLY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39245095 | 189032.3467 | 4765948.206 | 2/23/2022 | 7:12 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39246046 | 189019.33 | 4765693.39 | 2/24/2022 | 7:05 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39246054 | 189018.4 | 4765678.29 | 2/23/2022 | 12:57 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39246833 | 189997.31 | 4766795.56 | 2/26/2022 | 11:19 AM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | SNOW | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39246837 | 189858.48 | 4766811.31 | 2/25/2022 | 8:05 PM | 2022 | SIDESWIPE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | SNOW | C - POSSIBLE INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39249605 | 189860.7354 | 4766816.973 | 2/28/2022 | 12:47 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39249608 | 190954.98 | 4766536.54 | 2/28/2022 | 2:50 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39249610 | 189514.06 | 4765632.86 | 2/28/2022 | 5:26 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,CELL PHONE (HAND HELD)) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39250773 | 189018.4 | 4765678.29 | 3/1/2022 | 12:28 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39257181 | 189017.49 | 4765347.34 | 3/6/2022 | 2:20 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | YIELD SIGN | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39258789 | 190223.1394 | 4765547.347 | 3/7/2022 | 1:22 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39258792 | 190238.28 | 4765545.61 | 3/7/2022 | 1:29 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39265096 | 188726.51 | 4765728.74 | 3/10/2022 | 4:33 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39265101 | 188847.65 | 4765975.54 | 3/11/2022 | 3:08 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 39266051 | 188924.0144 | 4766868.426 | 3/13/2022 | 11:26 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,DIVIDED,UNPROTECTED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39266057 | 188441.9334 | 4768061.861 | 3/13/2022 | 6:25 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39268846 | 188359.5374 | 4766925.969 | 3/5/2022 | 6:42 AM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39271027 | 189518.47 | 4765713.68 | 3/15/2022 | 5:50 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39272070 | 190845.93 | 4766813.68 | 3/17/2022 | 4:13 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) |
| 39273942 | 189858.48 | 4766811.31 | 3/19/2022 | 5:06 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39277305 | 189017.51 | 4766325.63 | 3/20/2022 | 8:53 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39277310 | 188413.4186 | 4767566.103 | 3/21/2022 | 2:44 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39278530 | 191175.22 | 4766873.175 | 3/18/2022 | 3:48 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(NOT APPLICABLE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39279920 | 190955.8846 | 4766810.7 | 3/21/2022 | 4:23 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39279921 | 188439.76 | 4768061.98 | 3/22/2022 | 8:11 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39281377 | 188858.6817 | 4765698.037 | 3/24/2022 | 1:00 PM | 2022 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39281381 | 190954.98 | 4766536.54 | 3/20/2022 | 5:29 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39282244 | 190967.26 | 4766528.08 | 3/25/2022 | 3:30 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39282958 | 188439.76 | 4768061.98 | 3/26/2022 | 2:43 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39286851 | 188416.97 | 4767626.4 | 3/26/2022 | 2:15 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39286856 | 189557.8751 | 4766344.108 | 3/28/2022 | 4:52 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39291265 | 189205.432 | 4765670.652 | 3/31/2022 | 7:06 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39291266 | 188282.82 | 4765652.11 | 4/1/2022 | 11:20 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39291271 | 188380.4449 | 4766959.981 | 3/30/2022 | 6:19 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39291852 | 189017.49 | 4765347.34 | 4/1/2022 | 3:53 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:(TURNING IMPROPER,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39293645 | 189031.12 | 4767182.2 | 4/3/2022 | 1:45 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39293692 | 189858.48 | 4766811.31 | 4/2/2022 | 10:57 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:(ALCOHOL INVOLVEMENT,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39295250 | 188376.97 | 4766899.12 | 4/4/2022 | 8:46 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(UNKNOWN,UNKNOWN) / V2:(UNKNOWN,UNKNOWN) |
| 39296916 | 188364.8217 | 4766734.747 | 4/4/2022 | 4:01 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39296918 | 191163.4575 | 4766854.822 | 4/5/2022 | 2:02 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39298986 | 190954.98 | 4766536.54 | 4/5/2022 | 6:21 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39300528 | 189011.25 | 4766863.69 | 4/6/2022 | 4:13 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:(FAILURE TO YIELD RIGHT OF WAY,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39301369 | 188294.63 | 4765765.98 | 4/8/2022 | 7:31 AM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39304328 | 188816.3062 | 4765718.086 | 4/9/2022 | 3:00 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:(AGGRESSIVE DRIVING/ROAD RAGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39304331 | 190954.98 | 4766536.54 | 4/10/2022 | 6:00 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39306084 | 188439.76 | 4768061.98 | 4/11/2022 | 7:10 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | C - POSSIBLE INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39309838 | 189012.5417 | 4766880.018 | 4/14/2022 | 12:19 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39309916 | 190214.0517 | 4765512.963 | 4/12/2022 | 4:18

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39317868 | 190238.09 | 4766810.13 | 4/22/2022 | 10:55 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39317877 | 190331.09 | 4765668.06 | 4/22/2022 | 4:27 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39322984 | 190954.98 | 4766536.54 | 4/25/2022 | 6:26 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:{FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER} / V2:{NOT APPLICABLE,NOT APPLICABLE} / V3:{NOT APPLICABLE,NOT APPLICABLE} |
| 39324212 | 190960.2703 | 4766822.464 | 4/27/2022 | 9:47 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:{PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39324217 | 188809.94 | 4766874.62 | 4/26/2022 | 9:33 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39325494 | 189858.48 | 4766811.31 | 4/28/2022 | 1:14 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{DRIVER INATTENTION,FOLLOWING TOO CLOSELY} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39328390 | 189078.9184 | 4765670.966 | 3/30/2022 | 2:50 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{BACKING UNSAFELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39328458 | 188847.65 | 4765975.54 | 5/1/2022 | 12:49 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | C - POSSIBLE INJURY | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,UNKNOWN} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39329659 | 188435.0401 | 4768214.739 | 5/2/2022 | 7:13 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{UNSAFE SPEED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39331211 | 189048.6592 | 4765674.628 | 5/3/2022 | 9:53 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{DRIVER INEXPERIENCE,DRIVER INATTENTION} / V2:{NOT APPLICABLE,NOT APPLICABLE} / V3:{NOT APPLICABLE,NOT APPLICABLE} |
| 39334130 | 190838.1 | 4766813.93 | 5/4/2022 | 11:10 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | | V1:{UNSAFE LANE CHANGE,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39335067 | 190226.55 | 4765530.23 | 5/6/2022 | 4:10 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:{TURNING IMPROPER,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39335071 | 188376.97 | 4766899.12 | 5/6/2022 | 4:29 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39336953 | 189017.49 | 4765347.34 | 5/8/2022 | 4:39 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39336954 | 188561.3843 | 4768053.816 | 5/7/2022 | 5:44 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,VIEW OBSTRUCTED/LIMITED} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39337979 | 190686.0669 | 4766830.105 | 5/8/2022 | 7:46 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{PASSING OR LANE USAGE IMPROPERLY,UNKNOWN} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39341184 | 188270.29 | 4765658.69 | 5/7/2022 | 1:33 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39342790 | 188462.03 | 4768514.94 | 5/12/2022 | 6:53 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39343446 | 191004.28 | 4766821.22 | 5/13/2022 | 5:02 PM | 2022 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39344276 | 189828.0098 | 4766812.081 | 5/14/2022 | 10:03 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{UNSAFE LANE CHANGE,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39344279 | 189539.4853 | 4766057.837 | 5/13/2022 | 10:15 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FOLLOWING TOO CLOSELY,DRIVER INATTENTION} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39351786 | 190954.98 | 4766536.54 | 5/17/2022 | 5:58 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,UNKNOWN} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39352703 | 189514.06 | 4765632.86 | 5/20/2022 | 12:03 AM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,ALCOHOL INVOLVEMENT} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39352704 | 188268.0461 | 4765628.293 | 5/20/2022 | 12:10 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{FOLLOWING TOO CLOSELY,UNKNOWN} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39356718 | 189949 | 4765579.86 | 5/24/2022 | 10:51 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{TURNING IMPROPER,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39356722 | 188942.99 | 4765969.75 | 5/24/2022 | 5:08 PM | 2022 | HEAD ON | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | | V1:{TURNING IMPROPER,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39360570 | 189847.9313 | 4766789.335 | 5/26/2022 | 7:22 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{DRIVER INATTENTION,TURNING IMPROPER} / V2:{DRIVER INATTENTION,TURNING IMPROPER} |
| 39360573 | 190238.28 | 4765545.61 | 5/18/2022 | 2:50 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39361534 | 188579.802 | 4768052.522 | 5/27/2022 | 12:54 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39362301 | 189529.1885 | 4765631.02 | 5/28/2022 | 6:38 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39365534 | 191171.6959 | 4766867.641 | 5/24/2022 | 4:10 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39365535 | 190844.0254 | 4766752.75 | 5/31/2022 | 4:00 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FOLLOWING TOO CLOSELY,REACTION TO OTHER UNINVOLVED VEHICL} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39365553 | 188392.1737 | 4766898.068 | 5/31/2022 | 11:27 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{UNSAFE LANE CHANGE,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39365555 | 190437.8067 | 4765817.278 | 5/31/2022 | 10:11 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} / V3:{NOT APPLICABLE,NOT APPLICABLE} / V4:{REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE} |
| 39367071 | 188407.3774 | 4766897.017 | 5/31/2022 | 4:30 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39368234 | 188376.97 | 4766899.12 | 5/31/2022 | 6:10 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{DRIVER INATTENTION,FOLLOWING TOO CLOSELY} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39368236 | 190247.1752 | 4765543.577 | 6/1/2022 | 10:09 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{UNSAFE LANE CHANGE,NOT APPLICABLE} / V2:{UNSAFE SPEED,NOT APPLICABLE} |
| 39369219 | 188726.51 | 4765728.74 | 6/3/2022 | 11:58 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:{UNSAFE LANE CHANGE,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39369224 | 190988.7024 | 4766587.323 | 6/2/2022 | 5:30 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39370102 | 188379.3252 | 4766940.369 | 6/3/2022 | 11:59 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{DRIVER INATTENTION,FOLLOWING TOO CLOSELY} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39370104 | 189031.12 | 4767182.2 | 6/4/2022 | 12:46 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39370880 | 190967.26 | 4766528.08 | 6/1/2022 | 10:54 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39372284 | 189029.8922 | 4767151.745 | 6/4/2022 | 4:35 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39373674 | 189035.4052 | 4767287.561 | 6/6/2022 | 9:02 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{TURNING IMPROPER,UNKNOWN} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39376934 | 190967.26 | 4766528.08 | 3/18/2022 | 8:00 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | | V1:{NOT ENTERED,NOT ENTERED} / V2:{NOT ENTERED,NOT ENTERED} |
| 39377016 | 190238.28 | 4765545.61 | 6/8/2022 | 9:31 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39378885 | 189736.7773 | 4766818.037 | 6/8/2022 | 12:20 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39380011 | 190963.4106 | 4766549.236 | 6/10/2022 | 6:11 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39380736 | 188430.9132 | 4767874.781 | 6/10/2022 | 9:41 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39383624 | 188380.4449 | 4766959.981 | 6/13/2022 | 2:41 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39386958 | 188294.63 | 4765765.98 | 6/15/2022 | 6:15 AM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39391115 | 188385.6168 | 4767059.819 | 6/18/2022 | 8:16 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:{FOLLOWING TOO CLOSELY,FOLLOWING TOO CLOSELY,UNKNOWN,UNKNOWN} / V2:{NOT APPLICABLE,NOT APPLICABLE,NOT APPLICABLE,NOT APPLICABLE} |
| 39392619 | 189018.4 | 4765678.29 | 6/19/2022 | 9:59 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{UNKNOWN,PASSING OR LANE USAGE IMPROPERLY} / V2:{UNKNOWN,UNKNOWN} |
| 39394457 | 189867.27 | 4766807.02 | 6/21/2022 | 11:04 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{DRIVER INATTENTION,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39394459 | 189019.33 | 4765693.39 | 6/20/2022 | 4:56 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39396278 | 189011.25 | 4766863.69 | 6/21/2022 | 5:06 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | OTHER | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39396279 | 189928.154 | 4766804.662 | 6/21/2022 | 7:19 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:{UNSAFE SPEED,GLARE} / V2:{NOT APPLICABLE,NOT APPLICABLE} / V3:{NOT APPLICABLE,NOT APPLICABLE} |
| 39396280 | 189006.8234 | 4766802.891 | 6/22/2022 | 11:46 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE} / V2:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} |
| 39396284 | 189514.06 | 4765632.86 | 6/21/2022 | 5:39 PM | 2022 | BICYCLIST | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | A - SERIOUS INJURY | V1:} / V2:{NOT APPLICABLE,NOT APPLICABLE} / V3:{NOT APPLICABLE,NOT APPLICABLE} |
| 39396287 | 189867.27 | 4766807.02 | 6/22/2022 | 4:58 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{UNSAFE SPEED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39398742 | 189011.25 | 4766863.69 | 6/23/2022 | 5:57 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{DRIVER INATTENTION,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39403683 | 188326.35 | 4766431.76 | 6/6/2022 | 4:48 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:{NOT ENTERED,NOT ENTERED} / V2:{NOT ENTERED,NOT ENTERED} |
| 39408204 | 190431.3507 | 4765803.698 | 6/28/2022 | 9:43 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | YIELD SIGN | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39408207 | 188358.1 | 4766900.87 | 6/30/2022 | 1:02 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{DRIVER INATTENTION,FOLLOWING TOO CLOSELY} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39408210 | 188709.07 | 4765465.65 | 6/29/2022 | 6:41 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39409163 | 188950.3797 | 4766866.995 | 7/1/2022 | 3:19 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | | V1:{TURNING IMPROPER,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39415471 | 188335.5022 | 4766353.764 | 6/30/2022 | 6:25 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39417179 | 188372.1736 | 4765776.323 | 7/7/2022 | 1:13 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39417181 | 190846.1001 | 4766818.511 | 7/7/2022 | 9:15 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39417182 | 188534.55 | 4765541.7 | 7/7/2022 | 10:33 AM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{TURNING IMPROPER,DRIVER INATTENTION} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39419139 | 188414.2818 | 4767580.759 | 7/9/2022 | 1:41 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:{DRIVER INATTENTION,DRIVER INEXPERIENCE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39420827 | 188101.19 | 4765776.47 | 7/9/2022 | 4:41 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39422300 | 190238.28 | 4765545.61 | 6/27/2022 | 2:30 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:{NOT ENTERED,NOT ENTERED} / V2:{NOT ENTERED,NOT ENTERED} |
| 39425628 | 190954.98 | 4766536.54 | 7/13/2022 | 4:46 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | C - POSSIBLE INJURY | V1:{TRAFFIC CONTROL DEVICES DISREGARDED,UNSAFE SPEED} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39426572 | 189015.5086 | 4765632.55 | 7/11/2022 | 5:49 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} / V2:{FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE} |
| 39426610 | 190954.98 | 4766536.54 | 7/8/2022 | 7:40 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | | V1:{DRIVER INATTENTION,UNSAFE SPEED} / V2:{NOT APPLICABLE,NOT APPLICABLE} |
| 39427511 | 188442.569 | 4768338.236 | 7/11/2022 | 4:50 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | C - POSSIBLE INJURY | V1:{FOLLOWING TOO CLOSELY,NOT APPLICABLE} / V2:{NOT APPLICABLE,NOT APPLICABLE} / V3:{NOT APPLICABLE,NOT APPLICABLE} |
| 39433805 | 190238.28 | 4765545.61 | 7/20/2022

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39442915 | 188430.0549 | 4767858.02 | 7/26/2022 | 4:29 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39442922 | 189015.2659 | 4766324.205 | 7/26/2022 | 4:38 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39445743 | 190238.28 | 4765545.61 | 7/29/2022 | 4:42 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39446511 | 190967.26 | 4766528.08 | 7/30/2022 | 4:00 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39449860 | 189238.8 | 4766851.34 | 7/31/2022 | 9:18 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39451317 | 188727.4534 | 4765743.972 | 8/2/2022 | 11:45 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39451378 | 189221.1901 | 4765668.75 | 8/2/2022 | 1:34 PM | 2022 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39452601 | 190956.2409 | 4766538.691 | 8/3/2022 | 10:47 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,UNPROTECTED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39454283 | 189951.609 | 4766803.259 | 8/3/2022 | 1:24 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,UNPROTECTED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39456060 | 188422.1297 | 4767717.734 | 8/6/2022 | 2:50 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39458207 | 189514.06 | 4765632.86 | 8/6/2022 | 6:17 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39459626 | 188323.2744 | 4766185.79 | 8/8/2022 | 11:15 AM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39460904 | 188420.8617 | 4767695.288 | 8/9/2022 | 1:32 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,CELL PHONE (HANDS FREE)) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39463751 | 189882.5094 | 4766806.884 | 8/11/2022 | 11:27 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39468223 | 188293.6708 | 4765757.472 | 8/14/2022 | 10:02 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39471516 | 188470.1945 | 4768060.316 | 8/17/2022 | 1:42 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39473013 | 188439.76 | 4768061.98 | 8/17/2022 | 8:19 PM | 2022 | BICYCLIST | INJURY | COLLISION WITH BICYCLIST | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(VIEW OBSTRUCTED/LIMITED,NOT APPLICABLE) |
| 39476191 | 188642.07 | 4765988.45 | 8/21/2022 | 12:58 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39476195 | 189893.3963 | 4766861.862 | 8/20/2022 | 5:00 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39478495 | 188426.7747 | 4767799.956 | 8/23/2022 | 8:41 AM | 2022 | PEDESTRIAN | PROPERTY DAMAGE | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 39482210 | 188431.7983 | 4767893.51 | 8/26/2022 | 11:51 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39482300 | 189048.1865 | 4767628.632 | 8/25/2022 | 4:56 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39483633 | 188426.7067 | 4768062.508 | 8/23/2022 | 4:45 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39483919 | 188296.28 | 4765784.38 | 8/25/2022 | 7:53 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(TRAFFIC CONTROL DEVICES DISREGARDED,UNKNOWN) |
| 39485969 | 188438.4211 | 4768033.649 | 8/28/2022 | 3:08 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39488692 | 188474.5575 | 4767607.734 | 8/31/2022 | 12:35 PM | 2022 | HEAD ON | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39488694 | 188500.629 | 4768058.651 | 8/31/2022 | 1:57 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39488697 | 189244.9904 | 4767003.613 | 8/28/2022 | 6:33 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(DRIVER INEXPERIENCE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT ENTERED,NOT ENTERED) |
| 39488758 | 188415.6259 | 4767603.58 | 8/31/2022 | 12:24 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,REACTION TO OTHER UNINVOLVED VEHICL) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39490271 | 189453.5526 | 4765640.275 | 9/1/2022 | 4:15 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39490272 | 190964.7318 | 4766524.064 | 9/1/2022 | 9:22 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,REACTION TO OTHER UNINVOLVED VEHICL) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39490277 | 189013.8985 | 4765479.223 | 8/31/2022 | 12:27 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39491890 | 188448.3304 | 4768214.138 | 9/2/2022 | 8:30 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | YIELD SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39491895 | 189102.5179 | 4766858.154 | 9/2/2022 | 6:47 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39491896 | 190975.3396 | 4766541.002 | 9/1/2022 | 3:50 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39492256 | 190979.24 | 4766547.24 | 9/2/2022 | 4:24 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39494495 | 188742.21 | 4765982.22 | 8/4/2022 | 12:09 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(NOT APPLICABLE,NOT APPLICABLE) / V2:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) |
| 39496077 | 188440.6939 | 4768077.191 | 9/5/2022 | 8:00 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39497894 | 188445.8652 | 4768061.646 | 9/6/2022 | 3:53 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNKNOWN,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 39497910 | 190287.2348 | 4765610.675 | 9/7/2022 | 8:04 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39499726 | 189011.25 | 4766863.69 | 9/8/2022 | 8:29 AM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,GLARE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39501363 | 188598.5522 | 4765745.593 | 9/10/2022 | 11:13 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39501369 | 189243.73 | 4767262.02 | 9/10/2022 | 11:36 AM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39502198 | 188296.28 | 4765784.38 | 8/28/2022 | 10:30 AM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39503161 | 188366.25 | 4766749.92 | 9/10/2022 | 6:16 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39505311 | 188769.0864 | 4766326.809 | 9/13/2022 | 3:26 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39508350 | 189016.47 | 4765647.76 | 9/14/2022 | 4:58 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39508351 | 189863.8941 | 4766800.189 | 9/15/2022 | 9:00 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39512975 | 190916.8614 | 4766451.798 | 9/19/2022 | 9:42 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39512976 | 190967.26 | 4766528.08 | 9/19/2022 | 11:49 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39514239 | 190967.26 | 4766528.08 | 9/20/2022 | 3:21 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39514241 | 188726.51 | 4765728.74 | 9/20/2022 | 3:56 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39514255 | 189871.4901 | 4766820.74 | 9/19/2022 | 4:30 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND HILLCREST | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39514256 | 190195.69 | 4765675.19 | 9/20/2022 | 8:20 AM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,GLARE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39514261 | 188101.19 | 4765776.47 | 9/20/2022 | 2:02 PM | 2022 | LEFT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39515346 | 189022.9274 | 4767015.634 | 9/21/2022 | 1:04 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39517089 | 191048 | 4766656.76 | 9/22/2022 | 12:39 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39517094 | 189014.03 | 4765609.16 | 9/22/2022 | 1:27 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39517105 | 188041.9906 | 4765778.757 | 9/20/2022 | 2:05 PM | 2022 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | CLEAR | A - SERIOUS INJURY | V1:(ILLNESS,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) / V5.(NOT APPLICABLE,NOT APPLICABLE) / V6:(NOT APPLICABLE,NOT APPLICABLE) |
| 39518013 | 188282.82 | 4765652.11 | 9/23/2022 | 7:43 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK- ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,ALCOHOL INVOLVEMENT) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39518709 | 188435.4435 | 4767970.642 | 9/22/2022 | 4:25 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39518710 | 190967.26 | 4766528.08 | 9/24/2022 | 12:15 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39518712 | 188522.9552 | 4765756.477 | 9/24/2022 | 2:05 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39520176 | 188397.5579 | 4767300.924 | 9/24/2022 | 4:05 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39520179 | 190844.7171 | 4766774.992 | 9/25/2022 | 3:26 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39521456 | 188718.5983 | 4765729.754 | 9/26/2022 | 4:43 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39521472 | 188438.951 | 4768044.861 | 9/25/2022 | 6:40 PM | 2022 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39524334 | 189023.3122 | 4767022.835 | 9/28/2022 | 11:22 AM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39526703 | 189550.55 | 4766231.63 | 9/29/2022 | 4:49 PM | 2022 | PEDESTRIAN | INJURY | COLLISION WITH OTHER PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(NOT APPLICABLE,NOT APPLICABLE) |
| 39529278 | 188438.951 | 4768044.861 | 10/1/2022 | 11:43 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(AGGRESSIVE DRIVING/ROAD RAGE,PASSING OR LANE USAGE IMPROPERLY) / V2:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) |
| 39530577 | 188273.8966 | 4765561.106 | 9/29/2022 | 10:45 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39531909 | 189498.9332 | 4765634.714 | 10/3/2022 | 8:22 AM | 2022 | HEAD ON | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39531921 | 189845.4328 | 4766783.763 | 10/3/2022 | 1:10 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39532363 | 188726.51 | 4765728.74 | 10/3/2022 | 8:35 AM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NO

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39546730 | 189040.7896 | 4766080.489 | 10/14/2022 | 11:38 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39551498 | 189011.25 | 4766863.69 | 10/15/2022 | 7:11 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39551525 | 189243.73 | 4767262.02 | 10/15/2022 | 5:35 PM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39551608 | 189514.06 | 4765632.86 | 10/17/2022 | 11:52 AM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39553024 | 188520.5229 | 4765547.658 | 10/18/2022 | 2:30 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39553042 | 189845.4328 | 4766783.763 | 10/18/2022 | 6:05 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39553053 | 189941.8294 | 4766961.492 | 10/18/2022 | 7:30 PM | 2022 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT/ GRADE | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39554828 | 189703.1415 | 4766820.48 | 10/19/2022 | 4:13 PM | 2022 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39555786 | 188756.599 | 4766877.825 | 10/12/2022 | 3:24 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39555805 | 189845.8765 | 4766763.728 | 10/20/2022 | 2:44 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39556479 | 188296.28 | 4765784.38 | 10/21/2022 | 11:04 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39556489 | 188761.4 | 4766281.74 | 10/14/2022 | 12:40 PM | 2022 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39557937 | 191136.461 | 4766792.06 | 10/21/2022 | 9:17 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39557958 | 191200.0762 | 4766809.413 | 10/22/2022 | 7:33 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE SPEED,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39563876 | 190289.5445 | 4765523.442 | 10/26/2022 | 3:06 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39565865 | 189867.27 | 4766807.02 | 10/28/2022 | 11:24 AM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39567025 | 189221.1901 | 4765668.75 | 10/29/2022 | 5:05 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39567039 | 188398.6457 | 4767322.155 | 10/29/2022 | 7:22 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39568002 | 188422.4467 | 4767723.345 | 10/30/2022 | 3:30 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39568004 | 188414.7678 | 4767589.01 | 10/30/2022 | 4:12 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39568019 | 189518.47 | 4765713.68 | 10/30/2022 | 11:09 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39569359 | 189871.4901 | 4766820.74 | 10/31/2022 | 5:22 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39573049 | 188835.2793 | 4765777.693 | 11/2/2022 | 7:02 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39573059 | 188987.9016 | 4765353.267 | 11/2/2022 | 4:51 PM | 2022 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39574031 | 189033.24 | 4765963.42 | 11/3/2022 | 11:24 AM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNKNOWN,NOT APPLICABLE) / V2:(NOT ENTERED,NOT APPLICABLE) |
| 39576715 | 191136.461 | 4766792.06 | 10/21/2022 | 9:22 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39576727 | 188352.8492 | 4766595.287 | 11/5/2022 | 1:25 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39581854 | 190240.4457 | 4765545.022 | 10/28/2022 | 12:00 AM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39583619 | 190238.28 | 4765545.61 | 11/9/2022 | 1:27 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39583836 | 189037.3748 | 4767334.471 | 11/9/2022 | 12:22 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39584743 | 188302.3035 | 4765783.863 | 11/10/2022 | 3:30 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39584774 | 189016.16 | 4765642.856 | 11/10/2022 | 5:07 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39587304 | 188387.3201 | 4767101.1 | 11/12/2022 | 5:50 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39593280 | 189867.27 | 4766807.02 | 11/16/2022 | 10:37 PM | 2022 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(DRIVER INATTENTION,UNKNOWN) / V2:(DRIVER INATTENTION,UNKNOWN) |
| 39595282 | 188995.9366 | 4766627.984 | 11/17/2022 | 4:29 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39595286 | 189882.8554 | 4766842.075 | 11/17/2022 | 9:45 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT/ GRADE | SNOW/ICE | NONE | NOT ENTERED | SNOW | U - UNKNOWN | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39597044 | 189514.06 | 4765632.86 | 11/19/2022 | 2:21 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | SNOW | U - UNKNOWN | V1:(DRIVER INATTENTION,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39598340 | 190838.265 | 4766826.882 | 11/11/2022 | 9:22 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39599799 | 188426.813 | 4768064.617 | 11/21/2022 | 5:05 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39599886 | 188390.6946 | 4767166.964 | 11/21/2022 | 2:23 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39601273 | 190253.2279 | 4765542.852 | 11/22/2022 | 12:13 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | STRAIGHT AND LEVEL | UNKNOWN | NONE | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(UNKNOWN,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39602607 | 188998.7338 | 4766673.059 | 11/23/2022 | 9:15 AM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLOUDY | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39604133 | 188387.632 | 4767107.188 | 11/25/2022 | 2:45 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39605373 | 188418.6426 | 4767656.008 | 11/26/2022 | 3:03 PM | 2022 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39605727 | 190334.8644 | 4765673.291 | 10/31/2022 | 8:15 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39606522 | 188591.7982 | 4768051.896 | 11/27/2022 | 1:57 PM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39614221 | 188799.4851 | 4766723.953 | 12/2/2022 | 5:55 PM | 2022 | HEAD ON | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39615893 | 190853.7278 | 4766818.303 | 11/29/2022 | 4:57 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39617445 | 188742.21 | 4765982.22 | 12/2/2022 | 4:48 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39618222 | 190999.6182 | 4766579.743 | 11/8/2022 | 11:07 AM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AT HILLCREST | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(OTHER (VEHICLE),NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39619035 | 190025.1214 | 4766799.944 | 12/5/2022 | 12:10 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39620793 | 189907.3008 | 4766888.977 | 12/6/2022 | 2:08 PM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39622954 | 189017.51 | 4766325.63 | 12/7/2022 | 8:31 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39622958 | 188403.7892 | 4767630.625 | 12/7/2022 | 10:30 AM | 2022 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(DRIVER INATTENTION,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39623093 | 188436.8823 | 4768001.088 | 12/1/2022 | 7:49 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39623100 | 189072.0751 | 4766859.659 | 12/5/2022 | 12:57 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39624163 | 189022.1166 | 4766862.938 | 12/8/2022 | 9:40 AM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,NOT DIVIDED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39624167 | 190208.4326 | 4766816.716 | 12/7/2022 | 9:09 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39624931 | 189567.1702 | 4765710.978 | 12/9/2022 | 3:42 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39624933 | 189893.3963 | 4766861.862 | 12/9/2022 | 4:49 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(ALCOHOL INVOLVEMENT,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39624940 | 189035.5843 | 4767291.827 | 12/9/2022 | 1:58 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39626303 | 188633.1594 | 4766885.193 | 12/10/2022 | 3:19 PM | 2022 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39626909 | 189011.25 | 4766863.69 | 11/15/2022 | 6:00 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39627921 | 189859.9185 | 4766814.922 | 11/11/2022 | 6:00 PM | 2022 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39629245 | 188850.6924 | 4765975.355 | 12/12/2022 | 10:23 AM | 2022 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(DRIVER INEXPERIENCE,NOT APPLICABLE) |
| 39631747 | 188302.7432 | 4765870.884 | 12/13/2022 | 9:21 AM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(DRIVER INATTENTION,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39634128 | 189867.27 | 4766807.02 | 12/14/2022 | 11:38 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39635205 | 188376.97 | 4766899.12 | 12/15/2022 | 8:03 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SLEET/HAIL/FREEZING RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39637562 | 190238.28 | 4765545.61 | 11/16/2022 | 12:00 AM | 2022 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | UNKNOWN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39638275 | 189247.9268 | 4766850.779 | 12/17/2022 | 5:30 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39640782 | 188358.1 | 4766900.87 | 11/27/2022 | 5:15 PM | 2022 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39641326 | 189017.49 | 4765347.34 | 12/19/2022 | 12:02 PM | 2022 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39641347 | 188390.2233 | 4765604.174 | 12/19/2022 | 4:05 PM | 2022 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(TURNING IMPROPER,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39641371 | 188364.0273 | 4766726.307 | 12/19/2022 | 2:27 PM | 2022 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39641414 | 188416.7527 | 4767880.278 | 12/17/2022 | 12:05 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURN

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39646118 | 190967.26 | 4766528.08 | 12/19/2022 | 10:57 AM | 2022 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | WET | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39646123 | 188422.1297 | 4767717.734 | 12/21/2022 | 11:42 AM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39647230 | 189547.4629 | 4766088.048 | 12/22/2022 | 6:10 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39647402 | 189705.5235 | 4766623.136 | 12/22/2022 | 5:52 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39657800 | 188376.97 | 4766899.12 | 11/23/2022 | 9:35 AM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39659103 | 189011.25 | 4766863.69 | 1/1/2023 | 6:25 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39663261 | 188714.2565 | 4768046.252 | 1/3/2023 | 6:11 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39663273 | 189951.609 | 4766803.259 | 1/3/2023 | 3:51 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(FOLLOWING TOO CLOSELY,CELL PHONE (HAND HELD)) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39665062 | 188331.3619 | 4766296.888 | 1/4/2023 | 12:12 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39665200 | 188498.1497 | 4768058.787 | 1/4/2023 | 10:45 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39666438 | 190504.7724 | 4765918.917 | 1/6/2023 | 8:42 AM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39676099 | 188565.1304 | 4768053.454 | 1/13/2023 | 6:50 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | U - UNKNOWN | V1:(VIEW OBSTRUCTED/LIMITED,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39676109 | 189011.25 | 4766863.69 | 1/13/2023 | 7:43 AM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(PAVEMENT SLIPPERY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(PAVEMENT SLIPPERY,TRAFFIC CONTROL DEVICES DISREGARDED) |
| 39677471 | 189017.51 | 4766325.63 | 1/5/2023 | 5:48 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 39677512 | 188459.6037 | 4767609.887 | 1/14/2023 | 3:49 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39679229 | 188449.4222 | 4768475.445 | 12/17/2022 | 9:00 PM | 2022 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH GUIDE RAIL | DARK-ROAD LIGHTED | CURVE AND LEVEL | SNOW/ICE | UNKNOWN | NOT ENTERED | SNOW | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) |
| 39681805 | 188354.459 | 4766615.045 | 1/16/2023 | 12:17 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39681817 | 188766.5243 | 4766311.786 | 1/16/2023 | 8:44 AM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NO PASSING ZONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(VIEW OBSTRUCTED/LIMITED,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39683464 | 189514.06 | 4765632.86 | 1/18/2023 | 9:14 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39683518 | 188296.28 | 4765784.38 | 1/18/2023 | 6:07 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39684292 | 189044.538 | 4767542.639 | 1/19/2023 | 5:30 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39689308 | 188786.0727 | 4766650.936 | 1/23/2023 | 3:56 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TURNING IMPROPER,REACTION TO OTHER UNINVOLVED VEHICL) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39690907 | 188406.133 | 4767442.404 | 1/24/2023 | 6:41 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(BACKING UNSAFELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39691430 | 189867.27 | 4766807.02 | 1/23/2023 | 6:55 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39693257 | 189034.9366 | 4765989.729 | 1/25/2023 | 5:15 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | SLUSH | STOP SIGN | NOT ENTERED | SNOW | U - UNKNOWN | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39693327 | 188416.97 | 4767626.4 | 12/29/2022 | 5:31 PM | 2022 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39694163 | 189867.27 | 4766807.02 | 1/26/2023 | 9:00 AM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39698934 | 189191.7799 | 4766853.739 | 1/30/2023 | 3:40 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39700977 | 191305.072 | 4766805.832 | 1/31/2023 | 7:08 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39702934 | 188366.25 | 4766749.92 | 1/28/2023 | 2:06 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39706075 | 188426.7769 | 4768063.901 | 2/4/2023 | 7:45 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39711623 | 188439.76 | 4768061.98 | 2/8/2023 | 6:50 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39711625 | 188391.6161 | 4767184.95 | 2/8/2023 | 5:00 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39711644 | 188758.8735 | 4765724.9 | 2/8/2023 | 11:02 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,BRAKES DEFECTIVE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39712354 | 191195.5134 | 4766787.18 | 2/9/2023 | 2:47 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | WET | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39713330 | 188470.1945 | 4768060.316 | 2/10/2023 | 1:50 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(BACKING UNSAFELY,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39713332 | 189867.27 | 4766807.02 | 2/10/2023 | 6:44 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INEXPERIENCE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39713352 | 189566.493 | 4766472.817 | 2/10/2023 | 9:07 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39714327 | 188403.7892 | 4767630.625 | 2/11/2023 | 4:19 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39714472 | 190331.09 | 4765668.06 | 2/11/2023 | 4:01 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39714496 | 189015.6083 | 4765634.128 | 2/6/2023 | 6:09 AM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39719577 | 189867.27 | 4766807.02 | 2/14/2023 | 9:35 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39720771 | 188418.9925 | 4768062.809 | 2/14/2023 | 4:17 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(VIEW OBSTRUCTED/LIMITED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39720862 | 188723.4926 | 4765714.459 | 2/15/2023 | 4:45 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(BRAKES DEFECTIVE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39720883 | 188521.0361 | 4765756.753 | 2/15/2023 | 12:55 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39722976 | 189072.0751 | 4766859.659 | 2/11/2023 | 4:12 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39724242 | 190157.0464 | 4765554.932 | 2/19/2023 | 1:19 AM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(OTHER (VEHICLE),NOT APPLICABLE) |
| 39725205 | 190104.3061 | 4765545.697 | 2/20/2023 | 11:21 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39725223 | 188408.0095 | 4767474.264 | 2/20/2023 | 2:40 PM | 2023 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,REACTION TO OTHER UNINVOLVED VEHICL) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39726322 | 188470.1945 | 4768060.316 | 2/21/2023 | 2:07 PM | 2023 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39727699 | 188376.4894 | 4766891.515 | 2/22/2023 | 2:58 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39728528 | 188383.0515 | 4766898.699 | 2/22/2023 | 7:26 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SLEET/HAIL/FREEZING RAIN | U - UNKNOWN | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39729382 | 191052.937 | 4766664.311 | 2/24/2023 | 5:35 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39730480 | 190238.28 | 4765545.61 | 2/25/2023 | 4:11 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39732475 | 189867.27 | 4766807.02 | 2/26/2023 | 8:00 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39735265 | 188474.5575 | 4767607.734 | 2/28/2023 | 1:28 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39740594 | 190846.1001 | 4766818.511 | 1/25/2023 | 2:00 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39744787 | 188809.94 | 4766874.62 | 3/7/2023 | 8:53 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39746424 | 190238.28 | 4765545.61 | 3/8/2023 | 12:07 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39746435 | 190238.28 | 4765545.61 | 3/8/2023 | 4:37 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39746527 | 190979.24 | 4766547.24 | 3/8/2023 | 8:16 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39747398 | 190541.7229 | 4765967.87 | 3/9/2023 | 4:23 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39748170 | 189011.25 | 4766863.69 | 3/10/2023 | 11:30 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39748187 | 188694.543 | 4768063.271 | 3/10/2023 | 12:52 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,VIEW OBSTRUCTED/LIMITED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39748236 | 188386.6252 | 4767084.258 | 3/10/2023 | 6:51 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,PAVEMENT SLIPPERY) / V2:(PAVEMENT SLIPPERY,NOT APPLICABLE) |
| 39749386 | 188414.7678 | 4767589.01 | 3/11/2023 | 3:40 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39749394 | 189753.3617 | 4766816.833 | 3/10/2023 | 6:30 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | SNOW | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39749396 | 189087.2965 | 4766858.906 | 3/11/2023 | 12:41 PM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39749412 | 189019.432 | 4765701.5 | 2/28/2023 | 6:00 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39753675 | 190967.26 | 4766528.08 | 3/14/2023 | 2:46 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39757112 | 188703.936 | 4765716.848 | 3/17/2023 | 1:35 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39758443 | 190878.2529 | 4766395.011 | 3/18/2023 | 3:10 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39758449 | 190140.2427 | 4765678.475 | 3/13/2023 | 8:29 AM | 2023 | PEDESTRIAN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | TWO-WAY,NOT DIVIDED | CLOUDY | B - INJURY | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39765090 | 189199.2287 | 4765671.4 | 3/22/2023 | 3:11 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | TWO-WAY,NOT DIVIDED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39766786 | 189241.4228 | 4767198.572 | 3/

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39778689 | 188523.6026 | 4765756.384 | 4/3/2023 | 2:48 PM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39778705 | 189867.27 | 4766807.02 | 4/3/2023 | 8:27 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(UNSAFE SPEED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39781601 | 189860.5182 | 4766793.357 | 4/5/2023 | 2:54 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39782143 | 188928.5617 | 4765704.453 | 4/6/2023 | 1:15 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39783402 | 188365.7931 | 4768064.886 | 3/17/2023 | 12:10 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39783507 | 189762.3979 | 4766816.176 | 4/6/2023 | 11:29 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(BACKING UNSAFELY,NOT APPLICABLE) |
| 39784700 | 189026.3304 | 4765845.74 | 4/8/2023 | 2:50 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39785917 | 188422.1297 | 4767717.734 | 4/9/2023 | 12:22 PM | 2023 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39788521 | 190967.26 | 4766528.08 | 4/11/2023 | 2:01 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39788528 | 190967.26 | 4766528.08 | 4/11/2023 | 11:19 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39790047 | 189386.5976 | 4766799.216 | 4/12/2023 | 3:55 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39790059 | 189013.6902 | 4766894.072 | 4/12/2023 | 1:11 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39790161 | 189012.4489 | 4766878.883 | 4/12/2023 | 2:15 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39791842 | 188726.51 | 4765728.74 | 4/12/2023 | 4:12 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNKNOWN,UNKNOWN) / V2:(UNKNOWN,UNKNOWN) |
| 39792866 | 189238.8 | 4766851.34 | 4/15/2023 | 1:20 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) |
| 39794272 | 189342.3488 | 4765653.902 | 4/15/2023 | 1:04 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39795228 | 190030.13 | 4765570.51 | 4/17/2023 | 4:38 PM | 2023 | LEFT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39795863 | 188283.0324 | 4765785.416 | 4/3/2023 | 10:40 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39796540 | 188438.4211 | 4768033.649 | 4/18/2023 | 10:32 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39800469 | 188694.6862 | 4765471.972 | 4/16/2023 | 1:36 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39802650 | 189009.5373 | 4765557.366 | 4/18/2023 | 12:56 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39803658 | 190238.28 | 4765545.61 | 4/12/2023 | 1:55 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | UNKNOWN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39804216 | 190563.4347 | 4765987.244 | 4/24/2023 | 5:13 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39806859 | 188921.6339 | 4768034.376 | 4/24/2023 | 5:49 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NO PASSING ZONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39807483 | 188264.7742 | 4765786.459 | 4/22/2023 | 11:49 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | RAIN | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) |
| 39807539 | 188287.0728 | 4765766.732 | 4/26/2023 | 10:26 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(DRUGS (ILLEGAL),TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39809688 | 188462.9372 | 4768530.023 | 4/29/2023 | 5:09 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39809712 | 188485.4118 | 4768059.483 | 4/29/2023 | 7:55 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39812723 | 188461.8002 | 4768510.556 | 5/2/2023 | 5:36 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39813043 | 190963.8147 | 4766522.608 | 4/30/2023 | 5:03 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,FAILURE TO YIELD RIGHT OF WAY) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 39815399 | 188448.0257 | 4768208.629 | 5/3/2023 | 3:57 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(NOT APPLICABLE,NOT APPLICABLE) / V2:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) |
| 39816606 | 188425.5658 | 4767778.557 | 5/5/2023 | 5:45 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39818257 | 188419.5936 | 4767672.842 | 5/6/2023 | 10:17 AM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39871337 | 188296.28 | 4765784.38 | 10/26/2022 | 4:01 PM | 2022 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39824031 | 188430.055 | 4767858.023 | 5/11/2023 | 5:21 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39824951 | 190043.5396 | 4765553.541 | 5/12/2023 | 10:20 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39826316 | 189541.8213 | 4766097.392 | 5/13/2023 | 6:18 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE SPEED,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39828129 | 189031.4099 | 4765932.25 | 5/14/2023 | 3:32 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39829508 | 189512.8478 | 4765612.41 | 5/15/2023 | 1:34 PM | 2023 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39830981 | 189543.35 | 4766127.01 | 5/15/2023 | 5:58 PM | 2023 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39832431 | 189878.5936 | 4766855.841 | 5/17/2023 | 10:12 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39833292 | 188358.1 | 4766900.87 | 5/9/2023 | 12:55 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT APPLICABLE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39837077 | 189867.27 | 4766807.02 | 5/4/2023 | 10:45 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39837876 | 190967.26 | 4766528.08 | 5/22/2023 | 11:29 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AT HILLCREST | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39838788 | 189743.4367 | 4766648.688 | 5/21/2023 | 10:59 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NO PASSING ZONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39842317 | 188296.28 | 4765784.38 | 5/24/2023 | 7:00 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) |
| 39843123 | 188296.28 | 4765784.38 | 5/25/2023 | 12:22 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39843131 | 190238.28 | 4765545.61 | 5/25/2023 | 8:56 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,CELL PHONE (HANDS FREE)) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39843905 | 188296.28 | 4765784.38 | 5/26/2023 | 2:05 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(DRUGS (ILLEGAL),NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39851817 | 188347.6508 | 4766522.48 | 5/30/2023 | 1:07 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39851830 | 190223.1394 | 4765547.347 | 5/31/2023 | 9:30 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39853756 | 189514.06 | 4765632.86 | 6/2/2023 | 8:28 AM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39861950 | 188439.76 | 4768061.98 | 5/1/2023 | 9:30 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39862456 | 190846.1001 | 4766818.511 | 6/8/2023 | 10:21 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39872274 | 189221.1901 | 4765668.75 | 6/17/2023 | 1:07 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39874456 | 190238.28 | 4765545.61 | 6/18/2023 | 5:45 PM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,DIVIDED,UNPROTECTED | CLEAR | U - UNKNOWN | V1:(ALCOHOL INVOLVEMENT,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39876313 | 188376.97 | 4766899.12 | 6/20/2023 | 11:30 AM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39882578 | 188726.51 | 4765728.74 | 6/24/2023 | 1:40 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39882580 | 188462.9372 | 4768530.023 | 6/25/2023 | 8:52 AM | 2023 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) |
| 39882615 | 189867.27 | 4766807.02 | 6/23/2023 | 5:40 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39884487 | 188742.21 | 4765982.22 | 6/26/2023 | 4:13 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39884494 | 189513.5464 | 4765619.716 | 6/9/2023 | 7:10 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39887426 | 190844.7171 | 4766774.992 | 6/27/2023 | 5:54 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39887427 | 188534.55 | 4765541.7 | 6/28/2023 | 1:54 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 39889136 | 188054.9094 | 4765816.102 | 6/27/2023 | 11:11 AM | 2023 | BICYCLIST | INJURY | COLLISION WITH BICYCLIST | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39891080 | 188409.8016 | 4767504.691 | 7/2/2023 | 1:23 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(UNSAFE LANE CHANGE,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39895282 | 188915.88 | 4765377 | 7/5/2023 | 11:06 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39896046 | 191297.4566 | 4766806.097 | 7/6/2023 | 3:00 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39896902 | 191048 | 4766656.76 | 7/7/2023 | 3:40 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,ALCOHOL INVOLVEMENT) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39896929 | 191305.072 | 4766805.832 | 7/7/2023 | 12:08 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,VIEW OBSTRUCTED/LIMITED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39897615 | 188439.1003 | 4768048.02 | 7/7/2023 | 4:45 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNKNOWN,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39898402 | 191004.8416 | 4766837.752 | 7/8/2023 | 10:04 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39899523 | 188461.8967 | 4768512.397 | 7/9/2023 | 5:47 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39901144 | 189047.6103 | 4765342.671 | 7/7/2023 | 1:21 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39902335 | 189008.0989 | 4766821.077 | 7/11/2023 | 9:18 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39907245 | 190276.9505 | 4765597.218 | 7/15/2023 | 5:29 PM | 2023 | RIGHT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPRO

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 39920155 | 188101.19 | 4765776.47 | 6/19/2023 | 10:00 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39923705 | 188101.19 | 4765776.47 | 6/7/2023 | 12:00 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39924370 | 189512.103 | 4765618.707 | 7/27/2023 | 10:12 AM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 39924381 | 188451.0236 | 4768262.832 | 7/22/2023 | 8:45 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39924390 | 190238.28 | 4765545.61 | 7/27/2023 | 8:50 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39926708 | 189019.33 | 4765693.39 | 7/29/2023 | 5:20 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39926828 | 190268.3595 | 4765541.038 | 7/29/2023 | 1:50 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39928214 | 189432.1967 | 4765628.67 | 7/30/2023 | 7:11 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,DIVIDED,POSITIVE MEDIA BARR | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39932949 | 188432.5658 | 4767909.75 | 8/2/2023 | 7:10 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH BUILDING/WALL | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39935158 | 188378.0632 | 4766918.267 | 8/4/2023 | 6:37 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39935974 | 189867.27 | 4766807.02 | 8/5/2023 | 1:05 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39937272 | 189514.06 | 4765632.86 | 8/6/2023 | 1:29 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39937676 | 189018.0113 | 4765678.338 | 7/18/2023 | 5:18 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39941801 | 189017.51 | 4766325.63 | 8/9/2023 | 9:58 AM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39946851 | 188972.738 | 4768013.634 | 8/13/2023 | 1:45 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39946866 | 188358.2303 | 4766903.145 | 8/13/2023 | 9:16 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39946881 | 188993.1143 | 4765681.416 | 8/13/2023 | 8:55 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39948513 | 189827.5684 | 4766812.092 | 8/14/2023 | 9:30 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39949201 | 188376.97 | 4766899.12 | 7/19/2023 | 12:15 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39950220 | 189547.4629 | 4766088.048 | 8/15/2023 | 5:30 PM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | U - UNKNOWN | V1:(TURNING IMPROPER,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39950307 | 189185.6355 | 4767515.444 | 8/15/2023 | 3:35 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39951013 | 189322.4368 | 4766846.203 | 8/15/2023 | 8:37 PM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39952620 | 190238.28 | 4765545.61 | 8/14/2023 | 11:07 AM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39952652 | 189525.1109 | 4766233.245 | 8/17/2023 | 9:45 PM | 2023 | HEAD ON | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(DRIVER INATTENTION,PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39953328 | 190967.26 | 4766528.08 | 8/18/2023 | 2:58 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39957374 | 190618.8724 | 4766824.9 | 8/21/2023 | 1:10 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(REACTION TO OTHER UNINVOLVED VEHICL,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39957438 | 189017.8788 | 4766863.231 | 8/21/2023 | 7:08 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39960768 | 189017.8788 | 4766863.231 | 8/23/2023 | 11:31 AM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | A - SERIOUS INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39960798 | 189141.3675 | 4766856.232 | 8/23/2023 | 5:10 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39961454 | 190835.4718 | 4766819.208 | 8/24/2023 | 4:23 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39964924 | 189035.5843 | 4767291.827 | 8/28/2023 | 5:20 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39964981 | 190983.4251 | 4766553.92 | 8/26/2023 | 5:49 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE SPEED,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39965013 | 189579.887 | 4766540.222 | 8/26/2023 | 10:05 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39965018 | 190331.09 | 4765668.06 | 8/27/2023 | 1:40 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39965149 | 188403.7892 | 4767630.625 | 8/28/2023 | 12:50 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39968870 | 188950.3797 | 4766866.995 | 8/29/2023 | 5:47 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 39968877 | 188535.1788 | 4768056.343 | 8/30/2023 | 4:22 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,REACTION TO OTHER UNINVOLVED VEHICL) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39968897 | 188452.405 | 4768287.809 | 8/30/2023 | 9:12 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | YIELD SIGN | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39970494 | 190961.7754 | 4766519.369 | 8/29/2023 | 9:53 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39970507 | 190331.09 | 4765668.06 | 9/1/2023 | 2:47 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39970612 | 190238.28 | 4765545.61 | 9/1/2023 | 11:09 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39973047 | 189623.19 | 4765604.87 | 8/17/2023 | 8:42 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(DRIVER INATTENTION,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39973924 | 188439.76 | 4768061.98 | 9/4/2023 | 4:59 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,BRAKES DEFECTIVE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39975320 | 188438.951 | 4768044.861 | 9/5/2023 | 2:57 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39977301 | 190067.9903 | 4766799.865 | 9/7/2023 | 12:23 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,VIEW OBSTRUCTED/LIMITED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39978145 | 188626.9101 | 4765741.51 | 9/8/2023 | 12:33 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39978864 | 188718.9519 | 4765729.709 | 8/14/2023 | 9:45 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39979095 | 189055.9831 | 4766860.593 | 9/5/2023 | 6:20 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39979097 | 189045.16 | 4767557.52 | 8/9/2023 | 5:15 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39979836 | 189012.2548 | 4765348.389 | 9/9/2023 | 5:29 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39982730 | 191036.2159 | 4766660.699 | 9/11/2023 | 2:29 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39985667 | 188053.4949 | 4765817.551 | 8/15/2023 | 2:45 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39986130 | 188758.8735 | 4765724.9 | 9/13/2023 | 1:22 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39986141 | 190959.1402 | 4766515.183 | 9/13/2023 | 8:46 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39986147 | 189031.12 | 4767182.2 | 9/13/2023 | 7:54 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39987601 | 189238.8 | 4766851.34 | 9/15/2023 | 5:03 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39987734 | 188991.6658 | 4766410.013 | 9/15/2023 | 4:57 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39989152 | 189514.06 | 4765632.86 | 9/16/2023 | 9:10 AM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39990324 | 188388.5829 | 4767403.993 | 8/28/2023 | 2:00 PM | 2023 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39990875 | 188726.51 | 4765728.74 | 9/17/2023 | 6:09 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39990914 | 188415.1779 | 4767595.973 | 9/17/2023 | 5:58 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39990917 | 188422.1297 | 4767717.734 | 9/17/2023 | 11:20 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | RR CROSSING GATES | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 39992218 | 188803.7019 | 4766783.393 | 9/18/2023 | 2:52 PM | 2023 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) |
| 39992232 | 188726.51 | 4765728.74 | 9/18/2023 | 10:11 AM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLOUDY | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39993949 | 188756.599 | 4766877.825 | 9/19/2023 | 4:09 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 39994695 | 189759.1067 | 4766659.249 | 8/2/2023 | 2:35 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 39995747 | 188809.94 | 4766874.62 | 9/20/2023 | 3:33 PM | 2023 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 39995821 | 188485.4118 | 4768059.483 | 9/20/2023 | 10:02 AM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40000966 | 189517.3814 | 4765693.729 | 9/24/2023 | 4:20 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40004641 | 189011.25 | 4766863.69 | 9/22/2023 | 4:55 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(UNKNOWN,NOT APPLICABLE) |
| 40007566 | 189762.3979 | 4766816.176 | 9/28/2023 | 6:37 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAWN | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40007636 | 189011.25 | 4766863.69 | 9/28/2023 | 7:20 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 40008402 | 188438.951 | 4768044.861 | 9/26/2023 | 3:15 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(BRAKES DEFECTIVE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40010287 | 189238.8 | 4766851.34 | 9/30/2023 | 4:35 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40010297 | 190238.28 | 4765545.61 | 9/30/2023 | 4:57 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40014560 | 188726.51 | 4765728.74 | 3/29/2023 | 12:12 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40018076 | 188410.6989 | 4765752.594 | 10/4/2023 | 5:30 PM | 2023 | REAR END | PROPERTY DA

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 40019049 | 188559.5848 | 4766889.391 | 10/5/2023 | 4:59 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40020056 | 191215.2079 | 4766808.964 | 10/6/2023 | 7:15 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | CURVE AND LEVEL | DRY | YIELD SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40020662 | 189762.3979 | 4766816.176 | 10/7/2023 | 12:39 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40020687 | 189016.1729 | 4766924.451 | 10/7/2023 | 10:55 AM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40022370 | 189023.3122 | 4767022.835 | 10/8/2023 | 1:56 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40027029 | 189024.8508 | 4765820.54 | 10/11/2023 | 5:17 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40027072 | 190838.1 | 4766813.93 | 10/10/2023 | 7:38 PM | 2023 | RIGHT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40027114 | 188426.7067 | 4768062.508 | 8/31/2023 | 10:42 AM | 2023 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | B - INJURY | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40027167 | 190331.09 | 4765668.06 | 10/11/2023 | 10:41 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40027194 | 188489.4543 | 4768059.262 | 10/11/2023 | 9:27 AM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40028149 | 189867.27 | 4766807.02 | 10/11/2023 | 4:55 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40029031 | 189166.3233 | 4766854.998 | 10/13/2023 | 12:14 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40029704 | 189567.1702 | 4765710.978 | 9/24/2023 | 7:57 PM | 2023 | BICYCLIST | INJURY | COLLISION WITH BICYCLIST | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(UNKNOWN,NOT APPLICABLE) |
| 40033280 | 189032.8827 | 4765957.334 | 10/9/2023 | 5:00 PM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | SLEET/HAIL/FREEZING RAIN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40034155 | 188296.28 | 4765784.38 | 10/16/2023 | 6:16 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40034248 | 189529.8382 | 4765905.536 | 10/16/2023 | 12:08 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40036078 | 190354.1798 | 4765700.062 | 10/17/2023 | 10:44 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) |
| 40037085 | 188341.1339 | 4766431.205 | 10/18/2023 | 12:03 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40038850 | 190104.3061 | 4765545.697 | 10/20/2023 | 2:30 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40039021 | 189028.6794 | 4767125.967 | 10/20/2023 | 3:42 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40040354 | 189914.5433 | 4766931.473 | 10/21/2023 | 3:45 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40042667 | 190967.26 | 4766528.08 | 10/23/2023 | 5:18 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40043523 | 189019.33 | 4765693.39 | 10/11/2023 | 11:00 AM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40044238 | 189389.35 | 4766841.83 | 10/24/2023 | 3:51 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40046374 | 188279.8455 | 4765621.775 | 10/25/2023 | 4:21 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40047255 | 188296.28 | 4765784.38 | 10/27/2023 | 10:12 AM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40047272 | 191305.072 | 4766805.832 | 10/27/2023 | 11:50 AM | 2023 | RIGHT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40047793 | 190967.26 | 4766528.08 | 10/24/2023 | 3:40 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40049011 | 190838.9662 | 4766845.786 | 9/29/2023 | 3:35 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40050408 | 190897.9143 | 4766564.148 | 10/29/2023 | 12:25 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40050937 | 188474.5575 | 4767607.734 | 10/8/2023 | 12:00 AM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40053469 | 189019.33 | 4765693.39 | 10/31/2023 | 10:16 AM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40054927 | 189016.47 | 4765647.76 | 11/1/2023 | 12:30 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | OFFICER/FLAGMAN/GUARD | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) |
| 40054933 | 190970.4918 | 4766533.249 | 11/1/2023 | 1:47 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,BRAKES DEFECTIVE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40054940 | 189027.1284 | 4765859.331 | 11/1/2023 | 10:37 AM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40057110 | 189017.49 | 4765347.34 | 11/3/2023 | 12:35 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40057173 | 189018.8518 | 4766863.164 | 11/3/2023 | 8:00 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40057221 | 188449.64 | 4768479.67 | 11/2/2023 | 11:13 AM | 2023 | HEAD ON | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | TWO-WAY,DIVIDED,UNPROTECTED | SLEET/HAIL/FREEZING RAIN | B - INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40058003 | 188992.7298 | 4766577.927 | 11/1/2023 | 10:45 AM | 2023 | BICYCLIST | INJURY | COLLISION WITH BICYCLIST | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 40060675 | 189514.06 | 4765632.86 | 10/30/2023 | 1:33 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40060705 | 189010.0588 | 4766848.497 | 11/5/2023 | 1:30 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40061973 | 188695.3053 | 4768047.115 | 11/6/2023 | 4:04 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40063844 | 188441.2063 | 4768085.537 | 11/7/2023 | 8:47 AM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MEDIAN/BARRIER - END | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TURNING IMPROPER,REACTION TO OTHER UNINVOLVED VEHICL) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40067567 | 189018.5907 | 4766323.336 | 11/10/2023 | 7:44 PM | 2023 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40068350 | 189221.1901 | 4765668.75 | 11/10/2023 | 7:41 PM | 2023 | LEFT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40070807 | 188296.28 | 4765784.38 | 11/12/2023 | 12:29 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,FAILURE TO YIELD RIGHT OF WAY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40070808 | 188344.5672 | 4766479.291 | 11/12/2023 | 4:55 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40072300 | 190983.4251 | 4766553.92 | 11/13/2023 | 2:27 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40073746 | 188374.28 | 4767150.22 | 8/25/2023 | 8:40 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40077135 | 189518.47 | 4765713.68 | 11/16/2023 | 9:03 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40078177 | 188439.76 | 4768061.98 | 11/17/2023 | 4:20 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40080543 | 189867.27 | 4766807.02 | 11/17/2023 | 6:15 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) |
| 40080544 | 188366.25 | 4766749.92 | 11/18/2023 | 12:16 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40083567 | 188358.1 | 4766900.87 | 10/28/2023 | 12:00 PM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40084592 | 191048 | 4766656.76 | 11/20/2023 | 2:06 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40084593 | 189019.33 | 4765693.39 | 11/20/2023 | 8:53 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40087839 | 188726.51 | 4765728.74 | 11/22/2023 | 7:10 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAWN | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(DRIVER INATTENTION,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40088684 | 190859.811 | 4766818.137 | 11/22/2023 | 2:50 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40089937 | 189011.25 | 4766863.69 | 10/28/2023 | 4:00 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40091060 | 189014.1476 | 4765611.021 | 11/25/2023 | 4:20 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(AGGRESSIVE DRIVING/ROAD RAGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40095852 | 189867.27 | 4766807.02 | 11/28/2023 | 8:03 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40097743 | 188761.0884 | 4768044.117 | 11/29/2023 | 5:23 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40099014 | 189048.8702 | 4766240.392 | 11/29/2023 | 3:04 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40099828 | 191048 | 4766656.76 | 12/1/2023 | 2:52 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AT HILLCREST | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40100350 | 188078.347 | 4765777.352 | 11/10/2023 | 11:50 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | UNKNOWN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40101741 | 188523.85 | 4766891.43 | 12/2/2023 | 12:00 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40103198 | 188403.7892 | 4767630.625 | 12/3/2023 | 4:35 PM | 2023 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40103204 | 190931.1888 | 4766500.668 | 12/3/2023 | 7:47 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40103206 | 189012.3539 | 4766877.721 | 12/3/2023 | 9:21 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(PASSENGER DISTRACTION,NOT APPLICABLE) |
| 40104662 | 189867.27 | 4766807.02 | 12/4/2023 | 3:20 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40104719 | 188414.7678 | 4767589.01 | 12/4/2023 | 11:29 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40108469 | 190238.28 | 4765545.61 | 12/6/2023 | 11:30 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40109590 | 188892.9355 | 4767564.736 | 12/7/2023 | 5:48 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40110792 | 189024.8508 | 4765820.54 | 12/8/2023 | 3:40 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40116760 | 188387.3201 | 4767101.1 | 12/5/2023 | 5:17 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40119973 | 188278.0401 | 4765785.701 | 12/11/2023 | 2:53 PM | 2023 | LEFT TURN | INJURY | COLLISION WIT


| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 40130343 | 189008.956 | 4766833.297 | 12/21/2023 | 4:18 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40130352 | 188809.94 | 4766874.62 | 12/21/2023 | 8:53 PM | 2023 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | A - SERIOUS INJURY | V1:(NOT APPLICABLE,NOT APPLICABLE) |
| 40130385 | 188742.21 | 4765982.22 | 12/21/2023 | 7:40 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40132111 | 189011.25 | 4766863.69 | 12/23/2023 | 5:11 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(CELL PHONE (HAND HELD),NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40132123 | 188693 | 4767944 | 12/23/2023 | 6:03 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40133057 | 188424.3802 | 4767757.571 | 12/24/2023 | 11:08 AM | 2023 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40134658 | 190220.0615 | 4765673.907 | 12/25/2023 | 12:00 PM | 2023 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(AGGRESSIVE DRIVING/ROAD RAGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40135849 | 189787.821 | 4766680.195 | 12/26/2023 | 8:49 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40137519 | 188809.94 | 4766874.62 | 12/27/2023 | 5:25 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40138419 | 188416.97 | 4767626.4 | 12/26/2023 | 12:00 PM | 2023 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,UNKNOWN) / V2:(UNKNOWN,NOT APPLICABLE) |
| 40139420 | 188470.1945 | 4768060.316 | 12/29/2023 | 6:18 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40140233 | 188376.97 | 4766899.12 | 12/30/2023 | 11:11 AM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 40143433 | 188761.4 | 4766281.74 | 1/2/2024 | 1:30 PM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40144330 | 189665.3574 | 4765614.562 | 12/4/2023 | 6:00 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40149793 | 190240.0637 | 4765548.082 | 1/3/2024 | 5:12 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | SNOW | B - INJURY | V1:(UNSAFE SPEED,ALCOHOL INVOLVEMENT) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40150784 | 188809.3428 | 4766865.496 | 1/10/2024 | 11:01 AM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40151686 | 190846.1001 | 4766818.511 | 1/9/2024 | 9:10 AM | 2024 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(PAVEMENT SLIPPERY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40154558 | 189567.1702 | 4765710.978 | 12/22/2023 | 5:45 PM | 2023 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40154647 | 188304.0125 | 4766160.311 | 1/4/2024 | 6:24 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40157415 | 189518.47 | 4765713.68 | 1/11/2024 | 5:47 PM | 2024 | LEFT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | RAIN | A - SERIOUS INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40158503 | 189561.1992 | 4766394.698 | 1/12/2024 | 4:41 PM | 2024 | HEAD ON | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FELL ASLEEP,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40164146 | 188364.4779 | 4765777.228 | 1/16/2024 | 12:37 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40164155 | 188358.1545 | 4766659.589 | 1/16/2024 | 10:12 AM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40164162 | 189867.27 | 4766807.02 | 1/16/2024 | 7:53 AM | 2024 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(UNSAFE SPEED,PAVEMENT SLIPPERY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40164172 | 189029.94 | 4767152.76 | 1/16/2024 | 8:25 PM | 2024 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | U - UNKNOWN | V1:(PAVEMENT SLIPPERY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40173284 | 188439.8723 | 4768063.809 | 1/22/2024 | 11:23 AM | 2024 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNKNOWN,UNKNOWN) / V2:(UNKNOWN,UNKNOWN) |
| 40176893 | 188333.7545 | 4766329.755 | 1/24/2024 | 10:07 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | CURVE AND HILLCREST | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40178044 | 190238.28 | 4765545.61 | 1/25/2024 | 10:20 AM | 2024 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40182241 | 189019.33 | 4765693.39 | 1/27/2024 | 11:09 PM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | A - SERIOUS INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40183363 | 188809.94 | 4766874.62 | 1/5/2024 | 4:00 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40183912 | 188432.8579 | 4767915.932 | 1/29/2024 | 8:15 PM | 2024 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40184034 | 188296.28 | 4765784.38 | 1/29/2024 | 12:24 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40187607 | 189832.5915 | 4766756.121 | 1/31/2024 | 5:10 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40189488 | 189389.35 | 4766841.83 | 2/2/2024 | 7:19 AM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40190459 | 188812.17 | 4765421.9 | 2/3/2024 | 3:04 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,NOT DIVIDED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40190482 | 189015.5726 | 4765313.988 | 2/3/2024 | 5:43 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,AGGRESSIVE DRIVING/ROAD RAGE) / V2:(NOT APPLICABLE,AGGRESSIVE DRIVING/ROAD RAGE) |
| 40191622 | 189321.0228 | 4766846.289 | 2/3/2024 | 3:29 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40191736 | 189040.5954 | 4767557.781 | 2/4/2024 | 3:00 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH CURBING | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TURNING IMPROPER,BACKING UNSAFELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40192932 | 188439.76 | 4768061.98 | 2/5/2024 | 3:07 PM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40197079 | 188809.94 | 4766874.62 | 2/9/2024 | 9:01 PM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40197089 | 189386.5976 | 4766799.216 | 2/9/2024 | 7:15 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40197090 | 189867.27 | 4766807.02 | 2/9/2024 | 11:31 AM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40198421 | 190983.4251 | 4766553.92 | 2/9/2024 | 2:17 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40199616 | 189028.6794 | 4767325.967 | 2/11/2024 | 6:36 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40201722 | 188377.8387 | 4766914.335 | 7/6/2023 | 4:22 PM | 2023 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40202267 | 189348.8628 | 4766844.516 | 2/12/2024 | 4:43 PM | 2024 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40203920 | 188422.1297 | 4767717.734 | 2/14/2024 | 4:40 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40206987 | 189863.92 | 4766824.97 | 7/29/2023 | 12:30 PM | 2023 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40211869 | 190286.4578 | 4765523.803 | 2/24/2024 | 4:25 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40211879 | 190942.5434 | 4766489.623 | 2/24/2024 | 7:53 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40211883 | 188416.97 | 4767626.4 | 2/24/2024 | 12:47 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40211895 | 188422.1297 | 4767717.734 | 2/24/2024 | 6:26 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40211906 | 188420.4083 | 4767687.263 | 2/24/2024 | 3:55 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40213958 | 189011.25 | 4766863.69 | 2/18/2024 | 7:15 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | SNOW | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40214050 | 188439.76 | 4768061.98 | 2/23/2024 | 1:52 PM | 2024 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(DRIVER INATTENTION,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40217360 | 188422.6368 | 4767726.709 | 2/22/2024 | 5:27 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(UNKNOWN,UNKNOWN) |
| 40217361 | 188809.94 | 4766874.62 | 2/22/2024 | 1:39 PM | 2024 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40218230 | 189013.6902 | 4766894.072 | 2/23/2024 | 4:10 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40219805 | 190924.687 | 4766816.364 | 2/16/2024 | 8:43 AM | 2024 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40219913 | 188296.28 | 4765784.38 | 2/20/2024 | 5:15 PM | 2024 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40219944 | 189056.866 | 4767861.338 | 2/19/2024 | 11:32 AM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40219946 | 189033.24 | 4765963.42 | 2/21/2024 | 11:39 AM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40220039 | 189514.06 | 4765632.86 | 2/21/2024 | 9:39 AM | 2024 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40220558 | 188535.1788 | 4768056.343 | 2/15/2024 | 6:32 PM | 2024 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | WET | STOP SIGN | NOT ENTERED | SLEET/HAIL/FREEZING RAIN | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40221847 | 189019.6174 | 4765716.248 | 2/29/2024 | 12:33 PM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40221866 | 190238.28 | 4765545.61 | 2/28/2024 | 4:35 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40223378 | 188627.2704 | 4765747.378 | 12/6/2023 | 3:05 PM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40226258 | 189514.06 | 4765632.86 | 3/3/2024 | 1:51 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40227875 | 189238.8 | 4766851.34 | 3/4/2024 | 12:43 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40228964 | 189031.12 | 4767182.2 | 12/21/2023 | 3:31 PM | 2023 | SIDESWIPE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40231655 | 190207.9987 | 4765549.085 | 3/6/2024 | 1:07 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40231694 | 189017.49 | 4765347.34 | 3/6/2024 | 6:30 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAWN | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40232399 | 188591.7982 | 4768051.896 | 3/7/2024 | 1:53 PM | 2024 | LEFT TURN (WITH OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40234889 | 188278.7222 | 4765610.319 | 3/9/2024 | 10:10 AM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40234922 | 188413.4186 | 4767566.103 | 3/9/2024 | 12:50 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLIC


| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 40242314 | 190104.3079 | 4765545.696 | 3/11/2024 | 7:29 AM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40244942 | 188370.4438 | 4766807.914 | 3/17/2024 | 1:13 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40244952 | 190967.26 | 4766528.08 | 3/17/2024 | 3:22 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(CELL PHONE (HAND HELD),NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40246095 | 188358.1 | 4766900.87 | 3/17/2024 | 1:44 PM | 2024 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40247276 | 188659.5505 | 4766883.656 | 3/19/2024 | 1:59 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | SNOW | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40249661 | 188430.0549 | 4767858.02 | 3/21/2024 | 7:06 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40250999 | 188431.84 | 4768164.4 | 2/28/2024 | 10:00 AM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) / V3:(NOT ENTERED,NOT ENTERED) |
| 40251547 | 191281.0177 | 4766806.67 | 3/23/2024 | 12:13 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE SPEED,TIRE FAILURE/INADEQUATE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40251613 | 189026.3304 | 4765845.74 | 3/4/2024 | 5:00 PM | 2024 | BICYCLIST | INJURY | COLLISION WITH BICYCLIST | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:) / V2:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) |
| 40252940 | 189514.06 | 4765632.86 | 3/24/2024 | 11:28 AM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40255687 | 188426.8539 | 4767801.358 | 3/26/2024 | 4:43 PM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40257905 | 189019.33 | 4765693.39 | 3/28/2024 | 9:54 AM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40257931 | 189221.1901 | 4765668.75 | 3/27/2024 | 8:45 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40257947 | 188438.3212 | 4768031.534 | 3/28/2024 | 8:04 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,ALCOHOL INVOLVEMENT) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40258624 | 189032.972 | 4765958.856 | 3/29/2024 | 3:09 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,UNKNOWN) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40258630 | 188416.97 | 4767626.4 | 3/29/2024 | 2:53 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40258638 | 189033.24 | 4765963.42 | 3/29/2024 | 4:22 PM | 2024 | SIDESWIPE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | STOP SIGN | NOT ENTERED | CLEAR | B - INJURY | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) |
| 40259983 | 188809.94 | 4766874.62 | 3/30/2024 | 10:30 AM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40262784 | 190967.26 | 4766528.08 | 4/1/2024 | 3:36 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40264539 | 189221.1901 | 4765668.75 | 4/2/2024 | 1:10 PM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(DRIVER INATTENTION,TRAFFIC CONTROL DEVICES DISREGARDED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40264620 | 189162.11 | 4765675.88 | 4/2/2024 | 1:00 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | OTHER | NOT ENTERED | RAIN | U - UNKNOWN | V1:(DRIVER INATTENTION,UNSAFE LANE CHANGE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40267481 | 190964.0121 | 4766522.921 | 4/5/2024 | 4:44 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40268958 | 189514.06 | 4765632.86 | 4/6/2024 | 6:33 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(GLARE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40269441 | 188426.7067 | 4768062.508 | 3/21/2024 | 10:00 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40270397 | 189011.25 | 4766863.69 | 4/7/2024 | 6:40 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40271340 | 189011.25 | 4766863.69 | 4/7/2024 | 6:35 PM | 2024 | RIGHT ANGLE | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40272599 | 189867.27 | 4766807.02 | 4/9/2024 | 7:17 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO KEEP RIGHT,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40273894 | 189017.49 | 4765347.34 | 4/10/2024 | 10:20 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40273995 | 190238.28 | 4765545.61 | 4/9/2024 | 10:09 AM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40274778 | 188439.76 | 4768061.98 | 4/11/2024 | 12:37 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | WET | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40274808 | 188405.3252 | 4767428.689 | 4/11/2024 | 6:58 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40275618 | 188756.599 | 4766877.825 | 4/12/2024 | 3:36 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,UNSAFE SPEED) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40277192 | 188726.51 | 4765728.74 | 4/13/2024 | 7:20 PM | 2024 | PEDESTRIAN | INJURY | COLLISION WITH PEDESTRIAN | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(AGGRESSIVE DRIVING/ROAD RAGE,NOT APPLICABLE) |
| 40277646 | 188426.7067 | 4768062.508 | 3/26/2024 | 4:50 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40277840 | 189858.4799 | 4766811.31 | 3/21/2024 | 4:15 PM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40278030 | 189867.27 | 4766807.02 | 3/26/2024 | 3:35 PM | 2024 | RIGHT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | UNKNOWN | UNKNOWN | UNKNOWN | UNKNOWN | NOT ENTERED | UNKNOWN | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40281946 | 189997.256 | 4766799.995 | 4/16/2024 | 5:25 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40283335 | 188376.97 | 4766899.12 | 4/18/2024 | 7:35 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DUSK | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(NOT APPLICABLE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40283813 | 189514.06 | 4765632.86 | 4/17/2024 | 12:22 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40283990 | 189526.1364 | 4765852.167 | 4/17/2024 | 11:27 AM | 2024 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40284520 | 190967.26 | 4766528.08 | 4/5/2024 | 10:05 AM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) / V2:(TRAFFIC CONTROL DEVICES DISREGARDED,NOT APPLICABLE) |
| 40284627 | 188438.4211 | 4768033.649 | 4/19/2024 | 11:48 AM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40284697 | 190965.4304 | 4766529.34 | 4/19/2024 | 5:33 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40284701 | 189517.6397 | 4765698.463 | 4/19/2024 | 9:28 AM | 2024 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | NONE | NOT ENTERED | RAIN | B - INJURY | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40285293 | 190967.26 | 4766528.08 | 4/19/2024 | 3:09 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(UNSAFE LANE CHANGE,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(UNKNOWN,UNKNOWN) |
| 40295333 | 188296.28 | 4765784.38 | 4/10/2024 | 12:00 AM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40295740 | 189907.3008 | 4766888.977 | 4/29/2024 | 7:10 PM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40297436 | 190242.6922 | 4765544.412 | 4/30/2024 | 6:02 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40299182 | 189949.0001 | 4765579.86 | 5/1/2024 | 8:02 AM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | FOG/SMOG/SMOKE | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40299881 | 188673.567 | 4765481.255 | 5/2/2024 | 5:27 PM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40299898 | 189514.06 | 4765632.86 | 5/2/2024 | 12:43 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40302076 | 189098.2912 | 4765683.707 | 5/4/2024 | 1:33 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(BACKING UNSAFELY,NOT APPLICABLE) |
| 40302078 | 189024.8508 | 4765820.54 | 4/22/2024 | 3:20 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40302129 | 190967.26 | 4766528.08 | 5/4/2024 | 10:00 AM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AT HILLCREST | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TRAFFIC CONTROL DEVICES DISREGARDED,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40305937 | 188388.73 | 4767406.43 | 5/7/2024 | 3:20 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(DRIVER INATTENTION,FOLLOWING TOO CLOSELY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40307373 | 189035.4521 | 4765997.723 | 5/8/2024 | 11:54 AM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40309024 | 189022.1166 | 4766862.938 | 5/10/2024 | 5:05 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40310462 | 189635.092 | 4765618.172 | 5/11/2024 | 11:39 AM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40310493 | 190238.28 | 4765545.61 | 5/11/2024 | 11:55 AM | 2024 | RIGHT TURN (WITH OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40310772 | 190776.9236 | 4766274.053 | 5/11/2024 | 2:08 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,DRIVER INATTENTION) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40311614 | 189171.9278 | 4766854.721 | 5/12/2024 | 1:55 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40312544 | 188049.3969 | 4765794.774 | 4/28/2024 | 5:30 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40315003 | 189867.27 | 4766807.02 | 5/14/2024 | 8:10 AM | 2024 | LEFT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40316401 | 191148.4447 | 4766810.739 | 5/15/2024 | 10:16 PM | 2024 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40317342 | 188069.2167 | 4765803.258 | 5/15/2024 | 2:43 PM | 2024 | RIGHT ANGLE | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(NOT APPLICABLE,NOT APPLICABLE) / V2:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40317355 | 188089.507 | 4765786.256 | 5/15/2024 | 12:49 PM | 2024 | OVERTAKING | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLOUDY | B - INJURY | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) / V4:(NOT APPLICABLE,NOT APPLICABLE) / V5:(NOT APPLICABLE,NOT APPLICABLE) |
| 40318113 | 189017.0274 | 4766863.29 | 5/17/2024 | 12:41 PM | 2024 | RIGHT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLOUDY | B - INJURY | V1:(TURNING IMPROPER,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40318232 | 190813.8029 | 4766820.509 | 5/17/2024 | 5:23 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | WET | TRAFFIC SIGNAL | NOT ENTERED | RAIN | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) / V3:(NOT APPLICABLE,NOT APPLICABLE) |
| 40321314 | 190846.1001 | 4766818.511 | 5/19/2024 | 8:48 AM | 2024 | LEFT TURN | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40322957 | 188492.4226 | 4768512.634 | 5/20/2024 | 4:36 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND GRADE | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40323025 | 188633.1594 | 4766885.193 | 5/20/2024 | 5:27 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(PASSING OR LANE USAGE IMPROPERLY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40324455 | 191148.4447 | 4766810.739 | 5/21/2024 | 6:36 PM | 2024 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40324474 | 189035.5843 | 4767291.827 | 5/21/2024 | 1:42 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(UNSAFE SPEED,FOLLOWING TOO CLOSELY) / V2:(REACTION TO OTHER UNINVOLVED VEHICL,NOT APPLICABLE) |
| 40324500 | 188440.1399 | 4768068.167 | 5/21/2024 | 5:23 PM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | CURVE AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(FOLLOWING TOO CLOSELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40324636 | 191270.4993 | 4766807.037 | 5/21/2024 | 4:49 PM | 2024 | RIGHT TURN (AGAINST OTHER CAR) | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(FAILURE TO YIELD RIGHT OF WAY,NOT AP

| | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 40332064 | 189019.33 | 4765693.39 | 5/30/2024 | 7:20 AM | 2024 | REAR END | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | TWO-WAY,NOT DIVIDED | CLEAR | B - INJURY | V1:(BRAKES DEFECTIVE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40346017 | 188808.9258 | 4766859.414 | 1/26/2023 | 10:13 AM | 2023 | REAR END | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | SNOW/ICE | NONE | NOT ENTERED | SNOW | U - UNKNOWN | V1:(BACKING UNSAFELY,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40349924 | 190967.26 | 4766528.08 | 5/19/2024 | 9:30 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DARK-ROAD UNLIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40370077 | 188358.1 | 4766900.87 | 5/24/2024 | 6:25 PM | 2024 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(NOT ENTERED,NOT ENTERED) / V2:(NOT ENTERED,NOT ENTERED) |
| 40440233 | 189390.896 | 4766841.726 | 10/26/2023 | 8:53 PM | 2023 | LEFT TURN | INJURY | COLLISION WITH MOTOR VEHICLE | DARK-ROAD LIGHTED | STRAIGHT AND LEVEL | DRY | NONE | NOT ENTERED | CLEAR | B - INJURY | V1:(DRUGS (ILLEGAL),PASSING OR LANE USAGE IMPROPERLY) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40457736 | 190999.6182 | 4766579.743 | 7/18/2023 | 8:00 AM | 2023 | OVERTAKING | PROPERTY DAMAGE | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT/ GRADE | DRY | NONE | NOT ENTERED | CLEAR | U - UNKNOWN | V1:(UNSAFE LANE CHANGE,NOT APPLICABLE) / V2:(NOT APPLICABLE,NOT APPLICABLE) |
| 40457800 | 190917.6142 | 4766816.557 | 7/27/2023 | 8:23 AM | 2023 | LEFT TURN (AGAINST OTHER CAR) | INJURY | COLLISION WITH MOTOR VEHICLE | DAYLIGHT | STRAIGHT AND LEVEL | DRY | TRAFFIC SIGNAL | TWO-WAY,NOT DIVIDED | CLOUDY | B - INJURY | V1:(FAILURE TO YIELD RIGHT OF WAY,TURNING IMPROPER) / V2:(NOT APPLICABLE,NOT APPLICABLE) |

| | | | |
|---|---|---|---|
| Project | **Boulevard Central District** | Sheet | **1** of **X** |
| | **GEIS Update** | File # | **H22.007.005** |
| Prepared by | **J.Anastasia** | Date | **01/15/25** |
| Checked by | | Date | |

# Crash Analysis: #3 Niagara Falls Boulevard at Ridge Lea Road









| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 1 | 5/31/2021 | 1:33 PM | Rear End | Clear | PD | |
| 2 | 6/7/2021 | 12:04 AM | Pedestrian | Clear | I | |
| 3 | 6/7/2021 | 12:04 AM | Pedestrian | Clear | I | |
| 4 | 6/17/2021 | 3:36 PM | Rear End | Clear | I | |
| 5 | 7/19/2021 | 12:03 PM | Sideswipe | Clear | PD | |
| 6 | 9/7/2021 | 12:27 PM | Overtaking | Clear | PD | |
| 7 | 9/23/2021 | 12:47 PM | Rear End | Cloudy | PD | |
| 8 | 10/17/2021 | 5:28 PM | Overtaking | Cloudy | I | |
| 9 | 10/31/2021 | 1:39 PM | Rear End | Cloudy | PD | |
| 10 | 11/17/2021 | 11:15 AM | Bicyclist | Cloudy | PD | |
| 11 | 11/27/2021 | 7:42 PM | Left Turn | Cloudy | PD | |
| 12 | 2/4/2022 | 4:30 PM | Sideswipe | Cloudy | PD | |
| 13 | 3/13/2022 | 6:25 PM | Left Turn | Snow | PD | |
| 14 | 3/22/2022 | 8:11 PM | Rear End | Clear | I | |
| 15 | 3/26/2022 | 2:43 PM | Overtaking | Rain | PD | |
| 16 | 4/11/2022 | 7:10 PM | Left Turn | Rain | I | |
| 17 | 8/17/2022 | 8:19 PM | Bicyclist | Cloudy | I | |
| 18 | 8/17/2022 | 1:42 PM | Overtaking | Clear | PD | |

| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 19 | 8/23/2022 | 4:45 PM | Rear End | Cloudy | I | |
| 20 | 8/28/2022 | 3:08 PM | Right Turn | Clear | PD | |
| 21 | 9/5/2022 | 8:00 PM | Sideswipe | Rain | PD | |
| 22 | 9/6/2022 | 3:53 PM | Overtaking | Cloudy | PD | |
| 23 | 10/1/2022 | 11:43 AM | Overtaking | Clear | PD | |
| 24 | 9/25/2022 | 6:40 PM | Right Turn | Cloudy | I | |
| 25 | 11/21/2022 | 5:05 PM | Rear End | Cloudy | PD | |
| 26 | 12/1/2022 | 7:49 PM | Rear End | Clear | PD | |
| 27 | 1/4/2023 | 10:45 AM | Overtaking | Cloudy | PD | |
| 28 | 2/4/2023 | 7:45 PM | Left Turn | Clear | I | |
| 29 | 2/8/2023 | 6:50 PM | Left Turn | Cloudy | PD | |
| 30 | 2/10/2023 | 1:50 PM | Rear End | Rain | PD | |
| 31 | 2/14/2023 | 4:17 PM | Left Turn | Clear | PD | |
| 32 | 2/21/2023 | 2:07 PM | Left Turn | Cloudy | PD | |
| 33 | 4/18/2023 | 10:32 AM | Rear End | Cloudy | PD | |
| 34 | 4/29/2023 | 7:55 PM | Overtaking | Rain | I | |
| 35 | 5/1/2023 | 9:30 AM | Rear End | Clear | PD | |
| 36 | 6/4/2023 | 5:30 PM | Rear End | Unknown | I | |
| 39 | 8/31/2023 | 10:42 AM | Overtaking | Clear | I | |
| 40 | 9/4/2023 | 4:59 PM | Rear End | Clear | PD | |
| 41 | 9/5/2023 | 2:57 PM | Overtaking | Clear | PD | |
| 42 | 9/26/2023 | 3:15 PM | Rear End | Clear | PD | |
| 43 | 11/7/2023 | 8:47 AM | Sideswipe | Cloudy | PD | |
| 45 | 12/29/2023 | 6:18 PM | Left Turn | Cloudy | I | |
| 46 | 1/22/2024 | 11:23 AM | Right Turn | Cloudy | PD | |
| 47 | 2/5/2024 | 3:07 PM | Right Angle | Cloudy | I | |
| 48 | 2/23/2024 | 1:52 PM | Overtaking | Cloudy | I | |
| 49 | 3/21/2024 | 10:00 PM | Left Turn | Clear | I | |
| 52 | 4/11/2024 | 12:37 PM | Rear End | Cloudy | PD | |
| 53 | 4/19/2024 | 11:48 AM | Overtaking | Cloudy | PD | |
| 54 | 5/21/2024 | 5:23 PM | Rear End | Clear | I | |

## Crash Analysis: #7 Niagara Falls Boulevard @Maple Rd & Brighton Rd








| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 1 | 6/15/2021 | 6:15 PM | Rear End | Clear | I | |
| 2 | 8/3/2021 | 1:13 PM | Left Turn | Clear | PD | |
| 3 | 8/7/2021 | 4:23 PM | Rear End | Cloudy | I | |
| 4 | 8/13/2021 | 9:40 PM | Bicyclist | Clear | I | |
| 5 | 8/31/2021 | 9:47 PM | Rear End | Clear | I | |
| 6 | 9/8/2021 | 7:55 AM | Rear End | Rain | PD | |
| 7 | 9/21/2021 | 9:05 AM | Rear End | Clear | PD | |
| 8 | 9/25/2021 | 3:24 PM | Overtaking | Cloudy | PD | |
| 9 | 10/22/2021 | 7:30 PM | Rear End | Clear | PD | |
| 10 | 10/22/2021 | 7:08 PM | Right Angle | Clear | PD | |
| 11 | 11/19/2021 | 5:56 PM | Rear End | Clear | I | |
| 12 | 12/30/2021 | 5:12 PM | Rear End | Clear | I | |
| 13 | 1/1/2022 | 4:05 AM | Rear End | Cloudy | PD | |
| 14 | 1/5/2022 | 4:23 PM | Sideswipe | Rain | I | |
| 15 | 1/8/2022 | 6:45 PM | Rear End | Unknown | PD | |
| 16 | 1/28/2022 | 1:30 PM | Sideswipe | Cloudy | I | |
| 17 | 2/9/2022 | 8:46 AM | Left Turn | Cloudy | I | |
| 18 | 3/5/2022 | 6:42 AM | Right Angle | Cloudy | I | |

| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 19 | 3/30/2022 | 6:19 PM | Overtaking | Clear | PD | |
| 20 | 4/4/2022 | 8:46 AM | Sideswipe | Clear | PD | |
| 21 | 4/18/2022 | 10:35 AM | Rear End | Cloudy | PD | |
| 22 | 5/6/2022 | 4:29 PM | Rear End | Clear | PD | |
| 23 | 5/31/2022 | 4:30 PM | Rear End | Clear | PD | |
| 24 | 5/31/2022 | 11:27 AM | Overtaking | Clear | PD | |
| 25 | 5/31/2022 | 6:10 PM | Rear End | Clear | PD | |
| 26 | 6/3/2022 | 11:59 AM | Rear End | Clear | PD | |
| 27 | 6/30/2022 | 1:02 PM | Rear End | Clear | I | |
| 28 | 11/23/2022 | 9:35 AM | Overtaking | Clear | PD | |
| 29 | 11/27/2022 | 5:15 PM | Left Turn | Clear | PD | |
| 30 | 12/15/2022 | 8:03 AM | Rear End | Sleet/Hail/ Freezing Rain | PD | |
| 31 | 2/22/2023 | 7:26 PM | Rear End | Sleet/Hail/ Freezing Rain | PD | |
| 32 | 2/22/2023 | 2:58 PM | Rear End | Snow | PD | |
| 33 | 5/9/2023 | 12:55 PM | Rear End | Clear | PD | |
| 34 | 6/20/2023 | 11:30 AM | Left Turn | Clear | PD | |
| 35 | 7/6/2023 | 4:22 PM | Rear End | Cloudy | I | |
| 36 | 7/19/2023 | 12:15 PM | Rear End | Clear | PD | |
| 37 | 8/4/2023 | 6:37 PM | Left Turn | Clear | PD | |
| 38 | 8/13/2023 | 9:16 AM | Rear End | Clear | I | |
| 39 | 10/28/2023 | 12:00 PM | Overtaking | Clear | PD | |
| 40 | 12/30/2023 | 11:11 AM | Rear End | Cloudy | I | |
| 41 | 3/17/2024 | 1:44 PM | Left Turn | Rain | I | |
| 42 | 4/18/2024 | 7:35 PM | Rear End | Cloudy | PD | |
| 43 | 5/24/2024 | 6:25 PM | Overtaking | Clear | PD | |
| 44 | 7/13/2021 | 2:29 PM | Rear End | Clear | PD | |

| | | | |
|---|---|---|---|
| Project | **Boulevard Central District** | Sheet | **5** of **X** |
| | **GEIS Update** | File # | **H22.007.005** |
| Prepared by | **J.Anastasia** | Date | **01/14/25** |
| Checked by | | Date | |

## Crash Analysis: #10 Niagara Falls Boulevard @Sheridan Drive





| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 1 | 8/24/2021 | 3:45 PM | Rear End | Clear | I | |
| 2 | 9/18/2021 | 3:22 AM | Rear End | Clear | I | |
| 3 | 10/2/2021 | 10:55 AM | Right Turn | Clear | PD | |
| 4 | 1/3/2022 | 7:50 PM | Left Turn | Clear | PD | |
| 5 | 4/8/2022 | 7:31 AM | Right Angle | Clear | PD | |
| 6 | 6/15/2022 | 6:15 AM | Left Turn | Clear | I | |
| 7 | 8/14/2022 | 10:02 PM | Rear End | Cloudy | PD | |
| 8 | 8/25/2022 | 7:53 AM | Rear End | Clear | PD | |
| 9 | 8/28/2022 | 10:30 AM | Right Turn | Unknown | PD | |
| 10 | 10/6/2022 | 9:24 AM | Pedestrian | Cloudy | I | |
| 11 | 10/21/2022 | 11:04 AM | Rear End | Clear | PD | |
| 12 | 10/26/2022 | 4:01 PM | Rear End | Unknown | PD | |
| 13 | 11/10/2022 | 3:30 PM | Left Turn | Clear | PD | |
| 14 | 12/21/2022 | 4:52 PM | Pedestrian | Cloudy | I | |
| 15 | 1/18/2023 | 6:07 PM | Right Turn | Clear | PD | |
| 16 | 4/3/2023 | 10:40 PM | Rear End | Clear | PD | |
| 17 | 4/22/2023 | 11:49 AM | Rear End | Rain | I | |
| 18 | 4/26/2023 | 10:26 PM | Rear End | Clear | I | |




F:\Project\H22 - Town of Amherst\H22.007 - 2021 Professional Svcs Term\H22.007.005 - BCD Supplemental - GEIS\Planning-Study\Technical Information\Accident Analysis\Crash Diagrams

| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 19 | 5/24/2023 | 7:00 PM | Rear End | Clear | I | |
| 20 | 5/25/2023 | 12:22 PM | Rear End | Clear | PD | |
| 21 | 5/26/2023 | 2:05 PM | Rear End | Clear | I | |
| 22 | 10/4/2023 | 5:30 PM | Rear End | Clear | PD | |
| 23 | 10/16/2023 | 6:16 AM | Overtaking | Rain | PD | |
| 24 | 10/27/2023 | 10:12 AM | Sideswipe | Clear | PD | |
| 25 | 11/12/2023 | 12:29 PM | Overtaking | Clear | PD | |
| 26 | 12/11/2023 | 2:53 PM | Left Turn | Cloudy | I | |
| 27 | 1/16/2024 | 12:37 PM | Overtaking | Clear | PD | |
| 28 | 1/29/2024 | 12:24 PM | Rear End | Cloudy | PD | |
| 29 | 2/20/2024 | 5:15 PM | Left Turn | Clear | I | |
| 30 | 4/10/2024 | 12:00 AM | Overtaking | Clear | PD | |

# Crash Analysis: #12 Maple Road @Alberta Drive









PD - Property Damage
NR - Nonreportable
I - Injury
F - Fatality

| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 1 | 8/13/2021 | 7:40 PM | Rear End | Clear | PD | |
| 2 | 10/8/2021 | 6:13 PM | Left Turn | Cloudy | PD | |
| 3 | 11/5/2021 | 12:59 PM | Left Turn | Clear | PD | |
| 4 | 12/23/2021 | 12:00 PM | Rear End | Freezing Rain | PD | |
| 5 | 4/26/2022 | 9:33 PM | Rear End | Rain | PD | |
| 6 | 10/12/2022 | 3:24 PM | Rear End | Cloudy | PD | |
| 7 | 1/26/2023 | 10:13 AM | Rear End | Snow | PD | |
| 8 | 3/7/2023 | 8:53 PM | Overtaking | Clear | I | |
| 9 | 9/20/2023 | 3:33 PM | Right Angle | Clear | I | |
| 10 | 12/21/2023 | 8:53 PM | Pedestrian | Clear | I | |
| 11 | 12/27/2023 | 5:25 PM | Left Turn | Rain | PD | |
| 12 | 1/5/2024 | 4:00 PM | Rear End | Clear | PD | |
| 13 | 1/10/2024 | 11:01 AM | Rear End | Cloudy | PD | |
| 14 | 2/9/2024 | 9:01 PM | Left Turn | Clear | PD | |
| 15 | 2/22/2024 | 1:39 PM | Right Angle | Cloudy | PD | |
| 16 | 3/30/2024 | 10:30 AM | Right Angle | Clear | I | |
| 17 | 4/12/2024 | 3:36 PM | Rear End | Clear | I | |

| | | | |
|---|---|---|---|
| Project | **Boulevard Central District** | Sheet | **1** of **X** |
| | **GEIS Update** | File # | **H22.007.005** |
| Prepared by | **J.Anastasia** | Date | **01/14/25** |
| Checked by | | Date | |

## Crash Analysis: #13 Maple Road at North Bailey Avenue









| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 1 | 5/31/2021 | 10:25 AM | Rear End | Clear | PD | |
| 2 | 9/4/2021 | 12:25 PM | Rear End | Clear | PD | |
| 3 | 9/6/2021 | 8:23 PM | Sideswipe | Clear | PD | |
| 4 | 9/19/2021 | 10:34 AM | Rear End | Clear | PD | |
| 5 | 10/7/2021 | 3:55 PM | Rear End | Clear | PD | |
| 6 | 10/8/2021 | 12:11 PM | Rear End | Cloudy | PD | |
| 7 | 10/16/2021 | 3:21 PM | Rear End | Cloudy | I | |
| 8 | 11/4/2021 | 10:31 PM | Overtaking | Rain | PD | |
| 9 | 11/11/2021 | 2:38 PM | Left Turn | Clear | PD | |
| 10 | 11/20/2021 | 4:42 PM | Rear End | Cloudy | PD | |
| 11 | 12/19/2021 | 10:18 PM | Head On | Clear | PD | |
| 12 | 1/5/2022 | 10:31 AM | Right Turn | Cloudy | PD | |
| 13 | 3/13/2022 | 11:26 AM | Rear End | Cloudy | I | |
| 14 | 4/14/2022 | 12:19 PM | Left Turn | Rain | PD | |
| 15 | 6/21/2022 | 5:06 PM | Left Turn | Clear | I | |
| 16 | 6/23/2022 | 5:57 PM | Rear End | Clear | I | |
| 17 | 9/2/2022 | 6:47 PM | Rear End | Clear | PD | |

| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 18 | 9/8/2022 | 8:29 AM | Left Turn | Clear | PD | |
| 19 | 10/15/2022 | 7:11 PM | Left Turn | Cloudy | PD | |
| 20 | 11/15/2022 | 6:00 PM | Left Turn | Clear | PD | |
| 21 | 12/5/2022 | 12:57 PM | Rear End | Clear | PD | |
| 22 | 12/8/2022 | 9:40 AM | Left Turn | Cloudy | PD | |
| 23 | 1/1/2023 | 6:25 PM | Left Turn | Cloudy | I | |
| 24 | 1/13/2023 | 7:43 AM | Right Angle | Snow | PD | |
| 25 | 3/10/2023 | 11:30 AM | Overtaking | Cloudy | PD | |
| 26 | 3/11/2023 | 12:41 PM | Sideswipe | Cloudy | PD | |
| 27 | 4/12/2023 | 1:11 PM | Rear End | Clear | PD | |
| 28 | 4/12/2023 | 2:15 PM | Overtaking | Clear | PD | |
| 29 | 7/11/2023 | 9:18 PM | Rear End | Rain | PD | |
| 30 | 8/21/2023 | 7:08 PM | Right Turn | Cloudy | PD | |
| 31 | 8/23/2023 | 11:31 AM | Left Turn | Rain | I | |
| 32 | 8/29/2023 | 5:47 PM | Rear End | Clear | I | |
| 33 | 9/5/2023 | 6:20 PM | Rear End | Clear | PD | |
| 34 | 9/22/2023 | 4:55 PM | Rear End | Clear | PD | |
| 35 | 9/28/2023 | 7:20 PM | Left Turn | Clear | I | |
| 36 | 10/28/2023 | 4:00 PM | Rear End | Clear | PD | |
| 37 | 11/3/2023 | 8:00 PM | Overtaking | Clear | PD | |
| 38 | 12/3/2023 | 9:21 PM | Left Turn | Rain | PD | |
| 39 | 12/23/2023 | 5:11 PM | Rear End | Rain | I | |
| 40 | 2/18/2024 | 7:15 PM | Left Turn | Snow | PD | |
| 41 | 2/23/2024 | 4:10 PM | Rear End | Clear | PD | |
| 42 | 4/7/2024 | 6:35 PM | Right Angle | Clear | PD | |
| 43 | 4/7/2024 | 6:40 PM | Rear End | Clear | PD | |
| 44 | 5/10/2024 | 5:05 PM | Overtaking | Clear | PD | |
| 45 | 5/15/2024 | 10:16 PM | Rear End | Clear | PD | |

| | | | |
|---|---|---|---|
| Project | **Boulevard Central District** | Sheet | **1** of **X** |
| | **GEIS Update** | File # | **H22.007.005** |
| Prepared by | **J.Anastasia** | Date | **01/14/25** |
| Checked by | | Date | |

## Crash Analysis: #16 Maple Road @Sweet Home Road




| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 1 | 5/31/2021 | 12:28 PM | Left Turn | Clear | I | |
| 2 | 7/12/2021 | 7:11 PM | Sideswipe | Cloudy | PD | |
| 3 | 9/17/2021 | 6:46 PM | Rear End | Clear | I | |
| 4 | 9/26/2021 | 4:13 PM | Rear End | Clear | PD | |
| 5 | 9/27/2021 | 3:05 PM | Rear End | Cloudy | I | |
| 6 | 10/11/2021 | 5:46 PM | Rear End | Cloudy | I | |
| 7 | 10/15/2021 | 5:55 PM | Rear End | Rain | PD | |
| 8 | 10/30/2021 | 3:54 PM | Rear End | Cloudy | I | |
| 9 | 11/22/2021 | 6:34 PM | Rear End | Clear | I | |
| 10 | 11/29/2021 | 9:19 PM | Left Turn | Clear | PD | |
| 11 | 12/8/2021 | 3:38 PM | Sideswipe | Snow | PD | |
| 12 | 12/23/2021 | 10:30 AM | Rear End | Cloudy | PD | |
| 13 | 12/27/2021 | 7:00 PM | Left Turn | Cloudy | PD | |
| 14 | 1/19/2022 | 7:53 PM | Sideswipe | Cloudy | PD | |
| 15 | 2/24/2022 | 11:00 AM | Overtaking | Cloudy | PD | |
| 16 | 2/25/2022 | 8:05 PM | Sideswipe | Snow | I | |

| No. | Date | Time | Collision Type | Weather | Severity | Comment |
|---|---|---|---|---|---|---|
| 17 | 2/28/2022 | 12:47 PM | Rear End | Cloudy | I | |
| 18 | 3/19/2022 | 5:06 PM | Left Turn | Cloudy | I | |
| 19 | 4/2/2022 | 10:57 PM | Rear End | Clear | I | |
| 20 | 4/28/2022 | 1:14 PM | Rear End | Clear | PD | |
| 21 | 5/14/2022 | 10:03 AM | Overtaking | Clear | PD | |
| 22 | 6/21/2022 | 7:19 PM | Rear End | Clear | I | |
| 23 | 6/21/2022 | 11:04 AM | Rear End | Clear | I | |
| 24 | 6/22/2022 | 4:58 PM | Rear End | Clear | I | |
| 25 | 7/8/2022 | 2:40 PM | Sideswipe | Clear | PD | |
| 26 | 8/11/2022 | 11:27 AM | Rear End | Clear | PD | |
| 27 | 9/15/2022 | 9:00 AM | Rear End | Cloudy | I | |
| 28 | 10/3/2022 | 1:10 PM | Rear End | Cloudy | PD | |
| 29 | 10/18/2022 | 6:05 PM | Rear End | Rain | I | |
| 30 | 10/28/2022 | 11:24 AM | Left Turn | Cloudy | PD | |
| 31 | 11/11/2022 | 6:00 PM | Sideswipe | Clear | PD | |
| 32 | 11/16/2022 | 10:37 PM | Right Angle | Clear | I | |
| 33 | 11/17/2022 | 9:45 PM | Rear End | Snow | PD | |
| 34 | 12/14/2022 | 11:38 AM | Rear End | Clear | PD | |
| 35 | 1/23/2023 | 6:55 PM | Left Turn | Cloudy | I | |
| 36 | 1/26/2023 | 9:00 AM | Left Turn | Snow | I | |
| 37 | 2/10/2023 | 6:44 PM | Left Turn | Clear | I | |
| 38 | 2/14/2023 | 9:35 AM | Overtaking | Clear | PD | |
| 39 | 2/26/2023 | 8:00 PM | Overtaking | Clear | PD | |
| 40 | 4/3/2023 | 8:27 PM | Rear End | Rain | PD | |
| 41 | 4/5/2023 | 2:54 PM | Rear End | Rain | I | |
| 42 | 4/6/2023 | 11:29 PM | Rear End | Clear | PD | |
| 43 | 5/4/2023 | 10:45 AM | Rear End | Unknown | PD | |
| 44 | 5/17/2023 | 10:12 AM | Rear End | Cloudy | PD | |
| 45 | 6/23/2023 | 5:40 PM | Left Turn | Cloudy | PD | |
| 46 | 7/29/2023 | 12:30 PM | Left Turn | Rain | PD | |
| 47 | 8/5/2023 | 1:05 PM | Rear End | Cloudy | I | |
| 48 | 8/14/2023 | 9:30 AM | Rear End | Cloudy | PD | |
| 49 | 10/11/2023 | 4:55 PM | Rear End | Cloudy | I | |
| 50 | 10/31/2023 | 7:00 PM | Rear End | Unknown | PD | |
| 51 | 11/17/2023 | 6:15 PM | Right Turn | Cloudy | PD | |
| 52 | 11/28/2023 | 8:03 PM | Left Turn | Cloudy | I | |
| 53 | 12/4/2023 | 3:20 PM | Left Turn | Cloudy | I | |
| 54 | 1/16/2024 | 7:53 AM | Sideswipe | Snow | PD | |
| 55 | 1/31/2024 | 5:10 PM | Rear End | Clear | I | |
| 56 | 2/9/2024 | 11:31 AM | Rear End | Clear | PD | |
| 57 | 3/26/2024 | 3:35 PM | Left Turn | Unknown | PD | |
| 58 | 5/24/2024 | 9:25 AM | Right Turn | Clear | I | |

# Appendix C – Traffic Data

TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Niagara Falls Boulevard & M |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Niagara Falls Boulevard & M |
| **Latitude and Longitude** | 42.99274,-78.82253 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:45:00 | 2023-11-16 17:45:00 | 0.976 |


## Turning Movement Data


| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 1 | 210 | 7 | 11 | **229** | 0 | 0 | 8 | 1 | 1 | 0 | **10** | 0 | 0 | 7 | 264 | 0 | 1 | **272** | 1 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **512** |
| 3:15:00 PM | 4 | 247 | 11 | 4 | **266** | 0 | 0 | 6 | 0 | 1 | 0 | **7** | 1 | 0 | 13 | 265 | 0 | 1 | **279** | 1 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **553** |
| 3:30:00 PM | 1 | 253 | 12 | 5 | **271** | 0 | 0 | 6 | 0 | 4 | 0 | **10** | 3 | 1 | 9 | 313 | 0 | 0 | **322** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **605** |
| 3:45:00 PM | 2 | 230 | 7 | 7 | **246** | 0 | 0 | 10 | 0 | 1 | 0 | **11** | 2 | 1 | 7 | 298 | 0 | 0 | **305** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **563** |
| **Hourly Total** | 8 | 940 | 37 | 27 | **1012** | 0 | 0 | 30 | 1 | 7 | 0 | **38** | 6 | 2 | 36 | 1140 | 0 | 2 | **1178** | 2 | 0 | 5 | 0 | 0 | 0 | **5** | 0 | 0 | **2233** |
| 4:00:00 PM | 3 | 231 | 17 | 8 | **259** | 0 | 0 | 16 | 0 | 7 | 0 | **23** | 1 | 0 | 14 | 315 | 0 | 0 | **329** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **612** |
| 4:15:00 PM | 5 | 247 | 14 | 6 | **272** | 0 | 0 | 7 | 0 | 1 | 0 | **8** | 0 | 0 | 8 | 285 | 0 | 0 | **293** | 0 | 0 | 4 | 0 | 2 | 0 | **6** | 0 | 0 | **579** |
| 4:30:00 PM | 4 | 269 | 9 | 6 | **288** | 0 | 0 | 8 | 0 | 2 | 0 | **10** | 2 | 1 | 13 | 296 | 0 | 0 | **309** | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 1 | **611** |
| 4:45:00 PM | 0 | 251 | 9 | 11 | **271** | 0 | 0 | 5 | 0 | 2 | 0 | **7** | 1 | 1 | 12 | 342 | 0 | 1 | **355** | 0 | 0 | 3 | 0 | 1 | 0 | **4** | 0 | 0 | **637** |
| **Hourly Total** | 12 | 998 | 49 | 31 | **1090** | 0 | 0 | 36 | 0 | 12 | 0 | **48** | 4 | 2 | 47 | 1238 | 0 | 1 | **1286** | 0 | 0 | 12 | 0 | 3 | 0 | **15** | 0 | 1 | **2439** |
| 5:00:00 PM | 4 | 275 | 8 | 9 | **296** | 0 | 0 | 10 | 0 | 3 | 0 | **13** | 0 | 0 | 7 | 277 | 0 | 0 | **284** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **593** |
| 5:15:00 PM | 3 | 278 | 9 | 10 | **300** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 7 | 297 | 0 | 1 | **305** | 0 | 0 | 6 | 0 | 0 | 0 | **6** | 0 | 0 | **623** |
| 5:30:00 PM | 2 | 290 | 14 | 12 | **318** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 9 | 295 | 0 | 0 | **304** | 0 | 0 | 2 | 1 | 1 | 0 | **4** | 0 | 0 | **638** |
| 5:45:00 PM | 5 | 263 | 12 | 10 | **290** | 0 | 0 | 6 | 0 | 2 | 0 | **8** | 1 | 0 | 10 | 280 | 0 | 0 | **290** | 1 | 0 | 1 | 0 | 1 | 0 | **2** | 0 | 0 | **590** |
| **Hourly Total** | 14 | 1106 | 43 | 41 | **1204** | 0 | 0 | 36 | 0 | 9 | 0 | **45** | 1 | 0 | 33 | 1149 | 0 | 1 | **1183** | 1 | 0 | 9 | 1 | 2 | 0 | **12** | 0 | 0 | **2444** |
| **Grand Total** | 34 | 3044 | 129 | 99 | **3306** | 0 | 0 | 102 | 1 | 28 | 0 | **131** | 11 | 4 | 116 | 3527 | 0 | 4 | **3647** | 3 | 0 | 26 | 1 | 5 | 0 | **32** | 0 | 1 | **7116** |
| **% Approach** | 1.0% | 92.1% | 3.9% | 3.0% | **0.0%** | 0.0% | 0.0% | 77.9% | 0.8% | 21.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.2% | 96.7% | 0.0% | 0.1% | **0.0%** | 0.0% | 0.0% | 81.3% | 3.1% | 15.6% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 0.5% | 42.8% | 1.8% | 1.4% | **46.5%** | 0.0% | 0.0% | 1.4% | 0.0% | 0.4% | 0.0% | **1.8%** | 0.0% | 0.0% | 1.6% | 49.6% | 0.0% | 0.1% | **51.3%** | 0.0% | 0.0% | 0.4% | 0.0% | 0.1% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 34 | 3012 | 126 | 99 | **3271** | 0 | 0 | 102 | 1 | 28 | 0 | **131** | 0 | 0 | 115 | 3478 | 0 | 4 | **3597** | 0 | 0 | 26 | 1 | 5 | 0 | **32** | 0 | 0 | **7031** |
| **% Lights** | 100.0% | 98.9% | 97.7% | 100.0% | **98.9%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 99.1% | 98.6% | 0.0% | 100.0% | **98.6%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **98.8%** |
| **Trucks** | 0 | 18 | 1 | 0 | **19** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 21 | 0 | 0 | **22** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **41** |
| **% Trucks** | 0.0% | 0.6% | 0.8% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.9% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 10 | 2 | 0 | **12** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 19 | 0 | 0 | **19** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **31** |
| **% Buses** | 0.0% | 0.3% | 1.6% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 10 | 3 | 0 | 0 | 0 | 0 | **0** | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 90.9% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 9.1% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:45:00 PM | 0 | 251 | 9 | 11 | **271** | 0 | 0 | 5 | 0 | 2 | 0 | **7** | 1 | 1 | 12 | 342 | 0 | 1 | **355** | 0 | 0 | 3 | 0 | 1 | 0 | **4** | 0 | 0 | **637** |
| 5:00:00 PM | 4 | 275 | 8 | 9 | **296** | 0 | 0 | 10 | 0 | 3 | 0 | **13** | 0 | 0 | 7 | 277 | 0 | 0 | **284** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **593** |
| 5:15:00 PM | 3 | 278 | 9 | 10 | **300** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 7 | 297 | 0 | 1 | **305** | 0 | 0 | 6 | 0 | 0 | 0 | **6** | 0 | 0 | **623** |
| 5:30:00 PM | 2 | 290 | 14 | 12 | **318** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 9 | 295 | 0 | 0 | **304** | 0 | 0 | 2 | 1 | 1 | 0 | **4** | 0 | 0 | **638** |
| **Grand Total** | 9 | 1094 | 40 | 42 | **1185** | 0 | 0 | 35 | 0 | 9 | 0 | **44** | 1 | 1 | 35 | 1211 | 0 | 2 | **1248** | 0 | 0 | 11 | 1 | 2 | 0 | **14** | 0 | 0 | **2491** |
| **% Approach** | 0.8% | 92.3% | 3.4% | 3.5% | **0.0%** | 0.0% | 0.0% | 79.5% | 0.0% | 20.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.8% | 97.0% | 0.0% | 0.2% | **0.0%** | 0.0% | 0.0% | 78.6% | 7.1% | 14.3% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 0.4% | 43.9% | 1.6% | 1.7% | **47.6%** | 0.0% | 0.0% | 1.4% | 0.0% | 0.4% | 0.0% | **1.8%** | 0.0% | 0.0% | 1.4% | 48.6% | 0.0% | 0.1% | **50.1%** | 0.0% | 0.0% | 0.4% | 0.0% | 0.1% | 0.0% | **0.6%** | 0.0% | 0.0% | |
| **PHF** | 0.563 | 0.943 | 0.714 | 0.875 | **0.932** | 0.000 | 0.000 | 0.875 | 0.000 | 0.750 | 0.000 | **0.846** | 0.000 | 0.000 | 0.729 | 0.885 | 0.000 | 0.500 | **0.879** | 0.000 | 0.000 | 0.458 | 0.250 | 0.500 | 0.000 | **0.583** | 0.000 | 0.000 | **0.976** |
| **Lights** | 9 | 1085 | 40 | 42 | **1176** | 0 | 0 | 35 | 0 | 9 | 0 | **44** | 0 | 0 | 35 | 1201 | 0 | 2 | **1238** | 0 | 0 | 11 | 1 | 2 | 0 | **14** | 0 | 0 | **2472** |
| **% Lights** | 100.0% | 99.2% | 100.0% | 100.0% | **99.2%** | 0.0% | 0.0% | 100.0% | 0.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 99.2% | 0.0% | 100.0% | **99.2%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.2%** |
| **Trucks** | 0 | 6 | 0 | 0 | **6** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **11** |
| **% Trucks** | 0.0% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **6** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 1 | 210 | 7 | 11 | **229** | 0 | 0 | 8 | 1 | 1 | 0 | **10** | 0 | 0 | 7 | 264 | 0 | 1 | **272** | 1 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **512** |
| 3:15:00 PM | 4 | 247 | 11 | 4 | **266** | 0 | 0 | 6 | 0 | 1 | 0 | **7** | 1 | 0 | 13 | 265 | 0 | 1 | **279** | 1 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **553** |
| 3:30:00 PM | 1 | 253 | 12 | 5 | **271** | 0 | 0 | 6 | 0 | 4 | 0 | **10** | 3 | 1 | 9 | 313 | 0 | 0 | **322** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **605** |
| 3:45:00 PM | 2 | 230 | 7 | 7 | **246** | 0 | 0 | 10 | 0 | 1 | 0 | **11** | 2 | 1 | 7 | 298 | 0 | 0 | **305** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **563** |
| **Hourly Total** | 8 | 940 | 37 | 27 | **1012** | 0 | 0 | 30 | 1 | 7 | 0 | **38** | 6 | 2 | 36 | 1140 | 0 | 2 | **1178** | 2 | 0 | 5 | 0 | 0 | 0 | **5** | 0 | 0 | **2233** |
| 4:00:00 PM | 3 | 231 | 17 | 8 | **259** | 0 | 0 | 16 | 0 | 7 | 0 | **23** | 1 | 0 | 14 | 315 | 0 | 0 | **329** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **612** |
| 4:15:00 PM | 5 | 247 | 14 | 6 | **272** | 0 | 0 | 7 | 0 | 1 | 0 | **8** | 0 | 0 | 8 | 285 | 0 | 0 | **293** | 0 | 0 | 4 | 0 | 2 | 0 | **6** | 0 | 0 | **579** |
| 4:30:00 PM | 4 | 269 | 9 | 6 | **288** | 0 | 0 | 8 | 0 | 2 | 0 | **10** | 2 | 1 | 13 | 296 | 0 | 0 | **309** | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 1 | **611** |
| 4:45:00 PM | 0 | 251 | 9 | 11 | **271** | 0 | 0 | 5 | 0 | 2 | 0 | **7** | 1 | 1 | 12 | 342 | 0 | 1 | **355** | 0 | 0 | 3 | 0 | 1 | 0 | **4** | 0 | 0 | **637** |
| **Hourly Total** | 12 | 998 | 49 | 31 | **1090** | 0 | 0 | 36 | 0 | 12 | 0 | **48** | 4 | 2 | 47 | 1238 | 0 | 1 | **1286** | 0 | 0 | 12 | 0 | 3 | 0 | **15** | 0 | 1 | **2439** |
| 5:00:00 PM | 4 | 275 | 8 | 9 | **296** | 0 | 0 | 10 | 0 | 3 | 0 | **13** | 0 | 0 | 7 | 277 | 0 | 0 | **284** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **593** |
| 5:15:00 PM | 3 | 278 | 9 | 10 | **300** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 7 | 297 | 0 | 1 | **305** | 0 | 0 | 6 | 0 | 0 | 0 | **6** | 0 | 0 | **623** |
| 5:30:00 PM | 2 | 290 | 14 | 12 | **318** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 9 | 295 | 0 | 0 | **304** | 0 | 0 | 2 | 1 | 1 | 0 | **4** | 0 | 0 | **638** |
| 5:45:00 PM | 5 | 263 | 12 | 10 | **290** | 0 | 0 | 6 | 0 | 2 | 0 | **8** | 1 | 0 | 10 | 280 | 0 | 0 | **290** | 1 | 0 | 1 | 0 | 1 | 0 | **2** | 0 | 0 | **590** |
| **Hourly Total** | 14 | 1106 | 43 | 41 | **1204** | 0 | 0 | 36 | 0 | 9 | 0 | **45** | 1 | 0 | 33 | 1149 | 0 | 1 | **1183** | 1 | 0 | 9 | 1 | 2 | 0 | **12** | 0 | 0 | **2444** |
| **Grand Total** | 34 | 3044 | 129 | 99 | **3306** | 0 | 0 | 102 | 1 | 28 | 0 | **131** | 11 | 4 | 116 | 3527 | 0 | 4 | **3647** | 3 | 0 | 26 | 1 | 5 | 0 | **32** | 0 | 1 | **7116** |
| **% Approach** | 1.0% | 92.1% | 3.9% | 3.0% | **0.0%** | 0.0% | 0.0% | 77.9% | 0.8% | 21.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.2% | 96.7% | 0.0% | 0.1% | **0.0%** | 0.0% | 0.0% | 81.3% | 3.1% | 15.6% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 0.5% | 42.8% | 1.8% | 1.4% | **46.5%** | 0.0% | 0.0% | 1.4% | 0.0% | 0.4% | 0.0% | **1.8%** | 0.0% | 0.0% | 1.6% | 49.6% | 0.0% | 0.1% | **51.3%** | 0.0% | 0.0% | 0.4% | 0.0% | 0.1% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 34 | 3012 | 126 | 99 | **3271** | 0 | 0 | 102 | 1 | 28 | 0 | **131** | 0 | 0 | 115 | 3478 | 0 | 4 | **3597** | 0 | 0 | 26 | 1 | 5 | 0 | **32** | 0 | 0 | **7031** |
| **% Lights** | 100.0% | 98.9% | 97.7% | 100.0% | **98.9%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 99.1% | 98.6% | 0.0% | 100.0% | **98.6%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **98.8%** |
| **Trucks** | 0 | 18 | 1 | 0 | **19** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 21 | 0 | 0 | **22** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **41** |
| **% Trucks** | 0.0% | 0.6% | 0.8% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.9% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 10 | 2 | 0 | **12** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 19 | 0 | 0 | **19** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **31** |
| **% Buses** | 0.0% | 0.3% | 1.6% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 10 | 3 | 0 | 0 | 0 | 0 | **0** | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 90.9% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 9.1% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:45:00 PM | 0 | 251 | 9 | 11 | **271** | 0 | 0 | 5 | 0 | 2 | 0 | **7** | 1 | 1 | 12 | 342 | 0 | 1 | **355** | 0 | 0 | 3 | 0 | 1 | 0 | **4** | 0 | 0 | **637** |
| 5:00:00 PM | 4 | 275 | 8 | 9 | **296** | 0 | 0 | 10 | 0 | 3 | 0 | **13** | 0 | 0 | 7 | 277 | 0 | 0 | **284** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **593** |
| 5:15:00 PM | 3 | 278 | 9 | 10 | **300** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 7 | 297 | 0 | 1 | **305** | 0 | 0 | 6 | 0 | 0 | 0 | **6** | 0 | 0 | **623** |
| 5:30:00 PM | 2 | 290 | 14 | 12 | **318** | 0 | 0 | 10 | 0 | 2 | 0 | **12** | 0 | 0 | 9 | 295 | 0 | 0 | **304** | 0 | 0 | 2 | 1 | 1 | 0 | **4** | 0 | 0 | **638** |
| **Grand Total** | 9 | 1094 | 40 | 42 | **1185** | 0 | 0 | 35 | 0 | 9 | 0 | **44** | 1 | 1 | 35 | 1211 | 0 | 2 | **1248** | 0 | 0 | 11 | 1 | 2 | 0 | **14** | 0 | 0 | **2491** |
| **% Approach** | 0.8% | 92.3% | 3.4% | 3.5% | **0.0%** | 0.0% | 0.0% | 79.5% | 0.0% | 20.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.8% | 97.0% | 0.0% | 0.2% | **0.0%** | 0.0% | 0.0% | 78.6% | 7.1% | 14.3% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 0.4% | 43.9% | 1.6% | 1.7% | **47.6%** | 0.0% | 0.0% | 1.4% | 0.0% | 0.4% | 0.0% | **1.8%** | 0.0% | 0.0% | 1.4% | 48.6% | 0.0% | 0.1% | **50.1%** | 0.0% | 0.0% | 0.4% | 0.0% | 0.1% | 0.0% | **0.6%** | 0.0% | 0.0% | |
| **PHF** | 0.563 | 0.943 | 0.714 | 0.875 | **0.932** | 0.000 | 0.000 | 0.875 | 0.000 | 0.750 | 0.000 | **0.846** | 0.000 | 0.000 | 0.729 | 0.885 | 0.000 | 0.500 | **0.879** | 0.000 | 0.000 | 0.458 | 0.250 | 0.500 | 0.000 | **0.583** | 0.000 | 0.000 | **0.976** |
| **Lights** | 9 | 1085 | 40 | 42 | **1176** | 0 | 0 | 35 | 0 | 9 | 0 | **44** | 0 | 0 | 35 | 1201 | 0 | 2 | **1238** | 0 | 0 | 11 | 1 | 2 | 0 | **14** | 0 | 0 | **2472** |
| **% Lights** | 100.0% | 99.2% | 100.0% | 100.0% | **99.2%** | 0.0% | 0.0% | 100.0% | 0.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 99.2% | 0.0% | 100.0% | **99.2%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.2%** |
| **Trucks** | 0 | 6 | 0 | 0 | **6** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **11** |
| **% Trucks** | 0.0% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **6** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Niagara Falls Boulevard & M |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Niagara Falls Boulevard & M |
| **Latitude and Longitude** | 42.99274,-78.82253 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 13:45:00 | 2023-11-18 14:45:00 | 0.982 |


# Turning Movement Data


| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 7 | 294 | 7 | 10 | **318** | 1 | 0 | 6 | 0 | 2 | 0 | **8** | 1 | 1 | 12 | 350 | 0 | 1 | **363** | 0 | 0 | 4 | 0 | 1 | 0 | **5** | 0 | 0 | **694** |
| 12:15:00 | 3 | 308 | 11 | 17 | **339** | 0 | 0 | 5 | 0 | 0 | 0 | **5** | 2 | 1 | 5 | 332 | 1 | 0 | **338** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **684** |
| 12:30:00 | 2 | 272 | 12 | 11 | **297** | 0 | 0 | 11 | 0 | 2 | 0 | **13** | 0 | 0 | 20 | 376 | 0 | 0 | **396** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **708** |
| 12:45:00 | 5 | 310 | 14 | 19 | **348** | 0 | 0 | 17 | 0 | 3 | 0 | **20** | 0 | 1 | 10 | 377 | 0 | 1 | **388** | 0 | 0 | 4 | 0 | 1 | 0 | **5** | 0 | 0 | **761** |
| **Hourly Total** | 17 | 1184 | 44 | 57 | **1302** | 1 | 0 | 39 | 0 | 7 | 0 | **46** | 3 | 3 | 47 | 1435 | 1 | 2 | **1485** | 0 | 0 | 12 | 0 | 2 | 0 | **14** | 0 | 0 | **2847** |
| 13:00:00 | 1 | 304 | 16 | 18 | **339** | 0 | 0 | 18 | 0 | 2 | 0 | **20** | 1 | 1 | 9 | 363 | 0 | 0 | **372** | 0 | 0 | 5 | 0 | 0 | 0 | **5** | 0 | 0 | **736** |
| 13:15:00 | 6 | 315 | 9 | 13 | **343** | 0 | 0 | 11 | 0 | 8 | 0 | **19** | 0 | 4 | 9 | 352 | 0 | 2 | **363** | 0 | 2 | 3 | 0 | 1 | 0 | **4** | 0 | 0 | **729** |
| 13:30:00 | 6 | 290 | 8 | 13 | **317** | 0 | 0 | 8 | 0 | 3 | 0 | **11** | 2 | 0 | 6 | 386 | 0 | 1 | **393** | 0 | 0 | 4 | 1 | 0 | 0 | **5** | 0 | 0 | **726** |
| 13:45:00 | 5 | 302 | 13 | 16 | **336** | 0 | 0 | 19 | 0 | 0 | 0 | **19** | 1 | 0 | 11 | 381 | 1 | 0 | **393** | 1 | 0 | 6 | 1 | 0 | 0 | **7** | 0 | 0 | **755** |
| **Hourly Total** | 18 | 1211 | 46 | 60 | **1335** | 0 | 0 | 56 | 0 | 13 | 0 | **69** | 4 | 5 | 35 | 1482 | 1 | 3 | **1521** | 1 | 2 | 18 | 2 | 1 | 0 | **21** | 0 | 0 | **2946** |
| 14:00:00 | 4 | 324 | 12 | 9 | **349** | 0 | 0 | 17 | 0 | 6 | 0 | **23** | 0 | 0 | 16 | 367 | 0 | 0 | **383** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **757** |
| 14:15:00 | 2 | 327 | 6 | 12 | **347** | 0 | 0 | 15 | 0 | 4 | 0 | **19** | 0 | 4 | 14 | 346 | 0 | 0 | **360** | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 0 | **730** |
| 14:30:00 | 4 | 303 | 9 | 13 | **329** | 0 | 0 | 11 | 0 | 2 | 0 | **13** | 4 | 2 | 16 | 370 | 0 | 0 | **386** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **730** |
| 14:45:00 | 1 | 285 | 8 | 12 | **306** | 0 | 0 | 8 | 0 | 5 | 0 | **13** | 1 | 4 | 9 | 366 | 0 | 0 | **375** | 0 | 0 | 5 | 0 | 0 | 0 | **5** | 0 | 0 | **699** |
| **Hourly Total** | 11 | 1239 | 35 | 46 | **1331** | 0 | 0 | 51 | 0 | 17 | 0 | **68** | 5 | 10 | 55 | 1449 | 0 | 0 | **1504** | 0 | 0 | 13 | 0 | 0 | 0 | **13** | 0 | 0 | **2916** |
| **Grand Total** | 46 | 3634 | 125 | 163 | **3968** | 1 | 0 | 146 | 0 | 37 | 0 | **183** | 12 | 18 | 137 | 4366 | 2 | 5 | **4510** | 1 | 2 | 43 | 2 | 3 | 0 | **48** | 0 | 0 | **8709** |
| **% Approach** | 1.2% | 91.6% | 3.2% | 4.1% | **0.0%** | 0.0% | 0.0% | 79.8% | 0.0% | 20.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.0% | 96.8% | 0.0% | 0.1% | **0.0%** | 0.0% | 0.0% | 89.6% | 4.2% | 6.3% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 0.5% | 41.7% | 1.4% | 1.9% | **45.6%** | 0.0% | 0.0% | 1.7% | 0.0% | 0.4% | 0.0% | **2.1%** | 0.0% | 0.0% | 1.6% | 50.1% | 0.0% | 0.1% | **51.8%** | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 46 | 3605 | 124 | 163 | **3938** | 0 | 0 | 145 | 0 | 37 | 0 | **182** | 0 | 0 | 136 | 4341 | 2 | 5 | **4484** | 0 | 0 | 43 | 2 | 3 | 0 | **48** | 0 | 0 | **8652** |
| **% Lights** | 100.0% | 99.2% | 99.2% | 100.0% | **99.2%** | 0.0% | 0.0% | 99.3% | 0.0% | 100.0% | 0.0% | **99.5%** | 0.0% | 0.0% | 99.3% | 99.4% | 100.0% | 100.0% | **99.4%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.3%** |
| **Trucks** | 0 | 17 | 1 | 0 | **18** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 1 | 14 | 0 | 0 | **15** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **34** |
| **% Trucks** | 0.0% | 0.5% | 0.8% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.7% | 0.0% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.7% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 6 | 0 | 0 | **6** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **13** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 10 | 16 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 88.9% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 11.1% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**13:45:00**

| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 13:45:00 | 5 | 302 | 13 | 16 | **336** | 0 | 0 | 19 | 0 | 0 | 0 | **19** | 1 | 0 | 11 | 381 | 1 | 0 | **393** | 1 | 0 | 6 | 1 | 0 | 0 | **7** | 0 | 0 | **755** |
| 14:00:00 | 4 | 324 | 12 | 9 | **349** | 0 | 0 | 17 | 0 | 6 | 0 | **23** | 0 | 0 | 16 | 367 | 0 | 0 | **383** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **757** |
| 14:15:00 | 2 | 327 | 6 | 12 | **347** | 0 | 0 | 15 | 0 | 4 | 0 | **19** | 0 | 4 | 14 | 346 | 0 | 0 | **360** | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 0 | **730** |
| 14:30:00 | 4 | 303 | 9 | 13 | **329** | 0 | 0 | 11 | 0 | 2 | 0 | **13** | 4 | 2 | 16 | 370 | 0 | 0 | **386** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **730** |
| **Grand Total** | 15 | 1256 | 40 | 50 | **1361** | 0 | 0 | 62 | 0 | 12 | 0 | **74** | 5 | 6 | 57 | 1464 | 1 | 0 | **1522** | 1 | 0 | 14 | 1 | 0 | 0 | **15** | 0 | 0 | **2972** |
| **% Approach** | 1.1% | 92.3% | 2.9% | 3.7% | **0.0%** | 0.0% | 0.0% | 83.8% | 0.0% | 16.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.7% | 96.2% | 0.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 93.3% | 6.7% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 0.5% | 42.3% | 1.3% | 1.7% | **45.8%** | 0.0% | 0.0% | 2.1% | 0.0% | 0.4% | 0.0% | **2.5%** | 0.0% | 0.0% | 1.9% | 49.3% | 0.0% | 0.0% | **51.2%** | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | |
| **PHF** | 0.750 | 0.960 | 0.769 | 0.781 | **0.975** | 0.000 | 0.000 | 0.816 | 0.000 | 0.500 | 0.000 | **0.804** | 0.000 | 0.000 | 0.891 | 0.961 | 0.250 | 0.000 | **0.968** | 0.000 | 0.000 | 0.583 | 0.250 | 0.000 | 0.000 | **0.536** | 0.000 | 0.000 | **0.982** |
| **Lights** | 15 | 1248 | 40 | 50 | **1353** | 0 | 0 | 61 | 0 | 12 | 0 | **73** | 0 | 0 | 57 | 1455 | 1 | 0 | **1513** | 0 | 0 | 14 | 1 | 0 | 0 | **15** | 0 | 0 | **2954** |
| **% Lights** | 100.0% | 99.4% | 100.0% | 100.0% | **99.4%** | 0.0% | 0.0% | 98.4% | 0.0% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 100.0% | 99.4% | 100.0% | 0.0% | **99.4%** | 0.0% | 0.0% | 100.0% | 100.0% | 0.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.4%** |
| **Trucks** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **7** |
| **% Trucks** | 0.0% | 0.2% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 1.6% | 0.0% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **6** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 6 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 80.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 7 | 294 | 7 | 10 | **318** | 1 | 0 | 6 | 0 | 2 | 0 | **8** | 1 | 1 | 12 | 350 | 0 | 1 | **363** | 0 | 0 | 4 | 0 | 1 | 0 | **5** | 0 | 0 | **694** |
| 12:15:00 | 3 | 308 | 11 | 17 | **339** | 0 | 0 | 5 | 0 | 0 | 0 | **5** | 2 | 1 | 5 | 332 | 1 | 0 | **338** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **684** |
| 12:30:00 | 2 | 272 | 12 | 11 | **297** | 0 | 0 | 11 | 0 | 2 | 0 | **13** | 0 | 0 | 20 | 376 | 0 | 0 | **396** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **708** |
| 12:45:00 | 5 | 310 | 14 | 19 | **348** | 0 | 0 | 17 | 0 | 3 | 0 | **20** | 0 | 1 | 10 | 377 | 0 | 1 | **388** | 0 | 0 | 4 | 0 | 1 | 0 | **5** | 0 | 0 | **761** |
| **Hourly Total** | 17 | 1184 | 44 | 57 | **1302** | 1 | 0 | 39 | 0 | 7 | 0 | **46** | 3 | 3 | 47 | 1435 | 1 | 2 | **1485** | 0 | 0 | 12 | 0 | 2 | 0 | **14** | 0 | 0 | **2847** |
| 13:00:00 | 1 | 304 | 16 | 18 | **339** | 0 | 0 | 18 | 0 | 2 | 0 | **20** | 1 | 1 | 9 | 363 | 0 | 0 | **372** | 0 | 0 | 5 | 0 | 0 | 0 | **5** | 0 | 0 | **736** |
| 13:15:00 | 6 | 315 | 9 | 13 | **343** | 0 | 0 | 11 | 0 | 8 | 0 | **19** | 0 | 4 | 9 | 352 | 0 | 2 | **363** | 0 | 2 | 3 | 0 | 1 | 0 | **4** | 0 | 0 | **729** |
| 13:30:00 | 6 | 290 | 8 | 13 | **317** | 0 | 0 | 8 | 0 | 3 | 0 | **11** | 2 | 0 | 6 | 386 | 0 | 1 | **393** | 0 | 0 | 4 | 1 | 0 | 0 | **5** | 0 | 0 | **726** |
| 13:45:00 | 5 | 302 | 13 | 16 | **336** | 0 | 0 | 19 | 0 | 0 | 0 | **19** | 1 | 0 | 11 | 381 | 1 | 0 | **393** | 1 | 0 | 6 | 1 | 0 | 0 | **7** | 0 | 0 | **755** |
| **Hourly Total** | 18 | 1211 | 46 | 60 | **1335** | 0 | 0 | 56 | 0 | 13 | 0 | **69** | 4 | 5 | 35 | 1482 | 1 | 3 | **1521** | 1 | 2 | 18 | 2 | 1 | 0 | **21** | 0 | 0 | **2946** |
| 14:00:00 | 4 | 324 | 12 | 9 | **349** | 0 | 0 | 17 | 0 | 6 | 0 | **23** | 0 | 0 | 16 | 367 | 0 | 0 | **383** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **757** |
| 14:15:00 | 2 | 327 | 6 | 12 | **347** | 0 | 0 | 15 | 0 | 4 | 0 | **19** | 0 | 4 | 14 | 346 | 0 | 0 | **360** | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 0 | **730** |
| 14:30:00 | 4 | 303 | 9 | 13 | **329** | 0 | 0 | 11 | 0 | 2 | 0 | **13** | 4 | 2 | 16 | 370 | 0 | 0 | **386** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **730** |
| 14:45:00 | 1 | 285 | 8 | 12 | **306** | 0 | 0 | 8 | 0 | 5 | 0 | **13** | 1 | 4 | 9 | 366 | 0 | 0 | **375** | 0 | 0 | 5 | 0 | 0 | 0 | **5** | 0 | 0 | **699** |
| **Hourly Total** | 11 | 1239 | 35 | 46 | **1331** | 0 | 0 | 51 | 0 | 17 | 0 | **68** | 5 | 10 | 55 | 1449 | 0 | 0 | **1504** | 0 | 0 | 13 | 0 | 0 | 0 | **13** | 0 | 0 | **2916** |
| **Grand Total** | 46 | 3634 | 125 | 163 | **3968** | 1 | 0 | 146 | 0 | 37 | 0 | **183** | 12 | 18 | 137 | 4366 | 2 | 5 | **4510** | 1 | 2 | 43 | 2 | 3 | 0 | **48** | 0 | 0 | **8709** |
| **% Approach** | 1.2% | 91.6% | 3.2% | 4.1% | **0.0%** | 0.0% | 0.0% | 79.8% | 0.0% | 20.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.0% | 96.8% | 0.0% | 0.1% | **0.0%** | 0.0% | 0.0% | 89.6% | 4.2% | 6.3% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 0.5% | 41.7% | 1.4% | 1.9% | **45.6%** | 0.0% | 0.0% | 1.7% | 0.0% | 0.4% | 0.0% | **2.1%** | 0.0% | 0.0% | 1.6% | 50.1% | 0.0% | 0.1% | **51.8%** | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 46 | 3605 | 124 | 163 | **3938** | 0 | 0 | 145 | 0 | 37 | 0 | **182** | 0 | 0 | 136 | 4341 | 2 | 5 | **4484** | 0 | 0 | 43 | 2 | 3 | 0 | **48** | 0 | 0 | **8652** |
| **% Lights** | 100.0% | 99.2% | 99.2% | 100.0% | **99.2%** | 0.0% | 0.0% | 99.3% | 0.0% | 100.0% | 0.0% | **99.5%** | 0.0% | 0.0% | 99.3% | 99.4% | 100.0% | 100.0% | **99.4%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.3%** |
| **Trucks** | 0 | 17 | 1 | 0 | **18** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 1 | 14 | 0 | 0 | **15** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **34** |
| **% Trucks** | 0.0% | 0.5% | 0.8% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.7% | 0.0% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.7% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 6 | 0 | 0 | **6** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **13** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 10 | 18 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 88.9% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 11.1% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**13:45:00**

| Leg | Niagara Falls Boulevard | | | | | | | Meyer Road | | | | | | | Niagara Falls Boulevard | | | | | | | Driveway | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 13:45:00 | 5 | 302 | 13 | 16 | **336** | 0 | 0 | 19 | 0 | 0 | 0 | **19** | 1 | 0 | 11 | 381 | 1 | 0 | **393** | 1 | 0 | 6 | 1 | 0 | 0 | **7** | 0 | 0 | **755** |
| 14:00:00 | 4 | 324 | 12 | 9 | **349** | 0 | 0 | 17 | 0 | 6 | 0 | **23** | 0 | 0 | 16 | 367 | 0 | 0 | **383** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **757** |
| 14:15:00 | 2 | 327 | 6 | 12 | **347** | 0 | 0 | 15 | 0 | 4 | 0 | **19** | 0 | 4 | 14 | 346 | 0 | 0 | **360** | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 0 | **730** |
| 14:30:00 | 4 | 303 | 9 | 13 | **329** | 0 | 0 | 11 | 0 | 2 | 0 | **13** | 4 | 2 | 16 | 370 | 0 | 0 | **386** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | **730** |
| **Grand Total** | 15 | 1256 | 40 | 50 | **1361** | 0 | 0 | 62 | 0 | 12 | 0 | **74** | 5 | 6 | 57 | 1464 | 1 | 0 | **1522** | 1 | 0 | 14 | 1 | 0 | 0 | **15** | 0 | 0 | **2972** |
| **% Approach** | 1.1% | 92.3% | 2.9% | 3.7% | **0.0%** | 0.0% | 0.0% | 83.8% | 0.0% | 16.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.7% | 96.2% | 0.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 93.3% | 6.7% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 0.5% | 42.3% | 1.3% | 1.7% | **45.8%** | 0.0% | 0.0% | 2.1% | 0.0% | 0.4% | 0.0% | **2.5%** | 0.0% | 0.0% | 1.9% | 49.3% | 0.0% | 0.0% | **51.2%** | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | |
| **PHF** | 0.750 | 0.960 | 0.769 | 0.781 | **0.975** | 0.000 | 0.000 | 0.816 | 0.000 | 0.500 | 0.000 | **0.804** | 0.000 | 0.000 | 0.891 | 0.961 | 0.250 | 0.000 | **0.968** | 0.000 | 0.000 | 0.583 | 0.250 | 0.000 | 0.000 | **0.536** | 0.000 | 0.000 | **0.982** |
| **Lights** | 15 | 1248 | 40 | 50 | **1353** | 0 | 0 | 61 | 0 | 12 | 0 | **73** | 0 | 0 | 57 | 1455 | 1 | 0 | **1513** | 0 | 0 | 14 | 1 | 0 | 0 | **15** | 0 | 0 | **2954** |
| **% Lights** | 100.0% | 99.4% | 100.0% | 100.0% | **99.4%** | 0.0% | 0.0% | 98.4% | 0.0% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 100.0% | 99.4% | 100.0% | 0.0% | **99.4%** | 0.0% | 0.0% | 100.0% | 100.0% | 0.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.4%** |
| **Trucks** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **7** |
| **% Trucks** | 0.0% | 0.2% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 1.6% | 0.0% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **6** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 6 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 80.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Niagara Falls Boulevard & E |
| **Legs and Movements** | All Processed Legs & Move |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Niagara Falls Boulevard & E |
| **Latitude and Longitude** | 42.97965,-78.82296 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:45:00 | 2023-11-16 17:45:00 | 0.981 |


## Turning Movement Data


| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 8 | 134 | 19 | 0 | **161** | 0 | 0 | 23 | 67 | 11 | 0 | **101** | 0 | 1 | 13 | 167 | 27 | 0 | **207** | 0 | 0 | 33 | 45 | 0 | 0 | **78** | 0 | 0 | **547** |
| 3:15:00 PM | 4 | 136 | 25 | 1 | **166** | 0 | 0 | 19 | 72 | 9 | 0 | **100** | 0 | 0 | 13 | 128 | 31 | 1 | **173** | 0 | 1 | 39 | 67 | 1 | 0 | **107** | 0 | 0 | **546** |
| 3:30:00 PM | 12 | 155 | 18 | 1 | **186** | 0 | 1 | 23 | 70 | 14 | 0 | **107** | 0 | 0 | 13 | 177 | 22 | 0 | **212** | 1 | 0 | 28 | 75 | 0 | 0 | **103** | 0 | 0 | **608** |
| 3:45:00 PM | 8 | 163 | 20 | 0 | **191** | 1 | 1 | 23 | 85 | 17 | 0 | **125** | 0 | 0 | 8 | 195 | 43 | 0 | **246** | 0 | 0 | 39 | 62 | 0 | 0 | **101** | 0 | 0 | **663** |
| **Hourly Total** | 32 | 588 | 82 | 2 | **704** | 1 | 2 | 88 | 294 | 51 | 0 | **433** | 0 | 1 | 47 | 667 | 123 | 1 | **838** | 1 | 1 | 139 | 249 | 1 | 0 | **389** | 0 | 0 | **2364** |
| 4:00:00 PM | 10 | 162 | 15 | 0 | **187** | 0 | 0 | 27 | 84 | 16 | 0 | **127** | 0 | 0 | 14 | 171 | 37 | 0 | **222** | 0 | 0 | 45 | 58 | 0 | 0 | **103** | 0 | 1 | **639** |
| 4:15:00 PM | 5 | 151 | 24 | 1 | **181** | 0 | 0 | 27 | 97 | 14 | 0 | **138** | 0 | 0 | 12 | 145 | 44 | 0 | **201** | 0 | 0 | 50 | 64 | 0 | 0 | **114** | 0 | 0 | **634** |
| 4:30:00 PM | 12 | 187 | 19 | 1 | **219** | 0 | 0 | 23 | 73 | 7 | 0 | **103** | 0 | 0 | 8 | 163 | 37 | 1 | **209** | 0 | 0 | 37 | 67 | 0 | 0 | **104** | 0 | 0 | **635** |
| 4:45:00 PM | 8 | 199 | 22 | 1 | **230** | 0 | 0 | 10 | 76 | 16 | 0 | **102** | 0 | 1 | 8 | 198 | 43 | 1 | **250** | 0 | 0 | 49 | 54 | 0 | 0 | **103** | 2 | 0 | **685** |
| **Hourly Total** | 35 | 699 | 80 | 3 | **817** | 0 | 0 | 87 | 330 | 53 | 0 | **470** | 0 | 1 | 42 | 677 | 161 | 2 | **882** | 0 | 0 | 181 | 243 | 0 | 0 | **424** | 2 | 1 | **2593** |
| 5:00:00 PM | 6 | 206 | 24 | 0 | **236** | 0 | 0 | 18 | 67 | 9 | 0 | **94** | 0 | 0 | 13 | 182 | 41 | 0 | **236** | 0 | 1 | 42 | 62 | 1 | 0 | **105** | 0 | 0 | **671** |
| 5:15:00 PM | 6 | 203 | 25 | 1 | **235** | 1 | 1 | 20 | 82 | 14 | 0 | **116** | 0 | 0 | 12 | 156 | 32 | 0 | **200** | 1 | 0 | 41 | 59 | 0 | 0 | **100** | 0 | 1 | **651** |
| 5:30:00 PM | 12 | 209 | 20 | 2 | **243** | 0 | 1 | 25 | 81 | 12 | 0 | **118** | 1 | 0 | 9 | 178 | 38 | 0 | **225** | 0 | 0 | 41 | 52 | 1 | 0 | **94** | 1 | 0 | **680** |
| 5:45:00 PM | 11 | 168 | 17 | 1 | **197** | 0 | 0 | 18 | 59 | 11 | 0 | **88** | 0 | 0 | 12 | 180 | 48 | 1 | **241** | 0 | 1 | 40 | 49 | 0 | 0 | **89** | 0 | 0 | **615** |
| **Hourly Total** | 35 | 786 | 86 | 4 | **911** | 1 | 2 | 81 | 289 | 46 | 0 | **416** | 1 | 0 | 46 | 696 | 159 | 1 | **902** | 1 | 2 | 164 | 222 | 2 | 0 | **388** | 1 | 1 | **2617** |
| **Grand Total** | 102 | 2073 | 248 | 9 | **2432** | 2 | 4 | 256 | 913 | 150 | 0 | **1319** | 1 | 2 | 135 | 2040 | 443 | 4 | **2622** | 2 | 3 | 484 | 714 | 3 | 0 | **1201** | 3 | 2 | **7574** |
| **% Approach** | 4.2% | 85.2% | 10.2% | 0.4% | **0.0%** | 0.0% | 0.0% | 19.4% | 69.2% | 11.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.1% | 77.8% | 16.9% | 0.2% | **0.0%** | 0.0% | 0.0% | 40.3% | 59.5% | 0.2% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.3% | 27.4% | 3.3% | 0.1% | **32.1%** | 0.0% | 0.0% | 3.4% | 12.1% | 2.0% | 0.0% | **17.4%** | 0.0% | 0.0% | 1.8% | 26.9% | 5.8% | 0.1% | **34.6%** | 0.0% | 0.0% | 6.4% | 9.4% | 0.0% | 0.0% | **15.9%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 101 | 2048 | 244 | 9 | **2402** | 0 | 0 | 237 | 898 | 147 | 0 | **1282** | 0 | 0 | 122 | 2006 | 432 | 4 | **2564** | 0 | 0 | 350 | 705 | 3 | 0 | **1058** | 0 | 0 | **7306** |
| **% Lights** | 99.0% | 98.8% | 98.4% | 100.0% | **98.8%** | 0.0% | 0.0% | 92.6% | 98.4% | 98.0% | 0.0% | **97.2%** | 0.0% | 0.0% | 90.4% | 98.3% | 97.5% | 100.0% | **97.8%** | 0.0% | 0.0% | 72.3% | 98.7% | 100.0% | 0.0% | **88.1%** | 0.0% | 0.0% | **96.5%** |
| **Trucks** | 0 | 11 | 4 | 0 | **15** | 0 | 0 | 2 | 6 | 2 | 0 | **10** | 0 | 0 | 0 | 15 | 2 | 0 | **17** | 0 | 0 | 3 | 4 | 0 | 0 | **7** | 0 | 0 | **49** |
| **% Trucks** | 0.0% | 0.5% | 1.6% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.8% | 0.7% | 1.3% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.7% | 0.5% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.6% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 11 | 0 | 0 | **11** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 1 | 13 | 8 | 0 | **22** | 0 | 0 | 3 | 4 | 0 | 0 | **7** | 0 | 0 | **48** |
| **% Buses** | 0.0% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.9% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.7% | 0.6% | 1.8% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.6% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.6%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot




TSTData.com


## Summary

# Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:45:00 PM | 8 | 199 | 22 | 1 | **230** | 0 | 0 | 10 | 76 | 16 | 0 | **102** | 0 | 1 | 8 | 198 | 43 | 1 | **250** | 0 | 0 | 49 | 54 | 0 | 0 | **103** | 2 | 0 | **685** |
| 5:00:00 PM | 6 | 206 | 24 | 0 | **236** | 0 | 0 | 18 | 67 | 9 | 0 | **94** | 0 | 0 | 13 | 182 | 41 | 0 | **236** | 0 | 1 | 42 | 62 | 1 | 0 | **105** | 0 | 0 | **671** |
| 5:15:00 PM | 6 | 203 | 25 | 1 | **235** | 1 | 1 | 20 | 82 | 14 | 0 | **116** | 0 | 0 | 12 | 156 | 32 | 0 | **200** | 1 | 0 | 41 | 59 | 0 | 0 | **100** | 0 | 1 | **651** |
| 5:30:00 PM | 12 | 209 | 20 | 2 | **243** | 0 | 1 | 25 | 81 | 12 | 0 | **118** | 1 | 0 | 9 | 178 | 38 | 0 | **225** | 0 | 0 | 41 | 52 | 1 | 0 | **94** | 1 | 0 | **680** |
| **Grand Total** | 32 | 817 | 91 | 4 | **944** | 1 | 2 | 73 | 306 | 51 | 0 | **430** | 1 | 1 | 42 | 714 | 154 | 1 | **911** | 1 | 1 | 173 | 227 | 2 | 0 | **402** | 3 | 1 | **2687** |
| **% Approach** | 3.4% | 86.5% | 9.6% | 0.4% | **0.0%** | 0.0% | 0.0% | 17.0% | 71.2% | 11.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.6% | 78.4% | 16.9% | 0.1% | **0.0%** | 0.0% | 0.0% | 43.0% | 56.5% | 0.5% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.2% | 30.4% | 3.4% | 0.1% | **35.1%** | 0.0% | 0.0% | 2.7% | 11.4% | 1.9% | 0.0% | **16.0%** | 0.0% | 0.0% | 1.6% | 26.6% | 5.7% | 0.0% | **33.9%** | 0.0% | 0.0% | 6.4% | 8.4% | 0.1% | 0.0% | **15.0%** | 0.0% | 0.0% | |
| **PHF** | 0.667 | 0.977 | 0.910 | 0.500 | **0.971** | 0.000 | 0.000 | 0.730 | 0.933 | 0.797 | 0.000 | **0.911** | 0.000 | 0.000 | 0.808 | 0.902 | 0.895 | 0.250 | **0.911** | 0.000 | 0.000 | 0.883 | 0.915 | 0.500 | 0.000 | **0.957** | 0.000 | 0.000 | **0.981** |
| **Lights** | 32 | 810 | 91 | 4 | **937** | 0 | 0 | 67 | 301 | 50 | 0 | **418** | 0 | 0 | 35 | 707 | 154 | 1 | **897** | 0 | 0 | 119 | 226 | 2 | 0 | **347** | 0 | 0 | **2599** |
| **% Lights** | 100.0% | 99.1% | 100.0% | 100.0% | **99.3%** | 0.0% | 0.0% | 91.8% | 98.4% | 98.0% | 0.0% | **97.2%** | 0.0% | 0.0% | 83.3% | 99.0% | 100.0% | 100.0% | **98.6%** | 0.0% | 0.0% | 68.8% | 99.6% | 100.0% | 0.0% | **86.3%** | 0.0% | 0.0% | **96.7%** |
| **Trucks** | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 2 | 1 | 0 | 0 | **3** | 0 | 0 | **12** |
| **% Trucks** | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.7% | 2.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 1.2% | 0.4% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 1 | 4 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **9** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.7% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 2.4% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 3 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 8 | 134 | 19 | 0 | **161** | 0 | 0 | 23 | 67 | 11 | 0 | **101** | 0 | 1 | 13 | 167 | 27 | 0 | **207** | 0 | 0 | 33 | 45 | 0 | 0 | **78** | 0 | 0 | **547** |
| 3:15:00 PM | 4 | 136 | 25 | 1 | **166** | 0 | 0 | 19 | 72 | 9 | 0 | **100** | 0 | 0 | 13 | 128 | 31 | 1 | **173** | 0 | 1 | 39 | 67 | 1 | 0 | **107** | 0 | 0 | **546** |
| 3:30:00 PM | 12 | 155 | 18 | 1 | **186** | 0 | 1 | 23 | 70 | 14 | 0 | **107** | 0 | 0 | 13 | 177 | 22 | 0 | **212** | 1 | 0 | 28 | 75 | 0 | 0 | **103** | 0 | 0 | **608** |
| 3:45:00 PM | 8 | 163 | 20 | 0 | **191** | 1 | 1 | 23 | 85 | 17 | 0 | **125** | 0 | 0 | 8 | 195 | 43 | 0 | **246** | 0 | 0 | 39 | 62 | 0 | 0 | **101** | 0 | 0 | **663** |
| **Hourly Total** | 32 | 588 | 82 | 2 | **704** | 1 | 2 | 88 | 294 | 51 | 0 | **433** | 0 | 1 | 47 | 667 | 123 | 1 | **838** | 1 | 1 | 139 | 249 | 1 | 0 | **389** | 0 | 0 | **2364** |
| 4:00:00 PM | 10 | 162 | 15 | 0 | **187** | 0 | 0 | 27 | 84 | 16 | 0 | **127** | 0 | 0 | 14 | 171 | 37 | 0 | **222** | 0 | 0 | 45 | 58 | 0 | 0 | **103** | 0 | 1 | **639** |
| 4:15:00 PM | 5 | 151 | 24 | 1 | **181** | 0 | 0 | 27 | 97 | 14 | 0 | **138** | 0 | 0 | 12 | 145 | 44 | 0 | **201** | 0 | 0 | 50 | 64 | 0 | 0 | **114** | 0 | 0 | **634** |
| 4:30:00 PM | 12 | 187 | 19 | 1 | **219** | 0 | 0 | 23 | 73 | 7 | 0 | **103** | 0 | 0 | 8 | 163 | 37 | 1 | **209** | 0 | 0 | 37 | 67 | 0 | 0 | **104** | 0 | 0 | **635** |
| 4:45:00 PM | 8 | 199 | 22 | 1 | **230** | 0 | 0 | 10 | 76 | 16 | 0 | **102** | 0 | 1 | 8 | 198 | 43 | 1 | **250** | 0 | 0 | 49 | 54 | 0 | 0 | **103** | 2 | 0 | **685** |
| **Hourly Total** | 35 | 699 | 80 | 3 | **817** | 0 | 0 | 87 | 330 | 53 | 0 | **470** | 0 | 1 | 42 | 677 | 161 | 2 | **882** | 0 | 0 | 181 | 243 | 0 | 0 | **424** | 2 | 1 | **2593** |
| 5:00:00 PM | 6 | 206 | 24 | 0 | **236** | 0 | 0 | 18 | 67 | 9 | 0 | **94** | 0 | 0 | 13 | 182 | 41 | 0 | **236** | 0 | 1 | 42 | 62 | 1 | 0 | **105** | 0 | 0 | **671** |
| 5:15:00 PM | 6 | 203 | 25 | 1 | **235** | 1 | 1 | 20 | 82 | 14 | 0 | **116** | 0 | 0 | 12 | 156 | 32 | 0 | **200** | 1 | 0 | 41 | 59 | 0 | 0 | **100** | 0 | 1 | **651** |
| 5:30:00 PM | 12 | 209 | 20 | 2 | **243** | 0 | 1 | 25 | 81 | 12 | 0 | **118** | 1 | 0 | 9 | 178 | 38 | 0 | **225** | 0 | 0 | 41 | 52 | 1 | 0 | **94** | 1 | 0 | **680** |
| 5:45:00 PM | 11 | 168 | 17 | 1 | **197** | 0 | 0 | 18 | 59 | 11 | 0 | **88** | 0 | 0 | 12 | 180 | 48 | 1 | **241** | 0 | 1 | 40 | 49 | 0 | 0 | **89** | 0 | 0 | **615** |
| **Hourly Total** | 35 | 786 | 86 | 4 | **911** | 1 | 2 | 81 | 289 | 46 | 0 | **416** | 1 | 0 | 46 | 696 | 159 | 1 | **902** | 1 | 2 | 164 | 222 | 2 | 0 | **388** | 1 | 1 | **2617** |
| **Grand Total** | 102 | 2073 | 248 | 9 | **2432** | 2 | 4 | 256 | 913 | 150 | 0 | **1319** | 1 | 2 | 135 | 2040 | 443 | 4 | **2622** | 2 | 3 | 484 | 714 | 3 | 0 | **1201** | 3 | 2 | **7574** |
| **% Approach** | 4.2% | 85.2% | 10.2% | 0.4% | **0.0%** | 0.0% | 0.0% | 19.4% | 69.2% | 11.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.1% | 77.8% | 16.9% | 0.2% | **0.0%** | 0.0% | 0.0% | 40.3% | 59.5% | 0.2% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.3% | 27.4% | 3.3% | 0.1% | **32.1%** | 0.0% | 0.0% | 3.4% | 12.1% | 2.0% | 0.0% | **17.4%** | 0.0% | 0.0% | 1.8% | 26.9% | 5.8% | 0.1% | **34.6%** | 0.0% | 0.0% | 6.4% | 9.4% | 0.0% | 0.0% | **15.9%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 101 | 2048 | 244 | 9 | **2402** | 0 | 0 | 237 | 898 | 147 | 0 | **1282** | 0 | 0 | 122 | 2006 | 432 | 4 | **2564** | 0 | 0 | 350 | 705 | 3 | 0 | **1058** | 0 | 0 | **7306** |
| **% Lights** | 99.0% | 98.8% | 98.4% | 100.0% | **98.8%** | 0.0% | 0.0% | 92.6% | 98.4% | 98.0% | 0.0% | **97.2%** | 0.0% | 0.0% | 90.4% | 98.3% | 97.5% | 100.0% | **97.8%** | 0.0% | 0.0% | 72.3% | 98.7% | 100.0% | 0.0% | **88.1%** | 0.0% | 0.0% | **96.5%** |
| **Trucks** | 0 | 11 | 4 | 0 | **15** | 0 | 0 | 2 | 6 | 2 | 0 | **10** | 0 | 0 | 0 | 15 | 2 | 0 | **17** | 0 | 0 | 3 | 4 | 0 | 0 | **7** | 0 | 0 | **49** |
| **% Trucks** | 0.0% | 0.5% | 1.6% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.8% | 0.7% | 1.3% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.7% | 0.5% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.6% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 11 | 0 | 0 | **11** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 1 | 13 | 8 | 0 | **22** | 0 | 0 | 3 | 4 | 0 | 0 | **7** | 0 | 0 | **48** |
| **% Buses** | 0.0% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.9% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.7% | 0.6% | 1.8% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.6% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.6%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:45:00 PM | 8 | 199 | 22 | 1 | **230** | 0 | 0 | 10 | 76 | 16 | 0 | **102** | 0 | 1 | 8 | 198 | 43 | 1 | **250** | 0 | 0 | 49 | 54 | 0 | 0 | **103** | 2 | 0 | **685** |
| 5:00:00 PM | 6 | 206 | 24 | 0 | **236** | 0 | 0 | 18 | 67 | 9 | 0 | **94** | 0 | 0 | 13 | 182 | 41 | 0 | **236** | 0 | 1 | 42 | 62 | 1 | 0 | **105** | 0 | 0 | **671** |
| 5:15:00 PM | 6 | 203 | 25 | 1 | **235** | 1 | 1 | 20 | 82 | 14 | 0 | **116** | 0 | 0 | 12 | 156 | 32 | 0 | **200** | 1 | 0 | 41 | 59 | 0 | 0 | **100** | 0 | 1 | **651** |
| 5:30:00 PM | 12 | 209 | 20 | 2 | **243** | 0 | 1 | 25 | 81 | 12 | 0 | **118** | 1 | 0 | 9 | 178 | 38 | 0 | **225** | 0 | 0 | 41 | 52 | 1 | 0 | **94** | 1 | 0 | **680** |
| **Grand Total** | 32 | 817 | 91 | 4 | **944** | 1 | 2 | 73 | 306 | 51 | 0 | **430** | 1 | 1 | 42 | 714 | 154 | 1 | **911** | 1 | 1 | 173 | 227 | 2 | 0 | **402** | 3 | 1 | **2687** |
| **% Approach** | 3.4% | 86.5% | 9.6% | 0.4% | **0.0%** | 0.0% | 0.0% | 17.0% | 71.2% | 11.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.6% | 78.4% | 16.9% | 0.1% | **0.0%** | 0.0% | 0.0% | 43.0% | 56.5% | 0.5% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.2% | 30.4% | 3.4% | 0.1% | **35.1%** | 0.0% | 0.0% | 2.7% | 11.4% | 1.9% | 0.0% | **16.0%** | 0.0% | 0.0% | 1.6% | 26.6% | 5.7% | 0.0% | **33.9%** | 0.0% | 0.0% | 6.4% | 8.4% | 0.1% | 0.0% | **15.0%** | 0.0% | 0.0% | |
| **PHF** | 0.667 | 0.977 | 0.910 | 0.500 | **0.971** | 0.000 | 0.000 | 0.730 | 0.933 | 0.797 | 0.000 | **0.911** | 0.000 | 0.000 | 0.808 | 0.902 | 0.895 | 0.250 | **0.911** | 0.000 | 0.000 | 0.883 | 0.915 | 0.500 | 0.000 | **0.957** | 0.000 | 0.000 | **0.981** |
| **Lights** | 32 | 810 | 91 | 4 | **937** | 0 | 0 | 67 | 301 | 50 | 0 | **418** | 0 | 0 | 35 | 707 | 154 | 1 | **897** | 0 | 0 | 119 | 226 | 2 | 0 | **347** | 0 | 0 | **2599** |
| **% Lights** | 100.0% | 99.1% | 100.0% | 100.0% | **99.3%** | 0.0% | 0.0% | 91.8% | 98.4% | 98.0% | 0.0% | **97.2%** | 0.0% | 0.0% | 83.3% | 99.0% | 100.0% | 100.0% | **98.5%** | 0.0% | 0.0% | 68.8% | 99.6% | 100.0% | 0.0% | **86.3%** | 0.0% | 0.0% | **96.7%** |
| **Trucks** | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 2 | 1 | 0 | 0 | **3** | 0 | 0 | **12** |
| **% Trucks** | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.7% | 2.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 1.2% | 0.4% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 1 | 4 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **9** |
| **% Buses** | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.7% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 2.4% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 3 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Niagara Falls Boulevard & E |
| **Legs and Movements** | All Processed Legs & Move |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Niagara Falls Boulevard & E |
| **Latitude and Longitude** | 42.97965,-78.82296 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 14:00:00 | 2023-11-18 15:00:00 | 0.933 |


## Turning Movement Data


| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 8 | 151 | 18 | 0 | **177** | 0 | 0 | 22 | 57 | 13 | 0 | **92** | 6 | 0 | 15 | 180 | 23 | 0 | **218** | 6 | 0 | 47 | 40 | 0 | 0 | **87** | 0 | 1 | **574** |
| 12:15:00 | 11 | 146 | 25 | 0 | **182** | 1 | 0 | 15 | 58 | 11 | 0 | **84** | 0 | 2 | 8 | 148 | 29 | 0 | **185** | 0 | 0 | 39 | 55 | 1 | 0 | **95** | 0 | 1 | **546** |
| 12:30:00 | 7 | 121 | 21 | 0 | **149** | 0 | 0 | 16 | 59 | 15 | 0 | **90** | 0 | 1 | 16 | 172 | 31 | 3 | **222** | 0 | 0 | 27 | 64 | 0 | 0 | **91** | 0 | 0 | **552** |
| 12:45:00 | 6 | 177 | 14 | 1 | **198** | 0 | 0 | 18 | 44 | 15 | 0 | **77** | 0 | 1 | 16 | 174 | 35 | 2 | **227** | 0 | 0 | 22 | 45 | 0 | 0 | **67** | 0 | 0 | **569** |
| **Hourly Total** | 32 | 595 | 78 | 1 | **706** | 1 | 0 | 71 | 218 | 54 | 0 | **343** | 8 | 4 | 55 | 674 | 118 | 5 | **852** | 6 | 0 | 135 | 204 | 1 | 0 | **340** | 0 | 2 | **2241** |
| 13:00:00 | 8 | 156 | 13 | 0 | **177** | 0 | 0 | 13 | 46 | 9 | 0 | **68** | 0 | 0 | 18 | 162 | 17 | 0 | **197** | 0 | 0 | 38 | 54 | 0 | 0 | **92** | 0 | 0 | **534** |
| 13:15:00 | 7 | 150 | 23 | 0 | **180** | 0 | 0 | 18 | 43 | 20 | 0 | **81** | 0 | 0 | 9 | 162 | 38 | 0 | **209** | 0 | 0 | 32 | 51 | 0 | 0 | **83** | 0 | 0 | **553** |
| 13:30:00 | 11 | 154 | 17 | 0 | **182** | 0 | 1 | 23 | 51 | 16 | 0 | **90** | 2 | 1 | 11 | 156 | 21 | 1 | **189** | 0 | 1 | 32 | 52 | 0 | 0 | **84** | 0 | 0 | **545** |
| 13:45:00 | 7 | 175 | 16 | 0 | **198** | 0 | 0 | 14 | 37 | 10 | 0 | **61** | 0 | 0 | 12 | 177 | 24 | 0 | **213** | 0 | 0 | 30 | 40 | 0 | 0 | **70** | 1 | 0 | **542** |
| **Hourly Total** | 33 | 635 | 69 | 0 | **737** | 0 | 1 | 68 | 177 | 55 | 0 | **300** | 2 | 1 | 50 | 657 | 100 | 1 | **808** | 0 | 1 | 132 | 197 | 0 | 0 | **329** | 1 | 0 | **2174** |
| 14:00:00 | 7 | 178 | 22 | 0 | **207** | 0 | 0 | 16 | 37 | 8 | 0 | **61** | 0 | 0 | 12 | 209 | 33 | 0 | **254** | 0 | 0 | 38 | 56 | 0 | 0 | **94** | 0 | 0 | **616** |
| 14:15:00 | 14 | 132 | 18 | 0 | **164** | 0 | 0 | 22 | 53 | 14 | 0 | **89** | 0 | 0 | 21 | 152 | 23 | 1 | **197** | 3 | 0 | 34 | 43 | 0 | 0 | **77** | 0 | 0 | **527** |
| 14:30:00 | 7 | 204 | 17 | 0 | **228** | 0 | 0 | 22 | 35 | 6 | 0 | **63** | 1 | 0 | 13 | 180 | 22 | 0 | **215** | 0 | 0 | 35 | 42 | 0 | 0 | **77** | 0 | 1 | **583** |
| 14:45:00 | 7 | 164 | 21 | 3 | **195** | 0 | 0 | 21 | 43 | 12 | 0 | **76** | 0 | 1 | 13 | 186 | 25 | 0 | **224** | 0 | 0 | 31 | 48 | 0 | 0 | **79** | 0 | 1 | **574** |
| **Hourly Total** | 35 | 678 | 78 | 3 | **794** | 0 | 0 | 81 | 168 | 40 | 0 | **289** | 1 | 1 | 59 | 727 | 103 | 1 | **890** | 3 | 0 | 138 | 189 | 0 | 0 | **327** | 0 | 2 | **2300** |
| **Grand Total** | 100 | 1908 | 225 | 4 | **2237** | 1 | 1 | 220 | 563 | 149 | 0 | **932** | 11 | 6 | 164 | 2058 | 321 | 7 | **2550** | 9 | 1 | 405 | 590 | 1 | 0 | **996** | 1 | 4 | **6715** |
| **% Approach** | 4.5% | 85.3% | 10.1% | 0.2% | **0.0%** | 0.0% | 0.0% | 23.6% | 60.4% | 16.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 80.7% | 12.6% | 0.3% | **0.0%** | 0.0% | 0.0% | 40.7% | 59.2% | 0.1% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.5% | 28.4% | 3.4% | 0.1% | **33.3%** | 0.0% | 0.0% | 3.3% | 8.4% | 2.2% | 0.0% | **13.9%** | 0.0% | 0.0% | 2.4% | 30.6% | 4.8% | 0.1% | **38.0%** | 0.0% | 0.0% | 6.0% | 8.8% | 0.0% | 0.0% | **14.8%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 98 | 1893 | 220 | 4 | **2215** | 0 | 0 | 209 | 561 | 149 | 0 | **919** | 0 | 0 | 142 | 2048 | 318 | 7 | **2515** | 0 | 0 | 269 | 587 | 1 | 0 | **857** | 0 | 0 | **6506** |
| **% Lights** | 98.0% | 99.2% | 97.8% | 100.0% | **99.0%** | 0.0% | 0.0% | 95.0% | 99.6% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 86.6% | 99.5% | 99.1% | 100.0% | **98.6%** | 0.0% | 0.0% | 66.4% | 99.5% | 100.0% | 0.0% | **86.0%** | 0.0% | 0.0% | **96.9%** |
| **Trucks** | 0 | 6 | 5 | 0 | **11** | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 1 | 5 | 3 | 0 | **9** | 0 | 0 | 4 | 3 | 0 | 0 | **7** | 0 | 0 | **29** |
| **% Trucks** | 0.0% | 0.3% | 2.2% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.5% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.6% | 0.2% | 0.9% | 0.0% | **0.4%** | 0.0% | 0.0% | 1.0% | 0.5% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **10** |
| **% Buses** | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 9 | 3 | 0 | 0 | 0 | 0 | **0** | 8 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 81.8% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 88.9% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 75.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 18.2% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 11.1% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 25.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com

**Summary**

## Turning Movement Peak Hour Data (PM)

**14:00:00**

| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 14:00:00 | 7 | 178 | 22 | 0 | **207** | 0 | 0 | 16 | 37 | 8 | 0 | **61** | 0 | 0 | 12 | 209 | 33 | 0 | **254** | 0 | 0 | 38 | 56 | 0 | 0 | **94** | 0 | 0 | **616** |
| 14:15:00 | 14 | 132 | 18 | 0 | **164** | 0 | 0 | 22 | 53 | 14 | 0 | **89** | 0 | 0 | 21 | 152 | 23 | 1 | **197** | 3 | 0 | 34 | 43 | 0 | 0 | **77** | 0 | 0 | **527** |
| 14:30:00 | 7 | 204 | 17 | 0 | **228** | 0 | 0 | 22 | 35 | 6 | 0 | **63** | 1 | 0 | 13 | 180 | 22 | 0 | **215** | 0 | 0 | 35 | 42 | 0 | 0 | **77** | 0 | 1 | **583** |
| 14:45:00 | 7 | 164 | 21 | 3 | **195** | 0 | 0 | 21 | 43 | 12 | 0 | **76** | 0 | 1 | 13 | 186 | 25 | 0 | **224** | 0 | 0 | 31 | 48 | 0 | 0 | **79** | 0 | 1 | **574** |
| **Grand Total** | 35 | 678 | 78 | 3 | **794** | 0 | 0 | 81 | 168 | 40 | 0 | **289** | 1 | 1 | 59 | 727 | 103 | 1 | **890** | 3 | 0 | 138 | 189 | 0 | 0 | **327** | 0 | 2 | **2300** |
| **% Approach** | 4.4% | 85.4% | 9.8% | 0.4% | **0.0%** | 0.0% | 0.0% | 28.0% | 58.1% | 13.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.6% | 81.7% | 11.6% | 0.1% | **0.0%** | 0.0% | 0.0% | 42.2% | 57.8% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.5% | 29.5% | 3.4% | 0.1% | **34.5%** | 0.0% | 0.0% | 3.5% | 7.3% | 1.7% | 0.0% | **12.6%** | 0.0% | 0.0% | 2.6% | 31.6% | 4.5% | 0.0% | **38.7%** | 0.0% | 0.0% | 6.0% | 8.2% | 0.0% | 0.0% | **14.2%** | 0.0% | 0.0% | |
| **PHF** | 0.625 | 0.831 | 0.886 | 0.250 | **0.871** | 0.000 | 0.000 | 0.920 | 0.792 | 0.714 | 0.000 | **0.812** | 0.000 | 0.000 | 0.702 | 0.870 | 0.780 | 0.250 | **0.876** | 0.000 | 0.000 | 0.908 | 0.844 | 0.000 | 0.000 | **0.870** | 0.000 | 0.000 | **0.933** |
| **Lights** | 34 | 671 | 77 | 3 | **785** | 0 | 0 | 76 | 166 | 40 | 0 | **282** | 0 | 0 | 49 | 724 | 102 | 1 | **876** | 0 | 0 | 94 | 189 | 0 | 0 | **283** | 0 | 0 | **2226** |
| **% Lights** | 97.1% | 99.0% | 98.7% | 100.0% | **98.9%** | 0.0% | 0.0% | 93.8% | 98.8% | 100.0% | 0.0% | **97.6%** | 0.0% | 0.0% | 83.1% | 99.6% | 99.0% | 100.0% | **98.4%** | 0.0% | 0.0% | 68.1% | 100.0% | 0.0% | 0.0% | **86.5%** | 0.0% | 0.0% | **96.8%** |
| **Trucks** | 0 | 4 | 1 | 0 | **5** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.6% | 1.3% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.3% | 1.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.7% | 0.0% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **3** |
| **% Buses** | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |








## Turning Movement Data

| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 8 | 151 | 18 | 0 | **177** | 0 | 0 | 22 | 57 | 13 | 0 | **92** | 8 | 0 | 15 | 180 | 23 | 0 | **218** | 6 | 0 | 47 | 40 | 0 | 0 | **87** | 0 | 1 | **574** |
| 12:15:00 | 11 | 146 | 25 | 0 | **182** | 1 | 0 | 15 | 58 | 11 | 0 | **84** | 0 | 2 | 8 | 148 | 29 | 0 | **185** | 0 | 0 | 39 | 55 | 1 | 0 | **95** | 0 | 1 | **546** |
| 12:30:00 | 7 | 121 | 21 | 0 | **149** | 0 | 0 | 16 | 59 | 15 | 0 | **90** | 0 | 1 | 16 | 172 | 31 | 3 | **222** | 0 | 0 | 27 | 64 | 0 | 0 | **91** | 0 | 0 | **552** |
| 12:45:00 | 6 | 177 | 14 | 1 | **198** | 0 | 0 | 18 | 44 | 15 | 0 | **77** | 0 | 1 | 16 | 174 | 35 | 2 | **227** | 0 | 0 | 22 | 45 | 0 | 0 | **67** | 0 | 0 | **569** |
| **Hourly Total** | 32 | 595 | 78 | 1 | **706** | 1 | 0 | 71 | 218 | 54 | 0 | **343** | 8 | 4 | 55 | 674 | 118 | 5 | **852** | 6 | 0 | 135 | 204 | 1 | 0 | **340** | 0 | 2 | **2241** |
| 13:00:00 | 8 | 156 | 13 | 0 | **177** | 0 | 0 | 13 | 46 | 9 | 0 | **68** | 0 | 0 | 18 | 162 | 17 | 0 | **197** | 0 | 0 | 38 | 54 | 0 | 0 | **92** | 0 | 0 | **534** |
| 13:15:00 | 7 | 150 | 23 | 0 | **180** | 0 | 0 | 18 | 43 | 20 | 0 | **81** | 0 | 0 | 9 | 162 | 38 | 0 | **209** | 0 | 0 | 32 | 51 | 0 | 0 | **83** | 0 | 0 | **553** |
| 13:30:00 | 11 | 154 | 17 | 0 | **182** | 0 | 1 | 23 | 51 | 16 | 0 | **90** | 2 | 1 | 11 | 156 | 21 | 1 | **189** | 0 | 1 | 32 | 52 | 0 | 0 | **84** | 0 | 0 | **545** |
| 13:45:00 | 7 | 175 | 16 | 0 | **198** | 0 | 0 | 14 | 37 | 10 | 0 | **61** | 0 | 0 | 12 | 177 | 24 | 0 | **213** | 0 | 0 | 30 | 40 | 0 | 0 | **70** | 1 | 0 | **542** |
| **Hourly Total** | 33 | 635 | 69 | 0 | **737** | 0 | 1 | 68 | 177 | 55 | 0 | **300** | 2 | 1 | 50 | 657 | 100 | 1 | **808** | 0 | 1 | 132 | 197 | 0 | 0 | **329** | 1 | 0 | **2174** |
| 14:00:00 | 7 | 178 | 22 | 0 | **207** | 0 | 0 | 16 | 37 | 8 | 0 | **61** | 0 | 0 | 12 | 209 | 33 | 0 | **254** | 0 | 0 | 38 | 56 | 0 | 0 | **94** | 0 | 0 | **616** |
| 14:15:00 | 14 | 132 | 18 | 0 | **164** | 0 | 0 | 22 | 53 | 14 | 0 | **89** | 0 | 0 | 21 | 152 | 23 | 1 | **197** | 3 | 0 | 34 | 43 | 0 | 0 | **77** | 0 | 0 | **527** |
| 14:30:00 | 7 | 204 | 17 | 0 | **228** | 0 | 0 | 22 | 35 | 6 | 0 | **63** | 1 | 0 | 13 | 180 | 22 | 0 | **215** | 0 | 0 | 35 | 42 | 0 | 0 | **77** | 0 | 1 | **583** |
| 14:45:00 | 7 | 164 | 21 | 3 | **195** | 0 | 0 | 21 | 43 | 12 | 0 | **76** | 0 | 1 | 13 | 186 | 25 | 0 | **224** | 0 | 0 | 31 | 48 | 0 | 0 | **79** | 0 | 1 | **574** |
| **Hourly Total** | 35 | 678 | 78 | 3 | **794** | 0 | 0 | 81 | 168 | 40 | 0 | **289** | 1 | 1 | 59 | 727 | 103 | 1 | **890** | 3 | 0 | 138 | 189 | 0 | 0 | **327** | 0 | 2 | **2300** |
| **Grand Total** | 100 | 1908 | 225 | 4 | **2237** | 1 | 1 | 220 | 563 | 149 | 0 | **932** | 11 | 6 | 164 | 2058 | 321 | 7 | **2550** | 9 | 1 | 405 | 590 | 1 | 0 | **996** | 1 | 4 | **6715** |
| **% Approach** | 4.5% | 85.3% | 10.1% | 0.2% | **0.0%** | 0.0% | 0.0% | 23.6% | 60.4% | 16.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 80.7% | 12.6% | 0.3% | **0.0%** | 0.0% | 0.0% | 40.7% | 59.2% | 0.1% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.5% | 28.4% | 3.4% | 0.1% | **33.3%** | 0.0% | 0.0% | 3.3% | 8.4% | 2.2% | 0.0% | **13.9%** | 0.0% | 0.0% | 2.4% | 30.6% | 4.8% | 0.1% | **38.0%** | 0.0% | 0.0% | 6.0% | 8.8% | 0.0% | 0.0% | **14.8%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 98 | 1893 | 220 | 4 | **2215** | 0 | 0 | 209 | 561 | 149 | 0 | **919** | 0 | 0 | 142 | 2048 | 318 | 7 | **2515** | 0 | 0 | 269 | 587 | 1 | 0 | **857** | 0 | 0 | **6506** |
| **% Lights** | 98.0% | 99.2% | 97.8% | 100.0% | **99.0%** | 0.0% | 0.0% | 95.0% | 99.6% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 86.6% | 99.5% | 99.1% | 100.0% | **98.6%** | 0.0% | 0.0% | 66.4% | 99.5% | 100.0% | 0.0% | **86.0%** | 0.0% | 0.0% | **96.9%** |
| **Trucks** | 0 | 6 | 5 | 0 | **11** | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 1 | 5 | 3 | 0 | **9** | 0 | 0 | 4 | 3 | 0 | 0 | **7** | 0 | 0 | **29** |
| **% Trucks** | 0.0% | 0.3% | 2.2% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.5% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.6% | 0.2% | 0.9% | 0.0% | **0.4%** | 0.0% | 0.0% | 1.0% | 0.5% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **10** |
| **% Buses** | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 9 | 3 | 0 | 0 | 0 | 0 | **0** | 8 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 81.8% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 88.9% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 75.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 18.2% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 11.1% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 25.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**14:00:00**

| Leg | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | Niagara Falls Boulevard | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 14:00:00 | 7 | 178 | 22 | 0 | **207** | 0 | 0 | 16 | 37 | 8 | 0 | **61** | 0 | 0 | 12 | 209 | 33 | 0 | **254** | 0 | 0 | 38 | 56 | 0 | 0 | **94** | 0 | 0 | **616** |
| 14:15:00 | 14 | 132 | 18 | 0 | **164** | 0 | 0 | 22 | 53 | 14 | 0 | **89** | 0 | 0 | 21 | 152 | 23 | 1 | **197** | 3 | 0 | 34 | 43 | 0 | 0 | **77** | 0 | 0 | **527** |
| 14:30:00 | 7 | 204 | 17 | 0 | **228** | 0 | 0 | 22 | 35 | 6 | 0 | **63** | 1 | 0 | 13 | 180 | 22 | 0 | **215** | 0 | 0 | 35 | 42 | 0 | 0 | **77** | 0 | 1 | **583** |
| 14:45:00 | 7 | 164 | 21 | 3 | **195** | 0 | 0 | 21 | 43 | 12 | 0 | **76** | 0 | 1 | 13 | 186 | 25 | 0 | **224** | 0 | 0 | 31 | 48 | 0 | 0 | **79** | 0 | 1 | **574** |
| **Grand Total** | 35 | 678 | 78 | 3 | **794** | 0 | 0 | 81 | 168 | 40 | 0 | **289** | 1 | 1 | 59 | 727 | 103 | 1 | **890** | 3 | 0 | 138 | 189 | 0 | 0 | **327** | 0 | 2 | **2300** |
| **% Approach** | 4.4% | 85.4% | 9.8% | 0.4% | **0.0%** | 0.0% | 0.0% | 28.0% | 58.1% | 13.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.6% | 81.7% | 11.6% | 0.1% | **0.0%** | 0.0% | 0.0% | 42.2% | 57.8% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.5% | 29.5% | 3.4% | 0.1% | **34.5%** | 0.0% | 0.0% | 3.5% | 7.3% | 1.7% | 0.0% | **12.6%** | 0.0% | 0.0% | 2.6% | 31.6% | 4.5% | 0.0% | **38.7%** | 0.0% | 0.0% | 6.0% | 8.2% | 0.0% | 0.0% | **14.2%** | 0.0% | 0.0% | |
| **PHF** | 0.625 | 0.831 | 0.886 | 0.250 | **0.871** | 0.000 | 0.000 | 0.920 | 0.792 | 0.714 | 0.000 | **0.812** | 0.000 | 0.000 | 0.702 | 0.870 | 0.780 | 0.250 | **0.876** | 0.000 | 0.000 | 0.908 | 0.844 | 0.000 | 0.000 | **0.870** | 0.000 | 0.000 | **0.933** |
| **Lights** | 34 | 671 | 77 | 3 | **785** | 0 | 0 | 76 | 166 | 40 | 0 | **282** | 0 | 0 | 49 | 724 | 102 | 1 | **876** | 0 | 0 | 94 | 189 | 0 | 0 | **283** | 0 | 0 | **2226** |
| **% Lights** | 97.1% | 99.0% | 98.7% | 100.0% | **98.9%** | 0.0% | 0.0% | 93.8% | 98.8% | 100.0% | 0.0% | **97.6%** | 0.0% | 0.0% | 83.1% | 99.6% | 99.0% | 100.0% | **98.4%** | 0.0% | 0.0% | 68.1% | 100.0% | 0.0% | 0.0% | **86.5%** | 0.0% | 0.0% | **96.8%** |
| **Trucks** | 0 | 4 | 1 | 0 | **5** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.6% | 1.3% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.3% | 1.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.7% | 0.0% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **3** |
| **% Buses** | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TRI-STATE TRAFFIC DATA

TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Eggert Ro |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Sheridan Drive & Eggert Ro |
| **Latitude and Longitude** | 42.98074,-78.82546 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:15:00 | 2023-11-16 17:15:00 | 0.968 |


## Turning Movement Data


| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 13 | 40 | 36 | 0 | **89** | 0 | 1 | 35 | 200 | 0 | 0 | **235** | 1 | 1 | 2 | 44 | 47 | 0 | **93** | 0 | 0 | 34 | 183 | 11 | 2 | **230** | 0 | 0 | **647** |
| 3:15:00 PM | 13 | 53 | 32 | 0 | **98** | 0 | 1 | 22 | 188 | 0 | 0 | **210** | 1 | 0 | 3 | 44 | 31 | 0 | **78** | 1 | 0 | 43 | 187 | 23 | 0 | **253** | 0 | 0 | **639** |
| 3:30:00 PM | 15 | 49 | 22 | 0 | **86** | 0 | 0 | 26 | 198 | 0 | 0 | **224** | 0 | 0 | 2 | 57 | 38 | 0 | **97** | 0 | 1 | 46 | 205 | 11 | 1 | **263** | 1 | 0 | **670** |
| 3:45:00 PM | 6 | 60 | 20 | 0 | **86** | 0 | 0 | 33 | 182 | 0 | 0 | **215** | 0 | 0 | 3 | 72 | 47 | 0 | **122** | 0 | 1 | 44 | 208 | 7 | 0 | **259** | 0 | 0 | **682** |
| **Hourly Total** | 47 | 202 | 110 | 0 | **359** | 0 | 2 | 116 | 768 | 0 | 0 | **884** | 2 | 1 | 10 | 217 | 163 | 0 | **390** | 1 | 2 | 167 | 783 | 52 | 3 | **1005** | 1 | 0 | **2638** |
| 4:00:00 PM | 10 | 47 | 31 | 0 | **88** | 0 | 0 | 30 | 225 | 0 | 0 | **255** | 1 | 0 | 2 | 55 | 44 | 0 | **101** | 0 | 0 | 47 | 201 | 13 | 0 | **261** | 0 | 0 | **705** |
| 4:15:00 PM | 9 | 42 | 26 | 0 | **77** | 0 | 0 | 27 | 224 | 0 | 0 | **251** | 0 | 1 | 0 | 75 | 58 | 0 | **133** | 0 | 1 | 55 | 223 | 6 | 0 | **284** | 0 | 0 | **745** |
| 4:30:00 PM | 8 | 54 | 26 | 0 | **88** | 0 | 0 | 33 | 248 | 0 | 0 | **281** | 0 | 0 | 1 | 61 | 40 | 0 | **102** | 0 | 0 | 47 | 217 | 7 | 0 | **271** | 0 | 0 | **742** |
| 4:45:00 PM | 7 | 55 | 18 | 0 | **80** | 0 | 0 | 21 | 241 | 0 | 0 | **262** | 0 | 0 | 2 | 61 | 56 | 0 | **119** | 0 | 0 | 49 | 174 | 11 | 0 | **234** | 0 | 0 | **695** |
| **Hourly Total** | 34 | 198 | 101 | 0 | **333** | 0 | 0 | 111 | 938 | 0 | 0 | **1049** | 1 | 1 | 5 | 252 | 198 | 0 | **455** | 0 | 1 | 198 | 815 | 37 | 0 | **1050** | 0 | 0 | **2887** |
| 5:00:00 PM | 15 | 44 | 30 | 0 | **89** | 0 | 0 | 36 | 267 | 0 | 0 | **303** | 0 | 0 | 2 | 53 | 35 | 0 | **90** | 0 | 0 | 44 | 222 | 12 | 0 | **278** | 0 | 0 | **760** |
| 5:15:00 PM | 7 | 53 | 34 | 0 | **94** | 1 | 0 | 26 | 214 | 0 | 0 | **240** | 0 | 0 | 1 | 65 | 56 | 0 | **122** | 0 | 0 | 41 | 207 | 10 | 0 | **258** | 0 | 0 | **714** |
| 5:30:00 PM | 10 | 40 | 33 | 0 | **83** | 0 | 0 | 37 | 240 | 0 | 0 | **277** | 0 | 0 | 2 | 58 | 49 | 0 | **109** | 0 | 0 | 46 | 164 | 19 | 3 | **232** | 0 | 0 | **701** |
| 5:45:00 PM | 3 | 39 | 28 | 0 | **70** | 0 | 0 | 22 | 207 | 0 | 0 | **229** | 0 | 0 | 3 | 57 | 47 | 0 | **107** | 0 | 0 | 41 | 146 | 13 | 2 | **202** | 0 | 0 | **608** |
| **Hourly Total** | 35 | 176 | 125 | 0 | **336** | 1 | 0 | 121 | 928 | 0 | 0 | **1049** | 0 | 0 | 8 | 233 | 187 | 0 | **428** | 0 | 0 | 172 | 739 | 54 | 5 | **970** | 0 | 0 | **2783** |
| **Grand Total** | 116 | 576 | 336 | 0 | **1028** | 1 | 2 | 348 | 2634 | 0 | 0 | **2982** | 3 | 2 | 23 | 702 | 548 | 0 | **1273** | 1 | 3 | 537 | 2337 | 143 | 8 | **3025** | 1 | 0 | **8308** |
| **% Approach** | 11.3% | 56.0% | 32.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 11.7% | 88.3% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.8% | 55.1% | 43.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 17.8% | 77.3% | 4.7% | 0.3% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.4% | 6.9% | 4.0% | 0.0% | **12.4%** | 0.0% | 0.0% | 4.2% | 31.7% | 0.0% | 0.0% | **35.9%** | 0.0% | 0.0% | 0.3% | 8.4% | 6.6% | 0.0% | **15.3%** | 0.0% | 0.0% | 6.5% | 28.1% | 1.7% | 0.1% | **36.4%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 61 | 564 | 332 | 0 | **957** | 0 | 0 | 334 | 2609 | 0 | 0 | **2943** | 0 | 0 | 15 | 682 | 541 | 0 | **1238** | 0 | 0 | 510 | 2313 | 141 | 8 | **2972** | 0 | 0 | **8110** |
| **% Lights** | 52.6% | 97.9% | 98.8% | 0.0% | **93.1%** | 0.0% | 0.0% | 96.0% | 99.1% | 0.0% | 0.0% | **98.7%** | 0.0% | 0.0% | 65.2% | 97.2% | 98.7% | 0.0% | **97.3%** | 0.0% | 0.0% | 95.0% | 99.0% | 98.6% | 100.0% | **98.2%** | 0.0% | 0.0% | **97.6%** |
| **Trucks** | 0 | 5 | 4 | 0 | **9** | 0 | 0 | 0 | 16 | 0 | 0 | **16** | 0 | 0 | 0 | 3 | 5 | 0 | **8** | 0 | 0 | 2 | 15 | 1 | 0 | **18** | 0 | 0 | **51** |
| **% Trucks** | 0.0% | 0.9% | 1.2% | 0.0% | **0.9%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.9% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.4% | 0.6% | 0.7% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 1 | 6 | 0 | 0 | **7** | 0 | 0 | 0 | 16 | 1 | 0 | **17** | 0 | 0 | 4 | 5 | 0 | 0 | **9** | 0 | 0 | **36** |
| **% Buses** | 0.0% | 0.5% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 2.3% | 0.2% | 0.0% | **1.3%** | 0.0% | 0.0% | 0.7% | 0.2% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.4%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**


## Turning Movement Peak Hour Data (PM)

**4:15:00 PM**

| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:15:00 PM | 9 | 42 | 26 | 0 | **77** | 0 | 0 | 27 | 224 | 0 | 0 | **251** | 0 | 1 | 0 | 75 | 58 | 0 | **133** | 0 | 1 | 55 | 223 | 6 | 0 | **284** | 0 | 0 | **745** |
| 4:30:00 PM | 8 | 54 | 26 | 0 | **88** | 0 | 0 | 33 | 248 | 0 | 0 | **281** | 0 | 0 | 1 | 61 | 40 | 0 | **102** | 0 | 0 | 47 | 217 | 7 | 0 | **271** | 0 | 0 | **742** |
| 4:45:00 PM | 7 | 55 | 18 | 0 | **80** | 0 | 0 | 21 | 241 | 0 | 0 | **262** | 0 | 0 | 2 | 61 | 56 | 0 | **119** | 0 | 0 | 49 | 174 | 11 | 0 | **234** | 0 | 0 | **695** |
| 5:00:00 PM | 15 | 44 | 30 | 0 | **89** | 0 | 0 | 36 | 267 | 0 | 0 | **303** | 0 | 0 | 2 | 53 | 35 | 0 | **90** | 0 | 0 | 44 | 222 | 12 | 0 | **278** | 0 | 0 | **760** |
| **Grand Total** | 39 | 195 | 100 | 0 | **334** | 0 | 0 | 117 | 980 | 0 | 0 | **1097** | 0 | 1 | 5 | 250 | 189 | 0 | **444** | 0 | 1 | 195 | 836 | 36 | 0 | **1067** | 0 | 0 | **2942** |
| **% Approach** | 11.7% | 58.4% | 29.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 10.7% | 89.3% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.1% | 56.3% | 42.6% | 0.0% | **0.0%** | 0.0% | 0.0% | 18.3% | 78.4% | 3.4% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.3% | 6.6% | 3.4% | 0.0% | **11.4%** | 0.0% | 0.0% | 4.0% | 33.3% | 0.0% | 0.0% | **37.3%** | 0.0% | 0.0% | 0.2% | 8.5% | 6.4% | 0.0% | **15.1%** | 0.0% | 0.0% | 6.6% | 28.4% | 1.2% | 0.0% | **36.3%** | 0.0% | 0.0% | |
| **PHF** | 0.650 | 0.886 | 0.833 | 0.000 | **0.938** | 0.000 | 0.000 | 0.813 | 0.918 | 0.000 | 0.000 | **0.905** | 0.000 | 0.000 | 0.625 | 0.833 | 0.815 | 0.000 | **0.835** | 0.000 | 0.000 | 0.886 | 0.937 | 0.750 | 0.000 | **0.939** | 0.000 | 0.000 | **0.968** |
| **Lights** | 23 | 189 | 98 | 0 | **310** | 0 | 0 | 111 | 975 | 0 | 0 | **1086** | 0 | 0 | 1 | 246 | 187 | 0 | **434** | 0 | 0 | 189 | 832 | 36 | 0 | **1057** | 0 | 0 | **2887** |
| **% Lights** | 59.0% | 96.9% | 98.0% | 0.0% | **92.8%** | 0.0% | 0.0% | 94.9% | 99.5% | 0.0% | 0.0% | **99.0%** | 0.0% | 0.0% | 20.0% | 98.4% | 98.9% | 0.0% | **97.7%** | 0.0% | 0.0% | 96.9% | 99.5% | 100.0% | 0.0% | **99.1%** | 0.0% | 0.0% | **98.1%** |
| **Trucks** | 0 | 4 | 2 | 0 | **6** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | **13** |
| **% Trucks** | 0.0% | 2.1% | 2.0% | 0.0% | **1.8%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.5% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **6** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.9% | 0.1% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 1.2% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 13 | 40 | 36 | 0 | **89** | 0 | 1 | 35 | 200 | 0 | 0 | **235** | 1 | 1 | 2 | 44 | 47 | 0 | **93** | 0 | 0 | 34 | 183 | 11 | 2 | **230** | 0 | 0 | **647** |
| 3:15:00 PM | 13 | 53 | 32 | 0 | **98** | 0 | 1 | 22 | 188 | 0 | 0 | **210** | 1 | 0 | 3 | 44 | 31 | 0 | **78** | 1 | 0 | 43 | 187 | 23 | 0 | **253** | 0 | 0 | **639** |
| 3:30:00 PM | 15 | 49 | 22 | 0 | **86** | 0 | 0 | 26 | 198 | 0 | 0 | **224** | 0 | 0 | 2 | 57 | 38 | 0 | **97** | 0 | 1 | 46 | 205 | 11 | 1 | **263** | 1 | 0 | **670** |
| 3:45:00 PM | 6 | 60 | 20 | 0 | **86** | 0 | 0 | 33 | 182 | 0 | 0 | **215** | 0 | 0 | 3 | 72 | 47 | 0 | **122** | 0 | 1 | 44 | 208 | 7 | 0 | **259** | 0 | 0 | **682** |
| **Hourly Total** | 47 | 202 | 110 | 0 | **359** | 0 | 2 | 116 | 768 | 0 | 0 | **884** | 2 | 1 | 10 | 217 | 163 | 0 | **390** | 1 | 2 | 167 | 783 | 52 | 3 | **1005** | 1 | 0 | **2638** |
| 4:00:00 PM | 10 | 47 | 31 | 0 | **88** | 0 | 0 | 30 | 225 | 0 | 0 | **255** | 1 | 0 | 2 | 55 | 44 | 0 | **101** | 0 | 0 | 47 | 201 | 13 | 0 | **261** | 0 | 0 | **705** |
| 4:15:00 PM | 9 | 42 | 26 | 0 | **77** | 0 | 0 | 27 | 224 | 0 | 0 | **251** | 0 | 1 | 0 | 75 | 58 | 0 | **133** | 0 | 1 | 55 | 223 | 6 | 0 | **284** | 0 | 0 | **745** |
| 4:30:00 PM | 8 | 54 | 26 | 0 | **88** | 0 | 0 | 33 | 248 | 0 | 0 | **281** | 0 | 0 | 1 | 61 | 40 | 0 | **102** | 0 | 0 | 47 | 217 | 7 | 0 | **271** | 0 | 0 | **742** |
| 4:45:00 PM | 7 | 55 | 18 | 0 | **80** | 0 | 0 | 21 | 241 | 0 | 0 | **262** | 0 | 0 | 2 | 61 | 56 | 0 | **119** | 0 | 0 | 49 | 174 | 11 | 0 | **234** | 0 | 0 | **695** |
| **Hourly Total** | 34 | 198 | 101 | 0 | **333** | 0 | 0 | 111 | 938 | 0 | 0 | **1049** | 1 | 1 | 5 | 252 | 198 | 0 | **455** | 0 | 1 | 198 | 815 | 37 | 0 | **1050** | 0 | 0 | **2887** |
| 5:00:00 PM | 15 | 44 | 30 | 0 | **89** | 0 | 0 | 36 | 267 | 0 | 0 | **303** | 0 | 0 | 2 | 53 | 35 | 0 | **90** | 0 | 0 | 44 | 222 | 12 | 0 | **278** | 0 | 0 | **760** |
| 5:15:00 PM | 7 | 53 | 34 | 0 | **94** | 1 | 0 | 26 | 214 | 0 | 0 | **240** | 0 | 0 | 1 | 65 | 56 | 0 | **122** | 0 | 0 | 41 | 207 | 10 | 0 | **258** | 0 | 0 | **714** |
| 5:30:00 PM | 10 | 40 | 33 | 0 | **83** | 0 | 0 | 37 | 240 | 0 | 0 | **277** | 0 | 0 | 2 | 58 | 49 | 0 | **109** | 0 | 0 | 46 | 164 | 19 | 3 | **232** | 0 | 0 | **701** |
| 5:45:00 PM | 3 | 39 | 28 | 0 | **70** | 0 | 0 | 22 | 207 | 0 | 0 | **229** | 0 | 0 | 3 | 57 | 47 | 0 | **107** | 0 | 0 | 41 | 146 | 13 | 2 | **202** | 0 | 0 | **608** |
| **Hourly Total** | 35 | 176 | 125 | 0 | **336** | 1 | 0 | 121 | 928 | 0 | 0 | **1049** | 0 | 0 | 8 | 233 | 187 | 0 | **428** | 0 | 0 | 172 | 739 | 54 | 5 | **970** | 0 | 0 | **2783** |
| **Grand Total** | 116 | 576 | 336 | 0 | **1028** | 1 | 2 | 348 | 2634 | 0 | 0 | **2982** | 3 | 2 | 23 | 702 | 548 | 0 | **1273** | 1 | 3 | 537 | 2337 | 143 | 8 | **3025** | 1 | 0 | **8308** |
| **% Approach** | 11.3% | 56.0% | 32.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 11.7% | 88.3% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.8% | 55.1% | 43.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 17.8% | 77.3% | 4.7% | 0.3% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.4% | 6.9% | 4.0% | 0.0% | **12.4%** | 0.0% | 0.0% | 4.2% | 31.7% | 0.0% | 0.0% | **35.9%** | 0.0% | 0.0% | 0.3% | 8.4% | 6.6% | 0.0% | **15.3%** | 0.0% | 0.0% | 6.5% | 28.1% | 1.7% | 0.1% | **36.4%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 61 | 564 | 332 | 0 | **957** | 0 | 0 | 334 | 2609 | 0 | 0 | **2943** | 0 | 0 | 15 | 682 | 541 | 0 | **1238** | 0 | 0 | 510 | 2313 | 141 | 8 | **2972** | 0 | 0 | **8110** |
| **% Lights** | 52.6% | 97.9% | 98.8% | 0.0% | **93.1%** | 0.0% | 0.0% | 96.0% | 99.1% | 0.0% | 0.0% | **98.7%** | 0.0% | 0.0% | 65.2% | 97.2% | 98.7% | 0.0% | **97.3%** | 0.0% | 0.0% | 95.0% | 99.0% | 98.6% | 100.0% | **98.2%** | 0.0% | 0.0% | **97.6%** |
| **Trucks** | 0 | 5 | 4 | 0 | **9** | 0 | 0 | 0 | 16 | 0 | 0 | **16** | 0 | 0 | 0 | 3 | 5 | 0 | **8** | 0 | 0 | 2 | 15 | 1 | 0 | **18** | 0 | 0 | **51** |
| **% Trucks** | 0.0% | 0.9% | 1.2% | 0.0% | **0.9%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.9% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.4% | 0.6% | 0.7% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 1 | 6 | 0 | 0 | **7** | 0 | 0 | 0 | 16 | 1 | 0 | **17** | 0 | 0 | 4 | 5 | 0 | 0 | **9** | 0 | 0 | **36** |
| **% Buses** | 0.0% | 0.5% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 2.3% | 0.2% | 0.0% | **1.3%** | 0.0% | 0.0% | 0.7% | 0.2% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.4%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**4:15:00 PM**

| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:15:00 PM | 9 | 42 | 26 | 0 | **77** | 0 | 0 | 27 | 224 | 0 | 0 | **251** | 0 | 1 | 0 | 75 | 58 | 0 | **133** | 0 | 1 | 55 | 223 | 6 | 0 | **284** | 0 | 0 | **745** |
| 4:30:00 PM | 8 | 54 | 26 | 0 | **88** | 0 | 0 | 33 | 248 | 0 | 0 | **281** | 0 | 0 | 1 | 61 | 40 | 0 | **102** | 0 | 0 | 47 | 217 | 7 | 0 | **271** | 0 | 0 | **742** |
| 4:45:00 PM | 7 | 55 | 18 | 0 | **80** | 0 | 0 | 21 | 241 | 0 | 0 | **262** | 0 | 0 | 2 | 61 | 56 | 0 | **119** | 0 | 0 | 49 | 174 | 11 | 0 | **234** | 0 | 0 | **695** |
| 5:00:00 PM | 15 | 44 | 30 | 0 | **89** | 0 | 0 | 36 | 267 | 0 | 0 | **303** | 0 | 0 | 2 | 53 | 35 | 0 | **90** | 0 | 0 | 44 | 222 | 12 | 0 | **278** | 0 | 0 | **760** |
| **Grand Total** | 39 | 195 | 100 | 0 | **334** | 0 | 0 | 117 | 980 | 0 | 0 | **1097** | 0 | 1 | 5 | 250 | 189 | 0 | **444** | 0 | 1 | 195 | 836 | 36 | 0 | **1067** | 0 | 0 | **2942** |
| **% Approach** | 11.7% | 58.4% | 29.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 10.7% | 89.3% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.1% | 56.3% | 42.6% | 0.0% | **0.0%** | 0.0% | 0.0% | 18.3% | 78.4% | 3.4% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.3% | 6.6% | 3.4% | 0.0% | **11.4%** | 0.0% | 0.0% | 4.0% | 33.3% | 0.0% | 0.0% | **37.3%** | 0.0% | 0.0% | 0.2% | 8.5% | 6.4% | 0.0% | **15.1%** | 0.0% | 0.0% | 6.6% | 28.4% | 1.2% | 0.0% | **36.3%** | 0.0% | 0.0% | |
| **PHF** | 0.650 | 0.886 | 0.833 | 0.000 | **0.938** | 0.000 | 0.000 | 0.813 | 0.918 | 0.000 | 0.000 | **0.905** | 0.000 | 0.000 | 0.625 | 0.833 | 0.815 | 0.000 | **0.835** | 0.000 | 0.000 | 0.886 | 0.937 | 0.750 | 0.000 | **0.939** | 0.000 | 0.000 | **0.968** |
| **Lights** | 23 | 189 | 98 | 0 | **310** | 0 | 0 | 111 | 975 | 0 | 0 | **1086** | 0 | 0 | 1 | 246 | 187 | 0 | **434** | 0 | 0 | 189 | 832 | 36 | 0 | **1057** | 0 | 0 | **2887** |
| **% Lights** | 59.0% | 96.9% | 98.0% | 0.0% | **92.8%** | 0.0% | 0.0% | 94.9% | 99.5% | 0.0% | 0.0% | **99.0%** | 0.0% | 0.0% | 20.0% | 98.4% | 98.9% | 0.0% | **97.7%** | 0.0% | 0.0% | 96.9% | 99.5% | 100.0% | 0.0% | **99.1%** | 0.0% | 0.0% | **98.1%** |
| **Trucks** | 0 | 4 | 2 | 0 | **6** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | **13** |
| **% Trucks** | 0.0% | 2.1% | 2.0% | 0.0% | **1.8%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.5% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **6** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.9% | 0.1% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 1.2% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Eggert Ro |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Sheridan Drive & Eggert Ro |
| **Latitude and Longitude** | 42.98074,-78.82546 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 12:00:00 | 2023-11-18 13:00:00 | 0.945 |


# Turning Movement Data


| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 9 | 46 | 40 | 0 | **95** | 0 | 0 | 34 | 217 | 0 | 0 | **251** | 1 | 1 | 7 | 40 | 33 | 0 | **80** | 0 | 0 | 40 | 207 | 12 | 0 | **259** | 0 | 0 | **685** |
| 12:15:00 | 8 | 38 | 40 | 0 | **86** | 0 | 0 | 40 | 208 | 0 | 0 | **248** | 1 | 0 | 1 | 42 | 41 | 0 | **84** | 0 | 0 | 45 | 220 | 11 | 0 | **276** | 0 | 0 | **694** |
| 12:30:00 | 5 | 41 | 35 | 0 | **81** | 0 | 2 | 29 | 208 | 0 | 0 | **237** | 0 | 0 | 1 | 49 | 33 | 0 | **83** | 0 | 0 | 45 | 208 | 12 | 2 | **267** | 0 | 0 | **668** |
| 12:45:00 | 10 | 29 | 32 | 0 | **71** | 0 | 1 | 27 | 255 | 0 | 0 | **282** | 0 | 2 | 3 | 42 | 31 | 0 | **76** | 0 | 2 | 49 | 245 | 13 | 0 | **307** | 0 | 0 | **736** |
| **Hourly Total** | 32 | 154 | 147 | 0 | **333** | 0 | 3 | 130 | 888 | 0 | 0 | **1018** | 2 | 3 | 12 | 173 | 138 | 0 | **323** | 0 | 2 | 179 | 880 | 48 | 2 | **1109** | 0 | 0 | **2783** |
| 13:00:00 | 7 | 38 | 42 | 0 | **87** | 0 | 0 | 30 | 235 | 0 | 0 | **265** | 0 | 0 | 2 | 36 | 28 | 0 | **66** | 0 | 0 | 39 | 190 | 16 | 0 | **245** | 0 | 0 | **663** |
| 13:15:00 | 9 | 28 | 32 | 0 | **69** | 0 | 0 | 34 | 204 | 1 | 0 | **239** | 0 | 0 | 2 | 34 | 32 | 0 | **68** | 0 | 0 | 39 | 216 | 13 | 0 | **268** | 0 | 0 | **644** |
| 13:30:00 | 12 | 43 | 37 | 0 | **92** | 0 | 0 | 25 | 186 | 0 | 0 | **211** | 0 | 0 | 3 | 41 | 27 | 0 | **71** | 0 | 0 | 34 | 233 | 11 | 0 | **278** | 0 | 0 | **652** |
| 13:45:00 | 15 | 31 | 31 | 0 | **77** | 0 | 0 | 34 | 239 | 0 | 0 | **273** | 0 | 0 | 4 | 43 | 33 | 0 | **80** | 0 | 0 | 34 | 230 | 26 | 0 | **290** | 0 | 0 | **720** |
| **Hourly Total** | 43 | 140 | 142 | 0 | **325** | 0 | 0 | 123 | 864 | 1 | 0 | **988** | 0 | 0 | 11 | 154 | 120 | 0 | **285** | 0 | 0 | 146 | 869 | 66 | 0 | **1081** | 0 | 0 | **2679** |
| 14:00:00 | 8 | 36 | 36 | 0 | **80** | 0 | 0 | 36 | 215 | 0 | 0 | **251** | 0 | 0 | 1 | 30 | 23 | 0 | **54** | 0 | 0 | 48 | 214 | 13 | 0 | **275** | 0 | 0 | **660** |
| 14:15:00 | 8 | 38 | 27 | 0 | **73** | 1 | 0 | 28 | 225 | 0 | 0 | **253** | 0 | 0 | 4 | 31 | 39 | 0 | **74** | 0 | 0 | 36 | 204 | 13 | 1 | **254** | 0 | 0 | **654** |
| 14:30:00 | 6 | 40 | 39 | 0 | **85** | 0 | 0 | 33 | 211 | 0 | 0 | **244** | 0 | 0 | 2 | 33 | 24 | 0 | **59** | 0 | 0 | 36 | 200 | 16 | 1 | **253** | 0 | 0 | **641** |
| 14:45:00 | 17 | 35 | 35 | 0 | **87** | 0 | 0 | 37 | 208 | 0 | 0 | **245** | 0 | 0 | 1 | 39 | 37 | 0 | **77** | 0 | 0 | 39 | 210 | 12 | 0 | **261** | 0 | 0 | **670** |
| **Hourly Total** | 39 | 149 | 137 | 0 | **325** | 1 | 0 | 134 | 859 | 0 | 0 | **993** | 0 | 0 | 8 | 133 | 123 | 0 | **264** | 0 | 0 | 159 | 828 | 54 | 2 | **1043** | 0 | 0 | **2625** |
| **Grand Total** | 114 | 443 | 426 | 0 | **983** | 1 | 3 | 387 | 2611 | 1 | 0 | **2999** | 2 | 3 | 31 | 460 | 381 | 0 | **872** | 0 | 2 | 484 | 2577 | 168 | 4 | **3233** | 0 | 0 | **8087** |
| **% Approach** | 11.6% | 45.1% | 43.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 12.9% | 87.1% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.6% | 52.8% | 43.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 15.0% | 79.7% | 5.2% | 0.1% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.4% | 5.5% | 5.3% | 0.0% | **12.2%** | 0.0% | 0.0% | 4.8% | 32.3% | 0.0% | 0.0% | **37.1%** | 0.0% | 0.0% | 0.4% | 5.7% | 4.7% | 0.0% | **10.8%** | 0.0% | 0.0% | 6.0% | 31.9% | 2.1% | 0.0% | **40.0%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 55 | 441 | 425 | 0 | **921** | 0 | 0 | 369 | 2595 | 1 | 0 | **2965** | 0 | 0 | 19 | 459 | 376 | 0 | **854** | 0 | 0 | 468 | 2568 | 167 | 4 | **3207** | 0 | 0 | **7947** |
| **% Lights** | 48.2% | 99.5% | 99.8% | 0.0% | **93.7%** | 0.0% | 0.0% | 95.3% | 99.4% | 100.0% | 0.0% | **98.9%** | 0.0% | 0.0% | 61.3% | 99.8% | 98.7% | 0.0% | **97.9%** | 0.0% | 0.0% | 96.7% | 99.7% | 99.4% | 100.0% | **99.2%** | 0.0% | 0.0% | **98.3%** |
| **Trucks** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 1 | 9 | 0 | 0 | **10** | 0 | 0 | 0 | 1 | 4 | 0 | **5** | 0 | 0 | 4 | 5 | 1 | 0 | **10** | 0 | 0 | **27** |
| **% Trucks** | 0.0% | 0.5% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.3% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 1.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.8% | 0.2% | 0.6% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | **10** |
| **% Buses** | 0.0% | 0.0% | 0.2% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot




TSTData.com


**Summary**


## Turning Movement Peak Hour Data (PM)

**12:00:00**

| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 9 | 46 | 40 | 0 | **95** | 0 | 0 | 34 | 217 | 0 | 0 | **251** | 1 | 1 | 7 | 40 | 33 | 0 | **80** | 0 | 0 | 40 | 207 | 12 | 0 | **259** | 0 | 0 | **685** |
| 12:15:00 | 8 | 38 | 40 | 0 | **86** | 0 | 0 | 40 | 208 | 0 | 0 | **248** | 1 | 0 | 1 | 42 | 41 | 0 | **84** | 0 | 0 | 45 | 220 | 11 | 0 | **276** | 0 | 0 | **694** |
| 12:30:00 | 5 | 41 | 35 | 0 | **81** | 0 | 2 | 29 | 208 | 0 | 0 | **237** | 0 | 0 | 1 | 49 | 33 | 0 | **83** | 0 | 0 | 45 | 208 | 12 | 2 | **267** | 0 | 0 | **668** |
| 12:45:00 | 10 | 29 | 32 | 0 | **71** | 0 | 1 | 27 | 255 | 0 | 0 | **282** | 0 | 2 | 3 | 42 | 31 | 0 | **76** | 0 | 2 | 49 | 245 | 13 | 0 | **307** | 0 | 0 | **736** |
| **Grand Total** | 32 | 154 | 147 | 0 | **333** | 0 | 3 | 130 | 888 | 0 | 0 | **1018** | 2 | 3 | 12 | 173 | 138 | 0 | **323** | 0 | 2 | 179 | 880 | 48 | 2 | **1109** | 0 | 0 | **2783** |
| **% Approach** | 9.6% | 46.2% | 44.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 12.8% | 87.2% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.7% | 53.6% | 42.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 16.1% | 79.4% | 4.3% | 0.2% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.1% | 5.5% | 5.3% | 0.0% | **12.0%** | 0.0% | 0.0% | 4.7% | 31.9% | 0.0% | 0.0% | **36.6%** | 0.0% | 0.0% | 0.4% | 6.2% | 5.0% | 0.0% | **11.6%** | 0.0% | 0.0% | 6.4% | 31.6% | 1.7% | 0.1% | **39.8%** | 0.0% | 0.0% | |
| **PHF** | 0.800 | 0.837 | 0.919 | 0.000 | **0.876** | 0.000 | 0.000 | 0.813 | 0.871 | 0.000 | 0.000 | **0.902** | 0.000 | 0.000 | 0.429 | 0.883 | 0.841 | 0.000 | **0.961** | 0.000 | 0.000 | 0.913 | 0.898 | 0.923 | 0.250 | **0.903** | 0.000 | 0.000 | **0.945** |
| **Lights** | 15 | 153 | 146 | 0 | **314** | 0 | 0 | 124 | 881 | 0 | 0 | **1005** | 0 | 0 | 7 | 173 | 138 | 0 | **318** | 0 | 0 | 174 | 877 | 47 | 2 | **1100** | 0 | 0 | **2737** |
| **% Lights** | 46.9% | 99.4% | 99.3% | 0.0% | **94.3%** | 0.0% | 0.0% | 95.4% | 99.2% | 0.0% | 0.0% | **98.7%** | 0.0% | 0.0% | 58.3% | 100.0% | 100.0% | 0.0% | **98.5%** | 0.0% | 0.0% | 97.2% | 99.7% | 97.9% | 100.0% | **99.2%** | 0.0% | 0.0% | **98.3%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 2 | 1 | 0 | **4** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.6% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.6% | 0.2% | 2.1% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **3** |
| **% Buses** | 0.0% | 0.0% | 0.7% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 9 | 46 | 40 | 0 | **95** | 0 | 0 | 34 | 217 | 0 | 0 | **251** | 1 | 1 | 7 | 40 | 33 | 0 | **80** | 0 | 0 | 40 | 207 | 12 | 0 | **259** | 0 | 0 | **685** |
| 12:15:00 | 8 | 38 | 40 | 0 | **86** | 0 | 0 | 40 | 208 | 0 | 0 | **248** | 1 | 0 | 1 | 42 | 41 | 0 | **84** | 0 | 0 | 45 | 220 | 11 | 0 | **276** | 0 | 0 | **694** |
| 12:30:00 | 5 | 41 | 35 | 0 | **81** | 0 | 2 | 29 | 208 | 0 | 0 | **237** | 0 | 0 | 1 | 49 | 33 | 0 | **83** | 0 | 0 | 45 | 208 | 12 | 2 | **267** | 0 | 0 | **668** |
| 12:45:00 | 10 | 29 | 32 | 0 | **71** | 0 | 1 | 27 | 255 | 0 | 0 | **282** | 0 | 2 | 3 | 42 | 31 | 0 | **76** | 0 | 2 | 49 | 245 | 13 | 0 | **307** | 0 | 0 | **736** |
| **Hourly Total** | 32 | 154 | 147 | 0 | **333** | 0 | 3 | 130 | 888 | 0 | 0 | **1018** | 2 | 3 | 12 | 173 | 138 | 0 | **323** | 0 | 2 | 179 | 880 | 48 | 2 | **1109** | 0 | 0 | **2783** |
| 13:00:00 | 7 | 38 | 42 | 0 | **87** | 0 | 0 | 30 | 235 | 0 | 0 | **265** | 0 | 0 | 2 | 36 | 28 | 0 | **66** | 0 | 0 | 39 | 190 | 16 | 0 | **245** | 0 | 0 | **663** |
| 13:15:00 | 9 | 28 | 32 | 0 | **69** | 0 | 0 | 34 | 204 | 1 | 0 | **239** | 0 | 0 | 2 | 34 | 32 | 0 | **68** | 0 | 0 | 39 | 216 | 13 | 0 | **268** | 0 | 0 | **644** |
| 13:30:00 | 12 | 43 | 37 | 0 | **92** | 0 | 0 | 25 | 186 | 0 | 0 | **211** | 0 | 0 | 3 | 41 | 27 | 0 | **71** | 0 | 0 | 34 | 233 | 11 | 0 | **278** | 0 | 0 | **652** |
| 13:45:00 | 15 | 31 | 31 | 0 | **77** | 0 | 0 | 34 | 239 | 0 | 0 | **273** | 0 | 0 | 4 | 43 | 33 | 0 | **80** | 0 | 0 | 34 | 230 | 26 | 0 | **290** | 0 | 0 | **720** |
| **Hourly Total** | 43 | 140 | 142 | 0 | **325** | 0 | 0 | 123 | 864 | 1 | 0 | **988** | 0 | 0 | 11 | 154 | 120 | 0 | **285** | 0 | 0 | 146 | 869 | 66 | 0 | **1081** | 0 | 0 | **2679** |
| 14:00:00 | 8 | 36 | 36 | 0 | **80** | 0 | 0 | 36 | 215 | 0 | 0 | **251** | 0 | 0 | 1 | 30 | 23 | 0 | **54** | 0 | 0 | 48 | 214 | 13 | 0 | **275** | 0 | 0 | **660** |
| 14:15:00 | 8 | 38 | 27 | 0 | **73** | 1 | 0 | 28 | 225 | 0 | 0 | **253** | 0 | 0 | 4 | 31 | 39 | 0 | **74** | 0 | 0 | 36 | 204 | 13 | 1 | **254** | 0 | 0 | **654** |
| 14:30:00 | 6 | 40 | 39 | 0 | **85** | 0 | 0 | 33 | 211 | 0 | 0 | **244** | 0 | 0 | 2 | 33 | 24 | 0 | **59** | 0 | 0 | 36 | 200 | 16 | 1 | **253** | 0 | 0 | **641** |
| 14:45:00 | 17 | 35 | 35 | 0 | **87** | 0 | 0 | 37 | 208 | 0 | 0 | **245** | 0 | 0 | 1 | 39 | 37 | 0 | **77** | 0 | 0 | 39 | 210 | 12 | 0 | **261** | 0 | 0 | **670** |
| **Hourly Total** | 39 | 149 | 137 | 0 | **325** | 1 | 0 | 134 | 859 | 0 | 0 | **993** | 0 | 0 | 8 | 133 | 123 | 0 | **264** | 0 | 0 | 159 | 828 | 54 | 2 | **1043** | 0 | 0 | **2625** |
| **Grand Total** | 114 | 443 | 426 | 0 | **983** | 1 | 3 | 387 | 2611 | 1 | 0 | **2999** | 2 | 3 | 31 | 460 | 381 | 0 | **872** | 0 | 2 | 484 | 2577 | 168 | 4 | **3233** | 0 | 0 | **8087** |
| **% Approach** | 11.6% | 45.1% | 43.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 12.9% | 87.1% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.6% | 52.8% | 43.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 15.0% | 79.7% | 5.2% | 0.1% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.4% | 5.5% | 5.3% | 0.0% | **12.2%** | 0.0% | 0.0% | 4.8% | 32.3% | 0.0% | 0.0% | **37.1%** | 0.0% | 0.0% | 0.4% | 5.7% | 4.7% | 0.0% | **10.8%** | 0.0% | 0.0% | 6.0% | 31.9% | 2.1% | 0.0% | **40.0%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 55 | 441 | 425 | 0 | **921** | 0 | 0 | 369 | 2595 | 1 | 0 | **2965** | 0 | 0 | 19 | 459 | 376 | 0 | **854** | 0 | 0 | 468 | 2568 | 167 | 4 | **3207** | 0 | 0 | **7947** |
| **% Lights** | 48.2% | 99.5% | 99.8% | 0.0% | **93.7%** | 0.0% | 0.0% | 95.3% | 99.4% | 100.0% | 0.0% | **98.9%** | 0.0% | 0.0% | 61.3% | 99.8% | 98.7% | 0.0% | **97.9%** | 0.0% | 0.0% | 96.7% | 99.7% | 99.4% | 100.0% | **99.2%** | 0.0% | 0.0% | **98.3%** |
| **Trucks** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 1 | 9 | 0 | 0 | **10** | 0 | 0 | 0 | 1 | 4 | 0 | **5** | 0 | 0 | 4 | 5 | 1 | 0 | **10** | 0 | 0 | **27** |
| **% Trucks** | 0.0% | 0.5% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.3% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 1.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.8% | 0.2% | 0.6% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | **10** |
| **% Buses** | 0.0% | 0.0% | 0.2% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**12:00:00**

| Leg | Eggert Road | | | | | | | Sheridan Drive | | | | | | | Eggert Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 9 | 46 | 40 | 0 | **95** | 0 | 0 | 34 | 217 | 0 | 0 | **251** | 1 | 1 | 7 | 40 | 33 | 0 | **80** | 0 | 0 | 40 | 207 | 12 | 0 | **259** | 0 | 0 | **685** |
| 12:15:00 | 8 | 38 | 40 | 0 | **86** | 0 | 0 | 40 | 208 | 0 | 0 | **248** | 1 | 0 | 1 | 42 | 41 | 0 | **84** | 0 | 0 | 45 | 220 | 11 | 0 | **276** | 0 | 0 | **694** |
| 12:30:00 | 5 | 41 | 35 | 0 | **81** | 0 | 2 | 29 | 208 | 0 | 0 | **237** | 0 | 0 | 1 | 49 | 33 | 0 | **83** | 0 | 0 | 45 | 208 | 12 | 2 | **267** | 0 | 0 | **668** |
| 12:45:00 | 10 | 29 | 32 | 0 | **71** | 0 | 1 | 27 | 255 | 0 | 0 | **282** | 0 | 2 | 3 | 42 | 31 | 0 | **76** | 0 | 2 | 49 | 245 | 13 | 0 | **307** | 0 | 0 | **736** |
| **Grand Total** | 32 | 154 | 147 | 0 | **333** | 0 | 3 | 130 | 888 | 0 | 0 | **1018** | 2 | 3 | 12 | 173 | 138 | 0 | **323** | 0 | 2 | 179 | 880 | 48 | 2 | **1109** | 0 | 0 | **2783** |
| **% Approach** | 9.6% | 46.2% | 44.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 12.8% | 87.2% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.7% | 53.6% | 42.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 16.1% | 79.4% | 4.3% | 0.2% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.1% | 5.5% | 5.3% | 0.0% | **12.0%** | 0.0% | 0.0% | 4.7% | 31.9% | 0.0% | 0.0% | **36.6%** | 0.0% | 0.0% | 0.4% | 6.2% | 5.0% | 0.0% | **11.6%** | 0.0% | 0.0% | 6.4% | 31.6% | 1.7% | 0.1% | **39.8%** | 0.0% | 0.0% | |
| **PHF** | 0.800 | 0.837 | 0.919 | 0.000 | **0.876** | 0.000 | 0.000 | 0.813 | 0.871 | 0.000 | 0.000 | **0.902** | 0.000 | 0.000 | 0.429 | 0.883 | 0.841 | 0.000 | **0.961** | 0.000 | 0.000 | 0.913 | 0.898 | 0.923 | 0.250 | **0.903** | 0.000 | 0.000 | **0.945** |
| **Lights** | 15 | 153 | 146 | 0 | **314** | 0 | 0 | 124 | 881 | 0 | 0 | **1005** | 0 | 0 | 7 | 173 | 138 | 0 | **318** | 0 | 0 | 174 | 877 | 47 | 2 | **1100** | 0 | 0 | **2737** |
| **% Lights** | 46.9% | 99.4% | 99.3% | 0.0% | **94.3%** | 0.0% | 0.0% | 95.4% | 99.2% | 0.0% | 0.0% | **98.7%** | 0.0% | 0.0% | 58.3% | 100.0% | 100.0% | 0.0% | **98.5%** | 0.0% | 0.0% | 97.2% | 99.7% | 97.9% | 100.0% | **99.2%** | 0.0% | 0.0% | **98.3%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 2 | 1 | 0 | **4** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.6% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.6% | 0.2% | 2.1% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **3** |
| **% Buses** | 0.0% | 0.0% | 0.7% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Alberta Dri |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Sheridan Drive & Alberta Dri |
| **Latitude and Longitude** | 42.98047,-78.81752 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:15:00 | 2023-11-16 17:15:00 | 0.959 |


# Turning Movement Data


| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 34 | 13 | 23 | 0 | **70** | 0 | 0 | 15 | 230 | 8 | 3 | **256** | 0 | 0 | 8 | 17 | 12 | 0 | **37** | 0 | 0 | 12 | 185 | 36 | 6 | **239** | 0 | 1 | **602** |
| 3:15:00 PM | 36 | 26 | 33 | 0 | **95** | 1 | 2 | 15 | 205 | 15 | 4 | **239** | 0 | 0 | 4 | 24 | 9 | 0 | **37** | 0 | 0 | 12 | 142 | 31 | 5 | **190** | 0 | 0 | **561** |
| 3:30:00 PM | 38 | 28 | 30 | 0 | **96** | 1 | 3 | 20 | 254 | 16 | 1 | **291** | 0 | 0 | 2 | 10 | 9 | 0 | **21** | 0 | 0 | 7 | 181 | 32 | 5 | **225** | 0 | 0 | **633** |
| 3:45:00 PM | 25 | 25 | 22 | 0 | **72** | 1 | 2 | 23 | 211 | 14 | 3 | **251** | 0 | 0 | 8 | 22 | 5 | 0 | **35** | 0 | 0 | 16 | 195 | 30 | 6 | **247** | 0 | 1 | **605** |
| **Hourly Total** | 133 | 92 | 108 | 0 | **333** | 3 | 7 | 73 | 900 | 53 | 11 | **1037** | 0 | 0 | 22 | 73 | 35 | 0 | **130** | 0 | 0 | 47 | 703 | 129 | 22 | **901** | 0 | 2 | **2401** |
| 4:00:00 PM | 42 | 26 | 33 | 0 | **101** | 4 | 0 | 23 | 199 | 10 | 2 | **234** | 0 | 0 | 7 | 21 | 15 | 0 | **43** | 0 | 1 | 9 | 167 | 34 | 12 | **222** | 0 | 0 | **600** |
| 4:15:00 PM | 42 | 23 | 29 | 0 | **94** | 0 | 3 | 20 | 291 | 5 | 1 | **317** | 0 | 0 | 2 | 19 | 11 | 0 | **32** | 0 | 0 | 9 | 189 | 30 | 3 | **231** | 0 | 2 | **674** |
| 4:30:00 PM | 48 | 28 | 36 | 0 | **112** | 0 | 0 | 21 | 239 | 18 | 5 | **283** | 0 | 0 | 5 | 16 | 8 | 0 | **29** | 1 | 0 | 12 | 158 | 26 | 5 | **201** | 0 | 0 | **625** |
| 4:45:00 PM | 33 | 24 | 26 | 0 | **83** | 1 | 2 | 14 | 255 | 11 | 0 | **280** | 0 | 0 | 6 | 20 | 11 | 0 | **37** | 0 | 0 | 11 | 177 | 35 | 3 | **226** | 0 | 0 | **626** |
| **Hourly Total** | 165 | 101 | 124 | 0 | **390** | 5 | 5 | 78 | 984 | 44 | 8 | **1114** | 0 | 0 | 20 | 76 | 45 | 0 | **141** | 1 | 1 | 41 | 691 | 125 | 23 | **880** | 0 | 2 | **2525** |
| 5:00:00 PM | 40 | 19 | 28 | 0 | **87** | 2 | 1 | 16 | 281 | 15 | 2 | **314** | 0 | 0 | 6 | 17 | 8 | 0 | **31** | 0 | 0 | 10 | 179 | 34 | 6 | **229** | 1 | 0 | **661** |
| 5:15:00 PM | 42 | 34 | 40 | 0 | **116** | 2 | 2 | 16 | 212 | 11 | 1 | **240** | 0 | 0 | 1 | 13 | 9 | 0 | **23** | 0 | 0 | 10 | 171 | 34 | 11 | **226** | 2 | 1 | **605** |
| 5:30:00 PM | 37 | 24 | 32 | 0 | **93** | 0 | 0 | 15 | 256 | 20 | 1 | **292** | 0 | 0 | 9 | 15 | 6 | 0 | **30** | 0 | 0 | 11 | 196 | 26 | 6 | **239** | 1 | 0 | **654** |
| 5:45:00 PM | 36 | 19 | 24 | 0 | **79** | 1 | 0 | 16 | 200 | 11 | 3 | **230** | 0 | 0 | 7 | 15 | 10 | 0 | **32** | 0 | 0 | 14 | 152 | 27 | 8 | **201** | 0 | 0 | **542** |
| **Hourly Total** | 155 | 96 | 124 | 0 | **375** | 5 | 3 | 63 | 949 | 57 | 7 | **1076** | 0 | 0 | 23 | 60 | 33 | 0 | **116** | 0 | 0 | 45 | 698 | 121 | 31 | **895** | 4 | 1 | **2462** |
| **Grand Total** | 453 | 289 | 356 | 0 | **1098** | 13 | 15 | 214 | 2833 | 154 | 26 | **3227** | 0 | 0 | 65 | 209 | 113 | 0 | **387** | 1 | 1 | 133 | 2092 | 375 | 76 | **2676** | 4 | 5 | **7388** |
| **% Approach** | 41.3% | 26.3% | 32.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.6% | 87.8% | 4.8% | 0.8% | **0.0%** | 0.0% | 0.0% | 16.8% | 54.0% | 29.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.0% | 78.2% | 14.0% | 2.8% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 6.1% | 3.9% | 4.8% | 0.0% | **14.9%** | 0.0% | 0.0% | 2.9% | 38.3% | 2.1% | 0.4% | **43.7%** | 0.0% | 0.0% | 0.9% | 2.8% | 1.5% | 0.0% | **5.2%** | 0.0% | 0.0% | 1.8% | 28.3% | 5.1% | 1.0% | **36.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 286 | 287 | 354 | 0 | **927** | 0 | 0 | 187 | 2810 | 154 | 26 | **3177** | 0 | 0 | 61 | 207 | 112 | 0 | **380** | 0 | 0 | 102 | 2066 | 368 | 76 | **2612** | 0 | 0 | **7096** |
| **% Lights** | 63.1% | 99.3% | 99.4% | 0.0% | **84.4%** | 0.0% | 0.0% | 87.4% | 99.2% | 100.0% | 100.0% | **98.5%** | 0.0% | 0.0% | 93.8% | 99.0% | 99.1% | 0.0% | **98.2%** | 0.0% | 0.0% | 76.7% | 98.8% | 98.1% | 100.0% | **97.6%** | 0.0% | 0.0% | **96.0%** |
| **Trucks** | 1 | 0 | 1 | 0 | **2** | 0 | 0 | 3 | 14 | 0 | 0 | **17** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | 0 | 20 | 2 | 0 | **22** | 0 | 0 | **43** |
| **% Trucks** | 0.2% | 0.0% | 0.3% | 0.0% | **0.2%** | 0.0% | 0.0% | 1.4% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.9% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 1.0% | 0.5% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 2 | 1 | 1 | 0 | **4** | 0 | 0 | 3 | 7 | 0 | 0 | **10** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 4 | 0 | **7** | 0 | 0 | **21** |
| **% Buses** | 0.4% | 0.3% | 0.3% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 1.1% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 12 | 13 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 2 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 92.3% | 86.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 80.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 7.7% | 13.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 20.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot




TSTData.com


## Summary


# Turning Movement Peak Hour Data (PM)

**4:15:00 PM**

| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:15:00 PM | 42 | 23 | 29 | 0 | **94** | 0 | 3 | 20 | 291 | 5 | 1 | **317** | 0 | 0 | 2 | 19 | 11 | 0 | **32** | 0 | 0 | 9 | 189 | 30 | 3 | **231** | 0 | 2 | **674** |
| 4:30:00 PM | 48 | 28 | 36 | 0 | **112** | 0 | 0 | 21 | 239 | 18 | 5 | **283** | 0 | 0 | 5 | 16 | 8 | 0 | **29** | 1 | 0 | 12 | 158 | 26 | 5 | **201** | 0 | 0 | **625** |
| 4:45:00 PM | 33 | 24 | 26 | 0 | **83** | 1 | 2 | 14 | 255 | 11 | 0 | **280** | 0 | 0 | 6 | 20 | 11 | 0 | **37** | 0 | 0 | 11 | 177 | 35 | 3 | **226** | 0 | 0 | **626** |
| 5:00:00 PM | 40 | 19 | 28 | 0 | **87** | 2 | 1 | 16 | 281 | 15 | 2 | **314** | 0 | 0 | 6 | 17 | 8 | 0 | **31** | 0 | 0 | 10 | 179 | 34 | 6 | **229** | 1 | 0 | **661** |
| **Grand Total** | 163 | 94 | 119 | 0 | **376** | 3 | 6 | 71 | 1066 | 49 | 8 | **1194** | 0 | 0 | 19 | 72 | 38 | 0 | **129** | 1 | 0 | 42 | 703 | 125 | 17 | **887** | 1 | 2 | **2586** |
| **% Approach** | 43.4% | 25.0% | 31.6% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.9% | 89.3% | 4.1% | 0.7% | **0.0%** | 0.0% | 0.0% | 14.7% | 55.8% | 29.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.7% | 79.3% | 14.1% | 1.9% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 6.3% | 3.6% | 4.6% | 0.0% | **14.5%** | 0.0% | 0.0% | 2.7% | 41.2% | 1.9% | 0.3% | **46.2%** | 0.0% | 0.0% | 0.7% | 2.8% | 1.5% | 0.0% | **5.0%** | 0.0% | 0.0% | 1.6% | 27.2% | 4.8% | 0.7% | **34.3%** | 0.0% | 0.0% | |
| **PHF** | 0.849 | 0.839 | 0.826 | 0.000 | **0.839** | 0.000 | 0.000 | 0.845 | 0.916 | 0.681 | 0.400 | **0.942** | 0.000 | 0.000 | 0.792 | 0.900 | 0.864 | 0.000 | **0.872** | 0.000 | 0.000 | 0.875 | 0.930 | 0.893 | 0.708 | **0.960** | 0.000 | 0.000 | **0.959** |
| **Lights** | 97 | 93 | 119 | 0 | **309** | 0 | 0 | 65 | 1060 | 49 | 8 | **1182** | 0 | 0 | 18 | 71 | 38 | 0 | **127** | 0 | 0 | 33 | 697 | 124 | 17 | **871** | 0 | 0 | **2489** |
| **% Lights** | 59.5% | 98.9% | 100.0% | 0.0% | **82.2%** | 0.0% | 0.0% | 91.5% | 99.4% | 100.0% | 100.0% | **99.0%** | 0.0% | 0.0% | 94.7% | 98.6% | 100.0% | 0.0% | **98.4%** | 0.0% | 0.0% | 78.6% | 99.1% | 99.2% | 100.0% | **98.2%** | 0.0% | 0.0% | **96.2%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **9** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 1.4% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 1 | 2 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | **7** |
| **% Buses** | 0.6% | 1.1% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 1.4% | 0.2% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.8% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 3 | 5 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 83.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 16.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 34 | 13 | 23 | 0 | **70** | 0 | 0 | 15 | 230 | 8 | 3 | **256** | 0 | 0 | 8 | 17 | 12 | 0 | **37** | 0 | 0 | 12 | 185 | 36 | 6 | **239** | 0 | 1 | **602** |
| 3:15:00 PM | 36 | 26 | 33 | 0 | **95** | 1 | 2 | 15 | 205 | 15 | 4 | **239** | 0 | 0 | 4 | 24 | 9 | 0 | **37** | 0 | 0 | 12 | 142 | 31 | 5 | **190** | 0 | 0 | **561** |
| 3:30:00 PM | 38 | 28 | 30 | 0 | **96** | 1 | 3 | 20 | 254 | 16 | 1 | **291** | 0 | 0 | 2 | 10 | 9 | 0 | **21** | 0 | 0 | 7 | 181 | 32 | 5 | **225** | 0 | 0 | **633** |
| 3:45:00 PM | 25 | 25 | 22 | 0 | **72** | 1 | 2 | 23 | 211 | 14 | 3 | **251** | 0 | 0 | 8 | 22 | 5 | 0 | **35** | 0 | 0 | 16 | 195 | 30 | 6 | **247** | 0 | 1 | **605** |
| **Hourly Total** | 133 | 92 | 108 | 0 | **333** | 3 | 7 | 73 | 900 | 53 | 11 | **1037** | 0 | 0 | 22 | 73 | 35 | 0 | **130** | 0 | 0 | 47 | 703 | 129 | 22 | **901** | 0 | 2 | **2401** |
| 4:00:00 PM | 42 | 26 | 33 | 0 | **101** | 4 | 0 | 23 | 199 | 10 | 2 | **234** | 0 | 0 | 7 | 21 | 15 | 0 | **43** | 0 | 1 | 9 | 167 | 34 | 12 | **222** | 0 | 0 | **600** |
| 4:15:00 PM | 42 | 23 | 29 | 0 | **94** | 0 | 3 | 20 | 291 | 5 | 1 | **317** | 0 | 0 | 2 | 19 | 11 | 0 | **32** | 0 | 0 | 9 | 189 | 30 | 3 | **231** | 0 | 2 | **674** |
| 4:30:00 PM | 48 | 28 | 36 | 0 | **112** | 0 | 0 | 21 | 239 | 18 | 5 | **283** | 0 | 0 | 5 | 16 | 8 | 0 | **29** | 1 | 0 | 12 | 158 | 26 | 5 | **201** | 0 | 0 | **625** |
| 4:45:00 PM | 33 | 24 | 26 | 0 | **83** | 1 | 2 | 14 | 255 | 11 | 0 | **280** | 0 | 0 | 6 | 20 | 11 | 0 | **37** | 0 | 0 | 11 | 177 | 35 | 3 | **226** | 0 | 0 | **626** |
| **Hourly Total** | 165 | 101 | 124 | 0 | **390** | 5 | 5 | 78 | 984 | 44 | 8 | **1114** | 0 | 0 | 20 | 76 | 45 | 0 | **141** | 1 | 1 | 41 | 691 | 125 | 23 | **880** | 0 | 2 | **2525** |
| 5:00:00 PM | 40 | 19 | 28 | 0 | **87** | 2 | 1 | 16 | 281 | 15 | 2 | **314** | 0 | 0 | 6 | 17 | 8 | 0 | **31** | 0 | 0 | 10 | 179 | 34 | 6 | **229** | 1 | 0 | **661** |
| 5:15:00 PM | 42 | 34 | 40 | 0 | **116** | 2 | 2 | 16 | 212 | 11 | 1 | **240** | 0 | 0 | 1 | 13 | 9 | 0 | **23** | 0 | 0 | 10 | 171 | 34 | 11 | **226** | 2 | 1 | **605** |
| 5:30:00 PM | 37 | 24 | 32 | 0 | **93** | 0 | 0 | 15 | 256 | 20 | 1 | **292** | 0 | 0 | 9 | 15 | 6 | 0 | **30** | 0 | 0 | 11 | 196 | 26 | 6 | **239** | 1 | 0 | **654** |
| 5:45:00 PM | 36 | 19 | 24 | 0 | **79** | 1 | 0 | 16 | 200 | 11 | 3 | **230** | 0 | 0 | 7 | 15 | 10 | 0 | **32** | 0 | 0 | 14 | 152 | 27 | 8 | **201** | 0 | 0 | **542** |
| **Hourly Total** | 155 | 96 | 124 | 0 | **375** | 5 | 3 | 63 | 949 | 57 | 7 | **1076** | 0 | 0 | 23 | 60 | 33 | 0 | **116** | 0 | 0 | 45 | 698 | 121 | 31 | **895** | 4 | 1 | **2462** |
| **Grand Total** | 453 | 289 | 356 | 0 | **1098** | 13 | 15 | 214 | 2833 | 154 | 26 | **3227** | 0 | 0 | 65 | 209 | 113 | 0 | **387** | 1 | 1 | 133 | 2092 | 375 | 76 | **2676** | 4 | 5 | **7388** |
| **% Approach** | 41.3% | 26.3% | 32.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.6% | 87.8% | 4.8% | 0.8% | **0.0%** | 0.0% | 0.0% | 16.8% | 54.0% | 29.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.0% | 78.2% | 14.0% | 2.8% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 6.1% | 3.9% | 4.8% | 0.0% | **14.9%** | 0.0% | 0.0% | 2.9% | 38.3% | 2.1% | 0.4% | **43.7%** | 0.0% | 0.0% | 0.9% | 2.8% | 1.5% | 0.0% | **5.2%** | 0.0% | 0.0% | 1.8% | 28.3% | 5.1% | 1.0% | **36.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 286 | 287 | 354 | 0 | **927** | 0 | 0 | 187 | 2810 | 154 | 26 | **3177** | 0 | 0 | 61 | 207 | 112 | 0 | **380** | 0 | 0 | 102 | 2066 | 368 | 76 | **2612** | 0 | 0 | **7096** |
| **% Lights** | 63.1% | 99.3% | 99.4% | 0.0% | **84.4%** | 0.0% | 0.0% | 87.4% | 99.2% | 100.0% | 100.0% | **98.5%** | 0.0% | 0.0% | 93.8% | 99.0% | 99.1% | 0.0% | **98.2%** | 0.0% | 0.0% | 76.7% | 98.8% | 98.1% | 100.0% | **97.6%** | 0.0% | 0.0% | **96.0%** |
| **Trucks** | 1 | 0 | 1 | 0 | **2** | 0 | 0 | 3 | 14 | 0 | 0 | **17** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | 0 | 20 | 2 | 0 | **22** | 0 | 0 | **43** |
| **% Trucks** | 0.2% | 0.0% | 0.3% | 0.0% | **0.2%** | 0.0% | 0.0% | 1.4% | 0.5% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.9% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 1.0% | 0.5% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 2 | 1 | 1 | 0 | **4** | 0 | 0 | 3 | 7 | 0 | 0 | **10** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 4 | 0 | **7** | 0 | 0 | **21** |
| **% Buses** | 0.4% | 0.3% | 0.3% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 1.1% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 12 | 13 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 2 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 92.3% | 86.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 80.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 7.7% | 13.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 20.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**4:15:00 PM**

| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:15:00 PM | 42 | 23 | 29 | 0 | **94** | 0 | 3 | 20 | 291 | 5 | 1 | **317** | 0 | 0 | 2 | 19 | 11 | 0 | **32** | 0 | 0 | 9 | 189 | 30 | 3 | **231** | 0 | 2 | **674** |
| 4:30:00 PM | 48 | 28 | 36 | 0 | **112** | 0 | 0 | 21 | 239 | 18 | 5 | **283** | 0 | 0 | 5 | 16 | 8 | 0 | **29** | 1 | 0 | 12 | 158 | 26 | 5 | **201** | 0 | 0 | **625** |
| 4:45:00 PM | 33 | 24 | 26 | 0 | **83** | 1 | 2 | 14 | 255 | 11 | 0 | **280** | 0 | 0 | 6 | 20 | 11 | 0 | **37** | 0 | 0 | 11 | 177 | 35 | 3 | **226** | 0 | 0 | **626** |
| 5:00:00 PM | 40 | 19 | 28 | 0 | **87** | 2 | 1 | 16 | 281 | 15 | 2 | **314** | 0 | 0 | 6 | 17 | 8 | 0 | **31** | 0 | 0 | 10 | 179 | 34 | 6 | **229** | 1 | 0 | **661** |
| **Grand Total** | 163 | 94 | 119 | 0 | **376** | 3 | 6 | 71 | 1066 | 49 | 8 | **1194** | 0 | 0 | 19 | 72 | 38 | 0 | **129** | 1 | 0 | 42 | 703 | 125 | 17 | **887** | 1 | 2 | **2586** |
| **% Approach** | 43.4% | 25.0% | 31.6% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.9% | 89.3% | 4.1% | 0.7% | **0.0%** | 0.0% | 0.0% | 14.7% | 55.8% | 29.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.7% | 79.3% | 14.1% | 1.9% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 6.3% | 3.6% | 4.6% | 0.0% | **14.5%** | 0.0% | 0.0% | 2.7% | 41.2% | 1.9% | 0.3% | **46.2%** | 0.0% | 0.0% | 0.7% | 2.8% | 1.5% | 0.0% | **5.0%** | 0.0% | 0.0% | 1.6% | 27.2% | 4.8% | 0.7% | **34.3%** | 0.0% | 0.0% | |
| **PHF** | 0.849 | 0.839 | 0.826 | 0.000 | **0.839** | 0.000 | 0.000 | 0.845 | 0.916 | 0.681 | 0.400 | **0.942** | 0.000 | 0.000 | 0.792 | 0.900 | 0.864 | 0.000 | **0.872** | 0.000 | 0.000 | 0.875 | 0.930 | 0.893 | 0.708 | **0.960** | 0.000 | 0.000 | **0.959** |
| **Lights** | 97 | 93 | 119 | 0 | **309** | 0 | 0 | 65 | 1060 | 49 | 8 | **1182** | 0 | 0 | 18 | 71 | 38 | 0 | **127** | 0 | 0 | 33 | 697 | 124 | 17 | **871** | 0 | 0 | **2489** |
| **% Lights** | 59.5% | 98.9% | 100.0% | 0.0% | **82.2%** | 0.0% | 0.0% | 91.5% | 99.4% | 100.0% | 100.0% | **99.0%** | 0.0% | 0.0% | 94.7% | 98.6% | 100.0% | 0.0% | **98.4%** | 0.0% | 0.0% | 78.6% | 99.1% | 99.2% | 100.0% | **98.2%** | 0.0% | 0.0% | **96.2%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **9** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 1.4% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 1 | 2 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | **7** |
| **% Buses** | 0.6% | 1.1% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 1.4% | 0.2% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.8% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 3 | 5 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 83.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 16.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Alberta Dri |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Sheridan Drive & Alberta Dri |
| **Latitude and Longitude** | 42.98047,-78.81752 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 12:15:00 | 2023-11-18 13:15:00 | 0.961 |


## Turning Movement Data


| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 60 | 36 | 32 | 0 | **128** | 1 | 0 | 29 | 210 | 20 | 2 | **261** | 0 | 0 | 6 | 26 | 18 | 0 | **50** | 0 | 0 | 17 | 229 | 31 | 4 | **281** | 2 | 0 | **720** |
| 12:15:00 | 45 | 24 | 20 | 0 | **89** | 3 | 0 | 26 | 252 | 27 | 3 | **308** | 0 | 0 | 10 | 16 | 22 | 0 | **48** | 0 | 0 | 23 | 196 | 57 | 12 | **288** | 2 | 1 | **733** |
| 12:30:00 | 55 | 27 | 26 | 0 | **108** | 3 | 1 | 28 | 211 | 10 | 0 | **249** | 0 | 0 | 4 | 19 | 18 | 0 | **41** | 1 | 1 | 17 | 198 | 45 | 14 | **274** | 2 | 0 | **672** |
| 12:45:00 | 39 | 25 | 36 | 0 | **100** | 1 | 2 | 29 | 253 | 18 | 3 | **303** | 0 | 2 | 5 | 24 | 18 | 0 | **47** | 0 | 0 | 21 | 193 | 26 | 11 | **251** | 0 | 0 | **701** |
| **Hourly Total** | 199 | 112 | 114 | 0 | **425** | 8 | 3 | 112 | 926 | 75 | 8 | **1121** | 0 | 2 | 25 | 85 | 76 | 0 | **186** | 1 | 1 | 78 | 816 | 159 | 41 | **1094** | 6 | 1 | **2826** |
| 13:00:00 | 55 | 26 | 33 | 0 | **114** | 3 | 0 | 19 | 251 | 24 | 4 | **298** | 2 | 0 | 6 | 30 | 17 | 0 | **53** | 0 | 1 | 26 | 196 | 42 | 12 | **276** | 0 | 0 | **741** |
| 13:15:00 | 46 | 23 | 33 | 0 | **102** | 1 | 0 | 20 | 218 | 17 | 1 | **256** | 0 | 0 | 8 | 35 | 21 | 0 | **64** | 1 | 0 | 15 | 172 | 50 | 10 | **247** | 0 | 0 | **669** |
| 13:30:00 | 48 | 28 | 24 | 0 | **100** | 1 | 0 | 31 | 274 | 21 | 1 | **327** | 0 | 1 | 6 | 17 | 16 | 0 | **39** | 0 | 0 | 23 | 193 | 21 | 7 | **244** | 0 | 0 | **710** |
| 13:45:00 | 49 | 37 | 37 | 0 | **123** | 2 | 0 | 27 | 222 | 13 | 4 | **266** | 0 | 0 | 5 | 30 | 17 | 0 | **52** | 0 | 0 | 23 | 187 | 48 | 6 | **264** | 0 | 0 | **705** |
| **Hourly Total** | 198 | 114 | 127 | 0 | **439** | 7 | 0 | 97 | 965 | 75 | 10 | **1147** | 2 | 1 | 25 | 112 | 71 | 0 | **208** | 1 | 1 | 87 | 748 | 161 | 35 | **1031** | 0 | 0 | **2825** |
| 14:00:00 | 51 | 35 | 47 | 0 | **133** | 0 | 1 | 20 | 209 | 10 | 3 | **242** | 0 | 0 | 19 | 18 | 17 | 0 | **54** | 0 | 0 | 23 | 192 | 33 | 6 | **254** | 0 | 1 | **683** |
| 14:15:00 | 44 | 32 | 23 | 0 | **99** | 0 | 2 | 20 | 231 | 20 | 1 | **272** | 0 | 0 | 7 | 26 | 16 | 0 | **49** | 2 | 1 | 18 | 219 | 45 | 14 | **296** | 0 | 1 | **716** |
| 14:30:00 | 69 | 35 | 32 | 0 | **136** | 0 | 0 | 23 | 212 | 16 | 1 | **252** | 0 | 0 | 8 | 15 | 10 | 0 | **33** | 1 | 0 | 21 | 173 | 35 | 7 | **236** | 0 | 2 | **657** |
| 14:45:00 | 47 | 36 | 37 | 0 | **120** | 5 | 3 | 16 | 244 | 25 | 3 | **288** | 0 | 0 | 4 | 21 | 17 | 0 | **42** | 0 | 2 | 28 | 192 | 33 | 8 | **261** | 0 | 1 | **711** |
| **Hourly Total** | 211 | 138 | 139 | 0 | **488** | 5 | 6 | 79 | 896 | 71 | 8 | **1054** | 0 | 0 | 38 | 80 | 60 | 0 | **178** | 3 | 3 | 90 | 776 | 146 | 35 | **1047** | 0 | 5 | **2767** |
| **Grand Total** | 608 | 364 | 380 | 0 | **1352** | 20 | 9 | 288 | 2787 | 221 | 26 | **3322** | 2 | 3 | 88 | 277 | 207 | 0 | **572** | 5 | 5 | 255 | 2340 | 466 | 111 | **3172** | 6 | 6 | **8418** |
| **% Approach** | 45.0% | 26.9% | 28.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.7% | 83.9% | 6.7% | 0.8% | **0.0%** | 0.0% | 0.0% | 15.4% | 48.4% | 36.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.0% | 73.8% | 14.7% | 3.5% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 7.2% | 4.3% | 4.5% | 0.0% | **16.1%** | 0.0% | 0.0% | 3.4% | 33.1% | 2.6% | 0.3% | **39.5%** | 0.0% | 0.0% | 1.0% | 3.3% | 2.5% | 0.0% | **6.8%** | 0.0% | 0.0% | 3.0% | 27.8% | 5.5% | 1.3% | **37.7%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 434 | 363 | 377 | 0 | **1174** | 0 | 0 | 248 | 2774 | 221 | 26 | **3269** | 0 | 0 | 80 | 274 | 207 | 0 | **561** | 0 | 0 | 210 | 2328 | 462 | 111 | **3111** | 0 | 0 | **8115** |
| **% Lights** | 71.4% | 99.7% | 99.2% | 0.0% | **86.8%** | 0.0% | 0.0% | 86.1% | 99.5% | 100.0% | 100.0% | **98.4%** | 0.0% | 0.0% | 90.9% | 98.9% | 100.0% | 0.0% | **98.1%** | 0.0% | 0.0% | 82.4% | 99.5% | 99.1% | 100.0% | **98.1%** | 0.0% | 0.0% | **96.4%** |
| **Trucks** | 0 | 0 | 3 | 0 | **3** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 10 | 0 | 0 | **10** | 0 | 0 | **20** |
| **% Trucks** | 0.0% | 0.0% | 0.8% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 6 | 3 | 0 | 0 | **9** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 4 | 0 | **5** | 0 | 0 | **15** |
| **% Buses** | 0.2% | 0.0% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.9% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 20 | 8 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 5 | 4 | 0 | 0 | 0 | 0 | **0** | 5 | 6 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 88.9% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 80.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 11.1% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


## Summary


# Turning Movement Peak Hour Data (PM)

**12:15:00**

| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:15:00 | 45 | 24 | 20 | 0 | **89** | 3 | 0 | 26 | 252 | 27 | 3 | **308** | 0 | 0 | 10 | 16 | 22 | 0 | **48** | 0 | 0 | 23 | 196 | 57 | 12 | **288** | 2 | 1 | **733** |
| 12:30:00 | 55 | 27 | 26 | 0 | **108** | 3 | 1 | 28 | 211 | 10 | 0 | **249** | 0 | 0 | 4 | 19 | 18 | 0 | **41** | 1 | 1 | 17 | 198 | 45 | 14 | **274** | 2 | 0 | **672** |
| 12:45:00 | 39 | 25 | 36 | 0 | **100** | 1 | 2 | 29 | 253 | 18 | 3 | **303** | 0 | 2 | 5 | 24 | 18 | 0 | **47** | 0 | 0 | 21 | 193 | 26 | 11 | **251** | 0 | 0 | **701** |
| 13:00:00 | 55 | 26 | 33 | 0 | **114** | 3 | 0 | 19 | 251 | 24 | 4 | **298** | 2 | 0 | 6 | 30 | 17 | 0 | **53** | 0 | 1 | 26 | 196 | 42 | 12 | **276** | 0 | 0 | **741** |
| **Grand Total** | 194 | 102 | 115 | 0 | **411** | 10 | 3 | 102 | 967 | 79 | 10 | **1158** | 2 | 2 | 25 | 89 | 75 | 0 | **189** | 1 | 2 | 87 | 783 | 170 | 49 | **1089** | 4 | 1 | **2847** |
| **% Approach** | 47.2% | 24.8% | 28.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.8% | 83.5% | 6.8% | 0.9% | **0.0%** | 0.0% | 0.0% | 13.2% | 47.1% | 39.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.0% | 71.9% | 15.6% | 4.5% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 6.8% | 3.6% | 4.0% | 0.0% | **14.4%** | 0.0% | 0.0% | 3.6% | 34.0% | 2.8% | 0.4% | **40.7%** | 0.0% | 0.0% | 0.9% | 3.1% | 2.6% | 0.0% | **6.6%** | 0.0% | 0.0% | 3.1% | 27.5% | 6.0% | 1.7% | **38.3%** | 0.0% | 0.0% | |
| **PHF** | 0.882 | 0.944 | 0.799 | 0.000 | **0.901** | 0.000 | 0.000 | 0.879 | 0.956 | 0.731 | 0.625 | **0.940** | 0.000 | 0.000 | 0.625 | 0.742 | 0.852 | 0.000 | **0.892** | 0.000 | 0.000 | 0.837 | 0.989 | 0.746 | 0.875 | **0.945** | 0.000 | 0.000 | **0.961** |
| **Lights** | 129 | 101 | 114 | 0 | **344** | 0 | 0 | 91 | 963 | 79 | 10 | **1143** | 0 | 0 | 25 | 89 | 75 | 0 | **189** | 0 | 0 | 73 | 778 | 169 | 49 | **1069** | 0 | 0 | **2745** |
| **% Lights** | 66.5% | 99.0% | 99.1% | 0.0% | **83.7%** | 0.0% | 0.0% | 89.2% | 99.6% | 100.0% | 100.0% | **98.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 83.9% | 99.4% | 99.4% | 100.0% | **98.2%** | 0.0% | 0.0% | **96.4%** |
| **Trucks** | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | **7** |
| **% Trucks** | 0.0% | 0.0% | 0.9% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | **3** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.6% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 10 | 2 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 75.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 25.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 60 | 36 | 32 | 0 | **128** | 1 | 0 | 29 | 210 | 20 | 2 | **261** | 0 | 0 | 6 | 26 | 18 | 0 | **50** | 0 | 0 | 17 | 229 | 31 | 4 | **281** | 2 | 0 | **720** |
| 12:15:00 | 45 | 24 | 20 | 0 | **89** | 3 | 0 | 26 | 252 | 27 | 3 | **308** | 0 | 0 | 10 | 16 | 22 | 0 | **48** | 0 | 0 | 23 | 196 | 57 | 12 | **288** | 2 | 1 | **733** |
| 12:30:00 | 55 | 27 | 26 | 0 | **108** | 3 | 1 | 28 | 211 | 10 | 0 | **249** | 0 | 0 | 4 | 19 | 18 | 0 | **41** | 1 | 1 | 17 | 198 | 45 | 14 | **274** | 2 | 0 | **672** |
| 12:45:00 | 39 | 25 | 36 | 0 | **100** | 1 | 2 | 29 | 253 | 18 | 3 | **303** | 0 | 2 | 5 | 24 | 18 | 0 | **47** | 0 | 0 | 21 | 193 | 26 | 11 | **251** | 0 | 0 | **701** |
| **Hourly Total** | 199 | 112 | 114 | 0 | **425** | 8 | 3 | 112 | 926 | 75 | 8 | **1121** | 0 | 2 | 25 | 85 | 76 | 0 | **186** | 1 | 1 | 78 | 816 | 159 | 41 | **1094** | 6 | 1 | **2826** |
| 13:00:00 | 55 | 26 | 33 | 0 | **114** | 3 | 0 | 19 | 251 | 24 | 4 | **298** | 2 | 0 | 6 | 30 | 17 | 0 | **53** | 0 | 1 | 26 | 196 | 42 | 12 | **276** | 0 | 0 | **741** |
| 13:15:00 | 46 | 23 | 33 | 0 | **102** | 1 | 0 | 20 | 218 | 17 | 1 | **256** | 0 | 0 | 8 | 35 | 21 | 0 | **64** | 1 | 0 | 15 | 172 | 50 | 10 | **247** | 0 | 0 | **669** |
| 13:30:00 | 48 | 28 | 24 | 0 | **100** | 1 | 0 | 31 | 274 | 21 | 1 | **327** | 0 | 1 | 6 | 17 | 16 | 0 | **39** | 0 | 0 | 23 | 193 | 21 | 7 | **244** | 0 | 0 | **710** |
| 13:45:00 | 49 | 37 | 37 | 0 | **123** | 2 | 0 | 27 | 222 | 13 | 4 | **266** | 0 | 0 | 5 | 30 | 17 | 0 | **52** | 0 | 0 | 23 | 187 | 48 | 6 | **264** | 0 | 0 | **705** |
| **Hourly Total** | 198 | 114 | 127 | 0 | **439** | 7 | 0 | 97 | 965 | 75 | 10 | **1147** | 2 | 1 | 25 | 112 | 71 | 0 | **208** | 1 | 1 | 87 | 748 | 161 | 35 | **1031** | 0 | 0 | **2825** |
| 14:00:00 | 51 | 35 | 47 | 0 | **133** | 0 | 1 | 20 | 209 | 10 | 3 | **242** | 0 | 0 | 19 | 18 | 17 | 0 | **54** | 0 | 0 | 23 | 192 | 33 | 6 | **254** | 0 | 1 | **683** |
| 14:15:00 | 44 | 32 | 23 | 0 | **99** | 0 | 2 | 20 | 231 | 20 | 1 | **272** | 0 | 0 | 7 | 26 | 16 | 0 | **49** | 2 | 1 | 18 | 219 | 45 | 14 | **296** | 0 | 1 | **716** |
| 14:30:00 | 69 | 35 | 32 | 0 | **136** | 0 | 0 | 23 | 212 | 16 | 1 | **252** | 0 | 0 | 8 | 15 | 10 | 0 | **33** | 1 | 0 | 21 | 173 | 35 | 7 | **236** | 0 | 2 | **657** |
| 14:45:00 | 47 | 36 | 37 | 0 | **120** | 5 | 3 | 16 | 244 | 25 | 3 | **288** | 0 | 0 | 4 | 21 | 17 | 0 | **42** | 0 | 2 | 28 | 192 | 33 | 8 | **261** | 0 | 1 | **711** |
| **Hourly Total** | 211 | 138 | 139 | 0 | **488** | 5 | 6 | 79 | 896 | 71 | 8 | **1054** | 0 | 0 | 38 | 80 | 60 | 0 | **178** | 3 | 3 | 90 | 776 | 146 | 35 | **1047** | 0 | 5 | **2767** |
| **Grand Total** | 608 | 364 | 380 | 0 | **1352** | 20 | 9 | 288 | 2787 | 221 | 26 | **3322** | 2 | 3 | 88 | 277 | 207 | 0 | **572** | 5 | 5 | 255 | 2340 | 466 | 111 | **3172** | 6 | 6 | **8418** |
| **% Approach** | 45.0% | 26.9% | 28.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.7% | 83.9% | 6.7% | 0.8% | **0.0%** | 0.0% | 0.0% | 15.4% | 48.4% | 36.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.0% | 73.8% | 14.7% | 3.5% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 7.2% | 4.3% | 4.5% | 0.0% | **16.1%** | 0.0% | 0.0% | 3.4% | 33.1% | 2.6% | 0.3% | **39.5%** | 0.0% | 0.0% | 1.0% | 3.3% | 2.5% | 0.0% | **6.8%** | 0.0% | 0.0% | 3.0% | 27.8% | 5.5% | 1.3% | **37.7%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 434 | 363 | 377 | 0 | **1174** | 0 | 0 | 248 | 2774 | 221 | 26 | **3269** | 0 | 0 | 80 | 274 | 207 | 0 | **561** | 0 | 0 | 210 | 2328 | 462 | 111 | **3111** | 0 | 0 | **8115** |
| **% Lights** | 71.4% | 99.7% | 99.2% | 0.0% | **86.8%** | 0.0% | 0.0% | 86.1% | 99.5% | 100.0% | 100.0% | **98.4%** | 0.0% | 0.0% | 90.9% | 98.9% | 100.0% | 0.0% | **98.1%** | 0.0% | 0.0% | 82.4% | 99.5% | 99.1% | 100.0% | **98.1%** | 0.0% | 0.0% | **96.4%** |
| **Trucks** | 0 | 0 | 3 | 0 | **3** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 10 | 0 | 0 | **10** | 0 | 0 | **20** |
| **% Trucks** | 0.0% | 0.0% | 0.8% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 6 | 3 | 0 | 0 | **9** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 4 | 0 | **5** | 0 | 0 | **15** |
| **% Buses** | 0.2% | 0.0% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.9% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 20 | 8 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 5 | 4 | 0 | 0 | 0 | 0 | **0** | 5 | 6 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 88.9% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 80.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 11.1% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 0.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**12:15:00**

| Leg | Alberta Drive | | | | | | | Sheridan Drive | | | | | | | Unnamed Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:15:00 | 45 | 24 | 20 | 0 | **89** | 3 | 0 | 26 | 252 | 27 | 3 | **308** | 0 | 0 | 10 | 16 | 22 | 0 | **48** | 0 | 0 | 23 | 196 | 57 | 12 | **288** | 2 | 1 | **733** |
| 12:30:00 | 55 | 27 | 26 | 0 | **108** | 3 | 1 | 28 | 211 | 10 | 0 | **249** | 0 | 0 | 4 | 19 | 18 | 0 | **41** | 1 | 1 | 17 | 198 | 45 | 14 | **274** | 2 | 0 | **672** |
| 12:45:00 | 39 | 25 | 36 | 0 | **100** | 1 | 2 | 29 | 253 | 18 | 3 | **303** | 0 | 2 | 5 | 24 | 18 | 0 | **47** | 0 | 0 | 21 | 193 | 26 | 11 | **251** | 0 | 0 | **701** |
| 13:00:00 | 55 | 26 | 33 | 0 | **114** | 3 | 0 | 19 | 251 | 24 | 4 | **298** | 2 | 0 | 6 | 30 | 17 | 0 | **53** | 0 | 1 | 26 | 196 | 42 | 12 | **276** | 0 | 0 | **741** |
| **Grand Total** | 194 | 102 | 115 | 0 | **411** | 10 | 3 | 102 | 967 | 79 | 10 | **1158** | 2 | 2 | 25 | 89 | 75 | 0 | **189** | 1 | 2 | 87 | 783 | 170 | 49 | **1089** | 4 | 1 | **2847** |
| **% Approach** | 47.2% | 24.8% | 28.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.8% | 83.5% | 6.8% | 0.9% | **0.0%** | 0.0% | 0.0% | 13.2% | 47.1% | 39.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.0% | 71.9% | 15.6% | 4.5% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 6.8% | 3.6% | 4.0% | 0.0% | **14.4%** | 0.0% | 0.0% | 3.6% | 34.0% | 2.8% | 0.4% | **40.7%** | 0.0% | 0.0% | 0.9% | 3.1% | 2.6% | 0.0% | **6.6%** | 0.0% | 0.0% | 3.1% | 27.5% | 6.0% | 1.7% | **38.3%** | 0.0% | 0.0% | |
| **PHF** | 0.882 | 0.944 | 0.799 | 0.000 | **0.901** | 0.000 | 0.000 | 0.879 | 0.956 | 0.731 | 0.625 | **0.940** | 0.000 | 0.000 | 0.625 | 0.742 | 0.852 | 0.000 | **0.892** | 0.000 | 0.000 | 0.837 | 0.989 | 0.746 | 0.875 | **0.945** | 0.000 | 0.000 | **0.961** |
| **Lights** | 129 | 101 | 114 | 0 | **344** | 0 | 0 | 91 | 963 | 79 | 10 | **1143** | 0 | 0 | 25 | 89 | 75 | 0 | **189** | 0 | 0 | 73 | 778 | 169 | 49 | **1069** | 0 | 0 | **2745** |
| **% Lights** | 66.5% | 99.0% | 99.1% | 0.0% | **83.7%** | 0.0% | 0.0% | 89.2% | 99.6% | 100.0% | 100.0% | **98.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 83.9% | 99.4% | 99.4% | 100.0% | **98.2%** | 0.0% | 0.0% | **96.4%** |
| **Trucks** | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | **7** |
| **% Trucks** | 0.0% | 0.0% | 0.9% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | **3** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.6% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 10 | 2 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 75.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 25.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Bailey Ave |
| **Legs and Movements** | All Processed Legs & Move |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Sheridan Drive & Bailey Ave |
| **Latitude and Longitude** | 42.98023, -78.81391 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:15:00 | 2023-11-16 17:15:00 | 0.981 |


## Turning Movement Data


| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 20 | 69 | 36 | 0 | **125** | 2 | 1 | 22 | 223 | 16 | 0 | **261** | 0 | 0 | 17 | 63 | 13 | 0 | **93** | 0 | 0 | 9 | 193 | 21 | 5 | **228** | 0 | 0 | **707** |
| 3:15:00 PM | 11 | 74 | 39 | 0 | **124** | 0 | 4 | 22 | 205 | 26 | 3 | **256** | 1 | 0 | 27 | 89 | 34 | 0 | **150** | 1 | 2 | 9 | 155 | 27 | 3 | **194** | 0 | 0 | **724** |
| 3:30:00 PM | 9 | 69 | 32 | 0 | **110** | 1 | 0 | 22 | 234 | 18 | 5 | **279** | 0 | 2 | 26 | 83 | 25 | 0 | **134** | 1 | 1 | 12 | 182 | 31 | 2 | **227** | 0 | 0 | **750** |
| 3:45:00 PM | 11 | 78 | 38 | 0 | **127** | 2 | 2 | 32 | 222 | 27 | 1 | **282** | 0 | 0 | 18 | 95 | 19 | 0 | **132** | 0 | 0 | 8 | 182 | 43 | 2 | **235** | 0 | 0 | **776** |
| **Hourly Total** | 51 | 290 | 145 | 0 | **486** | 5 | 7 | 98 | 884 | 87 | 9 | **1078** | 1 | 2 | 88 | 330 | 91 | 0 | **509** | 2 | 3 | 38 | 712 | 122 | 12 | **884** | 0 | 0 | **2957** |
| 4:00:00 PM | 26 | 80 | 56 | 0 | **162** | 1 | 1 | 29 | 176 | 27 | 0 | **232** | 2 | 1 | 20 | 96 | 35 | 0 | **151** | 1 | 0 | 17 | 153 | 31 | 2 | **203** | 2 | 0 | **748** |
| 4:15:00 PM | 18 | 72 | 40 | 0 | **130** | 2 | 0 | 30 | 267 | 20 | 2 | **319** | 0 | 0 | 12 | 71 | 31 | 0 | **114** | 3 | 0 | 19 | 187 | 24 | 10 | **240** | 2 | 1 | **803** |
| 4:30:00 PM | 27 | 71 | 26 | 0 | **124** | 1 | 0 | 26 | 229 | 23 | 2 | **280** | 0 | 0 | 22 | 96 | 20 | 0 | **138** | 0 | 0 | 15 | 194 | 26 | 4 | **239** | 0 | 0 | **781** |
| 4:45:00 PM | 29 | 92 | 34 | 0 | **155** | 1 | 1 | 30 | 218 | 28 | 3 | **279** | 1 | 1 | 25 | 101 | 28 | 0 | **154** | 1 | 1 | 12 | 169 | 23 | 3 | **207** | 1 | 1 | **795** |
| **Hourly Total** | 100 | 315 | 156 | 0 | **571** | 5 | 2 | 115 | 890 | 98 | 7 | **1110** | 3 | 2 | 79 | 364 | 114 | 0 | **557** | 5 | 1 | 63 | 703 | 104 | 19 | **889** | 5 | 2 | **3127** |
| 5:00:00 PM | 17 | 79 | 26 | 0 | **122** | 2 | 3 | 32 | 254 | 32 | 3 | **321** | 0 | 0 | 24 | 83 | 25 | 0 | **132** | 1 | 0 | 13 | 187 | 32 | 7 | **239** | 0 | 1 | **814** |
| 5:15:00 PM | 15 | 93 | 32 | 0 | **140** | 0 | 2 | 21 | 215 | 32 | 1 | **269** | 0 | 0 | 17 | 91 | 22 | 0 | **130** | 0 | 0 | 15 | 171 | 28 | 6 | **220** | 0 | 1 | **759** |
| 5:30:00 PM | 15 | 88 | 35 | 0 | **138** | 0 | 0 | 27 | 246 | 27 | 0 | **300** | 0 | 0 | 23 | 80 | 27 | 0 | **130** | 0 | 0 | 15 | 189 | 29 | 3 | **236** | 0 | 0 | **804** |
| 5:45:00 PM | 7 | 82 | 37 | 0 | **126** | 1 | 0 | 30 | 218 | 29 | 2 | **279** | 0 | 0 | 18 | 79 | 22 | 0 | **119** | 0 | 0 | 5 | 175 | 28 | 6 | **214** | 0 | 0 | **738** |
| **Hourly Total** | 54 | 342 | 130 | 0 | **526** | 3 | 5 | 110 | 933 | 120 | 6 | **1169** | 0 | 0 | 82 | 333 | 96 | 0 | **511** | 1 | 0 | 48 | 722 | 117 | 22 | **909** | 0 | 2 | **3115** |
| **Grand Total** | 205 | 947 | 431 | 0 | **1583** | 13 | 14 | 323 | 2707 | 305 | 22 | **3357** | 4 | 4 | 249 | 1027 | 301 | 0 | **1577** | 8 | 4 | 149 | 2137 | 343 | 53 | **2682** | 5 | 4 | **9199** |
| **% Approach** | 13.0% | 59.8% | 27.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.6% | 80.6% | 9.1% | 0.7% | **0.0%** | 0.0% | 0.0% | 15.8% | 65.1% | 19.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.6% | 79.7% | 12.8% | 2.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 2.2% | 10.3% | 4.7% | 0.0% | **17.2%** | 0.0% | 0.0% | 3.5% | 29.4% | 3.3% | 0.2% | **36.5%** | 0.0% | 0.0% | 2.7% | 11.2% | 3.3% | 0.0% | **17.1%** | 0.0% | 0.0% | 1.6% | 23.2% | 3.7% | 0.6% | **29.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 199 | 944 | 426 | 0 | **1569** | 0 | 0 | 318 | 2685 | 301 | 21 | **3325** | 0 | 0 | 235 | 1019 | 299 | 0 | **1553** | 0 | 0 | 140 | 2113 | 339 | 53 | **2645** | 0 | 0 | **9092** |
| **% Lights** | 97.1% | 99.7% | 98.8% | 0.0% | **99.1%** | 0.0% | 0.0% | 98.5% | 99.2% | 98.7% | 95.5% | **99.0%** | 0.0% | 0.0% | 94.4% | 99.2% | 99.3% | 0.0% | **98.5%** | 0.0% | 0.0% | 94.0% | 98.9% | 98.8% | 100.0% | **98.6%** | 0.0% | 0.0% | **98.8%** |
| **Trucks** | 2 | 2 | 3 | 0 | **7** | 0 | 0 | 2 | 14 | 1 | 1 | **18** | 0 | 0 | 3 | 3 | 0 | 0 | **6** | 0 | 0 | 0 | 18 | 3 | 0 | **21** | 0 | 0 | **52** |
| **% Trucks** | 1.0% | 0.2% | 0.7% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.6% | 0.5% | 0.3% | 4.5% | **0.5%** | 0.0% | 0.0% | 1.2% | 0.3% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.8% | 0.9% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 1 | 1 | 2 | 0 | **4** | 0 | 0 | 1 | 6 | 2 | 0 | **9** | 0 | 0 | 2 | 4 | 2 | 0 | **8** | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | **25** |
| **% Buses** | 0.5% | 0.1% | 0.5% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.7% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.8% | 0.4% | 0.7% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.3% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 11 | 12 | 0 | 0 | 0 | 0 | **0** | 4 | 2 | 0 | 0 | 0 | 0 | **0** | 7 | 3 | 0 | 0 | 0 | 0 | **0** | 5 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 84.6% | 85.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 87.5% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 15.4% | 14.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 12.5% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**4:15:00 PM**

| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:15:00 PM | 18 | 72 | 40 | 0 | **130** | 2 | 0 | 30 | 267 | 20 | 2 | **319** | 0 | 0 | 12 | 71 | 31 | 0 | **114** | 3 | 0 | 19 | 187 | 24 | 10 | **240** | 2 | 1 | **803** |
| 4:30:00 PM | 27 | 71 | 26 | 0 | **124** | 1 | 0 | 26 | 229 | 23 | 2 | **280** | 0 | 0 | 22 | 96 | 20 | 0 | **138** | 0 | 0 | 15 | 194 | 26 | 4 | **239** | 0 | 0 | **781** |
| 4:45:00 PM | 29 | 92 | 34 | 0 | **155** | 1 | 1 | 30 | 218 | 28 | 3 | **279** | 1 | 1 | 25 | 101 | 28 | 0 | **154** | 1 | 1 | 12 | 169 | 23 | 3 | **207** | 1 | 1 | **795** |
| 5:00:00 PM | 17 | 79 | 26 | 0 | **122** | 2 | 3 | 32 | 254 | 32 | 3 | **321** | 0 | 0 | 24 | 83 | 25 | 0 | **132** | 1 | 0 | 13 | 187 | 32 | 7 | **239** | 0 | 1 | **814** |
| **Grand Total** | 91 | 314 | 126 | 0 | **531** | 6 | 4 | 118 | 968 | 103 | 10 | **1199** | 1 | 1 | 83 | 351 | 104 | 0 | **538** | 5 | 1 | 59 | 737 | 105 | 24 | **925** | 3 | 3 | **3193** |
| **% Approach** | 17.1% | 59.1% | 23.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.8% | 80.7% | 8.6% | 0.8% | **0.0%** | 0.0% | 0.0% | 15.4% | 65.2% | 19.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 79.7% | 11.4% | 2.6% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 2.8% | 9.8% | 3.9% | 0.0% | **16.6%** | 0.0% | 0.0% | 3.7% | 30.3% | 3.2% | 0.3% | **37.6%** | 0.0% | 0.0% | 2.6% | 11.0% | 3.3% | 0.0% | **16.8%** | 0.0% | 0.0% | 1.8% | 23.1% | 3.3% | 0.8% | **29.0%** | 0.0% | 0.0% | |
| **PHF** | 0.784 | 0.853 | 0.788 | 0.000 | **0.856** | 0.000 | 0.000 | 0.922 | 0.906 | 0.805 | 0.833 | **0.934** | 0.000 | 0.000 | 0.830 | 0.869 | 0.839 | 0.000 | **0.873** | 0.000 | 0.000 | 0.776 | 0.950 | 0.820 | 0.600 | **0.964** | 0.000 | 0.000 | **0.981** |
| **Lights** | 86 | 314 | 124 | 0 | **524** | 0 | 0 | 117 | 962 | 102 | 9 | **1190** | 0 | 0 | 78 | 349 | 104 | 0 | **531** | 0 | 0 | 54 | 733 | 102 | 24 | **913** | 0 | 0 | **3158** |
| **% Lights** | 94.5% | 100.0% | 98.4% | 0.0% | **98.7%** | 0.0% | 0.0% | 99.2% | 99.4% | 99.0% | 90.0% | **99.2%** | 0.0% | 0.0% | 94.0% | 99.4% | 100.0% | 0.0% | **98.7%** | 0.0% | 0.0% | 91.5% | 99.5% | 97.1% | 100.0% | **98.7%** | 0.0% | 0.0% | **98.9%** |
| **Trucks** | 2 | 0 | 2 | 0 | **4** | 0 | 0 | 0 | 3 | 0 | 1 | **4** | 0 | 0 | 2 | 2 | 0 | 0 | **4** | 0 | 0 | 0 | 3 | 2 | 0 | **5** | 0 | 0 | **17** |
| **% Trucks** | 2.2% | 0.0% | 1.6% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 10.0% | **0.3%** | 0.0% | 0.0% | 2.4% | 0.6% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.4% | 1.9% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.5%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **5** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 1.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 1.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 5 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 5 | 1 | 0 | 0 | 0 | 0 | **0** | 3 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 20 | 69 | 36 | 0 | **125** | 2 | 1 | 22 | 223 | 16 | 0 | **261** | 0 | 0 | 17 | 63 | 13 | 0 | **93** | 0 | 0 | 9 | 193 | 21 | 5 | **228** | 0 | 0 | **707** |
| 3:15:00 PM | 11 | 74 | 39 | 0 | **124** | 0 | 4 | 22 | 205 | 26 | 3 | **256** | 1 | 0 | 27 | 89 | 34 | 0 | **150** | 1 | 2 | 9 | 155 | 27 | 3 | **194** | 0 | 0 | **724** |
| 3:30:00 PM | 9 | 69 | 32 | 0 | **110** | 1 | 0 | 22 | 234 | 18 | 5 | **279** | 0 | 2 | 26 | 83 | 25 | 0 | **134** | 1 | 1 | 12 | 182 | 31 | 2 | **227** | 0 | 0 | **750** |
| 3:45:00 PM | 11 | 78 | 38 | 0 | **127** | 2 | 2 | 32 | 222 | 27 | 1 | **282** | 0 | 0 | 18 | 95 | 19 | 0 | **132** | 0 | 0 | 8 | 182 | 43 | 2 | **235** | 0 | 0 | **776** |
| **Hourly Total** | 51 | 290 | 145 | 0 | **486** | 5 | 7 | 98 | 884 | 87 | 9 | **1078** | 1 | 2 | 88 | 330 | 91 | 0 | **509** | 2 | 3 | 38 | 712 | 122 | 12 | **884** | 0 | 0 | **2957** |
| 4:00:00 PM | 26 | 80 | 56 | 0 | **162** | 1 | 1 | 29 | 176 | 27 | 0 | **232** | 2 | 1 | 20 | 96 | 35 | 0 | **151** | 1 | 0 | 17 | 153 | 31 | 2 | **203** | 2 | 0 | **748** |
| 4:15:00 PM | 18 | 72 | 40 | 0 | **130** | 2 | 0 | 30 | 267 | 20 | 2 | **319** | 0 | 0 | 12 | 71 | 31 | 0 | **114** | 3 | 0 | 19 | 187 | 24 | 10 | **240** | 2 | 1 | **803** |
| 4:30:00 PM | 27 | 71 | 26 | 0 | **124** | 1 | 0 | 26 | 229 | 23 | 2 | **280** | 0 | 0 | 22 | 96 | 20 | 0 | **138** | 0 | 0 | 15 | 194 | 26 | 4 | **239** | 0 | 0 | **781** |
| 4:45:00 PM | 29 | 92 | 34 | 0 | **155** | 1 | 1 | 30 | 218 | 28 | 3 | **279** | 1 | 1 | 25 | 101 | 28 | 0 | **154** | 1 | 1 | 12 | 169 | 23 | 3 | **207** | 1 | 1 | **795** |
| **Hourly Total** | 100 | 315 | 156 | 0 | **571** | 5 | 2 | 115 | 890 | 98 | 7 | **1110** | 3 | 2 | 79 | 364 | 114 | 0 | **557** | 5 | 1 | 63 | 703 | 104 | 19 | **889** | 5 | 2 | **3127** |
| 5:00:00 PM | 17 | 79 | 26 | 0 | **122** | 2 | 3 | 32 | 254 | 32 | 3 | **321** | 0 | 0 | 24 | 83 | 25 | 0 | **132** | 1 | 0 | 13 | 187 | 32 | 7 | **239** | 0 | 1 | **814** |
| 5:15:00 PM | 15 | 93 | 32 | 0 | **140** | 0 | 2 | 21 | 215 | 32 | 1 | **269** | 0 | 0 | 17 | 91 | 22 | 0 | **130** | 0 | 0 | 15 | 171 | 28 | 6 | **220** | 0 | 1 | **759** |
| 5:30:00 PM | 15 | 88 | 35 | 0 | **138** | 0 | 0 | 27 | 246 | 27 | 0 | **300** | 0 | 0 | 23 | 80 | 27 | 0 | **130** | 0 | 0 | 15 | 189 | 29 | 3 | **236** | 0 | 0 | **804** |
| 5:45:00 PM | 7 | 82 | 37 | 0 | **126** | 1 | 0 | 30 | 218 | 29 | 2 | **279** | 0 | 0 | 18 | 79 | 22 | 0 | **119** | 0 | 0 | 5 | 175 | 28 | 6 | **214** | 0 | 0 | **738** |
| **Hourly Total** | 54 | 342 | 130 | 0 | **526** | 3 | 5 | 110 | 933 | 120 | 6 | **1169** | 0 | 0 | 82 | 333 | 96 | 0 | **511** | 1 | 0 | 48 | 722 | 117 | 22 | **909** | 0 | 2 | **3115** |
| **Grand Total** | 205 | 947 | 431 | 0 | **1583** | 13 | 14 | 323 | 2707 | 305 | 22 | **3357** | 4 | 4 | 249 | 1027 | 301 | 0 | **1577** | 8 | 4 | 149 | 2137 | 343 | 53 | **2682** | 5 | 4 | **9199** |
| **% Approach** | 13.0% | 59.8% | 27.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.6% | 80.6% | 9.1% | 0.7% | **0.0%** | 0.0% | 0.0% | 15.8% | 65.1% | 19.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.6% | 79.7% | 12.8% | 2.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 2.2% | 10.3% | 4.7% | 0.0% | **17.2%** | 0.0% | 0.0% | 3.5% | 29.4% | 3.3% | 0.2% | **36.5%** | 0.0% | 0.0% | 2.7% | 11.2% | 3.3% | 0.0% | **17.1%** | 0.0% | 0.0% | 1.6% | 23.2% | 3.7% | 0.6% | **29.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 199 | 944 | 426 | 0 | **1569** | 0 | 0 | 318 | 2685 | 301 | 21 | **3325** | 0 | 0 | 235 | 1019 | 299 | 0 | **1553** | 0 | 0 | 140 | 2113 | 339 | 53 | **2645** | 0 | 0 | **9092** |
| **% Lights** | 97.1% | 99.7% | 98.8% | 0.0% | **99.1%** | 0.0% | 0.0% | 98.5% | 99.2% | 98.7% | 95.5% | **99.0%** | 0.0% | 0.0% | 94.4% | 99.2% | 99.3% | 0.0% | **98.5%** | 0.0% | 0.0% | 94.0% | 98.9% | 98.8% | 100.0% | **98.6%** | 0.0% | 0.0% | **98.8%** |
| **Trucks** | 2 | 2 | 3 | 0 | **7** | 0 | 0 | 2 | 14 | 1 | 1 | **18** | 0 | 0 | 3 | 3 | 0 | 0 | **6** | 0 | 0 | 0 | 18 | 3 | 0 | **21** | 0 | 0 | **52** |
| **% Trucks** | 1.0% | 0.2% | 0.7% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.6% | 0.5% | 0.3% | 4.5% | **0.5%** | 0.0% | 0.0% | 1.2% | 0.3% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.8% | 0.9% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 1 | 1 | 2 | 0 | **4** | 0 | 0 | 1 | 6 | 2 | 0 | **9** | 0 | 0 | 2 | 4 | 2 | 0 | **8** | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | **25** |
| **% Buses** | 0.5% | 0.1% | 0.5% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.7% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.8% | 0.4% | 0.7% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.3% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 11 | 12 | 0 | 0 | 0 | 0 | **0** | 4 | 2 | 0 | 0 | 0 | 0 | **0** | 7 | 3 | 0 | 0 | 0 | 0 | **0** | 5 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 84.6% | 85.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 87.5% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 15.4% | 14.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 12.5% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**4:15:00 PM**

| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:15:00 PM | 18 | 72 | 40 | 0 | **130** | 2 | 0 | 30 | 267 | 20 | 2 | **319** | 0 | 0 | 12 | 71 | 31 | 0 | **114** | 3 | 0 | 19 | 187 | 24 | 10 | **240** | 2 | 1 | **803** |
| 4:30:00 PM | 27 | 71 | 26 | 0 | **124** | 1 | 0 | 26 | 229 | 23 | 2 | **280** | 0 | 0 | 22 | 96 | 20 | 0 | **138** | 0 | 0 | 15 | 194 | 26 | 4 | **239** | 0 | 0 | **781** |
| 4:45:00 PM | 29 | 92 | 34 | 0 | **155** | 1 | 1 | 30 | 218 | 28 | 3 | **279** | 1 | 1 | 25 | 101 | 28 | 0 | **154** | 1 | 1 | 12 | 169 | 23 | 3 | **207** | 1 | 1 | **795** |
| 5:00:00 PM | 17 | 79 | 26 | 0 | **122** | 2 | 3 | 32 | 254 | 32 | 3 | **321** | 0 | 0 | 24 | 83 | 25 | 0 | **132** | 1 | 0 | 13 | 187 | 32 | 7 | **239** | 0 | 1 | **814** |
| **Grand Total** | 91 | 314 | 126 | 0 | **531** | 6 | 4 | 118 | 968 | 103 | 10 | **1199** | 1 | 1 | 83 | 351 | 104 | 0 | **538** | 5 | 1 | 59 | 737 | 105 | 24 | **925** | 3 | 3 | **3193** |
| **% Approach** | 17.1% | 59.1% | 23.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.8% | 80.7% | 8.6% | 0.8% | **0.0%** | 0.0% | 0.0% | 15.4% | 65.2% | 19.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 79.7% | 11.4% | 2.6% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 2.8% | 9.8% | 3.9% | 0.0% | **16.6%** | 0.0% | 0.0% | 3.7% | 30.3% | 3.2% | 0.3% | **37.6%** | 0.0% | 0.0% | 2.6% | 11.0% | 3.3% | 0.0% | **16.8%** | 0.0% | 0.0% | 1.8% | 23.1% | 3.3% | 0.8% | **29.0%** | 0.0% | 0.0% | |
| **PHF** | 0.784 | 0.853 | 0.788 | 0.000 | **0.856** | 0.000 | 0.000 | 0.922 | 0.906 | 0.805 | 0.833 | **0.934** | 0.000 | 0.000 | 0.830 | 0.869 | 0.839 | 0.000 | **0.873** | 0.000 | 0.000 | 0.776 | 0.950 | 0.820 | 0.600 | **0.964** | 0.000 | 0.000 | **0.981** |
| **Lights** | 86 | 314 | 124 | 0 | **524** | 0 | 0 | 117 | 962 | 102 | 9 | **1190** | 0 | 0 | 78 | 349 | 104 | 0 | **531** | 0 | 0 | 54 | 733 | 102 | 24 | **913** | 0 | 0 | **3158** |
| **% Lights** | 94.5% | 100.0% | 98.4% | 0.0% | **98.7%** | 0.0% | 0.0% | 99.2% | 99.4% | 99.0% | 90.0% | **99.2%** | 0.0% | 0.0% | 94.0% | 99.4% | 100.0% | 0.0% | **98.7%** | 0.0% | 0.0% | 91.5% | 99.5% | 97.1% | 100.0% | **98.7%** | 0.0% | 0.0% | **98.9%** |
| **Trucks** | 2 | 0 | 2 | 0 | **4** | 0 | 0 | 0 | 3 | 0 | 1 | **4** | 0 | 0 | 2 | 2 | 0 | 0 | **4** | 0 | 0 | 0 | 3 | 2 | 0 | **5** | 0 | 0 | **17** |
| **% Trucks** | 2.2% | 0.0% | 1.6% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 10.0% | **0.3%** | 0.0% | 0.0% | 2.4% | 0.6% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.4% | 1.9% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.5%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **5** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 1.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 1.0% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 5 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 5 | 1 | 0 | 0 | 0 | 0 | **0** | 3 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Bailey Ave |
| **Legs and Movements** | All Processed Legs & Move |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Sheridan Drive & Bailey Ave |
| **Latitude and Longitude** | 42.98023,-78.81391 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 12:45:00 | 2023-11-18 13:45:00 | 0.97 |


# Turning Movement Data


| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 21 | 97 | 60 | 0 | **178** | 3 | 0 | 36 | 188 | 24 | 7 | **255** | 1 | 1 | 22 | 96 | 32 | 0 | **150** | 0 | 0 | 10 | 187 | 27 | 10 | **234** | 0 | 0 | **817** |
| 12:15:00 | 19 | 89 | 48 | 0 | **156** | 2 | 0 | 40 | 234 | 23 | 5 | **302** | 0 | 2 | 21 | 99 | 26 | 0 | **146** | 2 | 2 | 22 | 185 | 35 | 5 | **247** | 0 | 0 | **851** |
| 12:30:00 | 30 | 69 | 43 | 0 | **142** | 2 | 1 | 21 | 197 | 31 | 4 | **253** | 0 | 0 | 25 | 119 | 24 | 0 | **168** | 0 | 2 | 8 | 159 | 45 | 6 | **218** | 0 | 1 | **781** |
| 12:45:00 | 21 | 77 | 37 | 0 | **135** | 1 | 0 | 24 | 256 | 28 | 5 | **313** | 1 | 0 | 22 | 99 | 32 | 0 | **153** | 0 | 2 | 15 | 202 | 42 | 4 | **263** | 2 | 0 | **864** |
| **Hourly Total** | 91 | 332 | 188 | 0 | **611** | 8 | 1 | 121 | 875 | 106 | 21 | **1123** | 2 | 3 | 90 | 413 | 114 | 0 | **617** | 2 | 6 | 55 | 733 | 149 | 25 | **962** | 2 | 1 | **3313** |
| 13:00:00 | 11 | 77 | 38 | 0 | **126** | 4 | 2 | 31 | 225 | 27 | 6 | **289** | 1 | 1 | 18 | 98 | 41 | 0 | **157** | 2 | 0 | 21 | 209 | 43 | 5 | **278** | 0 | 0 | **850** |
| 13:15:00 | 19 | 90 | 39 | 0 | **148** | 2 | 2 | 27 | 200 | 29 | 8 | **264** | 0 | 1 | 26 | 86 | 32 | 0 | **144** | 1 | 1 | 14 | 160 | 48 | 5 | **227** | 1 | 0 | **783** |
| 13:30:00 | 25 | 73 | 45 | 0 | **143** | 3 | 1 | 35 | 269 | 44 | 3 | **351** | 3 | 3 | 11 | 80 | 32 | 0 | **123** | 0 | 0 | 14 | 180 | 38 | 5 | **237** | 0 | 0 | **854** |
| 13:45:00 | 20 | 90 | 37 | 0 | **147** | 0 | 4 | 29 | 220 | 30 | 4 | **283** | 1 | 1 | 32 | 98 | 22 | 0 | **152** | 0 | 1 | 13 | 178 | 45 | 4 | **240** | 0 | 1 | **822** |
| **Hourly Total** | 75 | 330 | 159 | 0 | **564** | 9 | 9 | 122 | 914 | 130 | 21 | **1187** | 5 | 6 | 87 | 362 | 127 | 0 | **576** | 3 | 2 | 62 | 727 | 174 | 19 | **982** | 1 | 1 | **3309** |
| 14:00:00 | 21 | 96 | 53 | 0 | **170** | 1 | 1 | 26 | 175 | 21 | 9 | **231** | 2 | 2 | 26 | 92 | 30 | 0 | **148** | 1 | 0 | 15 | 193 | 44 | 10 | **262** | 0 | 2 | **811** |
| 14:15:00 | 12 | 78 | 34 | 0 | **124** | 2 | 2 | 33 | 209 | 37 | 3 | **282** | 0 | 0 | 11 | 89 | 22 | 0 | **122** | 0 | 1 | 10 | 220 | 44 | 12 | **286** | 1 | 1 | **814** |
| 14:30:00 | 29 | 95 | 46 | 0 | **170** | 0 | 0 | 27 | 195 | 28 | 3 | **253** | 2 | 1 | 24 | 95 | 25 | 0 | **144** | 1 | 0 | 14 | 170 | 50 | 6 | **240** | 0 | 0 | **807** |
| 14:45:00 | 23 | 71 | 50 | 0 | **144** | 0 | 3 | 46 | 219 | 51 | 1 | **317** | 0 | 2 | 19 | 75 | 28 | 0 | **122** | 0 | 2 | 17 | 184 | 48 | 4 | **253** | 0 | 0 | **836** |
| **Hourly Total** | 85 | 340 | 183 | 0 | **608** | 3 | 6 | 132 | 798 | 137 | 16 | **1083** | 4 | 5 | 80 | 351 | 105 | 0 | **536** | 2 | 3 | 56 | 767 | 186 | 32 | **1041** | 1 | 3 | **3268** |
| **Grand Total** | 251 | 1002 | 530 | 0 | **1783** | 20 | 16 | 375 | 2587 | 373 | 58 | **3393** | 11 | 14 | 257 | 1126 | 346 | 0 | **1729** | 7 | 11 | 173 | 2227 | 509 | 76 | **2985** | 4 | 5 | **9890** |
| **% Approach** | 14.1% | 56.2% | 29.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 11.1% | 76.2% | 11.0% | 1.7% | **0.0%** | 0.0% | 0.0% | 14.9% | 65.1% | 20.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.8% | 74.6% | 17.1% | 2.5% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 2.5% | 10.1% | 5.4% | 0.0% | **18.0%** | 0.0% | 0.0% | 3.8% | 26.2% | 3.8% | 0.6% | **34.3%** | 0.0% | 0.0% | 2.6% | 11.4% | 3.5% | 0.0% | **17.5%** | 0.0% | 0.0% | 1.7% | 22.5% | 5.1% | 0.8% | **30.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 250 | 997 | 529 | 0 | **1776** | 0 | 0 | 372 | 2569 | 372 | 57 | **3370** | 0 | 0 | 246 | 1123 | 344 | 0 | **1713** | 0 | 0 | 159 | 2213 | 508 | 76 | **2956** | 0 | 0 | **9815** |
| **% Lights** | 99.6% | 99.5% | 99.8% | 0.0% | **99.6%** | 0.0% | 0.0% | 99.2% | 99.3% | 99.7% | 98.3% | **99.3%** | 0.0% | 0.0% | 95.7% | 99.7% | 99.4% | 0.0% | **99.1%** | 0.0% | 0.0% | 91.9% | 99.4% | 99.8% | 100.0% | **99.0%** | 0.0% | 0.0% | **99.2%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 2 | 7 | 1 | 1 | **11** | 0 | 0 | 2 | 1 | 1 | 0 | **4** | 0 | 0 | 0 | 13 | 0 | 0 | **13** | 0 | 0 | **29** |
| **% Trucks** | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.5% | 0.3% | 0.3% | 1.7% | **0.3%** | 0.0% | 0.0% | 0.8% | 0.1% | 0.3% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 4 | 1 | 0 | **5** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 3 | 2 | 1 | 0 | **6** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **20** |
| **% Buses** | 0.0% | 0.4% | 0.2% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 1.2% | 0.2% | 0.3% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 20 | 15 | 0 | 0 | 0 | 0 | **0** | 9 | 11 | 0 | 0 | 0 | 0 | **0** | 7 | 11 | 0 | 0 | 0 | 0 | **0** | 3 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 93.8% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 81.8% | 78.6% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 75.0% | 80.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 6.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 18.2% | 21.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 25.0% | 20.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**12:45:00**

| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:45:00 | 21 | 77 | 37 | 0 | **135** | 1 | 0 | 24 | 256 | 28 | 5 | **313** | 1 | 0 | 22 | 99 | 32 | 0 | **153** | 0 | 2 | 15 | 202 | 42 | 4 | **263** | 2 | 0 | **864** |
| 13:00:00 | 11 | 77 | 38 | 0 | **126** | 4 | 2 | 31 | 225 | 27 | 6 | **289** | 1 | 1 | 18 | 98 | 41 | 0 | **157** | 2 | 0 | 21 | 209 | 43 | 5 | **278** | 0 | 0 | **850** |
| 13:15:00 | 19 | 90 | 39 | 0 | **148** | 2 | 2 | 27 | 200 | 29 | 8 | **264** | 0 | 1 | 26 | 86 | 32 | 0 | **144** | 1 | 1 | 14 | 160 | 48 | 5 | **227** | 1 | 0 | **783** |
| 13:30:00 | 25 | 73 | 45 | 0 | **143** | 3 | 1 | 35 | 269 | 44 | 3 | **351** | 3 | 3 | 11 | 80 | 32 | 0 | **123** | 0 | 0 | 14 | 180 | 38 | 5 | **237** | 0 | 0 | **854** |
| **Grand Total** | 76 | 317 | 159 | 0 | **552** | 10 | 5 | 117 | 950 | 128 | 22 | **1217** | 5 | 5 | 77 | 363 | 137 | 0 | **577** | 3 | 3 | 64 | 751 | 171 | 19 | **1005** | 3 | 0 | **3351** |
| **% Approach** | 13.8% | 57.4% | 28.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.6% | 78.1% | 10.5% | 1.8% | **0.0%** | 0.0% | 0.0% | 13.3% | 62.9% | 23.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 74.7% | 17.0% | 1.9% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 2.3% | 9.5% | 4.7% | 0.0% | **16.5%** | 0.0% | 0.0% | 3.5% | 28.3% | 3.8% | 0.7% | **36.3%** | 0.0% | 0.0% | 2.3% | 10.8% | 4.1% | 0.0% | **17.2%** | 0.0% | 0.0% | 1.9% | 22.4% | 5.1% | 0.6% | **30.0%** | 0.0% | 0.0% | |
| **PHF** | 0.760 | 0.881 | 0.883 | 0.000 | **0.932** | 0.000 | 0.000 | 0.836 | 0.883 | 0.727 | 0.688 | **0.867** | 0.000 | 0.000 | 0.740 | 0.917 | 0.835 | 0.000 | **0.919** | 0.000 | 0.000 | 0.762 | 0.898 | 0.891 | 0.950 | **0.904** | 0.000 | 0.000 | **0.970** |
| **Lights** | 76 | 314 | 158 | 0 | **548** | 0 | 0 | 117 | 945 | 127 | 21 | **1210** | 0 | 0 | 73 | 362 | 135 | 0 | **570** | 0 | 0 | 57 | 746 | 170 | 19 | **992** | 0 | 0 | **3320** |
| **% Lights** | 100.0% | 99.1% | 99.4% | 0.0% | **99.3%** | 0.0% | 0.0% | 100.0% | 99.5% | 99.2% | 95.5% | **99.4%** | 0.0% | 0.0% | 94.8% | 99.7% | 98.5% | 0.0% | **98.8%** | 0.0% | 0.0% | 89.1% | 99.3% | 99.4% | 100.0% | **98.7%** | 0.0% | 0.0% | **99.1%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 2 | 1 | 1 | **4** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.8% | 4.5% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.7% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 1 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **7** |
| **% Buses** | 0.0% | 0.6% | 0.6% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.3% | 0.3% | 0.7% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 10 | 5 | 0 | 0 | 0 | 0 | **0** | 4 | 4 | 0 | 0 | 0 | 0 | **0** | 3 | 3 | 0 | 0 | 0 | 0 | **0** | 3 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 80.0% | 80.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 20.0% | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 21 | 97 | 60 | 0 | **178** | 3 | 0 | 36 | 188 | 24 | 7 | **255** | 1 | 1 | 22 | 96 | 32 | 0 | **150** | 0 | 0 | 10 | 187 | 27 | 10 | **234** | 0 | 0 | **817** |
| 12:15:00 | 19 | 89 | 48 | 0 | **156** | 2 | 0 | 40 | 234 | 23 | 5 | **302** | 0 | 2 | 21 | 99 | 26 | 0 | **146** | 2 | 2 | 22 | 185 | 35 | 5 | **247** | 0 | 0 | **851** |
| 12:30:00 | 30 | 69 | 43 | 0 | **142** | 2 | 1 | 21 | 197 | 31 | 4 | **253** | 0 | 0 | 25 | 119 | 24 | 0 | **168** | 0 | 2 | 8 | 159 | 45 | 6 | **218** | 0 | 1 | **781** |
| 12:45:00 | 21 | 77 | 37 | 0 | **135** | 1 | 0 | 24 | 256 | 28 | 5 | **313** | 1 | 0 | 22 | 99 | 32 | 0 | **153** | 0 | 2 | 15 | 202 | 42 | 4 | **263** | 2 | 0 | **864** |
| **Hourly Total** | 91 | 332 | 188 | 0 | **611** | 8 | 1 | 121 | 875 | 106 | 21 | **1123** | 2 | 3 | 90 | 413 | 114 | 0 | **617** | 2 | 6 | 55 | 733 | 149 | 25 | **962** | 2 | 1 | **3313** |
| 13:00:00 | 11 | 77 | 38 | 0 | **126** | 4 | 2 | 31 | 225 | 27 | 6 | **289** | 1 | 1 | 18 | 98 | 41 | 0 | **157** | 2 | 0 | 21 | 209 | 43 | 5 | **278** | 0 | 0 | **850** |
| 13:15:00 | 19 | 90 | 39 | 0 | **148** | 2 | 2 | 27 | 200 | 29 | 8 | **264** | 0 | 1 | 26 | 86 | 32 | 0 | **144** | 1 | 1 | 14 | 160 | 48 | 5 | **227** | 1 | 0 | **783** |
| 13:30:00 | 25 | 73 | 45 | 0 | **143** | 3 | 1 | 35 | 269 | 44 | 3 | **351** | 3 | 3 | 11 | 80 | 32 | 0 | **123** | 0 | 0 | 14 | 180 | 38 | 5 | **237** | 0 | 0 | **854** |
| 13:45:00 | 20 | 90 | 37 | 0 | **147** | 0 | 4 | 29 | 220 | 30 | 4 | **283** | 1 | 1 | 32 | 98 | 22 | 0 | **152** | 0 | 1 | 13 | 178 | 45 | 4 | **240** | 0 | 1 | **822** |
| **Hourly Total** | 75 | 330 | 159 | 0 | **564** | 9 | 9 | 122 | 914 | 130 | 21 | **1187** | 5 | 6 | 87 | 362 | 127 | 0 | **576** | 3 | 2 | 62 | 727 | 174 | 19 | **982** | 1 | 1 | **3309** |
| 14:00:00 | 21 | 96 | 53 | 0 | **170** | 1 | 1 | 26 | 175 | 21 | 9 | **231** | 2 | 2 | 26 | 92 | 30 | 0 | **148** | 1 | 0 | 15 | 193 | 44 | 10 | **262** | 0 | 2 | **811** |
| 14:15:00 | 12 | 78 | 34 | 0 | **124** | 2 | 2 | 33 | 209 | 37 | 3 | **282** | 0 | 0 | 11 | 89 | 22 | 0 | **122** | 0 | 1 | 10 | 220 | 44 | 12 | **286** | 1 | 1 | **814** |
| 14:30:00 | 29 | 95 | 46 | 0 | **170** | 0 | 0 | 27 | 195 | 28 | 3 | **253** | 2 | 1 | 24 | 95 | 25 | 0 | **144** | 1 | 0 | 14 | 170 | 50 | 6 | **240** | 0 | 0 | **807** |
| 14:45:00 | 23 | 71 | 50 | 0 | **144** | 0 | 3 | 46 | 219 | 51 | 1 | **317** | 0 | 2 | 19 | 75 | 28 | 0 | **122** | 0 | 2 | 17 | 184 | 48 | 4 | **253** | 0 | 0 | **836** |
| **Hourly Total** | 85 | 340 | 183 | 0 | **608** | 3 | 6 | 132 | 798 | 137 | 16 | **1083** | 4 | 5 | 80 | 351 | 105 | 0 | **536** | 2 | 3 | 56 | 767 | 186 | 32 | **1041** | 1 | 3 | **3268** |
| **Grand Total** | 251 | 1002 | 530 | 0 | **1783** | 20 | 16 | 375 | 2587 | 373 | 58 | **3393** | 11 | 14 | 257 | 1126 | 346 | 0 | **1729** | 7 | 11 | 173 | 2227 | 509 | 76 | **2985** | 4 | 5 | **9890** |
| **% Approach** | 14.1% | 56.2% | 29.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 11.1% | 76.2% | 11.0% | 1.7% | **0.0%** | 0.0% | 0.0% | 14.9% | 65.1% | 20.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.8% | 74.6% | 17.1% | 2.5% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 2.5% | 10.1% | 5.4% | 0.0% | **18.0%** | 0.0% | 0.0% | 3.8% | 26.2% | 3.8% | 0.6% | **34.3%** | 0.0% | 0.0% | 2.6% | 11.4% | 3.5% | 0.0% | **17.5%** | 0.0% | 0.0% | 1.7% | 22.5% | 5.1% | 0.8% | **30.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 250 | 997 | 529 | 0 | **1776** | 0 | 0 | 372 | 2569 | 372 | 57 | **3370** | 0 | 0 | 246 | 1123 | 344 | 0 | **1713** | 0 | 0 | 159 | 2213 | 508 | 76 | **2956** | 0 | 0 | **9815** |
| **% Lights** | 99.6% | 99.5% | 99.8% | 0.0% | **99.6%** | 0.0% | 0.0% | 99.2% | 99.3% | 99.7% | 98.3% | **99.3%** | 0.0% | 0.0% | 95.7% | 99.7% | 99.4% | 0.0% | **99.1%** | 0.0% | 0.0% | 91.9% | 99.4% | 99.8% | 100.0% | **99.0%** | 0.0% | 0.0% | **99.2%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 2 | 7 | 1 | 1 | **11** | 0 | 0 | 2 | 1 | 1 | 0 | **4** | 0 | 0 | 0 | 13 | 0 | 0 | **13** | 0 | 0 | **29** |
| **% Trucks** | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.5% | 0.3% | 0.3% | 1.7% | **0.3%** | 0.0% | 0.0% | 0.8% | 0.1% | 0.3% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 4 | 1 | 0 | **5** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 3 | 2 | 1 | 0 | **6** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **20** |
| **% Buses** | 0.0% | 0.4% | 0.2% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 1.2% | 0.2% | 0.3% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 20 | 15 | 0 | 0 | 0 | 0 | **0** | 9 | 11 | 0 | 0 | 0 | 0 | **0** | 7 | 11 | 0 | 0 | 0 | 0 | **0** | 3 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 93.8% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 81.8% | 78.6% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 75.0% | 80.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 6.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 18.2% | 21.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 25.0% | 20.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**12:45:00**

| Leg | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | Bailey Avenue | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:45:00 | 21 | 77 | 37 | 0 | **135** | 1 | 0 | 24 | 256 | 28 | 5 | **313** | 1 | 0 | 22 | 99 | 32 | 0 | **153** | 0 | 2 | 15 | 202 | 42 | 4 | **263** | 2 | 0 | **864** |
| 13:00:00 | 11 | 77 | 38 | 0 | **126** | 4 | 2 | 31 | 225 | 27 | 6 | **289** | 1 | 1 | 18 | 98 | 41 | 0 | **157** | 2 | 0 | 21 | 209 | 43 | 5 | **278** | 0 | 0 | **850** |
| 13:15:00 | 19 | 90 | 39 | 0 | **148** | 2 | 2 | 27 | 200 | 29 | 8 | **264** | 0 | 1 | 26 | 86 | 32 | 0 | **144** | 1 | 1 | 14 | 160 | 48 | 5 | **227** | 1 | 0 | **783** |
| 13:30:00 | 25 | 73 | 45 | 0 | **143** | 3 | 1 | 35 | 269 | 44 | 3 | **351** | 3 | 3 | 11 | 80 | 32 | 0 | **123** | 0 | 0 | 14 | 180 | 38 | 5 | **237** | 0 | 0 | **854** |
| **Grand Total** | 76 | 317 | 159 | 0 | **552** | 10 | 5 | 117 | 950 | 128 | 22 | **1217** | 5 | 5 | 77 | 363 | 137 | 0 | **577** | 3 | 3 | 64 | 751 | 171 | 19 | **1005** | 3 | 0 | **3351** |
| **% Approach** | 13.8% | 57.4% | 28.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.6% | 78.1% | 10.5% | 1.8% | **0.0%** | 0.0% | 0.0% | 13.3% | 62.9% | 23.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 74.7% | 17.0% | 1.9% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 2.3% | 9.5% | 4.7% | 0.0% | **16.5%** | 0.0% | 0.0% | 3.5% | 28.3% | 3.8% | 0.7% | **36.3%** | 0.0% | 0.0% | 2.3% | 10.8% | 4.1% | 0.0% | **17.2%** | 0.0% | 0.0% | 1.9% | 22.4% | 5.1% | 0.6% | **30.0%** | 0.0% | 0.0% | |
| **PHF** | 0.760 | 0.881 | 0.883 | 0.000 | **0.932** | 0.000 | 0.000 | 0.836 | 0.883 | 0.727 | 0.688 | **0.867** | 0.000 | 0.000 | 0.740 | 0.917 | 0.835 | 0.000 | **0.919** | 0.000 | 0.000 | 0.762 | 0.898 | 0.891 | 0.950 | **0.904** | 0.000 | 0.000 | **0.970** |
| **Lights** | 76 | 314 | 158 | 0 | **548** | 0 | 0 | 117 | 945 | 127 | 21 | **1210** | 0 | 0 | 73 | 362 | 135 | 0 | **570** | 0 | 0 | 57 | 746 | 170 | 19 | **992** | 0 | 0 | **3320** |
| **% Lights** | 100.0% | 99.1% | 99.4% | 0.0% | **99.3%** | 0.0% | 0.0% | 100.0% | 99.5% | 99.2% | 95.5% | **99.4%** | 0.0% | 0.0% | 94.8% | 99.7% | 98.5% | 0.0% | **98.8%** | 0.0% | 0.0% | 89.1% | 99.3% | 99.4% | 100.0% | **98.7%** | 0.0% | 0.0% | **99.1%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 2 | 1 | 1 | **4** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.8% | 4.5% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.7% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 1 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **7** |
| **% Buses** | 0.0% | 0.6% | 0.6% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.3% | 0.3% | 0.7% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 10 | 5 | 0 | 0 | 0 | 0 | **0** | 4 | 4 | 0 | 0 | 0 | 0 | **0** | 3 | 3 | 0 | 0 | 0 | 0 | **0** | 3 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 80.0% | 80.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 20.0% | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Sweet Hor |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Sheridan Drive & Sweet Hor |
| **Latitude and Longitude** | 42.9799, -78.80785 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:30:00 | 2023-11-16 17:30:00 | 0.979 |


## Turning Movement Data


| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 27 | 68 | 37 | 0 | **132** | 4 | 1 | 29 | 188 | 9 | 6 | **232** | 0 | 0 | 7 | 47 | 4 | 0 | **58** | 0 | 0 | 5 | 192 | 28 | 1 | **226** | 0 | 0 | **648** |
| 3:15:00 PM | 29 | 49 | 28 | 0 | **106** | 2 | 1 | 35 | 229 | 9 | 3 | **276** | 0 | 0 | 10 | 60 | 12 | 0 | **82** | 1 | 0 | 7 | 206 | 38 | 6 | **257** | 0 | 1 | **721** |
| 3:30:00 PM | 27 | 73 | 27 | 0 | **127** | 0 | 1 | 22 | 206 | 11 | 7 | **246** | 0 | 0 | 9 | 80 | 9 | 0 | **98** | 1 | 0 | 8 | 181 | 43 | 1 | **233** | 0 | 0 | **704** |
| 3:45:00 PM | 31 | 50 | 28 | 0 | **109** | 0 | 5 | 34 | 209 | 4 | 3 | **250** | 0 | 0 | 7 | 65 | 5 | 0 | **77** | 0 | 0 | 5 | 194 | 35 | 4 | **238** | 0 | 1 | **674** |
| **Hourly Total** | 114 | 240 | 120 | 0 | **474** | 6 | 8 | 120 | 832 | 33 | 19 | **1004** | 0 | 0 | 33 | 252 | 30 | 0 | **315** | 2 | 0 | 25 | 773 | 144 | 12 | **954** | 0 | 2 | **2747** |
| 4:00:00 PM | 35 | 55 | 33 | 0 | **123** | 0 | 1 | 21 | 210 | 13 | 6 | **250** | 0 | 1 | 12 | 73 | 8 | 0 | **93** | 0 | 1 | 12 | 197 | 39 | 1 | **249** | 3 | 4 | **715** |
| 4:15:00 PM | 24 | 43 | 42 | 0 | **109** | 2 | 0 | 41 | 241 | 16 | 7 | **305** | 1 | 1 | 10 | 71 | 7 | 0 | **88** | 1 | 1 | 8 | 166 | 36 | 2 | **212** | 1 | 1 | **714** |
| 4:30:00 PM | 31 | 49 | 21 | 0 | **101** | 0 | 3 | 29 | 227 | 10 | 5 | **271** | 1 | 0 | 7 | 60 | 6 | 0 | **73** | 0 | 0 | 6 | 204 | 47 | 2 | **259** | 0 | 2 | **704** |
| 4:45:00 PM | 37 | 60 | 24 | 0 | **121** | 2 | 0 | 27 | 226 | 14 | 4 | **271** | 0 | 0 | 11 | 81 | 9 | 0 | **101** | 0 | 1 | 4 | 179 | 46 | 1 | **230** | 0 | 0 | **723** |
| **Hourly Total** | 127 | 207 | 120 | 0 | **454** | 4 | 4 | 118 | 904 | 53 | 22 | **1097** | 2 | 2 | 40 | 285 | 30 | 0 | **355** | 1 | 3 | 30 | 746 | 168 | 6 | **950** | 4 | 7 | **2856** |
| 5:00:00 PM | 29 | 73 | 32 | 0 | **134** | 1 | 1 | 31 | 241 | 13 | 4 | **289** | 0 | 3 | 8 | 72 | 8 | 0 | **88** | 0 | 2 | 6 | 195 | 27 | 1 | **229** | 1 | 1 | **740** |
| 5:15:00 PM | 31 | 70 | 26 | 0 | **127** | 1 | 3 | 35 | 252 | 12 | 7 | **306** | 0 | 1 | 14 | 51 | 4 | 0 | **69** | 0 | 1 | 5 | 183 | 36 | 4 | **228** | 0 | 0 | **730** |
| 5:30:00 PM | 29 | 63 | 34 | 0 | **126** | 1 | 0 | 24 | 209 | 9 | 3 | **245** | 1 | 0 | 10 | 59 | 8 | 0 | **77** | 0 | 1 | 5 | 183 | 40 | 1 | **229** | 0 | 1 | **677** |
| 5:45:00 PM | 25 | 47 | 24 | 0 | **96** | 0 | 2 | 24 | 223 | 4 | 0 | **251** | 0 | 1 | 8 | 40 | 5 | 0 | **53** | 0 | 0 | 5 | 186 | 28 | 1 | **220** | 0 | 1 | **620** |
| **Hourly Total** | 114 | 253 | 116 | 0 | **483** | 3 | 6 | 114 | 925 | 38 | 14 | **1091** | 1 | 5 | 40 | 222 | 25 | 0 | **287** | 0 | 4 | 21 | 747 | 131 | 7 | **906** | 1 | 3 | **2767** |
| **Grand Total** | 355 | 700 | 356 | 0 | **1411** | 13 | 18 | 352 | 2661 | 124 | 55 | **3192** | 3 | 7 | 113 | 759 | 85 | 0 | **957** | 3 | 7 | 76 | 2266 | 443 | 25 | **2810** | 5 | 12 | **8370** |
| **% Approach** | 25.2% | 49.6% | 25.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 11.0% | 83.4% | 3.9% | 1.7% | **0.0%** | 0.0% | 0.0% | 11.8% | 79.3% | 8.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.7% | 80.6% | 15.8% | 0.9% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 4.2% | 8.4% | 4.3% | 0.0% | **16.9%** | 0.0% | 0.0% | 4.2% | 31.8% | 1.5% | 0.7% | **38.1%** | 0.0% | 0.0% | 1.4% | 9.1% | 1.0% | 0.0% | **11.4%** | 0.0% | 0.0% | 0.9% | 27.1% | 5.3% | 0.3% | **33.6%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 342 | 684 | 353 | 0 | **1379** | 0 | 0 | 324 | 2640 | 120 | 55 | **3139** | 0 | 0 | 83 | 735 | 83 | 0 | **901** | 0 | 0 | 60 | 2236 | 439 | 25 | **2760** | 0 | 0 | **8179** |
| **% Lights** | 96.3% | 97.7% | 99.2% | 0.0% | **97.7%** | 0.0% | 0.0% | 92.0% | 99.2% | 96.8% | 100.0% | **98.3%** | 0.0% | 0.0% | 73.5% | 96.8% | 97.6% | 0.0% | **94.1%** | 0.0% | 0.0% | 78.9% | 98.7% | 99.1% | 100.0% | **98.2%** | 0.0% | 0.0% | **97.7%** |
| **Trucks** | 2 | 2 | 1 | 0 | **5** | 0 | 0 | 1 | 12 | 2 | 0 | **15** | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 25 | 2 | 0 | **27** | 0 | 0 | **49** |
| **% Trucks** | 0.6% | 0.3% | 0.3% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.3% | 0.5% | 1.6% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 1.1% | 0.5% | 0.0% | **1.0%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 4 | 7 | 2 | 0 | **13** | 0 | 0 | 0 | 7 | 2 | 0 | **9** | 0 | 0 | 25 | 21 | 2 | 0 | **48** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | **73** |
| **% Buses** | 1.1% | 1.0% | 0.6% | 0.0% | **0.9%** | 0.0% | 0.0% | 0.0% | 0.3% | 1.6% | 0.0% | **0.3%** | 0.0% | 0.0% | 22.1% | 2.8% | 2.4% | 0.0% | **5.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.2% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.9%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 13 | 14 | 0 | 0 | 0 | 0 | **0** | 3 | 5 | 0 | 0 | 0 | 0 | **0** | 2 | 5 | 0 | 0 | 0 | 0 | **0** | 5 | 10 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 77.8% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 71.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 71.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 83.3% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 4 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 22.2% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 28.6% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 28.6% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 16.7% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**


## Turning Movement Peak Hour Data (PM)

**4:30:00 PM**

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:30:00 PM | 31 | 49 | 21 | 0 | **101** | 0 | 3 | 29 | 227 | 10 | 5 | **271** | 1 | 0 | 7 | 60 | 6 | 0 | **73** | 0 | 0 | 6 | 204 | 47 | 2 | **259** | 0 | 2 | **704** |
| 4:45:00 PM | 37 | 60 | 24 | 0 | **121** | 2 | 0 | 27 | 226 | 14 | 4 | **271** | 0 | 0 | 11 | 81 | 9 | 0 | **101** | 0 | 1 | 4 | 179 | 46 | 1 | **230** | 0 | 0 | **723** |
| 5:00:00 PM | 29 | 73 | 32 | 0 | **134** | 1 | 1 | 31 | 241 | 13 | 4 | **289** | 0 | 3 | 8 | 72 | 8 | 0 | **88** | 0 | 2 | 6 | 195 | 27 | 1 | **229** | 1 | 1 | **740** |
| 5:15:00 PM | 31 | 70 | 26 | 0 | **127** | 1 | 3 | 35 | 252 | 12 | 7 | **306** | 0 | 1 | 14 | 51 | 4 | 0 | **69** | 0 | 1 | 5 | 183 | 36 | 4 | **228** | 0 | 0 | **730** |
| **Grand Total** | 128 | 252 | 103 | 0 | **483** | 4 | 7 | 122 | 946 | 49 | 20 | **1137** | 1 | 4 | 40 | 264 | 27 | 0 | **331** | 0 | 4 | 21 | 761 | 156 | 8 | **946** | 1 | 3 | **2897** |
| **% Approach** | 26.5% | 52.2% | 21.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 10.7% | 83.2% | 4.3% | 1.8% | **0.0%** | 0.0% | 0.0% | 12.1% | 79.8% | 8.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.2% | 80.4% | 16.5% | 0.8% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 4.4% | 8.7% | 3.6% | 0.0% | **16.7%** | 0.0% | 0.0% | 4.2% | 32.7% | 1.7% | 0.7% | **39.2%** | 0.0% | 0.0% | 1.4% | 9.1% | 0.9% | 0.0% | **11.4%** | 0.0% | 0.0% | 0.7% | 26.3% | 5.4% | 0.3% | **32.7%** | 0.0% | 0.0% | |
| **PHF** | 0.865 | 0.863 | 0.805 | 0.000 | **0.901** | 0.000 | 0.000 | 0.871 | 0.938 | 0.875 | 0.714 | **0.929** | 0.000 | 0.000 | 0.714 | 0.815 | 0.750 | 0.000 | **0.819** | 0.000 | 0.000 | 0.875 | 0.933 | 0.830 | 0.500 | **0.913** | 0.000 | 0.000 | **0.979** |
| **Lights** | 122 | 248 | 103 | 0 | **473** | 0 | 0 | 111 | 942 | 48 | 20 | **1121** | 0 | 0 | 31 | 259 | 27 | 0 | **317** | 0 | 0 | 17 | 753 | 155 | 8 | **933** | 0 | 0 | **2844** |
| **% Lights** | 95.3% | 98.4% | 100.0% | 0.0% | **97.9%** | 0.0% | 0.0% | 91.0% | 99.6% | 98.0% | 100.0% | **98.6%** | 0.0% | 0.0% | 77.5% | 98.1% | 100.0% | 0.0% | **95.8%** | 0.0% | 0.0% | 81.0% | 98.9% | 99.4% | 100.0% | **98.6%** | 0.0% | 0.0% | **98.2%** |
| **Trucks** | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | **12** |
| **% Trucks** | 0.8% | 0.4% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.2% | 2.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.9% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 2 | 1 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 8 | 4 | 0 | 0 | **12** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **16** |
| **% Buses** | 1.6% | 0.4% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 20.0% | 1.5% | 0.0% | 0.0% | **3.6%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.6%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 4 | 6 | 0 | 0 | 0 | 0 | **0** | 1 | 3 | 0 | 0 | 0 | 0 | **0** | 0 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 85.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 14.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | **0.0%** |











## Turning Movement Data

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 27 | 68 | 37 | 0 | **132** | 4 | 1 | 29 | 188 | 9 | 6 | **232** | 0 | 0 | 7 | 47 | 4 | 0 | **58** | 0 | 0 | 5 | 192 | 28 | 1 | **226** | 0 | 0 | **648** |
| 3:15:00 PM | 29 | 49 | 28 | 0 | **106** | 2 | 1 | 35 | 229 | 9 | 3 | **276** | 0 | 0 | 10 | 60 | 12 | 0 | **82** | 1 | 0 | 7 | 206 | 38 | 6 | **257** | 0 | 1 | **721** |
| 3:30:00 PM | 27 | 73 | 27 | 0 | **127** | 0 | 1 | 22 | 206 | 11 | 7 | **246** | 0 | 0 | 9 | 80 | 9 | 0 | **98** | 1 | 0 | 8 | 181 | 43 | 1 | **233** | 0 | 0 | **704** |
| 3:45:00 PM | 31 | 50 | 28 | 0 | **109** | 0 | 5 | 34 | 209 | 4 | 3 | **250** | 0 | 0 | 7 | 65 | 5 | 0 | **77** | 0 | 0 | 5 | 194 | 35 | 4 | **238** | 0 | 1 | **674** |
| **Hourly Total** | 114 | 240 | 120 | 0 | **474** | 6 | 8 | 120 | 832 | 33 | 19 | **1004** | 0 | 0 | 33 | 252 | 30 | 0 | **315** | 2 | 0 | 25 | 773 | 144 | 12 | **954** | 0 | 2 | **2747** |
| 4:00:00 PM | 35 | 55 | 33 | 0 | **123** | 0 | 1 | 21 | 210 | 13 | 6 | **250** | 0 | 1 | 12 | 73 | 8 | 0 | **93** | 0 | 1 | 12 | 197 | 39 | 1 | **249** | 3 | 4 | **715** |
| 4:15:00 PM | 24 | 43 | 42 | 0 | **109** | 2 | 0 | 41 | 241 | 16 | 7 | **305** | 1 | 1 | 10 | 71 | 7 | 0 | **88** | 1 | 1 | 8 | 166 | 36 | 2 | **212** | 1 | 1 | **714** |
| 4:30:00 PM | 31 | 49 | 21 | 0 | **101** | 0 | 3 | 29 | 227 | 10 | 5 | **271** | 1 | 0 | 7 | 60 | 6 | 0 | **73** | 0 | 0 | 6 | 204 | 47 | 2 | **259** | 0 | 2 | **704** |
| 4:45:00 PM | 37 | 60 | 24 | 0 | **121** | 2 | 0 | 27 | 226 | 14 | 4 | **271** | 0 | 0 | 11 | 81 | 9 | 0 | **101** | 0 | 1 | 4 | 179 | 46 | 1 | **230** | 0 | 0 | **723** |
| **Hourly Total** | 127 | 207 | 120 | 0 | **454** | 4 | 4 | 118 | 904 | 53 | 22 | **1097** | 2 | 2 | 40 | 285 | 30 | 0 | **355** | 1 | 3 | 30 | 746 | 168 | 6 | **950** | 4 | 7 | **2856** |
| 5:00:00 PM | 29 | 73 | 32 | 0 | **134** | 1 | 1 | 31 | 241 | 13 | 4 | **289** | 0 | 3 | 8 | 72 | 8 | 0 | **88** | 0 | 2 | 6 | 195 | 27 | 1 | **229** | 1 | 1 | **740** |
| 5:15:00 PM | 31 | 70 | 26 | 0 | **127** | 1 | 3 | 35 | 252 | 12 | 7 | **306** | 0 | 1 | 14 | 51 | 4 | 0 | **69** | 0 | 1 | 5 | 183 | 36 | 4 | **228** | 0 | 0 | **730** |
| 5:30:00 PM | 29 | 63 | 34 | 0 | **126** | 1 | 0 | 24 | 209 | 9 | 3 | **245** | 1 | 0 | 10 | 59 | 8 | 0 | **77** | 0 | 1 | 5 | 183 | 40 | 1 | **229** | 0 | 1 | **677** |
| 5:45:00 PM | 25 | 47 | 24 | 0 | **96** | 0 | 2 | 24 | 223 | 4 | 0 | **251** | 0 | 1 | 8 | 40 | 5 | 0 | **53** | 0 | 0 | 5 | 186 | 28 | 1 | **220** | 0 | 1 | **620** |
| **Hourly Total** | 114 | 253 | 116 | 0 | **483** | 3 | 6 | 114 | 925 | 38 | 14 | **1091** | 1 | 5 | 40 | 222 | 25 | 0 | **287** | 0 | 4 | 21 | 747 | 131 | 7 | **906** | 1 | 3 | **2767** |
| **Grand Total** | 355 | 700 | 356 | 0 | **1411** | 13 | 18 | 352 | 2661 | 124 | 55 | **3192** | 3 | 7 | 113 | 759 | 85 | 0 | **957** | 3 | 7 | 76 | 2266 | 443 | 25 | **2810** | 5 | 12 | **8370** |
| **% Approach** | 25.2% | 49.6% | 25.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 11.0% | 83.4% | 3.9% | 1.7% | **0.0%** | 0.0% | 0.0% | 11.8% | 79.3% | 8.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.7% | 80.6% | 15.8% | 0.9% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 4.2% | 8.4% | 4.3% | 0.0% | **16.9%** | 0.0% | 0.0% | 4.2% | 31.8% | 1.5% | 0.7% | **38.1%** | 0.0% | 0.0% | 1.4% | 9.1% | 1.0% | 0.0% | **11.4%** | 0.0% | 0.0% | 0.9% | 27.1% | 5.3% | 0.3% | **33.6%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 342 | 684 | 353 | 0 | **1379** | 0 | 0 | 324 | 2640 | 120 | 55 | **3139** | 0 | 0 | 83 | 735 | 83 | 0 | **901** | 0 | 0 | 60 | 2236 | 439 | 25 | **2760** | 0 | 0 | **8179** |
| **% Lights** | 96.3% | 97.7% | 99.2% | 0.0% | **97.7%** | 0.0% | 0.0% | 92.0% | 99.2% | 96.8% | 100.0% | **98.3%** | 0.0% | 0.0% | 73.5% | 96.8% | 97.6% | 0.0% | **94.1%** | 0.0% | 0.0% | 78.9% | 98.7% | 99.1% | 100.0% | **98.2%** | 0.0% | 0.0% | **97.7%** |
| **Trucks** | 2 | 2 | 1 | 0 | **5** | 0 | 0 | 1 | 12 | 2 | 0 | **15** | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 25 | 2 | 0 | **27** | 0 | 0 | **49** |
| **% Trucks** | 0.6% | 0.3% | 0.3% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.3% | 0.5% | 1.6% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 1.1% | 0.5% | 0.0% | **1.0%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 4 | 7 | 2 | 0 | **13** | 0 | 0 | 0 | 7 | 2 | 0 | **9** | 0 | 0 | 25 | 21 | 2 | 0 | **48** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | **73** |
| **% Buses** | 1.1% | 1.0% | 0.6% | 0.0% | **0.9%** | 0.0% | 0.0% | 0.0% | 0.3% | 1.6% | 0.0% | **0.3%** | 0.0% | 0.0% | 22.1% | 2.8% | 2.4% | 0.0% | **5.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.2% | 0.0% | **0.1%** | 0.0% | 0.0% | **0.9%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 13 | 14 | 0 | 0 | 0 | 0 | **0** | 3 | 5 | 0 | 0 | 0 | 0 | **0** | 2 | 5 | 0 | 0 | 0 | 0 | **0** | 5 | 10 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 77.8% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 71.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 66.7% | 71.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 83.3% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 4 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 22.2% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 28.6% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 33.3% | 28.6% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 16.7% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**4:30:00 PM**

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:30:00 PM | 31 | 49 | 21 | 0 | **101** | 0 | 3 | 29 | 227 | 10 | 5 | **271** | 1 | 0 | 7 | 60 | 6 | 0 | **73** | 0 | 0 | 6 | 204 | 47 | 2 | **259** | 0 | 2 | **704** |
| 4:45:00 PM | 37 | 60 | 24 | 0 | **121** | 2 | 0 | 27 | 226 | 14 | 4 | **271** | 0 | 0 | 11 | 81 | 9 | 0 | **101** | 0 | 1 | 4 | 179 | 46 | 1 | **230** | 0 | 0 | **723** |
| 5:00:00 PM | 29 | 73 | 32 | 0 | **134** | 1 | 1 | 31 | 241 | 13 | 4 | **289** | 0 | 3 | 8 | 72 | 8 | 0 | **88** | 0 | 2 | 6 | 195 | 27 | 1 | **229** | 1 | 1 | **740** |
| 5:15:00 PM | 31 | 70 | 26 | 0 | **127** | 1 | 3 | 35 | 252 | 12 | 7 | **306** | 0 | 1 | 14 | 51 | 4 | 0 | **69** | 0 | 1 | 5 | 183 | 36 | 4 | **228** | 0 | 0 | **730** |
| **Grand Total** | 128 | 252 | 103 | 0 | **483** | 4 | 7 | 122 | 946 | 49 | 20 | **1137** | 1 | 4 | 40 | 264 | 27 | 0 | **331** | 0 | 4 | 21 | 761 | 156 | 8 | **946** | 1 | 3 | **2897** |
| **% Approach** | 26.5% | 52.2% | 21.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 10.7% | 83.2% | 4.3% | 1.8% | **0.0%** | 0.0% | 0.0% | 12.1% | 79.8% | 8.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.2% | 80.4% | 16.5% | 0.8% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 4.4% | 8.7% | 3.6% | 0.0% | **16.7%** | 0.0% | 0.0% | 4.2% | 32.7% | 1.7% | 0.7% | **39.2%** | 0.0% | 0.0% | 1.4% | 9.1% | 0.9% | 0.0% | **11.4%** | 0.0% | 0.0% | 0.7% | 26.3% | 5.4% | 0.3% | **32.7%** | 0.0% | 0.0% | |
| **PHF** | 0.865 | 0.863 | 0.805 | 0.000 | **0.901** | 0.000 | 0.000 | 0.871 | 0.938 | 0.875 | 0.714 | **0.929** | 0.000 | 0.000 | 0.714 | 0.815 | 0.750 | 0.000 | **0.819** | 0.000 | 0.000 | 0.875 | 0.933 | 0.830 | 0.500 | **0.913** | 0.000 | 0.000 | **0.979** |
| **Lights** | 122 | 248 | 103 | 0 | **473** | 0 | 0 | 111 | 942 | 48 | 20 | **1121** | 0 | 0 | 31 | 259 | 27 | 0 | **317** | 0 | 0 | 17 | 753 | 155 | 8 | **933** | 0 | 0 | **2844** |
| **% Lights** | 95.3% | 98.4% | 100.0% | 0.0% | **97.9%** | 0.0% | 0.0% | 91.0% | 99.6% | 98.0% | 100.0% | **98.6%** | 0.0% | 0.0% | 77.5% | 98.1% | 100.0% | 0.0% | **95.8%** | 0.0% | 0.0% | 81.0% | 98.9% | 99.4% | 100.0% | **98.6%** | 0.0% | 0.0% | **98.2%** |
| **Trucks** | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | **12** |
| **% Trucks** | 0.8% | 0.4% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.2% | 2.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.9% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 2 | 1 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 8 | 4 | 0 | 0 | **12** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **16** |
| **% Buses** | 1.6% | 0.4% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 20.0% | 1.5% | 0.0% | 0.0% | **3.6%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.6%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 4 | 6 | 0 | 0 | 0 | 0 | **0** | 1 | 3 | 0 | 0 | 0 | 0 | **0** | 0 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 85.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 75.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 14.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 25.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | **0.0%** |



TRI-STATE TRAFFIC DATA

TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive & Sweet Hor |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Sheridan Drive & Sweet Hor |
| **Latitude and Longitude** | 42.9799, -78.80785 |


| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 12:30:00 | 2023-11-18 13:30:00 | 0.978 |


# Turning Movement Data

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 PM | 29 | 36 | 31 | 0 | **96** | 1 | 0 | 22 | 209 | 12 | 3 | **246** | 0 | 0 | 9 | 43 | 8 | 0 | **60** | 2 | 1 | 10 | 206 | 36 | 5 | **257** | 2 | 0 | **659** |
| 12:15:00 PM | 24 | 40 | 30 | 0 | **94** | 0 | 0 | 20 | 220 | 8 | 0 | **248** | 0 | 0 | 5 | 45 | 12 | 0 | **62** | 0 | 0 | 3 | 170 | 33 | 0 | **206** | 0 | 0 | **610** |
| 12:30:00 PM | 19 | 38 | 32 | 0 | **89** | 0 | 1 | 21 | 211 | 12 | 0 | **244** | 1 | 0 | 12 | 33 | 8 | 0 | **53** | 2 | 0 | 4 | 209 | 38 | 1 | **252** | 2 | 0 | **638** |
| 12:45:00 PM | 33 | 39 | 44 | 0 | **116** | 0 | 5 | 18 | 205 | 9 | 0 | **232** | 0 | 0 | 2 | 45 | 12 | 0 | **59** | 1 | 0 | 6 | 200 | 38 | 11 | **255** | 0 | 0 | **662** |
| **Hourly Total** | 105 | 153 | 137 | 0 | **395** | 1 | 6 | 81 | 845 | 41 | 3 | **970** | 1 | 0 | 28 | 166 | 40 | 0 | **234** | 5 | 1 | 23 | 785 | 145 | 17 | **970** | 4 | 0 | **2569** |
| 1:00:00 PM | 27 | 47 | 37 | 0 | **111** | 0 | 6 | 21 | 218 | 7 | 3 | **249** | 1 | 1 | 2 | 32 | 5 | 0 | **39** | 0 | 0 | 9 | 176 | 44 | 3 | **232** | 0 | 2 | **631** |
| 1:15:00 PM | 31 | 41 | 21 | 0 | **93** | 0 | 0 | 24 | 232 | 7 | 1 | **264** | 0 | 1 | 11 | 37 | 8 | 0 | **56** | 1 | 0 | 5 | 196 | 41 | 4 | **246** | 0 | 0 | **659** |
| 1:30:00 PM | 45 | 33 | 37 | 0 | **115** | 6 | 0 | 18 | 229 | 4 | 5 | **256** | 0 | 0 | 7 | 38 | 13 | 0 | **58** | 3 | 3 | 6 | 145 | 44 | 7 | **202** | 0 | 2 | **631** |
| 1:45:00 PM | 32 | 38 | 35 | 0 | **105** | 0 | 1 | 14 | 211 | 9 | 5 | **239** | 0 | 0 | 4 | 33 | 8 | 0 | **45** | 0 | 0 | 4 | 202 | 36 | 2 | **244** | 1 | 0 | **633** |
| **Hourly Total** | 135 | 159 | 130 | 0 | **424** | 6 | 7 | 77 | 890 | 27 | 14 | **1008** | 1 | 2 | 24 | 140 | 34 | 0 | **198** | 4 | 3 | 24 | 719 | 165 | 16 | **924** | 1 | 4 | **2554** |
| 2:00:00 PM | 22 | 37 | 22 | 0 | **81** | 4 | 2 | 28 | 195 | 3 | 4 | **230** | 0 | 0 | 4 | 53 | 6 | 0 | **63** | 0 | 1 | 5 | 232 | 53 | 1 | **291** | 1 | 0 | **665** |
| 2:15:00 PM | 34 | 36 | 30 | 0 | **100** | 2 | 0 | 26 | 202 | 11 | 4 | **243** | 0 | 0 | 7 | 45 | 5 | 0 | **57** | 0 | 0 | 4 | 198 | 39 | 0 | **241** | 0 | 5 | **641** |
| 2:30:00 PM | 23 | 37 | 30 | 0 | **90** | 2 | 0 | 21 | 219 | 10 | 3 | **253** | 1 | 0 | 6 | 36 | 6 | 0 | **48** | 0 | 1 | 3 | 185 | 43 | 8 | **239** | 0 | 0 | **630** |
| 2:45:00 PM | 32 | 57 | 35 | 0 | **124** | 1 | 1 | 30 | 191 | 11 | 1 | **233** | 0 | 0 | 7 | 38 | 8 | 0 | **53** | 0 | 1 | 7 | 193 | 37 | 4 | **241** | 0 | 0 | **651** |
| **Hourly Total** | 111 | 167 | 117 | 0 | **395** | 9 | 3 | 105 | 807 | 35 | 12 | **959** | 1 | 0 | 24 | 172 | 25 | 0 | **221** | 0 | 3 | 19 | 808 | 172 | 13 | **1012** | 1 | 5 | **2587** |
| **Grand Total** | 351 | 479 | 384 | 0 | **1214** | 16 | 16 | 263 | 2542 | 103 | 29 | **2937** | 3 | 2 | 76 | 478 | 99 | 0 | **653** | 9 | 7 | 66 | 2312 | 482 | 46 | **2906** | 6 | 9 | **7710** |
| **% Approach** | 28.9% | 39.5% | 31.6% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.0% | 86.6% | 3.5% | 1.0% | **0.0%** | 0.0% | 0.0% | 11.6% | 73.2% | 15.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.3% | 79.6% | 16.6% | 1.6% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 4.6% | 6.2% | 5.0% | 0.0% | **15.7%** | 0.0% | 0.0% | 3.4% | 33.0% | 1.3% | 0.4% | **38.1%** | 0.0% | 0.0% | 1.0% | 6.2% | 1.3% | 0.0% | **8.5%** | 0.0% | 0.0% | 0.9% | 30.0% | 6.3% | 0.6% | **37.7%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 332 | 476 | 384 | 0 | **1192** | 0 | 0 | 239 | 2530 | 103 | 29 | **2901** | 0 | 0 | 67 | 476 | 98 | 0 | **641** | 0 | 0 | 35 | 2295 | 482 | 46 | **2858** | 0 | 0 | **7592** |
| **% Lights** | 94.6% | 99.4% | 100.0% | 0.0% | **98.2%** | 0.0% | 0.0% | 90.9% | 99.5% | 100.0% | 100.0% | **98.8%** | 0.0% | 0.0% | 88.2% | 99.6% | 99.0% | 0.0% | **98.2%** | 0.0% | 0.0% | 53.0% | 99.3% | 100.0% | 100.0% | **98.3%** | 0.0% | 0.0% | **98.5%** |
| **Trucks** | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 14 | 0 | 0 | **14** | 0 | 0 | **27** |
| **% Trucks** | 0.3% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.4% | 1.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 5 | 1 | 0 | 0 | **6** | 0 | 0 | 2 | 1 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **10** |
| **% Buses** | 1.4% | 0.2% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 7 | 8 | 0 | 0 | 0 | 0 | **0** | 3 | 2 | 0 | 0 | 0 | 0 | **0** | 9 | 7 | 0 | 0 | 0 | 0 | **0** | 6 | 9 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 43.8% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 9 | 8 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 56.3% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**




TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**12:30:00 PM**

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:30:00 PM | 19 | 38 | 32 | 0 | **89** | 0 | 1 | 21 | 211 | 12 | 0 | **244** | 1 | 0 | 12 | 33 | 8 | 0 | **53** | 2 | 0 | 4 | 209 | 38 | 1 | **252** | 2 | 0 | **638** |
| 12:45:00 PM | 33 | 39 | 44 | 0 | **116** | 0 | 5 | 18 | 205 | 9 | 0 | **232** | 0 | 0 | 2 | 45 | 12 | 0 | **59** | 1 | 0 | 6 | 200 | 38 | 11 | **255** | 0 | 0 | **662** |
| 1:00:00 PM | 27 | 47 | 37 | 0 | **111** | 0 | 6 | 21 | 218 | 7 | 3 | **249** | 1 | 1 | 2 | 32 | 5 | 0 | **39** | 0 | 0 | 9 | 176 | 44 | 3 | **232** | 0 | 2 | **631** |
| 1:15:00 PM | 31 | 41 | 21 | 0 | **93** | 0 | 0 | 24 | 232 | 7 | 1 | **264** | 0 | 1 | 11 | 37 | 8 | 0 | **56** | 1 | 0 | 5 | 196 | 41 | 4 | **246** | 0 | 0 | **659** |
| **Grand Total** | 110 | 165 | 134 | 0 | **409** | 0 | 12 | 84 | 866 | 35 | 4 | **989** | 2 | 2 | 27 | 147 | 33 | 0 | **207** | 4 | 0 | 24 | 781 | 161 | 19 | **985** | 2 | 2 | **2590** |
| **% Approach** | 26.9% | 40.3% | 32.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.5% | 87.6% | 3.5% | 0.4% | **0.0%** | 0.0% | 0.0% | 13.0% | 71.0% | 15.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.4% | 79.3% | 16.3% | 1.9% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 4.2% | 6.4% | 5.2% | 0.0% | **15.8%** | 0.0% | 0.0% | 3.2% | 33.4% | 1.4% | 0.2% | **38.2%** | 0.0% | 0.0% | 1.0% | 5.7% | 1.3% | 0.0% | **8.0%** | 0.0% | 0.0% | 0.9% | 30.2% | 6.2% | 0.7% | **38.0%** | 0.0% | 0.0% | |
| **PHF** | 0.833 | 0.878 | 0.761 | 0.000 | **0.881** | 0.000 | 0.000 | 0.875 | 0.933 | 0.729 | 0.333 | **0.937** | 0.000 | 0.000 | 0.563 | 0.817 | 0.688 | 0.000 | **0.877** | 0.000 | 0.000 | 0.667 | 0.934 | 0.915 | 0.432 | **0.966** | 0.000 | 0.000 | **0.978** |
| **Lights** | 104 | 162 | 134 | 0 | **400** | 0 | 0 | 80 | 863 | 35 | 4 | **982** | 0 | 0 | 25 | 147 | 32 | 0 | **204** | 0 | 0 | 13 | 776 | 161 | 19 | **969** | 0 | 0 | **2555** |
| **% Lights** | 94.5% | 98.2% | 100.0% | 0.0% | **97.8%** | 0.0% | 0.0% | 95.2% | 99.7% | 100.0% | 100.0% | **99.3%** | 0.0% | 0.0% | 92.6% | 100.0% | 97.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 54.2% | 99.4% | 100.0% | 100.0% | **98.4%** | 0.0% | 0.0% | **98.6%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | **8** |
| **% Trucks** | 0.0% | 0.6% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 3.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **1** |
| **% Buses** | 0.0% | 0.6% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 4 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 8 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |








## Turning Movement Data

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 PM | 29 | 36 | 31 | 0 | **96** | 1 | 0 | 22 | 209 | 12 | 3 | **246** | 0 | 0 | 9 | 43 | 8 | 0 | **60** | 2 | 1 | 10 | 206 | 36 | 5 | **257** | 2 | 0 | **659** |
| 12:15:00 PM | 24 | 40 | 30 | 0 | **94** | 0 | 0 | 20 | 220 | 8 | 0 | **248** | 0 | 0 | 5 | 45 | 12 | 0 | **62** | 0 | 0 | 3 | 170 | 33 | 0 | **206** | 0 | 0 | **610** |
| 12:30:00 PM | 19 | 38 | 32 | 0 | **89** | 0 | 1 | 21 | 211 | 12 | 0 | **244** | 1 | 0 | 12 | 33 | 8 | 0 | **53** | 2 | 0 | 4 | 209 | 38 | 1 | **252** | 2 | 0 | **638** |
| 12:45:00 PM | 33 | 39 | 44 | 0 | **116** | 0 | 5 | 18 | 205 | 9 | 0 | **232** | 0 | 0 | 2 | 45 | 12 | 0 | **59** | 1 | 0 | 6 | 200 | 38 | 11 | **255** | 0 | 0 | **662** |
| **Hourly Total** | 105 | 153 | 137 | 0 | **395** | 1 | 6 | 81 | 845 | 41 | 3 | **970** | 1 | 0 | 28 | 166 | 40 | 0 | **234** | 5 | 1 | 23 | 785 | 145 | 17 | **970** | 4 | 0 | **2569** |
| 1:00:00 PM | 27 | 47 | 37 | 0 | **111** | 0 | 6 | 21 | 218 | 7 | 3 | **249** | 1 | 1 | 2 | 32 | 5 | 0 | **39** | 0 | 0 | 9 | 176 | 44 | 3 | **232** | 0 | 2 | **631** |
| 1:15:00 PM | 31 | 41 | 21 | 0 | **93** | 0 | 0 | 24 | 232 | 7 | 1 | **264** | 0 | 1 | 11 | 37 | 8 | 0 | **56** | 1 | 0 | 5 | 196 | 41 | 4 | **246** | 0 | 0 | **659** |
| 1:30:00 PM | 45 | 33 | 37 | 0 | **115** | 6 | 0 | 18 | 229 | 4 | 5 | **256** | 0 | 0 | 7 | 38 | 13 | 0 | **58** | 3 | 3 | 6 | 145 | 44 | 7 | **202** | 0 | 2 | **631** |
| 1:45:00 PM | 32 | 38 | 35 | 0 | **105** | 0 | 1 | 14 | 211 | 9 | 5 | **239** | 0 | 0 | 4 | 33 | 8 | 0 | **45** | 0 | 0 | 4 | 202 | 36 | 2 | **244** | 1 | 0 | **633** |
| **Hourly Total** | 135 | 159 | 130 | 0 | **424** | 6 | 7 | 77 | 890 | 27 | 14 | **1008** | 1 | 2 | 24 | 140 | 34 | 0 | **198** | 4 | 3 | 24 | 719 | 165 | 16 | **924** | 1 | 4 | **2554** |
| 2:00:00 PM | 22 | 37 | 22 | 0 | **81** | 4 | 2 | 28 | 195 | 3 | 4 | **230** | 0 | 0 | 4 | 53 | 6 | 0 | **63** | 0 | 1 | 5 | 232 | 53 | 1 | **291** | 1 | 0 | **665** |
| 2:15:00 PM | 34 | 36 | 30 | 0 | **100** | 2 | 0 | 26 | 202 | 11 | 4 | **243** | 0 | 0 | 7 | 45 | 5 | 0 | **57** | 0 | 0 | 4 | 198 | 39 | 0 | **241** | 0 | 5 | **641** |
| 2:30:00 PM | 23 | 37 | 30 | 0 | **90** | 2 | 0 | 21 | 219 | 10 | 3 | **253** | 1 | 0 | 6 | 36 | 6 | 0 | **48** | 0 | 1 | 3 | 185 | 43 | 8 | **239** | 0 | 0 | **630** |
| 2:45:00 PM | 32 | 57 | 35 | 0 | **124** | 1 | 1 | 30 | 191 | 11 | 1 | **233** | 0 | 0 | 7 | 38 | 8 | 0 | **53** | 0 | 1 | 7 | 193 | 37 | 4 | **241** | 0 | 0 | **651** |
| **Hourly Total** | 111 | 167 | 117 | 0 | **395** | 9 | 3 | 105 | 807 | 35 | 12 | **959** | 1 | 0 | 24 | 172 | 25 | 0 | **221** | 0 | 3 | 19 | 808 | 172 | 13 | **1012** | 1 | 5 | **2587** |
| **Grand Total** | 351 | 479 | 384 | 0 | **1214** | 16 | 16 | 263 | 2542 | 103 | 29 | **2937** | 3 | 2 | 76 | 478 | 99 | 0 | **653** | 9 | 7 | 66 | 2312 | 482 | 46 | **2906** | 6 | 9 | **7710** |
| **% Approach** | 28.9% | 39.5% | 31.6% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.0% | 86.6% | 3.5% | 1.0% | **0.0%** | 0.0% | 0.0% | 11.6% | 73.2% | 15.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.3% | 79.6% | 16.6% | 1.6% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 4.6% | 6.2% | 5.0% | 0.0% | **15.7%** | 0.0% | 0.0% | 3.4% | 33.0% | 1.3% | 0.4% | **38.1%** | 0.0% | 0.0% | 1.0% | 6.2% | 1.3% | 0.0% | **8.5%** | 0.0% | 0.0% | 0.9% | 30.0% | 6.3% | 0.6% | **37.7%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 332 | 476 | 384 | 0 | **1192** | 0 | 0 | 239 | 2530 | 103 | 29 | **2901** | 0 | 0 | 67 | 476 | 98 | 0 | **641** | 0 | 0 | 35 | 2295 | 482 | 46 | **2858** | 0 | 0 | **7592** |
| **% Lights** | 94.6% | 99.4% | 100.0% | 0.0% | **98.2%** | 0.0% | 0.0% | 90.9% | 99.5% | 100.0% | 100.0% | **98.8%** | 0.0% | 0.0% | 88.2% | 99.6% | 99.0% | 0.0% | **98.2%** | 0.0% | 0.0% | 53.0% | 99.3% | 100.0% | 100.0% | **98.3%** | 0.0% | 0.0% | **98.5%** |
| **Trucks** | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 14 | 0 | 0 | **14** | 0 | 0 | **27** |
| **% Trucks** | 0.3% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.4% | 1.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.4%** |
| **Buses** | 5 | 1 | 0 | 0 | **6** | 0 | 0 | 2 | 1 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **10** |
| **% Buses** | 1.4% | 0.2% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 7 | 8 | 0 | 0 | 0 | 0 | **0** | 3 | 2 | 0 | 0 | 0 | 0 | **0** | 9 | 7 | 0 | 0 | 0 | 0 | **0** | 6 | 9 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 43.8% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 9 | 8 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 56.3% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**12:30:00 PM**

| Leg | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | Sweet Home Road | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:30:00 PM | 19 | 38 | 32 | 0 | **89** | 0 | 1 | 21 | 211 | 12 | 0 | **244** | 1 | 0 | 12 | 33 | 8 | 0 | **53** | 2 | 0 | 4 | 209 | 38 | 1 | **252** | 2 | 0 | **638** |
| 12:45:00 PM | 33 | 39 | 44 | 0 | **116** | 0 | 5 | 18 | 205 | 9 | 0 | **232** | 0 | 0 | 2 | 45 | 12 | 0 | **59** | 1 | 0 | 6 | 200 | 38 | 11 | **255** | 0 | 0 | **662** |
| 1:00:00 PM | 27 | 47 | 37 | 0 | **111** | 0 | 6 | 21 | 218 | 7 | 3 | **249** | 1 | 1 | 2 | 32 | 5 | 0 | **39** | 0 | 0 | 9 | 176 | 44 | 3 | **232** | 0 | 2 | **631** |
| 1:15:00 PM | 31 | 41 | 21 | 0 | **93** | 0 | 0 | 24 | 232 | 7 | 1 | **264** | 0 | 1 | 11 | 37 | 8 | 0 | **56** | 1 | 0 | 5 | 196 | 41 | 4 | **246** | 0 | 0 | **659** |
| **Grand Total** | 110 | 165 | 134 | 0 | **409** | 0 | 12 | 84 | 866 | 35 | 4 | **989** | 2 | 2 | 27 | 147 | 33 | 0 | **207** | 4 | 0 | 24 | 781 | 161 | 19 | **985** | 2 | 2 | **2590** |
| **% Approach** | 26.9% | 40.3% | 32.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.5% | 87.6% | 3.5% | 0.4% | **0.0%** | 0.0% | 0.0% | 13.0% | 71.0% | 15.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.4% | 79.3% | 16.3% | 1.9% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 4.2% | 6.4% | 5.2% | 0.0% | **15.8%** | 0.0% | 0.0% | 3.2% | 33.4% | 1.4% | 0.2% | **38.2%** | 0.0% | 0.0% | 1.0% | 5.7% | 1.3% | 0.0% | **8.0%** | 0.0% | 0.0% | 0.9% | 30.2% | 6.2% | 0.7% | **38.0%** | 0.0% | 0.0% | |
| **PHF** | 0.833 | 0.878 | 0.761 | 0.000 | **0.881** | 0.000 | 0.000 | 0.875 | 0.933 | 0.729 | 0.333 | **0.937** | 0.000 | 0.000 | 0.563 | 0.817 | 0.688 | 0.000 | **0.877** | 0.000 | 0.000 | 0.667 | 0.934 | 0.915 | 0.432 | **0.966** | 0.000 | 0.000 | **0.978** |
| **Lights** | 104 | 162 | 134 | 0 | **400** | 0 | 0 | 80 | 863 | 35 | 4 | **982** | 0 | 0 | 25 | 147 | 32 | 0 | **204** | 0 | 0 | 13 | 776 | 161 | 19 | **969** | 0 | 0 | **2555** |
| **% Lights** | 94.5% | 98.2% | 100.0% | 0.0% | **97.8%** | 0.0% | 0.0% | 95.2% | 99.7% | 100.0% | 100.0% | **99.3%** | 0.0% | 0.0% | 92.6% | 100.0% | 97.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 54.2% | 99.4% | 100.0% | 100.0% | **98.4%** | 0.0% | 0.0% | **98.6%** |
| **Trucks** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 0 | 0 | **8** |
| **% Trucks** | 0.0% | 0.6% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 3.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **1** |
| **% Buses** | 0.0% | 0.6% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 4 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 8 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive at Millersport |
| **Legs and Movements** | All Processed Legs & Movements |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Sheridan Drive at Millersport |
| **Latitude and Longitude** | 42.97934,-78.79902 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:45:00 | 2023-11-16 17:45:00 | 0.965 |


## Turning Movement Data


| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 72 | 159 | 29 | 0 | **260** | 3 | 2 | 22 | 142 | 27 | 0 | **191** | 2 | 1 | 21 | 102 | 11 | 0 | **134** | 0 | 0 | 6 | 171 | 60 | 2 | **239** | 6 | 0 | **824** |
| 3:15:00 PM | 77 | 167 | 28 | 0 | **272** | 0 | 0 | 14 | 172 | 29 | 0 | **215** | 0 | 0 | 20 | 99 | 12 | 0 | **131** | 0 | 0 | 8 | 166 | 63 | 5 | **242** | 0 | 0 | **860** |
| 3:30:00 PM | 75 | 198 | 22 | 0 | **295** | 0 | 0 | 28 | 170 | 27 | 0 | **225** | 1 | 0 | 19 | 107 | 10 | 0 | **136** | 2 | 3 | 6 | 163 | 48 | 1 | **218** | 0 | 3 | **874** |
| 3:45:00 PM | 71 | 159 | 32 | 0 | **262** | 1 | 0 | 27 | 159 | 21 | 0 | **207** | 1 | 0 | 27 | 108 | 8 | 0 | **143** | 1 | 1 | 5 | 182 | 61 | 2 | **250** | 2 | 0 | **862** |
| **Hourly Total** | 295 | 683 | 111 | 0 | **1089** | 4 | 2 | 91 | 643 | 104 | 0 | **838** | 4 | 1 | 87 | 416 | 41 | 0 | **544** | 3 | 4 | 25 | 682 | 232 | 10 | **949** | 8 | 3 | **3420** |
| 4:00:00 PM | 70 | 143 | 26 | 0 | **239** | 0 | 0 | 16 | 154 | 56 | 0 | **226** | 0 | 0 | 28 | 106 | 16 | 0 | **150** | 0 | 0 | 7 | 183 | 62 | 0 | **252** | 0 | 0 | **867** |
| 4:15:00 PM | 93 | 169 | 25 | 0 | **287** | 0 | 0 | 20 | 194 | 37 | 0 | **251** | 0 | 0 | 28 | 96 | 5 | 0 | **129** | 0 | 0 | 5 | 149 | 51 | 3 | **208** | 0 | 0 | **875** |
| 4:30:00 PM | 56 | 148 | 23 | 0 | **227** | 1 | 0 | 25 | 176 | 35 | 0 | **236** | 0 | 0 | 29 | 95 | 14 | 0 | **138** | 0 | 0 | 8 | 170 | 66 | 2 | **246** | 0 | 1 | **847** |
| 4:45:00 PM | 91 | 188 | 25 | 0 | **304** | 0 | 0 | 18 | 189 | 42 | 0 | **249** | 0 | 0 | 22 | 102 | 15 | 0 | **139** | 0 | 0 | 8 | 142 | 54 | 1 | **205** | 0 | 0 | **897** |
| **Hourly Total** | 310 | 648 | 99 | 0 | **1057** | 1 | 0 | 79 | 713 | 170 | 0 | **962** | 0 | 0 | 107 | 399 | 50 | 0 | **556** | 0 | 0 | 28 | 644 | 233 | 6 | **911** | 0 | 1 | **3486** |
| 5:00:00 PM | 79 | 181 | 20 | 0 | **280** | 0 | 0 | 28 | 169 | 31 | 0 | **228** | 0 | 0 | 33 | 99 | 4 | 0 | **136** | 0 | 0 | 4 | 166 | 67 | 0 | **237** | 0 | 0 | **881** |
| 5:15:00 PM | 78 | 180 | 24 | 0 | **282** | 0 | 0 | 14 | 180 | 54 | 0 | **248** | 0 | 0 | 36 | 106 | 5 | 0 | **147** | 0 | 0 | 6 | 185 | 50 | 0 | **241** | 0 | 0 | **918** |
| 5:30:00 PM | 87 | 159 | 21 | 0 | **267** | 0 | 0 | 21 | 156 | 37 | 0 | **214** | 0 | 0 | 27 | 113 | 6 | 0 | **146** | 0 | 0 | 2 | 151 | 68 | 0 | **221** | 0 | 0 | **848** |
| 5:45:00 PM | 78 | 156 | 31 | 0 | **265** | 1 | 0 | 17 | 159 | 34 | 0 | **210** | 0 | 1 | 25 | 100 | 7 | 0 | **132** | 0 | 0 | 4 | 167 | 54 | 0 | **225** | 0 | 0 | **832** |
| **Hourly Total** | 322 | 676 | 96 | 0 | **1094** | 1 | 0 | 80 | 664 | 156 | 0 | **900** | 0 | 1 | 121 | 418 | 22 | 0 | **561** | 0 | 0 | 16 | 669 | 239 | 0 | **924** | 0 | 0 | **3479** |
| **Grand Total** | 927 | 2007 | 306 | 0 | **3240** | 6 | 2 | 250 | 2020 | 430 | 0 | **2700** | 4 | 2 | 315 | 1233 | 113 | 0 | **1661** | 3 | 4 | 69 | 1995 | 704 | 16 | **2784** | 8 | 4 | **10385** |
| **% Approach** | 28.6% | 61.9% | 9.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.3% | 74.8% | 15.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 19.0% | 74.2% | 6.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.5% | 71.7% | 25.3% | 0.6% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 8.9% | 19.3% | 2.9% | 0.0% | **31.2%** | 0.0% | 0.0% | 2.4% | 19.5% | 4.1% | 0.0% | **26.0%** | 0.0% | 0.0% | 3.0% | 11.9% | 1.1% | 0.0% | **16.0%** | 0.0% | 0.0% | 0.7% | 19.2% | 6.8% | 0.2% | **26.8%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 884 | 1925 | 301 | 0 | **3110** | 0 | 0 | 226 | 2006 | 430 | 0 | **2662** | 0 | 0 | 301 | 1204 | 111 | 0 | **1616** | 0 | 0 | 68 | 1974 | 660 | 16 | **2718** | 0 | 0 | **10106** |
| **% Lights** | 95.4% | 95.9% | 98.4% | 0.0% | **96.0%** | 0.0% | 0.0% | 90.4% | 99.3% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 95.6% | 97.6% | 98.2% | 0.0% | **97.3%** | 0.0% | 0.0% | 98.6% | 98.9% | 93.8% | 100.0% | **97.6%** | 0.0% | 0.0% | **97.3%** |
| **Trucks** | 9 | 18 | 5 | 0 | **32** | 0 | 0 | 10 | 6 | 0 | 0 | **16** | 0 | 0 | 2 | 8 | 2 | 0 | **12** | 0 | 0 | 0 | 16 | 13 | 0 | **29** | 0 | 0 | **89** |
| **% Trucks** | 1.0% | 0.9% | 1.6% | 0.0% | **1.0%** | 0.0% | 0.0% | 4.0% | 0.3% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.6% | 0.6% | 1.8% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.8% | 1.8% | 0.0% | **1.0%** | 0.0% | 0.0% | **0.9%** |
| **Buses** | 1 | 61 | 0 | 0 | **62** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 4 | 18 | 0 | 0 | **22** | 0 | 0 | 0 | 4 | 28 | 0 | **32** | 0 | 0 | **123** |
| **% Buses** | 0.1% | 3.0% | 0.0% | 0.0% | **1.9%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 1.3% | 1.5% | 0.0% | 0.0% | **1.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 4.0% | 0.0% | **1.1%** | 0.0% | 0.0% | **1.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 5 | 2 | 0 | 0 | 0 | 0 | **0** | 4 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 4 | 0 | 0 | 0 | 0 | **0** | 8 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:45:00 PM | 91 | 188 | 25 | 0 | **304** | 0 | 0 | 18 | 189 | 42 | 0 | **249** | 0 | 0 | 22 | 102 | 15 | 0 | **139** | 0 | 0 | 8 | 142 | 54 | 1 | **205** | 0 | 0 | **897** |
| 5:00:00 PM | 79 | 181 | 20 | 0 | **280** | 0 | 0 | 28 | 169 | 31 | 0 | **228** | 0 | 0 | 33 | 99 | 4 | 0 | **136** | 0 | 0 | 4 | 166 | 67 | 0 | **237** | 0 | 0 | **881** |
| 5:15:00 PM | 78 | 180 | 24 | 0 | **282** | 0 | 0 | 14 | 180 | 54 | 0 | **248** | 0 | 0 | 36 | 106 | 5 | 0 | **147** | 0 | 0 | 6 | 185 | 50 | 0 | **241** | 0 | 0 | **918** |
| 5:30:00 PM | 87 | 159 | 21 | 0 | **267** | 0 | 0 | 21 | 156 | 37 | 0 | **214** | 0 | 0 | 27 | 113 | 6 | 0 | **146** | 0 | 0 | 2 | 151 | 68 | 0 | **221** | 0 | 0 | **848** |
| **Grand Total** | 335 | 708 | 90 | 0 | **1133** | 0 | 0 | 81 | 694 | 164 | 0 | **939** | 0 | 0 | 118 | 420 | 30 | 0 | **568** | 0 | 0 | 20 | 644 | 239 | 1 | **904** | 0 | 0 | **3544** |
| **% Approach** | 29.6% | 62.5% | 7.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.6% | 73.9% | 17.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 20.8% | 73.9% | 5.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.2% | 71.2% | 26.4% | 0.1% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 9.5% | 20.0% | 2.5% | 0.0% | **32.0%** | 0.0% | 0.0% | 2.3% | 19.6% | 4.6% | 0.0% | **26.5%** | 0.0% | 0.0% | 3.3% | 11.9% | 0.8% | 0.0% | **16.0%** | 0.0% | 0.0% | 0.6% | 18.2% | 6.7% | 0.0% | **25.5%** | 0.0% | 0.0% | |
| **PHF** | 0.920 | 0.941 | 0.900 | 0.000 | **0.932** | 0.000 | 0.000 | 0.723 | 0.918 | 0.759 | 0.000 | **0.943** | 0.000 | 0.000 | 0.819 | 0.929 | 0.500 | 0.000 | **0.966** | 0.000 | 0.000 | 0.625 | 0.870 | 0.879 | 0.250 | **0.938** | 0.000 | 0.000 | **0.965** |
| **Lights** | 324 | 688 | 89 | 0 | **1101** | 0 | 0 | 72 | 690 | 164 | 0 | **926** | 0 | 0 | 116 | 414 | 29 | 0 | **559** | 0 | 0 | 19 | 641 | 224 | 1 | **885** | 0 | 0 | **3471** |
| **% Lights** | 96.7% | 97.2% | 98.9% | 0.0% | **97.2%** | 0.0% | 0.0% | 88.9% | 99.4% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 98.3% | 98.6% | 96.7% | 0.0% | **98.4%** | 0.0% | 0.0% | 95.0% | 99.5% | 93.7% | 100.0% | **97.9%** | 0.0% | 0.0% | **97.9%** |
| **Trucks** | 2 | 5 | 1 | 0 | **8** | 0 | 0 | 5 | 2 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 4 | 0 | **7** | 0 | 0 | **23** |
| **% Trucks** | 0.6% | 0.7% | 1.1% | 0.0% | **0.7%** | 0.0% | 0.0% | 6.2% | 0.3% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 3.3% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.5% | 1.7% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 14 | 0 | 0 | **14** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 6 | 0 | 0 | **6** | 0 | 0 | 0 | 0 | 10 | 0 | **10** | 0 | 0 | **31** |
| **% Buses** | 0.0% | 2.0% | 0.0% | 0.0% | **1.2%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 1.4% | 0.0% | 0.0% | **1.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 4.2% | 0.0% | **1.1%** | 0.0% | 0.0% | **0.9%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 72 | 159 | 29 | 0 | **260** | 3 | 2 | 22 | 142 | 27 | 0 | **191** | 2 | 1 | 21 | 102 | 11 | 0 | **134** | 0 | 0 | 6 | 171 | 60 | 2 | **239** | 6 | 0 | **824** |
| 3:15:00 PM | 77 | 167 | 28 | 0 | **272** | 0 | 0 | 14 | 172 | 29 | 0 | **215** | 0 | 0 | 20 | 99 | 12 | 0 | **131** | 0 | 0 | 8 | 166 | 63 | 5 | **242** | 0 | 0 | **860** |
| 3:30:00 PM | 75 | 198 | 22 | 0 | **295** | 0 | 0 | 28 | 170 | 27 | 0 | **225** | 1 | 0 | 19 | 107 | 10 | 0 | **136** | 2 | 3 | 6 | 163 | 48 | 1 | **218** | 0 | 3 | **874** |
| 3:45:00 PM | 71 | 159 | 32 | 0 | **262** | 1 | 0 | 27 | 159 | 21 | 0 | **207** | 1 | 0 | 27 | 108 | 8 | 0 | **143** | 1 | 1 | 5 | 182 | 61 | 2 | **250** | 2 | 0 | **862** |
| **Hourly Total** | 295 | 683 | 111 | 0 | **1089** | 4 | 2 | 91 | 643 | 104 | 0 | **838** | 4 | 1 | 87 | 416 | 41 | 0 | **544** | 3 | 4 | 25 | 682 | 232 | 10 | **949** | 8 | 3 | **3420** |
| 4:00:00 PM | 70 | 143 | 26 | 0 | **239** | 0 | 0 | 16 | 154 | 56 | 0 | **226** | 0 | 0 | 28 | 106 | 16 | 0 | **150** | 0 | 0 | 7 | 183 | 62 | 0 | **252** | 0 | 0 | **867** |
| 4:15:00 PM | 93 | 169 | 25 | 0 | **287** | 0 | 0 | 20 | 194 | 37 | 0 | **251** | 0 | 0 | 28 | 96 | 5 | 0 | **129** | 0 | 0 | 5 | 149 | 51 | 3 | **208** | 0 | 0 | **875** |
| 4:30:00 PM | 56 | 148 | 23 | 0 | **227** | 1 | 0 | 25 | 176 | 35 | 0 | **236** | 0 | 0 | 29 | 95 | 14 | 0 | **138** | 0 | 0 | 8 | 170 | 66 | 2 | **246** | 0 | 1 | **847** |
| 4:45:00 PM | 91 | 188 | 25 | 0 | **304** | 0 | 0 | 18 | 189 | 42 | 0 | **249** | 0 | 0 | 22 | 102 | 15 | 0 | **139** | 0 | 0 | 8 | 142 | 54 | 1 | **205** | 0 | 0 | **897** |
| **Hourly Total** | 310 | 648 | 99 | 0 | **1057** | 1 | 0 | 79 | 713 | 170 | 0 | **962** | 0 | 0 | 107 | 399 | 50 | 0 | **556** | 0 | 0 | 28 | 644 | 233 | 6 | **911** | 0 | 1 | **3486** |
| 5:00:00 PM | 79 | 181 | 20 | 0 | **280** | 0 | 0 | 28 | 169 | 31 | 0 | **228** | 0 | 0 | 33 | 99 | 4 | 0 | **136** | 0 | 0 | 4 | 166 | 67 | 0 | **237** | 0 | 0 | **881** |
| 5:15:00 PM | 78 | 180 | 24 | 0 | **282** | 0 | 0 | 14 | 180 | 54 | 0 | **248** | 0 | 0 | 36 | 106 | 5 | 0 | **147** | 0 | 0 | 6 | 185 | 50 | 0 | **241** | 0 | 0 | **918** |
| 5:30:00 PM | 87 | 159 | 21 | 0 | **267** | 0 | 0 | 21 | 156 | 37 | 0 | **214** | 0 | 0 | 27 | 113 | 6 | 0 | **146** | 0 | 0 | 2 | 151 | 68 | 0 | **221** | 0 | 0 | **848** |
| 5:45:00 PM | 78 | 156 | 31 | 0 | **265** | 1 | 0 | 17 | 159 | 34 | 0 | **210** | 0 | 1 | 25 | 100 | 7 | 0 | **132** | 0 | 0 | 4 | 167 | 54 | 0 | **225** | 0 | 0 | **832** |
| **Hourly Total** | 322 | 676 | 96 | 0 | **1094** | 1 | 0 | 80 | 664 | 156 | 0 | **900** | 0 | 1 | 121 | 418 | 22 | 0 | **561** | 0 | 0 | 16 | 669 | 239 | 0 | **924** | 0 | 0 | **3479** |
| **Grand Total** | 927 | 2007 | 306 | 0 | **3240** | 6 | 2 | 250 | 2020 | 430 | 0 | **2700** | 4 | 2 | 315 | 1233 | 113 | 0 | **1661** | 3 | 4 | 69 | 1995 | 704 | 16 | **2784** | 8 | 4 | **10385** |
| **% Approach** | 28.6% | 61.9% | 9.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 9.3% | 74.8% | 15.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 19.0% | 74.2% | 6.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.5% | 71.7% | 25.3% | 0.6% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 8.9% | 19.3% | 2.9% | 0.0% | **31.2%** | 0.0% | 0.0% | 2.4% | 19.5% | 4.1% | 0.0% | **26.0%** | 0.0% | 0.0% | 3.0% | 11.9% | 1.1% | 0.0% | **16.0%** | 0.0% | 0.0% | 0.7% | 19.2% | 6.8% | 0.2% | **26.8%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 884 | 1925 | 301 | 0 | **3110** | 0 | 0 | 226 | 2006 | 430 | 0 | **2662** | 0 | 0 | 301 | 1204 | 111 | 0 | **1616** | 0 | 0 | 68 | 1974 | 660 | 16 | **2718** | 0 | 0 | **10106** |
| **% Lights** | 95.4% | 95.9% | 98.4% | 0.0% | **96.0%** | 0.0% | 0.0% | 90.4% | 99.3% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 95.6% | 97.6% | 98.2% | 0.0% | **97.3%** | 0.0% | 0.0% | 98.6% | 98.9% | 93.8% | 100.0% | **97.6%** | 0.0% | 0.0% | **97.3%** |
| **Trucks** | 9 | 18 | 5 | 0 | **32** | 0 | 0 | 10 | 6 | 0 | 0 | **16** | 0 | 0 | 2 | 8 | 2 | 0 | **12** | 0 | 0 | 0 | 16 | 13 | 0 | **29** | 0 | 0 | **89** |
| **% Trucks** | 1.0% | 0.9% | 1.6% | 0.0% | **1.0%** | 0.0% | 0.0% | 4.0% | 0.3% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.6% | 0.6% | 1.8% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.8% | 1.8% | 0.0% | **1.0%** | 0.0% | 0.0% | **0.9%** |
| **Buses** | 1 | 61 | 0 | 0 | **62** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 4 | 18 | 0 | 0 | **22** | 0 | 0 | 0 | 4 | 28 | 0 | **32** | 0 | 0 | **123** |
| **% Buses** | 0.1% | 3.0% | 0.0% | 0.0% | **1.9%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 1.3% | 1.5% | 0.0% | 0.0% | **1.3%** | 0.0% | 0.0% | 0.0% | 0.2% | 4.0% | 0.0% | **1.1%** | 0.0% | 0.0% | **1.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 5 | 2 | 0 | 0 | 0 | 0 | **0** | 4 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 4 | 0 | 0 | 0 | 0 | **0** | 8 | 4 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 83.3% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 16.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 4:45:00 PM | 91 | 188 | 25 | 0 | **304** | 0 | 0 | 18 | 189 | 42 | 0 | **249** | 0 | 0 | 22 | 102 | 15 | 0 | **139** | 0 | 0 | 8 | 142 | 54 | 1 | **205** | 0 | 0 | **897** |
| 5:00:00 PM | 79 | 181 | 20 | 0 | **280** | 0 | 0 | 28 | 169 | 31 | 0 | **228** | 0 | 0 | 33 | 99 | 4 | 0 | **136** | 0 | 0 | 4 | 166 | 67 | 0 | **237** | 0 | 0 | **881** |
| 5:15:00 PM | 78 | 180 | 24 | 0 | **282** | 0 | 0 | 14 | 180 | 54 | 0 | **248** | 0 | 0 | 36 | 106 | 5 | 0 | **147** | 0 | 0 | 6 | 185 | 50 | 0 | **241** | 0 | 0 | **918** |
| 5:30:00 PM | 87 | 159 | 21 | 0 | **267** | 0 | 0 | 21 | 156 | 37 | 0 | **214** | 0 | 0 | 27 | 113 | 6 | 0 | **146** | 0 | 0 | 2 | 151 | 68 | 0 | **221** | 0 | 0 | **848** |
| **Grand Total** | 335 | 708 | 90 | 0 | **1133** | 0 | 0 | 81 | 694 | 164 | 0 | **939** | 0 | 0 | 118 | 420 | 30 | 0 | **568** | 0 | 0 | 20 | 644 | 239 | 1 | **904** | 0 | 0 | **3544** |
| **% Approach** | 29.6% | 62.5% | 7.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.6% | 73.9% | 17.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 20.8% | 73.9% | 5.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.2% | 71.2% | 26.4% | 0.1% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 9.5% | 20.0% | 2.5% | 0.0% | **32.0%** | 0.0% | 0.0% | 2.3% | 19.6% | 4.6% | 0.0% | **26.5%** | 0.0% | 0.0% | 3.3% | 11.9% | 0.8% | 0.0% | **16.0%** | 0.0% | 0.0% | 0.6% | 18.2% | 6.7% | 0.0% | **25.5%** | 0.0% | 0.0% | |
| **PHF** | 0.920 | 0.941 | 0.900 | 0.000 | **0.932** | 0.000 | 0.000 | 0.723 | 0.918 | 0.759 | 0.000 | **0.943** | 0.000 | 0.000 | 0.819 | 0.929 | 0.500 | 0.000 | **0.966** | 0.000 | 0.000 | 0.625 | 0.870 | 0.879 | 0.250 | **0.938** | 0.000 | 0.000 | **0.965** |
| **Lights** | 324 | 688 | 89 | 0 | **1101** | 0 | 0 | 72 | 690 | 164 | 0 | **926** | 0 | 0 | 116 | 414 | 29 | 0 | **559** | 0 | 0 | 19 | 641 | 224 | 1 | **885** | 0 | 0 | **3471** |
| **% Lights** | 96.7% | 97.2% | 98.9% | 0.0% | **97.2%** | 0.0% | 0.0% | 88.9% | 99.4% | 100.0% | 0.0% | **98.6%** | 0.0% | 0.0% | 98.3% | 98.6% | 96.7% | 0.0% | **98.4%** | 0.0% | 0.0% | 95.0% | 99.5% | 93.7% | 100.0% | **97.9%** | 0.0% | 0.0% | **97.9%** |
| **Trucks** | 2 | 5 | 1 | 0 | **8** | 0 | 0 | 5 | 2 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | 0 | 3 | 4 | 0 | **7** | 0 | 0 | **23** |
| **% Trucks** | 0.6% | 0.7% | 1.1% | 0.0% | **0.7%** | 0.0% | 0.0% | 6.2% | 0.3% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 3.3% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.5% | 1.7% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 14 | 0 | 0 | **14** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 6 | 0 | 0 | **6** | 0 | 0 | 0 | 0 | 10 | 0 | **10** | 0 | 0 | **31** |
| **% Buses** | 0.0% | 2.0% | 0.0% | 0.0% | **1.2%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 1.4% | 0.0% | 0.0% | **1.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 4.2% | 0.0% | **1.1%** | 0.0% | 0.0% | **0.9%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TRI-STATE TRAFFIC DATA

TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Sheridan Drive at Millersport |
| **Legs and Movements** | All Processed Legs & Movements |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Sheridan Drive at Millersport |
| **Latitude and Longitude** | 42.97934,-78.79902 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 12:00:00 | 2023-11-18 13:00:00 | 0.996 |


## Turning Movement Data


| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Direction** | **Southbound** | | | | | | | **Westbound** | | | | | | | **Northbound** | | | | | | | **Eastbound** | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | **Total** |
| 12:00:00 | 70 | 95 | 19 | 0 | **184** | 0 | 1 | 11 | 155 | 27 | 6 | **199** | 0 | 0 | 21 | 122 | 20 | 0 | **163** | 0 | 0 | 3 | 162 | 55 | 1 | **221** | 0 | 5 | **767** |
| 12:15:00 | 82 | 97 | 18 | 0 | **197** | 0 | 0 | 12 | 165 | 30 | 3 | **210** | 0 | 0 | 20 | 113 | 22 | 0 | **155** | 1 | 1 | 7 | 131 | 65 | 0 | **203** | 0 | 0 | **765** |
| 12:30:00 | 70 | 104 | 19 | 0 | **193** | 0 | 0 | 12 | 142 | 19 | 2 | **175** | 0 | 1 | 25 | 115 | 14 | 0 | **154** | 0 | 1 | 3 | 166 | 66 | 0 | **235** | 0 | 0 | **757** |
| 12:45:00 | 76 | 103 | 28 | 0 | **207** | 0 | 0 | 13 | 156 | 24 | 3 | **196** | 0 | 0 | 24 | 90 | 9 | 0 | **123** | 0 | 0 | 6 | 159 | 73 | 2 | **240** | 0 | 0 | **766** |
| **Hourly Total** | 298 | 399 | 84 | 0 | **781** | 0 | 1 | 48 | 618 | 100 | 14 | **780** | 0 | 1 | 90 | 440 | 65 | 0 | **595** | 1 | 2 | 19 | 618 | 259 | 3 | **899** | 0 | 5 | **3055** |
| 13:00:00 | 76 | 112 | 28 | 0 | **216** | 0 | 0 | 12 | 139 | 30 | 2 | **183** | 0 | 0 | 24 | 70 | 12 | 0 | **106** | 2 | 1 | 5 | 137 | 51 | 1 | **194** | 1 | 0 | **699** |
| 13:15:00 | 76 | 89 | 27 | 0 | **192** | 0 | 0 | 16 | 175 | 29 | 4 | **224** | 0 | 0 | 26 | 113 | 12 | 0 | **151** | 3 | 0 | 3 | 162 | 44 | 0 | **209** | 0 | 0 | **776** |
| 13:30:00 | 78 | 85 | 19 | 0 | **182** | 0 | 1 | 10 | 171 | 16 | 5 | **202** | 0 | 0 | 21 | 107 | 13 | 0 | **141** | 0 | 0 | 6 | 151 | 65 | 1 | **223** | 0 | 0 | **748** |
| 13:45:00 | 77 | 100 | 25 | 0 | **202** | 0 | 0 | 14 | 140 | 10 | 5 | **169** | 0 | 0 | 35 | 114 | 10 | 0 | **159** | 1 | 0 | 2 | 156 | 50 | 1 | **209** | 0 | 0 | **739** |
| **Hourly Total** | 307 | 386 | 99 | 0 | **792** | 0 | 1 | 52 | 625 | 85 | 16 | **778** | 0 | 0 | 106 | 404 | 47 | 0 | **557** | 6 | 1 | 16 | 606 | 210 | 3 | **835** | 1 | 0 | **2962** |
| 14:00:00 | 60 | 84 | 23 | 0 | **167** | 0 | 0 | 17 | 147 | 26 | 7 | **197** | 0 | 0 | 28 | 94 | 15 | 0 | **137** | 2 | 1 | 7 | 166 | 67 | 0 | **240** | 0 | 0 | **741** |
| 14:15:00 | 71 | 88 | 29 | 0 | **188** | 0 | 0 | 10 | 153 | 19 | 4 | **186** | 0 | 0 | 24 | 88 | 15 | 0 | **127** | 0 | 1 | 4 | 165 | 64 | 0 | **233** | 0 | 0 | **734** |
| 14:30:00 | 82 | 117 | 18 | 0 | **217** | 0 | 0 | 16 | 151 | 18 | 0 | **185** | 0 | 0 | 32 | 117 | 12 | 0 | **161** | 0 | 0 | 5 | 135 | 51 | 2 | **193** | 0 | 0 | **756** |
| 14:45:00 | 55 | 93 | 27 | 0 | **175** | 0 | 0 | 14 | 147 | 30 | 1 | **192** | 0 | 0 | 28 | 90 | 18 | 0 | **136** | 0 | 1 | 5 | 149 | 66 | 2 | **222** | 1 | 0 | **725** |
| **Hourly Total** | 268 | 382 | 97 | 0 | **747** | 0 | 0 | 57 | 598 | 93 | 12 | **760** | 0 | 0 | 112 | 389 | 60 | 0 | **561** | 2 | 3 | 21 | 615 | 248 | 4 | **888** | 1 | 0 | **2956** |
| **Grand Total** | 873 | 1167 | 280 | 0 | **2320** | 0 | 2 | 157 | 1841 | 278 | 42 | **2318** | 0 | 1 | 308 | 1233 | 172 | 0 | **1713** | 9 | 6 | 56 | 1839 | 717 | 10 | **2622** | 2 | 5 | **8973** |
| **% Approach** | 37.6% | 50.3% | 12.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.8% | 79.4% | 12.0% | 1.8% | **0.0%** | 0.0% | 0.0% | 18.0% | 72.0% | 10.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.1% | 70.1% | 27.3% | 0.4% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 9.7% | 13.0% | 3.1% | 0.0% | **25.9%** | 0.0% | 0.0% | 1.7% | 20.5% | 3.1% | 0.5% | **25.8%** | 0.0% | 0.0% | 3.4% | 13.7% | 1.9% | 0.0% | **19.1%** | 0.0% | 0.0% | 0.6% | 20.5% | 8.0% | 0.1% | **29.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 752 | 1147 | 276 | 0 | **2175** | 0 | 0 | 151 | 1836 | 276 | 42 | **2305** | 0 | 0 | 262 | 1214 | 164 | 0 | **1640** | 0 | 0 | 55 | 1828 | 711 | 10 | **2604** | 0 | 0 | **8724** |
| **% Lights** | 86.1% | 98.3% | 98.6% | 0.0% | **93.8%** | 0.0% | 0.0% | 96.2% | 99.7% | 99.3% | 100.0% | **99.4%** | 0.0% | 0.0% | 85.1% | 98.5% | 95.3% | 0.0% | **95.7%** | 0.0% | 0.0% | 98.2% | 99.4% | 99.2% | 100.0% | **99.3%** | 0.0% | 0.0% | **97.2%** |
| **Trucks** | 3 | 8 | 3 | 0 | **14** | 0 | 0 | 0 | 3 | 2 | 0 | **5** | 0 | 0 | 4 | 8 | 1 | 0 | **13** | 0 | 0 | 0 | 10 | 5 | 0 | **15** | 0 | 0 | **47** |
| **% Trucks** | 0.3% | 0.7% | 1.1% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.7% | 0.0% | **0.2%** | 0.0% | 0.0% | 1.3% | 0.6% | 0.6% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.7% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.5%** |
| **Buses** | 0 | 11 | 0 | 0 | **11** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 10 | 2 | 0 | **12** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **25** |
| **% Buses** | 0.0% | 0.9% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.8% | 1.2% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 9 | 5 | 0 | 0 | 0 | 0 | **0** | 2 | 5 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 83.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 16.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot




TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

**12:00:00**

| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 70 | 95 | 19 | 0 | **184** | 0 | 1 | 11 | 155 | 27 | 6 | **199** | 0 | 0 | 21 | 122 | 20 | 0 | **163** | 0 | 0 | 3 | 162 | 55 | 1 | **221** | 0 | 5 | **767** |
| 12:15:00 | 82 | 97 | 18 | 0 | **197** | 0 | 0 | 12 | 165 | 30 | 3 | **210** | 0 | 0 | 20 | 113 | 22 | 0 | **155** | 1 | 1 | 7 | 131 | 65 | 0 | **203** | 0 | 0 | **765** |
| 12:30:00 | 70 | 104 | 19 | 0 | **193** | 0 | 0 | 12 | 142 | 19 | 2 | **175** | 0 | 1 | 25 | 115 | 14 | 0 | **154** | 0 | 1 | 3 | 166 | 66 | 0 | **235** | 0 | 0 | **757** |
| 12:45:00 | 76 | 103 | 28 | 0 | **207** | 0 | 0 | 13 | 156 | 24 | 3 | **196** | 0 | 0 | 24 | 90 | 9 | 0 | **123** | 0 | 0 | 6 | 159 | 73 | 2 | **240** | 0 | 0 | **766** |
| **Grand Total** | 298 | 399 | 84 | 0 | **781** | 0 | 1 | 48 | 618 | 100 | 14 | **780** | 0 | 1 | 90 | 440 | 65 | 0 | **595** | 1 | 2 | 19 | 618 | 259 | 3 | **899** | 0 | 5 | **3055** |
| **% Approach** | 38.2% | 51.1% | 10.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.2% | 79.2% | 12.8% | 1.8% | **0.0%** | 0.0% | 0.0% | 15.1% | 73.9% | 10.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.1% | 68.7% | 28.8% | 0.3% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 9.8% | 13.1% | 2.7% | 0.0% | **25.6%** | 0.0% | 0.0% | 1.6% | 20.2% | 3.3% | 0.5% | **25.5%** | 0.0% | 0.0% | 2.9% | 14.4% | 2.1% | 0.0% | **19.5%** | 0.0% | 0.0% | 0.6% | 20.2% | 8.5% | 0.1% | **29.4%** | 0.0% | 0.0% | |
| **PHF** | 0.909 | 0.959 | 0.750 | 0.000 | **0.943** | 0.000 | 0.000 | 0.923 | 0.936 | 0.833 | 0.583 | **0.929** | 0.000 | 0.000 | 0.900 | 0.902 | 0.739 | 0.000 | **0.913** | 0.000 | 0.000 | 0.679 | 0.931 | 0.887 | 0.375 | **0.936** | 0.000 | 0.000 | **0.996** |
| **Lights** | 263 | 393 | 82 | 0 | **738** | 0 | 0 | 48 | 618 | 98 | 14 | **778** | 0 | 0 | 77 | 431 | 62 | 0 | **570** | 0 | 0 | 18 | 615 | 257 | 3 | **893** | 0 | 0 | **2979** |
| **% Lights** | 88.3% | 98.5% | 97.6% | 0.0% | **94.5%** | 0.0% | 0.0% | 100.0% | 100.0% | 98.0% | 100.0% | **99.7%** | 0.0% | 0.0% | 85.6% | 98.0% | 95.4% | 0.0% | **95.8%** | 0.0% | 0.0% | 94.7% | 99.5% | 99.2% | 100.0% | **99.3%** | 0.0% | 0.0% | **97.5%** |
| **Trucks** | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 2 | 0 | **2** | 0 | 0 | 3 | 6 | 1 | 0 | **10** | 0 | 0 | 0 | 3 | 2 | 0 | **5** | 0 | 0 | **20** |
| **% Trucks** | 0.0% | 0.5% | 1.2% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 2.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 3.3% | 1.4% | 1.5% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.8% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.7%** |
| **Buses** | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **8** |
| **% Buses** | 0.0% | 1.0% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.7% | 1.5% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 5 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 15:00:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 15:15:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 15:30:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 15:45:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **Hourly Total** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 16:00:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 16:15:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 16:30:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 16:45:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **Hourly Total** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 17:00:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 17:15:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 17:30:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| 17:45:00 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **Hourly Total** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **Grand Total** | 873 | 1167 | 280 | 0 | **2320** | 0 | 2 | 157 | 1841 | 278 | 42 | **2318** | 0 | 1 | 308 | 1233 | 172 | 0 | **1713** | 9 | 6 | 56 | 1839 | 717 | 10 | **2622** | 2 | 5 | **8973** |
| **% Approach** | 37.6% | 50.3% | 12.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.8% | 79.4% | 12.0% | 1.8% | **0.0%** | 0.0% | 0.0% | 18.0% | 72.0% | 10.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.1% | 70.1% | 27.3% | 0.4% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 9.7% | 13.0% | 3.1% | 0.0% | **25.9%** | 0.0% | 0.0% | 1.7% | 20.5% | 3.1% | 0.5% | **25.8%** | 0.0% | 0.0% | 3.4% | 13.7% | 1.9% | 0.0% | **19.1%** | 0.0% | 0.0% | 0.6% | 20.5% | 8.0% | 0.1% | **29.2%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 752 | 1147 | 276 | 0 | **2175** | 0 | 0 | 151 | 1836 | 276 | 42 | **2305** | 0 | 0 | 262 | 1214 | 164 | 0 | **1640** | 0 | 0 | 55 | 1828 | 711 | 10 | **2604** | 0 | 0 | **8724** |
| **% Lights** | 86.1% | 98.3% | 98.6% | 0.0% | **93.8%** | 0.0% | 0.0% | 96.2% | 99.7% | 99.3% | 100.0% | **99.4%** | 0.0% | 0.0% | 85.1% | 98.5% | 95.3% | 0.0% | **95.7%** | 0.0% | 0.0% | 98.2% | 99.4% | 99.2% | 100.0% | **99.3%** | 0.0% | 0.0% | **97.2%** |
| **Trucks** | 3 | 8 | 3 | 0 | **14** | 0 | 0 | 0 | 3 | 2 | 0 | **5** | 0 | 0 | 4 | 8 | 1 | 0 | **13** | 0 | 0 | 0 | 10 | 5 | 0 | **15** | 0 | 0 | **47** |
| **% Trucks** | 0.3% | 0.7% | 1.1% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.7% | 0.0% | **0.2%** | 0.0% | 0.0% | 1.3% | 0.6% | 0.6% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.7% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.5%** |
| **Buses** | 0 | 11 | 0 | 0 | **11** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 10 | 2 | 0 | **12** | 0 | 0 | 0 | 0 | 1 | 0 | **1** | 0 | 0 | **25** |
| **% Buses** | 0.0% | 0.9% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.8% | 1.2% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 9 | 5 | 0 | 0 | 0 | 0 | **0** | 2 | 5 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 83.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 16.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot




## Turning Movement Peak Hour Data (PM)

**12:00:00**

| Leg | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | Millersport Highway | | | | | | | Sheridan Drive | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 70 | 95 | 19 | 0 | **184** | 0 | 1 | 11 | 155 | 27 | 6 | **199** | 0 | 0 | 21 | 122 | 20 | 0 | **163** | 0 | 0 | 3 | 162 | 55 | 1 | **221** | 0 | 5 | **767** |
| 12:15:00 | 82 | 97 | 18 | 0 | **197** | 0 | 0 | 12 | 165 | 30 | 3 | **210** | 0 | 0 | 20 | 113 | 22 | 0 | **155** | 1 | 1 | 7 | 131 | 65 | 0 | **203** | 0 | 0 | **765** |
| 12:30:00 | 70 | 104 | 19 | 0 | **193** | 0 | 0 | 12 | 142 | 19 | 2 | **175** | 0 | 1 | 25 | 115 | 14 | 0 | **154** | 0 | 1 | 3 | 166 | 66 | 0 | **235** | 0 | 0 | **757** |
| 12:45:00 | 76 | 103 | 28 | 0 | **207** | 0 | 0 | 13 | 156 | 24 | 3 | **196** | 0 | 0 | 24 | 90 | 9 | 0 | **123** | 0 | 0 | 6 | 159 | 73 | 2 | **240** | 0 | 0 | **766** |
| **Grand Total** | 298 | 399 | 84 | 0 | **781** | 0 | 1 | 48 | 618 | 100 | 14 | **780** | 0 | 1 | 90 | 440 | 65 | 0 | **595** | 1 | 2 | 19 | 618 | 259 | 3 | **899** | 0 | 5 | **3055** |
| **% Approach** | 38.2% | 51.1% | 10.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.2% | 79.2% | 12.8% | 1.8% | **0.0%** | 0.0% | 0.0% | 15.1% | 73.9% | 10.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 2.1% | 68.7% | 28.8% | 0.3% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 9.8% | 13.1% | 2.7% | 0.0% | **25.6%** | 0.0% | 0.0% | 1.6% | 20.2% | 3.3% | 0.5% | **25.5%** | 0.0% | 0.0% | 2.9% | 14.4% | 2.1% | 0.0% | **19.5%** | 0.0% | 0.0% | 0.6% | 20.2% | 8.5% | 0.1% | **29.4%** | 0.0% | 0.0% | |
| **PHF** | 0.909 | 0.959 | 0.750 | 0.000 | **0.943** | 0.000 | 0.000 | 0.923 | 0.936 | 0.833 | 0.583 | **0.929** | 0.000 | 0.000 | 0.900 | 0.902 | 0.739 | 0.000 | **0.913** | 0.000 | 0.000 | 0.679 | 0.931 | 0.887 | 0.375 | **0.936** | 0.000 | 0.000 | **0.996** |
| **Lights** | 263 | 393 | 82 | 0 | **738** | 0 | 0 | 48 | 618 | 98 | 14 | **778** | 0 | 0 | 77 | 431 | 62 | 0 | **570** | 0 | 0 | 18 | 615 | 257 | 3 | **893** | 0 | 0 | **2979** |
| **% Lights** | 88.3% | 98.5% | 97.6% | 0.0% | **94.5%** | 0.0% | 0.0% | 100.0% | 100.0% | 98.0% | 100.0% | **99.7%** | 0.0% | 0.0% | 85.6% | 98.0% | 95.4% | 0.0% | **95.8%** | 0.0% | 0.0% | 94.7% | 99.5% | 99.2% | 100.0% | **99.3%** | 0.0% | 0.0% | **97.5%** |
| **Trucks** | 0 | 2 | 1 | 0 | **3** | 0 | 0 | 0 | 0 | 2 | 0 | **2** | 0 | 0 | 3 | 6 | 1 | 0 | **10** | 0 | 0 | 0 | 3 | 2 | 0 | **5** | 0 | 0 | **20** |
| **% Trucks** | 0.0% | 0.5% | 1.2% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 2.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 3.3% | 1.4% | 1.5% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.0% | 0.5% | 0.8% | 0.0% | **0.6%** | 0.0% | 0.0% | **0.7%** |
| **Buses** | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **8** |
| **% Buses** | 0.0% | 1.0% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.7% | 1.5% | 0.0% | **0.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 5 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TRI-STATE TRAFFIC DATA

TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Eggert Road & Alberta Drive |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Eggert Road & Alberta Drive |
| **Latitude and Longitude** | 42.97815,-78.81758 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 15:30:00 | 2023-11-16 16:30:00 | 0.956 |


## Turning Movement Data


| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 8 | 4 | 7 | 0 | **19** | 0 | 0 | 4 | 88 | 1 | 0 | **93** | 0 | 0 | 2 | 2 | 1 | 0 | **5** | 0 | 1 | 1 | 74 | 11 | 0 | **86** | 0 | 1 | **203** |
| 3:15:00 PM | 15 | 7 | 8 | 0 | **30** | 0 | 0 | 4 | 89 | 3 | 0 | **96** | 1 | 1 | 2 | 2 | 0 | 0 | **4** | 0 | 1 | 1 | 95 | 12 | 0 | **108** | 1 | 0 | **238** |
| 3:30:00 PM | 15 | 13 | 6 | 0 | **34** | 0 | 0 | 7 | 113 | 3 | 0 | **123** | 0 | 2 | 5 | 0 | 0 | 0 | **5** | 1 | 0 | 2 | 94 | 5 | 0 | **101** | 0 | 0 | **263** |
| 3:45:00 PM | 17 | 6 | 12 | 0 | **35** | 0 | 0 | 8 | 122 | 2 | 0 | **132** | 0 | 1 | 4 | 5 | 1 | 0 | **10** | 0 | 0 | 4 | 90 | 14 | 0 | **108** | 1 | 0 | **285** |
| **Hourly Total** | 55 | 30 | 33 | 0 | **118** | 0 | 0 | 23 | 412 | 9 | 0 | **444** | 1 | 4 | 13 | 9 | 2 | 0 | **24** | 1 | 2 | 8 | 353 | 42 | 0 | **403** | 2 | 1 | **989** |
| 4:00:00 PM | 16 | 9 | 7 | 0 | **32** | 0 | 0 | 7 | 120 | 3 | 0 | **130** | 1 | 0 | 2 | 9 | 2 | 0 | **13** | 0 | 0 | 1 | 90 | 10 | 0 | **101** | 0 | 0 | **276** |
| 4:15:00 PM | 14 | 10 | 4 | 0 | **28** | 0 | 0 | 3 | 116 | 4 | 0 | **123** | 0 | 0 | 2 | 6 | 0 | 0 | **8** | 0 | 0 | 0 | 96 | 11 | 0 | **107** | 0 | 0 | **266** |
| 4:30:00 PM | 8 | 9 | 14 | 0 | **31** | 1 | 0 | 5 | 108 | 0 | 0 | **113** | 0 | 0 | 3 | 6 | 0 | 0 | **9** | 0 | 0 | 2 | 82 | 8 | 0 | **92** | 0 | 1 | **245** |
| 4:45:00 PM | 13 | 8 | 4 | 0 | **25** | 0 | 0 | 6 | 114 | 2 | 0 | **122** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 1 | 0 | 1 | 83 | 16 | 0 | **100** | 0 | 0 | **250** |
| **Hourly Total** | 51 | 36 | 29 | 0 | **116** | 1 | 0 | 21 | 458 | 9 | 0 | **488** | 1 | 0 | 7 | 24 | 2 | 0 | **33** | 1 | 0 | 4 | 351 | 45 | 0 | **400** | 0 | 1 | **1037** |
| 5:00:00 PM | 9 | 5 | 11 | 0 | **25** | 0 | 0 | 4 | 91 | 0 | 0 | **95** | 0 | 0 | 1 | 9 | 0 | 0 | **10** | 0 | 0 | 0 | 101 | 9 | 0 | **110** | 0 | 1 | **240** |
| 5:15:00 PM | 15 | 7 | 13 | 0 | **35** | 0 | 0 | 3 | 102 | 0 | 0 | **105** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 1 | 0 | 1 | 78 | 4 | 0 | **83** | 0 | 0 | **230** |
| 5:30:00 PM | 10 | 11 | 5 | 0 | **26** | 0 | 0 | 6 | 109 | 3 | 0 | **118** | 0 | 0 | 3 | 2 | 3 | 0 | **8** | 1 | 0 | 1 | 82 | 8 | 0 | **91** | 0 | 0 | **243** |
| 5:45:00 PM | 14 | 10 | 3 | 0 | **27** | 0 | 0 | 8 | 82 | 2 | 0 | **92** | 0 | 0 | 1 | 6 | 2 | 0 | **9** | 0 | 0 | 1 | 76 | 15 | 0 | **92** | 0 | 0 | **220** |
| **Hourly Total** | 48 | 33 | 32 | 0 | **113** | 0 | 0 | 21 | 384 | 5 | 0 | **410** | 0 | 0 | 5 | 24 | 5 | 0 | **34** | 2 | 0 | 3 | 337 | 36 | 0 | **376** | 0 | 1 | **933** |
| **Grand Total** | 154 | 99 | 94 | 0 | **347** | 1 | 0 | 65 | 1254 | 23 | 0 | **1342** | 2 | 4 | 25 | 57 | 9 | 0 | **91** | 4 | 2 | 15 | 1041 | 123 | 0 | **1179** | 2 | 3 | **2959** |
| **% Approach** | 44.4% | 28.5% | 27.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.8% | 93.4% | 1.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 27.5% | 62.6% | 9.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.3% | 88.3% | 10.4% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 5.2% | 3.3% | 3.2% | 0.0% | **11.7%** | 0.0% | 0.0% | 2.2% | 42.4% | 0.8% | 0.0% | **45.4%** | 0.0% | 0.0% | 0.8% | 1.9% | 0.3% | 0.0% | **3.1%** | 0.0% | 0.0% | 0.5% | 35.2% | 4.2% | 0.0% | **39.8%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 82 | 96 | 94 | 0 | **272** | 0 | 0 | 55 | 1235 | 23 | 0 | **1313** | 0 | 0 | 14 | 54 | 9 | 0 | **77** | 0 | 0 | 12 | 1025 | 121 | 0 | **1158** | 0 | 0 | **2820** |
| **% Lights** | 53.2% | 97.0% | 100.0% | 0.0% | **78.4%** | 0.0% | 0.0% | 84.6% | 98.5% | 100.0% | 0.0% | **97.8%** | 0.0% | 0.0% | 56.0% | 94.7% | 100.0% | 0.0% | **84.6%** | 0.0% | 0.0% | 80.0% | 98.5% | 98.4% | 0.0% | **98.2%** | 0.0% | 0.0% | **95.3%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 10 | 0 | 0 | **11** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 8 | 2 | 0 | **10** | 0 | 0 | **21** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.5% | 0.8% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.8% | 1.6% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.7%** |
| **Buses** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 3 | 0 | 0 | 0 | **3** | 0 | 0 | 0 | 6 | 0 | 0 | **6** | 0 | 0 | **19** |
| **% Buses** | 0.0% | 2.0% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 12.0% | 0.0% | 0.0% | 0.0% | **3.3%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.6%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 4 | 0 | 0 | 0 | 0 | **0** | 4 | 1 | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**


## Turning Movement Peak Hour Data (PM)

**3:30:00 PM**

| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:30:00 PM | 15 | 13 | 6 | 0 | **34** | 0 | 0 | 7 | 113 | 3 | 0 | **123** | 0 | 2 | 5 | 0 | 0 | 0 | **5** | 1 | 0 | 2 | 94 | 5 | 0 | **101** | 0 | 0 | **263** |
| 3:45:00 PM | 17 | 6 | 12 | 0 | **35** | 0 | 0 | 8 | 122 | 2 | 0 | **132** | 0 | 1 | 4 | 5 | 1 | 0 | **10** | 0 | 0 | 4 | 90 | 14 | 0 | **108** | 1 | 0 | **285** |
| 4:00:00 PM | 16 | 9 | 7 | 0 | **32** | 0 | 0 | 7 | 120 | 3 | 0 | **130** | 1 | 0 | 2 | 9 | 2 | 0 | **13** | 0 | 0 | 1 | 90 | 10 | 0 | **101** | 0 | 0 | **276** |
| 4:15:00 PM | 14 | 10 | 4 | 0 | **28** | 0 | 0 | 3 | 116 | 4 | 0 | **123** | 0 | 0 | 2 | 6 | 0 | 0 | **8** | 0 | 0 | 0 | 96 | 11 | 0 | **107** | 0 | 0 | **266** |
| **Grand Total** | 62 | 38 | 29 | 0 | **129** | 0 | 0 | 25 | 471 | 12 | 0 | **508** | 1 | 3 | 13 | 20 | 3 | 0 | **36** | 1 | 0 | 7 | 370 | 40 | 0 | **417** | 1 | 0 | **1090** |
| **% Approach** | 48.1% | 29.5% | 22.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.9% | 92.7% | 2.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 36.1% | 55.6% | 8.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.7% | 88.7% | 9.6% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 5.7% | 3.5% | 2.7% | 0.0% | **11.8%** | 0.0% | 0.0% | 2.3% | 43.2% | 1.1% | 0.0% | **46.6%** | 0.0% | 0.0% | 1.2% | 1.8% | 0.3% | 0.0% | **3.3%** | 0.0% | 0.0% | 0.6% | 33.9% | 3.7% | 0.0% | **38.3%** | 0.0% | 0.0% | |
| **PHF** | 0.912 | 0.731 | 0.604 | 0.000 | **0.921** | 0.000 | 0.000 | 0.781 | 0.965 | 0.750 | 0.000 | **0.962** | 0.000 | 0.000 | 0.650 | 0.556 | 0.375 | 0.000 | **0.692** | 0.000 | 0.000 | 0.438 | 0.964 | 0.714 | 0.000 | **0.965** | 0.000 | 0.000 | **0.956** |
| **Lights** | 33 | 36 | 29 | 0 | **98** | 0 | 0 | 21 | 460 | 12 | 0 | **493** | 0 | 0 | 7 | 20 | 3 | 0 | **30** | 0 | 0 | 5 | 365 | 40 | 0 | **410** | 0 | 0 | **1031** |
| **% Lights** | 53.2% | 94.7% | 100.0% | 0.0% | **76.0%** | 0.0% | 0.0% | 84.0% | 97.7% | 100.0% | 0.0% | **97.0%** | 0.0% | 0.0% | 53.8% | 100.0% | 100.0% | 0.0% | **83.3%** | 0.0% | 0.0% | 71.4% | 98.6% | 100.0% | 0.0% | **98.3%** | 0.0% | 0.0% | **94.6%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **11** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 1.5% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 1.1% | 0.0% | 0.0% | **1.0%** | 0.0% | 0.0% | **1.0%** |
| **Buses** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **8** |
| **% Buses** | 0.0% | 2.6% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.8% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 15.4% | 0.0% | 0.0% | 0.0% | **5.6%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.7%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:00:00 PM | 8 | 4 | 7 | 0 | **19** | 0 | 0 | 4 | 88 | 1 | 0 | **93** | 0 | 0 | 2 | 2 | 1 | 0 | **5** | 0 | 1 | 1 | 74 | 11 | 0 | **86** | 0 | 1 | **203** |
| 3:15:00 PM | 15 | 7 | 8 | 0 | **30** | 0 | 0 | 4 | 89 | 3 | 0 | **96** | 1 | 1 | 2 | 2 | 0 | 0 | **4** | 0 | 1 | 1 | 95 | 12 | 0 | **108** | 1 | 0 | **238** |
| 3:30:00 PM | 15 | 13 | 6 | 0 | **34** | 0 | 0 | 7 | 113 | 3 | 0 | **123** | 0 | 2 | 5 | 0 | 0 | 0 | **5** | 1 | 0 | 2 | 94 | 5 | 0 | **101** | 0 | 0 | **263** |
| 3:45:00 PM | 17 | 6 | 12 | 0 | **35** | 0 | 0 | 8 | 122 | 2 | 0 | **132** | 0 | 1 | 4 | 5 | 1 | 0 | **10** | 0 | 0 | 4 | 90 | 14 | 0 | **108** | 1 | 0 | **285** |
| **Hourly Total** | 55 | 30 | 33 | 0 | **118** | 0 | 0 | 23 | 412 | 9 | 0 | **444** | 1 | 4 | 13 | 9 | 2 | 0 | **24** | 1 | 2 | 8 | 353 | 42 | 0 | **403** | 2 | 1 | **989** |
| 4:00:00 PM | 16 | 9 | 7 | 0 | **32** | 0 | 0 | 7 | 120 | 3 | 0 | **130** | 1 | 0 | 2 | 9 | 2 | 0 | **13** | 0 | 0 | 1 | 90 | 10 | 0 | **101** | 0 | 0 | **276** |
| 4:15:00 PM | 14 | 10 | 4 | 0 | **28** | 0 | 0 | 3 | 116 | 4 | 0 | **123** | 0 | 0 | 2 | 6 | 0 | 0 | **8** | 0 | 0 | 0 | 96 | 11 | 0 | **107** | 0 | 0 | **266** |
| 4:30:00 PM | 8 | 9 | 14 | 0 | **31** | 1 | 0 | 5 | 108 | 0 | 0 | **113** | 0 | 0 | 3 | 6 | 0 | 0 | **9** | 0 | 0 | 2 | 82 | 8 | 0 | **92** | 0 | 1 | **245** |
| 4:45:00 PM | 13 | 8 | 4 | 0 | **25** | 0 | 0 | 6 | 114 | 2 | 0 | **122** | 0 | 0 | 0 | 3 | 0 | 0 | **3** | 1 | 0 | 1 | 83 | 16 | 0 | **100** | 0 | 0 | **250** |
| **Hourly Total** | 51 | 36 | 29 | 0 | **116** | 1 | 0 | 21 | 458 | 9 | 0 | **488** | 1 | 0 | 7 | 24 | 2 | 0 | **33** | 1 | 0 | 4 | 351 | 45 | 0 | **400** | 0 | 1 | **1037** |
| 5:00:00 PM | 9 | 5 | 11 | 0 | **25** | 0 | 0 | 4 | 91 | 0 | 0 | **95** | 0 | 0 | 1 | 9 | 0 | 0 | **10** | 0 | 0 | 0 | 101 | 9 | 0 | **110** | 0 | 1 | **240** |
| 5:15:00 PM | 15 | 7 | 13 | 0 | **35** | 0 | 0 | 3 | 102 | 0 | 0 | **105** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 1 | 0 | 1 | 78 | 4 | 0 | **83** | 0 | 0 | **230** |
| 5:30:00 PM | 10 | 11 | 5 | 0 | **26** | 0 | 0 | 6 | 109 | 3 | 0 | **118** | 0 | 0 | 3 | 2 | 3 | 0 | **8** | 1 | 0 | 1 | 82 | 8 | 0 | **91** | 0 | 0 | **243** |
| 5:45:00 PM | 14 | 10 | 3 | 0 | **27** | 0 | 0 | 8 | 82 | 2 | 0 | **92** | 0 | 0 | 1 | 6 | 2 | 0 | **9** | 0 | 0 | 1 | 76 | 15 | 0 | **92** | 0 | 0 | **220** |
| **Hourly Total** | 48 | 33 | 32 | 0 | **113** | 0 | 0 | 21 | 384 | 5 | 0 | **410** | 0 | 0 | 5 | 24 | 5 | 0 | **34** | 2 | 0 | 3 | 337 | 36 | 0 | **376** | 0 | 1 | **933** |
| **Grand Total** | 154 | 99 | 94 | 0 | **347** | 1 | 0 | 65 | 1254 | 23 | 0 | **1342** | 2 | 4 | 25 | 57 | 9 | 0 | **91** | 4 | 2 | 15 | 1041 | 123 | 0 | **1179** | 2 | 3 | **2959** |
| **% Approach** | 44.4% | 28.5% | 27.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.8% | 93.4% | 1.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 27.5% | 62.6% | 9.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.3% | 88.3% | 10.4% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 5.2% | 3.3% | 3.2% | 0.0% | **11.7%** | 0.0% | 0.0% | 2.2% | 42.4% | 0.8% | 0.0% | **45.4%** | 0.0% | 0.0% | 0.8% | 1.9% | 0.3% | 0.0% | **3.1%** | 0.0% | 0.0% | 0.5% | 35.2% | 4.2% | 0.0% | **39.8%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 82 | 96 | 94 | 0 | **272** | 0 | 0 | 55 | 1235 | 23 | 0 | **1313** | 0 | 0 | 14 | 54 | 9 | 0 | **77** | 0 | 0 | 12 | 1025 | 121 | 0 | **1158** | 0 | 0 | **2820** |
| **% Lights** | 53.2% | 97.0% | 100.0% | 0.0% | **78.4%** | 0.0% | 0.0% | 84.6% | 98.5% | 100.0% | 0.0% | **97.8%** | 0.0% | 0.0% | 56.0% | 94.7% | 100.0% | 0.0% | **84.6%** | 0.0% | 0.0% | 80.0% | 98.5% | 98.4% | 0.0% | **98.2%** | 0.0% | 0.0% | **95.3%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 10 | 0 | 0 | **11** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 8 | 2 | 0 | **10** | 0 | 0 | **21** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.5% | 0.8% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.8% | 1.6% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.7%** |
| **Buses** | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | 3 | 0 | 0 | 0 | **3** | 0 | 0 | 0 | 6 | 0 | 0 | **6** | 0 | 0 | **19** |
| **% Buses** | 0.0% | 2.0% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 12.0% | 0.0% | 0.0% | 0.0% | **3.3%** | 0.0% | 0.0% | 0.0% | 0.6% | 0.0% | 0.0% | **0.5%** | 0.0% | 0.0% | **0.6%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 4 | 0 | 0 | 0 | 0 | **0** | 4 | 1 | 0 | 0 | 0 | 0 | **0** | 2 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**3:30:00 PM**

| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 3:30:00 PM | 15 | 13 | 6 | 0 | **34** | 0 | 0 | 7 | 113 | 3 | 0 | **123** | 0 | 2 | 5 | 0 | 0 | 0 | **5** | 1 | 0 | 2 | 94 | 5 | 0 | **101** | 0 | 0 | **263** |
| 3:45:00 PM | 17 | 6 | 12 | 0 | **35** | 0 | 0 | 8 | 122 | 2 | 0 | **132** | 0 | 1 | 4 | 5 | 1 | 0 | **10** | 0 | 0 | 4 | 90 | 14 | 0 | **108** | 1 | 0 | **285** |
| 4:00:00 PM | 16 | 9 | 7 | 0 | **32** | 0 | 0 | 7 | 120 | 3 | 0 | **130** | 1 | 0 | 2 | 9 | 2 | 0 | **13** | 0 | 0 | 1 | 90 | 10 | 0 | **101** | 0 | 0 | **276** |
| 4:15:00 PM | 14 | 10 | 4 | 0 | **28** | 0 | 0 | 3 | 116 | 4 | 0 | **123** | 0 | 0 | 2 | 6 | 0 | 0 | **8** | 0 | 0 | 0 | 96 | 11 | 0 | **107** | 0 | 0 | **266** |
| **Grand Total** | 62 | 38 | 29 | 0 | **129** | 0 | 0 | 25 | 471 | 12 | 0 | **508** | 1 | 3 | 13 | 20 | 3 | 0 | **36** | 1 | 0 | 7 | 370 | 40 | 0 | **417** | 1 | 0 | **1090** |
| **% Approach** | 48.1% | 29.5% | 22.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.9% | 92.7% | 2.4% | 0.0% | **0.0%** | 0.0% | 0.0% | 36.1% | 55.6% | 8.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.7% | 88.7% | 9.6% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 5.7% | 3.5% | 2.7% | 0.0% | **11.8%** | 0.0% | 0.0% | 2.3% | 43.2% | 1.1% | 0.0% | **46.6%** | 0.0% | 0.0% | 1.2% | 1.8% | 0.3% | 0.0% | **3.3%** | 0.0% | 0.0% | 0.6% | 33.9% | 3.7% | 0.0% | **38.3%** | 0.0% | 0.0% | |
| **PHF** | 0.912 | 0.731 | 0.604 | 0.000 | **0.921** | 0.000 | 0.000 | 0.781 | 0.965 | 0.750 | 0.000 | **0.962** | 0.000 | 0.000 | 0.650 | 0.556 | 0.375 | 0.000 | **0.692** | 0.000 | 0.000 | 0.438 | 0.964 | 0.714 | 0.000 | **0.965** | 0.000 | 0.000 | **0.956** |
| **Lights** | 33 | 36 | 29 | 0 | **98** | 0 | 0 | 21 | 460 | 12 | 0 | **493** | 0 | 0 | 7 | 20 | 3 | 0 | **30** | 0 | 0 | 5 | 365 | 40 | 0 | **410** | 0 | 0 | **1031** |
| **% Lights** | 53.2% | 94.7% | 100.0% | 0.0% | **76.0%** | 0.0% | 0.0% | 84.0% | 97.7% | 100.0% | 0.0% | **97.0%** | 0.0% | 0.0% | 53.8% | 100.0% | 100.0% | 0.0% | **83.3%** | 0.0% | 0.0% | 71.4% | 98.6% | 100.0% | 0.0% | **98.3%** | 0.0% | 0.0% | **94.6%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 7 | 0 | 0 | **7** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **11** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 1.5% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 1.1% | 0.0% | 0.0% | **1.0%** | 0.0% | 0.0% | **1.0%** |
| **Buses** | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | **8** |
| **% Buses** | 0.0% | 2.6% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 0.0% | 0.8% | 0.0% | 0.0% | **0.8%** | 0.0% | 0.0% | 15.4% | 0.0% | 0.0% | 0.0% | **5.6%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | **0.7%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 3 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TSTData.com

## Summary

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Eggert Road & Alberta Drive |
| **Legs and Movements** | All Processed Legs & Mover |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Eggert Road & Alberta Drive |
| **Latitude and Longitude** | 42.97815,-78.81758 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 12:15:00 | 2023-11-18 13:15:00 | 0.947 |


## Turning Movement Data


| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Direction** | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | **App Total** | Peds CW | Peds CCW | **Total** |
| 12:00:00 | 8 | 5 | 10 | 0 | **23** | 0 | 0 | 4 | 90 | 2 | 0 | **96** | 1 | 0 | 2 | 4 | 0 | 0 | **6** | 0 | 0 | 1 | 84 | 7 | 0 | **92** | 0 | 0 | **217** |
| 12:15:00 | 15 | 8 | 15 | 0 | **38** | 0 | 0 | 4 | 82 | 2 | 0 | **88** | 0 | 2 | 1 | 2 | 0 | 0 | **3** | 1 | 0 | 1 | 88 | 9 | 0 | **98** | 0 | 0 | **227** |
| 12:30:00 | 15 | 8 | 7 | 0 | **30** | 0 | 0 | 7 | 77 | 1 | 0 | **85** | 0 | 0 | 4 | 4 | 2 | 0 | **10** | 0 | 1 | 1 | 84 | 22 | 0 | **107** | 1 | 0 | **232** |
| 12:45:00 | 17 | 7 | 2 | 0 | **26** | 0 | 0 | 8 | 71 | 0 | 0 | **79** | 0 | 0 | 4 | 7 | 3 | 0 | **14** | 0 | 0 | 3 | 70 | 9 | 0 | **82** | 0 | 1 | **201** |
| **Hourly Total** | 55 | 28 | 34 | 0 | **117** | 0 | 0 | 23 | 320 | 5 | 0 | **348** | 1 | 2 | 11 | 17 | 5 | 0 | **33** | 1 | 1 | 6 | 326 | 47 | 0 | **379** | 1 | 1 | **877** |
| 13:00:00 | 16 | 10 | 11 | 0 | **37** | 1 | 0 | 7 | 66 | 4 | 0 | **77** | 2 | 0 | 2 | 7 | 1 | 0 | **10** | 0 | 0 | 1 | 82 | 12 | 0 | **95** | 0 | 0 | **219** |
| 13:15:00 | 14 | 6 | 8 | 0 | **28** | 0 | 0 | 3 | 74 | 2 | 0 | **79** | 0 | 0 | 2 | 10 | 0 | 0 | **12** | 0 | 0 | 0 | 80 | 13 | 0 | **93** | 0 | 0 | **212** |
| 13:30:00 | 8 | 11 | 13 | 0 | **32** | 3 | 0 | 4 | 79 | 2 | 0 | **85** | 0 | 0 | 3 | 2 | 3 | 0 | **8** | 0 | 0 | 2 | 80 | 12 | 0 | **94** | 1 | 0 | **219** |
| 13:45:00 | 13 | 9 | 11 | 0 | **33** | 0 | 0 | 6 | 60 | 2 | 0 | **68** | 1 | 0 | 0 | 8 | 1 | 0 | **9** | 0 | 0 | 1 | 74 | 10 | 0 | **85** | 1 | 0 | **195** |
| **Hourly Total** | 51 | 36 | 43 | 0 | **130** | 4 | 0 | 20 | 279 | 10 | 0 | **309** | 3 | 0 | 7 | 27 | 5 | 0 | **39** | 0 | 0 | 4 | 316 | 47 | 0 | **367** | 2 | 0 | **845** |
| 14:00:00 | 9 | 12 | 6 | 0 | **27** | 0 | 0 | 4 | 67 | 1 | 0 | **72** | 0 | 0 | 1 | 5 | 0 | 0 | **6** | 3 | 0 | 0 | 91 | 5 | 0 | **96** | 0 | 0 | **201** |
| 14:15:00 | 15 | 9 | 17 | 0 | **41** | 0 | 1 | 3 | 83 | 3 | 0 | **89** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 3 | 0 | 1 | 75 | 15 | 0 | **91** | 0 | 1 | **226** |
| 14:30:00 | 10 | 5 | 7 | 0 | **22** | 0 | 0 | 6 | 58 | 1 | 0 | **65** | 0 | 0 | 3 | 4 | 3 | 0 | **10** | 0 | 1 | 1 | 62 | 12 | 0 | **75** | 0 | 1 | **172** |
| 14:45:00 | 14 | 11 | 5 | 0 | **30** | 0 | 0 | 8 | 86 | 1 | 0 | **95** | 0 | 0 | 1 | 6 | 1 | 0 | **8** | 0 | 0 | 1 | 87 | 8 | 0 | **96** | 0 | 0 | **229** |
| **Hourly Total** | 48 | 37 | 35 | 0 | **120** | 0 | 1 | 21 | 294 | 6 | 0 | **321** | 0 | 0 | 5 | 20 | 4 | 0 | **29** | 6 | 1 | 3 | 315 | 40 | 0 | **358** | 0 | 2 | **828** |
| **Grand Total** | 154 | 101 | 112 | 0 | **367** | 4 | 1 | 64 | 893 | 21 | 0 | **978** | 4 | 2 | 23 | 64 | 14 | 0 | **101** | 7 | 2 | 13 | 957 | 134 | 0 | **1104** | 3 | 3 | **2550** |
| **% Approach** | 42.0% | 27.5% | 30.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.5% | 91.3% | 2.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 22.8% | 63.4% | 13.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.2% | 86.7% | 12.1% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 6.0% | 4.0% | 4.4% | 0.0% | **14.4%** | 0.0% | 0.0% | 2.5% | 35.0% | 0.8% | 0.0% | **38.4%** | 0.0% | 0.0% | 0.9% | 2.5% | 0.5% | 0.0% | **4.0%** | 0.0% | 0.0% | 0.5% | 37.5% | 5.3% | 0.0% | **43.3%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 82 | 100 | 112 | 0 | **294** | 0 | 0 | 55 | 886 | 21 | 0 | **962** | 0 | 0 | 14 | 63 | 14 | 0 | **91** | 0 | 0 | 11 | 948 | 133 | 0 | **1092** | 0 | 0 | **2439** |
| **% Lights** | 53.2% | 99.0% | 100.0% | 0.0% | **80.1%** | 0.0% | 0.0% | 85.9% | 99.2% | 100.0% | 0.0% | **98.4%** | 0.0% | 0.0% | 60.9% | 98.4% | 100.0% | 0.0% | **90.1%** | 0.0% | 0.0% | 84.6% | 99.1% | 99.3% | 0.0% | **98.9%** | 0.0% | 0.0% | **95.6%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | **12** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.8% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.5%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **2** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 4.3% | 0.0% | 0.0% | 0.0% | **1.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 4 | 1 | 0 | 0 | 0 | 0 | **0** | 4 | 2 | 0 | 0 | 0 | 0 | **0** | 6 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 85.7% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 14.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot




TSTData.com


**Summary**


## Turning Movement Peak Hour Data (PM)

**12:15:00**

| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:15:00 | 15 | 8 | 15 | 0 | **38** | 0 | 0 | 4 | 82 | 2 | 0 | **88** | 0 | 2 | 1 | 2 | 0 | 0 | **3** | 1 | 0 | 1 | 88 | 9 | 0 | **98** | 0 | 0 | **227** |
| 12:30:00 | 15 | 8 | 7 | 0 | **30** | 0 | 0 | 7 | 77 | 1 | 0 | **85** | 0 | 0 | 4 | 4 | 2 | 0 | **10** | 0 | 1 | 1 | 84 | 22 | 0 | **107** | 1 | 0 | **232** |
| 12:45:00 | 17 | 7 | 2 | 0 | **26** | 0 | 0 | 8 | 71 | 0 | 0 | **79** | 0 | 0 | 4 | 7 | 3 | 0 | **14** | 0 | 0 | 3 | 70 | 9 | 0 | **82** | 0 | 1 | **201** |
| 13:00:00 | 16 | 10 | 11 | 0 | **37** | 1 | 0 | 7 | 66 | 4 | 0 | **77** | 2 | 0 | 2 | 7 | 1 | 0 | **10** | 0 | 0 | 1 | 82 | 12 | 0 | **95** | 0 | 0 | **219** |
| **Grand Total** | 63 | 33 | 35 | 0 | **131** | 1 | 0 | 26 | 296 | 7 | 0 | **329** | 2 | 2 | 11 | 20 | 6 | 0 | **37** | 1 | 1 | 6 | 324 | 52 | 0 | **382** | 1 | 1 | **879** |
| **% Approach** | 48.1% | 25.2% | 26.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 7.9% | 90.0% | 2.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 29.7% | 54.1% | 16.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.6% | 84.8% | 13.6% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 7.2% | 3.8% | 4.0% | 0.0% | **14.9%** | 0.0% | 0.0% | 3.0% | 33.7% | 0.8% | 0.0% | **37.4%** | 0.0% | 0.0% | 1.3% | 2.3% | 0.7% | 0.0% | **4.2%** | 0.0% | 0.0% | 0.7% | 36.9% | 5.9% | 0.0% | **43.5%** | 0.0% | 0.0% | |
| **PHF** | 0.926 | 0.825 | 0.583 | 0.000 | **0.862** | 0.000 | 0.000 | 0.813 | 0.902 | 0.438 | 0.000 | **0.935** | 0.000 | 0.000 | 0.688 | 0.714 | 0.500 | 0.000 | **0.661** | 0.000 | 0.000 | 0.500 | 0.920 | 0.591 | 0.000 | **0.893** | 0.000 | 0.000 | **0.947** |
| **Lights** | 35 | 32 | 35 | 0 | **102** | 0 | 0 | 22 | 295 | 7 | 0 | **324** | 0 | 0 | 7 | 20 | 6 | 0 | **33** | 0 | 0 | 5 | 319 | 51 | 0 | **375** | 0 | 0 | **834** |
| **% Lights** | 55.6% | 97.0% | 100.0% | 0.0% | **77.9%** | 0.0% | 0.0% | 84.6% | 99.7% | 100.0% | 0.0% | **98.5%** | 0.0% | 0.0% | 63.6% | 100.0% | 100.0% | 0.0% | **89.2%** | 0.0% | 0.0% | 83.3% | 98.5% | 98.1% | 0.0% | **98.2%** | 0.0% | 0.0% | **94.9%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **5** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 1.2% | 0.0% | 0.0% | **1.0%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |











## Turning Movement Data

| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:00:00 | 8 | 5 | 10 | 0 | **23** | 0 | 0 | 4 | 90 | 2 | 0 | **96** | 1 | 0 | 2 | 4 | 0 | 0 | **6** | 0 | 0 | 1 | 84 | 7 | 0 | **92** | 0 | 0 | **217** |
| 12:15:00 | 15 | 8 | 15 | 0 | **38** | 0 | 0 | 4 | 82 | 2 | 0 | **88** | 0 | 2 | 1 | 2 | 0 | 0 | **3** | 1 | 0 | 1 | 88 | 9 | 0 | **98** | 0 | 0 | **227** |
| 12:30:00 | 15 | 8 | 7 | 0 | **30** | 0 | 0 | 7 | 77 | 1 | 0 | **85** | 0 | 0 | 4 | 4 | 2 | 0 | **10** | 0 | 1 | 1 | 84 | 22 | 0 | **107** | 1 | 0 | **232** |
| 12:45:00 | 17 | 7 | 2 | 0 | **26** | 0 | 0 | 8 | 71 | 0 | 0 | **79** | 0 | 0 | 4 | 7 | 3 | 0 | **14** | 0 | 0 | 3 | 70 | 9 | 0 | **82** | 0 | 1 | **201** |
| **Hourly Total** | 55 | 28 | 34 | 0 | **117** | 0 | 0 | 23 | 320 | 5 | 0 | **348** | 1 | 2 | 11 | 17 | 5 | 0 | **33** | 1 | 1 | 6 | 326 | 47 | 0 | **379** | 1 | 1 | **877** |
| 13:00:00 | 16 | 10 | 11 | 0 | **37** | 1 | 0 | 7 | 66 | 4 | 0 | **77** | 2 | 0 | 2 | 7 | 1 | 0 | **10** | 0 | 0 | 1 | 82 | 12 | 0 | **95** | 0 | 0 | **219** |
| 13:15:00 | 14 | 6 | 8 | 0 | **28** | 0 | 0 | 3 | 74 | 2 | 0 | **79** | 0 | 0 | 2 | 10 | 0 | 0 | **12** | 0 | 0 | 0 | 80 | 13 | 0 | **93** | 0 | 0 | **212** |
| 13:30:00 | 8 | 11 | 13 | 0 | **32** | 3 | 0 | 4 | 79 | 2 | 0 | **85** | 0 | 0 | 3 | 2 | 3 | 0 | **8** | 0 | 0 | 2 | 80 | 12 | 0 | **94** | 1 | 0 | **219** |
| 13:45:00 | 13 | 9 | 11 | 0 | **33** | 0 | 0 | 6 | 60 | 2 | 0 | **68** | 1 | 0 | 0 | 8 | 1 | 0 | **9** | 0 | 0 | 1 | 74 | 10 | 0 | **85** | 1 | 0 | **195** |
| **Hourly Total** | 51 | 36 | 43 | 0 | **130** | 4 | 0 | 20 | 279 | 10 | 0 | **309** | 3 | 0 | 7 | 27 | 5 | 0 | **39** | 0 | 0 | 4 | 316 | 47 | 0 | **367** | 2 | 0 | **845** |
| 14:00:00 | 9 | 12 | 6 | 0 | **27** | 0 | 0 | 4 | 67 | 1 | 0 | **72** | 0 | 0 | 1 | 5 | 0 | 0 | **6** | 3 | 0 | 0 | 91 | 5 | 0 | **96** | 0 | 0 | **201** |
| 14:15:00 | 15 | 9 | 17 | 0 | **41** | 0 | 1 | 3 | 83 | 3 | 0 | **89** | 0 | 0 | 0 | 5 | 0 | 0 | **5** | 3 | 0 | 1 | 75 | 15 | 0 | **91** | 0 | 1 | **226** |
| 14:30:00 | 10 | 5 | 7 | 0 | **22** | 0 | 0 | 6 | 58 | 1 | 0 | **65** | 0 | 0 | 3 | 4 | 3 | 0 | **10** | 0 | 1 | 1 | 62 | 12 | 0 | **75** | 0 | 1 | **172** |
| 14:45:00 | 14 | 11 | 5 | 0 | **30** | 0 | 0 | 8 | 86 | 1 | 0 | **95** | 0 | 0 | 1 | 6 | 1 | 0 | **8** | 0 | 0 | 1 | 87 | 8 | 0 | **96** | 0 | 0 | **229** |
| **Hourly Total** | 48 | 37 | 35 | 0 | **120** | 0 | 1 | 21 | 294 | 6 | 0 | **321** | 0 | 0 | 5 | 20 | 4 | 0 | **29** | 6 | 1 | 3 | 315 | 40 | 0 | **358** | 0 | 2 | **828** |
| **Grand Total** | 154 | 101 | 112 | 0 | **367** | 4 | 1 | 64 | 893 | 21 | 0 | **978** | 4 | 2 | 23 | 64 | 14 | 0 | **101** | 7 | 2 | 13 | 957 | 134 | 0 | **1104** | 3 | 3 | **2550** |
| **% Approach** | 42.0% | 27.5% | 30.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.5% | 91.3% | 2.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 22.8% | 63.4% | 13.9% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.2% | 86.7% | 12.1% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 6.0% | 4.0% | 4.4% | 0.0% | **14.4%** | 0.0% | 0.0% | 2.5% | 35.0% | 0.8% | 0.0% | **38.4%** | 0.0% | 0.0% | 0.9% | 2.5% | 0.5% | 0.0% | **4.0%** | 0.0% | 0.0% | 0.5% | 37.5% | 5.3% | 0.0% | **43.3%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 82 | 100 | 112 | 0 | **294** | 0 | 0 | 55 | 886 | 21 | 0 | **962** | 0 | 0 | 14 | 63 | 14 | 0 | **91** | 0 | 0 | 11 | 948 | 133 | 0 | **1092** | 0 | 0 | **2439** |
| **% Lights** | 53.2% | 99.0% | 100.0% | 0.0% | **80.1%** | 0.0% | 0.0% | 85.9% | 99.2% | 100.0% | 0.0% | **98.4%** | 0.0% | 0.0% | 60.9% | 98.4% | 100.0% | 0.0% | **90.1%** | 0.0% | 0.0% | 84.6% | 99.1% | 99.3% | 0.0% | **98.9%** | 0.0% | 0.0% | **95.6%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 8 | 0 | 0 | **8** | 0 | 0 | **12** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.8% | 0.0% | 0.0% | **0.7%** | 0.0% | 0.0% | **0.5%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **2** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 4.3% | 0.0% | 0.0% | 0.0% | **1.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 4 | 1 | 0 | 0 | 0 | 0 | **0** | 4 | 2 | 0 | 0 | 0 | 0 | **0** | 6 | 2 | 0 | 0 | 0 | 0 | **0** | 3 | 3 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 85.7% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 14.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

## Turning Movement Data Plot








## Turning Movement Peak Hour Data (PM)

**12:15:00**

| Leg | Unnamed Road | | | | | | | Eggert Road | | | | | | | Alberta Drive | | | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | App Total | Peds CW | Peds CCW | Total |
| 12:15:00 | 15 | 8 | 15 | 0 | **38** | 0 | 0 | 4 | 82 | 2 | 0 | **88** | 0 | 2 | 1 | 2 | 0 | 0 | **3** | 1 | 0 | 1 | 88 | 9 | 0 | **98** | 0 | 0 | **227** |
| 12:30:00 | 15 | 8 | 7 | 0 | **30** | 0 | 0 | 7 | 77 | 1 | 0 | **85** | 0 | 0 | 4 | 4 | 2 | 0 | **10** | 0 | 1 | 1 | 84 | 22 | 0 | **107** | 1 | 0 | **232** |
| 12:45:00 | 17 | 7 | 2 | 0 | **26** | 0 | 0 | 8 | 71 | 0 | 0 | **79** | 0 | 0 | 4 | 7 | 3 | 0 | **14** | 0 | 0 | 3 | 70 | 9 | 0 | **82** | 0 | 1 | **201** |
| 13:00:00 | 16 | 10 | 11 | 0 | **37** | 1 | 0 | 7 | 66 | 4 | 0 | **77** | 2 | 0 | 2 | 7 | 1 | 0 | **10** | 0 | 0 | 1 | 82 | 12 | 0 | **95** | 0 | 0 | **219** |
| **Grand Total** | 63 | 33 | 35 | 0 | **131** | 1 | 0 | 26 | 296 | 7 | 0 | **329** | 2 | 2 | 11 | 20 | 6 | 0 | **37** | 1 | 1 | 6 | 324 | 52 | 0 | **382** | 1 | 1 | **879** |
| **% Approach** | 48.1% | 25.2% | 26.7% | 0.0% | **0.0%** | 0.0% | 0.0% | 7.9% | 90.0% | 2.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 29.7% | 54.1% | 16.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.6% | 84.8% | 13.6% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 7.2% | 3.8% | 4.0% | 0.0% | **14.9%** | 0.0% | 0.0% | 3.0% | 33.7% | 0.8% | 0.0% | **37.4%** | 0.0% | 0.0% | 1.3% | 2.3% | 0.7% | 0.0% | **4.2%** | 0.0% | 0.0% | 0.7% | 36.9% | 5.9% | 0.0% | **43.5%** | 0.0% | 0.0% | |
| **PHF** | 0.926 | 0.825 | 0.583 | 0.000 | **0.862** | 0.000 | 0.000 | 0.813 | 0.902 | 0.438 | 0.000 | **0.935** | 0.000 | 0.000 | 0.688 | 0.714 | 0.500 | 0.000 | **0.661** | 0.000 | 0.000 | 0.500 | 0.920 | 0.591 | 0.000 | **0.893** | 0.000 | 0.000 | **0.947** |
| **Lights** | 35 | 32 | 35 | 0 | **102** | 0 | 0 | 22 | 295 | 7 | 0 | **324** | 0 | 0 | 7 | 20 | 6 | 0 | **33** | 0 | 0 | 5 | 319 | 51 | 0 | **375** | 0 | 0 | **834** |
| **% Lights** | 55.6% | 97.0% | 100.0% | 0.0% | **77.9%** | 0.0% | 0.0% | 84.6% | 99.7% | 100.0% | 0.0% | **98.5%** | 0.0% | 0.0% | 63.6% | 100.0% | 100.0% | 0.0% | **89.2%** | 0.0% | 0.0% | 83.3% | 98.5% | 98.1% | 0.0% | **98.2%** | 0.0% | 0.0% | **94.9%** |
| **Trucks** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 1 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | **5** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 1.2% | 0.0% | 0.0% | **1.0%** | 0.0% | 0.0% | **0.6%** |
| **Buses** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 | 0 | 0 | 0 | **0** | 1 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TRI-STATE TRAFFIC DATA

TSTData.com

**Summary**

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Bailey Road & Emerson Drive |
| **Legs and Movements** | All Processed Legs & Movements |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-16, Thursday |
| **Location** | Bailey Road & Emerson Drive |
| **Latitude and Longitude** | 42.98602, -78.8143 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-16 16:45:00 | 2023-11-16 17:45:00 | 0.9621 |

## Turning Movement Data


| Leg | Bailey Road | | | | | | | | Emerson Drive | | | | | | | | Bailey Road | | | | | | | | Emerson Drive | | | | | | | | Amsterdam Ave | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | | Westbound | | | | | | | | Northbound | | | | | | | | Eastbound | | | | | | | | Southwestbound | | | | | | | | |
| Start Time | Hard Right | Right | Thru | Left | U-Turn | App. Total | Peds | Bicycles | Hard Right | Soft Right | Thru | Left | U-Turn | App. Total | Peds | Bicycles | Right | Thru | Soft Left | Left | U-Turn | App. Total | Peds | Bicycles | Right | Thru | Left | Hard Left | U-Turn | App. Total | Peds | Bicycles | Hard Right | Soft Right | Soft Left | Hard Left | U-Turn | App. Total | Peds | Bicycles | Total |
| 3:00:00 PM | 5 | 7 | 109 | 3 | 0 | **124** | 0 | 0 | 9 | 4 | 7 | 14 | 0 | **34** | 0 | 0 | 8 | 67 | 2 | 1 | 0 | **98** | 0 | 0 | 1 | 6 | 1 | 1 | 0 | **9** | 0 | 0 | 1 | 3 | 8 | 0 | 0 | **12** | 0 | 0 | **277** |
| 3:15:00 PM | 2 | 3 | 105 | 8 | 0 | **118** | 0 | 0 | 4 | 2 | 3 | 6 | 0 | **15** | 0 | 1 | 9 | 125 | 5 | 1 | 0 | **140** | 0 | 0 | 1 | 6 | 1 | 0 | 0 | **8** | 1 | 0 | 0 | 3 | 3 | 1 | 0 | **7** | 2 | 0 | **288** |
| 3:30:00 PM | 3 | 7 | 106 | 11 | 0 | **127** | 0 | 0 | 6 | 5 | 5 | 8 | 0 | **24** | 0 | 0 | 9 | 120 | 2 | 0 | 0 | **131** | 1 | 1 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 3 | 1 | 0 | 0 | **4** | 0 | 0 | **288** |
| 3:45:00 PM | 4 | 1 | 122 | 4 | 0 | **131** | 0 | 0 | 6 | 3 | 4 | 11 | 0 | **26** | 0 | 0 | 7 | 105 | 2 | 0 | 0 | **114** | 0 | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 1 | 1 | 4 | 4 | 0 | 0 | **9** | 2 | 1 | **302** |
| **Hourly Total** | 14 | 18 | 442 | 26 | 0 | **500** | 0 | 0 | 25 | 14 | 19 | 39 | 0 | **99** | 0 | 1 | 33 | 417 | 11 | 2 | 0 | **483** | 1 | 1 | 2 | 16 | 2 | 1 | 0 | **21** | 1 | 1 | 2 | 10 | 16 | 1 | 0 | **30** | 4 | 1 | **1155** |
| 4:00:00 PM | 5 | 11 | 121 | 4 | 0 | **141** | 0 | 0 | 7 | 6 | 3 | 6 | 0 | **22** | 0 | 0 | 11 | 110 | 5 | 0 | 0 | **126** | 0 | 0 | 0 | 2 | 1 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 0 | 4 | 0 | **6** | 0 | 0 | **301** |
| 4:15:00 PM | 2 | 5 | 100 | 6 | 0 | **113** | 0 | 0 | 13 | 2 | 7 | 5 | 0 | **27** | 0 | 0 | 13 | 109 | 1 | 0 | 0 | **123** | 0 | 0 | 0 | 1 | 2 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 0 | 1 | 0 | **2** | 0 | 0 | **268** |
| 4:30:00 PM | 4 | 7 | 121 | 5 | 0 | **137** | 1 | 0 | 4 | 10 | 3 | 7 | 0 | **24** | 0 | 0 | 15 | 96 | 2 | 0 | 0 | **113** | 0 | 1 | 2 | 5 | 3 | 0 | 0 | **10** | 0 | 1 | 0 | 2 | 0 | 1 | 0 | **5** | 0 | 0 | **289** |
| 4:45:00 PM | 4 | 7 | 118 | 6 | 0 | **135** | 0 | 0 | 12 | 3 | 7 | 11 | 0 | **33** | 2 | 1 | 14 | 123 | 0 | 1 | 0 | **138** | 0 | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 3 | 0 | 4 | 0 | **12** | 0 | 1 | **323** |
| **Hourly Total** | 15 | 30 | 460 | 21 | 0 | **526** | 1 | 0 | 36 | 21 | 20 | 29 | 0 | **106** | 2 | 1 | 53 | 438 | 8 | 1 | 0 | **500** | 0 | 1 | 2 | 8 | 6 | 0 | 0 | **18** | 0 | 1 | 0 | 6 | 0 | 10 | 0 | **25** | 0 | 1 | **1181** |
| 5:00:00 PM | 4 | 8 | 113 | 6 | 0 | **131** | 0 | 0 | 5 | 4 | 6 | 11 | 0 | **26** | 0 | 0 | 10 | 126 | 3 | 0 | 0 | **139** | 1 | 0 | 0 | 3 | 3 | 0 | 0 | **6** | 0 | 1 | 0 | 4 | 0 | 0 | 0 | **10** | 0 | 1 | **289** |
| 5:15:00 PM | 3 | 4 | 118 | 5 | 0 | **130** | 0 | 0 | 11 | 5 | 6 | 14 | 0 | **36** | 0 | 0 | 9 | 126 | 7 | 0 | 0 | **142** | 0 | 0 | 0 | 2 | 3 | 0 | 0 | **5** | 0 | 0 | 0 | 2 | 0 | 2 | 0 | **6** | 0 | 0 | **323** |
| 5:30:00 PM | 1 | 4 | 132 | 7 | 0 | **144** | 0 | 0 | 16 | 6 | 2 | 8 | 0 | **32** | 0 | 0 | 10 | 90 | 2 | 0 | 0 | **102** | 0 | 0 | 1 | 2 | 1 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 0 | 3 | 0 | **7** | 0 | 1 | **312** |
| 5:45:00 PM | 5 | 10 | 111 | 5 | 0 | **131** | 0 | 0 | 13 | 9 | 5 | 11 | 0 | **38** | 0 | 1 | 8 | 105 | 4 | 0 | 0 | **126** | 0 | 0 | 0 | 4 | 2 | 0 | 0 | **6** | 0 | 0 | 1 | 0 | 0 | 3 | 0 | **4** | 2 | 0 | **319** |
| **Hourly Total** | 13 | 26 | 474 | 23 | 0 | **536** | 0 | 0 | 45 | 24 | 19 | 44 | 0 | **132** | 0 | 1 | 37 | 447 | 16 | 0 | 0 | **509** | 1 | 0 | 1 | 11 | 9 | 0 | 0 | **21** | 0 | 2 | 1 | 8 | 0 | 8 | 0 | **27** | 2 | 1 | **1243** |
| **Grand Total** | 42 | 74 | 1373 | 70 | 0 | **1559** | 1 | 0 | 106 | 59 | 58 | 112 | 0 | **345** | 2 | 3 | 123 | 1383 | 35 | 3 | 0 | **1524** | 2 | 1 | 5 | 35 | 19 | 1 | 0 | **68** | 1 | 3 | 3 | 24 | 40 | 10 | 0 | **80** | 6 | 2 | **13866** |
| **% Approach** | 2.7% | 4.7% | 88.1% | 7000.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 30.8% | 20.2% | 16.8% | 5600.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.1% | 89.4% | 2.3% | 150.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.3% | 58.3% | 31.7% | 100.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 3.5% | 27.9% | 46.5% | 316.7% | 0.0% | **0.8%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.2% | 2.1% | 39.4% | 2.0% | 0.0% | **43.6%** | 0.0% | 0.0% | 3.0% | 2.0% | 1.6% | 3.1% | 0.0% | **9.7%** | 0.0% | 0.0% | 3.4% | 38.1% | 1.0% | 0.1% | 0.0% | **42.6%** | 0.0% | 0.0% | 0.1% | 1.0% | 0.5% | 0.0% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.1% | 0.7% | 1.1% | 0.0% | 0.0% | **2.4%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 41 | 74 | 1366 | 68 | 0 | **1549** | 0 | 0 | 105 | 59 | 57 | 111 | 0 | **342** | 0 | 0 | 122 | 1353 | 35 | 3 | 0 | **1513** | 0 | 0 | 4 | 34 | 19 | 1 | 0 | **58** | 0 | 0 | 3 | 24 | 38 | 19 | 0 | **84** | 0 | 0 | **3546** |
| **% Lights** | 97.6% | 100.0% | 99.5% | 97.1% | 0.0% | **99.4%** | 0.0% | 0.0% | 99.1% | 98.8% | 98.3% | 99.1% | 0.0% | **98.8%** | 0.0% | 0.0% | 99.2% | 99.3% | 100.0% | 100.0% | 0.0% | **99.3%** | 0.0% | 0.0% | 80.0% | 97.1% | 100.0% | 100.0% | 0.0% | **85.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 95.0% | 100.0% | 0.0% | **97.7%** | 0.0% | 0.0% | **25.6%** |
| **Trucks** | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 1 | 0 | 0 | 1 | 0 | **2** | 0 | 0 | 0 | 3 | 0 | 0 | 0 | **3** | 0 | 0 | 1 | 0 | 0 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.9% | 0.0% | 0.0% | 0.9% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Buses** | 1 | 0 | 3 | 1 | 0 | **5** | 0 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 1 | 6 | 0 | 0 | 0 | **6** | 0 | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | **16** |
| **% Buses** | 2.4% | 0.0% | 0.2% | 1.4% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 1.4% | 1.7% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 2.9% | 0.0% | 0.0% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 5.0% | 0.0% | 0.0% | **2.5%** | 0.0% | 0.0% | **0.4%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | **3** |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



**Summary**

TRI-STATE TRAFFIC DATA


TSTData.com

**Summary**

## Turning Movement Peak Hour Data (PM)

**4:45:00 PM**

| Leg | Bailey Road | | | | | | | Emerson Drive | | | | | | | Bailey Road | | | | | | | Emerson Drive | | | | | | | Amsterdam Ave | | | | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | Southbound | | | | | | | |
| Start Time | Heavy Right | Right | Thru | Left | U-Turn | App. Total | Peds | Heavy Left | Soft Right | Right | Thru | Left | U-Turn | App. Total | Peds | Heavy Left | Right | Thru | Soft Left | Left | U-Turn | App. Total | Peds | Heavy Left | Right | Thru | Left | Heavy Left | U-Turn | App. Total | Peds | Heavy Left | Heavy Left | Soft Right | Soft Left | Heavy Left | U-Turn | App. Total | Peds | Heavy Left | |
| 4:45:00 PM | 4 | 7 | 115 | 6 | 0 | 132 | 0 | 0 | 12 | 9 | 7 | 11 | 0 | 39 | 2 | 1 | 14 | 123 | 0 | 1 | 0 | 138 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 2 | 0 | 0 | 0 | 3 | 5 | 4 | 0 | 12 | 0 | 1 | 323 |
| 5:00:00 PM | 4 | 8 | 113 | 6 | 0 | 131 | 0 | 0 | 5 | 4 | 6 | 11 | 0 | 26 | 0 | 0 | 10 | 126 | 3 | 0 | 0 | 139 | 1 | 0 | 0 | 3 | 3 | 0 | 0 | 6 | 0 | 1 | 0 | 4 | 6 | 0 | 0 | 10 | 0 | 1 | 312 |
| 5:15:00 PM | 3 | 4 | 118 | 5 | 0 | 130 | 0 | 0 | 11 | 5 | 6 | 14 | 0 | 36 | 0 | 0 | 9 | 126 | 7 | 0 | 0 | 142 | 0 | 0 | 0 | 2 | 3 | 0 | 0 | 5 | 0 | 0 | 0 | 2 | 2 | 2 | 0 | 6 | 0 | 0 | 319 |
| 5:30:00 PM | 1 | 4 | 132 | 7 | 0 | 144 | 0 | 0 | 16 | 6 | 2 | 8 | 0 | 32 | 0 | 0 | 10 | 90 | 2 | 0 | 0 | 102 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 4 | 0 | 0 | 0 | 2 | 2 | 3 | 0 | 7 | 0 | 1 | 289 |
| Grand Total | 12 | 23 | 478 | 24 | 0 | 537 | 0 | 0 | 44 | 24 | 21 | 44 | 0 | 133 | 2 | 1 | 43 | 465 | 12 | 1 | 0 | 521 | 1 | 0 | 1 | 7 | 9 | 0 | 0 | 17 | 0 | 1 | 0 | 11 | 15 | 9 | 0 | 35 | 0 | 2 | 1240 |
| % Approach | 2.2% | 4.3% | 89.0% | 4.5% | 0.0% | 0.0% | 0.0% | 0.0% | 33.1% | 18.0% | 15.8% | 33.1% | 0.0% | 0.0% | 0.0% | 0.0% | 8.3% | 89.3% | 2.3% | 0.2% | 0.0% | 0.0% | 0.0% | 0.0% | 5.9% | 41.2% | 52.9% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 31.4% | 42.9% | 25.7% | 0.0% | 0.0% | 0.0% | 0.0% | |
| % Total | 1.0% | 1.9% | 38.5% | 1.9% | 0.0% | 43.3% | 0.0% | 0.0% | 3.5% | 1.9% | 1.7% | 3.5% | 0.0% | 10.7% | 0.0% | 0.0% | 3.5% | 37.4% | 1.0% | 0.1% | 0.0% | 41.9% | 0.0% | 0.0% | 0.1% | 0.6% | 0.7% | 0.0% | 0.0% | 1.4% | 0.0% | 0.0% | 0.0% | 0.9% | 1.2% | 0.7% | 0.0% | 2.8% | 0.0% | 0.0% | |
| PHF | 0.750 | 0.719 | 0.905 | 0.857 | 0.000 | 0.932 | 0.000 | 0.000 | 0.688 | 0.667 | 0.700 | 0.786 | 0.000 | 0.853 | 0.500 | 0.000 | 0.768 | 0.923 | 0.429 | 0.250 | 0.000 | 0.917 | 0.500 | 0.000 | 0.250 | 0.583 | 0.750 | 0.000 | 0.000 | 0.708 | 0.000 | 0.000 | 0.000 | 0.688 | 0.625 | 0.563 | 0.000 | 0.729 | 0.000 | 0.000 | 0.962 |
| Lights | 12 | 23 | 478 | 24 | 0 | 537 | 0 | 0 | 44 | 24 | 21 | 44 | 0 | 133 | 0 | 0 | 43 | 461 | 12 | 1 | 0 | 517 | 0 | 0 | 1 | 7 | 9 | 0 | 0 | 17 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1239 |
| % Lights | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | 100.0% | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | 100.0% | 0.0% | 0.0% | 100.0% | 99.1% | 100.0% | 100.0% | 0.0% | 99.2% | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | 0.0% | 100.0% | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 99.7% |
| Trucks | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 15 | 9 | 0 | 35 | 0 | 0 | 2 |
| % Trucks | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | 100.0% | 0.0% | 0.0% | 0.2% |
| Buses | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| % Buses | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.2% |
| Pedestrians | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| % Pedestrians | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% |
| Bicycles on Crosswalk | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| % Bicycles on Crosswalk | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% |







## TurningMovementData

| Leg | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | AmsterdamAve | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | | Westbound | | | | | | | | Northbound | | | | | | | | Eastbound | | | | | | | | Southeastbound | | | | | | | | |
| StartTime | HardRight | Right | Thru | Left | UTurn | AppTotal | PedsCW | PedsCCW | Right | SoftRight | Thru | Left | UTurn | AppTotal | PedsCW | PedsCCW | Right | Thru | SoftLeft | Left | UTurn | AppTotal | PedsCW | PedsCCW | Right | Thru | Left | HardLeft | UTurn | AppTotal | PedsCW | PedsCCW | HardRight | SoftRight | SoftLeft | HardLeft | UTurn | AppTotal | PedsCW | PedsCCW | Total |
| 3:00:00PM | 5 | 7 | 109 | 3 | 0 | **124** | 0 | 0 | 9 | 4 | 7 | 14 | 0 | **34** | 0 | 0 | 8 | 87 | 2 | 1 | 0 | **98** | 0 | 0 | 1 | 6 | 1 | 1 | 0 | **9** | 0 | 0 | 1 | 3 | 8 | 0 | 0 | **12** | 0 | 0 | **277** |
| 3:15:00PM | 2 | 3 | 105 | 8 | 0 | **118** | 0 | 0 | 4 | 2 | 3 | 6 | 0 | **15** | 0 | 1 | 9 | 125 | 5 | 1 | 0 | **140** | 0 | 0 | 1 | 6 | 1 | 0 | 0 | **8** | 1 | 0 | 0 | 3 | 3 | 1 | 0 | **7** | 2 | 0 | **288** |
| 3:30:00PM | 3 | 7 | 106 | 11 | 0 | **127** | 0 | 0 | 6 | 5 | 5 | 8 | 0 | **24** | 0 | 0 | 9 | 120 | 2 | 0 | 0 | **131** | 1 | 1 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 3 | 1 | 0 | **4** | 0 | 0 | **288** |
| 3:45:00PM | 4 | 1 | 122 | 4 | 0 | **131** | 0 | 0 | 6 | 5 | 4 | 11 | 0 | **26** | 0 | 0 | 7 | 125 | 2 | 0 | 0 | **134** | 0 | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 1 | 1 | 4 | 4 | 0 | 0 | **9** | 2 | 1 | **302** |
| **HourlyTotal** | 14 | 18 | 442 | 26 | 0 | **500** | 0 | 0 | 25 | 16 | 19 | 39 | 0 | **99** | 0 | 1 | 33 | 457 | 11 | 2 | 0 | **503** | 1 | 1 | 2 | 16 | 2 | 1 | 0 | **21** | 1 | 1 | 2 | 10 | 18 | 2 | 0 | **32** | 4 | 1 | **1155** |
| 4:00:00PM | 5 | 11 | 121 | 4 | 0 | **141** | 0 | 2 | 7 | 9 | 3 | 6 | 0 | **25** | 0 | 0 | 11 | 110 | 5 | 0 | 0 | **126** | 0 | 0 | 0 | 2 | 1 | 0 | 0 | **3** | 0 | 0 | 0 | 1 | 1 | 4 | 0 | **6** | 0 | 2 | **301** |
| 4:15:00PM | 2 | 5 | 100 | 6 | 0 | **113** | 0 | 0 | 13 | 2 | 7 | 5 | 0 | **27** | 0 | 0 | 13 | 109 | 1 | 0 | 0 | **123** | 0 | 0 | 0 | 1 | 2 | 0 | 0 | **3** | 0 | 0 | 0 | 0 | 1 | 1 | 0 | **2** | 0 | 0 | **268** |
| 4:30:00PM | 4 | 7 | 121 | 5 | 0 | **137** | 1 | 0 | 4 | 10 | 3 | 7 | 0 | **24** | 0 | 0 | 15 | 96 | 2 | 0 | 0 | **113** | 0 | 1 | 2 | 5 | 3 | 0 | 0 | **10** | 0 | 1 | 0 | 2 | 2 | 1 | 0 | **5** | 0 | 0 | **289** |
| 4:45:00PM | 4 | 7 | 115 | 6 | 0 | **132** | 0 | 0 | 12 | 9 | 7 | 11 | 0 | **39** | 2 | 1 | 14 | 123 | 0 | 1 | 0 | **138** | 0 | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 3 | 5 | 4 | 0 | **12** | 0 | 1 | **323** |
| **HourlyTotal** | 15 | 30 | 457 | 21 | 0 | **523** | 1 | 2 | 36 | 30 | 20 | 29 | 0 | **115** | 2 | 1 | 53 | 438 | 8 | 1 | 0 | **500** | 0 | 1 | 2 | 8 | 8 | 0 | 0 | **18** | 0 | 1 | 0 | 6 | 9 | 10 | 0 | **25** | 0 | 3 | **1181** |
| 5:00:00PM | 4 | 8 | 113 | 6 | 0 | **131** | 0 | 0 | 5 | 4 | 6 | 11 | 0 | **26** | 0 | 0 | 10 | 126 | 3 | 0 | 0 | **139** | 1 | 0 | 0 | 3 | 3 | 0 | 0 | **6** | 0 | 1 | 0 | 4 | 6 | 0 | 0 | **10** | 0 | 1 | **312** |
| 5:15:00PM | 3 | 4 | 118 | 5 | 0 | **130** | 0 | 0 | 11 | 5 | 6 | 14 | 0 | **36** | 0 | 0 | 9 | 126 | 7 | 0 | 0 | **142** | 0 | 0 | 0 | 2 | 3 | 0 | 0 | **5** | 0 | 0 | 0 | 2 | 2 | 2 | 0 | **6** | 0 | 0 | **319** |
| 5:30:00PM | 1 | 4 | 132 | 7 | 0 | **144** | 0 | 0 | 16 | 6 | 2 | 8 | 0 | **32** | 0 | 0 | 10 | 90 | 2 | 0 | 0 | **102** | 0 | 0 | 1 | 2 | 1 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 2 | 3 | 0 | **7** | 0 | 1 | **289** |
| 5:45:00PM | 5 | 10 | 111 | 5 | 0 | **131** | 0 | 0 | 13 | 9 | 5 | 11 | 0 | **38** | 0 | 1 | 8 | 126 | 4 | 0 | 0 | **138** | 0 | 0 | 0 | 4 | 2 | 0 | 0 | **6** | 0 | 0 | 1 | 0 | 3 | 2 | 0 | **6** | 2 | 0 | **319** |
| **HourlyTotal** | 13 | 26 | 474 | 23 | 0 | **536** | 0 | 0 | 45 | 24 | 19 | 44 | 0 | **132** | 0 | 1 | 37 | 468 | 16 | 0 | 0 | **521** | 1 | 0 | 1 | 11 | 9 | 0 | 0 | **21** | 0 | 2 | 1 | 8 | 13 | 7 | 0 | **29** | 2 | 2 | **1239** |
| **GrandTotal** | 42 | 74 | 1373 | 70 | 0 | **1559** | 1 | 2 | 106 | 70 | 58 | 112 | 0 | **346** | 2 | 3 | 123 | 1363 | 35 | 3 | 0 | **1524** | 2 | 2 | 5 | 35 | 19 | 1 | 0 | **60** | 1 | 4 | 3575 | 0 | 0 | 0 | 0 | **0** | 6 | 6 | **3575** |
| **% Approach** | 2.7% | 4.7% | 88.1% | 7000.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 30.6% | 20.2% | 16.8% | 5600.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.1% | 89.4% | 2.3% | 150.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.3% | 58.3% | 31.7% | 100.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.2% | 2.1% | 38.4% | 2.0% | 0.0% | **43.6%** | 0.0% | 0.0% | 3.0% | 2.0% | 1.6% | 3.1% | 0.0% | **9.7%** | 0.0% | 0.0% | 3.4% | 38.1% | 1.0% | 0.1% | 0.0% | **42.6%** | 0.0% | 0.0% | 0.1% | 1.0% | 0.5% | 0.0% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 41 | 74 | 1366 | 68 | 0 | **1549** | 0 | 0 | 105 | 69 | 57 | 111 | 0 | **342** | 0 | 0 | 122 | 1353 | 35 | 3 | 0 | **1513** | 0 | 0 | 4 | 34 | 19 | 1 | 0 | **58** | 0 | 0 | 3546 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **3546** |
| **% Lights** | 97.6% | 100.0% | 99.5% | 97.1% | 0.0% | **99.4%** | 0.0% | 0.0% | 99.1% | 98.6% | 98.3% | 99.1% | 0.0% | **98.8%** | 0.0% | 0.0% | 99.2% | 99.3% | 100.0% | 100.0% | 0.0% | **99.3%** | 0.0% | 0.0% | 80.0% | 97.1% | 100.0% | 100.0% | 0.0% | **96.7%** | 0.0% | 0.0% | 99.2% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **99.2%** |
| **Trucks** | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 1 | 0 | 0 | 1 | 0 | **2** | 0 | 0 | 0 | 3 | 0 | 0 | 0 | **3** | 0 | 0 | 1 | 0 | 0 | 0 | 0 | **1** | 0 | 0 | 10 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **10** |
| **% Trucks** | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.9% | 0.0% | 0.0% | 0.9% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 20.0% | 0.0% | 0.0% | 0.0% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Buses** | 1 | 0 | 3 | 1 | 0 | **5** | 0 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 6 | 0 | 0 | 0 | **6** | 0 | 0 | 0 | 1 | 0 | 0 | 0 | **1** | 0 | 0 | 16 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **16** |
| **% Buses** | 2.4% | 0.0% | 0.2% | 1.4% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 1.4% | 1.7% | 0.0% | 0.0% | **0.6%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 2.9% | 0.0% | 0.0% | 0.0% | **1.7%** | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.4%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 6 | 6 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 66.7% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | **0.0%** |
| **Bicycleson Crosswalk** | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycleson Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 33.3% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |


## TurningMovementDataPlot




## TurningMovementPeakHourData (PM)

**4:45:00PM**

| Leg | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | AmsterdamAve | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | | Westbound | | | | | | | | Northbound | | | | | | | | Eastbound | | | | | | | | Southeastbound | | | | | | | | |
| StartTime | HardRight | Right | Thru | Left | U-Turn | App Total | PedsCW | PedsCCW | Right | SoftRight | Thru | Left | U-Turn | App Total | PedsCW | PedsCCW | Right | Thru | SoftLeft | Left | U-Turn | App Total | PedsCW | PedsCCW | Right | Thru | Left | HardLeft | U-Turn | App Total | PedsCW | PedsCCW | HardRight | SoftRight | SoftLeft | HardLeft | U-Turn | App Total | PedsCW | PedsCCW | Total |
| 4:45:00PM | 4 | 7 | 115 | 6 | 0 | **132** | 0 | 0 | 12 | 9 | 7 | 11 | 0 | **39** | 2 | 1 | 14 | 123 | 0 | 1 | 0 | **138** | 0 | 0 | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 3 | 5 | 4 | 0 | **12** | 0 | 1 | **323** |
| 5:00:00PM | 4 | 8 | 113 | 6 | 0 | **131** | 0 | 0 | 5 | 4 | 6 | 11 | 0 | **26** | 0 | 0 | 10 | 126 | 3 | 0 | 0 | **139** | 1 | 0 | 0 | 3 | 3 | 0 | 0 | **6** | 0 | 1 | 0 | 4 | 6 | 0 | 0 | **10** | 0 | 1 | **312** |
| 5:15:00PM | 3 | 4 | 118 | 5 | 0 | **130** | 0 | 0 | 11 | 5 | 6 | 14 | 0 | **36** | 0 | 0 | 9 | 126 | 7 | 0 | 0 | **142** | 0 | 0 | 0 | 2 | 3 | 0 | 0 | **5** | 0 | 0 | 0 | 2 | 2 | 2 | 0 | **6** | 0 | 0 | **319** |
| 5:30:00PM | 1 | 4 | 132 | 7 | 0 | **144** | 0 | 0 | 16 | 6 | 2 | 8 | 0 | **32** | 0 | 0 | 10 | 90 | 2 | 0 | 0 | **102** | 0 | 0 | 1 | 2 | 1 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 2 | 3 | 0 | **7** | 0 | 1 | **289** |
| **GrandTotal** | 12 | 23 | 478 | 24 | 0 | **537** | 0 | 0 | 44 | 24 | 21 | 44 | 0 | **133** | 2 | 1 | 43 | 465 | 12 | 1 | 0 | **521** | 1 | 0 | 1 | 7 | 9 | 0 | 0 | **17** | 0 | 2 | 0 | 11 | 15 | 9 | 0 | **35** | 0 | 3 | **1243** |
| **% Approach** | 2.2% | 4.3% | 89.0% | 4.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 33.1% | 18.0% | 15.8% | 33.1% | 0.0% | **0.0%** | 0.0% | 0.0% | 8.3% | 89.3% | 2.3% | 0.2% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.9% | 41.2% | 52.9% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 31.4% | 42.9% | 25.7% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 1.0% | 1.9% | 38.5% | 1.9% | 0.0% | **43.2%** | 0.0% | 0.0% | 3.5% | 1.9% | 1.7% | 3.5% | 0.0% | **10.7%** | 0.0% | 0.0% | 3.5% | 37.4% | 1.0% | 0.1% | 0.0% | **41.9%** | 0.0% | 0.0% | 0.1% | 0.6% | 0.7% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.0% | 0.9% | 1.2% | 0.7% | 0.0% | **2.8%** | 0.0% | 0.0% | |
| **PHF** | 0.750 | 0.719 | 0.905 | 0.857 | 0.000 | **0.932** | 0.000 | 0.000 | 0.688 | 0.667 | 0.750 | 0.786 | 0.000 | **0.853** | 0.000 | 0.000 | 0.768 | 0.923 | 0.429 | 0.250 | 0.000 | **0.917** | 0.000 | 0.000 | 0.250 | 0.583 | 0.750 | 0.000 | 0.000 | **0.708** | 0.000 | 0.000 | 0.000 | 0.688 | 0.625 | 0.563 | 0.000 | **0.729** | 0.000 | 0.000 | **0.962** |
| **Lights** | 12 | 23 | 478 | 24 | 0 | **537** | 0 | 0 | 44 | 24 | 21 | 44 | 0 | **133** | 0 | 0 | 43 | 461 | 12 | 1 | 0 | **517** | 0 | 0 | 1 | 7 | 9 | 0 | 0 | **17** | 0 | 0 | 0 | 11 | 15 | 9 | 0 | **35** | 0 | 0 | **1239** |
| **% Lights** | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 99.1% | 100.0% | 100.0% | 0.0% | **99.2%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.7%** |
| **Trucks** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **2** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Buses** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **2** |
| **% Buses** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | **0.4%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | **0** | 0 | 0 | 0 | 0 | 0 | **0** | 2 | **0** | 0 | 0 | 0 | 0 | 0 | **0** | 1 | **0** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | **2** | 0 | 0 | 0 | 0 | 0 | **0** | 3 | **0** | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycleson Crosswalk** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycleson Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



TRI-STATE TRAFFIC DATA

TSTData.com

**Summary**

| | |
|---|---|
| **Project** | C & S |
| **Project Code** | 11682 |
| **Site Name** | Bailey Road & Emerson Drive |
| **Legs and Movements** | All Processed Legs & Movements |
| **Bin Size** | 15 minutes |
| **Survey Date** | 2023-11-18, Saturday |
| **Location** | Bailey Road & Emerson Drive |
| **Latitude and Longitude** | 42.98602, -78.8143 |

| | Start | End | PHF |
|---|---|---|---|
| **PM Peak** | 2023-11-18 13:15:00 | 2023-11-18 14:15:00 | 0.9724 |

## Turning Movement Data


| Leg | Bailey Road | | | | | | | | Emerson Drive | | | | | | | | Bailey Road | | | | | | | | Emerson Drive | | | | | | | | Amsterdam Ave | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | | Westbound | | | | | | | | Northbound | | | | | | | | Eastbound | | | | | | | | Southwestbound | | | | | | | | |
| Start Time | Hard Right | Right | Thru | Left | U-Turn | App. Total | Peds | Bike | Hard Right | Soft Right | Thru | Left | U-Turn | App. Total | Peds | Bike | Right | Thru | Soft Left | Left | U-Turn | App. Total | Peds | Bike | Right | Thru | Left | Hard Left | U-Turn | App. Total | Peds | Bike | Hard Right | Soft Right | Soft Left | Hard Left | U-Turn | App. Total | Peds | Bike | Total |
| 12:00:00 | 4 | 7 | 132 | 5 | 0 | **148** | 0 | 0 | 5 | 6 | 4 | 5 | 0 | **20** | 0 | 0 | 8 | 124 | 2 | 0 | 0 | **134** | 0 | 0 | 0 | 2 | 2 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 1 | 4 | 0 | **7** | 0 | 1 | **313** |
| 12:15:00 | 5 | 9 | 132 | 4 | 0 | **150** | 0 | 0 | 8 | 4 | 4 | 8 | 0 | **24** | 0 | 1 | 8 | 142 | 2 | 0 | 0 | **152** | 0 | 0 | 1 | 4 | 2 | 0 | 0 | **7** | 0 | 0 | 0 | 5 | 2 | 4 | 0 | **11** | 0 | 0 | **344** |
| 12:30:00 | 9 | 9 | 138 | 7 | 0 | **163** | 0 | 0 | 7 | 4 | 3 | 8 | 0 | **22** | 0 | 0 | 7 | 142 | 2 | 0 | 0 | **151** | 0 | 1 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 1 | 0 | 2 | 3 | 4 | 0 | **9** | 0 | 2 | **347** |
| 12:45:00 | 4 | 8 | 129 | 12 | 0 | **153** | 0 | 0 | 10 | 4 | 2 | 7 | 0 | **23** | 0 | 1 | 6 | 118 | 4 | 3 | 0 | **132** | 0 | 0 | 0 | 1 | 2 | 0 | 0 | **3** | 1 | 0 | 0 | 4 | 4 | 5 | 0 | **13** | 1 | 0 | **319** |
| **Hourly Total** | **22** | **33** | **531** | **28** | **0** | **614** | **0** | **0** | **30** | **18** | **13** | **28** | **0** | **89** | **0** | **2** | **29** | **527** | **10** | **3** | **0** | **569** | **0** | **1** | **1** | **8** | **7** | **0** | **0** | **16** | **1** | **2** | **0** | **13** | **10** | **17** | **0** | **40** | **1** | **3** | **1323** |
| 13:00:00 | 3 | 8 | 132 | 7 | 0 | **150** | 0 | 1 | 10 | 3 | 6 | 8 | 0 | **27** | 0 | 1 | 7 | 139 | 0 | 0 | 0 | **146** | 0 | 0 | 0 | 3 | 1 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 3 | 4 | 0 | **9** | 0 | 1 | **336** |
| 13:15:00 | 0 | 11 | 144 | 6 | 0 | **161** | 0 | 0 | 7 | 4 | 5 | 4 | 0 | **20** | 0 | 0 | 11 | 132 | 4 | 0 | 0 | **147** | 0 | 0 | 1 | 3 | 5 | 0 | 0 | **9** | 0 | 0 | 0 | 1 | 5 | 5 | 0 | **11** | 0 | 0 | **348** |
| 13:30:00 | 3 | 9 | 138 | 6 | 0 | **156** | 0 | 0 | 7 | 4 | 2 | 5 | 0 | **18** | 0 | 2 | 10 | 129 | 4 | 2 | 0 | **145** | 0 | 2 | 0 | 2 | 4 | 0 | 0 | **6** | 0 | 1 | 0 | 1 | 2 | 2 | 0 | **5** | 0 | 0 | **330** |
| 13:45:00 | 3 | 14 | 143 | 8 | 0 | **168** | 0 | 0 | 5 | 7 | 2 | 7 | 0 | **21** | 1 | 0 | 5 | 129 | 3 | 0 | 0 | **137** | 0 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 1 | 1 | 0 | 1 | 7 | 4 | 0 | **12** | 0 | 1 | **340** |
| **Hourly Total** | **9** | **42** | **557** | **27** | **0** | **635** | **0** | **1** | **29** | **18** | **15** | **24** | **0** | **86** | **1** | **4** | **33** | **529** | **11** | **2** | **0** | **575** | **0** | **3** | **1** | **9** | **11** | **0** | **0** | **21** | **1** | **4** | **0** | **5** | **17** | **15** | **0** | **37** | **0** | **3** | **1354** |
| 14:00:00 | 6 | 10 | 131 | 11 | 0 | **158** | 0 | 0 | 8 | 4 | 1 | 4 | 0 | **17** | 0 | 0 | 11 | 132 | 1 | 1 | 0 | **145** | 1 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 1 | 0 | 2 | 5 | 5 | 3 | 0 | **15** | 0 | 0 | **337** |
| 14:15:00 | 3 | 10 | 136 | 5 | 0 | **154** | 0 | 0 | 8 | 3 | 2 | 11 | 0 | **24** | 2 | 0 | 5 | 138 | 2 | 1 | 0 | **146** | 0 | 0 | 0 | 3 | 1 | 1 | 0 | **5** | 0 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | **331** |
| 14:30:00 | 5 | 14 | 154 | 8 | 0 | **181** | 0 | 0 | 8 | 6 | 2 | 9 | 0 | **25** | 1 | 2 | 7 | 124 | 1 | 0 | 0 | **132** | 0 | 0 | 1 | 4 | 0 | 0 | 0 | **5** | 0 | 0 | 0 | 1 | 6 | 1 | 0 | **8** | 0 | 0 | **351** |
| 14:45:00 | 5 | 11 | 157 | 6 | 0 | **179** | 0 | 1 | 6 | 7 | 6 | 9 | 0 | **28** | 1 | 0 | 11 | 102 | 1 | 1 | 0 | **103** | 1 | 0 | 1 | 5 | 0 | 0 | 0 | **6** | 0 | 0 | 0 | 4 | 4 | 4 | 0 | **12** | 0 | 0 | **334** |
| **Hourly Total** | **19** | **45** | **578** | **30** | **0** | **672** | **0** | **1** | **30** | **20** | **11** | **33** | **0** | **94** | **4** | **2** | **34** | **514** | **5** | **3** | **0** | **526** | **1** | **0** | **2** | **13** | **2** | **1** | **0** | **18** | **1** | **0** | **2** | **11** | **16** | **8** | **0** | **37** | **0** | **0** | **1352** |
| **Grand Total** | **50** | **120** | **1646** | **85** | **0** | **1991** | **0** | **2** | **89** | **56** | **39** | **85** | **0** | **269** | **1** | **6** | **96** | **1570** | **26** | **8** | **0** | **1730** | **1** | **3** | **4** | **26** | **20** | **1** | **0** | **51** | **1** | **6** | **2** | **29** | **43** | **35** | **0** | **109** | **1** | **3** | **4038** |
| **% Approach** | 2.6% | 6.3% | 86.6% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 33.1% | 20.8% | 14.5% | 1700.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.6% | 92.4% | 1.5% | 200.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 7.8% | 51.0% | 39.2% | 20.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.8% | 26.6% | 39.4% | 3500.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.2% | 3.0% | 40.8% | 2.1% | 0.0% | **47.2%** | 0.0% | 0.0% | 2.2% | 1.4% | 1.0% | 2.1% | 0.0% | **6.7%** | 0.0% | 0.0% | 2.4% | 39.0% | 0.6% | 0.2% | 0.0% | **42.2%** | 0.0% | 0.0% | 0.1% | 0.6% | 0.5% | 0.0% | 0.0% | **1.3%** | 0.0% | 0.0% | 0.0% | 0.7% | 1.1% | 0.9% | 0.0% | **2.7%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 50 | 119 | 1641 | 85 | 0 | **1895** | 0 | 0 | 89 | 56 | 39 | 85 | 0 | **269** | 0 | 0 | 95 | 1564 | 26 | 8 | 0 | **1693** | 0 | 0 | 4 | 26 | 20 | 1 | 0 | **51** | 0 | 0 | 2 | 29 | 43 | 35 | 0 | **109** | 0 | 0 | **4017** |
| **% Lights** | 100.0% | 99.2% | 99.7% | 100.0% | 0.0% | **99.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 99.0% | 99.6% | 100.0% | 100.0% | 0.0% | **99.6%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.5%** |
| **Trucks** | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 1 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **4** |
| **% Trucks** | 0.0% | 0.8% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.0% | 0.1% | 0.0% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Buses** | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **8** |
| **% Buses** | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 3 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | **0** |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 0.0% | **0.0%** |
| **Bicycles on Crosswalk** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 3 | 6 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 0 | **0** |
| **% Bicycles on Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 50.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |

TSTData.com

**Summary**

## Turning Movement Data Plot



**Summary**

TRI-STATE TRAFFIC DATA


TSTData.com


**Summary**

## Turning Movement Peak Hour Data (PM)

13:15:00

| Leg | Bailey Road | | | | | | | Emerson Drive | | | | | | | Bailey Road | | | | | | | Emerson Drive | | | | | | | Amsterdam Ave | | | | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | Westbound | | | | | | | Northbound | | | | | | | Eastbound | | | | | | | Southbound | | | | | | | |
| Start Time | Heavy Right | Right | Thru | Left | U-Turn | App. Total | Peds | Bicycles on Crosswalk | Heavy Right | Soft Right | Thru | Left | U-Turn | App. Total | Peds | Bicycles on Crosswalk | Heavy Right | Thru | Soft Left | Left | U-Turn | App. Total | Peds | Bicycles on Crosswalk | Heavy Right | Thru | Left | Heavy Left | U-Turn | App. Total | Peds | Bicycles on Crosswalk | Heavy Right | Soft Right | Soft Left | Heavy Left | U-Turn | App. Total | Peds | Bicycles on Crosswalk | |
| 13:15:00 | 0 | 11 | 144 | 6 | 0 | **161** | 0 | 0 | 7 | 4 | 5 | 4 | 0 | **20** | 0 | 2 | 11 | 132 | 4 | 0 | 0 | **147** | 0 | 0 | 1 | 3 | 5 | 0 | 0 | **9** | 0 | 0 | 0 | 1 | 5 | 5 | 0 | **11** | 0 | 0 | **348** |
| 13:30:00 | 3 | 9 | 138 | 6 | 0 | **156** | 0 | 0 | 7 | 4 | 2 | 5 | 0 | **18** | 0 | 2 | 10 | 129 | 4 | 2 | 0 | **145** | 0 | 2 | 0 | 2 | 4 | 0 | 0 | **6** | 0 | 1 | 0 | 1 | 2 | 2 | 0 | **5** | 0 | 0 | **330** |
| 13:45:00 | 3 | 14 | 143 | 8 | 0 | **168** | 0 | 0 | 5 | 7 | 2 | 7 | 0 | **21** | 1 | 0 | 5 | 129 | 3 | 0 | 0 | **137** | 3 | 1 | 0 | 1 | 1 | 0 | 0 | **2** | 1 | 2 | 0 | 1 | 7 | 4 | 0 | **12** | 0 | 1 | **340** |
| 14:00:00 | 6 | 10 | 131 | 11 | 0 | **158** | 0 | 0 | 8 | 4 | 1 | 4 | 0 | **17** | 0 | 0 | 11 | 132 | 1 | 1 | 0 | **145** | | | 0 | 1 | 1 | 0 | 0 | **2** | | | 2 | 5 | 5 | 3 | 0 | **15** | 0 | 0 | **337** |
| Grand Total | 12 | 44 | 556 | 31 | 0 | **643** | 0 | 0 | 27 | 19 | 10 | 20 | 0 | **76** | 1 | 4 | 37 | 522 | 12 | 3 | 0 | **574** | 3 | 3 | 1 | 7 | 11 | 0 | 0 | **19** | 1 | 3 | 2 | 8 | 19 | 14 | 0 | **43** | 0 | 1 | **1355** |
| % Approach | 1.9% | 6.8% | 86.5% | 4.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 35.5% | 25.0% | 13.2% | 26.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 90.9% | 2.1% | 0.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.3% | 36.8% | 57.9% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.7% | 18.6% | 44.2% | 32.6% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| % Total | 0.9% | 3.2% | 41.0% | 2.3% | 0.0% | **47.5%** | 0.0% | 0.0% | 2.0% | 1.4% | 0.7% | 1.5% | 0.0% | **5.6%** | 0.0% | 0.0% | 2.7% | 38.5% | 0.9% | 0.2% | 0.0% | **42.4%** | 0.0% | 0.0% | 0.1% | 0.5% | 0.8% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.1% | 0.6% | 1.4% | 1.0% | 0.0% | **3.2%** | 0.0% | 0.0% | |
| PHF | 0.500 | 0.786 | 0.965 | 0.705 | 0.000 | **0.957** | 0.000 | 0.000 | 0.944 | 0.679 | 0.500 | 0.714 | 0.000 | **0.905** | 0.500 | 0.500 | 0.841 | 0.969 | 0.750 | 0.375 | 0.000 | **0.976** | 0.500 | 0.500 | 0.250 | 0.583 | 0.550 | 0.000 | 0.000 | **0.528** | 0.250 | 0.250 | 0.400 | 0.679 | 0.700 | 0.000 | **0.717** | 0.000 | 0.000 | **0.000** | |
| Lights | 12 | 44 | 554 | 31 | 0 | **641** | 0 | 0 | 27 | 19 | 10 | 20 | 0 | **76** | 1 | 4 | 37 | 520 | 12 | 3 | 0 | **572** | 0 | 0 | 1 | 7 | 11 | 0 | 0 | **19** | 1 | 3 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| % Lights | 100.0% | 100.0% | 99.6% | 100.0% | 0.0% | **99.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 100.0% | 100.0% | 100.0% | 99.6% | 100.0% | 100.0% | 0.0% | **99.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | 0.0% | **100.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| Trucks | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 2 | 8 | 19 | 14 | 0 | **43** | 0 | 0 | **0** |
| % Trucks | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **0.0%** |
| Buses | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| % Buses | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| Pedestrians | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 3 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 3 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| % Pedestrians | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| Bicycles on Crosswalk | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| % Bicycles on Crosswalk | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |










## TurningMovementData

| Leg | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | AmsterdamAve | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | | Westbound | | | | | | | | Northbound | | | | | | | | Eastbound | | | | | | | | Southeastbound | | | | | | | | |
| StartTime | HardRight | Right | Thru | Left | UTurn | App Total | PedsCW | PedsCCW | Right | SoftRight | Thru | Left | UTurn | App Total | PedsCW | PedsCCW | Right | Thru | SoftLeft | Left | UTurn | App Total | PedsCW | PedsCCW | Right | Thru | Left | HardLeft | UTurn | App Total | PedsCW | PedsCCW | HardRight | SoftRight | SoftLeft | HardLeft | UTurn | App Total | PedsCW | PedsCCW | Total |
| 12:00:00 | 4 | 7 | 132 | 5 | 0 | **148** | 0 | 0 | 5 | 6 | 4 | 5 | 0 | **20** | 0 | 0 | 8 | 124 | 2 | 0 | 0 | **134** | 0 | 0 | 0 | 2 | 2 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 1 | 4 | 0 | **7** | 0 | 1 | **313** |
| 12:15:00 | 5 | 9 | 132 | 4 | 0 | **150** | 0 | 0 | 8 | 4 | 4 | 8 | 0 | **24** | 0 | 1 | 8 | 142 | 2 | 0 | 0 | **152** | 0 | 0 | 1 | 4 | 2 | 0 | 0 | **7** | 0 | 0 | 0 | 5 | 2 | 4 | 0 | **11** | 0 | 0 | **344** |
| 12:30:00 | 9 | 9 | 138 | 7 | 0 | **163** | 0 | 0 | 7 | 4 | 3 | 8 | 0 | **22** | 0 | 0 | 7 | 142 | 2 | 0 | 0 | **151** | 0 | 1 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 1 | 0 | 2 | 3 | 4 | 0 | **9** | 0 | 2 | **347** |
| 12:45:00 | 4 | 8 | 129 | 12 | 0 | **153** | 0 | 0 | 10 | 4 | 2 | 7 | 0 | **23** | 0 | 1 | 6 | 119 | 4 | 3 | 0 | **132** | 0 | 0 | 0 | 1 | 2 | 0 | 0 | **3** | 1 | 0 | 0 | 4 | 4 | 0 | 0 | **8** | 1 | 0 | **319** |
| **HourlyTotal** | 22 | 33 | 531 | 28 | 0 | **614** | 0 | 0 | 30 | 18 | 13 | 28 | 0 | **89** | 0 | 2 | 29 | 527 | 10 | 3 | 0 | **569** | 0 | 1 | 1 | 8 | 7 | 0 | 0 | **16** | 1 | 2 | 0 | 13 | 10 | 12 | 0 | **35** | 1 | 3 | **1323** |
| 13:00:00 | 3 | 8 | 132 | 7 | 0 | **150** | 0 | 1 | 10 | 3 | 6 | 8 | 0 | **27** | 0 | 2 | 7 | 139 | 0 | 0 | 0 | **146** | 0 | 0 | 0 | 3 | 1 | 0 | 0 | **4** | 0 | 1 | 0 | 2 | 3 | 4 | 0 | **9** | 0 | 2 | **336** |
| 13:15:00 | 0 | 11 | 144 | 6 | 0 | **161** | 0 | 0 | 7 | 4 | 5 | 4 | 0 | **20** | 0 | 0 | 11 | 132 | 4 | 0 | 0 | **147** | 0 | 0 | 1 | 3 | 5 | 0 | 0 | **9** | 0 | 0 | 0 | 1 | 5 | 5 | 0 | **11** | 0 | 0 | **348** |
| 13:30:00 | 3 | 9 | 138 | 6 | 0 | **156** | 0 | 0 | 7 | 4 | 2 | 5 | 0 | **18** | 0 | 2 | 10 | 129 | 4 | 2 | 0 | **145** | 0 | 2 | 0 | 2 | 4 | 0 | 0 | **6** | 0 | 1 | 0 | 1 | 2 | 2 | 0 | **5** | 0 | 0 | **330** |
| 13:45:00 | 3 | 14 | 143 | 8 | 0 | **168** | 0 | 0 | 5 | 7 | 2 | 7 | 0 | **21** | 1 | 0 | 5 | 129 | 3 | 0 | 0 | **137** | 3 | 1 | 0 | 1 | 1 | 0 | 0 | **2** | 3 | 2 | 0 | 1 | 7 | 4 | 0 | **12** | 0 | 1 | **340** |
| **HourlyTotal** | 9 | 42 | 557 | 27 | 0 | **635** | 0 | 1 | 29 | 18 | 15 | 24 | 0 | **86** | 1 | 4 | 33 | 529 | 11 | 2 | 0 | **575** | 3 | 3 | 1 | 9 | 11 | 0 | 0 | **21** | 3 | 4 | 0 | 5 | 17 | 15 | 0 | **37** | 0 | 3 | **1354** |
| 14:00:00 | 6 | 10 | 131 | 11 | 0 | **158** | 0 | 0 | 8 | 4 | 1 | 4 | 0 | **17** | 0 | 0 | 11 | 132 | 1 | 1 | 0 | **145** | 1 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 1 | 0 | 2 | 5 | 5 | 3 | 0 | **15** | 0 | 0 | **337** |
| 14:15:00 | 3 | 10 | 136 | 5 | 0 | **154** | 0 | 0 | 8 | 3 | 2 | 11 | 0 | **24** | 2 | 0 | 5 | 138 | 2 | 1 | 0 | **146** | 0 | 0 | 0 | 3 | 1 | 1 | 0 | **5** | 0 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | **331** |
| 14:30:00 | 5 | 14 | 154 | 8 | 0 | **181** | 0 | 0 | 8 | 6 | 2 | 9 | 0 | **25** | 1 | 2 | 7 | 124 | 1 | 0 | 0 | **132** | 0 | 0 | 1 | 4 | 0 | 0 | 0 | **5** | 0 | 0 | 0 | 1 | 6 | 1 | 0 | **8** | 0 | 0 | **351** |
| 14:45:00 | 5 | 11 | 137 | 6 | 0 | **159** | 0 | 1 | 6 | 7 | 6 | 9 | 0 | **28** | 1 | 2 | 11 | 120 | 1 | 1 | 0 | **133** | 0 | 0 | 1 | 1 | 0 | 0 | 0 | **2** | 0 | 4 | 0 | 4 | 4 | 4 | 0 | **12** | 0 | 4 | **334** |
| **HourlyTotal** | 19 | 45 | 558 | 30 | 0 | **652** | 0 | 1 | 30 | 20 | 11 | 33 | 0 | **94** | 4 | 4 | 34 | 514 | 5 | 3 | 0 | **556** | 1 | 0 | 2 | 9 | 2 | 1 | 0 | **14** | 1 | 4 | 2 | 11 | 16 | 8 | 0 | **37** | 0 | 4 | **1353** |
| **GrandTotal** | 50 | 120 | 1646 | 85 | 0 | **1901** | 0 | 2 | 89 | 56 | 39 | 85 | 0 | **269** | 5 | 10 | 96 | 1570 | 26 | 8 | 0 | **1700** | 4 | 4 | 4 | 26 | 20 | 1 | 0 | **51** | 5 | 10 | 4030 | 0 | 0 | 0 | 0 | **0** | 1 | 10 | **4030** |
| **% Approach** | 2.6% | 6.3% | 86.6% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 33.1% | 20.8% | 14.5% | 1700.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.6% | 92.4% | 1.5% | 200.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 7.8% | 51.0% | 39.2% | 20.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **% Total** | 1.2% | 3.0% | 40.8% | 2.1% | 0.0% | **47.2%** | 0.0% | 0.0% | 2.2% | 1.4% | 1.0% | 2.1% | 0.0% | **6.7%** | 0.0% | 0.0% | 2.4% | 39.0% | 0.6% | 0.2% | 0.0% | **42.2%** | 0.0% | 0.0% | 0.1% | 0.6% | 0.5% | 0.0% | 0.0% | **1.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Lights** | 50 | 119 | 1641 | 85 | 0 | **1895** | 0 | 0 | 89 | 56 | 39 | 85 | 0 | **269** | 0 | 0 | 95 | 1564 | 26 | 8 | 0 | **1693** | 0 | 0 | 4 | 26 | 20 | 1 | 0 | **51** | 0 | 0 | 4017 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **4017** |
| **% Lights** | 100.0% | 99.2% | 99.7% | 100.0% | 0.0% | **99.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 99.0% | 99.6% | 100.0% | 100.0% | 0.0% | **99.6%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 99.7% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **99.7%** |
| **Trucks** | 0 | 1 | 1 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 1 | 1 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 4 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **4** |
| **% Trucks** | 0.0% | 0.8% | 0.1% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 1.0% | 0.1% | 0.0% | 0.0% | 0.0% | **0.1%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.1% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.1%** |
| **Buses** | 0 | 0 | 4 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 4 | 0 | 0 | 0 | **4** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 8 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **8** |
| **% Buses** | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.3% | 0.0% | 0.0% | 0.0% | **0.2%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.2% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.2%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 3 | 6 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 5 | 9 | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 9 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 60.0% | 60.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 90.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 90.0% | **0.0%** |
| **Bicycleson Crosswalk** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 2 | 4 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 |
| **% Bicycleson Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 40.0% | 40.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 10.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 10.0% | **0.0%** |


## TurningMovementDataPlot




## TurningMovementPeakHourData (PM)

**13:15:00**

| Leg | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | BaileyRoad | | | | | | | | EmersonDrive | | | | | | | | AmsterdamAve | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | | | Westbound | | | | | | | | Northbound | | | | | | | | Eastbound | | | | | | | | Southeastbound | | | | | | | | |
| StartTime | HardRight | Right | Thru | Left | UTurn | AppTotal | PedsCW | PedsCCW | Right | SoftRight | Thru | Left | UTurn | AppTotal | PedsCW | PedsCCW | Right | Thru | SoftLeft | Left | UTurn | AppTotal | PedsCW | PedsCCW | Right | Thru | Left | HardLeft | UTurn | AppTotal | PedsCW | PedsCCW | HardRight | SoftRight | SoftLeft | HardLeft | UTurn | AppTotal | PedsCW | PedsCCW | Total |
| 13:15:00 | 0 | 11 | 144 | 6 | 0 | **161** | 0 | 0 | 7 | 4 | 5 | 4 | 0 | **20** | 0 | 0 | 11 | 132 | 4 | 0 | 0 | **147** | 0 | 0 | 1 | 3 | 5 | 0 | 0 | **9** | 0 | 0 | 0 | 1 | 5 | 5 | 0 | **11** | 0 | 0 | **348** |
| 13:30:00 | 3 | 9 | 138 | 6 | 0 | **156** | 0 | 0 | 7 | 4 | 2 | 5 | 0 | **18** | 0 | 2 | 10 | 129 | 4 | 2 | 0 | **145** | 0 | 2 | 0 | 2 | 4 | 0 | 0 | **6** | 0 | 1 | 0 | 1 | 2 | 2 | 0 | **5** | 0 | 0 | **330** |
| 13:45:00 | 3 | 14 | 143 | 8 | 0 | **168** | 0 | 0 | 5 | 7 | 2 | 7 | 0 | **21** | 1 | 0 | 5 | 129 | 3 | 0 | 0 | **137** | 3 | 1 | 0 | 1 | 1 | 0 | 0 | **2** | 3 | 2 | 0 | 1 | 7 | 4 | 0 | **12** | 0 | 1 | **340** |
| 14:00:00 | 6 | 10 | 131 | 11 | 0 | **158** | 0 | 0 | 8 | 4 | 1 | 4 | 0 | **17** | 0 | 0 | 11 | 132 | 1 | 1 | 0 | **145** | 1 | 0 | 0 | 1 | 1 | 0 | 0 | **2** | 1 | 0 | 2 | 5 | 5 | 3 | 0 | **15** | 0 | 0 | **337** |
| **GrandTotal** | 12 | 44 | 556 | 31 | 0 | **643** | 0 | 0 | 27 | 19 | 10 | 20 | 0 | **76** | 1 | 2 | 37 | 522 | 12 | 3 | 0 | **574** | 4 | 3 | 1 | 7 | 11 | 0 | 0 | **19** | 4 | 3 | 2 | 8 | 19 | 14 | 0 | **43** | 0 | 1 | **1355** |
| **% Approach** | 1.9% | 6.8% | 86.5% | 4.8% | 0.0% | **0.0%** | 0.0% | 0.0% | 35.5% | 25.0% | 13.2% | 26.3% | 0.0% | **0.0%** | 0.0% | 0.0% | 6.4% | 90.9% | 2.1% | 0.5% | 0.0% | **0.0%** | 0.0% | 0.0% | 5.3% | 36.8% | 57.9% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 4.7% | 18.6% | 44.2% | 32.6% | 0.0% | **0.0%** | 0.0% | 0.0% | |
| **% Total** | 0.9% | 3.2% | 41.0% | 2.3% | 0.0% | **47.5%** | 0.0% | 0.0% | 2.0% | 1.4% | 0.7% | 1.5% | 0.0% | **5.6%** | 0.0% | 0.0% | 2.7% | 38.5% | 0.9% | 0.2% | 0.0% | **42.4%** | 0.0% | 0.0% | 0.1% | 0.5% | 0.8% | 0.0% | 0.0% | **1.4%** | 0.0% | 0.0% | 0.1% | 0.6% | 1.4% | 1.0% | 0.0% | **3.2%** | 0.0% | 0.0% | |
| **PHF** | 0.500 | 0.786 | 0.965 | 0.705 | 0.000 | **0.957** | 0.000 | 0.000 | 0.844 | 0.679 | 0.500 | 0.714 | 0.000 | **0.905** | 0.000 | 0.000 | 0.841 | 0.989 | 0.750 | 0.375 | 0.000 | **0.976** | 0.000 | 0.000 | 0.250 | 0.583 | 0.550 | 0.000 | 0.000 | **0.528** | 0.000 | 0.000 | 0.250 | 0.400 | 0.679 | 0.700 | 0.000 | **0.717** | 0.000 | 0.000 | **0.973** |
| **Lights** | 12 | 44 | 554 | 31 | 0 | **641** | 0 | 0 | 27 | 19 | 10 | 20 | 0 | **76** | 0 | 0 | 37 | 520 | 12 | 3 | 0 | **572** | 0 | 0 | 1 | 7 | 11 | 0 | 0 | **19** | 0 | 0 | 2 | 8 | 19 | 14 | 0 | **43** | 0 | 0 | **1351** |
| **% Lights** | 100.0% | 100.0% | 99.6% | 100.0% | 0.0% | **99.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 99.6% | 100.0% | 100.0% | 0.0% | **99.7%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 0.0% | 0.0% | **100.0%** | 0.0% | 0.0% | 100.0% | 100.0% | 100.0% | 100.0% | 0.0% | **100.0%** | 0.0% | 0.0% | **99.7%** |
| **Trucks** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **0** |
| **% Trucks** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |
| **Buses** | 0 | 0 | 2 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 2 | 0 | 0 | 0 | **2** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | **4** |
| **% Buses** | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.4% | 0.0% | 0.0% | 0.0% | **0.3%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.3%** |
| **Pedestrians** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | | 0 | 0 | 0 | 0 | 0 | **0** | 1 | 2 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 3 | 0 | 0 | 0 | 0 | 0 | **0** | 4 | 3 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 1 | 0 |
| **% Pedestrians** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 100.0% | 100.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 100.0% | **0.0%** |
| **Bicycleson Crosswalk** | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 | 0 | 0 | 0 | 0 | **0** | 0 | 0 | 0 |
| **% Bicycleson Crosswalk** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | 0.0% | **0.0%** | 0.0% | 0.0% | **0.0%** |



Amherst, NY
January 23 & 25, 2025

Location: 43.002693, -78.822384

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 EB Off Ramp
Site Code: 11991-2
Start Date: 01/23/2025
Page No: 1

# Turning Movement Data

| Start Time | I 290 EB Off-Ramp/NB Niagara Falls Blvd | | | | | | NB Niagara Falls Blvd/I 290 EB On-Ramp | | | I 290 EB Off-Ramp/SB Niagara Falls Blvd | | | | | | SB Niagara Falls Blvd/I 290 EB On-Ramp | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Southbound | | | | | | Westbound | | | Northbound | | | | | | Eastbound | | | |
| | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Peds | App. Total | Int. Total |
| 3:00 PM | 122 | 252 | 0 | 0 | 0 | 374 | 58 | 0 | 58 | 119 | 287 | 0 | 0 | 0 | 406 | 88 | 0 | 88 | 926 |
| 3:15 PM | 123 | 244 | 0 | 0 | 0 | 367 | 59 | 1 | 59 | 111 | 310 | 0 | 0 | 0 | 421 | 95 | 0 | 95 | 942 |
| 3:30 PM | 128 | 314 | 0 | 0 | 0 | 442 | 81 | 1 | 81 | 117 | 289 | 0 | 0 | 0 | 406 | 84 | 2 | 84 | 1013 |
| 3:45 PM | 117 | 285 | 0 | 0 | 0 | 402 | 95 | 1 | 95 | 106 | 300 | 0 | 0 | 0 | 406 | 117 | 0 | 117 | 1020 |
| Hourly Total | 490 | 1095 | 0 | 0 | 0 | 1585 | 293 | 3 | 293 | 453 | 1186 | 0 | 0 | 0 | 1639 | 384 | 2 | 384 | 3901 |
| 4:00 PM | 111 | 297 | 0 | 0 | 0 | 408 | 70 | 0 | 70 | 134 | 301 | 0 | 0 | 0 | 435 | 87 | 0 | 87 | 1000 |
| 4:15 PM | 125 | 337 | 0 | 0 | 0 | 462 | 70 | 1 | 70 | 130 | 307 | 0 | 0 | 0 | 437 | 117 | 0 | 117 | 1086 |
| 4:30 PM | 129 | 271 | 0 | 0 | 0 | 400 | 86 | 0 | 86 | 107 | 293 | 0 | 0 | 0 | 400 | 87 | 0 | 87 | 973 |
| 4:45 PM | 120 | 329 | 0 | 0 | 0 | 449 | 93 | 0 | 93 | 107 | 271 | 0 | 0 | 0 | 378 | 124 | 0 | 124 | 1044 |
| Hourly Total | 485 | 1234 | 0 | 0 | 0 | 1719 | 319 | 1 | 319 | 478 | 1172 | 0 | 0 | 0 | 1650 | 415 | 0 | 415 | 4103 |
| 5:00 PM | 127 | 321 | 0 | 0 | 0 | 448 | 108 | 0 | 108 | 127 | 335 | 0 | 0 | 0 | 462 | 113 | 0 | 113 | 1131 |
| 5:15 PM | 107 | 293 | 0 | 0 | 0 | 400 | 99 | 0 | 99 | 133 | 285 | 0 | 0 | 0 | 418 | 98 | 0 | 98 | 1015 |
| 5:30 PM | 104 | 282 | 0 | 0 | 0 | 386 | 71 | 0 | 71 | 111 | 270 | 0 | 0 | 0 | 381 | 79 | 0 | 79 | 917 |
| 5:45 PM | 99 | 267 | 0 | 0 | 0 | 366 | 67 | 0 | 67 | 109 | 262 | 0 | 0 | 0 | 371 | 73 | 0 | 73 | 877 |
| Hourly Total | 437 | 1163 | 0 | 0 | 0 | 1600 | 345 | 0 | 345 | 480 | 1152 | 0 | 0 | 0 | 1632 | 363 | 0 | 363 | 3940 |
| *** BREAK *** | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 11:00 AM | 121 | 272 | 0 | 0 | 0 | 393 | 63 | 0 | 63 | 95 | 253 | 0 | 0 | 0 | 348 | 124 | 0 | 124 | 928 |
| 11:15 AM | 107 | 345 | 0 | 0 | 0 | 452 | 55 | 0 | 55 | 118 | 281 | 0 | 0 | 0 | 399 | 103 | 0 | 103 | 1009 |
| 11:30 AM | 127 | 323 | 0 | 0 | 0 | 450 | 52 | 1 | 52 | 131 | 326 | 0 | 0 | 0 | 457 | 130 | 0 | 130 | 1089 |
| 11:45 AM | 157 | 411 | 0 | 0 | 0 | 568 | 70 | 0 | 70 | 131 | 312 | 0 | 0 | 0 | 443 | 132 | 0 | 132 | 1213 |
| Hourly Total | 512 | 1351 | 0 | 0 | 0 | 1863 | 240 | 1 | 240 | 475 | 1172 | 0 | 0 | 0 | 1647 | 489 | 0 | 489 | 4239 |
| 12:00 PM | 109 | 354 | 0 | 0 | 0 | 463 | 58 | 2 | 58 | 131 | 319 | 0 | 0 | 0 | 450 | 165 | 1 | 165 | 1136 |
| 12:15 PM | 127 | 395 | 0 | 0 | 0 | 522 | 67 | 0 | 67 | 152 | 334 | 0 | 0 | 0 | 486 | 179 | 0 | 179 | 1254 |
| 12:30 PM | 120 | 371 | 0 | 0 | 0 | 491 | 66 | 0 | 66 | 165 | 325 | 0 | 0 | 0 | 490 | 172 | 0 | 172 | 1219 |
| 12:45 PM | 139 | 383 | 0 | 0 | 0 | 522 | 57 | 0 | 57 | 149 | 356 | 0 | 0 | 0 | 505 | 142 | 0 | 142 | 1226 |
| Hourly Total | 495 | 1503 | 0 | 0 | 0 | 1998 | 248 | 2 | 248 | 597 | 1334 | 0 | 0 | 0 | 1931 | 658 | 1 | 658 | 4835 |
| 1:00 PM | 114 | 353 | 0 | 0 | 0 | 467 | 52 | 0 | 52 | 131 | 355 | 0 | 0 | 0 | 486 | 146 | 0 | 146 | 1151 |
| 1:15 PM | 113 | 354 | 0 | 0 | 0 | 467 | 57 | 1 | 57 | 154 | 366 | 0 | 0 | 0 | 520 | 168 | 0 | 168 | 1212 |
| 1:30 PM | 122 | 397 | 0 | 0 | 0 | 519 | 55 | 0 | 55 | 152 | 362 | 0 | 0 | 0 | 514 | 124 | 0 | 124 | 1212 |
| 1:45 PM | 122 | 337 | 0 | 0 | 0 | 459 | 69 | 1 | 69 | 162 | 372 | 0 | 0 | 0 | 534 | 144 | 0 | 144 | 1206 |
| Hourly Total | 471 | 1441 | 0 | 0 | 0 | 1912 | 233 | 2 | 233 | 599 | 1455 | 0 | 0 | 0 | 2054 | 582 | 0 | 582 | 4781 |
| Grand Total | 2890 | 7787 | 0 | 0 | 0 | 10677 | 1678 | 9 | 1678 | 3082 | 7471 | 0 | 0 | 0 | 10553 | 2891 | 3 | 2891 | 25799 |
| Approach % | 27.1 | 72.9 | 0.0 | 0.0 | - | - | 100.0 | - | - | 29.2 | 70.8 | 0.0 | 0.0 | - | - | 100.0 | - | - | - |
| Total % | 11.2 | 30.2 | 0.0 | 0.0 | - | 41.4 | 6.5 | - | 6.5 | 11.9 | 29.0 | 0.0 | 0.0 | - | 40.9 | 11.2 | - | 11.2 | - |
| Motorcycles | 0 | 0 | 0 | 0 | - | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | - | 0 | 0 |
| % Motorcycles | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | 0.0 |
| Cars & Light Goods | 2835 | 7731 | 0 | 0 | - | 10566 | 1649 | - | 1649 | 3057 | 7408 | 0 | 0 | - | 10465 | 2879 | - | 2879 | 25559 |
| % Cars & Light Goods | 98.1 | 99.3 | - | - | - | 99.0 | 98.3 | - | 98.3 | 99.2 | 99.2 | - | - | - | 99.2 | 99.6 | - | 99.6 | 99.1 |
| Other Vehicles | 55 | 56 | 0 | 0 | - | 111 | 29 | - | 29 | 25 | 63 | 0 | 0 | - | 88 | 12 | - | 12 | 240 |
| % Other Vehicles | 1.9 | 0.7 | - | - | - | 1.0 | 1.7 | - | 1.7 | 0.8 | 0.8 | - | - | - | 0.8 | 0.4 | - | 0.4 | 0.9 |
| Bicycles on Crosswalk | - | - | - | - | 0 | - | - | 0 | - | - | - | - | - | 0 | - | - | 0 | - | - |
| % Bicycles on Crosswalk | - | - | - | - | - | - | - | 0.0 | - | - | - | - | - | - | - | - | 0.0 | - | - |
| Pedestrians | - | - | - | - | 0 | - | - | 9 | - | - | - | - | - | 0 | - | - | 3 | - | - |
| % Pedestrians | - | - | - | - | - | - | - | 100.0 | - | - | - | - | - | - | - | - | 100.0 | - | - |


Amherst, NY
January 23 & 25, 2025

Location: 43.002693, -78.822384

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 EB Off Ramp
Site Code: 11991-2
Start Date: 01/23/2025
Page No: 2




Turning Movement Data Plot

Amherst, NY
January 23 & 25, 2025

Location: 43.002693, -78.822384

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 EB Off Ramp
Site Code: 11991-2
Start Date: 01/23/2025


# Turning Movement Peak Hour Data (4:15 PM)

| Start Time | I 290 EB Off-Ramp/NB Niagara Falls Blvd | | | | | | NB Niagara Falls Blvd/I 290 EB On-Ramp | | | I 290 EB Off-Ramp/SB Niagara Falls Blvd | | | | | | SB Niagara Falls Blvd/I 290 EB On-Ramp | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Southbound | | | | | | Westbound | | | Northbound | | | | | | Eastbound | | | |
| | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Peds | App. Total | Int. Total |
| 4:15 PM | 125 | 337 | 0 | 0 | 0 | 462 | 70 | 1 | 70 | 130 | 307 | 0 | 0 | 0 | 437 | 117 | 0 | 117 | 1086 |
| 4:30 PM | 129 | 271 | 0 | 0 | 0 | 400 | 86 | 0 | 86 | 107 | 293 | 0 | 0 | 0 | 400 | 87 | 0 | 87 | 973 |
| 4:45 PM | 120 | 329 | 0 | 0 | 0 | 449 | 93 | 0 | 93 | 107 | 271 | 0 | 0 | 0 | 378 | 124 | 0 | 124 | 1044 |
| 5:00 PM | 127 | 321 | 0 | 0 | 0 | 448 | 108 | 0 | 108 | 127 | 335 | 0 | 0 | 0 | 462 | 113 | 0 | 113 | 1131 |
| Total | 501 | 1258 | 0 | 0 | 0 | 1759 | 357 | 1 | 357 | 471 | 1206 | 0 | 0 | 0 | 1677 | 441 | 0 | 441 | 4234 |
| Approach % | 28.5 | 71.5 | 0.0 | 0.0 | - | - | 100.0 | - | - | 28.1 | 71.9 | 0.0 | 0.0 | - | - | 100.0 | - | - | - |
| Total % | 11.8 | 29.7 | 0.0 | 0.0 | - | 41.5 | 8.4 | - | 8.4 | 11.1 | 28.5 | 0.0 | 0.0 | - | 39.6 | 10.4 | - | 10.4 | - |
| PHF | 0.971 | 0.933 | 0.000 | 0.000 | - | 0.952 | 0.826 | - | 0.826 | 0.906 | 0.900 | 0.000 | 0.000 | - | 0.907 | 0.889 | - | 0.889 | 0.936 |
| Motorcycles | 0 | 0 | 0 | 0 | - | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | - | 0 | 0 |
| % Motorcycles | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | 0.0 |
| Cars & Light Goods | 488 | 1247 | 0 | 0 | - | 1735 | 350 | - | 350 | 469 | 1195 | 0 | 0 | - | 1664 | 439 | - | 439 | 4188 |
| % Cars & Light Goods | 97.4 | 99.1 | - | - | - | 98.6 | 98.0 | - | 98.0 | 99.6 | 99.1 | - | - | - | 99.2 | 99.5 | - | 99.5 | 98.9 |
| Other Vehicles | 13 | 11 | 0 | 0 | - | 24 | 7 | - | 7 | 2 | 11 | 0 | 0 | - | 13 | 2 | - | 2 | 46 |
| % Other Vehicles | 2.6 | 0.9 | - | - | - | 1.4 | 2.0 | - | 2.0 | 0.4 | 0.9 | - | - | - | 0.8 | 0.5 | - | 0.5 | 1.1 |
| Bicycles on Crosswalk | - | - | - | - | 0 | - | - | 0 | - | - | - | - | - | 0 | - | - | 0 | - | - |
| % Bicycles on Crosswalk | - | - | - | - | - | - | - | 0.0 | - | - | - | - | - | - | - | - | - | - | - |
| Pedestrians | - | - | - | - | 0 | - | - | 1 | - | - | - | - | - | 0 | - | - | 0 | - | - |
| % Pedestrians | - | - | - | - | - | - | - | 100.0 | - | - | - | - | - | - | - | - | - | - | - |


Amherst, NY
January 23 & 25, 2025

Location: 43.002693, -78.822384

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 EB Off Ramp
Site Code: 11991-2
Start Date: 01/23/2025
Page No: 4




Turning Movement Peak Hour Data Plot (4:15 PM)

Amherst, NY
January 23 & 25, 2025

Location: 43.002693, -78.822384

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 EB Off Ramp
Site Code: 11991-2
Start Date: 01/23/2025


# Turning Movement Peak Hour Data (12:15 PM)

| Start Time | I 290 EB Off-Ramp/NB Niagara Falls Blvd | | | | | | NB Niagara Falls Blvd/I 290 EB On-Ramp | | | I 290 EB Off-Ramp/SB Niagara Falls Blvd | | | | | | SB Niagara Falls Blvd/I 290 EB On-Ramp | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Southbound | | | | | | Westbound | | | Northbound | | | | | | Eastbound | | | |
| | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Peds | App. Total | Int. Total |
| 12:15 PM | 127 | 395 | 0 | 0 | 0 | 522 | 67 | 0 | 67 | 152 | 334 | 0 | 0 | 0 | 486 | 179 | 0 | 179 | 1254 |
| 12:30 PM | 120 | 371 | 0 | 0 | 0 | 491 | 66 | 0 | 66 | 165 | 325 | 0 | 0 | 0 | 490 | 172 | 0 | 172 | 1219 |
| 12:45 PM | 139 | 383 | 0 | 0 | 0 | 522 | 57 | 0 | 57 | 149 | 356 | 0 | 0 | 0 | 505 | 142 | 0 | 142 | 1226 |
| 1:00 PM | 114 | 353 | 0 | 0 | 0 | 467 | 52 | 0 | 52 | 131 | 355 | 0 | 0 | 0 | 486 | 146 | 0 | 146 | 1151 |
| Total | 500 | 1502 | 0 | 0 | 0 | 2002 | 242 | 0 | 242 | 597 | 1370 | 0 | 0 | 0 | 1967 | 639 | 0 | 639 | 4850 |
| Approach % | 25.0 | 75.0 | 0.0 | 0.0 | - | - | 100.0 | - | - | 30.4 | 69.6 | 0.0 | 0.0 | - | - | 100.0 | - | - | - |
| Total % | 10.3 | 31.0 | 0.0 | 0.0 | - | 41.3 | 5.0 | - | 5.0 | 12.3 | 28.2 | 0.0 | 0.0 | - | 40.6 | 13.2 | - | 13.2 | - |
| PHF | 0.899 | 0.951 | 0.000 | 0.000 | - | 0.959 | 0.903 | - | 0.903 | 0.905 | 0.962 | 0.000 | 0.000 | - | 0.974 | 0.892 | - | 0.892 | 0.967 |
| Motorcycles | 0 | 0 | 0 | 0 | - | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | - | 0 | 0 |
| % Motorcycles | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | 0.0 |
| Cars & Light Goods | 497 | 1496 | 0 | 0 | - | 1993 | 238 | - | 238 | 594 | 1365 | 0 | 0 | - | 1959 | 637 | - | 637 | 4827 |
| % Cars & Light Goods | 99.4 | 99.6 | - | - | - | 99.6 | 98.3 | - | 98.3 | 99.5 | 99.6 | - | - | - | 99.6 | 99.7 | - | 99.7 | 99.5 |
| Other Vehicles | 3 | 6 | 0 | 0 | - | 9 | 4 | - | 4 | 3 | 5 | 0 | 0 | - | 8 | 2 | - | 2 | 23 |
| % Other Vehicles | 0.6 | 0.4 | - | - | - | 0.4 | 1.7 | - | 1.7 | 0.5 | 0.4 | - | - | - | 0.4 | 0.3 | - | 0.3 | 0.5 |
| Bicycles on Crosswalk | - | - | - | - | 0 | - | - | 0 | - | - | - | - | - | 0 | - | - | 0 | - | - |
| % Bicycles on Crosswalk | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Pedestrians | - | - | - | - | 0 | - | - | 0 | - | - | - | - | - | 0 | - | - | 0 | - | - |
| % Pedestrians | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |


Amherst, NY
January 23 & 25, 2025

Location: 43.002693, -78.822384

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 EB Off Ramp
Site Code: 11991-2
Start Date: 01/23/2025
Page No: 6




Turning Movement Peak Hour Data Plot (12:15 PM)

Amherst, NY
January 23 & 25, 2025

Location: 43.005303, -78.822316

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 WB Off Ramp
Site Code: 11991-1
Start Date: 01/23/2025
Page No: 1

# Turning Movement Data

| Start Time | Niagara Falls Blvd Southbound | | | | | I 290 WB On-Ramp Westbound | | | | | | Northbound Approach Northbound | | | | | | I 290 WB Off-Ramp Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Int. Total |
| 3:00 PM | 363 | 0 | 0 | 0 | 363 | 159 | 1 | 65 | 0 | 0 | 225 | 81 | 259 | 0 | 0 | 0 | 340 | 0 | 0 | 1 | 0 | 0 | 1 | 929 |
| 3:15 PM | 326 | 0 | 0 | 0 | 326 | 175 | 2 | 93 | 0 | 1 | 270 | 80 | 289 | 0 | 0 | 0 | 369 | 2 | 0 | 2 | 0 | 0 | 4 | 969 |
| 3:30 PM | 370 | 0 | 0 | 0 | 370 | 167 | 3 | 110 | 0 | 1 | 280 | 91 | 268 | 0 | 0 | 0 | 359 | 1 | 0 | 2 | 0 | 0 | 3 | 1012 |
| 3:45 PM | 346 | 0 | 0 | 0 | 346 | 148 | 1 | 134 | 0 | 1 | 283 | 77 | 311 | 0 | 0 | 0 | 388 | 1 | 0 | 2 | 0 | 0 | 3 | 1020 |
| Hourly Total | 1405 | 0 | 0 | 0 | 1405 | 649 | 7 | 402 | 0 | 3 | 1058 | 329 | 1127 | 0 | 0 | 0 | 1456 | 4 | 0 | 7 | 0 | 0 | 11 | 3930 |
| 4:00 PM | 330 | 0 | 0 | 0 | 330 | 148 | 1 | 125 | 0 | 0 | 274 | 99 | 266 | 0 | 0 | 0 | 365 | 0 | 0 | 2 | 0 | 0 | 2 | 971 |
| 4:15 PM | 376 | 0 | 0 | 0 | 376 | 188 | 0 | 134 | 0 | 1 | 322 | 93 | 285 | 0 | 0 | 0 | 378 | 0 | 0 | 0 | 0 | 0 | 0 | 1076 |
| 4:30 PM | 338 | 0 | 0 | 0 | 338 | 154 | 1 | 107 | 0 | 0 | 262 | 98 | 284 | 1 | 0 | 0 | 383 | 1 | 0 | 0 | 0 | 0 | 1 | 984 |
| 4:45 PM | 360 | 0 | 0 | 0 | 360 | 179 | 2 | 128 | 0 | 0 | 309 | 100 | 278 | 1 | 0 | 0 | 379 | 4 | 0 | 1 | 0 | 0 | 5 | 1053 |
| Hourly Total | 1404 | 0 | 0 | 0 | 1404 | 669 | 4 | 494 | 0 | 1 | 1167 | 390 | 1113 | 2 | 0 | 0 | 1505 | 5 | 0 | 3 | 0 | 0 | 8 | 4084 |
| 5:00 PM | 359 | 0 | 0 | 1 | 359 | 169 | 4 | 127 | 0 | 0 | 300 | 102 | 334 | 0 | 0 | 0 | 436 | 3 | 0 | 3 | 0 | 1 | 6 | 1101 |
| 5:15 PM | 321 | 0 | 0 | 0 | 321 | 177 | 4 | 116 | 0 | 1 | 297 | 93 | 300 | 1 | 0 | 0 | 394 | 1 | 0 | 0 | 0 | 0 | 1 | 1013 |
| 5:30 PM | 320 | 0 | 0 | 0 | 320 | 141 | 5 | 99 | 0 | 0 | 245 | 108 | 227 | 0 | 0 | 0 | 335 | 1 | 0 | 1 | 0 | 0 | 2 | 902 |
| 5:45 PM | 306 | 0 | 0 | 0 | 306 | 142 | 8 | 96 | 0 | 1 | 246 | 95 | 215 | 0 | 1 | 0 | 311 | 0 | 0 | 2 | 0 | 0 | 2 | 865 |
| Hourly Total | 1306 | 0 | 0 | 1 | 1306 | 629 | 21 | 438 | 0 | 2 | 1088 | 398 | 1076 | 1 | 1 | 0 | 1476 | 5 | 0 | 6 | 0 | 1 | 11 | 3881 |
| 6:00 PM | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| *** BREAK *** | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Hourly Total | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| 11:00 AM | 324 | 0 | 0 | 0 | 324 | 109 | 0 | 92 | 0 | 0 | 201 | 61 | 252 | 1 | 0 | 0 | 314 | 4 | 0 | 0 | 0 | 0 | 4 | 843 |
| 11:15 AM | 317 | 0 | 0 | 0 | 317 | 119 | 2 | 125 | 0 | 1 | 246 | 62 | 256 | 1 | 0 | 0 | 319 | 1 | 0 | 1 | 0 | 0 | 2 | 884 |
| 11:30 AM | 312 | 0 | 0 | 0 | 312 | 120 | 7 | 104 | 0 | 0 | 231 | 84 | 284 | 0 | 0 | 0 | 368 | 3 | 0 | 0 | 0 | 0 | 3 | 914 |
| 11:45 AM | 345 | 0 | 0 | 0 | 345 | 127 | 8 | 114 | 0 | 3 | 249 | 86 | 281 | 0 | 0 | 0 | 367 | 15 | 0 | 2 | 0 | 0 | 17 | 978 |
| Hourly Total | 1298 | 0 | 0 | 0 | 1298 | 475 | 17 | 435 | 0 | 4 | 927 | 293 | 1073 | 2 | 0 | 0 | 1368 | 23 | 0 | 3 | 0 | 0 | 26 | 3619 |
| 12:00 PM | 404 | 0 | 0 | 0 | 404 | 109 | 0 | 113 | 0 | 0 | 222 | 97 | 292 | 1 | 0 | 0 | 390 | 8 | 0 | 0 | 0 | 0 | 8 | 1024 |
| 12:15 PM | 417 | 0 | 0 | 0 | 417 | 121 | 3 | 126 | 0 | 0 | 250 | 92 | 291 | 0 | 0 | 0 | 383 | 3 | 0 | 2 | 0 | 0 | 5 | 1055 |
| 12:30 PM | 410 | 0 | 0 | 0 | 410 | 137 | 4 | 132 | 0 | 0 | 273 | 106 | 307 | 0 | 0 | 0 | 413 | 5 | 0 | 0 | 0 | 0 | 5 | 1101 |
| 12:45 PM | 440 | 0 | 0 | 0 | 440 | 137 | 6 | 129 | 0 | 0 | 272 | 108 | 304 | 0 | 0 | 0 | 412 | 6 | 0 | 3 | 0 | 0 | 9 | 1133 |
| Hourly Total | 1671 | 0 | 0 | 0 | 1671 | 504 | 13 | 500 | 0 | 0 | 1017 | 403 | 1194 | 1 | 0 | 0 | 1598 | 22 | 0 | 5 | 0 | 0 | 27 | 4313 |
| 1:00 PM | 335 | 0 | 0 | 0 | 335 | 133 | 1 | 137 | 0 | 0 | 271 | 111 | 305 | 0 | 0 | 0 | 416 | 5 | 0 | 1 | 0 | 0 | 6 | 1028 |
| 1:15 PM | 344 | 0 | 0 | 0 | 344 | 131 | 3 | 142 | 0 | 0 | 276 | 104 | 299 | 0 | 0 | 0 | 403 | 4 | 0 | 1 | 0 | 0 | 5 | 1028 |
| 1:30 PM | 336 | 0 | 0 | 0 | 336 | 128 | 4 | 122 | 0 | 0 | 254 | 115 | 285 | 0 | 0 | 0 | 400 | 5 | 0 | 0 | 0 | 0 | 5 | 995 |
| 1:45 PM | 291 | 0 | 0 | 0 | 291 | 124 | 8 | 130 | 0 | 1 | 262 | 109 | 307 | 0 | 0 | 0 | 416 | 8 | 0 | 0 | 0 | 0 | 8 | 977 |
| Hourly Total | 1306 | 0 | 0 | 0 | 1306 | 516 | 16 | 531 | 0 | 1 | 1063 | 439 | 1196 | 0 | 0 | 0 | 1635 | 22 | 0 | 2 | 0 | 0 | 24 | 4028 |
| 2:00 PM | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| Grand Total | 8390 | 0 | 0 | 1 | 8390 | 3444 | 78 | 2801 | 0 | 11 | 6323 | 2252 | 6779 | 6 | 1 | 0 | 9038 | 81 | 0 | 26 | 0 | 1 | 107 | 23858 |
| Approach % | 100.0 | 0.0 | 0.0 | - | - | 54.5 | 1.2 | 44.3 | 0.0 | - | - | 24.9 | 75.0 | 0.1 | 0.0 | - | - | 75.7 | 0.0 | 24.3 | 0.0 | - | - | - |
| Total % | 35.2 | 0.0 | 0.0 | - | 35.2 | 14.4 | 0.3 | 11.7 | 0.0 | - | 26.5 | 9.4 | 28.4 | 0.0 | 0.0 | - | 37.9 | 0.3 | 0.0 | 0.1 | 0.0 | - | 0.4 | - |
| Motorcycles | 1 | 0 | 0 | - | 1 | 1 | 0 | 0 | 0 | - | 1 | 0 | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 2 |
| % Motorcycles | 0.0 | - | - | - | 0.0 | 0.0 | 0.0 | 0.0 | - | - | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | - | 0.0 | 0.0 | - | 0.0 | - | - | 0.0 | 0.0 |
| Cars & Light Goods | 8271 | 0 | 0 | - | 8271 | 3398 | 77 | 2775 | 0 | - | 6250 | 2237 | 6702 | 5 | 1 | - | 8945 | 81 | 0 | 25 | 0 | - | 106 | 23572 |
| % Cars & Light Goods | 98.6 | - | - | - | 98.6 | 98.7 | 98.7 | 99.1 | - | - | 98.8 | 99.3 | 98.9 | 83.3 | 100.0 | - | 99.0 | 100.0 | - | 96.2 | - | - | 99.1 | 98.8 |
| Other Vehicles | 118 | 0 | 0 | - | 118 | 45 | 1 | 26 | 0 | - | 72 | 15 | 77 | 1 | 0 | - | 93 | 0 | 0 | 1 | 0 | - | 1 | 284 |
| % Other Vehicles | 1.4 | - | - | - | 1.4 | 1.3 | 1.3 | 0.9 | - | - | 1.1 | 0.7 | 1.1 | 16.7 | 0.0 | - | 1.0 | 0.0 | - | 3.8 | - | - | 0.9 | 1.2 |
| Bicycles on Crosswalk | - | - | - | 0 | - | - | - | - | - | 1 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - |
| % Bicycles on Crosswalk | - | - | - | 0.0 | - | - | - | - | - | 9.1 | - | - | - | - | - | - | - | - | - | - | - | 0.0 | - | - |
| Pedestrians | - | - | - | 1 | - | - | - | - | - | 10 | - | - | - | - | - | 0 | - | - | - | - | - | 1 | - | - |
| % Pedestrians | - | - | - | 100.0 | - | - | - | - | - | 90.9 | - | - | - | - | - | - | - | - | - | - | - | 100.0 | - | - |


Amherst, NY
January 23 & 25, 2025

Location: 43.005303, -78.822316

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 WB Off Ramp
Site Code: 11991-1
Start Date: 01/23/2025


Turning Movement Data Plot

Amherst, NY
January 23 & 25, 2025

Location: 43.005303, -78.822316

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 WB Off Ramp
Site Code: 11991-1
Start Date: 01/23/2025


# Turning Movement Peak Hour Data (4:15 PM)

| Start Time | Niagara Falls Blvd Southbound | | | | | I 290 WB On-Ramp Westbound | | | | | | Northbound Approach Northbound | | | | | | I 290 WB Off-Ramp Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Int. Total |
| 4:15 PM | 376 | 0 | 0 | 0 | 376 | 188 | 0 | 134 | 0 | 1 | 322 | 93 | 285 | 0 | 0 | 0 | 378 | 0 | 0 | 0 | 0 | 0 | 0 | 1076 |
| 4:30 PM | 338 | 0 | 0 | 0 | 338 | 154 | 1 | 107 | 0 | 0 | 262 | 98 | 284 | 1 | 0 | 0 | 383 | 1 | 0 | 0 | 0 | 0 | 1 | 984 |
| 4:45 PM | 360 | 0 | 0 | 0 | 360 | 179 | 2 | 128 | 0 | 0 | 309 | 100 | 278 | 1 | 0 | 0 | 379 | 4 | 0 | 1 | 0 | 0 | 5 | 1053 |
| 5:00 PM | 359 | 0 | 0 | 1 | 359 | 169 | 4 | 127 | 0 | 0 | 300 | 102 | 334 | 0 | 0 | 0 | 436 | 3 | 0 | 3 | 0 | 1 | 6 | 1101 |
| Total | 1433 | 0 | 0 | 1 | 1433 | 690 | 7 | 496 | 0 | 1 | 1193 | 393 | 1181 | 2 | 0 | 0 | 1576 | 8 | 0 | 4 | 0 | 1 | 12 | 4214 |
| Approach % | 100.0 | 0.0 | 0.0 | - | - | 57.8 | 0.6 | 41.6 | 0.0 | - | - | 24.9 | 74.9 | 0.1 | 0.0 | - | - | 66.7 | 0.0 | 33.3 | 0.0 | - | - | - |
| Total % | 34.0 | 0.0 | 0.0 | - | 34.0 | 16.4 | 0.2 | 11.8 | 0.0 | - | 28.3 | 9.3 | 28.0 | 0.0 | 0.0 | - | 37.4 | 0.2 | 0.0 | 0.1 | 0.0 | - | 0.3 | - |
| PHF | 0.953 | 0.000 | 0.000 | - | 0.953 | 0.918 | 0.438 | 0.925 | 0.000 | - | 0.926 | 0.963 | 0.884 | 0.500 | 0.000 | - | 0.904 | 0.500 | 0.000 | 0.333 | 0.000 | - | 0.500 | 0.957 |
| Motorcycles | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 |
| % Motorcycles | 0.0 | - | - | - | 0.0 | 0.0 | 0.0 | 0.0 | - | - | 0.0 | 0.0 | 0.0 | 0.0 | - | - | 0.0 | 0.0 | - | 0.0 | - | - | 0.0 | 0.0 |
| Cars & Light Goods | 1412 | 0 | 0 | - | 1412 | 686 | 6 | 492 | 0 | - | 1184 | 391 | 1167 | 2 | 0 | - | 1560 | 8 | 0 | 4 | 0 | - | 12 | 4168 |
| % Cars & Light Goods | 98.5 | - | - | - | 98.5 | 99.4 | 85.7 | 99.2 | - | - | 99.2 | 99.5 | 98.8 | 100.0 | - | - | 99.0 | 100.0 | - | 100.0 | - | - | 100.0 | 98.9 |
| Other Vehicles | 21 | 0 | 0 | - | 21 | 4 | 1 | 4 | 0 | - | 9 | 2 | 14 | 0 | 0 | - | 16 | 0 | 0 | 0 | 0 | - | 0 | 46 |
| % Other Vehicles | 1.5 | - | - | - | 1.5 | 0.6 | 14.3 | 0.8 | - | - | 0.8 | 0.5 | 1.2 | 0.0 | - | - | 1.0 | 0.0 | - | 0.0 | - | - | 0.0 | 1.1 |
| Bicycles on Crosswalk | - | - | - | 0 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - |
| % Bicycles on Crosswalk | - | - | - | 0.0 | - | - | - | - | - | 0.0 | - | - | - | - | - | - | - | - | - | - | - | 0.0 | - | - |
| Pedestrians | - | - | - | 1 | - | - | - | - | - | 1 | - | - | - | - | - | 0 | - | - | - | - | - | 1 | - | - |
| % Pedestrians | - | - | - | 100.0 | - | - | - | - | - | 100.0 | - | - | - | - | - | - | - | - | - | - | - | 100.0 | - | - |


Amherst, NY
January 23 & 25, 2025

Location: 43.005303, -78.822316

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 WB Off Ramp
Site Code: 11991-1
Start Date: 01/23/2025


Turning Movement Peak Hour Data Plot (4:15 PM)

Amherst, NY
January 23 & 25, 2025

Location: 43.005303, -78.822316

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 WB Off Ramp
Site Code: 11991-1
Start Date: 01/23/2025


# Turning Movement Peak Hour Data (12:15 PM)

| Start Time | Niagara Falls Blvd Southbound | | | | | I 290 WB On-Ramp Westbound | | | | | | Northbound Approach Northbound | | | | | | I 290 WB Off-Ramp Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Right | Thru | Left | U-Turn | Peds | App. Total | Int. Total |
| 12:15 PM | 417 | 0 | 0 | 0 | 417 | 121 | 3 | 126 | 0 | 0 | 250 | 92 | 291 | 0 | 0 | 0 | 383 | 3 | 0 | 2 | 0 | 0 | 5 | 1055 |
| 12:30 PM | 410 | 0 | 0 | 0 | 410 | 137 | 4 | 132 | 0 | 0 | 273 | 106 | 307 | 0 | 0 | 0 | 413 | 5 | 0 | 0 | 0 | 0 | 5 | 1101 |
| 12:45 PM | 440 | 0 | 0 | 0 | 440 | 137 | 6 | 129 | 0 | 0 | 272 | 108 | 304 | 0 | 0 | 0 | 412 | 6 | 0 | 3 | 0 | 0 | 9 | 1133 |
| 1:00 PM | 335 | 0 | 0 | 0 | 335 | 133 | 1 | 137 | 0 | 0 | 271 | 111 | 305 | 0 | 0 | 0 | 416 | 5 | 0 | 1 | 0 | 0 | 6 | 1028 |
| Total | 1602 | 0 | 0 | 0 | 1602 | 528 | 14 | 524 | 0 | 0 | 1066 | 417 | 1207 | 0 | 0 | 0 | 1624 | 19 | 0 | 6 | 0 | 0 | 25 | 4317 |
| Approach % | 100.0 | 0.0 | 0.0 | - | - | 49.5 | 1.3 | 49.2 | 0.0 | - | - | 25.7 | 74.3 | 0.0 | 0.0 | - | - | 76.0 | 0.0 | 24.0 | 0.0 | - | - | - |
| Total % | 37.1 | 0.0 | 0.0 | - | 37.1 | 12.2 | 0.3 | 12.1 | 0.0 | - | 24.7 | 9.7 | 28.0 | 0.0 | 0.0 | - | 37.6 | 0.4 | 0.0 | 0.1 | 0.0 | - | 0.6 | - |
| PHF | 0.910 | 0.000 | 0.000 | - | 0.910 | 0.964 | 0.583 | 0.956 | 0.000 | - | 0.976 | 0.939 | 0.983 | 0.000 | 0.000 | - | 0.976 | 0.792 | 0.000 | 0.500 | 0.000 | - | 0.694 | 0.953 |
| Motorcycles | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 | 0 | 0 | 0 | - | 0 | 0 |
| % Motorcycles | 0.0 | - | - | - | 0.0 | 0.0 | 0.0 | 0.0 | - | - | 0.0 | 0.0 | 0.0 | - | - | - | 0.0 | 0.0 | - | 0.0 | - | - | 0.0 | 0.0 |
| Cars & Light Goods | 1595 | 0 | 0 | - | 1595 | 518 | 14 | 522 | 0 | - | 1054 | 415 | 1201 | 0 | 0 | - | 1616 | 19 | 0 | 6 | 0 | - | 25 | 4290 |
| % Cars & Light Goods | 99.6 | - | - | - | 99.6 | 98.1 | 100.0 | 99.6 | - | - | 98.9 | 99.5 | 99.5 | - | - | - | 99.5 | 100.0 | - | 100.0 | - | - | 100.0 | 99.4 |
| Other Vehicles | 7 | 0 | 0 | - | 7 | 10 | 0 | 2 | 0 | - | 12 | 2 | 6 | 0 | 0 | - | 8 | 0 | 0 | 0 | 0 | - | 0 | 27 |
| % Other Vehicles | 0.4 | - | - | - | 0.4 | 1.9 | 0.0 | 0.4 | - | - | 1.1 | 0.5 | 0.5 | - | - | - | 0.5 | 0.0 | - | 0.0 | - | - | 0.0 | 0.6 |
| Bicycles on Crosswalk | - | - | - | 0 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - |
| % Bicycles on Crosswalk | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Pedestrians | - | - | - | 0 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - | - | - | - | 0 | - | - |
| % Pedestrians | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |


Amherst, NY
January 23 & 25, 2025

Location: 43.005303, -78.822316

Tri-State Traffic Data: New York Division
184 Baker Rd

Coatesville , Pennsylvania, United States 19320
610-517-2338

Count Name: Niagara Falls Blvd @ I-290 WB Off Ramp
Site Code: 11991-1
Start Date: 01/23/2025


Turning Movement Peak Hour Data Plot (12:15 PM)


Type of peak hour being reported: Intersection Peak


Method for determining peak hour: Total Entering Volume

**LOCATION:** Bowmart Pkwy -- Meyer Rd
**CITY/STATE:** Amherst, NY


**QC JOB #:** 16077706
**DATE:** Sat, Feb 4 2023

**Peak-Hour: 12:00 PM -- 1:00 PM**
**Peak 15-Min: 12:15 PM -- 12:30 PM**









Quality Counts
DATA THAT DRIVES COMMUNITIES

















| 15-Min Count Period Beginning At | Bowmart Pkwy (Northbound) | | | | Bowmart Pkwy (Southbound) | | | | Meyer Rd (Eastbound) | | | | Meyer Rd (Westbound) | | | | Total | Hourly Totals |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | | |
| 12:00 PM | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 0 | 1 | 1 | 0 | 0 | 64 | |
| 12:15 PM | 33 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 33 | 0 | 1 | 1 | 0 | 0 | 69 | |
| 12:30 PM | 34 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 32 | 0 | 0 | 0 | 0 | 0 | 68 | |
| 12:45 PM | 36 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 29 | 0 | 0 | 0 | 0 | 0 | 68 | 269 |
| 1:00 PM | 35 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 26 | 1 | 1 | 0 | 0 | 0 | 63 | 268 |
| 1:15 PM | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 26 | 0 | 1 | 0 | 0 | 0 | 62 | 261 |
| 1:30 PM | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 41 | 0 | 0 | 2 | 0 | 0 | 75 | 268 |
| 1:45 PM | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 25 | 0 | 2 | 2 | 0 | 0 | 62 | 262 |
| 2:00 PM | 27 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 21 | 0 | 0 | 3 | 0 | 0 | 53 | 252 |
| 2:15 PM | 26 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 1 | 0 | 0 | 0 | 0 | 56 | 246 |
| 2:30 PM | 34 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 28 | 0 | 0 | 0 | 0 | 0 | 63 | 234 |
| 2:45 PM | 36 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 30 | 0 | 2 | 0 | 0 | 0 | 70 | 242 |

| Peak 15-Min Flowrates | Northbound | | | | Southbound | | | | Eastbound | | | | Westbound | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | |
| All Vehicles | 132 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 132 | 0 | 4 | 4 | 0 | 0 | 276 |
| Heavy Trucks | 4 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 4 | | 0 | 0 | 0 | | 8 |
| Buses | | | | | | | | | | | | | | | | | |
| Pedestrians | | 0 | | | | 0 | | | | 0 | | | | 0 | | | 0 |
| Bicycles | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Scooters | | | | | | | | | | | | | | | | | |

*Comments:*


Report generated on 2/10/2023 10:53 AM


SOURCE: Quality Counts, LLC (http://www.qualitycounts.net) 1-877-580-2212

Type of peak hour being reported: Intersection Peak | Method for determining peak hour: Total Entering Volume


**LOCATION:** Bowmart Pkwy -- Meyer Rd | **QC JOB #:** 16077705
**CITY/STATE:** Amherst, NY | **DATE:** Thu, Feb 2 2023

**Peak-Hour: 4:30 PM -- 5:30 PM**
**Peak 15-Min: 4:45 PM -- 5:00 PM**









Quality Counts
DATA THAT DRIVES COMMUNITIES

















| 15-Min Count Period Beginning At | Bowmart Pkwy (Northbound) | | | | Bowmart Pkwy (Southbound) | | | | Meyer Rd (Eastbound) | | | | Meyer Rd (Westbound) | | | | Total | Hourly Totals |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | | |
| 3:00 PM | 21 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 26 | 0 | 0 | 1 | 0 | 0 | 48 | |
| 3:15 PM | 27 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 24 | 0 | 4 | 1 | 0 | 0 | 60 | |
| 3:30 PM | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 35 | 0 | 0 | 1 | 0 | 0 | 74 | |
| 3:45 PM | 57 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 32 | 0 | 1 | 1 | 0 | 0 | 91 | 273 |
| 4:00 PM | 29 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 30 | 0 | 0 | 2 | 0 | 0 | 65 | 290 |
| 4:15 PM | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 39 | 0 | 1 | 1 | 0 | 0 | 76 | 306 |
| 4:30 PM | 40 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 33 | 0 | 2 | 1 | 0 | 0 | 78 | 310 |
| 4:45 PM | 39 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 40 | 0 | 2 | 1 | 0 | 0 | 85 | 304 |
| 5:00 PM | 32 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 51 | 0 | 0 | 0 | 0 | 0 | 84 | 323 |
| 5:15 PM | 42 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 39 | 0 | 2 | 0 | 0 | 0 | 84 | 331 |
| 5:30 PM | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 26 | 0 | 0 | 0 | 0 | 0 | 59 | 312 |
| 5:45 PM | 37 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 36 | 0 | 0 | 1 | 0 | 0 | 75 | 302 |

| Peak 15-Min Flowrates | Northbound | | | | Southbound | | | | Eastbound | | | | Westbound | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | |
| All Vehicles | 156 | 0 | 4 | 4 | 0 | 0 | 0 | 0 | 0 | 4 | 160 | 0 | 8 | 4 | 0 | 0 | 340 |
| Heavy Trucks | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Buses | | | | | | | | | | | | | | | | | |
| Pedestrians | | 0 | | | | 0 | | | | 0 | | | | 0 | | | 0 |
| Bicycles | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 4 | | 0 | 0 | 0 | | 4 |
| Scooters | | | | | | | | | | | | | | | | | |


*Comments:*


Report generated on 2/10/2023 10:53 AM | SOURCE: Quality Counts, LLC (http://www.qualitycounts.net) 1-877-580-2212

Type of peak hour being reported: Intersection Peak | Method for determining peak hour: Total Entering Volume


**LOCATION:** N Bailey Ave -- Romney Dr | **QC JOB #:** 16077704
**CITY/STATE:** Amherst, NY | **DATE:** Sat, Feb 4 2023

**Peak-Hour: 2:00 PM -- 3:00 PM**
**Peak 15-Min: 2:45 PM -- 3:00 PM**









Quality Counts
DATA THAT DRIVES COMMUNITIES












| 15-Min Count Period Beginning At | N Bailey Ave (Northbound) | | | | N Bailey Ave (Southbound) | | | | Romney Dr (Eastbound) | | | | Romney Dr (Westbound) | | | | Total | Hourly Totals |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | | |
| 12:00 PM | 44 | 142 | 0 | 0 | 0 | 155 | 3 | 0 | 2 | 0 | 58 | 0 | 0 | 0 | 0 | 0 | 404 | |
| 12:15 PM | 49 | 142 | 0 | 0 | 0 | 141 | 4 | 0 | 3 | 0 | 47 | 0 | 0 | 0 | 0 | 0 | 386 | |
| 12:30 PM | 44 | 157 | 0 | 0 | 0 | 139 | 9 | 0 | 3 | 0 | 71 | 0 | 0 | 0 | 0 | 0 | 423 | |
| 12:45 PM | 42 | 164 | 0 | 0 | 0 | 135 | 8 | 0 | 2 | 0 | 73 | 0 | 0 | 0 | 0 | 0 | 424 | 1637 |
| 1:00 PM | 50 | 154 | 0 | 0 | 0 | 150 | 9 | 0 | 6 | 0 | 56 | 0 | 0 | 0 | 0 | 0 | 425 | 1658 |
| 1:15 PM | 49 | 166 | 0 | 0 | 0 | 152 | 5 | 0 | 5 | 0 | 76 | 0 | 0 | 0 | 0 | 0 | 453 | 1725 |
| 1:30 PM | 47 | 164 | 0 | 0 | 0 | 164 | 3 | 0 | 4 | 0 | 71 | 0 | 0 | 0 | 0 | 0 | 453 | 1755 |
| 1:45 PM | 51 | 156 | 0 | 0 | 0 | 131 | 7 | 0 | 8 | 0 | 56 | 0 | 0 | 0 | 0 | 0 | 409 | 1740 |
| 2:00 PM | 50 | 155 | 0 | 0 | 0 | 183 | 6 | 0 | 7 | 0 | 66 | 0 | 0 | 0 | 0 | 0 | 467 | 1782 |
| 2:15 PM | 44 | 164 | 0 | 0 | 0 | 178 | 7 | 0 | 9 | 0 | 60 | 0 | 0 | 0 | 0 | 0 | 462 | 1791 |
| 2:30 PM | 43 | 158 | 0 | 0 | 0 | 180 | 6 | 0 | 18 | 0 | 58 | 0 | 0 | 0 | 0 | 0 | 463 | 1801 |
| 2:45 PM | 49 | 161 | 0 | 0 | 0 | 178 | 5 | 0 | 18 | 0 | 75 | 0 | 0 | 0 | 0 | 0 | 486 | 1878 |

| Peak 15-Min Flowrates | Northbound | | | | Southbound | | | | Eastbound | | | | Westbound | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | |
| All Vehicles | 196 | 644 | 0 | 0 | 0 | 712 | 20 | 0 | 72 | 0 | 300 | 0 | 0 | 0 | 0 | 0 | 1944 |
| Heavy Trucks | 4 | 4 | 0 | | 0 | 12 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 20 |
| Buses | | | | | | | | | | | | | | | | | |
| Pedestrians | | 0 | | | | 0 | | | | 0 | | | | 0 | | | 0 |
| Bicycles | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Scooters | | | | | | | | | | | | | | | | | |

*Comments:*

Report generated on 2/10/2023 10:53 AM | SOURCE: Quality Counts, LLC (http://www.qualitycounts.net) 1-877-580-2212


Type of peak hour being reported: Intersection Peak


Method for determining peak hour: Total Entering Volume


**LOCATION:** N Bailey Ave -- Romney Dr
**CITY/STATE:** Amherst, NY

**QC JOB #:** 16077703
**DATE:** Thu, Feb 2 2023


**Peak-Hour: 4:30 PM -- 5:30 PM**
**Peak 15-Min: 5:00 PM -- 5:15 PM**













| 15-Min Count Period Beginning At | N Bailey Ave (Northbound) | | | | N Bailey Ave (Southbound) | | | | Romney Dr (Eastbound) | | | | Romney Dr (Westbound) | | | | Total | Hourly Totals |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | | |
| 3:00 PM | 22 | 127 | 0 | 0 | 0 | 123 | 2 | 0 | 3 | 0 | 54 | 0 | 0 | 0 | 0 | 0 | 331 | |
| 3:15 PM | 25 | 129 | 0 | 1 | 0 | 115 | 3 | 0 | 1 | 0 | 52 | 0 | 0 | 0 | 0 | 0 | 326 | |
| 3:30 PM | 38 | 127 | 0 | 0 | 0 | 123 | 5 | 0 | 3 | 0 | 47 | 0 | 0 | 0 | 0 | 0 | 343 | |
| 3:45 PM | 38 | 171 | 0 | 0 | 0 | 135 | 3 | 0 | 4 | 0 | 51 | 0 | 0 | 0 | 0 | 0 | 402 | 1402 |
| 4:00 PM | 32 | 176 | 0 | 0 | 0 | 136 | 2 | 0 | 6 | 0 | 55 | 0 | 0 | 0 | 0 | 0 | 407 | 1478 |
| 4:15 PM | 32 | 148 | 0 | 0 | 0 | 127 | 2 | 0 | 5 | 0 | 61 | 0 | 0 | 0 | 0 | 0 | 375 | 1527 |
| 4:30 PM | 38 | 172 | 0 | 0 | 0 | 149 | 1 | 0 | 4 | 0 | 47 | 0 | 0 | 0 | 0 | 0 | 411 | 1595 |
| 4:45 PM | 40 | 160 | 0 | 0 | 0 | 137 | 2 | 0 | 5 | 0 | 61 | 0 | 0 | 0 | 0 | 0 | 405 | 1598 |
| 5:00 PM | 34 | 183 | 0 | 0 | 0 | 140 | 3 | 0 | 5 | 0 | 51 | 0 | 0 | 0 | 0 | 0 | 416 | 1607 |
| 5:15 PM | 35 | 179 | 0 | 0 | 0 | 135 | 5 | 0 | 6 | 0 | 42 | 0 | 0 | 0 | 0 | 0 | 402 | 1634 |
| 5:30 PM | 33 | 166 | 0 | 0 | 0 | 141 | 2 | 0 | 1 | 0 | 58 | 0 | 0 | 0 | 0 | 0 | 401 | 1624 |
| 5:45 PM | 27 | 154 | 0 | 0 | 0 | 137 | 3 | 0 | 4 | 0 | 53 | 0 | 0 | 0 | 0 | 0 | 378 | 1597 |

| Peak 15-Min Flowrates | Northbound | | | | Southbound | | | | Eastbound | | | | Westbound | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | |
| All Vehicles | 136 | 732 | 0 | 0 | 0 | 560 | 12 | 0 | 20 | 0 | 204 | 0 | 0 | 0 | 0 | 0 | 1664 |
| Heavy Trucks | 4 | 8 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 12 |
| Buses | | | | | | | | | | | | | | | | | |
| Pedestrians | | 0 | | | | 12 | | | | 0 | | | | 12 | | | 24 |
| Bicycles | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Scooters | | | | | | | | | | | | | | | | | |

*Comments:*

Report generated on 2/10/2023 10:53 AM

SOURCE: Quality Counts, LLC (http://www.qualitycounts.net) 1-877-580-2212


Type of peak hour being reported: Intersection Peak


Method for determining peak hour: Total Entering Volume


**LOCATION:** Niagara Falls Blvd -- Koenig Rd/Ridge Lea Rd
**CITY/STATE:** Amherst, NY


**QC JOB #:** 16077702
**DATE:** Sat, Feb 4 2023


**Peak-Hour: 1:15 PM -- 2:15 PM**
**Peak 15-Min: 2:00 PM -- 2:15 PM**

















| 15-Min Count Period Beginning At | Niagara Falls Blvd (Northbound) | | | | Niagara Falls Blvd (Southbound) | | | | Koenig Rd/Ridge Lea Rd (Eastbound) | | | | Koenig Rd/Ridge Lea Rd (Westbound) | | | | Total | Hourly Totals |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | | |
| 12:00 PM | 7 | 220 | 6 | 2 | 162 | 295 | 17 | 1 | 34 | 21 | 2 | 0 | 9 | 13 | 156 | 0 | 945 | |
| 12:15 PM | 8 | 268 | 4 | 2 | 162 | 328 | 14 | 0 | 18 | 18 | 5 | 0 | 5 | 20 | 143 | 0 | 995 | |
| 12:30 PM | 8 | 301 | 6 | 0 | 159 | 320 | 13 | 1 | 28 | 23 | 3 | 0 | 6 | 14 | 171 | 0 | 1053 | |
| 12:45 PM | 8 | 251 | 6 | 2 | 175 | 303 | 17 | 0 | 32 | 14 | 6 | 0 | 11 | 17 | 172 | 0 | 1014 | 4007 |
| 1:00 PM | 12 | 268 | 7 | 0 | 155 | 283 | 11 | 0 | 25 | 19 | 9 | 0 | 7 | 15 | 191 | 0 | 1002 | 4064 |
| 1:15 PM | 5 | 296 | 3 | 2 | 167 | 344 | 14 | 0 | 21 | 12 | 6 | 0 | 10 | 10 | 155 | 0 | 1045 | 4114 |
| 1:30 PM | 7 | 280 | 3 | 0 | 156 | 323 | 17 | 0 | 22 | 20 | 6 | 0 | 3 | 14 | 192 | 0 | 1043 | 4104 |
| 1:45 PM | 12 | 265 | 2 | 0 | 163 | 255 | 13 | 0 | 40 | 29 | 5 | 0 | 9 | 15 | 193 | 0 | 1001 | 4091 |
| 2:00 PM | 15 | 301 | 4 | 0 | 165 | 323 | 14 | 0 | 29 | 19 | 3 | 0 | 7 | 13 | 186 | 0 | 1079 | 4168 |
| 2:15 PM | 9 | 298 | 4 | 1 | 167 | 286 | 14 | 1 | 25 | 14 | 2 | 0 | 6 | 21 | 159 | 0 | 1007 | 4130 |
| 2:30 PM | 4 | 274 | 2 | 1 | 158 | 272 | 19 | 1 | 32 | 20 | 8 | 0 | 15 | 13 | 224 | 0 | 1043 | 4130 |
| 2:45 PM | 12 | 271 | 8 | 2 | 173 | 260 | 14 | 0 | 38 | 16 | 6 | 0 | 9 | 15 | 207 | 0 | 1031 | 4160 |

| Peak 15-Min Flowrates | Northbound | | | | Southbound | | | | Eastbound | | | | Westbound | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | |
| All Vehicles | 60 | 1204 | 16 | 0 | 660 | 1292 | 56 | 0 | 116 | 76 | 12 | 0 | 28 | 52 | 744 | 0 | 4316 |
| Heavy Trucks | 0 | 8 | 0 | | 0 | 8 | 0 | | 4 | 0 | 0 | | 0 | 0 | 0 | | 20 |
| Buses | | | | | | | | | | | | | | | | | |
| Pedestrians | | 0 | | | | 0 | | | | 0 | | | | 4 | | | 4 |
| Bicycles | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Scooters | | | | | | | | | | | | | | | | | |

*Comments:*

Report generated on 2/10/2023 10:53 AM

SOURCE: Quality Counts, LLC (http://www.qualitycounts.net) 1-877-580-2212


Type of peak hour being reported: Intersection Peak


Method for determining peak hour: Total Entering Volume

**LOCATION:** Niagara Falls Blvd -- Koenig Rd/Ridge Lea Rd
**CITY/STATE:** Amherst, NY


**QC JOB #:** 16077701
**DATE:** Thu, Feb 2 2023


**Peak-Hour: 4:45 PM -- 5:45 PM**
**Peak 15-Min: 5:30 PM -- 5:45 PM**










Quality Counts
DATA THAT DRIVES COMMUNITIES









| 15-Min Count Period Beginning At | Niagara Falls Blvd (Northbound) | | | | Niagara Falls Blvd (Southbound) | | | | Koenig Rd/Ridge Lea Rd (Eastbound) | | | | Koenig Rd/Ridge Lea Rd (Westbound) | | | | Total | Hourly Totals |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | | |
| 3:00 PM | 6 | 249 | 3 | 1 | 102 | 220 | 22 | 0 | 45 | 10 | 4 | 0 | 6 | 6 | 137 | 0 | 811 | |
| 3:15 PM | 7 | 214 | 6 | 0 | 125 | 216 | 19 | 0 | 33 | 15 | 3 | 0 | 5 | 15 | 123 | 0 | 781 | |
| 3:30 PM | 8 | 228 | 2 | 0 | 126 | 221 | 15 | 0 | 38 | 16 | 2 | 0 | 10 | 13 | 134 | 0 | 813 | |
| 3:45 PM | 8 | 263 | 2 | 0 | 157 | 288 | 26 | 1 | 28 | 14 | 6 | 0 | 3 | 14 | 165 | 0 | 975 | 3380 |
| 4:00 PM | 5 | 271 | 2 | 0 | 129 | 261 | 29 | 0 | 26 | 15 | 3 | 0 | 6 | 19 | 197 | 0 | 963 | 3532 |
| 4:15 PM | 8 | 280 | 5 | 1 | 136 | 258 | 19 | 0 | 34 | 11 | 3 | 0 | 6 | 28 | 166 | 0 | 955 | 3706 |
| 4:30 PM | 7 | 243 | 4 | 0 | 164 | 270 | 22 | 0 | 39 | 13 | 1 | 0 | 9 | 12 | 199 | 0 | 983 | 3876 |
| 4:45 PM | 4 | 286 | 3 | 0 | 136 | 274 | 33 | 0 | 20 | 15 | 4 | 0 | 8 | 10 | 140 | 0 | 933 | 3834 |
| 5:00 PM | 9 | 272 | 0 | 1 | 163 | 265 | 19 | 0 | 38 | 15 | 5 | 0 | 9 | 18 | 188 | 0 | 1002 | 3873 |
| 5:15 PM | 5 | 246 | 1 | 0 | 144 | 275 | 30 | 0 | 26 | 21 | 5 | 0 | 5 | 17 | 191 | 0 | 966 | 3884 |
| 5:30 PM | 9 | 288 | 2 | 0 | 151 | 279 | 19 | 0 | 35 | 13 | 6 | 0 | 5 | 17 | 179 | 0 | 1003 | 3904 |
| 5:45 PM | 5 | 249 | 4 | 0 | 155 | 262 | 19 | 0 | 34 | 17 | 3 | 0 | 9 | 15 | 141 | 0 | 913 | 3884 |

| Peak 15-Min Flowrates | Northbound | | | | Southbound | | | | Eastbound | | | | Westbound | | | | Total |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | Left | Thru | Right | U | |
| All Vehicles | 36 | 1152 | 8 | 0 | 604 | 1116 | 76 | 0 | 140 | 52 | 24 | 0 | 20 | 68 | 716 | 0 | 4012 |
| Heavy Trucks | 0 | 8 | 0 | | 12 | 8 | 0 | | 0 | 0 | 0 | | 0 | 0 | 4 | | 32 |
| Buses | | | | | | | | | | | | | | | | | |
| Pedestrians | | 0 | | | | 0 | | | | 4 | | | | 0 | | | 4 |
| Bicycles | 0 | 0 | 0 | | 0 | 4 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 4 |
| Scooters | | | | | | | | | | | | | | | | | |

*Comments:*

Report generated on 2/10/2023 10:53 AM

SOURCE: Quality Counts, LLC (http://www.qualitycounts.net) 1-877-580-2212

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/28/2023 0:00
End Time 10/28/2023 23:59
Location 05-53-036 Rt 324 @ Rt 62 (NFB)
Latitude an 42.98077018,-78.82289704
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 13 | 37 | 1 | 0 | 0 | 0 | 3 | 16 | 10 | 0 | 0 | 0 | 0 | 25 | 0 | 0 | 0 | 0 | 0 | 9 | 5 | 0 | 0 | 0 | 119 |
| 0:15:00 | 9 | 28 | 1 | 0 | 0 | 0 | 1 | 15 | 4 | 0 | 0 | 0 | 2 | 17 | 0 | 0 | 0 | 0 | 0 | 9 | 11 | 0 | 0 | 0 | 97 |
| 0:30:00 | 7 | 31 | 2 | 0 | 0 | 0 | 0 | 9 | 3 | 0 | 0 | 0 | 1 | 21 | 0 | 0 | 0 | 0 | 0 | 10 | 6 | 0 | 0 | 0 | 90 |
| 0:45:00 | 4 | 30 | 1 | 0 | 0 | 0 | 5 | 16 | 1 | 0 | 0 | 0 | 1 | 26 | 0 | 0 | 0 | 0 | 0 | 9 | 4 | 0 | 0 | 0 | 97 |
| 1:00:00 | 6 | 19 | 1 | 0 | 0 | 0 | 2 | 4 | 1 | 0 | 0 | 0 | 0 | 30 | 0 | 0 | 0 | 0 | 0 | 5 | 5 | 0 | 0 | 0 | 73 |
| 1:15:00 | 5 | 19 | 0 | 0 | 0 | 0 | 1 | 12 | 3 | 0 | 0 | 0 | 0 | 22 | 0 | 0 | 0 | 0 | 0 | 17 | 5 | 0 | 0 | 0 | 84 |
| 1:30:00 | 5 | 16 | 0 | 0 | 0 | 0 | 3 | 11 | 2 | 0 | 0 | 0 | 0 | 37 | 0 | 0 | 0 | 0 | 0 | 5 | 2 | 0 | 0 | 0 | 81 |
| 1:45:00 | 6 | 24 | 0 | 0 | 0 | 0 | 2 | 7 | 2 | 0 | 0 | 0 | 0 | 24 | 0 | 0 | 0 | 0 | 0 | 10 | 5 | 0 | 0 | 0 | 80 |
| 2:00:00 | 5 | 19 | 0 | 0 | 0 | 0 | 2 | 7 | 1 | 0 | 0 | 0 | 0 | 25 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 67 |
| 2:15:00 | 6 | 19 | 0 | 0 | 0 | 0 | 5 | 5 | 4 | 0 | 0 | 0 | 0 | 27 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 71 |
| 2:30:00 | 3 | 23 | 0 | 0 | 0 | 0 | 1 | 4 | 3 | 0 | 0 | 0 | 0 | 25 | 0 | 0 | 0 | 0 | 0 | 4 | 2 | 0 | 0 | 0 | 65 |
| 2:45:00 | 1 | 14 | 0 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 20 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 45 |
| 3:00:00 | 2 | 16 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 11 | 0 | 0 | 0 | 0 | 0 | 5 | 4 | 0 | 0 | 0 | 43 |
| 3:15:00 | 5 | 9 | 1 | 0 | 0 | 0 | 0 | 4 | 2 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 3 | 3 | 0 | 0 | 0 | 34 |
| 3:30:00 | 2 | 6 | 0 | 0 | 0 | 0 | 1 | 5 | 1 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 0 | 6 | 1 | 0 | 0 | 0 | 37 |
| 3:45:00 | 3 | 4 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 1 | 7 | 0 | 0 | 0 | 0 | 0 | 6 | 4 | 0 | 0 | 0 | 28 |
| 4:00:00 | 4 | 4 | 0 | 0 | 0 | 0 | 1 | 2 | 2 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 21 |
| 4:15:00 | 0 | 7 | 1 | 0 | 0 | 0 | 0 | 6 | 2 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 5 | 2 | 0 | 0 | 0 | 33 |
| 4:30:00 | 3 | 9 | 0 | 0 | 0 | 0 | 1 | 5 | 3 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 10 | 1 | 0 | 0 | 0 | 40 |
| 4:45:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 11 | 3 | 0 | 0 | 0 | 32 |
| 5:00:00 | 2 | 8 | 0 | 0 | 0 | 0 | 0 | 3 | 2 | 0 | 0 | 0 | 1 | 7 | 0 | 0 | 0 | 0 | 0 | 5 | 3 | 0 | 0 | 0 | 31 |
| 5:15:00 | 1 | 7 | 2 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 9 | 4 | 0 | 0 | 0 | 32 |
| 5:30:00 | 3 | 13 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 12 | 4 | 0 | 0 | 0 | 43 |
| 5:45:00 | 2 | 6 | 1 | 0 | 0 | 0 | 0 | 6 | 2 | 0 | 0 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 20 | 6 | 0 | 0 | 0 | 54 |
| 6:00:00 | 6 | 6 | 1 | 0 | 0 | 0 | 0 | 10 | 2 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 18 | 3 | 0 | 0 | 0 | 51 |
| 6:15:00 | 1 | 12 | 1 | 0 | 0 | 0 | 1 | 12 | 3 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 17 | 2 | 0 | 0 | 0 | 55 |
| 6:30:00 | 5 | 10 | 0 | 0 | 0 | 0 | 2 | 5 | 1 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 14 | 6 | 0 | 0 | 0 | 50 |
| 6:45:00 | 6 | 12 | 0 | 0 | 0 | 0 | 6 | 10 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 15 | 5 | 0 | 0 | 0 | 62 |
| 7:00:00 | 12 | 7 | 2 | 0 | 0 | 0 | 13 | 15 | 1 | 0 | 0 | 0 | 4 | 3 | 0 | 0 | 0 | 0 | 0 | 17 | 12 | 0 | 0 | 0 | 86 |
| 7:15:00 | 11 | 13 | 2 | 0 | 0 | 0 | 2 | 13 | 0 | 0 | 0 | 0 | 8 | 7 | 0 | 0 | 0 | 0 | 0 | 36 | 15 | 0 | 0 | 0 | 107 |
| 7:30:00 | 16 | 19 | 5 | 0 | 0 | 0 | 3 | 42 | 8 | 0 | 0 | 0 | 9 | 25 | 0 | 0 | 0 | 0 | 0 | 48 | 12 | 0 | 0 | 0 | 187 |
| 7:45:00 | 12 | 28 | 5 | 2 | 0 | 0 | 3 | 48 | 12 | 0 | 0 | 0 | 13 | 36 | 0 | 0 | 0 | 0 | 0 | 68 | 37 | 1 | 0 | 0 | 265 |
| 8:00:00 | 16 | 41 | 6 | 2 | 0 | 0 | 4 | 43 | 12 | 0 | 0 | 0 | 12 | 47 | 0 | 0 | 0 | 0 | 0 | 58 | 39 | 0 | 0 | 0 | 280 |
| 8:15:00 | 8 | 44 | 6 | 3 | 0 | 0 | 4 | 61 | 14 | 0 | 0 | 0 | 10 | 55 | 0 | 0 | 0 | 0 | 0 | 71 | 30 | 0 | 0 | 0 | 306 |
| 8:30:00 | 31 | 56 | 3 | 1 | 0 | 0 | 4 | 78 | 21 | 0 | 0 | 0 | 11 | 59 | 0 | 0 | 0 | 0 | 0 | 88 | 31 | 1 | 0 | 0 | 384 |
| 8:45:00 | 39 | 49 | 8 | 1 | 0 | 0 | 6 | 67 | 19 | 0 | 0 | 0 | 16 | 75 | 0 | 0 | 0 | 0 | 0 | 86 | 56 | 1 | 0 | 0 | 423 |
| 9:00:00 | 29 | 47 | 13 | 3 | 0 | 0 | 7 | 77 | 30 | 0 | 0 | 0 | 14 | 84 | 0 | 0 | 0 | 0 | 0 | 74 | 41 | 0 | 0 | 0 | 419 |
| 9:15:00 | 30 | 46 | 12 | 9 | 0 | 0 | 10 | 83 | 17 | 0 | 0 | 0 | 17 | 73 | 0 | 0 | 0 | 0 | 0 | 103 | 55 | 0 | 0 | 0 | 455 |
| 9:30:00 | 47 | 69 | 25 | 3 | 0 | 0 | 3 | 91 | 41 | 1 | 0 | 0 | 14 | 75 | 0 | 0 | 0 | 0 | 0 | 103 | 66 | 0 | 0 | 0 | 538 |
| 9:45:00 | 46 | 79 | 18 | 8 | 0 | 0 | 15 | 105 | 35 | 0 | 0 | 0 | 23 | 102 | 0 | 0 | 0 | 0 | 0 | 113 | 77 | 0 | 0 | 0 | 621 |
| 10:00:00 | 50 | 77 | 29 | 9 | 0 | 0 | 11 | 90 | 48 | 0 | 0 | 0 | 19 | 83 | 0 | 0 | 0 | 0 | 0 | 102 | 63 | 0 | 0 | 0 | 581 |
| 10:15:00 | 42 | 82 | 31 | 7 | 0 | 0 | 10 | 133 | 29 | 1 | 0 | 0 | 10 | 94 | 0 | 0 | 0 | 0 | 0 | 128 | 58 | 1 | 0 | 0 | 626 |
| 10:30:00 | 62 | 89 | 27 | 12 | 0 | 0 | 11 | 135 | 37 | 0 | 0 | 0 | 8 | 91 | 0 | 0 | 0 | 0 | 0 | 130 | 87 | 0 | 0 | 0 | 689 |
| 10:45:00 | 62 | 101 | 30 | 4 | 0 | 0 | 17 | 136 | 48 | 0 | 0 | 0 | 12 | 135 | 0 | 0 | 0 | 0 | 0 | 149 | 98 | 1 | 0 | 0 | 793 |
| 11:00:00 | 67 | 94 | 42 | 9 | 0 | 0 | 8 | 125 | 48 | 1 | 0 | 0 | 13 | 137 | 0 | 0 | 0 | 0 | 0 | 130 | 90 | 0 | 0 | 0 | 764 |
| 11:15:00 | 81 | 115 | 36 | 13 | 0 | 0 | 16 | 138 | 54 | 0 | 0 | 0 | 32 | 110 | 0 | 0 | 0 | 0 | 0 | 168 | 71 | 1 | 0 | 0 | 835 |
| 11:30:00 | 73 | 136 | 31 | 11 | 0 | 0 | 14 | 167 | 48 | 2 | 0 | 0 | 24 | 97 | 0 | 0 | 0 | 0 | 0 | 157 | 85 | 0 | 0 | 0 | 845 |
| 11:45:00 | 80 | 100 | 24 | 8 | 0 | 0 | 19 | 164 | 80 | 1 | 0 | 0 | 16 | 151 | 0 | 0 | 0 | 0 | 0 | 166 | 99 | 0 | 0 | 0 | 908 |
| 12:00 PM | 84 | 132 | 46 | 12 | 0 | 0 | 17 | 138 | 46 | 1 | 0 | 0 | 25 | 128 | 0 | 0 | 0 | 0 | 0 | 144 | 78 | 0 | 0 | 0 | 851 |
| 12:15 PM | 83 | 122 | 38 | 12 | 0 | 0 | 15 | 161 | 48 | 0 | 0 | 0 | 21 | 145 | 0 | 0 | 0 | 0 | 0 | 140 | 115 | 0 | 0 | 0 | 900 |
| 12:30 PM | 91 | 112 | 50 | 12 | 0 | 0 | 15 | 169 | 67 | 0 | 0 | 0 | 17 | 133 | 0 | 0 | 0 | 0 | 0 | 164 | 109 | 1 | 0 | 0 | 940 |
| 12:45 PM | 85 | 110 | 57 | 13 | 0 | 0 | 8 | 138 | 77 | 0 | 0 | 0 | 4 | 150 | 0 | 0 | 0 | 0 | 0 | 154 | 112 | 0 | 0 | 0 | 908 |
| 1:00 PM | 110 | 131 | 51 | 16 | 0 | 0 | 16 | 157 | 49 | 2 | 0 | 0 | 14 | 157 | 0 | 0 | 0 | 0 | 0 | 156 | 96 | 0 | 0 | 0 | 955 |
| 1:15 PM | 97 | 138 | 40 | 15 | 0 | 0 | 19 | 178 | 55 | 2 | 0 | 0 | 13 | 117 | 0 | 0 | 0 | 0 | 0 | 160 | 108 | 3 | 0 | 0 | 945 |
| 1:30 PM | 89 | 107 | 46 | 4 | 0 | 0 | 10 | 184 | 56 | 2 | 0 | 0 | 19 | 115 | 0 | 0 | 0 | 0 | 0 | 168 | 114 | 1 | 0 | 0 | 915 |
| 1:45 PM | 104 | 139 | 63 | 7 | 0 | 0 | 10 | 148 | 54 | 1 | 0 | 0 | 13 | 177 | 0 | 0 | 0 | 0 | 0 | 135 | 96 | 1 | 0 | 0 | 948 |
| 2:00 PM | 96 | 135 | 48 | 15 | 0 | 0 | 13 | 178 | 56 | 0 | 0 | 0 | 20 | 138 | 0 | 0 | 0 | 0 | 0 | 149 | 81 | 0 | 0 | 0 | 929 |
| 2:15 PM | 87 | 126 | 52 | 9 | 0 | 0 | 19 | 158 | 63 | 0 | 0 | 0 | 7 | 128 | 0 | 0 | 0 | 0 | 0 | 139 | 108 | 0 | 0 | 0 | 896 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.972574 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 2:30 PM | 83 | 122 | 49 | 13 | 0 | 0 | 9 | 161 | 67 | 0 | 0 | 0 | 13 | 149 | 0 | 0 | 0 | 0 | 0 | 136 | 122 | 0 | 0 | 0 | 924 |
| 2:45 PM | 101 | 133 | 50 | 22 | 0 | 0 | 9 | 152 | 72 | 1 | 0 | 0 | 14 | 150 | 0 | 0 | 0 | 0 | 0 | 121 | 95 | 0 | 0 | 0 | 920 |
| 15:00:00 | 99 | 144 | 34 | 13 | 0 | 0 | 11 | 145 | 52 | 1 | 0 | 0 | 19 | 154 | 0 | 0 | 0 | 0 | 0 | 112 | 58 | 0 | 0 | 0 | 842 |
| 15:15:00 | 95 | 132 | 39 | 19 | 0 | 0 | 14 | 185 | 63 | 1 | 0 | 0 | 11 | 123 | 0 | 0 | 0 | 0 | 0 | 154 | 104 | 2 | 0 | 0 | 942 |
| 15:30:00 | 79 | 126 | 44 | 13 | 0 | 0 | 13 | 158 | 60 | 3 | 0 | 0 | 7 | 123 | 0 | 0 | 0 | 0 | 0 | 147 | 96 | 0 | 0 | 0 | 869 |
| 15:45:00 | 101 | 143 | 40 | 9 | 0 | 0 | 10 | 172 | 44 | 1 | 0 | 0 | 15 | 137 | 0 | 0 | 0 | 0 | 0 | 108 | 83 | 0 | 0 | 0 | 863 |
| 16:00:00 | 87 | 141 | 50 | 16 | 0 | 0 | 14 | 181 | 62 | 0 | 0 | 0 | 8 | 129 | 0 | 0 | 0 | 0 | 0 | 143 | 102 | 1 | 0 | 0 | 934 |
| 16:15:00 | 79 | 145 | 30 | 6 | 0 | 0 | 10 | 136 | 42 | 1 | 0 | 0 | 9 | 141 | 0 | 0 | 0 | 0 | 0 | 119 | 97 | 0 | 0 | 0 | 815 |
| 16:30:00 | 112 | 140 | 38 | 12 | 0 | 0 | 18 | 163 | 47 | 1 | 0 | 0 | 17 | 133 | 0 | 0 | 0 | 0 | 0 | 151 | 69 | 0 | 0 | 0 | 901 |
| 16:45:00 | 86 | 121 | 31 | 14 | 0 | 0 | 13 | 164 | 65 | 2 | 0 | 0 | 18 | 129 | 0 | 0 | 0 | 0 | 0 | 139 | 96 | 0 | 0 | 0 | 878 |
| 17:00:00 | 86 | 141 | 47 | 12 | 0 | 0 | 11 | 134 | 42 | 0 | 0 | 0 | 11 | 130 | 0 | 0 | 0 | 0 | 0 | 105 | 84 | 0 | 0 | 0 | 803 |
| 17:15:00 | 70 | 132 | 35 | 8 | 0 | 0 | 7 | 162 | 59 | 2 | 0 | 0 | 11 | 112 | 0 | 0 | 0 | 0 | 0 | 139 | 89 | 1 | 0 | 0 | 827 |
| 17:30:00 | 70 | 118 | 28 | 15 | 0 | 0 | 6 | 135 | 38 | 2 | 0 | 0 | 6 | 139 | 0 | 0 | 0 | 0 | 0 | 124 | 81 | 1 | 0 | 0 | 763 |
| 17:45:00 | 73 | 130 | 21 | 9 | 0 | 0 | 11 | 125 | 47 | 0 | 0 | 0 | 9 | 133 | 0 | 0 | 0 | 0 | 0 | 91 | 70 | 1 | 0 | 0 | 720 |
| 18:00:00 | 74 | 120 | 39 | 7 | 0 | 0 | 27 | 153 | 62 | 1 | 0 | 0 | 10 | 110 | 0 | 0 | 0 | 0 | 0 | 126 | 83 | 1 | 0 | 0 | 813 |
| 18:15:00 | 57 | 106 | 27 | 10 | 0 | 0 | 9 | 126 | 51 | 0 | 0 | 0 | 7 | 124 | 0 | 0 | 0 | 0 | 0 | 86 | 74 | 2 | 0 | 0 | 679 |
| 18:30:00 | 68 | 155 | 33 | 16 | 0 | 0 | 12 | 111 | 37 | 0 | 0 | 0 | 14 | 74 | 0 | 0 | 0 | 0 | 0 | 83 | 38 | 0 | 0 | 0 | 641 |
| 18:45:00 | 70 | 144 | 11 | 7 | 0 | 0 | 19 | 133 | 34 | 0 | 0 | 0 | 14 | 75 | 0 | 0 | 0 | 0 | 0 | 113 | 55 | 2 | 0 | 0 | 677 |
| 19:00:00 | 66 | 145 | 23 | 9 | 0 | 0 | 12 | 86 | 32 | 0 | 0 | 0 | 5 | 57 | 0 | 0 | 0 | 0 | 0 | 65 | 56 | 1 | 0 | 0 | 557 |
| 19:15:00 | 55 | 119 | 11 | 10 | 0 | 0 | 16 | 115 | 41 | 2 | 0 | 0 | 3 | 55 | 0 | 0 | 0 | 0 | 0 | 74 | 50 | 0 | 0 | 0 | 551 |
| 19:30:00 | 66 | 100 | 10 | 1 | 0 | 0 | 10 | 94 | 39 | 0 | 0 | 0 | 8 | 61 | 0 | 0 | 0 | 0 | 0 | 82 | 48 | 1 | 0 | 0 | 520 |
| 19:45:00 | 57 | 106 | 18 | 6 | 0 | 0 | 8 | 74 | 25 | 0 | 0 | 0 | 9 | 71 | 0 | 0 | 0 | 0 | 0 | 61 | 33 | 0 | 0 | 0 | 468 |
| 20:00:00 | 49 | 102 | 16 | 5 | 0 | 0 | 15 | 102 | 23 | 0 | 0 | 0 | 8 | 65 | 0 | 0 | 0 | 0 | 0 | 56 | 26 | 3 | 0 | 0 | 470 |
| 20:15:00 | 46 | 97 | 11 | 3 | 0 | 0 | 12 | 67 | 27 | 0 | 0 | 0 | 7 | 56 | 0 | 0 | 0 | 0 | 0 | 56 | 20 | 1 | 0 | 0 | 403 |
| 20:30:00 | 32 | 86 | 10 | 4 | 0 | 0 | 6 | 81 | 27 | 0 | 0 | 0 | 3 | 51 | 0 | 0 | 0 | 0 | 0 | 47 | 25 | 0 | 0 | 0 | 372 |
| 20:45:00 | 32 | 94 | 9 | 3 | 0 | 0 | 9 | 61 | 22 | 0 | 0 | 0 | 4 | 47 | 0 | 0 | 0 | 0 | 0 | 63 | 26 | 0 | 0 | 0 | 370 |
| 21:00:00 | 39 | 91 | 8 | 4 | 0 | 0 | 3 | 71 | 27 | 1 | 0 | 0 | 3 | 29 | 0 | 0 | 0 | 0 | 0 | 40 | 9 | 0 | 0 | 0 | 325 |
| 21:15:00 | 34 | 81 | 5 | 3 | 0 | 0 | 8 | 64 | 14 | 0 | 0 | 0 | 3 | 42 | 0 | 0 | 0 | 0 | 0 | 39 | 13 | 0 | 0 | 0 | 306 |
| 21:30:00 | 37 | 69 | 3 | 2 | 0 | 0 | 6 | 62 | 23 | 0 | 0 | 0 | 5 | 40 | 0 | 0 | 0 | 0 | 0 | 40 | 19 | 0 | 0 | 0 | 306 |
| 21:45:00 | 25 | 73 | 3 | 2 | 0 | 0 | 6 | 38 | 17 | 0 | 0 | 0 | 4 | 32 | 0 | 0 | 0 | 0 | 0 | 35 | 15 | 0 | 0 | 0 | 250 |
| 22:00:00 | 39 | 68 | 6 | 1 | 0 | 0 | 6 | 58 | 14 | 0 | 0 | 0 | 5 | 32 | 0 | 0 | 0 | 0 | 0 | 42 | 14 | 0 | 0 | 0 | 285 |
| 22:15:00 | 14 | 66 | 6 | 3 | 0 | 0 | 6 | 53 | 12 | 0 | 0 | 0 | 4 | 44 | 0 | 0 | 0 | 0 | 0 | 46 | 10 | 0 | 0 | 0 | 264 |
| 22:30:00 | 21 | 49 | 2 | 2 | 0 | 0 | 7 | 33 | 10 | 0 | 0 | 0 | 2 | 28 | 0 | 0 | 0 | 0 | 0 | 33 | 17 | 0 | 0 | 0 | 204 |
| 22:45:00 | 19 | 50 | 4 | 0 | 0 | 0 | 5 | 45 | 10 | 0 | 0 | 0 | 3 | 39 | 0 | 0 | 0 | 0 | 0 | 24 | 14 | 0 | 0 | 0 | 213 |
| 23:00:00 | 26 | 52 | 1 | 0 | 0 | 0 | 2 | 35 | 16 | 0 | 0 | 0 | 6 | 30 | 0 | 0 | 0 | 0 | 0 | 26 | 7 | 0 | 0 | 0 | 201 |
| 23:15:00 | 15 | 52 | 2 | 0 | 0 | 0 | 2 | 24 | 7 | 0 | 0 | 0 | 5 | 35 | 0 | 0 | 0 | 0 | 0 | 27 | 8 | 0 | 0 | 0 | 177 |
| 23:30:00 | 12 | 62 | 4 | 0 | 0 | 0 | 1 | 20 | 8 | 0 | 0 | 0 | 3 | 45 | 0 | 0 | 0 | 0 | 0 | 24 | 16 | 0 | 0 | 0 | 195 |
| 23:45:00 | 16 | 53 | 3 | 0 | 0 | 0 | 3 | 23 | 10 | 0 | 0 | 0 | 2 | 38 | 0 | 0 | 0 | 0 | 0 | 20 | 6 | 0 | 0 | 0 | 174 |

| | | |
|---|---|---|
| **Lights** | 913 | 2 |
| HV | 944 | 4 |
| | 926 | 3 |
| | 894 | 2 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/26/2023 0:00
End Time 10/26/2023 23:59
Location 05-53-036 Rt 324 @ Rt 62 (NFB)
Latitude an 42.98077018, -78.82289704
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 5 | 11 | 0 | 1 | 0 | 0 | 7 | 10 | 3 | 0 | 0 | 0 | 2 | 5 | 0 | 0 | 0 | 0 | 0 | 6 | 5 | 0 | 0 | 0 | 55 |
| 0:15:00 | 7 | 9 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 9 | 2 | 0 | 0 | 0 | 38 |
| 0:30:00 | 5 | 6 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 4 | 3 | 0 | 0 | 0 | 23 |
| 0:45:00 | 4 | 5 | 2 | 1 | 0 | 0 | 4 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 23 |
| 1:00:00 | 1 | 4 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 13 |
| 1:15:00 | 4 | 2 | 2 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 5 | 0 | 0 | 0 | 21 |
| 1:30:00 | 1 | 1 | 0 | 0 | 0 | 0 | 2 | 6 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 18 |
| 1:45:00 | 3 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 10 |
| 2:00:00 | 4 | 0 | 1 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 16 |
| 2:15:00 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 10 |
| 2:30:00 | 2 | 2 | 1 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 12 |
| 2:45:00 | 2 | 2 | 1 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 12 |
| 3:00:00 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 6 |
| 3:15:00 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 9 |
| 3:30:00 | 3 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 12 |
| 3:45:00 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 4 | 0 | 0 | 0 | 13 |
| 4:00:00 | 2 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 |
| 4:15:00 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 10 |
| 4:30:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 11 |
| 4:45:00 | 1 | 2 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 4 | 0 | 0 | 0 | 0 | 0 | 8 | 5 | 0 | 0 | 0 | 25 |
| 5:00:00 | 1 | 3 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 7 | 2 | 0 | 0 | 0 | 21 |
| 5:15:00 | 3 | 3 | 3 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 8 | 0 | 0 | 0 | 31 |
| 5:30:00 | 3 | 6 | 0 | 0 | 0 | 0 | 3 | 6 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 10 | 8 | 0 | 0 | 0 | 43 |
| 5:45:00 | 3 | 6 | 0 | 0 | 0 | 0 | 1 | 8 | 1 | 0 | 0 | 0 | 3 | 8 | 0 | 0 | 0 | 0 | 0 | 19 | 6 | 0 | 0 | 0 | 55 |
| 6:00:00 | 12 | 12 | 1 | 0 | 0 | 0 | 2 | 15 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 30 | 7 | 1 | 0 | 0 | 83 |
| 6:15:00 | 7 | 18 | 0 | 1 | 0 | 0 | 3 | 10 | 2 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 25 | 10 | 0 | 0 | 0 | 78 |
| 6:30:00 | 14 | 22 | 3 | 0 | 0 | 0 | 5 | 12 | 3 | 0 | 0 | 0 | 4 | 4 | 0 | 0 | 0 | 0 | 0 | 51 | 9 | 0 | 0 | 0 | 127 |
| 6:45:00 | 23 | 24 | 2 | 0 | 0 | 0 | 8 | 39 | 2 | 0 | 0 | 0 | 2 | 5 | 0 | 0 | 0 | 0 | 0 | 60 | 21 | 0 | 0 | 0 | 186 |
| 7:00:00 | 22 | 32 | 3 | 0 | 0 | 0 | 6 | 22 | 1 | 0 | 0 | 0 | 6 | 5 | 0 | 0 | 0 | 0 | 0 | 59 | 24 | 0 | 0 | 0 | 180 |
| 7:15:00 | 38 | 59 | 2 | 0 | 0 | 0 | 7 | 70 | 12 | 0 | 0 | 0 | 10 | 20 | 0 | 0 | 0 | 0 | 0 | 110 | 23 | 0 | 0 | 0 | 351 |
| 7:30:00 | 39 | 132 | 9 | 2 | 0 | 0 | 8 | 74 | 28 | 0 | 0 | 0 | 17 | 59 | 0 | 0 | 0 | 0 | 0 | 140 | 30 | 0 | 0 | 0 | 538 |
| 7:45:00 | 30 | 149 | 21 | 0 | 0 | 0 | 6 | 81 | 28 | 0 | 0 | 0 | 22 | 86 | 0 | 0 | 0 | 0 | 0 | 130 | 63 | 0 | 0 | 0 | 616 |
| 8:00:00 | 31 | 83 | 8 | 2 | 0 | 0 | 3 | 88 | 30 | 0 | 0 | 0 | 25 | 98 | 0 | 0 | 0 | 0 | 0 | 162 | 43 | 0 | 0 | 0 | 573 |
| 8:15:00 | 39 | 99 | 19 | 2 | 0 | 0 | 2 | 102 | 20 | 1 | 0 | 0 | 14 | 88 | 0 | 0 | 0 | 0 | 0 | 116 | 48 | 0 | 0 | 0 | 550 |
| 8:30:00 | 42 | 88 | 18 | 4 | 0 | 0 | 6 | 71 | 21 | 1 | 0 | 0 | 16 | 104 | 0 | 0 | 0 | 0 | 0 | 107 | 43 | 0 | 0 | 0 | 521 |
| 8:45:00 | 49 | 72 | 15 | 2 | 0 | 0 | 7 | 108 | 27 | 1 | 0 | 0 | 17 | 110 | 0 | 0 | 0 | 0 | 0 | 135 | 57 | 1 | 0 | 0 | 601 |
| 9:00:00 | 51 | 82 | 18 | 1 | 0 | 0 | 3 | 102 | 28 | 1 | 0 | 0 | 19 | 88 | 0 | 0 | 0 | 0 | 0 | 112 | 51 | 0 | 0 | 0 | 556 |
| 9:15:00 | 39 | 65 | 21 | 4 | 0 | 0 | 9 | 124 | 30 | 1 | 0 | 0 | 10 | 92 | 0 | 0 | 0 | 0 | 0 | 118 | 42 | 0 | 0 | 0 | 555 |
| 9:30:00 | 30 | 73 | 20 | 6 | 0 | 0 | 8 | 110 | 30 | 0 | 0 | 0 | 26 | 76 | 0 | 0 | 0 | 0 | 0 | 120 | 68 | 0 | 0 | 0 | 567 |
| 9:45:00 | 40 | 63 | 29 | 1 | 0 | 0 | 8 | 110 | 30 | 0 | 0 | 0 | 16 | 83 | 0 | 0 | 0 | 0 | 0 | 112 | 57 | 0 | 0 | 0 | 549 |
| 10:00:00 | 55 | 79 | 24 | 2 | 0 | 0 | 7 | 90 | 34 | 0 | 0 | 0 | 14 | 92 | 0 | 0 | 0 | 0 | 0 | 85 | 71 | 0 | 0 | 0 | 553 |
| 10:15:00 | 58 | 72 | 22 | 9 | 0 | 0 | 13 | 135 | 35 | 0 | 0 | 0 | 21 | 87 | 0 | 0 | 0 | 0 | 0 | 137 | 50 | 0 | 0 | 0 | 639 |
| 10:30:00 | 62 | 93 | 26 | 2 | 0 | 0 | 9 | 138 | 34 | 0 | 0 | 0 | 16 | 80 | 0 | 0 | 0 | 0 | 0 | 127 | 66 | 0 | 0 | 0 | 653 |
| 10:45:00 | 56 | 76 | 18 | 5 | 0 | 0 | 9 | 138 | 41 | 1 | 0 | 0 | 14 | 101 | 0 | 0 | 0 | 0 | 0 | 101 | 63 | 1 | 0 | 0 | 624 |
| 11:00:00 | 58 | 89 | 30 | 8 | 0 | 0 | 12 | 120 | 37 | 0 | 0 | 0 | 25 | 114 | 0 | 0 | 0 | 0 | 0 | 118 | 86 | 1 | 0 | 0 | 698 |
| 11:15:00 | 71 | 116 | 33 | 6 | 0 | 0 | 13 | 137 | 32 | 2 | 0 | 0 | 26 | 105 | 0 | 0 | 0 | 0 | 0 | 133 | 60 | 1 | 0 | 0 | 735 |
| 11:30:00 | 69 | 98 | 31 | 4 | 0 | 0 | 6 | 123 | 42 | 1 | 0 | 0 | 17 | 84 | 0 | 0 | 0 | 0 | 0 | 125 | 87 | 0 | 0 | 0 | 687 |
| 11:45:00 | 76 | 97 | 19 | 7 | 0 | 0 | 16 | 159 | 50 | 3 | 0 | 0 | 19 | 124 | 0 | 0 | 0 | 0 | 0 | 117 | 79 | 1 | 0 | 0 | 767 |
| 12:00:00 | 61 | 97 | 35 | 9 | 0 | 0 | 11 | 128 | 42 | 0 | 0 | 0 | 19 | 131 | 0 | 0 | 0 | 0 | 0 | 145 | 64 | 1 | 0 | 0 | 743 |
| 12:15:00 | 67 | 109 | 40 | 12 | 0 | 0 | 7 | 142 | 50 | 1 | 0 | 0 | 8 | 119 | 0 | 0 | 0 | 0 | 0 | 138 | 73 | 1 | 0 | 0 | 767 |
| 12:30:00 | 77 | 125 | 38 | 8 | 0 | 0 | 5 | 179 | 50 | 1 | 0 | 0 | 14 | 84 | 0 | 0 | 0 | 0 | 0 | 160 | 80 | 1 | 0 | 0 | 822 |
| 12:45:00 | 67 | 136 | 29 | 14 | 0 | 0 | 8 | 158 | 67 | 0 | 0 | 0 | 10 | 121 | 0 | 0 | 0 | 0 | 0 | 129 | 84 | 0 | 0 | 0 | 823 |
| 13:00:00 | 80 | 117 | 49 | 14 | 0 | 0 | 10 | 159 | 40 | 1 | 0 | 0 | 12 | 100 | 0 | 0 | 0 | 0 | 0 | 124 | 54 | 0 | 0 | 0 | 760 |
| 13:15:00 | 76 | 90 | 34 | 8 | 0 | 0 | 3 | 161 | 46 | 1 | 0 | 0 | 12 | 105 | 0 | 0 | 0 | 0 | 0 | 160 | 84 | 0 | 0 | 0 | 780 |
| 13:30:00 | 58 | 101 | 36 | 6 | 0 | 0 | 12 | 147 | 53 | 1 | 0 | 0 | 13 | 110 | 0 | 0 | 0 | 0 | 0 | 144 | 89 | 0 | 0 | 0 | 770 |
| 13:45:00 | 67 | 131 | 44 | 9 | 0 | 0 | 8 | 123 | 44 | 1 | 0 | 0 | 9 | 111 | 0 | 0 | 0 | 0 | 0 | 113 | 71 | 1 | 0 | 0 | 732 |
| 14:00:00 | 90 | 128 | 45 | 10 | 0 | 0 | 6 | 162 | 39 | 1 | 0 | 0 | 8 | 104 | 0 | 0 | 0 | 0 | 0 | 119 | 54 | 0 | 0 | 0 | 766 |
| 14:15:00 | 78 | 107 | 40 | 10 | 0 | 0 | 6 | 170 | 40 | 1 | 0 | 0 | 10 | 95 | 0 | 0 | 0 | 0 | 0 | 160 | 71 | 0 | 0 | 0 | 788 |
| 14:30:00 | 73 | 150 | 31 | 3 | 0 | 0 | 5 | 151 | 57 | 1 | 0 | 0 | 13 | 120 | 0 | 0 | 0 | 0 | 0 | 152 | 79 | 0 | 0 | 0 | 835 |
| 14:45:00 | 84 | 199 | 54 | 6 | 0 | 0 | 12 | 141 | 47 | 0 | 0 | 0 | 11 | 147 | 0 | 0 | 0 | 0 | 0 | 118 | 75 | 1 | 0 | 0 | 895 |
| 3:00 PM | 83 | 173 | 54 | 4 | 0 | 0 | 6 | 172 | 42 | 1 | 0 | 0 | 15 | 146 | 0 | 0 | 0 | 0 | 0 | 192 | 53 | 2 | 0 | 0 | 943 |
| 3:15 PM | 63 | 188 | 45 | 9 | 0 | 0 | 9 | 166 | 74 | 0 | 0 | 0 | 10 | 112 | 0 | 0 | 0 | 0 | 0 | 200 | 80 | 0 | 0 | 0 | 956 |
| 3:30 PM | 70 | 155 | 38 | 7 | 0 | 0 | 7 | 168 | 52 | 0 | 0 | 0 | 11 | 145 | 0 | 0 | 0 | 0 | 0 | 203 | 81 | 1 | 0 | 0 | 938 |
| 3:45 PM | 88 | 176 | 49 | 10 | 0 | 0 | 13 | 126 | 63 | 1 | 0 | 0 | 15 | 170 | 0 | 0 | 0 | 0 | 0 | 170 | 65 | 0 | 0 | 0 | 946 |
| 4:00 PM | 80 | 182 | 48 | 7 | 0 | 0 | 7 | 190 | 57 | 0 | 0 | 0 | 16 | 126 | 0 | 0 | 0 | 0 | 0 | 190 | 75 | 0 | 0 | 0 | 978 |
| 4:15 PM | 75 | 162 | 44 | 10 | 0 | 0 | 9 | 182 | 59 | 0 | 0 | 0 | 14 | 122 | 0 | 0 | 0 | 0 | 0 | 187 | 79 | 0 | 0 | 0 | 943 |
| 4:30 PM | 98 | 159 | 36 | 3 | 0 | 0 | 13 | 165 | 68 | 0 | 0 | 0 | 20 | 131 | 0 | 0 | 0 | 0 | 0 | 175 | 90 | 0 | 0 | 0 | 958 |
| 4:45 PM | 83 | 149 | 46 | 7 | 0 | 0 | 9 | 169 | 70 | 0 | 0 | 0 | 7 | 156 | 0 | 0 | 0 | 0 | 0 | 154 | 64 | 0 | 0 | 0 | 914 |
| 5:00 PM | 83 | 188 | 42 | 15 | 0 | 0 | 7 | 177 | 70 | 1 | 0 | 0 | 15 | 120 | 0 | 0 | 0 | 0 | 0 | 159 | 85 | 0 | 0 | 0 | 962 |
| 5:15 PM | 90 | 155 | 34 | 9 | 0 | 0 | 10 | 203 | 75 | 1 | 0 | 0 | 14 | 121 | 0 | 0 | 0 | 0 | 0 | 184 | 89 | 0 | 0 | 0 | 985 |
| PHF | | | | | | | | | | | | | | | | | | | | | | | | | 0.969289 |
| % HV | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 5:30 PM | 74 | 134 | 28 | 13 | 0 | 0 | 11 | 155 | 71 | 1 | 0 | 0 | 8 | 141 | 0 | 0 | 0 | 0 | 0 | 129 | 68 | 2 | 0 | 0 | 835 |
| 5:45 PM | 60 | 148 | 42 | 11 | 0 | 0 | 5 | 184 | 59 | 2 | 0 | 0 | 21 | 135 | 0 | 0 | 0 | 0 | 0 | 113 | 51 | 2 | 0 | 0 | 833 |
| 18:00:00 | 56 | 159 | 38 | 13 | 0 | 0 | 10 | 169 | 63 | 2 | 0 | 0 | 7 | 133 | 0 | 0 | 0 | 0 | 0 | 144 | 70 | 1 | 0 | 0 | 865 |
| 18:15:00 | 60 | 120 | 32 | 4 | 0 | 0 | 7 | 141 | 57 | 0 | 0 | 0 | 21 | 139 | 0 | 0 | 0 | 0 | 0 | 116 | 68 | 0 | 0 | 0 | 765 |
| 18:30:00 | 63 | 124 | 15 | 13 | 0 | 0 | 15 | 146 | 38 | 0 | 0 | 0 | 12 | 58 | 0 | 0 | 0 | 0 | 0 | 92 | 59 | 0 | 0 | 0 | 635 |
| 18:45:00 | 59 | 125 | 19 | 3 | 0 | 0 | 16 | 129 | 55 | 0 | 0 | 0 | 3 | 68 | 0 | 0 | 0 | 0 | 0 | 117 | 51 | 0 | 0 | 0 | 645 |
| 19:00:00 | 74 | 142 | 19 | 8 | 0 | 0 | 13 | 101 | 36 | 0 | 0 | 0 | 6 | 75 | 0 | 0 | 0 | 0 | 0 | 92 | 46 | 0 | 0 | 0 | 612 |
| 19:15:00 | 81 | 125 | 8 | 11 | 0 | 0 | 12 | 115 | 57 | 0 | 0 | 0 | 6 | 50 | 0 | 0 | 0 | 0 | 0 | 99 | 52 | 0 | 0 | 0 | 616 |
| 19:30:00 | 63 | 111 | 8 | 4 | 0 | 0 | 15 | 98 | 31 | 0 | 0 | 0 | 9 | 54 | 0 | 0 | 0 | 0 | 0 | 75 | 50 | 0 | 0 | 0 | 518 |
| 19:45:00 | 62 | 103 | 16 | 6 | 0 | 0 | 8 | 96 | 23 | 1 | 0 | 0 | 4 | 60 | 0 | 0 | 0 | 0 | 0 | 59 | 50 | 0 | 0 | 0 | 488 |
| 20:00:00 | 55 | 107 | 8 | 5 | 0 | 0 | 9 | 92 | 33 | 0 | 0 | 0 | 8 | 51 | 0 | 0 | 0 | 0 | 0 | 52 | 34 | 2 | 0 | 0 | 456 |
| 20:15:00 | 45 | 64 | 8 | 0 | 0 | 0 | 3 | 80 | 36 | 1 | 0 | 0 | 6 | 42 | 0 | 0 | 0 | 0 | 0 | 58 | 25 | 0 | 0 | 0 | 368 |
| 20:30:00 | 32 | 68 | 6 | 2 | 0 | 0 | 5 | 70 | 31 | 0 | 0 | 0 | 2 | 53 | 0 | 0 | 0 | 0 | 0 | 48 | 18 | 0 | 0 | 0 | 335 |
| 20:45:00 | 35 | 76 | 8 | 3 | 0 | 0 | 3 | 53 | 14 | 1 | 0 | 0 | 0 | 27 | 0 | 0 | 0 | 0 | 0 | 37 | 23 | 0 | 0 | 0 | 280 |
| 21:00:00 | 29 | 83 | 3 | 2 | 0 | 0 | 4 | 65 | 21 | 0 | 0 | 0 | 5 | 35 | 0 | 0 | 0 | 0 | 0 | 39 | 17 | 0 | 0 | 0 | 303 |
| 21:15:00 | 31 | 59 | 5 | 0 | 0 | 0 | 0 | 46 | 16 | 0 | 0 | 0 | 1 | 28 | 0 | 0 | 0 | 0 | 0 | 30 | 12 | 0 | 0 | 0 | 228 |
| 21:30:00 | 24 | 48 | 4 | 2 | 0 | 0 | 4 | 43 | 20 | 0 | 0 | 0 | 1 | 30 | 0 | 0 | 0 | 0 | 0 | 41 | 10 | 0 | 0 | 0 | 227 |
| 21:45:00 | 21 | 66 | 4 | 5 | 0 | 0 | 2 | 35 | 12 | 0 | 0 | 0 | 4 | 27 | 0 | 0 | 0 | 0 | 0 | 33 | 16 | 0 | 0 | 0 | 225 |
| 22:00:00 | 17 | 45 | 3 | 1 | 0 | 0 | 6 | 51 | 18 | 0 | 0 | 0 | 4 | 32 | 0 | 0 | 0 | 0 | 0 | 33 | 16 | 0 | 0 | 0 | 226 |
| 22:15:00 | 18 | 42 | 1 | 0 | 0 | 0 | 2 | 36 | 12 | 0 | 0 | 0 | 3 | 30 | 0 | 0 | 0 | 0 | 0 | 18 | 8 | 0 | 0 | 0 | 170 |
| 22:30:00 | 11 | 40 | 1 | 0 | 0 | 0 | 3 | 27 | 13 | 1 | 0 | 0 | 1 | 25 | 0 | 0 | 0 | 0 | 0 | 19 | 8 | 0 | 0 | 0 | 149 |
| 22:45:00 | 13 | 33 | 1 | 0 | 0 | 0 | 0 | 16 | 3 | 0 | 0 | 0 | 1 | 29 | 0 | 0 | 0 | 0 | 0 | 17 | 10 | 0 | 0 | 0 | 123 |
| 23:00:00 | 7 | 43 | 0 | 0 | 0 | 0 | 1 | 23 | 9 | 0 | 0 | 0 | 0 | 19 | 0 | 0 | 0 | 0 | 0 | 8 | 6 | 0 | 0 | 0 | 116 |
| 23:15:00 | 8 | 34 | 1 | 0 | 0 | 0 | 1 | 29 | 10 | 0 | 0 | 0 | 1 | 16 | 0 | 0 | 0 | 0 | 0 | 20 | 6 | 0 | 0 | 0 | 126 |
| 23:30:00 | 27 | 38 | 2 | 0 | 0 | 0 | 0 | 29 | 12 | 0 | 0 | 0 | 0 | 22 | 0 | 0 | 0 | 0 | 0 | 27 | 4 | 0 | 0 | 0 | 161 |
| 23:45:00 | 8 | 25 | 1 | 0 | 0 | 0 | 3 | 33 | 9 | 0 | 0 | 0 | 0 | 24 | 0 | 0 | 0 | 0 | 0 | 20 | 7 | 1 | 0 | 0 | 131 |

Lights HV
943
958 951 7
914 908 6
962 959 3
985 982 3

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time ########
End Time ########
Location 05-53-282 Rt 62 (NFB) @ Treadwell Rd
Latitude an 42.98670806, -78.82272476
Lights

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 0 | 43 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 58 |
| 0:15:00 | 0 | 30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 39 |
| 0:30:00 | 0 | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 42 |
| 0:45:00 | 0 | 28 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 37 |
| 1:00:00 | 0 | 25 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 34 |
| 1:15:00 | 0 | 19 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 27 |
| 1:30:00 | 0 | 21 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 31 |
| 1:45:00 | 0 | 27 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 37 |
| 2:00:00 | 0 | 19 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 25 |
| 2:15:00 | 1 | 20 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 30 |
| 2:30:00 | 0 | 23 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 9 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 35 |
| 2:45:00 | 0 | 15 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 25 |
| 3:00:00 | 0 | 16 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 20 |
| 3:15:00 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 |
| 3:30:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 |
| 3:45:00 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 |
| 4:00:00 | 1 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 |
| 4:15:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 |
| 4:30:00 | 0 | 14 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 16 |
| 4:45:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 |
| 5:00:00 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 |
| 5:15:00 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 |
| 5:30:00 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 16 |
| 5:45:00 | 0 | 9 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 |
| 6:00:00 | 0 | 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 17 |
| 6:15:00 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 9 |
| 6:30:00 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 17 |
| 6:45:00 | 0 | 16 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 23 |
| 7:00:00 | 0 | 16 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 8 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 26 |
| 7:15:00 | 0 | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 39 |
| 7:30:00 | 1 | 35 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 36 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 76 |
| 7:45:00 | 2 | 57 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 63 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 129 |
| 8:00:00 | 2 | 69 | 1 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 2 | 60 | 3 | 2 | 0 | 0 | 1 | 1 | 2 | 0 | 0 | 0 | 147 |
| 8:15:00 | 4 | 67 | 2 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 2 | 60 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 141 |
| 8:30:00 | 5 | 94 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 87 | 0 | 1 | 0 | 0 | 4 | 0 | 1 | 0 | 0 | 0 | 193 |
| 8:45:00 | 3 | 108 | 5 | 0 | 0 | 0 | 3 | 0 | 4 | 0 | 0 | 0 | 1 | 111 | 4 | 3 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 0 | 246 |
| 9:00:00 | 7 | 102 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 3 | 117 | 0 | 6 | 0 | 0 | 2 | 5 | 5 | 0 | 0 | 0 | 250 |
| 9:15:00 | 6 | 104 | 9 | 0 | 0 | 0 | 4 | 1 | 2 | 0 | 0 | 0 | 2 | 149 | 5 | 1 | 0 | 0 | 3 | 3 | 1 | 0 | 0 | 0 | 290 |
| 9:30:00 | 12 | 134 | 7 | 0 | 0 | 0 | 1 | 1 | 4 | 0 | 0 | 0 | 3 | 146 | 3 | 4 | 0 | 0 | 6 | 2 | 8 | 0 | 0 | 0 | 331 |
| 9:45:00 | 7 | 168 | 4 | 0 | 0 | 0 | 5 | 1 | 7 | 0 | 0 | 0 | 7 | 179 | 7 | 4 | 0 | 0 | 5 | 7 | 4 | 0 | 0 | 0 | 405 |
| 10:00:00 | 5 | 147 | 7 | 0 | 0 | 0 | 1 | 1 | 4 | 0 | 0 | 0 | 6 | 154 | 6 | 6 | 0 | 0 | 5 | 1 | 4 | 0 | 0 | 0 | 347 |
| 10:15:00 | 9 | 181 | 10 | 0 | 0 | 0 | 6 | 2 | 3 | 0 | 0 | 0 | 3 | 174 | 4 | 2 | 0 | 0 | 8 | 3 | 7 | 0 | 0 | 0 | 412 |
| 10:30:00 | 9 | 180 | 13 | 0 | 0 | 0 | 8 | 2 | 6 | 0 | 0 | 0 | 8 | 204 | 9 | 8 | 0 | 0 | 3 | 4 | 8 | 0 | 0 | 0 | 462 |
| 10:45:00 | 7 | 177 | 9 | 0 | 0 | 0 | 1 | 1 | 6 | 0 | 0 | 0 | 6 | 212 | 5 | 8 | 0 | 0 | 9 | 4 | 8 | 0 | 0 | 0 | 453 |
| 11:00:00 | 14 | 202 | 13 | 0 | 0 | 0 | 8 | 0 | 6 | 0 | 0 | 0 | 16 | 251 | 6 | 6 | 0 | 0 | 5 | 5 | 4 | 0 | 0 | 0 | 536 |
| 11:15:00 | 11 | 210 | 12 | 0 | 0 | 0 | 3 | 6 | 4 | 0 | 0 | 0 | 10 | 164 | 6 | 5 | 0 | 0 | 8 | 10 | 6 | 0 | 0 | 0 | 455 |
| 11:30:00 | 11 | 236 | 13 | 0 | 0 | 0 | 6 | 4 | 8 | 0 | 0 | 0 | 14 | 214 | 3 | 4 | 0 | 0 | 2 | 2 | 7 | 0 | 0 | 0 | 524 |
| 11:45:00 | 7 | 213 | 8 | 0 | 0 | 0 | 4 | 3 | 13 | 0 | 0 | 0 | 19 | 238 | 5 | 7 | 0 | 0 | 6 | 4 | 6 | 0 | 0 | 0 | 533 |
| 12:00:00 | 7 | 239 | 7 | 0 | 0 | 0 | 8 | 3 | 13 | 0 | 0 | 0 | 14 | 229 | 7 | 6 | 0 | 0 | 4 | 2 | 7 | 0 | 0 | 0 | 546 |
| 12:15:00 | 9 | 216 | 9 | 0 | 0 | 0 | 6 | 2 | 8 | 0 | 0 | 0 | 15 | 298 | 6 | 9 | 0 | 0 | 6 | 5 | 2 | 0 | 0 | 0 | 591 |
| 12:30:00 | 7 | 275 | 8 | 0 | 0 | 0 | 14 | 2 | 12 | 0 | 0 | 0 | 1 | 256 | 9 | 8 | 0 | 0 | 8 | 1 | 6 | 0 | 0 | 0 | 607 |
| 12:45:00 | 7 | 253 | 8 | 0 | 0 | 0 | 8 | 2 | 14 | 0 | 0 | 0 | 3 | 277 | 6 | 7 | 0 | 0 | 8 | 3 | 6 | 0 | 0 | 0 | 602 |
| 13:00:00 | 5 | 270 | 9 | 0 | 0 | 0 | 9 | 2 | 8 | 0 | 0 | 0 | 5 | 266 | 5 | 11 | 0 | 0 | 6 | 2 | 12 | 0 | 0 | 0 | 610 |
| 13:15:00 | 10 | 245 | 7 | 0 | 0 | 0 | 17 | 3 | 11 | 0 | 0 | 0 | 12 | 245 | 5 | 11 | 0 | 0 | 3 | 3 | 4 | 0 | 0 | 0 | 576 |
| 13:30:00 | 12 | 264 | 5 | 0 | 0 | 0 | 6 | 6 | 9 | 0 | 0 | 0 | 11 | 229 | 10 | 4 | 0 | 0 | 12 | 2 | 7 | 0 | 0 | 0 | 577 |
| 13:45:00 | 9 | 268 | 7 | 0 | 0 | 0 | 5 | 4 | 10 | 0 | 0 | 0 | 14 | 268 | 6 | 7 | 0 | 0 | 3 | 4 | 7 | 0 | 0 | 0 | 612 |
| 14:00:00 | 7 | 258 | 8 | 0 | 0 | 0 | 13 | 3 | 10 | 0 | 0 | 0 | 15 | 275 | 5 | 8 | 0 | 0 | 3 | 5 | 4 | 0 | 0 | 0 | 614 |
| 14:15:00 | 9 | 246 | 6 | 0 | 0 | 0 | 12 | 2 | 4 | 0 | 0 | 0 | 8 | 274 | 7 | 6 | 0 | 0 | 1 | 4 | 5 | 0 | 0 | 0 | 584 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.971906 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | 7 | 252 | 6 | 0 | 0 | 0 | 11 | 4 | 12 | 0 | 0 | 0 | 6 | 297 | 4 | 6 | 0 | 0 | 4 | 6 | 2 | 0 | 0 | 0 | 617 |
| 14:45:00 | 6 | 254 | 7 | 0 | 0 | 0 | 6 | 1 | 18 | 0 | 0 | 0 | 13 | 267 | 3 | 5 | 0 | 0 | 0 | 2 | 5 | 0 | 0 | 0 | 587 |
| 15:00:00 | 7 | 250 | 11 | 0 | 0 | 0 | 4 | 1 | 6 | 0 | 0 | 0 | 3 | 265 | 5 | 12 | 0 | 0 | 1 | 4 | 1 | 0 | 0 | 0 | 570 |
| 15:15:00 | 6 | 249 | 2 | 1 | 0 | 0 | 15 | 3 | 17 | 0 | 0 | 0 | 11 | 259 | 7 | 8 | 0 | 0 | 6 | 1 | 12 | 0 | 0 | 0 | 597 |
| 15:30:00 | 6 | 266 | 10 | 0 | 0 | 0 | 2 | 5 | 14 | 0 | 0 | 0 | 9 | 258 | 7 | 3 | 0 | 0 | 3 | 1 | 7 | 0 | 0 | 0 | 591 |
| 15:45:00 | 8 | 269 | 8 | 0 | 0 | 0 | 6 | 1 | 11 | 0 | 0 | 0 | 7 | 251 | 9 | 5 | 0 | 0 | 6 | 1 | 2 | 0 | 0 | 0 | 584 |
| 16:00:00 | 6 | 252 | 15 | 1 | 0 | 0 | 8 | 1 | 7 | 0 | 0 | 0 | 9 | 260 | 6 | 8 | 0 | 0 | 1 | 2 | 8 | 0 | 0 | 0 | 584 |
| 16:15:00 | 8 | 227 | 2 | 0 | 0 | 0 | 10 | 1 | 9 | 0 | 0 | 0 | 3 | 216 | 5 | 10 | 0 | 0 | 4 | 2 | 3 | 0 | 0 | 0 | 500 |
| 16:30:00 | 7 | 292 | 5 | 0 | 0 | 0 | 19 | 1 | 9 | 0 | 0 | 0 | 8 | 232 | 0 | 3 | 0 | 0 | 0 | 4 | 2 | 0 | 0 | 0 | 582 |
| 16:45:00 | 5 | 234 | 8 | 0 | 0 | 0 | 7 | 0 | 9 | 0 | 0 | 0 | 10 | 246 | 6 | 7 | 0 | 0 | 7 | 2 | 4 | 0 | 0 | 0 | 545 |
| 17:00:00 | 7 | 233 | 4 | 0 | 0 | 0 | 11 | 2 | 11 | 0 | 0 | 0 | 7 | 220 | 5 | 10 | 0 | 0 | 5 | 6 | 2 | 0 | 0 | 0 | 523 |
| 17:15:00 | 8 | 193 | 8 | 0 | 0 | 0 | 6 | 4 | 5 | 0 | 0 | 0 | 10 | 232 | 1 | 8 | 0 | 0 | 4 | 6 | 4 | 0 | 0 | 0 | 489 |
| 17:30:00 | 7 | 218 | 7 | 0 | 0 | 0 | 14 | 6 | 6 | 0 | 0 | 0 | 6 | 243 | 4 | 7 | 0 | 0 | 2 | 1 | 5 | 0 | 0 | 0 | 526 |
| 17:45:00 | 5 | 207 | 7 | 0 | 0 | 0 | 9 | 4 | 7 | 0 | 0 | 0 | 5 | 226 | 4 | 4 | 0 | 0 | 3 | 2 | 2 | 0 | 0 | 0 | 485 |
| 18:00:00 | 3 | 186 | 3 | 0 | 0 | 0 | 11 | 2 | 6 | 0 | 0 | 0 | 13 | 228 | 3 | 8 | 0 | 0 | 6 | 1 | 3 | 0 | 0 | 0 | 473 |
| 18:15:00 | 2 | 205 | 11 | 0 | 0 | 0 | 12 | 1 | 8 | 0 | 0 | 0 | 1 | 208 | 1 | 1 | 0 | 0 | 2 | 3 | 1 | 0 | 0 | 0 | 456 |
| 18:30:00 | 4 | 214 | 8 | 0 | 0 | 0 | 9 | 2 | 10 | 0 | 0 | 0 | 2 | 122 | 3 | 6 | 0 | 0 | 8 | 3 | 2 | 0 | 0 | 0 | 393 |
| 18:45:00 | 1 | 213 | 6 | 0 | 0 | 0 | 3 | 3 | 3 | 0 | 0 | 0 | 2 | 100 | 3 | 1 | 0 | 0 | 4 | 1 | 2 | 0 | 0 | 0 | 342 |
| 19:00:00 | 6 | 187 | 6 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 1 | 60 | 2 | 1 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 270 |
| 19:15:00 | 3 | 165 | 4 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 2 | 50 | 4 | 3 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 236 |
| 19:30:00 | 7 | 149 | 2 | 0 | 0 | 0 | 1 | 0 | 6 | 0 | 0 | 0 | 3 | 85 | 4 | 0 | 0 | 0 | 2 | 1 | 2 | 0 | 0 | 0 | 262 |
| 19:45:00 | 2 | 147 | 3 | 0 | 0 | 0 | 1 | 0 | 2 | 0 | 0 | 0 | 1 | 61 | 1 | 1 | 0 | 0 | 2 | 0 | 3 | 0 | 0 | 0 | 224 |
| 20:00:00 | 1 | 123 | 4 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 49 | 3 | 1 | 0 | 0 | 4 | 1 | 3 | 0 | 0 | 0 | 190 |
| 20:15:00 | 2 | 141 | 2 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 1 | 50 | 6 | 1 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 208 |
| 20:30:00 | 1 | 124 | 0 | 0 | 0 | 0 | 0 | 3 | 3 | 0 | 0 | 0 | 0 | 61 | 2 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 195 |
| 20:45:00 | 0 | 124 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 4 | 50 | 2 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 184 |
| 21:00:00 | 1 | 114 | 2 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 1 | 22 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 146 |
| 21:15:00 | 2 | 96 | 2 | 0 | 0 | 0 | 1 | 0 | 2 | 0 | 0 | 0 | 2 | 30 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 138 |
| 21:30:00 | 0 | 93 | 2 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 3 | 36 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 136 |
| 21:45:00 | 2 | 89 | 2 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 31 | 2 | 2 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 133 |
| 22:00:00 | 1 | 101 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 22 | 3 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 133 |
| 22:15:00 | 1 | 67 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 19 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 91 |
| 22:30:00 | 3 | 62 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 18 | 1 | 1 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 88 |
| 22:45:00 | 1 | 54 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 14 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 74 |
| 23:00:00 | 1 | 62 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 21 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 88 |
| 23:15:00 | 0 | 68 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 11 | 3 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 85 |
| 23:30:00 | 0 | 59 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 25 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 86 |
| 23:45:00 | 3 | 58 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 19 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 84 |

| Lights | HV |
|---|---|
| 576 | 1 |
| 607 | 5 |
| 584 | 0 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/26/2023 0:00
End Time 10/26/2023 23:59
Location 05-53-282 Rt 62 (NFB) @ Treadwell Rd
Latitude an 42.98670806,-78.82272476
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total | | |
| 0:00:00 | | 1 | 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | | |
| 0:15:00 | | 0 | 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 4 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 17 | | |
| 0:30:00 | | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | | |
| 0:45:00 | | 1 | 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | | |
| 1:00:00 | | 0 | 9 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | | |
| 1:15:00 | | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | | |
| 1:30:00 | | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 6 | | |
| 1:45:00 | | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 4 | | |
| 2:00:00 | | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | | |
| 2:15:00 | | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | | |
| 2:30:00 | | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | | |
| 2:45:00 | | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 3 | | |
| 3:00:00 | | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | | |
| 3:15:00 | | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | | |
| 3:30:00 | | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | | |
| 3:45:00 | | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | | |
| 4:00:00 | | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 6 | | |
| 4:15:00 | | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 5 | | |
| 4:30:00 | | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 3 | | |
| 4:45:00 | | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | | |
| 5:00:00 | | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 5 | | |
| 5:15:00 | | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | | |
| 5:30:00 | | 0 | 8 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 17 | | |
| 5:45:00 | | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 10 | | |
| 6:00:00 | | 0 | 18 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 24 | | |
| 6:15:00 | | 1 | 19 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 3 | 2 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 32 | | |
| 6:30:00 | | 0 | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 38 | | |
| 6:45:00 | | 1 | 38 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 10 | 1 | 0 | 0 | 0 | 1 | 0 | 2 | 0 | 0 | 56 | | |
| 7:00:00 | | 2 | 43 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 57 | | |
| 7:15:00 | | 1 | 85 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 15 | 2 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 109 | | |
| 7:30:00 | | 2 | 170 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 54 | 0 | 1 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 238 | | |
| 7:45:00 | | 7 | 189 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 142 | 1 | 4 | 0 | 0 | 10 | 1 | 2 | 0 | 0 | 362 | | |
| 8:00:00 | | 5 | 112 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 4 | 131 | 3 | 1 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 264 | | |
| 8:15:00 | | 2 | 153 | 1 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 1 | 142 | 0 | 3 | 0 | 0 | 5 | 0 | 2 | 0 | 0 | 312 | | |
| 8:30:00 | | 5 | 141 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 152 | 2 | 3 | 0 | 0 | 4 | 0 | 3 | 0 | 0 | 313 | | |
| 8:45:00 | | 2 | 153 | 5 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 3 | 168 | 1 | 4 | 0 | 0 | 4 | 1 | 1 | 0 | 0 | 346 | | |
| 9:00:00 | | 5 | 142 | 5 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 4 | 139 | 2 | 7 | 0 | 0 | 3 | 5 | 3 | 0 | 0 | 318 | | |
| 9:15:00 | | 5 | 131 | 4 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 3 | 140 | 3 | 3 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 300 | | |
| 9:30:00 | | 7 | 119 | 1 | 0 | 0 | 0 | 3 | 2 | 2 | 0 | 0 | 0 | 1 | 158 | 3 | 4 | 0 | 0 | 5 | 5 | 4 | 0 | 0 | 314 | | |
| 9:45:00 | | 7 | 137 | 5 | 0 | 0 | 0 | 4 | 1 | 5 | 0 | 0 | 0 | 5 | 167 | 5 | 5 | 0 | 0 | 3 | 2 | 1 | 0 | 0 | 347 | | |
| 10:00:00 | | 4 | 146 | 5 | 0 | 0 | 0 | 1 | 1 | 4 | 0 | 0 | 0 | 6 | 171 | 2 | 8 | 0 | 0 | 5 | 4 | 6 | 0 | 0 | 363 | | |
| 10:15:00 | | 5 | 171 | 2 | 0 | 0 | 0 | 2 | 1 | 2 | 0 | 0 | 0 | 6 | 165 | 3 | 3 | 0 | 0 | 9 | 2 | 2 | 0 | 0 | 373 | | |
| 10:30:00 | | 9 | 162 | 5 | 0 | 0 | 0 | 5 | 1 | 4 | 0 | 0 | 0 | 2 | 169 | 2 | 0 | 0 | 0 | 4 | 3 | 7 | 0 | 0 | 373 | | |
| 10:45:00 | | 6 | 164 | 8 | 0 | 0 | 0 | 4 | 1 | 6 | 0 | 0 | 0 | 6 | 167 | 2 | 2 | 0 | 0 | 4 | 1 | 1 | 0 | 0 | 372 | | |
| 11:00:00 | | 6 | 177 | 8 | 0 | 0 | 0 | 8 | 0 | 8 | 0 | 0 | 0 | 8 | 191 | 5 | 9 | 0 | 0 | 4 | 2 | 2 | 0 | 0 | 428 | | |
| 11:15:00 | | 7 | 195 | 5 | 0 | 0 | 0 | 2 | 2 | 9 | 0 | 0 | 0 | 7 | 193 | 5 | 2 | 0 | 0 | 5 | 7 | 6 | 0 | 0 | 445 | | |
| 11:30:00 | | 4 | 196 | 9 | 0 | 0 | 0 | 7 | 2 | 11 | 0 | 0 | 0 | 7 | 211 | 5 | 4 | 0 | 0 | 4 | 2 | 2 | 0 | 0 | 464 | | |
| 11:45:00 | | 7 | 185 | 11 | 0 | 0 | 0 | 3 | 3 | 9 | 0 | 0 | 0 | 8 | 194 | 3 | 3 | 0 | 0 | 4 | 5 | 5 | 0 | 0 | 440 | | |
| 12:00:00 | | 1 | 203 | 11 | 0 | 0 | 0 | 3 | 2 | 3 | 0 | 0 | 0 | 12 | 251 | 2 | 5 | 0 | 0 | 4 | 4 | 4 | 0 | 0 | 505 | | |
| 12:15:00 | | 2 | 203 | 5 | 0 | 0 | 0 | 13 | 5 | 9 | 0 | 0 | 0 | 8 | 198 | 5 | 2 | 0 | 0 | 3 | 8 | 1 | 0 | 0 | 462 | | |
| 12:30:00 | | 6 | 236 | 7 | 0 | 0 | 0 | 4 | 2 | 8 | 0 | 0 | 0 | 3 | 218 | 4 | 6 | 0 | 0 | 1 | 5 | 2 | 0 | 0 | 502 | | |
| 12:45:00 | | 5 | 261 | 4 | 0 | 0 | 0 | 8 | 3 | 6 | 0 | 0 | 0 | 3 | 222 | 2 | 12 | 0 | 0 | 4 | 2 | 6 | 0 | 0 | 538 | | |
| 13:00:00 | | 3 | 223 | 7 | 0 | 0 | 0 | 6 | 3 | 9 | 0 | 0 | 0 | 6 | 204 | 4 | 8 | 0 | 0 | 7 | 3 | 4 | 0 | 0 | 487 | | |
| 13:15:00 | | 14 | 192 | 6 | 0 | 0 | 0 | 6 | 1 | 5 | 0 | 0 | 0 | 3 | 230 | 5 | 12 | 0 | 0 | 3 | 5 | 8 | 0 | 0 | 490 | | |
| 13:30:00 | | 9 | 186 | 6 | 0 | 0 | 0 | 7 | 2 | 7 | 0 | 0 | 0 | 3 | 234 | 6 | 6 | 0 | 0 | 5 | 6 | 3 | 0 | 0 | 480 | | |
| 13:45:00 | | 5 | 231 | 5 | 0 | 0 | 0 | 6 | 2 | 7 | 0 | 0 | 0 | 8 | 200 | 4 | 8 | 0 | 0 | 4 | 0 | 8 | 0 | 0 | 488 | | |
| 14:00:00 | | 8 | 246 | 7 | 0 | 0 | 0 | 6 | 3 | 9 | 0 | 0 | 0 | 4 | 178 | 4 | 0 | 0 | 0 | 5 | 6 | 5 | 0 | 0 | 481 | | |
| 14:15:00 | | 4 | 219 | 7 | 0 | 0 | 0 | 8 | 4 | 6 | 0 | 0 | 0 | 5 | 199 | 7 | 12 | 0 | 0 | 5 | 0 | 5 | 0 | 0 | 481 | | |
| 14:30:00 | | 6 | 267 | 7 | 0 | 0 | 0 | 7 | 3 | 6 | 0 | 0 | 0 | 2 | 230 | 5 | 6 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 545 | | |
| 14:45:00 | | 5 | 299 | 10 | 0 | 0 | 0 | 8 | 3 | 13 | 0 | 0 | 0 | 4 | 235 | 3 | 4 | 0 | 0 | 5 | 4 | 5 | 0 | 0 | 598 | | |
| 3:00 PM | | 7 | 285 | 5 | 0 | 0 | 0 | 3 | 1 | 7 | 0 | 0 | 0 | 10 | 211 | 5 | 7 | 0 | 0 | 9 | 6 | 6 | 0 | 0 | 0 | 562 | |
| 3:15 PM | | 8 | 278 | 10 | 0 | 0 | 0 | 9 | 7 | 13 | 0 | 0 | 0 | 5 | 227 | 3 | 4 | 0 | 0 | 4 | 5 | 4 | 0 | 0 | 0 | 577 | |
| 3:30 PM | | 8 | 288 | 8 | 0 | 0 | 0 | 12 | 1 | 6 | 0 | 0 | 0 | 5 | 229 | 5 | 8 | 0 | 0 | 4 | 2 | 3 | 0 | 0 | 0 | 579 | |
| 3:45 PM | | 10 | 279 | 5 | 0 | 0 | 0 | 8 | 8 | 9 | 0 | 0 | 0 | 5 | 244 | 4 | 2 | 0 | 0 | 2 | 2 | 5 | 0 | 0 | 0 | 583 | |
| 4:00 PM | | 12 | 285 | 4 | 0 | 0 | 0 | 11 | 5 | 16 | 0 | 0 | 0 | 1 | 215 | 3 | 9 | 0 | 0 | 4 | 2 | 7 | 0 | 0 | 0 | 574 | |
| 4:15 PM | | 9 | 290 | 6 | 0 | 0 | 0 | 4 | 5 | 2 | 0 | 0 | 0 | 1 | 254 | 4 | 9 | 0 | 0 | 5 | 2 | 3 | 0 | 0 | 0 | 594 | **Lights** HV |
| 4:30 PM | | 4 | 301 | 4 | 0 | 0 | 0 | 2 | 3 | 5 | 0 | 0 | 0 | 6 | 251 | 5 | 6 | 0 | 0 | 4 | 4 | 3 | 0 | 0 | 0 | 598 | 596 2 |
| 4:45 PM | | 10 | 244 | 6 | 0 | 0 | 0 | 1 | 1 | 10 | 0 | 0 | 0 | 5 | 229 | 3 | 2 | 0 | 0 | 4 | 4 | 8 | 0 | 0 | 0 | 527 | 521 6 |
| 5:00 PM | | 8 | 271 | 8 | 0 | 0 | 0 | 10 | 4 | 11 | 0 | 0 | 0 | 3 | 231 | 4 | 7 | 0 | 0 | 8 | 4 | 6 | 0 | 0 | 0 | 575 | 572 3 |
| 5:15 PM | | 5 | 265 | 2 | 0 | 0 | 0 | 8 | 3 | 16 | 0 | 0 | 0 | 4 | 239 | 6 | 6 | 0 | 0 | 4 | 2 | 4 | 0 | 0 | 0 | 564 | 560 4 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.946488 | | |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% | | |
| 5:30 PM | | 3 | 228 | 6 | 0 | 0 | 0 | 5 | 3 | 6 | 0 | 0 | 0 | 5 | 225 | 6 | 9 | 0 | 0 | 4 | 1 | 1 | 0 | 0 | 0 | 502 | |
| 5:45 PM | | 5 | 238 | 9 | 0 | 0 | 0 | 6 | 4 | 11 | 0 | 0 | 0 | 5 | 195 | 4 | 2 | 0 | 0 | 6 | 4 | 2 | 0 | 0 | 0 | 491 | |
| 18:00:00 | | 3 | 211 | 10 | 0 | 0 | 0 | 6 | 4 | 9 | 0 | 0 | 0 | 7 | 221 | 6 | 5 | 0 | 0 | 1 | 3 | 4 | 0 | 0 | 0 | 490 | |
| 18:15:00 | | 14 | 184 | 4 | 0 | 0 | 0 | 6 | 3 | 12 | 0 | 0 | 0 | 1 | 202 | 6 | 3 | 0 | 0 | 5 | 2 | 6 | 0 | 0 | 0 | 448 | |
| 18:30:00 | | 8 | 176 | 5 | 0 | 0 | 0 | 1 | 3 | 5 | 0 | 0 | 0 | 2 | 114 | 1 | 2 | 0 | 0 | 6 | 2 | 4 | 0 | 0 | 0 | 329 | |
| 18:45:00 | | 4 | 194 | 6 | 0 | 0 | 0 | 6 | 3 | 6 | 0 | 0 | 0 | 7 | 70 | 1 | 1 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 0 | 304 | |
| 19:00:00 | | 4 | 156 | 3 | 0 | 0 | 0 | 1 | 5 | 4 | 0 | 0 | 0 | 3 | 64 | 5 | 1 | 0 | 0 | 2 | 1 | 3 | 0 | 0 | 0 | 252 | |
| 19:15:00 | | 5 | 188 | 1 | 0 | 0 | 0 | 2 | 2 | 3 | 0 | 0 | 0 | 10 | 56 | 5 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 275 | |
| 19:30:00 | | 5 | 143 | 7 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 3 | 47 | 1 | 0 | 0 | 0 | 2 | 0 | 3 | 0 | 0 | 0 | 213 | |
| 19:45:00 | | 1 | 154 | 2 | 0 | 0 | 0 | 1 | 0 | 4 | 0 | 0 | 0 | 4 | 39 | 1 | 2 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 212 | |
| 20:00:00 | | 3 | 126 | 1 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 2 | 36 | 3 | 2 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 182 | |
| 20:15:00 | | 2 | 92 | 1 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 1 | 25 | 2 | 0 | 0 | 0 | 1 | 1 | 2 | 0 | 0 | 0 | 130 | |
| 20:30:00 | | 0 | 88 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 4 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 112 | |
| 20:45:00 | | 1 | 94 | 6 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 15 | 0 | 3 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 127 | |
| 21:00:00 | | 1 | 80 | 2 | 0 | 0 | 0 | 1 | 2 | 3 | 0 | 0 | 0 | 0 | 29 | 2 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 123 | |
| 21:15:00 | | 0 | 77 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 21 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 103 | |
| 21:30:00 | | 1 | 60 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 17 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 84 | |
| 21:45:00 | | 1 | 81 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 15 | 1 | 2 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 102 | |
| 22:00:00 | | 1 | 53 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 23 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 81 | |
| 22:15:00 | | 1 | 59 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 73 | |
| 22:30:00 | | 0 | 41 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 14 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 58 | |
| 22:45:00 | | 0 | 39 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 55 | |
| 23:00:00 | | 0 | 44 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 56 | |
| 23:15:00 | | 2 | 35 | 1 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 7 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 52 | |
| 23:30:00 | | 3 | 52 | 1 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 1 | 11 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 75 | |
| 23:45:00 | | 3 | 39 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 57 | |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time ########
End Time ########
Location 05-53-298P Rt 62 (NFB) @ Boulevard Mall
Latitude an 42.98879028, -78.8225715
Lights

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total | |
| 0:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | |
| 0:15:00 | 0 | 3 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | |
| 0:30:00 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 4 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 9 | |
| 0:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17 | |
| 1:00:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | |
| 1:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | |
| 1:30:00 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | |
| 1:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 3 | |
| 2:00:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | |
| 2:15:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | |
| 2:30:00 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | |
| 2:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | |
| 3:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 3:15:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 3:30:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | |
| 3:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 4:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 4:15:00 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | |
| 4:30:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 4:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 5:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 5:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 5:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 5:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | |
| 6:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 6:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 6:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 6:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 7:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | |
| 7:15:00 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | |
| 7:30:00 | 0 | 19 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 51 | |
| 7:45:00 | 1 | 47 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 59 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 110 | |
| 8:00:00 | 0 | 58 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 66 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 124 | |
| 8:15:00 | 1 | 54 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 70 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 126 | |
| 8:30:00 | 0 | 86 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 91 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 178 | |
| 8:45:00 | 0 | 91 | 6 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 113 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 217 | |
| 9:00:00 | 0 | 96 | 5 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 128 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 234 | |
| 9:15:00 | 1 | 115 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 157 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 280 | |
| 9:30:00 | 4 | 143 | 2 | 3 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 161 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 317 | |
| 9:45:00 | 3 | 165 | 3 | 1 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 2 | 188 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 366 | |
| 10:00:00 | 2 | 147 | 8 | 2 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 164 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 327 | |
| 10:15:00 | 4 | 180 | 12 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 5 | 182 | 3 | 3 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 396 | |
| 10:30:00 | 4 | 194 | 9 | 1 | 0 | 0 | 4 | 1 | 2 | 0 | 0 | 0 | 6 | 220 | 0 | 0 | 0 | 0 | 3 | 0 | 3 | 0 | 0 | 0 | 447 | |
| 10:45:00 | 10 | 178 | 10 | 2 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 5 | 217 | 2 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 432 | |
| 11:00:00 | 9 | 207 | 9 | 3 | 0 | 0 | 6 | 0 | 2 | 0 | 0 | 0 | 10 | 251 | 4 | 1 | 0 | 0 | 7 | 0 | 2 | 0 | 0 | 0 | 511 | |
| 11:15:00 | 6 | 216 | 9 | 8 | 0 | 0 | 6 | 0 | 4 | 0 | 0 | 0 | 4 | 211 | 0 | 2 | 0 | 0 | 7 | 1 | 0 | 0 | 0 | 0 | 474 | |
| 11:30:00 | 9 | 224 | 7 | 2 | 0 | 0 | 6 | 1 | 11 | 0 | 0 | 0 | 9 | 264 | 4 | 1 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 544 | |
| 11:45:00 | 8 | 220 | 9 | 4 | 0 | 0 | 8 | 0 | 5 | 0 | 0 | 0 | 5 | 272 | 1 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 537 | |
| 12:00:00 | 4 | 231 | 10 | 2 | 0 | 0 | 11 | 1 | 4 | 0 | 0 | 0 | 13 | 247 | 3 | 2 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 531 | |
| 12:15:00 | 2 | 222 | 7 | 2 | 0 | 0 | 8 | 0 | 6 | 0 | 0 | 0 | 6 | 308 | 2 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 567 | |
| 12:30:00 | 6 | 273 | 18 | 2 | 0 | 0 | 8 | 1 | 5 | 0 | 0 | 0 | 7 | 259 | 1 | 0 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 0 | 586 | |
| 12:45:00 | 6 | 254 | 12 | 7 | 0 | 0 | 11 | 0 | 7 | 0 | 0 | 0 | 9 | 266 | 5 | 0 | 0 | 0 | 5 | 0 | 2 | 0 | 0 | 0 | 584 | |
| 13:00:00 | 4 | 268 | 17 | 3 | 0 | 0 | 7 | 3 | 6 | 0 | 0 | 0 | 11 | 284 | 2 | 1 | 0 | 0 | 6 | 1 | 3 | 0 | 0 | 0 | 616 | |
| 13:15:00 | 8 | 252 | 11 | 3 | 0 | 0 | 7 | 1 | 6 | 0 | 0 | 0 | 9 | 266 | 2 | 1 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 570 | **Lights** HV |
| 13:30:00 | 8 | 264 | 11 | 5 | 0 | 0 | 5 | 0 | 12 | 0 | 0 | 0 | 6 | 254 | 2 | 0 | 0 | 0 | 5 | 0 | 4 | 0 | 0 | 0 | 576 | 575 1 |
| 13:45:00 | 6 | 257 | 9 | 5 | 0 | 0 | 6 | 3 | 9 | 0 | 0 | 0 | 7 | 278 | 0 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 586 | 582 4 |
| 14:00:00 | 3 | 260 | 9 | 1 | 0 | 0 | 10 | 3 | 5 | 0 | 0 | 0 | 7 | 302 | 0 | 0 | 0 | 0 | 2 | 1 | 3 | 0 | 0 | 0 | 606 | 606 0 |
| 14:15:00 | 7 | 237 | 12 | 5 | 0 | 0 | 15 | 1 | 4 | 0 | 0 | 0 | 5 | 282 | 4 | 1 | 0 | 0 | 3 | 1 | 1 | 0 | 0 | 0 | 578 | 575 3 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.967822 | |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% | |
| 14:30:00 | 9 | 253 | 11 | 3 | 0 | 0 | 14 | 1 | 3 | 0 | 0 | 0 | 7 | 298 | 3 | 1 | 0 | 0 | 4 | 1 | 2 | 0 | 0 | 0 | 610 | |
| 14:45:00 | 6 | 254 | 10 | 2 | 0 | 0 | 14 | 2 | 7 | 0 | 0 | 0 | 9 | 286 | 1 | 1 | 0 | 0 | 7 | 0 | 3 | 0 | 0 | 0 | 602 | |
| 15:00:00 | 4 | 259 | 6 | 6 | 0 | 0 | 5 | 2 | 8 | 0 | 0 | 0 | 12 | 260 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 565 | |
| 15:15:00 | 5 | 234 | 12 | 7 | 0 | 0 | 15 | 2 | 4 | 0 | 0 | 0 | 10 | 277 | 0 | 0 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 0 | 572 | |
| 15:30:00 | 3 | 267 | 11 | 8 | 0 | 0 | 14 | 0 | 5 | 0 | 0 | 0 | 8 | 265 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 585 | |
| 15:45:00 | 6 | 271 | 8 | 6 | 0 | 0 | 14 | 1 | 6 | 0 | 0 | 0 | 8 | 266 | 0 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 590 | |
| 16:00:00 | 5 | 272 | 11 | 2 | 0 | 0 | 10 | 1 | 0 | 0 | 0 | 0 | 8 | 265 | 0 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 577 | |
| 16:15:00 | 7 | 215 | 12 | 7 | 0 | 0 | 10 | 0 | 9 | 0 | 0 | 0 | 8 | 227 | 2 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 0 | 503 | |
| 16:30:00 | 11 | 260 | 16 | 0 | 0 | 0 | 11 | 0 | 6 | 0 | 0 | 0 | 6 | 247 | 1 | 0 | 0 | 0 | 6 | 0 | 3 | 0 | 0 | 0 | 567 | |
| 16:45:00 | 9 | 222 | 13 | 3 | 0 | 0 | 14 | 2 | 2 | 0 | 0 | 0 | 9 | 258 | 1 | 0 | 0 | 0 | 12 | 0 | 1 | 1 | 0 | 0 | 547 | |
| 17:00:00 | 6 | 154 | 18 | 1 | 0 | 0 | 11 | 0 | 7 | 0 | 0 | 0 | 6 | 199 | 0 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 406 | |
| 17:15:00 | 33 | 10 | 8 | 1 | 0 | 0 | 14 | 0 | 3 | 0 | 0 | 0 | 5 | 95 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 171 | |
| 17:30:00 | 22 | 56 | 9 | 1 | 0 | 0 | 14 | 1 | 2 | 0 | 0 | 0 | 3 | 177 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 288 | |
| 17:45:00 | 14 | 127 | 13 | 3 | 0 | 0 | 11 | 2 | 1 | 0 | 0 | 0 | 2 | 225 | 3 | 1 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 405 | |
| 18:00:00 | 1 | 187 | 12 | 4 | 0 | 0 | 8 | 0 | 4 | 0 | 0 | 0 | 6 | 236 | 0 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 462 | |
| 18:15:00 | 0 | 196 | 9 | 2 | 0 | 0 | 7 | 2 | 6 | 0 | 0 | 0 | 4 | 221 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 450 | |
| 18:30:00 | 3 | 201 | 3 | 2 | 0 | 0 | 5 | 2 | 3 | 0 | 0 | 0 | 5 | 148 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 378 | |
| 18:45:00 | 4 | 194 | 5 | 1 | 0 | 0 | 13 | 2 | 5 | 0 | 0 | 0 | 5 | 111 | 3 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 349 | |
| 19:00:00 | 4 | 168 | 4 | 2 | 0 | 0 | 10 | 1 | 4 | 0 | 0 | 0 | 2 | 79 | 0 | 0 | 0 | 0 | 6 | 1 | 2 | 0 | 0 | 0 | 283 | |
| 19:15:00 | 1 | 156 | 2 | 0 | 0 | 0 | 6 | 2 | 3 | 0 | 0 | 0 | 1 | 74 | 0 | 0 | 0 | 0 | 8 | 0 | 1 | 0 | 0 | 0 | 254 | |
| 19:30:00 | 3 | 137 | 4 | 0 | 0 | 0 | 4 | 2 | 0 | 0 | 0 | 0 | 0 | 98 | 0 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 252 | |
| 19:45:00 | 1 | 146 | 6 | 1 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 1 | 64 | 1 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 227 | |
| 20:00:00 | 1 | 121 | 4 | 0 | 0 | 0 | 4 | 0 | 1 | 0 | 0 | 0 | 0 | 80 | 1 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 215 | |
| 20:15:00 | 1 | 131 | 2 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 0 | 48 | 1 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 190 | |
| 20:30:00 | 2 | 116 | 0 | 1 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 38 | 1 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 166 | |
| 20:45:00 | 3 | 103 | 2 | 1 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 3 | 50 | 1 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 173 | |
| 21:00:00 | 0 | 109 | 5 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 22 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 139 | |
| 21:15:00 | 1 | 103 | 3 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 0 | 33 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 145 | |
| 21:30:00 | 2 | 96 | 2 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 31 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 134 | |
| 21:45:00 | 0 | 89 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 26 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 115 | |
| 22:00:00 | 1 | 90 | 1 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 0 | 24 | 0 | 1 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 126 | |
| 22:15:00 | 0 | 64 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 22 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 89 | |
| 22:30:00 | 1 | 63 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 25 | 0 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 94 | |
| 22:45:00 | 0 | 57 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 75 | |
| 23:00:00 | 0 | 61 | 2 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 14 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 80 | |
| 23:15:00 | 0 | 65 | 2 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 23 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 93 | |
| 23:30:00 | 0 | 57 | 1 | 0 | 0 | 0 | 2 | 1 | 1 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 74 | |
| 23:45:00 | 0 | 51 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 17 | 2 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 73 | |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/26/2023 0:00
End Time 10/26/2023 23:59
Location 05-53-298P Rt 62 (NFB) @ Boulevard Mall
Latitude an 42.98879028,-78.8225715
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| 0:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0:45:00 | | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 2:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 2:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 2:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 2:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 3:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 3:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 3:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 3:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 4:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 4:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 4:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 4:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 5:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 5:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 5:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 5:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 |
| 6:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 5 |
| 6:15:00 | | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 |
| 6:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 3 |
| 6:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 12 |
| 7:00:00 | | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 |
| 7:15:00 | | 3 | 8 | 1 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 18 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 34 |
| 7:30:00 | | 8 | 124 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 64 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 202 |
| 7:45:00 | | 2 | 155 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 153 | 1 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 318 |
| 8:00:00 | | 1 | 100 | 1 | 2 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 152 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 259 |
| 8:15:00 | | 1 | 136 | 1 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 150 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 296 |
| 8:30:00 | | 1 | 128 | 0 | 2 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 2 | 156 | 0 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 296 |
| 8:45:00 | | 5 | 128 | 1 | 1 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 2 | 172 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 312 |
| 9:00:00 | | 3 | 111 | 4 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 153 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 280 |
| 9:15:00 | | 3 | 117 | 1 | 2 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 2 | 147 | 0 | 1 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 279 |
| 9:30:00 | | 2 | 104 | 3 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 7 | 183 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 302 |
| 9:45:00 | | 1 | 122 | 3 | 1 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 0 | 2 | 167 | 0 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 302 |
| 10:00:00 | | 5 | 131 | 2 | 1 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 5 | 186 | 1 | 0 | 0 | 0 | 3 | 1 | 2 | 0 | 0 | 343 |
| 10:15:00 | | 3 | 150 | 3 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 1 | 173 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 335 |
| 10:30:00 | | 5 | 150 | 4 | 3 | 0 | 0 | 3 | 3 | 1 | 0 | 0 | 0 | 7 | 175 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 354 |
| 10:45:00 | | 4 | 154 | 6 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 4 | 175 | 0 | 0 | 0 | 0 | 5 | 1 | 1 | 0 | 0 | 354 |
| 11:00:00 | | 4 | 178 | 6 | 1 | 0 | 0 | 6 | 1 | 1 | 0 | 0 | 0 | 6 | 201 | 1 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 408 |
| 11:15:00 | | 5 | 186 | 6 | 2 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 4 | 205 | 1 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 419 |
| 11:30:00 | | 4 | 189 | 6 | 0 | 0 | 0 | 5 | 1 | 5 | 0 | 0 | 0 | 6 | 220 | 0 | 1 | 0 | 0 | 4 | 0 | 1 | 0 | 0 | 442 |
| 11:45:00 | | 2 | 191 | 13 | 0 | 0 | 0 | 6 | 2 | 2 | 0 | 0 | 0 | 3 | 196 | 2 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 421 |
| 12:00:00 | | 6 | 199 | 9 | 1 | 0 | 0 | 2 | 2 | 2 | 0 | 0 | 0 | 8 | 265 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 498 |
| 12:15:00 | | 5 | 201 | 9 | 0 | 0 | 0 | 8 | 1 | 3 | 0 | 0 | 0 | 4 | 216 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 451 |
| 12:30:00 | | 6 | 228 | 7 | 0 | 0 | 0 | 8 | 0 | 5 | 0 | 0 | 0 | 7 | 216 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 479 |
| 12:45:00 | | 8 | 250 | 14 | 2 | 0 | 0 | 6 | 1 | 6 | 0 | 0 | 0 | 7 | 231 | 3 | 0 | 0 | 0 | 1 | 0 | 5 | 0 | 0 | 534 |
| 13:00:00 | | 3 | 218 | 4 | 2 | 0 | 0 | 9 | 2 | 2 | 0 | 0 | 0 | 5 | 218 | 2 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 471 |
| 13:15:00 | | 5 | 200 | 8 | 1 | 0 | 0 | 9 | 2 | 2 | 0 | 0 | 0 | 5 | 246 | 1 | 0 | 0 | 0 | 6 | 0 | 1 | 0 | 0 | 486 |
| 13:30:00 | | 1 | 199 | 9 | 3 | 0 | 0 | 10 | 1 | 3 | 0 | 0 | 0 | 9 | 226 | 0 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 466 |
| 13:45:00 | | 1 | 226 | 6 | 6 | 0 | 0 | 15 | 2 | 5 | 0 | 0 | 0 | 3 | 230 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 497 |
| 14:00:00 | | 2 | 248 | 7 | 5 | 0 | 0 | 4 | 1 | 3 | 0 | 0 | 0 | 10 | 193 | 1 | 0 | 0 | 0 | 2 | 0 | 1 | 0 | 0 | 477 |
| 14:15:00 | | 5 | 228 | 5 | 4 | 0 | 0 | 6 | 0 | 8 | 0 | 0 | 0 | 5 | 214 | 0 | 1 | 0 | 0 | 2 | 1 | 3 | 0 | 0 | 482 |
| 14:30:00 | | 4 | 269 | 7 | 3 | 0 | 0 | 10 | 0 | 6 | 0 | 0 | 0 | 7 | 243 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 554 |
| 14:45:00 | | 4 | 288 | 4 | 6 | 0 | 0 | 5 | 2 | 2 | 0 | 0 | 0 | 5 | 235 | 1 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 558 |
| 3:00 PM | | 3 | 301 | 6 | 2 | 0 | 0 | 9 | 1 | 8 | 0 | 0 | 0 | 4 | 231 | 3 | 1 | 0 | 0 | 1 | 0 | 3 | 0 | 0 | 573 |
| 3:15 PM | | 3 | 269 | 4 | 1 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 5 | 246 | 1 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 538 |
| 3:30 PM | | 6 | 296 | 8 | 2 | 0 | 0 | 10 | 0 | 3 | 0 | 0 | 0 | 9 | 233 | 0 | 0 | 0 | 0 | 2 | 0 | 3 | 0 | 0 | 572 |
| 3:45 PM | | 2 | 281 | 5 | 4 | 0 | 0 | 7 | 0 | 4 | 0 | 0 | 0 | 3 | 268 | 1 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 579 |
| 4:00 PM | | 5 | 298 | 7 | 0 | 0 | 0 | 6 | 1 | 6 | 0 | 0 | 0 | 5 | 231 | 2 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 563 |
| 4:15 PM | | 6 | 275 | 3 | 2 | 0 | 0 | 4 | 0 | 4 | 0 | 0 | 0 | 7 | 253 | 2 | 1 | 0 | 0 | 4 | 0 | 5 | 0 | 0 | 566 |
| 4:30 PM | | 2 | 297 | 4 | 1 | 0 | 0 | 8 | 2 | 3 | 0 | 0 | 0 | 4 | 255 | 1 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 580 |
| 4:45 PM | | 2 | 247 | 4 | 1 | 0 | 0 | 7 | 1 | 6 | 0 | 0 | 0 | 8 | 240 | 2 | 1 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 522 |
| 5:00 PM | | 5 | 273 | 11 | 7 | 0 | 0 | 6 | 0 | 6 | 0 | 0 | 0 | 7 | 241 | 1 | 0 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 560 |
| 5:15 PM | | 6 | 244 | 3 | 4 | 0 | 0 | 4 | 1 | 8 | 0 | 0 | 0 | 6 | 233 | 3 | 0 | 0 | 0 | 1 | 0 | 3 | 0 | 0 | 516 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.938793 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 5:30 PM | | 1 | 232 | 11 | 1 | 0 | 0 | 7 | 1 | 7 | 0 | 0 | 0 | 1 | 236 | 3 | 0 | 0 | 0 | 4 | 0 | 4 | 0 | 0 | 508 |
| 5:45 PM | | 6 | 237 | 9 | 6 | 0 | 0 | 8 | 0 | 2 | 0 | 0 | 0 | 1 | 200 | 1 | 0 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 473 |
| 18:00:00 | | 3 | 206 | 4 | 7 | 0 | 0 | 5 | 0 | 3 | 0 | 0 | 0 | 3 | 232 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 466 |
| 18:15:00 | | 3 | 176 | 6 | 3 | 0 | 0 | 5 | 1 | 1 | 0 | 0 | 0 | 1 | 206 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 403 |
| 18:30:00 | | 8 | 153 | 7 | 0 | 0 | 0 | 8 | 1 | 1 | 0 | 0 | 0 | 3 | 132 | 1 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 318 |
| 18:45:00 | | 7 | 162 | 3 | 0 | 0 | 0 | 8 | 2 | 3 | 0 | 0 | 0 | 1 | 69 | 2 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 262 |
| 19:00:00 | | 2 | 126 | 0 | 2 | 0 | 0 | 8 | 1 | 0 | 0 | 0 | 0 | 1 | 38 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 183 |
| 19:15:00 | | 3 | 146 | 3 | 0 | 0 | 0 | 1 | 0 | 2 | 0 | 0 | 0 | 0 | 51 | 2 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 212 |
| 19:30:00 | | 2 | 136 | 1 | 0 | 0 | 0 | 5 | 0 | 2 | 0 | 0 | 0 | 0 | 35 | 2 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 187 |
| 19:45:00 | | 3 | 123 | 3 | 0 | 0 | 0 | 2 | 0 | 3 | 0 | 0 | 0 | 0 | 33 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 169 |
| 20:00:00 | | 7 | 101 | 2 | 0 | 0 | 0 | 4 | 1 | 2 | 0 | 0 | 0 | 0 | 24 | 2 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 144 |
| 20:15:00 | | 1 | 81 | 1 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 0 | 1 | 15 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 104 |
| 20:30:00 | | 2 | 61 | 2 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 15 | 0 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 87 |
| 20:45:00 | | 1 | 84 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 99 |
| 21:00:00 | | 0 | 66 | 0 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 0 | 24 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 94 |
| 21:15:00 | | 1 | 78 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 9 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 93 |
| 21:30:00 | | 0 | 62 | 1 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 16 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 84 |
| 21:45:00 | | 0 | 82 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 100 |
| 22:00:00 | | 0 | 54 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 12 | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 71 |
| 22:15:00 | | 0 | 58 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 23 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 87 |
| 22:30:00 | | 0 | 37 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 60 |
| 22:45:00 | | 0 | 38 | 1 | 1 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 56 |
| 23:00:00 | | 0 | 42 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 54 |
| 23:15:00 | | 0 | 39 | 2 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 59 |
| 23:30:00 | | 0 | 58 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 16 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 76 |
| 23:45:00 | | 1 | 41 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 59 |

| | | |
|---|---|---|
| **Lights** | 577 | 3 |
| HV | 559 | 1 |
| | 518 | 4 |
| | 512 | 4 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/28/2023 0:00
End Time 10/28/2023 23:59
Location 05-53-424 Sweet Home Rd @ Maple Rd
Latitude an 42.99070136,-78.80420219
Lights

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 22 | 32 | 16 | 0 | 0 | 0 | 12 | 14 | 2 | 0 | 0 | 0 | 4 | 23 | 2 | 0 | 0 | 0 | 2 | 23 | 26 | 0 | 0 | 0 | 178 |
| 0:15:00 | 19 | 29 | 11 | 0 | 0 | 0 | 8 | 20 | 3 | 0 | 0 | 0 | 8 | 22 | 5 | 0 | 0 | 0 | 3 | 15 | 25 | 0 | 0 | 0 | 168 |
| 0:30:00 | 16 | 35 | 19 | 0 | 0 | 0 | 4 | 13 | 4 | 0 | 0 | 0 | 5 | 25 | 1 | 0 | 0 | 0 | 4 | 11 | 19 | 0 | 0 | 0 | 156 |
| 0:45:00 | 21 | 22 | 8 | 0 | 0 | 0 | 6 | 11 | 5 | 0 | 0 | 0 | 4 | 28 | 1 | 0 | 0 | 0 | 1 | 13 | 26 | 0 | 0 | 0 | 146 |
| 1:00:00 | 12 | 23 | 8 | 0 | 0 | 0 | 4 | 10 | 3 | 0 | 0 | 0 | 7 | 31 | 3 | 0 | 0 | 0 | 2 | 9 | 37 | 0 | 0 | 0 | 149 |
| 1:15:00 | 16 | 13 | 8 | 0 | 0 | 0 | 1 | 10 | 1 | 0 | 0 | 0 | 2 | 32 | 1 | 0 | 0 | 0 | 2 | 8 | 24 | 0 | 0 | 0 | 118 |
| 1:30:00 | 16 | 25 | 9 | 0 | 0 | 0 | 0 | 9 | 5 | 0 | 0 | 0 | 2 | 27 | 0 | 0 | 0 | 0 | 2 | 7 | 24 | 0 | 0 | 0 | 126 |
| 1:45:00 | 15 | 23 | 8 | 0 | 0 | 0 | 1 | 7 | 1 | 0 | 0 | 0 | 1 | 25 | 2 | 0 | 0 | 0 | 2 | 10 | 23 | 0 | 0 | 0 | 118 |
| 2:00:00 | 13 | 26 | 4 | 0 | 0 | 0 | 2 | 10 | 5 | 0 | 0 | 0 | 4 | 18 | 1 | 0 | 0 | 0 | 1 | 9 | 26 | 0 | 0 | 0 | 119 |
| 2:15:00 | 9 | 11 | 7 | 0 | 0 | 0 | 1 | 6 | 2 | 0 | 0 | 0 | 1 | 29 | 2 | 0 | 0 | 0 | 3 | 3 | 30 | 0 | 0 | 0 | 104 |
| 2:30:00 | 17 | 23 | 9 | 0 | 0 | 0 | 2 | 4 | 2 | 0 | 0 | 0 | 3 | 35 | 1 | 0 | 0 | 0 | 1 | 4 | 21 | 0 | 0 | 0 | 122 |
| 2:45:00 | 11 | 28 | 5 | 0 | 0 | 0 | 0 | 3 | 4 | 0 | 0 | 0 | 0 | 28 | 1 | 0 | 0 | 0 | 1 | 5 | 15 | 0 | 0 | 0 | 101 |
| 3:00:00 | 9 | 21 | 5 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 4 | 14 | 1 | 0 | 0 | 0 | 1 | 3 | 20 | 0 | 0 | 0 | 81 |
| 3:15:00 | 6 | 19 | 3 | 0 | 0 | 0 | 1 | 2 | 3 | 0 | 0 | 0 | 2 | 24 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 67 |
| 3:30:00 | 3 | 13 | 5 | 0 | 0 | 0 | 1 | 3 | 4 | 0 | 0 | 0 | 3 | 16 | 1 | 0 | 0 | 0 | 0 | 4 | 9 | 0 | 0 | 0 | 62 |
| 3:45:00 | 4 | 9 | 4 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 3 | 14 | 1 | 0 | 0 | 0 | 1 | 6 | 6 | 0 | 0 | 0 | 52 |
| 4:00:00 | 1 | 6 | 8 | 0 | 0 | 0 | 1 | 7 | 0 | 0 | 0 | 0 | 2 | 15 | 2 | 0 | 0 | 0 | 1 | 4 | 3 | 0 | 0 | 0 | 50 |
| 4:15:00 | 4 | 6 | 4 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 2 | 9 | 0 | 0 | 0 | 0 | 0 | 4 | 9 | 0 | 0 | 0 | 41 |
| 4:30:00 | 5 | 5 | 2 | 0 | 0 | 0 | 1 | 3 | 2 | 0 | 0 | 0 | 1 | 14 | 0 | 0 | 0 | 0 | 1 | 11 | 4 | 0 | 0 | 0 | 49 |
| 4:45:00 | 4 | 7 | 1 | 0 | 0 | 0 | 1 | 6 | 1 | 0 | 0 | 0 | 1 | 8 | 1 | 0 | 0 | 0 | 0 | 4 | 4 | 0 | 0 | 0 | 38 |
| 5:00:00 | 1 | 9 | 3 | 0 | 0 | 0 | 1 | 3 | 2 | 0 | 0 | 0 | 1 | 4 | 0 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 28 |
| 5:15:00 | 1 | 7 | 2 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 2 | 6 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 28 |
| 5:30:00 | 5 | 4 | 1 | 0 | 0 | 0 | 0 | 6 | 2 | 0 | 0 | 0 | 2 | 4 | 1 | 0 | 0 | 0 | 1 | 6 | 2 | 0 | 0 | 0 | 34 |
| 5:45:00 | 2 | 3 | 2 | 0 | 0 | 0 | 0 | 7 | 3 | 0 | 0 | 0 | 4 | 6 | 3 | 0 | 0 | 0 | 0 | 7 | 2 | 0 | 0 | 0 | 39 |
| 6:00:00 | 3 | 6 | 5 | 0 | 0 | 0 | 0 | 3 | 3 | 0 | 0 | 0 | 3 | 8 | 0 | 0 | 0 | 0 | 3 | 13 | 3 | 0 | 0 | 0 | 50 |
| 6:15:00 | 1 | 6 | 2 | 0 | 0 | 0 | 0 | 8 | 7 | 0 | 0 | 0 | 3 | 5 | 0 | 0 | 0 | 0 | 2 | 5 | 1 | 0 | 0 | 0 | 40 |
| 6:30:00 | 1 | 4 | 2 | 0 | 0 | 0 | 0 | 9 | 3 | 0 | 0 | 0 | 4 | 9 | 5 | 0 | 0 | 0 | 0 | 14 | 1 | 0 | 0 | 0 | 52 |
| 6:45:00 | 6 | 8 | 2 | 0 | 0 | 0 | 0 | 17 | 3 | 0 | 0 | 0 | 8 | 7 | 7 | 0 | 0 | 0 | 1 | 14 | 2 | 0 | 0 | 0 | 75 |
| 7:00:00 | 6 | 13 | 2 | 0 | 0 | 0 | 1 | 18 | 7 | 0 | 0 | 0 | 6 | 9 | 3 | 0 | 0 | 0 | 2 | 18 | 3 | 0 | 0 | 0 | 88 |
| 7:15:00 | 16 | 8 | 7 | 0 | 0 | 0 | 1 | 34 | 2 | 0 | 0 | 0 | 2 | 12 | 7 | 0 | 0 | 0 | 2 | 24 | 5 | 0 | 0 | 0 | 120 |
| 7:30:00 | 24 | 16 | 14 | 0 | 0 | 0 | 2 | 43 | 10 | 0 | 0 | 0 | 11 | 16 | 10 | 0 | 0 | 0 | 2 | 34 | 11 | 0 | 0 | 0 | 193 |
| 7:45:00 | 19 | 22 | 22 | 0 | 0 | 0 | 7 | 52 | 6 | 0 | 0 | 0 | 6 | 15 | 6 | 0 | 0 | 0 | 7 | 33 | 7 | 0 | 0 | 0 | 202 |
| 8:00:00 | 22 | 17 | 11 | 0 | 0 | 0 | 12 | 62 | 17 | 0 | 0 | 0 | 9 | 10 | 10 | 0 | 0 | 0 | 6 | 35 | 11 | 0 | 0 | 0 | 222 |
| 8:15:00 | 32 | 25 | 16 | 0 | 0 | 0 | 10 | 62 | 13 | 0 | 0 | 0 | 14 | 15 | 7 | 0 | 0 | 0 | 6 | 34 | 13 | 0 | 0 | 0 | 247 |
| 8:30:00 | 27 | 25 | 23 | 0 | 0 | 0 | 10 | 68 | 18 | 0 | 0 | 0 | 12 | 20 | 15 | 0 | 0 | 0 | 5 | 55 | 22 | 0 | 0 | 0 | 300 |
| 8:45:00 | 59 | 25 | 23 | 0 | 0 | 0 | 13 | 88 | 12 | 0 | 0 | 0 | 10 | 25 | 13 | 0 | 0 | 0 | 6 | 69 | 23 | 0 | 0 | 0 | 366 |
| 9:00:00 | 41 | 31 | 18 | 0 | 0 | 0 | 18 | 85 | 13 | 0 | 0 | 0 | 10 | 29 | 13 | 0 | 0 | 0 | 10 | 43 | 21 | 0 | 0 | 0 | 332 |
| 9:15:00 | 41 | 30 | 13 | 0 | 0 | 0 | 16 | 86 | 17 | 0 | 0 | 0 | 12 | 25 | 13 | 0 | 0 | 0 | 6 | 65 | 30 | 0 | 0 | 0 | 354 |
| 9:30:00 | 48 | 42 | 15 | 0 | 0 | 0 | 22 | 120 | 17 | 0 | 0 | 0 | 9 | 27 | 17 | 0 | 0 | 0 | 10 | 78 | 31 | 0 | 0 | 0 | 436 |
| 9:45:00 | 52 | 50 | 27 | 0 | 0 | 0 | 20 | 119 | 32 | 0 | 0 | 0 | 21 | 43 | 18 | 0 | 0 | 0 | 9 | 70 | 35 | 0 | 0 | 0 | 496 |
| 10:00:00 | 68 | 48 | 16 | 0 | 0 | 0 | 17 | 146 | 24 | 0 | 0 | 0 | 14 | 37 | 16 | 0 | 0 | 0 | 9 | 87 | 44 | 0 | 0 | 0 | 526 |
| 10:15:00 | 61 | 37 | 24 | 0 | 0 | 0 | 18 | 106 | 15 | 0 | 0 | 0 | 17 | 49 | 23 | 0 | 0 | 0 | 17 | 78 | 38 | 0 | 0 | 0 | 483 |
| 10:30:00 | 64 | 41 | 32 | 0 | 0 | 0 | 17 | 123 | 7 | 0 | 0 | 0 | 14 | 38 | 17 | 0 | 0 | 0 | 9 | 95 | 45 | 0 | 0 | 0 | 502 |
| 10:45:00 | 71 | 61 | 20 | 0 | 0 | 0 | 17 | 129 | 19 | 0 | 0 | 0 | 22 | 54 | 20 | 0 | 0 | 0 | 12 | 113 | 50 | 0 | 0 | 0 | 588 |
| 11:00:00 | 79 | 54 | 32 | 0 | 0 | 0 | 34 | 149 | 15 | 0 | 0 | 0 | 16 | 45 | 18 | 0 | 0 | 0 | 17 | 103 | 57 | 0 | 0 | 0 | 619 |
| 11:15:00 | 90 | 53 | 24 | 0 | 0 | 0 | 40 | 143 | 24 | 0 | 0 | 0 | 27 | 48 | 19 | 0 | 0 | 0 | 13 | 110 | 47 | 0 | 0 | 0 | 638 |
| 11:30:00 | 87 | 47 | 32 | 0 | 0 | 0 | 35 | 176 | 24 | 0 | 0 | 0 | 17 | 49 | 22 | 0 | 0 | 0 | 12 | 131 | 43 | 0 | 0 | 0 | 675 |
| 11:45:00 | 93 | 69 | 31 | 0 | 0 | 0 | 45 | 120 | 23 | 0 | 0 | 0 | 19 | 63 | 25 | 0 | 0 | 0 | 10 | 134 | 61 | 0 | 0 | 0 | 693 |
| 12:00:00 | 99 | 65 | 36 | 0 | 0 | 0 | 40 | 154 | 20 | 0 | 0 | 0 | 22 | 52 | 27 | 0 | 0 | 0 | 15 | 156 | 67 | 0 | 0 | 0 | 753 |
| 12:15:00 | 96 | 63 | 38 | 0 | 0 | 0 | 39 | 150 | 23 | 0 | 0 | 0 | 25 | 56 | 34 | 0 | 0 | 0 | 14 | 142 | 69 | 0 | 0 | 0 | 749 |
| 12:30:00 | 96 | 66 | 26 | 0 | 0 | 0 | 41 | 163 | 19 | 0 | 0 | 0 | 26 | 57 | 29 | 0 | 0 | 0 | 23 | 124 | 81 | 0 | 0 | 0 | 751 |
| 12:45:00 | 101 | 74 | 48 | 0 | 0 | 0 | 37 | 181 | 22 | 0 | 0 | 0 | 18 | 52 | 22 | 0 | 0 | 0 | 18 | 137 | 63 | 0 | 0 | 0 | 773 |
| 13:00:00 | 97 | 70 | 45 | 0 | 0 | 0 | 32 | 160 | 22 | 0 | 0 | 0 | 22 | 52 | 21 | 0 | 0 | 0 | 16 | 125 | 65 | 0 | 0 | 0 | 727 |
| 13:15:00 | 81 | 67 | 22 | 0 | 0 | 0 | 34 | 151 | 17 | 0 | 0 | 0 | 19 | 62 | 28 | 0 | 0 | 0 | 20 | 127 | 67 | 0 | 0 | 0 | 695 |
| 13:30:00 | 96 | 60 | 28 | 0 | 0 | 0 | 23 | 185 | 18 | 0 | 0 | 0 | 14 | 57 | 24 | 0 | 0 | 0 | 19 | 135 | 65 | 0 | 0 | 0 | 724 |
| 13:45:00 | 94 | 66 | 35 | 0 | 0 | 0 | 21 | 163 | 15 | 0 | 0 | 0 | 17 | 74 | 22 | 0 | 0 | 0 | 19 | 142 | 86 | 0 | 0 | 0 | 754 |
| 14:00:00 | 85 | 65 | 43 | 0 | 0 | 0 | 33 | 133 | 23 | 0 | 0 | 0 | 18 | 56 | 27 | 0 | 0 | 0 | 22 | 138 | 77 | 0 | 0 | 0 | 720 |
| 14:15:00 | 84 | 70 | 45 | 0 | 0 | 0 | 21 | 179 | 12 | 0 | 0 | 0 | 26 | 54 | 22 | 0 | 0 | 0 | 16 | 150 | 70 | 0 | 0 | 0 | 749 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.977122 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | 98 | 67 | 35 | 0 | 0 | 0 | 33 | 134 | 23 | 0 | 0 | 0 | 14 | 55 | 23 | 0 | 0 | 0 | 15 | 149 | 78 | 0 | 0 | 0 | 724 |
| 14:45:00 | 92 | 58 | 46 | 0 | 0 | 0 | 47 | 156 | 23 | 0 | 0 | 0 | 19 | 60 | 23 | 0 | 0 | 0 | 19 | 141 | 80 | 0 | 0 | 0 | 764 |
| 15:00:00 | 89 | 62 | 44 | 0 | 0 | 0 | 55 | 161 | 13 | 0 | 0 | 0 | 22 | 64 | 29 | 0 | 0 | 0 | 25 | 117 | 75 | 0 | 0 | 0 | 756 |
| 15:15:00 | 89 | 46 | 56 | 0 | 0 | 0 | 53 | 147 | 23 | 0 | 0 | 0 | 22 | 66 | 28 | 0 | 0 | 0 | 13 | 163 | 80 | 0 | 0 | 0 | 786 |
| 15:30:00 | 84 | 69 | 44 | 0 | 0 | 0 | 36 | 140 | 25 | 0 | 0 | 0 | 24 | 58 | 22 | 0 | 0 | 0 | 17 | 162 | 59 | 0 | 0 | 0 | 740 |
| 15:45:00 | 88 | 67 | 55 | 0 | 0 | 0 | 44 | 182 | 27 | 0 | 0 | 0 | 19 | 50 | 20 | 0 | 0 | 0 | 24 | 129 | 83 | 0 | 0 | 0 | 788 |
| 16:00:00 | 78 | 55 | 35 | 0 | 0 | 0 | 45 | 149 | 25 | 0 | 0 | 0 | 23 | 67 | 21 | 0 | 0 | 0 | 23 | 148 | 80 | 0 | 0 | 0 | 749 |
| 16:15:00 | 103 | 65 | 52 | 0 | 0 | 0 | 33 | 153 | 19 | 0 | 0 | 0 | 19 | 66 | 17 | 0 | 0 | 0 | 15 | 138 | 76 | 0 | 0 | 0 | 756 |
| 16:30:00 | 91 | 61 | 29 | 0 | 0 | 0 | 35 | 148 | 20 | 0 | 0 | 0 | 12 | 61 | 13 | 0 | 0 | 0 | 17 | 124 | 64 | 0 | 0 | 0 | 675 |
| 16:45:00 | 80 | 64 | 36 | 0 | 0 | 0 | 28 | 149 | 14 | 0 | 0 | 0 | 26 | 69 | 19 | 0 | 0 | 0 | 23 | 139 | 64 | 0 | 0 | 0 | 711 |
| 17:00:00 | 99 | 55 | 36 | 0 | 0 | 0 | 30 | 146 | 16 | 0 | 0 | 0 | 28 | 67 | 27 | 0 | 0 | 0 | 17 | 135 | 84 | 0 | 0 | 0 | 740 |
| 17:15:00 | 97 | 39 | 41 | 0 | 0 | 0 | 28 | 154 | 25 | 0 | 0 | 0 | 25 | 74 | 23 | 0 | 0 | 0 | 15 | 116 | 90 | 0 | 0 | 0 | 727 |
| 17:30:00 | 98 | 63 | 31 | 0 | 0 | 0 | 30 | 128 | 23 | 0 | 0 | 0 | 13 | 50 | 22 | 0 | 0 | 0 | 13 | 117 | 88 | 0 | 0 | 0 | 676 |
| 17:45:00 | 73 | 47 | 45 | 0 | 0 | 0 | 30 | 110 | 20 | 0 | 0 | 0 | 16 | 75 | 28 | 0 | 0 | 0 | 15 | 115 | 75 | 0 | 0 | 0 | 649 |
| 18:00:00 | 79 | 65 | 45 | 0 | 0 | 0 | 33 | 124 | 24 | 0 | 0 | 0 | 17 | 56 | 20 | 0 | 0 | 0 | 16 | 126 | 75 | 0 | 0 | 0 | 680 |
| 18:15:00 | 107 | 69 | 47 | 0 | 0 | 0 | 30 | 131 | 18 | 0 | 0 | 0 | 19 | 58 | 15 | 0 | 0 | 0 | 21 | 128 | 93 | 0 | 0 | 0 | 736 |
| 18:30:00 | 88 | 43 | 57 | 0 | 0 | 0 | 38 | 110 | 12 | 0 | 0 | 0 | 19 | 61 | 24 | 0 | 0 | 0 | 11 | 109 | 72 | 0 | 0 | 0 | 644 |
| 18:45:00 | 87 | 60 | 51 | 0 | 0 | 0 | 33 | 115 | 20 | 0 | 0 | 0 | 17 | 58 | 17 | 0 | 0 | 0 | 12 | 106 | 84 | 0 | 0 | 0 | 660 |
| 19:00:00 | 72 | 38 | 50 | 0 | 0 | 0 | 43 | 113 | 21 | 0 | 0 | 0 | 18 | 60 | 10 | 0 | 0 | 0 | 11 | 131 | 83 | 0 | 0 | 0 | 650 |
| 19:15:00 | 70 | 57 | 38 | 0 | 0 | 0 | 36 | 103 | 11 | 0 | 0 | 0 | 7 | 68 | 17 | 0 | 0 | 0 | 8 | 88 | 83 | 0 | 0 | 0 | 586 |
| 19:30:00 | 72 | 52 | 37 | 0 | 0 | 0 | 31 | 83 | 9 | 0 | 0 | 0 | 10 | 59 | 9 | 0 | 0 | 0 | 7 | 74 | 62 | 0 | 0 | 0 | 505 |
| 19:45:00 | 53 | 45 | 28 | 0 | 0 | 0 | 34 | 90 | 6 | 0 | 0 | 0 | 11 | 52 | 10 | 0 | 0 | 0 | 11 | 86 | 64 | 0 | 0 | 0 | 490 |
| 20:00:00 | 61 | 29 | 31 | 0 | 0 | 0 | 26 | 80 | 12 | 0 | 0 | 0 | 14 | 45 | 9 | 0 | 0 | 0 | 8 | 87 | 61 | 0 | 0 | 0 | 463 |
| 20:15:00 | 59 | 48 | 20 | 0 | 0 | 0 | 30 | 63 | 9 | 0 | 0 | 0 | 9 | 56 | 9 | 0 | 0 | 0 | 3 | 79 | 55 | 0 | 0 | 0 | 440 |
| 20:30:00 | 43 | 25 | 32 | 0 | 0 | 0 | 24 | 46 | 12 | 0 | 0 | 0 | 8 | 42 | 6 | 0 | 0 | 0 | 4 | 74 | 59 | 0 | 0 | 0 | 375 |
| 20:45:00 | 53 | 49 | 32 | 0 | 0 | 0 | 22 | 70 | 10 | 0 | 0 | 0 | 8 | 46 | 6 | 0 | 0 | 0 | 5 | 60 | 45 | 0 | 0 | 0 | 406 |
| 21:00:00 | 45 | 36 | 26 | 0 | 0 | 0 | 26 | 64 | 5 | 0 | 0 | 0 | 19 | 51 | 13 | 0 | 0 | 0 | 4 | 70 | 57 | 0 | 0 | 0 | 416 |
| 21:15:00 | 37 | 42 | 37 | 0 | 0 | 0 | 32 | 50 | 9 | 0 | 0 | 0 | 13 | 28 | 1 | 0 | 0 | 0 | 5 | 48 | 40 | 0 | 0 | 0 | 342 |
| 21:30:00 | 43 | 37 | 26 | 0 | 0 | 0 | 20 | 39 | 11 | 0 | 0 | 0 | 7 | 43 | 11 | 0 | 0 | 0 | 4 | 47 | 52 | 0 | 0 | 0 | 340 |
| 21:45:00 | 54 | 37 | 24 | 0 | 0 | 0 | 27 | 38 | 10 | 0 | 0 | 0 | 13 | 38 | 5 | 0 | 0 | 0 | 4 | 33 | 51 | 0 | 0 | 0 | 334 |
| 22:00:00 | 49 | 35 | 36 | 0 | 0 | 0 | 22 | 45 | 11 | 0 | 0 | 0 | 4 | 39 | 9 | 0 | 0 | 0 | 7 | 32 | 42 | 0 | 0 | 0 | 331 |
| 22:15:00 | 33 | 38 | 18 | 0 | 0 | 0 | 24 | 33 | 8 | 0 | 0 | 0 | 7 | 37 | 4 | 0 | 0 | 0 | 2 | 34 | 54 | 0 | 0 | 0 | 292 |
| 22:30:00 | 42 | 42 | 13 | 0 | 0 | 0 | 11 | 26 | 5 | 0 | 0 | 0 | 7 | 50 | 3 | 0 | 0 | 0 | 3 | 29 | 39 | 0 | 0 | 0 | 270 |
| 22:45:00 | 31 | 45 | 15 | 0 | 0 | 0 | 15 | 34 | 11 | 0 | 0 | 0 | 0 | 42 | 5 | 0 | 0 | 0 | 3 | 38 | 36 | 0 | 0 | 0 | 275 |
| 23:00:00 | 40 | 50 | 26 | 0 | 0 | 0 | 12 | 35 | 5 | 0 | 0 | 0 | 5 | 37 | 4 | 0 | 0 | 0 | 0 | 20 | 33 | 0 | 0 | 0 | 267 |
| 23:15:00 | 45 | 47 | 14 | 0 | 0 | 0 | 9 | 21 | 6 | 0 | 0 | 0 | 3 | 28 | 7 | 0 | 0 | 0 | 1 | 23 | 43 | 0 | 0 | 0 | 247 |
| 23:30:00 | 61 | 38 | 19 | 0 | 0 | 0 | 18 | 22 | 2 | 0 | 0 | 0 | 4 | 35 | 5 | 0 | 0 | 0 | 3 | 18 | 37 | 0 | 0 | 0 | 262 |
| 23:45:00 | 29 | 22 | 11 | 0 | 0 | 0 | 10 | 20 | 6 | 0 | 0 | 0 | 3 | 34 | 6 | 0 | 0 | 0 | 1 | 18 | 37 | 0 | 0 | 0 | 197 |

| | | |
|---|---|---|
| **Lights** | 721 | 3 |
| HV | 751 | 3 |
| | 745 | 4 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/26/2023 0:00
End Time 10/26/2023 23:59
Location 05-53-424 Sweet Home Rd @ Maple Rd
Latitude an 42.99070136,-78.80420219
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 6 | 13 | 4 | 0 | 0 | 0 | 2 | 10 | 8 | 0 | 0 | 0 | 2 | 10 | 3 | 0 | 0 | 0 | 4 | 13 | 10 | 0 | 0 | 0 | 85 |
| 0:15:00 | 4 | 9 | 1 | 0 | 0 | 0 | 0 | 4 | 5 | 0 | 0 | 0 | 2 | 10 | 2 | 0 | 0 | 0 | 2 | 14 | 12 | 0 | 0 | 0 | 65 |
| 0:30:00 | 7 | 7 | 0 | 0 | 0 | 0 | 4 | 3 | 4 | 0 | 0 | 0 | 7 | 15 | 3 | 0 | 0 | 0 | 3 | 11 | 3 | 0 | 0 | 0 | 67 |
| 0:45:00 | 3 | 5 | 2 | 0 | 0 | 0 | 1 | 4 | 3 | 0 | 0 | 0 | 1 | 14 | 0 | 0 | 0 | 0 | 1 | 5 | 6 | 0 | 0 | 0 | 45 |
| 1:00:00 | 3 | 6 | 1 | 0 | 0 | 0 | 0 | 5 | 2 | 0 | 0 | 0 | 2 | 9 | 0 | 0 | 0 | 0 | 2 | 10 | 0 | 0 | 0 | 0 | 40 |
| 1:15:00 | 1 | 8 | 1 | 0 | 0 | 0 | 1 | 3 | 2 | 0 | 0 | 0 | 2 | 8 | 1 | 0 | 0 | 0 | 0 | 1 | 7 | 0 | 0 | 0 | 35 |
| 1:30:00 | 3 | 10 | 1 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 5 | 13 | 2 | 0 | 0 | 0 | 2 | 7 | 2 | 0 | 0 | 0 | 48 |
| 1:45:00 | 1 | 3 | 1 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 4 | 6 | 1 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 24 |
| 2:00:00 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 5 | 3 | 0 | 0 | 0 | 2 | 8 | 1 | 0 | 0 | 0 | 1 | 4 | 1 | 0 | 0 | 0 | 29 |
| 2:15:00 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 9 | 2 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 23 |
| 2:30:00 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 1 | 7 | 0 | 0 | 0 | 0 | 2 | 11 | 3 | 0 | 0 | 0 | 30 |
| 2:45:00 | 1 | 6 | 1 | 0 | 0 | 0 | 0 | 5 | 4 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 7 | 2 | 0 | 0 | 0 | 31 |
| 3:00:00 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 2 | 2 | 1 | 0 | 0 | 0 | 16 |
| 3:15:00 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 13 |
| 3:30:00 | 0 | 4 | 1 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 15 |
| 3:45:00 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 4 | 3 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 18 |
| 4:00:00 | 2 | 2 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 2 | 5 | 1 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 21 |
| 4:15:00 | 1 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 2 | 3 | 1 | 0 | 0 | 0 | 15 |
| 4:30:00 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 1 | 5 | 5 | 0 | 0 | 0 | 21 |
| 4:45:00 | 2 | 2 | 0 | 0 | 0 | 0 | 0 | 4 | 4 | 0 | 0 | 0 | 1 | 3 | 5 | 0 | 0 | 0 | 1 | 6 | 2 | 0 | 0 | 0 | 30 |
| 5:00:00 | 0 | 4 | 3 | 0 | 0 | 0 | 0 | 6 | 1 | 0 | 0 | 0 | 1 | 3 | 1 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 23 |
| 5:15:00 | 4 | 6 | 1 | 0 | 0 | 0 | 0 | 10 | 5 | 0 | 0 | 0 | 3 | 6 | 2 | 0 | 0 | 0 | 2 | 11 | 4 | 0 | 0 | 0 | 54 |
| 5:30:00 | 3 | 4 | 5 | 0 | 0 | 0 | 0 | 16 | 3 | 0 | 0 | 0 | 8 | 4 | 4 | 0 | 0 | 0 | 2 | 18 | 3 | 0 | 0 | 0 | 70 |
| 5:45:00 | 6 | 8 | 1 | 0 | 0 | 0 | 1 | 17 | 6 | 0 | 0 | 0 | 9 | 12 | 5 | 0 | 0 | 0 | 3 | 19 | 11 | 0 | 0 | 0 | 98 |
| 6:00:00 | 7 | 9 | 3 | 0 | 0 | 0 | 1 | 14 | 8 | 0 | 0 | 0 | 5 | 9 | 2 | 0 | 0 | 0 | 2 | 27 | 11 | 0 | 0 | 0 | 98 |
| 6:15:00 | 7 | 10 | 4 | 0 | 0 | 0 | 2 | 18 | 9 | 0 | 0 | 0 | 6 | 13 | 5 | 0 | 0 | 0 | 3 | 31 | 9 | 0 | 0 | 0 | 117 |
| 6:30:00 | 18 | 13 | 10 | 0 | 0 | 0 | 2 | 30 | 13 | 0 | 0 | 0 | 13 | 23 | 4 | 0 | 0 | 0 | 5 | 51 | 8 | 0 | 0 | 0 | 190 |
| 6:45:00 | 17 | 27 | 21 | 0 | 0 | 0 | 2 | 29 | 15 | 0 | 0 | 0 | 23 | 30 | 4 | 0 | 0 | 0 | 5 | 58 | 27 | 0 | 0 | 0 | 258 |
| 7:00:00 | 28 | 36 | 18 | 0 | 0 | 0 | 7 | 31 | 26 | 0 | 0 | 0 | 20 | 47 | 5 | 0 | 0 | 0 | 3 | 66 | 21 | 0 | 0 | 0 | 308 |
| 7:15:00 | 34 | 72 | 46 | 0 | 0 | 0 | 10 | 57 | 19 | 0 | 0 | 0 | 16 | 60 | 10 | 0 | 0 | 0 | 8 | 91 | 28 | 0 | 0 | 0 | 451 |
| 7:30:00 | 41 | 86 | 53 | 0 | 0 | 0 | 22 | 97 | 22 | 0 | 0 | 0 | 36 | 60 | 9 | 0 | 0 | 0 | 12 | 107 | 23 | 0 | 0 | 0 | 568 |
| 7:45:00 | 72 | 66 | 55 | 0 | 0 | 0 | 28 | 122 | 25 | 0 | 0 | 0 | 31 | 79 | 17 | 0 | 0 | 0 | 13 | 143 | 41 | 0 | 0 | 0 | 692 |
| 8:00:00 | 58 | 45 | 40 | 0 | 0 | 0 | 19 | 111 | 27 | 0 | 0 | 0 | 41 | 64 | 17 | 0 | 0 | 0 | 15 | 98 | 47 | 0 | 0 | 0 | 582 |
| 8:15:00 | 55 | 54 | 47 | 0 | 0 | 0 | 23 | 98 | 31 | 0 | 0 | 0 | 34 | 40 | 11 | 0 | 0 | 0 | 2 | 126 | 56 | 0 | 0 | 0 | 577 |
| 8:30:00 | 57 | 73 | 49 | 0 | 0 | 0 | 20 | 99 | 24 | 0 | 0 | 0 | 37 | 65 | 11 | 0 | 0 | 0 | 8 | 104 | 35 | 0 | 0 | 0 | 582 |
| 8:45:00 | 76 | 62 | 38 | 0 | 0 | 0 | 30 | 145 | 29 | 0 | 0 | 0 | 24 | 54 | 18 | 0 | 0 | 0 | 12 | 114 | 53 | 0 | 0 | 0 | 655 |
| 9:00:00 | 78 | 54 | 48 | 0 | 0 | 0 | 31 | 117 | 28 | 0 | 0 | 0 | 31 | 74 | 34 | 0 | 0 | 0 | 16 | 123 | 79 | 0 | 0 | 0 | 713 |
| 9:15:00 | 49 | 57 | 37 | 0 | 0 | 0 | 13 | 126 | 25 | 0 | 0 | 0 | 22 | 54 | 10 | 0 | 0 | 0 | 8 | 83 | 72 | 0 | 0 | 0 | 556 |
| 9:30:00 | 63 | 55 | 35 | 0 | 0 | 0 | 27 | 106 | 14 | 0 | 0 | 0 | 27 | 56 | 11 | 0 | 0 | 0 | 5 | 106 | 44 | 0 | 0 | 0 | 549 |
| 9:45:00 | 62 | 56 | 39 | 0 | 0 | 0 | 21 | 125 | 29 | 0 | 0 | 0 | 17 | 54 | 15 | 0 | 0 | 0 | 9 | 105 | 42 | 0 | 0 | 0 | 574 |
| 10:00:00 | 57 | 45 | 33 | 0 | 0 | 0 | 28 | 141 | 24 | 0 | 0 | 0 | 26 | 46 | 16 | 0 | 0 | 0 | 13 | 84 | 42 | 0 | 0 | 0 | 555 |
| 10:15:00 | 48 | 44 | 33 | 0 | 0 | 0 | 30 | 142 | 27 | 0 | 0 | 0 | 19 | 60 | 19 | 0 | 0 | 0 | 13 | 93 | 39 | 0 | 0 | 0 | 567 |
| 10:30:00 | 76 | 47 | 36 | 0 | 0 | 0 | 27 | 125 | 19 | 0 | 0 | 0 | 16 | 54 | 13 | 0 | 0 | 0 | 11 | 111 | 46 | 0 | 0 | 0 | 581 |
| 10:45:00 | 82 | 58 | 34 | 0 | 0 | 0 | 31 | 174 | 30 | 0 | 0 | 0 | 27 | 64 | 16 | 0 | 0 | 0 | 10 | 91 | 69 | 0 | 0 | 0 | 686 |
| 11:00:00 | 88 | 61 | 24 | 0 | 0 | 0 | 29 | 148 | 34 | 0 | 0 | 0 | 24 | 49 | 15 | 0 | 0 | 0 | 8 | 95 | 64 | 0 | 0 | 0 | 639 |
| 11:15:00 | 73 | 60 | 30 | 0 | 0 | 0 | 28 | 152 | 23 | 0 | 0 | 0 | 25 | 53 | 19 | 0 | 0 | 0 | 11 | 115 | 56 | 0 | 0 | 0 | 645 |
| 11:30:00 | 79 | 49 | 42 | 0 | 0 | 0 | 37 | 171 | 27 | 0 | 0 | 0 | 18 | 53 | 16 | 0 | 0 | 0 | 13 | 105 | 55 | 0 | 0 | 0 | 665 |
| 11:45:00 | 73 | 51 | 35 | 0 | 0 | 0 | 31 | 195 | 29 | 0 | 0 | 0 | 21 | 58 | 21 | 0 | 0 | 0 | 12 | 134 | 60 | 0 | 0 | 0 | 720 |
| 12:00:00 | 101 | 78 | 47 | 0 | 0 | 0 | 38 | 191 | 24 | 0 | 0 | 0 | 21 | 64 | 31 | 0 | 0 | 0 | 13 | 124 | 59 | 0 | 0 | 0 | 791 |
| 12:15:00 | 94 | 65 | 43 | 0 | 0 | 0 | 40 | 191 | 28 | 0 | 0 | 0 | 25 | 56 | 27 | 0 | 0 | 0 | 13 | 150 | 73 | 0 | 0 | 0 | 805 |
| 12:30:00 | 97 | 90 | 39 | 0 | 0 | 0 | 33 | 178 | 30 | 0 | 0 | 0 | 28 | 51 | 28 | 0 | 0 | 0 | 17 | 150 | 87 | 0 | 0 | 0 | 828 |
| 12:45:00 | 97 | 73 | 56 | 0 | 0 | 0 | 35 | 171 | 28 | 0 | 0 | 0 | 31 | 79 | 19 | 0 | 0 | 0 | 23 | 139 | 84 | 0 | 0 | 0 | 835 |
| 13:00:00 | 93 | 53 | 28 | 0 | 0 | 0 | 34 | 171 | 27 | 0 | 0 | 0 | 32 | 57 | 15 | 0 | 0 | 0 | 15 | 149 | 68 | 0 | 0 | 0 | 742 |
| 13:15:00 | 89 | 59 | 30 | 0 | 0 | 0 | 36 | 149 | 24 | 0 | 0 | 0 | 17 | 68 | 19 | 0 | 0 | 0 | 17 | 133 | 78 | 0 | 0 | 0 | 719 |
| 13:30:00 | 78 | 55 | 37 | 0 | 0 | 0 | 36 | 146 | 30 | 0 | 0 | 0 | 26 | 50 | 23 | 0 | 0 | 0 | 16 | 133 | 76 | 0 | 0 | 0 | 706 |
| 13:45:00 | 84 | 75 | 36 | 0 | 0 | 0 | 37 | 171 | 21 | 0 | 0 | 0 | 29 | 88 | 23 | 0 | 0 | 0 | 18 | 171 | 71 | 0 | 0 | 0 | 824 |
| 14:00:00 | 129 | 89 | 49 | 0 | 0 | 0 | 24 | 185 | 24 | 0 | 0 | 0 | 38 | 71 | 16 | 0 | 0 | 0 | 12 | 142 | 76 | 0 | 0 | 0 | 855 |
| 14:15:00 | 96 | 63 | 39 | 0 | 0 | 0 | 40 | 156 | 31 | 0 | 0 | 0 | 21 | 80 | 22 | 0 | 0 | 0 | 18 | 141 | 85 | 0 | 0 | 0 | 792 |
| 14:30:00 | 98 | 87 | 53 | 0 | 0 | 0 | 31 | 166 | 33 | 0 | 0 | 0 | 29 | 79 | 22 | 0 | 0 | 0 | 8 | 148 | 77 | 0 | 0 | 0 | 831 |
| 14:45:00 | 120 | 87 | 65 | 0 | 0 | 0 | 44 | 166 | 43 | 0 | 0 | 0 | 29 | 65 | 20 | 0 | 0 | 0 | 12 | 164 | 79 | 0 | 0 | 0 | 894 |
| 3:00 PM | 106 | 103 | 63 | 0 | 0 | 0 | 42 | 207 | 43 | 0 | 0 | 0 | 33 | 91 | 17 | 0 | 0 | 0 | 20 | 146 | 81 | 0 | 0 | 0 | 952 |
| 3:15 PM | 115 | 111 | 64 | 0 | 0 | 0 | 36 | 208 | 52 | 0 | 0 | 0 | 30 | 74 | 32 | 0 | 0 | 0 | 22 | 160 | 77 | 0 | 0 | 0 | 981 |
| 3:30 PM | 135 | 115 | 45 | 0 | 0 | 0 | 53 | 202 | 40 | 0 | 0 | 0 | 35 | 77 | 38 | 0 | 0 | 0 | 15 | 155 | 67 | 0 | 0 | 0 | 977 |
| 3:45 PM | 120 | 104 | 62 | 0 | 0 | 0 | 55 | 217 | 55 | 0 | 0 | 0 | 27 | 83 | 27 | 0 | 0 | 0 | 23 | 162 | 63 | 0 | 0 | 0 | 998 |
| 4:00 PM | 143 | 117 | 44 | 0 | 0 | 0 | 51 | 197 | 43 | 0 | 0 | 0 | 29 | 88 | 17 | 0 | 0 | 0 | 29 | 184 | 82 | 0 | 0 | 0 | 1024 |
| 4:15 PM | 104 | 102 | 52 | 0 | 0 | 0 | 42 | 218 | 52 | 0 | 0 | 0 | 23 | 82 | 33 | 0 | 0 | 0 | 29 | 168 | 69 | 0 | 0 | 0 | 974 |
| 4:30 PM | 111 | 109 | 46 | 0 | 0 | 0 | 56 | 209 | 30 | 0 | 0 | 0 | 31 | 80 | 20 | 0 | 0 | 0 | 20 | 179 | 79 | 0 | 0 | 0 | 970 |
| 4:45 PM | 114 | 102 | 53 | 0 | 0 | 0 | 52 | 202 | 56 | 0 | 0 | 0 | 22 | 84 | 27 | 0 | 0 | 0 | 18 | 141 | 63 | 0 | 0 | 0 | 934 |
| 5:00 PM | 134 | 108 | 49 | 0 | 0 | 0 | 62 | 229 | 48 | 0 | 0 | 0 | 28 | 82 | 15 | 0 | 0 | 0 | 25 | 155 | 80 | 0 | 0 | 0 | 1015 |
| 5:15 PM | 140 | 119 | 33 | 0 | 0 | 0 | 52 | 214 | 56 | 0 | 0 | 0 | 35 | 87 | 36 | 0 | 0 | 0 | 16 | 125 | 71 | 0 | 0 | 0 | 984 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.96133 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 5:30 PM | 110 | 88 | 45 | 0 | 0 | 0 | 44 | 179 | 41 | 0 | 0 | 0 | 22 | 85 | 33 | 0 | 0 | 0 | 11 | 152 | 87 | 0 | 0 | 0 | 897 |
| 5:45 PM | 85 | 62 | 44 | 0 | 0 | 0 | 50 | 162 | 23 | 0 | 0 | 0 | 24 | 88 | 25 | 0 | 0 | 0 | 23 | 140 | 94 | 0 | 0 | 0 | 820 |
| 18:00:00 | 113 | 66 | 56 | 0 | 0 | 0 | 32 | 138 | 24 | 0 | 0 | 0 | 14 | 72 | 26 | 0 | 0 | 0 | 16 | 137 | 84 | 0 | 0 | 0 | 778 |
| 18:15:00 | 91 | 76 | 37 | 0 | 0 | 0 | 40 | 130 | 17 | 0 | 0 | 0 | 22 | 66 | 19 | 0 | 0 | 0 | 12 | 133 | 96 | 0 | 0 | 0 | 739 |
| 18:30:00 | 96 | 62 | 29 | 0 | 0 | 0 | 25 | 140 | 25 | 0 | 0 | 0 | 18 | 66 | 19 | 0 | 0 | 0 | 13 | 102 | 82 | 0 | 0 | 0 | 677 |
| 18:45:00 | 98 | 53 | 34 | 0 | 0 | 0 | 35 | 125 | 21 | 0 | 0 | 0 | 20 | 63 | 17 | 0 | 0 | 0 | 11 | 123 | 78 | 0 | 0 | 0 | 678 |
| 19:00:00 | 104 | 62 | 33 | 0 | 0 | 0 | 30 | 105 | 12 | 0 | 0 | 0 | 14 | 66 | 16 | 0 | 0 | 0 | 11 | 117 | 86 | 0 | 0 | 0 | 656 |
| 19:15:00 | 85 | 51 | 27 | 0 | 0 | 0 | 22 | 114 | 18 | 0 | 0 | 0 | 17 | 63 | 20 | 0 | 0 | 0 | 13 | 97 | 72 | 0 | 0 | 0 | 599 |
| 19:30:00 | 75 | 45 | 32 | 0 | 0 | 0 | 29 | 98 | 17 | 0 | 0 | 0 | 9 | 53 | 11 | 0 | 0 | 0 | 7 | 109 | 71 | 0 | 0 | 0 | 556 |
| 19:45:00 | 65 | 40 | 35 | 0 | 0 | 0 | 33 | 87 | 15 | 0 | 0 | 0 | 10 | 61 | 8 | 0 | 0 | 0 | 13 | 80 | 75 | 0 | 0 | 0 | 522 |
| 20:00:00 | 74 | 49 | 21 | 0 | 0 | 0 | 22 | 80 | 15 | 0 | 0 | 0 | 8 | 49 | 12 | 0 | 0 | 0 | 7 | 80 | 67 | 0 | 0 | 0 | 484 |
| 20:15:00 | 56 | 46 | 27 | 0 | 0 | 0 | 18 | 60 | 13 | 0 | 0 | 0 | 9 | 55 | 9 | 0 | 0 | 0 | 8 | 64 | 44 | 0 | 0 | 0 | 409 |
| 20:30:00 | 46 | 47 | 21 | 0 | 0 | 0 | 18 | 58 | 10 | 0 | 0 | 0 | 10 | 45 | 13 | 0 | 0 | 0 | 3 | 42 | 68 | 0 | 0 | 0 | 381 |
| 20:45:00 | 60 | 36 | 9 | 0 | 0 | 0 | 10 | 58 | 6 | 0 | 0 | 0 | 6 | 24 | 6 | 0 | 0 | 0 | 9 | 49 | 56 | 0 | 0 | 0 | 329 |
| 21:00:00 | 54 | 39 | 20 | 0 | 0 | 0 | 13 | 39 | 9 | 0 | 0 | 0 | 11 | 39 | 7 | 0 | 0 | 0 | 7 | 69 | 67 | 0 | 0 | 0 | 374 |
| 21:15:00 | 51 | 31 | 17 | 0 | 0 | 0 | 13 | 32 | 8 | 0 | 0 | 0 | 2 | 38 | 9 | 0 | 0 | 0 | 4 | 52 | 43 | 0 | 0 | 0 | 300 |
| 21:30:00 | 35 | 29 | 16 | 0 | 0 | 0 | 17 | 45 | 11 | 0 | 0 | 0 | 8 | 35 | 4 | 0 | 0 | 0 | 2 | 37 | 52 | 0 | 0 | 0 | 291 |
| 21:45:00 | 51 | 36 | 22 | 0 | 0 | 0 | 15 | 34 | 5 | 0 | 0 | 0 | 10 | 47 | 9 | 0 | 0 | 0 | 5 | 24 | 52 | 0 | 0 | 0 | 310 |
| 22:00:00 | 47 | 31 | 35 | 0 | 0 | 0 | 21 | 28 | 9 | 0 | 0 | 0 | 3 | 26 | 1 | 0 | 0 | 0 | 4 | 31 | 48 | 0 | 0 | 0 | 284 |
| 22:15:00 | 31 | 33 | 13 | 0 | 0 | 0 | 9 | 31 | 3 | 0 | 0 | 0 | 1 | 27 | 3 | 0 | 0 | 0 | 4 | 33 | 31 | 0 | 0 | 0 | 219 |
| 22:30:00 | 29 | 29 | 11 | 0 | 0 | 0 | 10 | 30 | 9 | 0 | 0 | 0 | 5 | 30 | 2 | 0 | 0 | 0 | 2 | 22 | 39 | 0 | 0 | 0 | 218 |
| 22:45:00 | 18 | 25 | 9 | 0 | 0 | 0 | 10 | 22 | 5 | 0 | 0 | 0 | 4 | 28 | 3 | 0 | 0 | 0 | 2 | 34 | 49 | 0 | 0 | 0 | 209 |
| 23:00:00 | 26 | 39 | 13 | 0 | 0 | 0 | 12 | 26 | 8 | 0 | 0 | 0 | 3 | 17 | 2 | 0 | 0 | 0 | 1 | 28 | 28 | 0 | 0 | 0 | 203 |
| 23:15:00 | 17 | 24 | 13 | 0 | 0 | 0 | 10 | 25 | 4 | 0 | 0 | 0 | 3 | 27 | 2 | 0 | 0 | 0 | 1 | 22 | 28 | 0 | 0 | 0 | 176 |
| 23:30:00 | 24 | 30 | 17 | 0 | 0 | 0 | 15 | 42 | 9 | 0 | 0 | 0 | 5 | 31 | 3 | 0 | 0 | 0 | 2 | 27 | 28 | 0 | 0 | 0 | 233 |
| 23:45:00 | 27 | 26 | 7 | 0 | 0 | 0 | 14 | 27 | 3 | 0 | 0 | 0 | 4 | 23 | 3 | 0 | 0 | 0 | 5 | 19 | 22 | 0 | 0 | 0 | 180 |

| Lights | | HV | |
|---|---|---|---|
| | 966 | | 4 |
| | 928 | | 6 |
| | 1010 | | 5 |
| | 979 | | 5 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/14/2023 0:00
End Time 10/14/2023 23:59
Location 05-53-431 Rt 263 Ramps (NW) @ Maple
Latitude an 42.99135941,-78.79031239
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 23 | 1 | 0 | 0 | 0 | 59 |
| 0:15:00 | 2 | 0 | 0 | 0 | 0 | 0 | 3 | 17 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | 2 | 0 | 0 | 0 | 44 |
| 0:30:00 | 3 | 0 | 3 | 0 | 0 | 0 | 2 | 23 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 16 | 2 | 0 | 0 | 0 | 49 |
| 0:45:00 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 14 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 1 | 0 | 0 | 0 | 27 |
| 1:00:00 | 3 | 0 | 4 | 0 | 0 | 0 | 3 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 1 | 0 | 0 | 0 | 33 |
| 1:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 0 | 0 | 0 | 17 |
| 1:30:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17 | 0 | 0 | 0 | 0 | 30 |
| 1:45:00 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 19 |
| 2:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 4 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 0 | 0 | 0 | 0 | 18 |
| 2:15:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 14 |
| 2:30:00 | 2 | 0 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 16 |
| 2:45:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 7 |
| 3:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 4 |
| 3:15:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 6 |
| 3:30:00 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 5 |
| 3:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 3 |
| 4:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 4:15:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 4 |
| 4:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 4:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 4 |
| 5:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 5 |
| 5:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 7 |
| 5:30:00 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 8 |
| 5:45:00 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 10 |
| 6:00:00 | 1 | 0 | 1 | 0 | 0 | 0 | 2 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 1 | 0 | 0 | 0 | 20 |
| 6:15:00 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 23 |
| 6:30:00 | 2 | 0 | 1 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | 1 | 0 | 0 | 0 | 23 |
| 6:45:00 | 5 | 0 | 0 | 0 | 0 | 0 | 1 | 18 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 24 | 1 | 0 | 0 | 0 | 49 |
| 7:00:00 | 5 | 0 | 1 | 0 | 0 | 0 | 1 | 25 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 31 | 2 | 0 | 0 | 0 | 65 |
| 7:15:00 | 9 | 0 | 0 | 0 | 0 | 0 | 18 | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 35 | 1 | 0 | 0 | 0 | 94 |
| 7:30:00 | 7 | 0 | 0 | 0 | 0 | 0 | 13 | 35 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 39 | 0 | 0 | 0 | 0 | 94 |
| 7:45:00 | 10 | 0 | 0 | 0 | 0 | 0 | 14 | 60 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 54 | 0 | 0 | 0 | 0 | 138 |
| 8:00:00 | 8 | 0 | 1 | 0 | 0 | 0 | 28 | 65 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 38 | 1 | 0 | 0 | 0 | 141 |
| 8:15:00 | 8 | 0 | 1 | 0 | 0 | 0 | 31 | 62 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 54 | 0 | 0 | 0 | 0 | 156 |
| 8:30:00 | 19 | 0 | 4 | 0 | 0 | 0 | 38 | 67 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 76 | 0 | 0 | 0 | 0 | 204 |
| 8:45:00 | 14 | 0 | 6 | 0 | 0 | 0 | 38 | 96 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 87 | 3 | 0 | 0 | 0 | 244 |
| 9:00:00 | 23 | 0 | 1 | 0 | 0 | 0 | 28 | 99 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 69 | 1 | 0 | 0 | 0 | 221 |
| 9:15:00 | 16 | 0 | 3 | 0 | 0 | 0 | 33 | 99 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 78 | 2 | 0 | 0 | 0 | 231 |
| 9:30:00 | 22 | 0 | 3 | 0 | 0 | 0 | 48 | 113 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 93 | 1 | 0 | 0 | 0 | 280 |
| 9:45:00 | 24 | 0 | 3 | 0 | 0 | 0 | 44 | 118 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 107 | 1 | 0 | 0 | 0 | 297 |
| 10:00:00 | 20 | 0 | 6 | 0 | 0 | 0 | 54 | 101 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 93 | 1 | 0 | 0 | 0 | 275 |
| 10:15:00 | 22 | 0 | 1 | 0 | 0 | 0 | 43 | 126 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 104 | 1 | 0 | 0 | 0 | 297 |
| 10:30:00 | 26 | 0 | 9 | 0 | 0 | 0 | 45 | 135 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 89 | 1 | 0 | 0 | 0 | 305 |
| 10:45:00 | 33 | 0 | 1 | 0 | 0 | 0 | 34 | 147 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 110 | 1 | 0 | 0 | 0 | 326 |
| 11:00:00 | 26 | 0 | 3 | 0 | 0 | 0 | 35 | 139 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 128 | 0 | 0 | 0 | 0 | 331 |
| 11:15:00 | 29 | 0 | 4 | 0 | 0 | 0 | 48 | 170 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 138 | 0 | 0 | 0 | 0 | 389 |
| 11:30:00 | 37 | 0 | 2 | 0 | 0 | 0 | 51 | 160 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 135 | 2 | 0 | 0 | 0 | 387 |
| 11:45:00 | 37 | 0 | 8 | 0 | 0 | 0 | 36 | 162 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 148 | 3 | 0 | 0 | 0 | 394 |
| 12:00:00 | 28 | 0 | 3 | 0 | 0 | 0 | 46 | 176 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 156 | 2 | 0 | 0 | 0 | 411 |
| 12:15:00 | 24 | 0 | 3 | 0 | 0 | 0 | 50 | 199 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 149 | 4 | 0 | 0 | 0 | 429 |
| 12:30:00 | 33 | 0 | 2 | 0 | 0 | 0 | 36 | 158 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 164 | 1 | 0 | 0 | 0 | 394 |
| 12:45:00 | 30 | 0 | 4 | 0 | 0 | 0 | 55 | 177 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 158 | 3 | 0 | 0 | 0 | 427 |
| 13:00:00 | 24 | 0 | 3 | 0 | 0 | 0 | 48 | 159 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 144 | 1 | 0 | 0 | 0 | 379 |
| 13:15:00 | 23 | 0 | 1 | 0 | 0 | 0 | 50 | 164 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 150 | 3 | 0 | 0 | 0 | 391 |
| 13:30:00 | 24 | 0 | 3 | 0 | 0 | 0 | 35 | 181 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 190 | 3 | 0 | 0 | 0 | 436 |
| 13:45:00 | 24 | 0 | 3 | 0 | 0 | 0 | 44 | 154 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 160 | 3 | 0 | 0 | 0 | 388 |
| 14:00:00 | 29 | 0 | 4 | 0 | 0 | 0 | 44 | 170 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 149 | 2 | 0 | 0 | 0 | 398 |
| 14:15:00 | 27 | 0 | 4 | 0 | 0 | 0 | 55 | 174 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 148 | 3 | 0 | 0 | 0 | 411 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.936353 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 14:30:00 | 29 | 0 | 0 | 0 | 0 | 0 | 43 | 153 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 147 | 2 | 0 | 0 | 0 | 374 |
| 14:45:00 | 26 | 0 | 2 | 0 | 0 | 0 | 44 | 163 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 175 | 3 | 0 | 0 | 0 | 413 |
| 15:00:00 | 40 | 0 | 3 | 0 | 0 | 0 | 48 | 154 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 164 | 0 | 0 | 0 | 0 | 409 |
| 15:15:00 | 28 | 0 | 4 | 0 | 0 | 0 | 42 | 137 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 134 | 1 | 0 | 0 | 0 | 346 |
| 15:30:00 | 29 | 0 | 1 | 0 | 0 | 0 | 50 | 153 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 153 | 2 | 0 | 0 | 0 | 388 |
| 15:45:00 | 27 | 0 | 2 | 0 | 0 | 0 | 31 | 162 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 153 | 1 | 0 | 0 | 0 | 376 |
| 16:00:00 | 37 | 0 | 1 | 0 | 0 | 0 | 44 | 138 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 134 | 0 | 0 | 0 | 0 | 354 |
| 16:15:00 | 19 | 0 | 4 | 0 | 0 | 0 | 51 | 157 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 146 | 2 | 0 | 0 | 0 | 379 |
| 16:30:00 | 20 | 0 | 0 | 0 | 0 | 0 | 38 | 158 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 146 | 1 | 0 | 0 | 0 | 363 |
| 16:45:00 | 24 | 0 | 3 | 0 | 0 | 0 | 46 | 137 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 139 | 2 | 0 | 0 | 0 | 351 |
| 17:00:00 | 31 | 0 | 5 | 0 | 0 | 0 | 31 | 161 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 154 | 0 | 0 | 0 | 0 | 382 |
| 17:15:00 | 32 | 0 | 6 | 0 | 0 | 0 | 59 | 200 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 135 | 4 | 0 | 0 | 0 | 436 |
| 17:30:00 | 20 | 0 | 3 | 0 | 0 | 0 | 35 | 181 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 116 | 1 | 0 | 0 | 0 | 356 |
| 17:45:00 | 21 | 0 | 4 | 0 | 0 | 0 | 41 | 127 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 116 | 2 | 0 | 0 | 0 | 311 |
| 18:00:00 | 28 | 0 | 3 | 0 | 0 | 0 | 46 | 130 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 142 | 2 | 0 | 0 | 0 | 351 |
| 18:15:00 | 16 | 0 | 2 | 0 | 0 | 0 | 34 | 113 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 151 | 4 | 0 | 0 | 0 | 320 |
| 18:30:00 | 23 | 0 | 3 | 0 | 0 | 0 | 37 | 112 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 112 | 2 | 0 | 0 | 0 | 289 |
| 18:45:00 | 26 | 0 | 2 | 0 | 0 | 0 | 21 | 128 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 121 | 3 | 0 | 0 | 0 | 301 |
| 19:00:00 | 26 | 0 | 3 | 0 | 0 | 0 | 3 | 72 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 95 | 3 | 0 | 0 | 0 | 202 |
| 19:15:00 | 21 | 0 | 8 | 0 | 0 | 0 | 3 | 60 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 78 | 6 | 0 | 0 | 0 | 176 |
| 19:30:00 | 11 | 0 | 1 | 0 | 0 | 0 | 3 | 60 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 80 | 9 | 0 | 0 | 0 | 164 |
| 19:45:00 | 23 | 0 | 1 | 0 | 0 | 0 | 7 | 35 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 75 | 4 | 0 | 0 | 0 | 145 |
| 20:00:00 | 10 | 0 | 1 | 0 | 0 | 0 | 6 | 46 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 53 | 3 | 0 | 0 | 0 | 119 |
| 20:15:00 | 9 | 0 | 3 | 0 | 0 | 0 | 2 | 58 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 64 | 7 | 0 | 0 | 0 | 143 |
| 20:30:00 | 8 | 0 | 1 | 0 | 0 | 0 | 4 | 48 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 65 | 4 | 0 | 0 | 0 | 130 |
| 20:45:00 | 10 | 0 | 3 | 0 | 0 | 0 | 3 | 42 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 45 | 5 | 0 | 0 | 0 | 108 |
| 21:00:00 | 14 | 0 | 5 | 0 | 0 | 0 | 5 | 36 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 53 | 2 | 0 | 0 | 0 | 115 |
| 21:15:00 | 16 | 0 | 3 | 0 | 0 | 0 | 1 | 55 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 53 | 0 | 0 | 0 | 0 | 128 |
| 21:30:00 | 10 | 0 | 1 | 0 | 0 | 0 | 3 | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 56 | 2 | 0 | 0 | 0 | 105 |
| 21:45:00 | 6 | 0 | 1 | 0 | 0 | 0 | 2 | 30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 55 | 5 | 0 | 0 | 0 | 99 |
| 22:00:00 | 9 | 0 | 2 | 0 | 0 | 0 | 1 | 35 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 32 | 2 | 0 | 0 | 0 | 81 |
| 22:15:00 | 13 | 0 | 3 | 0 | 0 | 0 | 4 | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 40 | 6 | 0 | 0 | 0 | 98 |
| 22:30:00 | 11 | 0 | 3 | 0 | 0 | 0 | 2 | 43 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 31 | 2 | 0 | 0 | 0 | 92 |
| 22:45:00 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 19 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 22 | 1 | 0 | 0 | 0 | 46 |
| 23:00:00 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17 | 0 | 0 | 0 | 0 | 52 |
| 23:15:00 | 4 | 0 | 1 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | 3 | 0 | 0 | 0 | 35 |
| 23:30:00 | 5 | 0 | 2 | 0 | 0 | 0 | 3 | 19 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 19 | 0 | 0 | 0 | 0 | 48 |
| 23:45:00 | 2 | 0 | 1 | 0 | 0 | 0 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 19 | 0 | 0 | 0 | 0 | 33 |

| Lights | HV | |
|---|---|---|
| 432 | 4 | |
| 388 | 0 | |
| 397 | 1 | |
| 407 | 4 | |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/12/2023 0:00
End Time 10/12/2023 23:59
Location 05-53-431 Rt 263 Ramps (NW) @ Maple
Latitude an 42.99135941,-78.79031239
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 9 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 1 | 0 | 0 | 0 | 23 |
| 0:15:00 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 2 | 0 | 0 | 0 | 21 |
| 0:30:00 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 14 |
| 0:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 0 | 0 | 0 | 13 |
| 1:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 9 |
| 1:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 7 |
| 1:30:00 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 11 |
| 1:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 3 |
| 2:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 5 |
| 2:15:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 4 |
| 2:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 2 |
| 2:45:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 5 |
| 3:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 3 |
| 3:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 |
| 3:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 2 |
| 3:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 6 |
| 4:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 4 |
| 4:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 3 |
| 4:30:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 5 |
| 4:45:00 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 8 |
| 5:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 6 |
| 5:15:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 2 | 0 | 0 | 0 | 16 |
| 5:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 19 |
| 5:45:00 | 7 | 0 | 1 | 0 | 0 | 0 | 1 | 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | 1 | 0 | 0 | 0 | 35 |
| 6:00:00 | 5 | 0 | 1 | 0 | 0 | 0 | 0 | 9 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17 | 1 | 0 | 0 | 0 | 33 |
| 6:15:00 | 4 | 0 | 1 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 1 | 0 | 0 | 0 | 48 |
| 6:30:00 | 9 | 0 | 1 | 0 | 0 | 0 | 1 | 21 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 41 | 1 | 0 | 0 | 0 | 75 |
| 6:45:00 | 6 | 0 | 1 | 0 | 0 | 0 | 14 | 38 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 47 | 0 | 0 | 0 | 0 | 106 |
| 7:00:00 | 6 | 0 | 4 | 0 | 0 | 0 | 44 | 89 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 67 | 0 | 0 | 0 | 0 | 210 |
| 7:15:00 | 6 | 0 | 7 | 0 | 0 | 0 | 67 | 124 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 123 | 0 | 0 | 0 | 0 | 327 |
| 7:30:00 | 22 | 0 | 12 | 0 | 0 | 0 | 100 | 160 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 140 | 4 | 0 | 0 | 0 | 438 |
| 7:45:00 | 14 | 0 | 7 | 0 | 0 | 0 | 80 | 180 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 191 | 3 | 0 | 0 | 0 | 475 |
| 8:00:00 | 14 | 0 | 7 | 0 | 0 | 0 | 69 | 146 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 128 | 3 | 0 | 0 | 0 | 367 |
| 8:15:00 | 10 | 0 | 6 | 0 | 0 | 0 | 70 | 176 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 147 | 1 | 0 | 0 | 0 | 410 |
| 8:30:00 | 24 | 0 | 5 | 0 | 0 | 0 | 93 | 176 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 140 | 1 | 0 | 0 | 0 | 439 |
| 8:45:00 | 20 | 0 | 3 | 0 | 0 | 0 | 57 | 190 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 127 | 2 | 0 | 0 | 0 | 399 |
| 9:00:00 | 20 | 0 | 7 | 0 | 0 | 0 | 57 | 190 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 118 | 1 | 0 | 0 | 0 | 393 |
| 9:15:00 | 23 | 0 | 2 | 0 | 0 | 0 | 58 | 171 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 115 | 1 | 0 | 0 | 0 | 370 |
| 9:30:00 | 15 | 0 | 3 | 0 | 0 | 0 | 62 | 165 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 117 | 2 | 0 | 0 | 0 | 364 |
| 9:45:00 | 19 | 0 | 6 | 0 | 0 | 0 | 36 | 163 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 120 | 2 | 0 | 0 | 0 | 346 |
| 10:00:00 | 26 | 0 | 4 | 0 | 0 | 0 | 56 | 157 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 113 | 0 | 0 | 0 | 0 | 356 |
| 10:15:00 | 23 | 0 | 5 | 0 | 0 | 0 | 31 | 150 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 111 | 1 | 0 | 0 | 0 | 321 |
| 10:30:00 | 26 | 0 | 10 | 0 | 0 | 0 | 57 | 144 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 135 | 0 | 0 | 0 | 0 | 372 |
| 10:45:00 | 29 | 0 | 3 | 0 | 0 | 0 | 55 | 193 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 119 | 1 | 0 | 0 | 0 | 400 |
| 11:00:00 | 35 | 0 | 11 | 0 | 0 | 0 | 39 | 183 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 145 | 0 | 0 | 0 | 0 | 413 |
| 11:15:00 | 33 | 0 | 4 | 0 | 0 | 0 | 54 | 162 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 140 | 5 | 0 | 0 | 0 | 398 |
| 11:30:00 | 31 | 0 | 4 | 0 | 0 | 0 | 51 | 148 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 139 | 4 | 0 | 0 | 0 | 377 |
| 11:45:00 | 24 | 0 | 5 | 0 | 0 | 0 | 56 | 147 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 136 | 3 | 0 | 0 | 0 | 371 |
| 12:00:00 | 35 | 0 | 10 | 0 | 0 | 0 | 57 | 161 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 148 | 0 | 0 | 0 | 0 | 411 |
| 12:15:00 | 41 | 0 | 4 | 0 | 0 | 0 | 66 | 194 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 163 | 4 | 0 | 0 | 0 | 473 |
| 12:30:00 | 27 | 0 | 6 | 0 | 0 | 0 | 54 | 170 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 157 | 2 | 0 | 0 | 0 | 416 |
| 12:45:00 | 24 | 0 | 6 | 0 | 0 | 0 | 46 | 156 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 148 | 1 | 0 | 0 | 0 | 381 |
| 13:00:00 | 34 | 0 | 3 | 0 | 0 | 0 | 48 | 184 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 166 | 2 | 0 | 0 | 0 | 437 |
| 13:15:00 | 27 | 0 | 12 | 0 | 0 | 0 | 52 | 176 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 148 | 2 | 1 | 0 | 0 | 418 |
| 13:30:00 | 29 | 0 | 4 | 0 | 0 | 0 | 58 | 177 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 185 | 4 | 0 | 0 | 0 | 457 |
| 13:45:00 | 24 | 0 | 3 | 0 | 0 | 0 | 54 | 188 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 151 | 3 | 0 | 0 | 0 | 423 |
| 14:00:00 | 34 | 0 | 7 | 0 | 0 | 0 | 62 | 178 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 193 | 5 | 0 | 0 | 0 | 479 |
| 14:15:00 | 23 | 0 | 8 | 0 | 0 | 0 | 63 | 165 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 160 | 3 | 0 | 0 | 0 | 422 |
| 14:30:00 | 22 | 0 | 6 | 0 | 0 | 0 | 62 | 177 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 173 | 3 | 0 | 0 | 0 | 443 |
| 14:45:00 | 30 | 0 | 9 | 0 | 0 | 0 | 42 | 192 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 175 | 1 | 0 | 0 | 0 | 449 |
| 3:00 PM | 27 | 0 | 10 | 0 | 0 | 0 | 70 | 212 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 154 | 2 | 0 | 0 | 0 | 475 |
| 3:15 PM | 32 | 0 | 9 | 0 | 0 | 0 | 61 | 189 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 164 | 3 | 0 | 0 | 0 | 458 |
| 3:30 PM | 44 | 0 | 7 | 0 | 0 | 0 | 71 | 164 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 222 | 6 | 1 | 0 | 0 | 515 |
| 3:45 PM | 28 | 0 | 5 | 0 | 0 | 0 | 51 | 187 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 177 | 2 | 0 | 0 | 0 | 450 |
| 4:00 PM | 30 | 0 | 7 | 0 | 0 | 0 | 82 | 203 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 165 | 1 | 0 | 0 | 0 | 488 |
| 4:15 PM | 20 | 0 | 11 | 0 | 0 | 0 | 84 | 200 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 174 | 6 | 0 | 0 | 0 | 495 |
| 4:30 PM | 28 | 0 | 9 | 0 | 0 | 0 | 83 | 243 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 182 | 2 | 2 | 0 | 0 | 549 |
| 4:45 PM | 29 | 0 | 11 | 0 | 0 | 0 | 44 | 227 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 213 | 2 | 0 | 0 | 0 | 526 |
| 5:00 PM | 43 | 0 | 9 | 0 | 0 | 0 | 47 | 203 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 203 | 4 | 0 | 0 | 0 | 509 |
| 5:15 PM | 37 | 0 | 8 | 0 | 0 | 0 | 62 | 214 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 196 | 4 | 0 | 0 | 0 | 521 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.958561 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 5:30 PM | 24 | 0 | 3 | 0 | 0 | 0 | 79 | 170 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 174 | 2 | 0 | 0 | 0 | 452 |
| 5:45 PM | 32 | 0 | 8 | 0 | 0 | 0 | 59 | 195 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 177 | 0 | 0 | 0 | 0 | 471 |
| 18:00:00 | 33 | 0 | 1 | 0 | 0 | 0 | 46 | 154 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 152 | 3 | 0 | 0 | 0 | 389 |
| 18:15:00 | 16 | 0 | 3 | 0 | 0 | 0 | 37 | 161 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 195 | 2 | 0 | 0 | 0 | 414 |
| 18:30:00 | 34 | 0 | 3 | 0 | 0 | 0 | 53 | 135 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 159 | 2 | 0 | 0 | 0 | 386 |
| 18:45:00 | 26 | 0 | 4 | 0 | 0 | 0 | 35 | 135 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 140 | 5 | 0 | 0 | 0 | 345 |
| 19:00:00 | 18 | 0 | 4 | 0 | 0 | 0 | 15 | 126 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 120 | 1 | 0 | 0 | 0 | 284 |
| 19:15:00 | 20 | 0 | 3 | 0 | 0 | 0 | 27 | 122 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 100 | 3 | 0 | 0 | 0 | 275 |
| 19:30:00 | 11 | 0 | 2 | 0 | 0 | 0 | 24 | 97 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 107 | 1 | 0 | 0 | 0 | 242 |
| 19:45:00 | 19 | 0 | 4 | 0 | 0 | 0 | 20 | 91 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 110 | 4 | 0 | 0 | 0 | 248 |
| 20:00:00 | 11 | 0 | 3 | 0 | 0 | 0 | 13 | 60 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 82 | 2 | 0 | 0 | 0 | 171 |
| 20:15:00 | 19 | 0 | 4 | 0 | 0 | 0 | 18 | 62 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 65 | 4 | 0 | 0 | 0 | 172 |
| 20:30:00 | 13 | 0 | 2 | 0 | 0 | 0 | 13 | 53 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 67 | 2 | 0 | 0 | 0 | 150 |
| 20:45:00 | 13 | 0 | 3 | 0 | 0 | 0 | 12 | 69 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 55 | 0 | 0 | 0 | 0 | 152 |
| 21:00:00 | 11 | 0 | 2 | 0 | 0 | 0 | 12 | 56 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 45 | 1 | 0 | 0 | 0 | 127 |
| 21:15:00 | 6 | 0 | 0 | 0 | 0 | 0 | 6 | 53 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 52 | 1 | 0 | 0 | 0 | 118 |
| 21:30:00 | 9 | 0 | 2 | 0 | 0 | 0 | 3 | 40 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 40 | 3 | 0 | 0 | 0 | 97 |
| 21:45:00 | 7 | 0 | 1 | 0 | 0 | 0 | 5 | 39 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 35 | 1 | 0 | 0 | 0 | 88 |
| 22:00:00 | 8 | 0 | 2 | 0 | 0 | 0 | 8 | 47 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 47 | 0 | 0 | 0 | 0 | 112 |
| 22:15:00 | 6 | 0 | 0 | 0 | 0 | 0 | 3 | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 37 | 1 | 0 | 0 | 0 | 78 |
| 22:30:00 | 2 | 0 | 1 | 0 | 0 | 0 | 2 | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 38 | 1 | 0 | 0 | 0 | 75 |
| 22:45:00 | 0 | 0 | 1 | 0 | 0 | 0 | 4 | 29 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 25 | 3 | 0 | 0 | 0 | 62 |
| 23:00:00 | 4 | 0 | 1 | 0 | 0 | 0 | 4 | 28 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | 2 | 0 | 0 | 0 | 52 |
| 23:15:00 | 5 | 0 | 3 | 0 | 0 | 0 | 3 | 29 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 19 | 0 | 0 | 0 | 0 | 59 |
| 23:30:00 | 4 | 0 | 1 | 0 | 0 | 0 | 7 | 19 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 23 | 2 | 0 | 0 | 0 | 56 |
| 23:45:00 | 3 | 0 | 2 | 0 | 0 | 0 | 2 | 16 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 0 | 0 | 0 | 38 |

| | Lights | HV | |
|---|---|---|---|
| | 543 | 6 | |
| | 517 | 9 | |
| | 504 | 5 | |
| | 515 | 6 | |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/28/2023 0:00
End Time 10/28/2023 23:59
Location 05-53-432 Rt 263 Ramps (SE) @ Maple
Latitude an 42.99121539,-78.787746
Lights

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 35 | 0 | 0 | 0 | 0 | 15 | 0 | 2 | 0 | 0 | 0 | 0 | 31 | 6 | 0 | 0 | 0 | 91 |
| 0:15:00 | | 0 | 0 | 0 | 0 | 0 | 5 | 33 | 0 | 0 | 0 | 0 | 26 | 0 | 3 | 0 | 0 | 0 | 0 | 17 | 5 | 0 | 0 | 0 | 89 |
| 0:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 15 | 0 | 3 | 0 | 0 | 0 | 0 | 22 | 3 | 0 | 0 | 0 | 55 |
| 0:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 28 | 0 | 0 | 0 | 0 | 9 | 1 | 2 | 0 | 0 | 0 | 0 | 16 | 0 | 0 | 0 | 0 | 56 |
| 1:00:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 17 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | 2 | 0 | 0 | 0 | 53 |
| 1:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 0 | 0 | 0 | 0 | 6 | 0 | 3 | 0 | 0 | 0 | 0 | 14 | 1 | 0 | 0 | 0 | 33 |
| 1:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 6 | 0 | 5 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 35 |
| 1:45:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 11 | 0 | 0 | 0 | 0 | 14 | 0 | 2 | 0 | 0 | 0 | 0 | 14 | 0 | 0 | 0 | 0 | 43 |
| 2:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 14 | 0 | 3 | 0 | 0 | 0 | 0 | 12 | 1 | 0 | 0 | 0 | 43 |
| 2:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 1 | 0 | 0 | 0 | 28 |
| 2:30:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 7 | 0 | 0 | 0 | 0 | 7 | 0 | 2 | 0 | 0 | 0 | 0 | 8 | 2 | 0 | 0 | 0 | 27 |
| 2:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 1 | 0 | 0 | 0 | 21 |
| 3:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 0 | 7 | 3 | 0 | 0 | 0 | 18 |
| 3:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 9 | 0 | 1 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 20 |
| 3:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 1 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 15 |
| 3:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 2 | 0 | 0 | 0 | 15 |
| 4:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 8 | 0 | 1 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 21 |
| 4:15:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 2 | 0 | 0 | 0 | 18 |
| 4:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 4 | 0 | 1 | 0 | 0 | 0 | 0 | 8 | 2 | 0 | 0 | 0 | 20 |
| 4:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 8 | 0 | 0 | 0 | 0 | 8 | 0 | 1 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 21 |
| 5:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 22 |
| 5:15:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 20 |
| 5:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 0 | 0 | 0 | 14 | 0 | 2 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 33 |
| 5:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 0 | 0 | 0 | 0 | 21 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 0 | 0 | 0 | 41 |
| 6:00:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 20 | 0 | 0 | 0 | 0 | 12 | 0 | 1 | 0 | 0 | 0 | 0 | 8 | 1 | 0 | 0 | 0 | 43 |
| 6:15:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 21 | 0 | 0 | 0 | 0 | 40 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 75 |
| 6:30:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 19 | 0 | 0 | 0 | 0 | 33 | 0 | 1 | 0 | 0 | 0 | 0 | 14 | 0 | 0 | 0 | 0 | 70 |
| 6:45:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 25 | 0 | 0 | 0 | 0 | 34 | 0 | 3 | 0 | 0 | 0 | 0 | 15 | 1 | 0 | 0 | 0 | 81 |
| 7:00:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 24 | 0 | 0 | 0 | 0 | 28 | 0 | 2 | 0 | 0 | 0 | 0 | 9 | 2 | 0 | 0 | 0 | 68 |
| 7:15:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 34 | 0 | 0 | 0 | 0 | 26 | 0 | 1 | 0 | 0 | 0 | 0 | 21 | 0 | 0 | 0 | 0 | 84 |
| 7:30:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 65 | 0 | 0 | 0 | 0 | 36 | 1 | 4 | 0 | 0 | 0 | 0 | 42 | 1 | 0 | 0 | 0 | 151 |
| 7:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 58 | 0 | 0 | 0 | 0 | 32 | 0 | 4 | 0 | 0 | 0 | 0 | 44 | 6 | 0 | 0 | 0 | 145 |
| 8:00:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 79 | 0 | 0 | 0 | 0 | 44 | 1 | 3 | 0 | 0 | 0 | 0 | 37 | 4 | 0 | 0 | 0 | 169 |
| 8:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 90 | 0 | 0 | 0 | 0 | 42 | 0 | 1 | 0 | 0 | 0 | 0 | 46 | 4 | 0 | 0 | 0 | 183 |
| 8:30:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 83 | 0 | 0 | 0 | 0 | 39 | 0 | 3 | 0 | 0 | 0 | 0 | 50 | 8 | 0 | 0 | 0 | 186 |
| 8:45:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 122 | 0 | 0 | 0 | 0 | 82 | 0 | 4 | 0 | 0 | 0 | 0 | 67 | 9 | 0 | 0 | 0 | 287 |
| 9:00:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 109 | 0 | 0 | 0 | 0 | 43 | 0 | 6 | 0 | 0 | 0 | 0 | 57 | 5 | 0 | 0 | 0 | 221 |
| 9:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 121 | 0 | 0 | 0 | 0 | 65 | 0 | 7 | 0 | 0 | 0 | 0 | 64 | 7 | 0 | 0 | 0 | 264 |
| 9:30:00 | | 0 | 0 | 0 | 0 | 0 | 4 | 158 | 0 | 0 | 0 | 0 | 57 | 0 | 8 | 0 | 0 | 0 | 0 | 72 | 8 | 0 | 0 | 0 | 307 |
| 9:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 158 | 0 | 0 | 0 | 0 | 83 | 0 | 6 | 0 | 0 | 0 | 0 | 67 | 11 | 0 | 0 | 0 | 325 |
| 10:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 163 | 0 | 0 | 0 | 0 | 60 | 0 | 7 | 0 | 0 | 0 | 0 | 84 | 15 | 0 | 0 | 0 | 329 |
| 10:15:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 164 | 0 | 0 | 0 | 0 | 67 | 0 | 4 | 0 | 0 | 0 | 0 | 75 | 7 | 0 | 0 | 0 | 320 |
| 10:30:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 149 | 0 | 0 | 0 | 0 | 64 | 0 | 1 | 0 | 0 | 0 | 0 | 110 | 13 | 0 | 0 | 0 | 339 |
| 10:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 168 | 0 | 0 | 0 | 0 | 72 | 0 | 11 | 0 | 0 | 0 | 0 | 120 | 19 | 0 | 0 | 0 | 390 |
| 11:00:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 178 | 0 | 0 | 0 | 0 | 72 | 0 | 5 | 0 | 0 | 0 | 0 | 93 | 7 | 0 | 0 | 0 | 356 |
| 11:15:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 214 | 0 | 0 | 0 | 0 | 72 | 0 | 13 | 0 | 0 | 0 | 0 | 107 | 19 | 0 | 0 | 0 | 428 |
| 11:30:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 183 | 0 | 0 | 0 | 0 | 86 | 0 | 8 | 0 | 0 | 0 | 0 | 124 | 30 | 0 | 0 | 0 | 433 |
| 11:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 168 | 0 | 0 | 0 | 0 | 84 | 0 | 7 | 0 | 0 | 0 | 0 | 130 | 17 | 0 | 0 | 0 | 406 |
| 12:00:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 225 | 0 | 0 | 0 | 0 | 60 | 0 | 8 | 0 | 0 | 0 | 0 | 130 | 18 | 0 | 0 | 0 | 444 |
| 12:15:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 221 | 0 | 0 | 0 | 0 | 67 | 0 | 14 | 0 | 0 | 0 | 0 | 156 | 13 | 0 | 0 | 0 | 472 |
| 12:30:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 191 | 0 | 0 | 0 | 0 | 67 | 0 | 4 | 0 | 0 | 0 | 0 | 126 | 24 | 0 | 0 | 0 | 413 |
| 12:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 231 | 0 | 0 | 0 | 0 | 85 | 0 | 12 | 0 | 0 | 0 | 0 | 143 | 14 | 0 | 0 | 0 | 486 |
| 13:00:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 187 | 0 | 0 | 0 | 0 | 90 | 1 | 9 | 0 | 0 | 0 | 0 | 139 | 16 | 0 | 0 | 0 | 445 |
| 13:15:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 208 | 0 | 0 | 0 | 0 | 84 | 0 | 9 | 0 | 0 | 0 | 0 | 121 | 16 | 0 | 0 | 0 | 440 |
| 13:30:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 232 | 0 | 0 | 0 | 0 | 101 | 0 | 11 | 0 | 0 | 0 | 0 | 116 | 15 | 0 | 0 | 0 | 478 |
| 13:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 177 | 0 | 0 | 0 | 0 | 79 | 0 | 10 | 0 | 0 | 0 | 0 | 129 | 17 | 0 | 0 | 0 | 413 |
| 14:00:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 199 | 0 | 0 | 0 | 0 | 87 | 1 | 8 | 0 | 0 | 0 | 0 | 135 | 14 | 0 | 0 | 0 | 446 |
| 14:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 214 | 0 | 0 | 0 | 0 | 68 | 0 | 9 | 0 | 0 | 0 | 0 | 146 | 16 | 0 | 0 | 0 | 453 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.936192 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | | 0 | 0 | 0 | 0 | 0 | 5 | 183 | 0 | 0 | 0 | 0 | 55 | 1 | 12 | 0 | 0 | 0 | 0 | 131 | 19 | 0 | 0 | 0 | 406 |
| 14:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 200 | 0 | 0 | 0 | 0 | 77 | 0 | 6 | 0 | 0 | 0 | 0 | 132 | 21 | 0 | 0 | 0 | 437 |
| 15:00:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 195 | 0 | 0 | 0 | 0 | 66 | 0 | 10 | 0 | 0 | 0 | 0 | 141 | 17 | 0 | 0 | 0 | 432 |
| 15:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 238 | 0 | 0 | 0 | 0 | 59 | 1 | 11 | 0 | 0 | 0 | 0 | 176 | 16 | 0 | 0 | 0 | 501 |
| 15:30:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 186 | 0 | 0 | 0 | 0 | 72 | 0 | 8 | 0 | 0 | 0 | 0 | 142 | 25 | 0 | 0 | 0 | 434 |
| 15:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 198 | 0 | 0 | 0 | 0 | 63 | 0 | 7 | 0 | 0 | 0 | 0 | 149 | 16 | 0 | 0 | 0 | 434 |
| 16:00:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 215 | 0 | 0 | 0 | 0 | 63 | 0 | 13 | 0 | 0 | 0 | 0 | 142 | 22 | 0 | 0 | 0 | 457 |
| 16:15:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 153 | 0 | 0 | 0 | 0 | 66 | 0 | 7 | 0 | 0 | 0 | 0 | 130 | 26 | 0 | 0 | 0 | 383 |
| 16:30:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 191 | 0 | 0 | 0 | 0 | 72 | 0 | 6 | 0 | 0 | 0 | 0 | 126 | 16 | 0 | 0 | 0 | 414 |
| 16:45:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 152 | 0 | 0 | 0 | 0 | 78 | 0 | 10 | 0 | 0 | 0 | 0 | 122 | 20 | 0 | 0 | 0 | 382 |
| 17:00:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 176 | 0 | 0 | 0 | 0 | 86 | 0 | 7 | 0 | 0 | 0 | 0 | 131 | 19 | 0 | 0 | 0 | 421 |
| 17:15:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 177 | 0 | 0 | 0 | 0 | 70 | 1 | 11 | 0 | 0 | 0 | 0 | 113 | 14 | 0 | 0 | 0 | 387 |
| 17:30:00 | | 0 | 0 | 0 | 0 | 0 | 4 | 145 | 0 | 0 | 0 | 0 | 64 | 0 | 10 | 0 | 0 | 0 | 0 | 114 | 20 | 0 | 0 | 0 | 357 |
| 17:45:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 159 | 0 | 0 | 0 | 0 | 69 | 1 | 12 | 0 | 0 | 0 | 0 | 100 | 17 | 0 | 0 | 0 | 360 |
| 18:00:00 | | 0 | 0 | 0 | 0 | 0 | 4 | 166 | 0 | 0 | 0 | 0 | 72 | 0 | 9 | 0 | 0 | 0 | 0 | 117 | 25 | 0 | 0 | 0 | 393 |
| 18:15:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 171 | 0 | 0 | 0 | 0 | 76 | 0 | 9 | 0 | 0 | 0 | 0 | 124 | 17 | 0 | 0 | 0 | 399 |
| 18:30:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 152 | 0 | 0 | 0 | 0 | 56 | 0 | 8 | 0 | 0 | 0 | 0 | 113 | 16 | 0 | 0 | 0 | 348 |
| 18:45:00 | | 0 | 0 | 0 | 0 | 0 | 9 | 149 | 0 | 0 | 0 | 0 | 59 | 0 | 6 | 0 | 0 | 0 | 0 | 118 | 17 | 0 | 0 | 0 | 358 |
| 19:00:00 | | 0 | 0 | 0 | 0 | 0 | 4 | 118 | 0 | 0 | 0 | 0 | 67 | 0 | 11 | 0 | 0 | 0 | 0 | 124 | 13 | 0 | 0 | 0 | 337 |
| 19:15:00 | | 0 | 0 | 0 | 0 | 0 | 8 | 121 | 0 | 0 | 0 | 0 | 52 | 0 | 8 | 0 | 0 | 0 | 0 | 103 | 7 | 0 | 0 | 0 | 299 |
| 19:30:00 | | 0 | 0 | 0 | 0 | 0 | 8 | 102 | 0 | 0 | 0 | 0 | 50 | 0 | 9 | 0 | 0 | 0 | 0 | 67 | 12 | 0 | 0 | 0 | 248 |
| 19:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 94 | 0 | 0 | 0 | 0 | 41 | 1 | 7 | 0 | 0 | 0 | 0 | 65 | 19 | 0 | 0 | 0 | 228 |
| 20:00:00 | | 0 | 0 | 0 | 0 | 0 | 5 | 104 | 0 | 1 | 0 | 0 | 41 | 1 | 4 | 0 | 0 | 0 | 0 | 89 | 11 | 0 | 0 | 0 | 256 |
| 20:15:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 83 | 0 | 0 | 0 | 0 | 36 | 0 | 4 | 0 | 0 | 0 | 0 | 64 | 9 | 0 | 0 | 0 | 198 |
| 20:30:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 81 | 0 | 0 | 0 | 0 | 28 | 0 | 4 | 0 | 0 | 0 | 0 | 73 | 7 | 0 | 0 | 0 | 196 |
| 20:45:00 | | 0 | 0 | 0 | 0 | 0 | 2 | 97 | 0 | 0 | 0 | 0 | 36 | 0 | 5 | 0 | 0 | 0 | 0 | 62 | 13 | 0 | 0 | 0 | 215 |
| 21:00:00 | | 0 | 0 | 0 | 0 | 0 | 4 | 90 | 0 | 0 | 0 | 0 | 37 | 0 | 3 | 0 | 0 | 0 | 0 | 73 | 7 | 0 | 0 | 0 | 214 |
| 21:15:00 | | 0 | 0 | 0 | 0 | 0 | 9 | 71 | 0 | 0 | 0 | 0 | 31 | 0 | 5 | 0 | 0 | 0 | 0 | 58 | 13 | 0 | 0 | 0 | 187 |
| 21:30:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 69 | 0 | 0 | 0 | 0 | 34 | 0 | 7 | 0 | 0 | 0 | 0 | 45 | 5 | 0 | 0 | 0 | 161 |
| 21:45:00 | | 0 | 0 | 0 | 0 | 0 | 7 | 71 | 0 | 0 | 0 | 0 | 38 | 1 | 1 | 0 | 0 | 0 | 0 | 45 | 4 | 0 | 0 | 0 | 167 |
| 22:00:00 | | 0 | 0 | 0 | 0 | 0 | 5 | 71 | 0 | 1 | 0 | 0 | 27 | 1 | 1 | 0 | 0 | 0 | 0 | 39 | 8 | 0 | 0 | 0 | 153 |
| 22:15:00 | | 0 | 0 | 0 | 0 | 0 | 5 | 56 | 0 | 0 | 0 | 0 | 41 | 1 | 3 | 0 | 0 | 0 | 0 | 33 | 9 | 0 | 0 | 0 | 148 |
| 22:30:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 50 | 0 | 0 | 0 | 0 | 20 | 0 | 3 | 0 | 0 | 0 | 0 | 28 | 7 | 0 | 0 | 0 | 109 |
| 22:45:00 | | 0 | 0 | 0 | 0 | 0 | 3 | 46 | 0 | 0 | 0 | 0 | 29 | 0 | 7 | 0 | 0 | 0 | 0 | 35 | 2 | 0 | 0 | 0 | 122 |
| 23:00:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 40 | 0 | 0 | 0 | 0 | 26 | 0 | 2 | 0 | 0 | 0 | 0 | 33 | 4 | 0 | 0 | 0 | 105 |
| 23:15:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 37 | 0 | 0 | 0 | 0 | 32 | 0 | 5 | 0 | 0 | 0 | 0 | 28 | 6 | 0 | 0 | 0 | 108 |
| 23:30:00 | | 0 | 0 | 0 | 0 | 0 | 0 | 33 | 0 | 0 | 0 | 0 | 23 | 0 | 2 | 0 | 0 | 0 | 0 | 24 | 2 | 0 | 0 | 0 | 84 |
| 23:45:00 | | 0 | 0 | 0 | 0 | 0 | 1 | 23 | 0 | 0 | 0 | 0 | 24 | 0 | 2 | 0 | 0 | 0 | 0 | 20 | 2 | 0 | 0 | 0 | 72 |

| | Lights | HV |
|---|---|---|
| | 477 | 1 |
| | 412 | 1 |
| | 443 | 3 |
| | 452 | 1 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/26/2023 0:00
End Time 10/26/2023 23:59
Location 05-53-432 Rt 263 Ramps (SE) @ Maple
Latitude an 42.99121539,-78.787746
Lights

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 2 | 0 | 0 | 0 | 0 | 5 | 3 | 0 | 0 | 0 | 34 |
| 0:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 14 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 1 | 0 | 0 | 0 | 0 | 11 | 2 | 0 | 0 | 0 | 36 |
| 0:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 9 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 2 | 0 | 0 | 0 | 0 | 11 | 2 | 0 | 0 | 0 | 32 |
| 0:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 8 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 17 |
| 1:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 4 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 19 |
| 1:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 9 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 22 |
| 1:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 19 |
| 1:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 12 |
| 2:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 15 |
| 2:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 6 |
| 2:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 12 |
| 2:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 7 |
| 3:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 8 |
| 3:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 10 |
| 3:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 10 |
| 3:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 13 |
| 4:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 8 |
| 4:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 9 |
| 4:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 14 |
| 4:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 10 | 0 | 0 | 0 | 0 | 0 | 11 | 0 | 2 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 32 |
| 5:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 2 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 20 |
| 5:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 16 | 0 | 0 | 0 | 0 | 0 | 20 | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 48 |
| 5:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | 0 | 0 | 0 | 0 | 0 | 27 | 0 | 1 | 0 | 0 | 0 | 0 | 22 | 0 | 0 | 0 | 0 | 70 |
| 5:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 18 | 0 | 0 | 0 | 0 | 0 | 43 | 1 | 1 | 0 | 0 | 0 | 0 | 21 | 0 | 0 | 0 | 0 | 85 |
| 6:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 22 | 0 | 0 | 0 | 0 | 0 | 30 | 0 | 1 | 0 | 0 | 0 | 0 | 21 | 2 | 0 | 0 | 0 | 79 |
| 6:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 40 | 0 | 0 | 0 | 0 | 0 | 67 | 0 | 0 | 0 | 0 | 0 | 0 | 32 | 0 | 0 | 0 | 0 | 141 |
| 6:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 58 | 0 | 0 | 0 | 0 | 0 | 66 | 0 | 0 | 0 | 0 | 0 | 0 | 45 | 2 | 0 | 0 | 0 | 177 |
| 6:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 66 | 0 | 1 | 0 | 0 | 0 | 92 | 0 | 3 | 0 | 0 | 0 | 0 | 51 | 6 | 0 | 0 | 0 | 225 |
| 7:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 82 | 0 | 2 | 0 | 0 | 0 | 77 | 0 | 5 | 0 | 0 | 0 | 0 | 47 | 9 | 1 | 0 | 0 | 231 |
| 7:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 166 | 0 | 0 | 0 | 0 | 0 | 117 | 0 | 7 | 0 | 0 | 0 | 0 | 74 | 6 | 0 | 0 | 0 | 377 |
| 7:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 241 | 0 | 0 | 0 | 0 | 0 | 110 | 0 | 9 | 0 | 0 | 0 | 0 | 149 | 7 | 0 | 0 | 0 | 523 |
| 7:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 244 | 0 | 0 | 0 | 0 | 0 | 145 | 1 | 12 | 0 | 0 | 0 | 0 | 179 | 10 | 0 | 0 | 0 | 598 |
| 8:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 238 | 0 | 0 | 0 | 0 | 0 | 133 | 0 | 11 | 0 | 0 | 0 | 0 | 128 | 6 | 0 | 0 | 0 | 518 |
| 8:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 193 | 0 | 0 | 0 | 0 | 0 | 135 | 1 | 16 | 0 | 0 | 0 | 0 | 148 | 19 | 0 | 0 | 0 | 516 |
| 8:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 223 | 0 | 0 | 0 | 0 | 0 | 110 | 1 | 13 | 0 | 0 | 0 | 0 | 141 | 10 | 0 | 0 | 0 | 505 |
| 8:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 260 | 0 | 0 | 0 | 0 | 0 | 156 | 0 | 20 | 0 | 0 | 0 | 0 | 107 | 12 | 0 | 0 | 0 | 562 |
| 9:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 237 | 0 | 0 | 0 | 0 | 0 | 86 | 1 | 9 | 0 | 0 | 0 | 0 | 119 | 8 | 0 | 0 | 0 | 470 |
| 9:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 201 | 0 | 0 | 0 | 0 | 0 | 91 | 0 | 10 | 0 | 0 | 0 | 0 | 97 | 16 | 0 | 0 | 0 | 426 |
| 9:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 177 | 0 | 0 | 0 | 0 | 0 | 91 | 2 | 12 | 0 | 0 | 0 | 0 | 119 | 12 | 0 | 0 | 0 | 417 |
| 9:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 183 | 0 | 0 | 0 | 0 | 0 | 88 | 0 | 13 | 0 | 0 | 0 | 0 | 127 | 13 | 0 | 0 | 0 | 430 |
| 10:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 171 | 0 | 0 | 0 | 0 | 0 | 83 | 0 | 10 | 0 | 0 | 0 | 0 | 101 | 10 | 0 | 0 | 0 | 375 |
| 10:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 212 | 0 | 0 | 0 | 0 | 0 | 84 | 0 | 5 | 0 | 0 | 0 | 0 | 115 | 9 | 0 | 0 | 0 | 426 |
| 10:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 212 | 0 | 0 | 0 | 0 | 0 | 87 | 1 | 9 | 0 | 0 | 0 | 0 | 105 | 11 | 0 | 0 | 0 | 428 |
| 10:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 208 | 0 | 0 | 0 | 0 | 0 | 95 | 1 | 11 | 0 | 0 | 0 | 0 | 117 | 12 | 0 | 0 | 0 | 452 |
| 11:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 208 | 0 | 0 | 0 | 0 | 0 | 80 | 0 | 12 | 0 | 0 | 0 | 0 | 118 | 10 | 0 | 0 | 0 | 431 |
| 11:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 213 | 0 | 0 | 0 | 0 | 0 | 78 | 0 | 8 | 0 | 0 | 0 | 0 | 125 | 12 | 0 | 0 | 0 | 437 |
| 11:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 207 | 0 | 0 | 0 | 0 | 0 | 72 | 0 | 12 | 0 | 0 | 0 | 0 | 130 | 14 | 0 | 0 | 0 | 437 |
| 11:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 228 | 0 | 0 | 0 | 0 | 0 | 69 | 2 | 12 | 0 | 0 | 0 | 0 | 146 | 14 | 0 | 0 | 0 | 475 |
| 12:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 229 | 0 | 0 | 0 | 0 | 0 | 77 | 0 | 12 | 0 | 0 | 0 | 0 | 141 | 21 | 0 | 0 | 0 | 481 |
| 12:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 227 | 0 | 0 | 0 | 0 | 0 | 75 | 0 | 9 | 0 | 0 | 0 | 0 | 168 | 17 | 0 | 0 | 0 | 499 |
| 12:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 208 | 0 | 0 | 0 | 0 | 0 | 92 | 1 | 10 | 0 | 0 | 0 | 0 | 180 | 19 | 0 | 0 | 0 | 512 |
| 12:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 183 | 0 | 0 | 0 | 0 | 0 | 112 | 0 | 15 | 0 | 0 | 0 | 0 | 161 | 19 | 0 | 0 | 0 | 494 |
| 13:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 205 | 0 | 0 | 0 | 0 | 0 | 83 | 0 | 14 | 0 | 0 | 0 | 0 | 150 | 19 | 0 | 0 | 0 | 474 |
| 13:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 214 | 0 | 0 | 0 | 0 | 0 | 88 | 0 | 2 | 0 | 0 | 0 | 0 | 141 | 8 | 0 | 0 | 0 | 456 |
| 13:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 215 | 0 | 0 | 0 | 0 | 0 | 103 | 0 | 13 | 0 | 0 | 0 | 0 | 142 | 20 | 0 | 0 | 0 | 499 |
| 13:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 183 | 0 | 0 | 0 | 0 | 0 | 104 | 1 | 17 | 0 | 0 | 0 | 0 | 145 | 23 | 0 | 0 | 0 | 478 |
| 14:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 229 | 0 | 0 | 0 | 0 | 0 | 97 | 2 | 11 | 0 | 0 | 0 | 0 | 205 | 16 | 0 | 0 | 0 | 564 |
| 14:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 234 | 0 | 0 | 0 | 0 | 0 | 103 | 0 | 12 | 0 | 0 | 0 | 0 | 143 | 15 | 0 | 0 | 0 | 510 |
| 14:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 232 | 0 | 0 | 0 | 0 | 0 | 110 | 0 | 9 | 0 | 0 | 0 | 0 | 203 | 17 | 0 | 0 | 0 | 573 |
| 14:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 252 | 0 | 0 | 0 | 0 | 0 | 114 | 1 | 12 | 0 | 0 | 0 | 0 | 242 | 20 | 0 | 0 | 0 | 643 |
| 3:00 PM | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 270 | 0 | 0 | 0 | 0 | 0 | 125 | 0 | 11 | 0 | 0 | 0 | 0 | 229 | 20 | 0 | 0 | 0 | 656 |
| 3:15 PM | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 259 | 0 | 0 | 0 | 0 | 0 | 106 | 0 | 19 | 0 | 0 | 0 | 0 | 250 | 30 | 0 | 0 | 0 | 666 |
| 3:30 PM | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 269 | 0 | 0 | 0 | 0 | 0 | 112 | 0 | 15 | 0 | 0 | 0 | 0 | 280 | 16 | 0 | 0 | 0 | 693 |
| 3:45 PM | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 279 | 0 | 0 | 0 | 0 | 0 | 123 | 2 | 12 | 0 | 0 | 0 | 0 | 270 | 26 | 0 | 0 | 0 | 714 |
| 4:00 PM | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 278 | 0 | 0 | 0 | 0 | 0 | 148 | 0 | 14 | 0 | 0 | 0 | 0 | 251 | 25 | 0 | 0 | 0 | 720 |
| 4:15 PM | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 266 | 0 | 0 | 0 | 0 | 0 | 164 | 1 | 12 | 0 | 0 | 0 | 0 | 220 | 27 | 0 | 0 | 0 | 695 |
| 4:30 PM | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 260 | 0 | 0 | 0 | 0 | 0 | 167 | 1 | 10 | 0 | 0 | 0 | 0 | 240 | 14 | 0 | 0 | 0 | 697 |
| 4:45 PM | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 263 | 0 | 0 | 0 | 0 | 0 | 150 | 0 | 18 | 0 | 0 | 0 | 0 | 205 | 23 | 0 | 0 | 0 | 662 |
| 5:00 PM | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 237 | 0 | 0 | 0 | 0 | 0 | 124 | 1 | 10 | 0 | 0 | 0 | 0 | 243 | 23 | 0 | 0 | 0 | 640 |
| 5:15 PM | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 280 | 0 | 0 | 0 | 0 | 0 | 119 | 0 | 18 | 0 | 0 | 0 | 0 | 183 | 23 | 0 | 0 | 0 | 628 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.942253 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 5:30 PM | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 227 | 0 | 0 | 0 | 0 | 0 | 139 | 0 | 11 | 0 | 0 | 0 | 0 | 196 | 22 | 0 | 0 | 0 | 598 |
| 5:45 PM | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 188 | 0 | 0 | 0 | 0 | 0 | 119 | 1 | 11 | 0 | 0 | 0 | 0 | 171 | 15 | 0 | 0 | 0 | 508 |
| 18:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 182 | 0 | 0 | 0 | 0 | 0 | 114 | 0 | 11 | 0 | 0 | 0 | 0 | 159 | 17 | 0 | 0 | 0 | 487 |
| 18:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 178 | 0 | 0 | 0 | 0 | 0 | 102 | 1 | 16 | 0 | 0 | 0 | 0 | 152 | 20 | 0 | 0 | 0 | 471 |
| 18:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 164 | 0 | 0 | 0 | 0 | 0 | 70 | 0 | 8 | 0 | 0 | 0 | 0 | 122 | 15 | 0 | 0 | 0 | 386 |
| 18:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 151 | 0 | 0 | 0 | 0 | 0 | 61 | 1 | 13 | 0 | 0 | 0 | 0 | 128 | 29 | 0 | 0 | 0 | 389 |
| 19:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 135 | 0 | 0 | 0 | 0 | 0 | 60 | 0 | 10 | 0 | 0 | 0 | 0 | 111 | 14 | 0 | 0 | 0 | 336 |
| 19:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 108 | 0 | 0 | 0 | 0 | 0 | 53 | 0 | 7 | 0 | 0 | 0 | 0 | 101 | 21 | 0 | 0 | 0 | 294 |
| 19:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 101 | 0 | 0 | 0 | 0 | 0 | 43 | 0 | 3 | 0 | 0 | 0 | 0 | 84 | 22 | 0 | 0 | 0 | 264 |
| 19:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 95 | 0 | 0 | 0 | 0 | 0 | 52 | 2 | 4 | 0 | 0 | 0 | 0 | 86 | 16 | 0 | 0 | 0 | 259 |
| 20:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 77 | 0 | 0 | 0 | 0 | 0 | 35 | 1 | 4 | 0 | 0 | 0 | 0 | 67 | 12 | 0 | 0 | 0 | 208 |
| 20:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 81 | 0 | 0 | 0 | 0 | 0 | 37 | 1 | 4 | 0 | 0 | 0 | 0 | 65 | 15 | 0 | 0 | 0 | 209 |
| 20:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 79 | 0 | 0 | 0 | 0 | 0 | 31 | 0 | 8 | 0 | 0 | 0 | 0 | 49 | 11 | 0 | 0 | 0 | 180 |
| 20:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 54 | 0 | 0 | 0 | 0 | 0 | 32 | 0 | 5 | 0 | 0 | 0 | 0 | 50 | 9 | 0 | 0 | 0 | 154 |
| 21:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 56 | 0 | 1 | 0 | 0 | 0 | 21 | 0 | 4 | 0 | 0 | 0 | 0 | 51 | 5 | 0 | 0 | 0 | 139 |
| 21:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 40 | 0 | 0 | 0 | 0 | 0 | 27 | 0 | 5 | 0 | 0 | 0 | 0 | 53 | 8 | 0 | 0 | 0 | 138 |
| 21:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 64 | 0 | 0 | 0 | 0 | 0 | 26 | 0 | 6 | 0 | 0 | 0 | 0 | 39 | 6 | 0 | 0 | 0 | 143 |
| 21:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 53 | 0 | 0 | 0 | 0 | 0 | 24 | 0 | 4 | 0 | 0 | 0 | 0 | 41 | 10 | 0 | 0 | 0 | 134 |
| 22:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 55 | 0 | 0 | 0 | 0 | 0 | 18 | 0 | 6 | 0 | 0 | 0 | 0 | 46 | 7 | 0 | 0 | 0 | 133 |
| 22:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 44 | 0 | 0 | 0 | 0 | 0 | 22 | 0 | 2 | 0 | 0 | 0 | 0 | 28 | 8 | 0 | 0 | 0 | 107 |
| 22:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 35 | 0 | 0 | 0 | 0 | 0 | 16 | 0 | 9 | 0 | 0 | 0 | 0 | 24 | 2 | 0 | 0 | 0 | 88 |
| 22:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 0 | 0 | 0 | 0 | 0 | 21 | 1 | 2 | 0 | 0 | 0 | 0 | 32 | 3 | 0 | 0 | 0 | 88 |
| 23:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 36 | 0 | 0 | 0 | 0 | 0 | 14 | 1 | 3 | 0 | 0 | 0 | 0 | 27 | 10 | 0 | 0 | 0 | 95 |
| 23:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 22 | 0 | 0 | 0 | 0 | 0 | 15 | 0 | 2 | 0 | 0 | 0 | 0 | 22 | 3 | 0 | 0 | 0 | 66 |
| 23:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 68 | 0 | 0 | 0 | 0 | 0 | 35 | 0 | 2 | 0 | 0 | 0 | 0 | 30 | 7 | 0 | 0 | 0 | 144 |
| 23:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 27 | 0 | 0 | 0 | 0 | 0 | 28 | 0 | 2 | 0 | 0 | 0 | 0 | 25 | 1 | 0 | 0 | 0 | 84 |

| Lights | HV |
|---|---|
| 692 | 5 |
| 651 | 11 |
| 634 | 6 |
| 626 | 2 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/28/2023 0:00
End Time 10/28/2023 23:59
Location 05-53-554P Rt 62 (NFB) @ Consumer Sq Plaza
Latitude an 42.99962237,-78.82240171
Lights

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 0:00:00 | 2 | 20 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 35 |
| 0:15:00 | 2 | 22 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 36 |
| 0:30:00 | 1 | 21 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 36 |
| 0:45:00 | 1 | 15 | 0 | 0 | 0 | 0 | 3 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 9 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 30 |
| 1:00:00 | 0 | 13 | 0 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 26 |
| 1:15:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 |
| 1:30:00 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 22 |
| 1:45:00 | 0 | 8 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 21 |
| 2:00:00 | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 18 |
| 2:15:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 16 |
| 2:30:00 | 0 | 4 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 |
| 2:45:00 | 0 | 9 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 13 |
| 3:00:00 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 |
| 3:15:00 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 14 |
| 3:30:00 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 |
| 3:45:00 | 0 | 3 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 |
| 4:00:00 | 0 | 5 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 |
| 4:15:00 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 8 |
| 4:30:00 | 0 | 8 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 |
| 4:45:00 | 0 | 3 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 |
| 5:00:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 |
| 5:15:00 | 0 | 7 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 |
| 5:30:00 | 0 | 5 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 |
| 5:45:00 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 |
| 6:00:00 | 0 | 5 | 2 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 12 |
| 6:15:00 | 0 | 4 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 |
| 6:30:00 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 |
| 6:45:00 | 0 | 2 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 |
| 7:00:00 | 0 | 6 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 10 |
| 7:15:00 | 0 | 7 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 19 |
| 7:30:00 | 0 | 26 | 3 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 21 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 56 |
| 7:45:00 | 0 | 71 | 16 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 0 | 8 | 41 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 143 |
| 8:00:00 | 1 | 92 | 16 | 0 | 0 | 0 | 6 | 1 | 8 | 0 | 0 | 0 | 0 | 3 | 64 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 192 |
| 8:15:00 | 1 | 80 | 9 | 0 | 0 | 0 | 3 | 0 | 5 | 0 | 0 | 0 | 0 | 7 | 67 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 172 |
| 8:30:00 | 0 | 87 | 18 | 0 | 0 | 0 | 12 | 1 | 7 | 0 | 0 | 0 | 0 | 2 | 76 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 203 |
| 8:45:00 | 4 | 114 | 28 | 0 | 0 | 0 | 16 | 0 | 3 | 0 | 0 | 0 | 0 | 6 | 93 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 264 |
| 9:00:00 | 1 | 132 | 24 | 0 | 0 | 0 | 17 | 1 | 9 | 0 | 0 | 0 | 0 | 7 | 89 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 282 |
| 9:15:00 | 1 | 134 | 27 | 0 | 0 | 0 | 14 | 0 | 12 | 0 | 0 | 0 | 0 | 11 | 137 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 337 |
| 9:30:00 | 0 | 161 | 29 | 0 | 0 | 0 | 23 | 1 | 7 | 0 | 0 | 0 | 0 | 8 | 142 | 0 | 2 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 375 |
| 9:45:00 | 3 | 159 | 43 | 0 | 0 | 0 | 20 | 1 | 18 | 0 | 0 | 0 | 0 | 23 | 145 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 414 |
| 10:00:00 | 2 | 203 | 43 | 0 | 0 | 0 | 24 | 0 | 18 | 0 | 0 | 0 | 0 | 25 | 149 | 2 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 468 |
| 10:15:00 | 0 | 179 | 41 | 0 | 0 | 0 | 26 | 0 | 29 | 0 | 0 | 0 | 0 | 19 | 162 | 2 | 2 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 462 |
| 10:30:00 | 3 | 239 | 43 | 0 | 0 | 0 | 28 | 2 | 31 | 0 | 0 | 0 | 0 | 30 | 197 | 1 | 2 | 0 | 0 | 3 | 1 | 4 | 0 | 0 | 584 |
| 10:45:00 | 4 | 215 | 47 | 0 | 0 | 0 | 26 | 2 | 25 | 0 | 0 | 0 | 0 | 20 | 163 | 2 | 2 | 0 | 0 | 4 | 2 | 1 | 0 | 0 | 513 |
| 11:00:00 | 7 | 232 | 58 | 0 | 0 | 0 | 41 | 0 | 34 | 0 | 0 | 0 | 0 | 35 | 216 | 4 | 1 | 0 | 0 | 6 | 1 | 5 | 0 | 0 | 640 |
| 11:15:00 | 8 | 225 | 65 | 0 | 0 | 0 | 28 | 0 | 40 | 0 | 0 | 0 | 0 | 24 | 203 | 1 | 1 | 0 | 0 | 4 | 3 | 8 | 0 | 0 | 610 |
| 11:30:00 | 11 | 221 | 57 | 0 | 0 | 0 | 29 | 0 | 29 | 0 | 0 | 0 | 0 | 33 | 210 | 1 | 0 | 0 | 0 | 5 | 0 | 4 | 2 | 0 | 602 |
| 11:45:00 | 7 | 257 | 65 | 1 | 0 | 0 | 46 | 2 | 36 | 0 | 0 | 0 | 0 | 46 | 242 | 2 | 0 | 0 | 0 | 6 | 1 | 2 | 0 | 0 | 713 |
| 12:00:00 | 10 | 210 | 74 | 0 | 0 | 0 | 55 | 3 | 35 | 0 | 0 | 0 | 0 | 28 | 217 | 5 | 0 | 0 | 0 | 12 | 3 | 7 | 0 | 0 | 0 | 659 |
| 12:15:00 | 10 | 264 | 78 | 0 | 0 | 0 | 57 | 1 | 35 | 0 | 0 | 0 | 0 | 31 | 254 | 8 | 2 | 0 | 0 | 10 | 2 | 4 | 0 | 0 | 0 | 756 |
| 12:30:00 | 10 | 274 | 61 | 0 | 0 | 0 | 49 | 1 | 42 | 0 | 0 | 0 | 0 | 38 | 235 | 1 | 0 | 0 | 0 | 4 | 0 | 5 | 0 | 0 | 0 | 720 |
| 12:45:00 | 8 | 228 | 76 | 1 | 0 | 0 | 60 | 1 | 40 | 0 | 0 | 0 | 0 | 32 | 242 | 1 | 1 | 0 | 0 | 8 | 1 | 5 | 1 | 0 | 0 | 705 |
| 13:00:00 | 15 | 237 | 95 | 0 | 0 | 0 | 53 | 3 | 42 | 0 | 0 | 0 | 0 | 24 | 257 | 5 | 3 | 0 | 0 | 8 | 3 | 9 | 0 | 0 | 0 | 754 |
| 13:15:00 | 8 | 265 | 64 | 0 | 0 | 0 | 47 | 1 | 45 | 0 | 0 | 0 | 0 | 26 | 282 | 4 | 0 | 0 | 0 | 6 | 0 | 9 | 0 | 0 | 0 | 757 |
| 13:30:00 | 10 | 270 | 59 | 0 | 0 | 0 | 71 | 0 | 53 | 0 | 0 | 0 | 0 | 30 | 263 | 6 | 0 | 0 | 0 | 6 | 1 | 4 | 0 | 0 | 0 | 773 |
| 13:45:00 | 12 | 259 | 81 | 0 | 0 | 0 | 58 | 2 | 44 | 0 | 0 | 0 | 0 | 24 | 227 | 2 | 0 | 0 | 0 | 8 | 3 | 5 | 0 | 0 | 0 | 725 |
| 14:00:00 | 10 | 254 | 59 | 0 | 0 | 0 | 50 | 2 | 49 | 0 | 0 | 0 | 0 | 29 | 260 | 5 | 3 | 0 | 0 | 7 | 3 | 6 | 0 | 0 | 0 | 737 |
| 14:15:00 | 11 | 279 | 59 | 0 | 0 | 0 | 81 | 1 | 30 | 0 | 0 | 0 | 0 | 29 | 276 | 3 | 6 | 0 | 0 | 3 | 3 | 5 | 0 | 0 | 0 | 786 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.960878 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | 9 | 218 | 50 | 0 | 0 | 0 | 77 | 3 | 61 | 0 | 0 | 0 | 0 | 29 | 257 | 3 | 1 | 0 | 0 | 8 | 5 | 9 | 0 | 0 | 0 | 730 |
| 14:45:00 | 7 | 232 | 80 | 1 | 0 | 0 | 75 | 1 | 46 | 0 | 0 | 0 | 0 | 24 | 250 | 7 | 0 | 0 | 0 | 3 | 1 | 8 | 0 | 0 | 0 | 735 |
| 15:00:00 | 7 | 243 | 57 | 0 | 0 | 0 | 50 | 2 | 43 | 0 | 0 | 0 | 0 | 19 | 282 | 2 | 1 | 0 | 0 | 5 | 3 | 5 | 0 | 0 | 0 | 719 |
| 15:15:00 | 7 | 207 | 61 | 0 | 0 | 0 | 74 | 1 | 48 | 0 | 0 | 0 | 0 | 11 | 270 | 8 | 1 | 0 | 0 | 6 | 1 | 6 | 0 | 0 | 0 | 701 |
| 15:30:00 | 6 | 241 | 59 | 0 | 0 | 0 | 50 | 1 | 46 | 0 | 0 | 0 | 0 | 27 | 260 | 4 | 5 | 0 | 0 | 4 | 4 | 2 | 0 | 0 | 0 | 709 |
| 15:45:00 | 13 | 221 | 57 | 1 | 0 | 0 | 58 | 2 | 39 | 0 | 0 | 0 | 0 | 25 | 254 | 4 | 1 | 0 | 0 | 7 | 2 | 2 | 0 | 0 | 0 | 686 |
| 16:00:00 | 5 | 223 | 56 | 0 | 0 | 0 | 63 | 4 | 41 | 0 | 0 | 0 | 0 | 20 | 269 | 2 | 1 | 0 | 0 | 3 | 1 | 4 | 1 | 0 | 0 | 693 |
| 16:15:00 | 7 | 186 | 55 | 0 | 0 | 0 | 55 | 4 | 51 | 0 | 0 | 0 | 0 | 21 | 242 | 2 | 4 | 0 | 0 | 3 | 1 | 3 | 1 | 0 | 0 | 635 |
| 16:30:00 | 12 | 233 | 68 | 0 | 0 | 0 | 55 | 3 | 43 | 0 | 0 | 0 | 0 | 14 | 232 | 5 | 1 | 0 | 0 | 10 | 1 | 5 | 1 | 0 | 0 | 683 |
| 16:45:00 | 16 | 214 | 53 | 1 | 0 | 0 | 60 | 2 | 34 | 0 | 0 | 0 | 0 | 25 | 271 | 3 | 4 | 0 | 0 | 8 | 3 | 1 | 1 | 0 | 0 | 696 |
| 17:00:00 | 5 | 199 | 43 | 0 | 0 | 0 | 59 | 1 | 46 | 0 | 0 | 0 | 0 | 27 | 247 | 1 | 1 | 0 | 0 | 23 | 2 | 12 | 0 | 0 | 0 | 666 |
| 17:15:00 | 14 | 209 | 58 | 0 | 0 | 0 | 52 | 2 | 31 | 0 | 0 | 0 | 0 | 28 | 231 | 7 | 1 | 0 | 0 | 12 | 2 | 6 | 0 | 0 | 0 | 653 |
| 17:30:00 | 11 | 185 | 38 | 1 | 0 | 0 | 46 | 1 | 42 | 0 | 0 | 0 | 0 | 31 | 245 | 1 | 3 | 0 | 0 | 4 | 0 | 4 | 1 | 0 | 0 | 613 |
| 17:45:00 | 9 | 207 | 38 | 0 | 0 | 0 | 53 | 2 | 48 | 0 | 0 | 0 | 0 | 33 | 259 | 2 | 1 | 0 | 0 | 7 | 5 | 5 | 2 | 0 | 0 | 671 |
| 18:00:00 | 7 | 185 | 54 | 0 | 0 | 0 | 50 | 0 | 38 | 0 | 0 | 0 | 0 | 37 | 223 | 4 | 0 | 0 | 0 | 4 | 0 | 3 | 1 | 0 | 0 | 606 |
| 18:15:00 | 13 | 192 | 48 | 0 | 0 | 0 | 35 | 1 | 32 | 0 | 0 | 0 | 0 | 25 | 227 | 5 | 0 | 0 | 0 | 3 | 2 | 7 | 1 | 0 | 0 | 591 |
| 18:30:00 | 12 | 206 | 40 | 0 | 0 | 0 | 48 | 1 | 41 | 0 | 0 | 0 | 0 | 21 | 246 | 4 | 2 | 0 | 0 | 6 | 2 | 6 | 0 | 0 | 0 | 635 |
| 18:45:00 | 13 | 143 | 34 | 0 | 0 | 0 | 54 | 5 | 24 | 0 | 0 | 0 | 0 | 13 | 212 | 7 | 0 | 0 | 0 | 4 | 0 | 7 | 1 | 0 | 0 | 517 |
| 19:00:00 | 9 | 213 | 51 | 0 | 0 | 0 | 49 | 2 | 28 | 0 | 0 | 0 | 0 | 10 | 197 | 4 | 1 | 0 | 0 | 9 | 2 | 5 | 0 | 0 | 0 | 580 |
| 19:15:00 | 6 | 126 | 35 | 1 | 0 | 0 | 44 | 0 | 25 | 0 | 0 | 0 | 0 | 15 | 225 | 3 | 0 | 0 | 0 | 5 | 0 | 9 | 1 | 0 | 0 | 495 |
| 19:30:00 | 15 | 114 | 30 | 0 | 0 | 0 | 37 | 5 | 36 | 0 | 0 | 0 | 0 | 9 | 160 | 2 | 1 | 0 | 0 | 13 | 2 | 10 | 0 | 0 | 0 | 434 |
| 19:45:00 | 5 | 134 | 24 | 1 | 0 | 0 | 41 | 1 | 21 | 0 | 0 | 0 | 0 | 7 | 147 | 1 | 0 | 0 | 0 | 4 | 1 | 2 | 0 | 0 | 0 | 389 |
| 20:00:00 | 3 | 90 | 17 | 1 | 0 | 0 | 43 | 0 | 16 | 0 | 0 | 0 | 0 | 9 | 165 | 1 | 1 | 0 | 0 | 7 | 2 | 6 | 0 | 0 | 0 | 361 |
| 20:15:00 | 7 | 93 | 26 | 0 | 0 | 0 | 37 | 2 | 31 | 0 | 0 | 0 | 0 | 3 | 127 | 1 | 0 | 0 | 0 | 4 | 1 | 5 | 0 | 0 | 0 | 337 |
| 20:30:00 | 6 | 92 | 19 | 0 | 0 | 0 | 33 | 1 | 20 | 0 | 0 | 0 | 0 | 5 | 134 | 3 | 0 | 0 | 0 | 7 | 2 | 6 | 0 | 0 | 0 | 328 |
| 20:45:00 | 4 | 69 | 18 | 1 | 0 | 0 | 38 | 0 | 14 | 0 | 0 | 0 | 0 | 6 | 94 | 0 | 0 | 0 | 0 | 1 | 2 | 5 | 0 | 0 | 0 | 252 |
| 21:00:00 | 8 | 81 | 7 | 0 | 0 | 0 | 19 | 0 | 14 | 0 | 0 | 0 | 0 | 5 | 105 | 2 | 0 | 0 | 0 | 5 | 0 | 3 | 0 | 0 | 0 | 249 |
| 21:15:00 | 1 | 76 | 11 | 0 | 0 | 0 | 27 | 0 | 15 | 0 | 0 | 0 | 0 | 5 | 96 | 0 | 2 | 0 | 0 | 2 | 1 | 3 | 0 | 0 | 0 | 239 |
| 21:30:00 | 4 | 70 | 9 | 2 | 0 | 0 | 25 | 0 | 7 | 0 | 0 | 0 | 0 | 1 | 83 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 204 |
| 21:45:00 | 2 | 53 | 5 | 0 | 0 | 0 | 15 | 0 | 11 | 0 | 0 | 0 | 0 | 2 | 77 | 0 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 168 |
| 22:00:00 | 2 | 57 | 6 | 0 | 0 | 0 | 16 | 1 | 10 | 0 | 0 | 0 | 0 | 0 | 64 | 1 | 0 | 0 | 0 | 1 | 0 | 4 | 0 | 0 | 0 | 162 |
| 22:15:00 | 0 | 51 | 6 | 0 | 0 | 0 | 15 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 54 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 132 |
| 22:30:00 | 4 | 45 | 4 | 0 | 0 | 0 | 5 | 2 | 6 | 0 | 0 | 0 | 0 | 1 | 44 | 1 | 1 | 0 | 0 | 2 | 0 | 3 | 0 | 0 | 0 | 118 |
| 22:45:00 | 2 | 52 | 6 | 0 | 0 | 0 | 4 | 0 | 3 | 0 | 0 | 0 | 0 | 2 | 47 | 0 | 0 | 0 | 0 | 2 | 0 | 2 | 0 | 0 | 0 | 120 |
| 23:00:00 | 2 | 36 | 8 | 0 | 0 | 0 | 5 | 2 | 1 | 0 | 0 | 0 | 0 | 4 | 42 | 0 | 0 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 0 | 104 |
| 23:15:00 | 1 | 43 | 1 | 0 | 0 | 0 | 8 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 42 | 1 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 105 |
| 23:30:00 | 3 | 28 | 1 | 0 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 0 | 0 | 2 | 38 | 0 | 0 | 0 | 0 | 1 | 0 | 3 | 0 | 0 | 0 | 82 |
| 23:45:00 | 5 | 46 | 1 | 0 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 44 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 102 |

| | | |
|---|---|---|
| **Lights** | 771 | 2 |
| | 723 | 2 |
| | 733 | 4 |
| | 784 | 2 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 10/26/2023 0:00
End Time 10/26/2023 23:59
Location 05-53-554P Rt 62 (NFB) @ Consumer Sq Plaza
Latitude an 42.99962237,-78.82240171
Lights

| Entry Direction | North Southbound | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total | |
| 0:00:00 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 0:15:00 | 0 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | |
| 0:30:00 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 0:45:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 1:00:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 1:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 1:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 1:45:00 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 2:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 2:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 2:30:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 2:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 3:00:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 3:15:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 3:30:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 3:45:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | |
| 4:00:00 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | |
| 4:15:00 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | |
| 4:30:00 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | |
| 4:45:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | |
| 5:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | |
| 5:15:00 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | |
| 5:30:00 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | |
| 5:45:00 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 4 | |
| 6:00:00 | 0 | 6 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | |
| 6:15:00 | 0 | 5 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 13 | |
| 6:30:00 | 1 | 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 19 | |
| 6:45:00 | 1 | 13 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | |
| 7:00:00 | 2 | 9 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 23 | |
| 7:15:00 | 2 | 31 | 2 | 1 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 14 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 54 | |
| 7:30:00 | 0 | 132 | 5 | 0 | 0 | 0 | 5 | 0 | 1 | 0 | 0 | 0 | 0 | 59 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 205 | |
| 7:45:00 | 1 | 161 | 16 | 0 | 0 | 0 | 5 | 1 | 2 | 0 | 0 | 0 | 7 | 105 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 299 | |
| 8:00:00 | 1 | 116 | 12 | 0 | 0 | 0 | 5 | 0 | 2 | 0 | 0 | 0 | 2 | 110 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 249 | |
| 8:15:00 | 1 | 158 | 20 | 0 | 0 | 0 | 9 | 0 | 4 | 0 | 0 | 0 | 1 | 131 | 1 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 327 | |
| 8:30:00 | 1 | 142 | 9 | 0 | 0 | 0 | 15 | 1 | 5 | 0 | 0 | 0 | 7 | 121 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 304 | |
| 8:45:00 | 1 | 149 | 23 | 0 | 0 | 0 | 14 | 0 | 12 | 0 | 0 | 0 | 11 | 117 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 329 | |
| 9:00:00 | 2 | 131 | 14 | 1 | 0 | 0 | 13 | 0 | 10 | 0 | 0 | 0 | 8 | 116 | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 297 | |
| 9:15:00 | 3 | 128 | 12 | 0 | 0 | 0 | 11 | 0 | 16 | 0 | 0 | 0 | 9 | 123 | 0 | 1 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 0 | 306 | |
| 9:30:00 | 0 | 135 | 20 | 0 | 0 | 0 | 17 | 0 | 6 | 0 | 0 | 0 | 11 | 143 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 333 | |
| 9:45:00 | 5 | 164 | 28 | 1 | 0 | 0 | 22 | 3 | 8 | 0 | 0 | 0 | 7 | 123 | 0 | 1 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 364 | |
| 10:00:00 | 4 | 125 | 27 | 1 | 0 | 0 | 22 | 2 | 11 | 0 | 0 | 0 | 16 | 148 | 2 | 1 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 362 | |
| 10:15:00 | 2 | 164 | 37 | 2 | 0 | 0 | 22 | 2 | 23 | 0 | 0 | 0 | 19 | 147 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 422 | |
| 10:30:00 | 2 | 149 | 33 | 1 | 0 | 0 | 25 | 1 | 25 | 0 | 0 | 0 | 16 | 148 | 0 | 0 | 0 | 0 | 1 | 1 | 2 | 0 | 0 | 0 | 404 | |
| 10:45:00 | 4 | 160 | 39 | 0 | 0 | 0 | 27 | 1 | 14 | 0 | 0 | 0 | 20 | 144 | 0 | 3 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 416 | |
| 11:00:00 | 3 | 173 | 33 | 0 | 0 | 0 | 26 | 3 | 18 | 0 | 0 | 0 | 26 | 166 | 0 | 1 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 454 | |
| 11:15:00 | 8 | 189 | 42 | 0 | 0 | 0 | 44 | 2 | 19 | 0 | 0 | 0 | 14 | 194 | 4 | 3 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 522 | |
| 11:30:00 | 5 | 188 | 36 | 0 | 0 | 0 | 29 | 6 | 24 | 0 | 0 | 0 | 21 | 217 | 1 | 1 | 0 | 0 | 2 | 1 | 2 | 0 | 0 | 0 | 533 | |
| 11:45:00 | 4 | 207 | 34 | 0 | 0 | 0 | 33 | 1 | 22 | 0 | 0 | 0 | 31 | 206 | 3 | 1 | 0 | 0 | 0 | 3 | 4 | 0 | 0 | 0 | 549 | |
| 12:00:00 | 4 | 187 | 49 | 2 | 0 | 0 | 27 | 3 | 25 | 0 | 0 | 0 | 34 | 194 | 2 | 1 | 0 | 0 | 1 | 3 | 3 | 1 | 0 | 0 | 536 | |
| 12:15:00 | 8 | 190 | 40 | 0 | 0 | 0 | 42 | 0 | 28 | 0 | 0 | 0 | 35 | 222 | 3 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 571 | |
| 12:30:00 | 2 | 209 | 42 | 0 | 0 | 0 | 38 | 1 | 36 | 0 | 0 | 0 | 23 | 217 | 2 | 0 | 0 | 0 | 1 | 0 | 5 | 0 | 0 | 0 | 576 | |
| 12:45:00 | 8 | 180 | 39 | 0 | 0 | 0 | 44 | 5 | 40 | 0 | 0 | 0 | 31 | 214 | 4 | 2 | 0 | 0 | 0 | 1 | 4 | 0 | 0 | 0 | 572 | |
| 13:00:00 | 2 | 185 | 45 | 0 | 0 | 0 | 42 | 2 | 23 | 0 | 0 | 0 | 29 | 224 | 1 | 2 | 0 | 0 | 3 | 1 | 5 | 0 | 0 | 0 | 564 | |
| 13:15:00 | 6 | 208 | 34 | 1 | 0 | 0 | 40 | 1 | 23 | 0 | 0 | 0 | 24 | 243 | 2 | 1 | 0 | 0 | 1 | 2 | 2 | 1 | 0 | 0 | 589 | |
| 13:30:00 | 6 | 182 | 40 | 0 | 0 | 0 | 42 | 0 | 42 | 0 | 0 | 0 | 31 | 216 | 5 | 0 | 0 | 0 | 4 | 2 | 5 | 0 | 0 | 0 | 575 | |
| 13:45:00 | 4 | 162 | 39 | 0 | 0 | 0 | 44 | 0 | 31 | 0 | 0 | 0 | 25 | 221 | 2 | 3 | 0 | 0 | 2 | 1 | 4 | 0 | 0 | 0 | 538 | |
| 14:00:00 | 6 | 206 | 43 | 0 | 0 | 0 | 42 | 1 | 33 | 0 | 0 | 0 | 31 | 221 | 4 | 2 | 0 | 0 | 0 | 2 | 3 | 0 | 0 | 0 | 594 | |
| 14:15:00 | 2 | 185 | 43 | 0 | 0 | 0 | 51 | 0 | 24 | 0 | 0 | 0 | 24 | 244 | 2 | 3 | 0 | 0 | 1 | 0 | 3 | 0 | 0 | 0 | 582 | |
| 14:30:00 | 9 | 201 | 46 | 0 | 0 | 0 | 30 | 0 | 41 | 0 | 0 | 0 | 22 | 227 | 2 | 0 | 0 | 0 | 1 | 0 | 5 | 0 | 0 | 0 | 584 | |
| 14:45:00 | 6 | 202 | 41 | 0 | 0 | 0 | 34 | 0 | 39 | 0 | 0 | 0 | 17 | 253 | 0 | 2 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 596 | |
| 3:00 PM | 9 | 260 | 36 | 0 | 0 | 0 | 32 | 1 | 35 | 0 | 0 | 0 | 24 | 241 | 1 | 0 | 0 | 0 | 7 | 2 | 3 | 0 | 0 | 0 | 651 | |
| 3:15 PM | 5 | 218 | 37 | 0 | 0 | 0 | 40 | 1 | 32 | 0 | 0 | 0 | 25 | 223 | 3 | 2 | 0 | 0 | 4 | 0 | 5 | 0 | 0 | 0 | 595 | |
| 3:30 PM | 7 | 227 | 54 | 0 | 0 | 0 | 36 | 1 | 40 | 0 | 0 | 0 | 25 | 254 | 1 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | 649 | |
| 3:45 PM | 9 | 217 | 45 | 1 | 0 | 0 | 31 | 1 | 36 | 0 | 0 | 0 | 27 | 224 | 2 | 1 | 0 | 0 | 2 | 2 | 2 | 0 | 0 | 0 | 600 | |
| 4:00 PM | 10 | 251 | 34 | 0 | 0 | 0 | 50 | 1 | 22 | 0 | 0 | 0 | 21 | 232 | 2 | 2 | 0 | 0 | 2 | 2 | 8 | 0 | 0 | 0 | 637 | |
| 4:15 PM | 8 | 229 | 44 | 0 | 0 | 0 | 40 | 1 | 37 | 0 | 0 | 0 | 24 | 251 | 2 | 5 | 0 | 0 | 0 | 1 | 5 | 0 | 0 | 0 | 647 | **Lights** HV |
| 4:30 PM | 1 | 225 | 38 | 0 | 0 | 0 | 48 | 3 | 23 | 0 | 0 | 0 | 26 | 238 | 3 | 2 | 0 | 0 | 1 | 4 | 4 | 0 | 0 | 0 | 616 | 608 8 |
| 4:45 PM | 5 | 234 | 27 | 1 | 0 | 0 | 44 | 1 | 33 | 0 | 0 | 0 | 23 | 243 | 2 | 1 | 0 | 0 | 3 | 2 | 5 | 0 | 0 | 0 | 624 | 619 5 |
| 5:00 PM | 9 | 244 | 58 | 0 | 0 | 0 | 66 | 1 | 31 | 0 | 0 | 0 | 26 | 211 | 1 | 0 | 0 | 0 | 2 | 1 | 4 | 0 | 0 | 0 | 654 | 649 5 |
| 5:15 PM | 7 | 169 | 34 | 0 | 0 | 0 | 39 | 2 | 26 | 0 | 0 | 0 | 33 | 239 | 2 | 2 | 0 | 0 | 4 | 2 | 1 | 0 | 0 | 0 | 560 | 557 3 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.938073 | |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% | |
| 5:30 PM | 12 | 204 | 43 | 0 | 0 | 0 | 46 | 3 | 22 | 0 | 0 | 0 | 23 | 236 | 1 | 0 | 0 | 0 | 1 | 1 | 2 | 0 | 0 | 0 | 594 | |
| 5:45 PM | 3 | 218 | 39 | 1 | 0 | 0 | 40 | 2 | 32 | 0 | 0 | 0 | 23 | 184 | 2 | 4 | 0 | 0 | 3 | 0 | 2 | 0 | 0 | 0 | 553 | |
| 18:00:00 | 8 | 182 | 51 | 1 | 0 | 0 | 45 | 1 | 28 | 0 | 0 | 0 | 24 | 213 | 4 | 1 | 0 | 0 | 1 | 2 | 5 | 0 | 0 | 0 | 566 | |
| 18:15:00 | 8 | 189 | 33 | 0 | 0 | 0 | 32 | 1 | 34 | 0 | 0 | 0 | 29 | 205 | 5 | 0 | 0 | 0 | 1 | 0 | 5 | 0 | 0 | 0 | 542 | |
| 18:30:00 | 5 | 159 | 23 | 1 | 0 | 0 | 48 | 2 | 32 | 0 | 0 | 0 | 17 | 232 | 4 | 0 | 0 | 0 | 6 | 1 | 7 | 0 | 0 | 0 | 537 | |
| 18:45:00 | 9 | 126 | 34 | 0 | 0 | 0 | 47 | 1 | 30 | 0 | 0 | 0 | 6 | 185 | 2 | 1 | 0 | 0 | 7 | 0 | 6 | 1 | 0 | 0 | 455 | |
| 19:00:00 | 19 | 130 | 34 | 0 | 0 | 0 | 42 | 2 | 34 | 0 | 0 | 0 | 8 | 172 | 1 | 0 | 0 | 0 | 4 | 3 | 6 | 0 | 0 | 0 | 455 | |
| 19:15:00 | 14 | 124 | 30 | 0 | 0 | 0 | 46 | 1 | 34 | 0 | 0 | 0 | 8 | 191 | 2 | 2 | 0 | 0 | 3 | 1 | 6 | 0 | 0 | 0 | 462 | |
| 19:30:00 | 13 | 98 | 22 | 0 | 0 | 0 | 47 | 8 | 27 | 0 | 0 | 0 | 8 | 130 | 3 | 1 | 0 | 0 | 3 | 2 | 6 | 0 | 0 | 0 | 368 | |
| 19:45:00 | 15 | 112 | 23 | 0 | 0 | 0 | 28 | 2 | 16 | 0 | 0 | 0 | 2 | 143 | 6 | 0 | 0 | 0 | 3 | 4 | 5 | 1 | 0 | 0 | 360 | |
| 20:00:00 | 10 | 82 | 19 | 0 | 0 | 0 | 32 | 1 | 26 | 0 | 0 | 0 | 5 | 140 | 3 | 2 | 0 | 0 | 2 | 2 | 2 | 1 | 0 | 0 | 327 | |
| 20:15:00 | 4 | 62 | 14 | 0 | 0 | 0 | 29 | 0 | 20 | 0 | 0 | 0 | 5 | 107 | 1 | 0 | 0 | 0 | 0 | 1 | 4 | 0 | 0 | 0 | 247 | |
| 20:30:00 | 5 | 55 | 23 | 0 | 0 | 0 | 25 | 2 | 15 | 0 | 0 | 0 | 2 | 93 | 3 | 2 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 227 | |
| 20:45:00 | 4 | 59 | 11 | 0 | 0 | 0 | 19 | 2 | 20 | 0 | 0 | 0 | 2 | 80 | 0 | 1 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 201 | |
| 21:00:00 | 3 | 48 | 11 | 2 | 0 | 0 | 26 | 2 | 13 | 0 | 0 | 0 | 3 | 94 | 2 | 0 | 0 | 0 | 3 | 1 | 4 | 0 | 0 | 0 | 212 | |
| 21:15:00 | 3 | 48 | 9 | 0 | 0 | 0 | 13 | 0 | 13 | 0 | 0 | 0 | 3 | 78 | 3 | 0 | 0 | 0 | 2 | 0 | 1 | 1 | 0 | 0 | 174 | |
| 21:30:00 | 3 | 31 | 12 | 0 | 0 | 0 | 16 | 2 | 10 | 0 | 0 | 0 | 1 | 53 | 1 | 1 | 0 | 0 | 1 | 2 | 9 | 0 | 0 | 0 | 142 | |
| 21:45:00 | 5 | 44 | 9 | 0 | 0 | 0 | 13 | 1 | 10 | 0 | 0 | 0 | 2 | 56 | 0 | 0 | 0 | 0 | 2 | 0 | 12 | 0 | 0 | 0 | 154 | |
| 22:00:00 | 6 | 35 | 5 | 1 | 0 | 0 | 13 | 2 | 10 | 0 | 0 | 0 | 2 | 38 | 1 | 1 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 118 | |
| 22:15:00 | 3 | 22 | 7 | 0 | 0 | 0 | 8 | 0 | 11 | 0 | 0 | 0 | 3 | 46 | 3 | 0 | 0 | 0 | 2 | 0 | 6 | 0 | 0 | 0 | 111 | |
| 22:30:00 | 2 | 28 | 4 | 0 | 0 | 0 | 7 | 1 | 2 | 0 | 0 | 0 | 3 | 33 | 5 | 0 | 0 | 0 | 2 | 2 | 10 | 0 | 0 | 0 | 99 | |
| 22:45:00 | 2 | 33 | 1 | 0 | 0 | 0 | 6 | 2 | 4 | 0 | 0 | 0 | 0 | 31 | 1 | 0 | 0 | 0 | 1 | 1 | 2 | 0 | 0 | 0 | 84 | |
| 23:00:00 | 4 | 32 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 0 | 34 | 1 | 0 | 0 | 0 | 2 | 0 | 6 | 0 | 0 | 0 | 84 | |
| 23:15:00 | 1 | 32 | 2 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 1 | 0 | 0 | 0 | 12 | 0 | 10 | 0 | 0 | 0 | 91 | |
| 23:30:00 | 3 | 33 | 2 | 0 | 0 | 0 | 1 | 1 | 4 | 0 | 0 | 0 | 0 | 32 | 1 | 1 | 0 | 0 | 0 | 0 | 7 | 0 | 0 | 0 | 85 | |
| 23:45:00 | 0 | 28 | 1 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 0 | 0 | 29 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 63 | |

Summary

| | |
|---|---|
| Study Name | Eggert Road and Bailey Avenue |
| Project | |
| Project Code | |
| Legs and Movements | |
| Bin Size | 15 minutes |
| Time Zone | |
| Start Time | 2024-11-09 00:00:00 +0000 |
| End Time | 2024-11-11 00:00:00 +0000 |
| Location | Eggert Road and Bailey Avenue |
| Latitude and Longitude | 42.97724343,-78.81372775 |

| | |
|---|---|
| AM Peak | 10:30-11:30 |
| Midday Peak | 12:15-13:15 |
| PM Peak (Overall Peak | 15:15-16:15 |
| Custom ID | |
| Tags | |

Summary

| Entry | Bailey Avenue | | | | | Eggert Road | | | | | Bailey Avenue | | | | | Eggert Road | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | Westbound | | | | | Northbound | | | | | Eastbound | | | | | | | |
| Start Time | Left | Thru | Right | Crosswalk | Crosswalk | Left | Thru | Right | Crosswalk | Crosswalk | Left | Thru | Right | Crosswalk | Crosswalk | Left | Thru | Right | U-Turn | Crosswalk | Crosswalk | Total | | |
| 2024-11-09 00:00:00 | 2 | 8 | 0 | 0 | 0 | 3 | 5 | 0 | 0 | 0 | 5 | 8 | 1 | 0 | 0 | 0 | 6 | 5 | 0 | 0 | 0 | 43 | | |
| 2024-11-09 00:15:00 | 1 | 10 | 2 | 0 | 0 | 2 | 8 | 1 | 0 | 0 | 5 | 6 | 4 | 0 | 0 | 0 | 8 | 4 | 0 | 0 | 0 | 51 | | |
| 2024-11-09 00:30:00 | 2 | 18 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 5 | 0 | 0 | 0 | 0 | 8 | 1 | 0 | 0 | 0 | 37 | | |
| 2024-11-09 00:45:00 | 0 | 5 | 0 | 0 | 0 | 4 | 5 | 0 | 0 | 0 | 0 | 8 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 24 | | |
| 2024-11-09 01:00:00 | 0 | 8 | 0 | 0 | 0 | 1 | 1 | 2 | 0 | 0 | 4 | 2 | 4 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 0 | 25 | | |
| 2024-11-09 01:15:00 | 0 | 6 | 0 | 0 | 0 | 3 | 2 | 0 | 0 | 0 | 0 | 3 | 3 | 0 | 0 | 0 | 1 | 5 | 0 | 0 | 0 | 23 | | |
| 2024-11-09 01:30:00 | 1 | 8 | 1 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 2 | 6 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 24 | | |
| 2024-11-09 01:45:00 | 1 | 2 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 2 | 5 | 1 | 0 | 0 | 1 | 7 | 2 | 0 | 0 | 0 | 23 | | |
| 2024-11-09 02:00:00 | 0 | 4 | 1 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 1 | 6 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 18 | | |
| 2024-11-09 02:15:00 | 0 | 2 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 12 | | |
| 2024-11-09 02:30:00 | 0 | 3 | 0 | 0 | 0 | 0 | 2 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 0 | 12 | | |
| 2024-11-09 02:45:00 | 0 | 6 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 15 | | |
| 2024-11-09 03:00:00 | 0 | 3 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 10 | | |
| 2024-11-09 03:15:00 | 1 | 3 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 10 | | |
| 2024-11-09 03:30:00 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 9 | | |
| 2024-11-09 03:45:00 | 0 | 3 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | | |
| 2024-11-09 04:00:00 | 0 | 5 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | | |
| 2024-11-09 04:15:00 | 1 | 2 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 3 | 2 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 14 | | |
| 2024-11-09 04:30:00 | 0 | 1 | 0 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 15 | | |
| 2024-11-09 04:45:00 | 1 | 4 | 0 | 0 | 0 | 0 | 2 | 4 | 0 | 0 | 2 | 5 | 1 | 0 | 0 | 1 | 4 | 2 | 0 | 0 | 0 | 26 | | |
| 2024-11-09 05:00:00 | 1 | 3 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 2 | 4 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 14 | | |
| 2024-11-09 05:15:00 | 0 | 8 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 3 | 4 | 0 | 0 | 0 | 0 | 4 | 3 | 0 | 0 | 0 | 26 | | |
| 2024-11-09 05:30:00 | 0 | 8 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 19 | | |
| 2024-11-09 05:45:00 | 1 | 5 | 0 | 0 | 0 | 1 | 5 | 2 | 0 | 0 | 6 | 8 | 0 | 0 | 0 | 5 | 3 | 5 | 0 | 0 | 0 | 41 | | |
| 2024-11-09 06:00:00 | 1 | 6 | 0 | 0 | 0 | 1 | 3 | 3 | 0 | 0 | 3 | 10 | 2 | 0 | 0 | 0 | 7 | 4 | 0 | 0 | 0 | 40 | | |
| 2024-11-09 06:15:00 | 1 | 8 | 0 | 0 | 0 | 1 | 8 | 3 | 0 | 0 | 9 | 9 | 2 | 0 | 0 | 1 | 3 | 3 | 0 | 0 | 0 | 48 | | |
| 2024-11-09 06:30:00 | 2 | 7 | 1 | 0 | 0 | 1 | 7 | 7 | 0 | 0 | 9 | 14 | 1 | 0 | 0 | 3 | 3 | 4 | 0 | 0 | 0 | 59 | | |
| 2024-11-09 06:45:00 | 1 | 13 | 1 | 0 | 0 | 3 | 6 | 5 | 0 | 0 | 6 | 20 | 0 | 0 | 0 | 1 | 9 | 2 | 0 | 0 | 0 | 67 | | |
| 2024-11-09 07:00:00 | 3 | 17 | 1 | 0 | 0 | 2 | 7 | 3 | 0 | 0 | 5 | 26 | 1 | 0 | 0 | 2 | 8 | 4 | 0 | 0 | 0 | 79 | | |
| 2024-11-09 07:15:00 | 5 | 25 | 3 | 0 | 0 | 3 | 7 | 6 | 0 | 0 | 8 | 18 | 7 | 0 | 0 | 3 | 10 | 3 | 0 | 0 | 0 | 98 | | |
| 2024-11-09 07:30:00 | 2 | 19 | 3 | 0 | 0 | 2 | 7 | 14 | 0 | 0 | 6 | 32 | 2 | 0 | 0 | 4 | 9 | 2 | 0 | 0 | 0 | 102 | | |
| 2024-11-09 07:45:00 | 7 | 26 | 4 | 0 | 0 | 1 | 15 | 19 | 0 | 0 | 5 | 35 | 4 | 0 | 0 | 6 | 10 | 3 | 0 | 0 | 0 | 135 | | |
| 2024-11-09 08:00:00 | 11 | 39 | 3 | 0 | 0 | 2 | 20 | 15 | 0 | 0 | 4 | 43 | 1 | 0 | 0 | 3 | 12 | 2 | 0 | 0 | 0 | 155 | | |
| 2024-11-09 08:15:00 | 7 | 18 | 1 | 0 | 0 | 6 | 22 | 19 | 0 | 0 | 9 | 41 | 3 | 0 | 0 | 5 | 14 | 8 | 0 | 0 | 0 | 153 | | |
| 2024-11-09 08:30:00 | 8 | 23 | 2 | 0 | 0 | 8 | 19 | 14 | 0 | 0 | 13 | 66 | 9 | 0 | 0 | 7 | 21 | 7 | 0 | 0 | 0 | 197 | | |
| 2024-11-09 08:45:00 | 10 | 46 | 3 | 0 | 0 | 2 | 44 | 22 | 0 | 0 | 9 | 42 | 7 | 0 | 0 | 10 | 35 | 11 | 0 | 0 | 0 | 241 | | |
| 2024-11-09 09:00:00 | 6 | 52 | 2 | 0 | 0 | 8 | 31 | 25 | 0 | 0 | 12 | 51 | 7 | 0 | 0 | 9 | 43 | 11 | 0 | 0 | 0 | 257 | | |
| 2024-11-09 09:15:00 | 6 | 53 | 6 | 0 | 0 | 10 | 29 | 24 | 0 | 0 | 8 | 62 | 3 | 0 | 0 | 5 | 32 | 15 | 0 | 0 | 0 | 253 | | |
| 2024-11-09 09:30:00 | 13 | 34 | 8 | 0 | 0 | 7 | 24 | 35 | 0 | 0 | 10 | 53 | 3 | 0 | 0 | 7 | 39 | 18 | 0 | 0 | 0 | 251 | | |
| 2024-11-09 09:45:00 | 17 | 48 | 10 | 0 | 0 | 5 | 40 | 29 | 0 | 0 | 8 | 52 | 4 | 0 | 0 | 5 | 37 | 9 | 0 | 0 | 0 | 264 | | |
| 2024-11-09 10:00:00 | 21 | 38 | 11 | 0 | 0 | 7 | 37 | 38 | 0 | 0 | 20 | 68 | 4 | 0 | 0 | 10 | 37 | 13 | 0 | 0 | 0 | 304 | | |
| 2024-11-09 10:15:00 | 20 | 63 | 10 | 0 | 0 | 8 | 55 | 30 | 0 | 0 | 22 | 63 | 7 | 0 | 0 | 17 | 56 | 18 | 0 | 0 | 0 | 369 | | |
| 2024-11-09 10:30:00 | 19 | 61 | 8 | 0 | 0 | 8 | 47 | 30 | 0 | 0 | 10 | 70 | 10 | 0 | 0 | 9 | 31 | 21 | 0 | 0 | 0 | 324 | | |
| 2024-11-09 10:45:00 | 20 | 73 | 12 | 0 | 0 | 8 | 48 | 29 | 0 | 0 | 24 | 68 | 8 | 0 | 0 | 17 | 73 | 20 | 0 | 0 | 0 | 400 | | |
| 2024-11-09 11:00:00 | 22 | 50 | 7 | 0 | 0 | 7 | 46 | 32 | 0 | 0 | 9 | 85 | 8 | 0 | 0 | 7 | 53 | 24 | 0 | 0 | 0 | 350 | | |
| 2024-11-09 11:15:00 | 23 | 72 | 10 | 0 | 0 | 9 | 72 | 25 | 0 | 0 | 31 | 75 | 9 | 0 | 0 | 8 | 63 | 15 | 0 | 0 | 0 | 412 | | |
| 2024-11-09 11:30:00 | 29 | 55 | 9 | 0 | 0 | 9 | 73 | 39 | 0 | 0 | 26 | 86 | 11 | 0 | 0 | 12 | 52 | 18 | 0 | 0 | 0 | 419 | | |
| 2024-11-09 11:45:00 | 28 | 79 | 18 | 0 | 0 | 13 | 70 | 26 | 0 | 0 | 18 | 58 | 6 | 0 | 0 | 9 | 54 | 17 | 0 | 0 | 0 | 396 | | |
| 2024-11-09 12:00:00 | 32 | 67 | 16 | 0 | 0 | 9 | 56 | 28 | 0 | 0 | 13 | 73 | 10 | 0 | 0 | 20 | 72 | 25 | 0 | 0 | 0 | 421 | | |
| 2024-11-09 12:15:00 | 18 | 88 | 5 | 0 | 0 | 5 | 59 | 33 | 0 | 0 | 16 | 91 | 11 | 0 | 0 | 14 | 67 | 14 | 0 | 0 | 0 | 421 | | |
| 2024-11-09 12:30:00 | 32 | 90 | 9 | 0 | 0 | 8 | 61 | 35 | 0 | 0 | 18 | 77 | 14 | 0 | 0 | 15 | 57 | 15 | 0 | 0 | 0 | 431 | | |
| 2024-11-09 12:45:00 | 26 | 88 | 11 | 0 | 0 | 11 | 43 | 33 | 0 | 0 | 24 | 75 | 11 | 0 | 0 | 14 | 72 | 29 | 0 | 0 | 0 | 437 | | |
| 2024-11-09 13:00:00 | 29 | 92 | 11 | 0 | 0 | 10 | 74 | 29 | 0 | 0 | 20 | 91 | 7 | 0 | 0 | 14 | 52 | 16 | 0 | 0 | 0 | 445 | | |
| 2024-11-09 13:15:00 | 28 | 83 | 7 | 0 | 0 | 8 | 43 | 37 | 0 | 0 | 15 | 73 | 8 | 0 | 0 | 18 | 61 | 19 | 0 | 0 | 0 | 400 | Lights | HV |
| 2024-11-09 13:30:00 | 30 | 73 | 5 | 0 | 0 | 8 | 54 | 27 | 0 | 0 | 18 | 84 | 7 | 0 | 0 | 15 | 41 | 12 | 0 | 0 | 0 | 374 | 373 | 1 |
| 2024-11-09 13:45:00 | 27 | 77 | 12 | 0 | 0 | 11 | 63 | 22 | 0 | 0 | 20 | 76 | 9 | 0 | 0 | 8 | 54 | 22 | 0 | 0 | 0 | 401 | 399 | 2 |
| 2024-11-09 14:00:00 | 35 | 92 | 13 | 0 | 0 | 7 | 60 | 48 | 0 | 0 | 20 | 96 | 9 | 0 | 0 | 8 | 59 | 30 | 0 | 0 | 0 | 477 | 476 | 1 |
| 2024-11-09 14:15:00 | 29 | 62 | 12 | 0 | 0 | 12 | 59 | 36 | 0 | 0 | 17 | 85 | 11 | 0 | 0 | 9 | 50 | 15 | 0 | 0 | 0 | 397 | 395 | 2 |
| | | | | | | | | | | | | | | | | | | | | | | 0.864256 | | |
| | | | | | | | | | | | | | | | | | | | | | | 0.4% | | |
| 2024-11-09 14:30:00 | 24 | 87 | 11 | 0 | 0 | 7 | 59 | 17 | 0 | 0 | 17 | 74 | 9 | 0 | 0 | 10 | 62 | 15 | 0 | 0 | 0 | 392 | | |
| 2024-11-09 14:45:00 | 27 | 94 | 5 | 0 | 0 | 3 | 44 | 37 | 0 | 0 | 20 | 63 | 4 | 0 | 0 | 7 | 68 | 18 | 0 | 0 | 0 | 390 | | |
| 2024-11-09 15:00:00 | 27 | 73 | 9 | 0 | 0 | 12 | 47 | 22 | 0 | 0 | 19 | 88 | 12 | 0 | 0 | 11 | 57 | 24 | 0 | 0 | 0 | 401 | | |
| 2024-11-09 15:15:00 | 36 | 104 | 9 | 0 | 0 | 10 | 52 | 32 | 0 | 0 | 14 | 77 | 4 | 0 | 0 | 4 | 61 | 12 | 0 | 0 | 0 | 415 | | |
| 2024-11-09 15:30:00 | 30 | 80 | 11 | 0 | 0 | 9 | 63 | 32 | 0 | 0 | 22 | 80 | 6 | 0 | 0 | 9 | 62 | 20 | 0 | 0 | 0 | 424 | | |
| 2024-11-09 15:45:00 | 26 | 79 | 12 | 0 | 0 | 10 | 67 | 26 | 0 | 0 | 18 | 63 | 9 | 0 | 0 | 9 | 66 | 17 | 0 | 0 | 0 | 402 | | |
| 2024-11-09 16:00:00 | 17 | 91 | 13 | 0 | 0 | 11 | 51 | 31 | 0 | 0 | 18 | 71 | 9 | 0 | 0 | 6 | 54 | 13 | 0 | 0 | 0 | 385 | | |
| 2024-11-09 16:15:00 | 25 | 95 | 6 | 0 | 0 | 8 | 40 | 28 | 0 | 0 | 20 | 77 | 9 | 0 | 0 | 9 | 55 | 21 | 0 | 0 | 0 | 393 | | |
| 2024-11-09 16:30:00 | 29 | 69 | 7 | 0 | 0 | 12 | 46 | 20 | 0 | 0 | 24 | 74 | 9 | 0 | 0 | 5 | 55 | 22 | 0 | 0 | 0 | 372 | | |
| 2024-11-09 16:45:00 | 20 | 97 | 10 | 0 | 0 | 14 | 40 | 25 | 0 | 0 | 15 | 88 | 10 | 0 | 0 | 5 | 44 | 13 | 0 | 0 | 0 | 381 | | |
| 2024-11-09 17:00:00 | 32 | 96 | 8 | 0 | 0 | 8 | 55 | 29 | 0 | 0 | 19 | 81 | 10 | 0 | 0 | 7 | 44 | 16 | 0 | 0 | 0 | 405 | | |
| 2024-11-09 17:15:00 | 20 | 96 | 13 | 0 | 0 | 11 | 45 | 22 | 0 | 0 | 24 | 77 | 12 | 0 | 0 | 7 | 54 | 14 | 0 | 0 | 0 | 395 | | |
| 2024-11-09 17:30:00 | 20 | 88 | 11 | 0 | 0 | 9 | 43 | 25 | 0 | 0 | 25 | 55 | 9 | 0 | 0 | 7 | 53 | 26 | 0 | 0 | 0 | 371 | | |
| 2024-11-09 17:45:00 | 34 | 77 | 6 | 0 | 0 | 12 | 57 | 29 | 0 | 0 | 20 | 62 | 5 | 0 | 0 | 7 | 51 | 35 | 0 | 0 | 0 | 395 | | |
| 2024-11-09 18:00:00 | 23 | 90 | 10 | 0 | 0 | 9 | 43 | 21 | 0 | 0 | 16 | 54 | 17 | 0 | 0 | 4 | 40 | 20 | 0 | 0 | 0 | 347 | | |
| 2024-11-09 18:15:00 | 30 | 65 | 12 | 0 | 0 | 17 | 57 | 19 | 0 | 0 | 15 | 50 | 10 | 0 | 0 | 7 | 51 | 22 | 0 | 0 | 0 | 355 | | |
| 2024-11-09 18:30:00 | 31 | 81 | 5 | 0 | 0 | 9 | 40 | 19 | 0 | 0 | 23 | 69 | 4 | 0 | 0 | 5 | 40 | 22 | 0 | 0 | 0 | 348 | | |
| 2024-11-09 18:45:00 | 22 | 84 | 3 | 0 | 0 | 11 | 27 | 15 | 0 | 0 | 24 | 51 | 6 | 0 | 0 | 6 | 37 | 14 | 0 | 0 | 0 | 300 | | |
| 2024-11-09 19:00:00 | 19 | 61 | 6 | 0 | 0 | 15 | 32 | 21 | 0 | 0 | 10 | 54 | 9 | 0 | 0 | 4 | 46 | 15 | 0 | 0 | 0 | 292 | | |
| 2024-11-09 19:15:00 | 21 | 66 | 3 | 0 | 0 | 9 | 30 | 12 | 0 | 0 | 14 | 52 | 5 | 0 | 0 | 6 | 26 | 15 | 0 | 0 | 0 | 259 | | |
| 2024-11-09 19:30:00 | 19 | 52 | 4 | 0 | 0 | 6 | 29 | 10 | 0 | 0 | 6 | 58 | 6 | 0 | 0 | 4 | 40 | 6 | 0 | 0 | 0 | 240 | | |
| 2024-11-09 19:45:00 | 23 | 60 | 4 | 0 | 0 | 8 | 19 | 9 | 0 | 0 | 9 | 37 | 5 | 0 | 0 | 3 | 24 | 17 | 0 | 0 | 0 | 218 | | |
| 2024-11-09 20:00:00 | 15 | 52 | 4 | 0 | 0 | 10 | 19 | 8 | 0 | 0 | 7 | 34 | 6 | 0 | 0 | 3 | 26 | 19 | 0 | 0 | 0 | 203 | | |
| 2024-11-09 20:15:00 | 11 | 50 | 1 | 0 | 0 | 7 | 23 | 11 | 0 | 0 | 8 | 27 | 6 | 0 | 0 | 0 | 34 | 11 | 0 | 0 | 0 | 189 | | |
| 2024-11-09 20:30:00 | 10 | 54 | 1 | 0 | 0 | 7 | 20 | 6 | 0 | 0 | 11 | 36 | 4 | 0 | 0 | 3 | 22 | 10 | 0 | 0 | 0 | 184 | | |
| 2024-11-09 20:45:00 | 5 | 45 | 5 | 0 | 0 | 8 | 25 | 6 | 0 | 0 | 10 | 32 | 3 | 0 | 0 | 4 | 24 | 12 | 0 | 0 | 0 | 179 | | |
| 2024-11-09 21:00:00 | 11 | 70 | 3 | 0 | 0 | 2 | 24 | 11 | 0 | 0 | 9 | 24 | 3 | 0 | 0 | 3 | 20 | 9 | 0 | 0 | 0 | 189 | | |
| 2024-11-09 21:15:00 | 7 | 51 | 2 | 0 | 0 | 7 | 11 | 8 | 0 | 0 | 7 | 26 | 2 | 0 | 0 | 2 | 20 | 10 | 0 | 0 | 0 | 153 | | |
| 2024-11-09 21:30:00 | 13 | 35 | 3 | 0 | 0 | 2 | 9 | 6 | 0 | 0 | 2 | 29 | 2 | 0 | 0 | 2 | 22 | 9 | 0 | 0 | 0 | 134 | | |
| 2024-11-09 21:45:00 | 4 | 35 | 4 | 0 | 0 | 5 | 9 | 7 | 0 | 0 | 6 | 30 | 3 | 0 | 0 | 1 | 14 | 5 | 0 | 0 | 0 | 123 | | |
| 2024-11-09 22:00:00 | 8 | 41 | 0 | 0 | 0 | 8 | 12 | 5 | 0 | 0 | 3 | 28 | 8 | 0 | 0 | 0 | 21 | 8 | 0 | 0 | 0 | 142 | | |
| 2024-11-09 22:15:00 | 6 | 19 | 1 | 0 | 0 | 6 | 15 | 5 | 0 | 0 | 7 | 26 | 1 | 0 | 0 | 0 | 20 | 5 | 0 | 0 | 0 | 111 | | |
| 2024-11-09 22:30:00 | 5 | 33 | 8 | 0 | 0 | 2 | 22 | 4 | 0 | 0 | 9 | 14 | 3 | 0 | 0 | 0 | 12 | 8 | 0 | 0 | 0 | 120 | | |
| 2024-11-09 22:45:00 | 3 | 30 | 2 | 0 | 0 | 1 | 9 | 3 | 0 | 0 | 9 | 10 | 4 | 0 | 0 | 1 | 10 | 5 | 0 | 0 | 0 | 87 | | |
| 2024-11-09 23:00:00 | 5 | 15 | 1 | 0 | 0 | 0 | 3 | 2 | 0 | 0 | 6 | 11 | 3 | 0 | 0 | 1 | 12 | 7 | 0 | 0 | 0 | 66 | | |
| 2024-11-09 23:15:00 | 1 | 22 | 0 | 0 | 0 | 1 | 7 | 1 | 0 | 0 | 3 | 16 | 0 | 0 | 0 | 1 | 6 | 5 | 0 | 0 | 0 | 63 | | |
| 2024-11-09 23:30:00 | 3 | 23 | 0 | 0 | 0 | 1 | 10 | 4 | 0 | 0 | 2 | 6 | 2 | 0 | 0 | 2 | 12 | 3 | 0 | 0 | 0 | 68 | | |
| 2024-11-09 23:45:00 | 0 | 8 | 1 | 0 | 0 | 2 | 3 | 2 | 0 | 0 | 7 | 8 | 1 | 0 | 0 | 1 | 9 | 7 | 0 | 0 | 0 | 49 | | |

Summary

| | |
|---|---|
| Study Name | Eggert Road and Bailey Avenue |
| Project | |
| Project Code | |
| Legs and Movements | |
| Bin Size | 15 minutes |
| Time Zone | |
| Start Time | 2024-12-03 00:00:00 +0000 |
| End Time | 2024-12-05 00:00:00 +0000 |
| Location | Eggert Road and Bailey Avenue |
| Latitude and Longitude | 42.97724343,-78.81372775 |

| | |
|---|---|
| AM Peak | 10:30-11:30 |
| Midday Peak | 15:00-16:00 |
| PM Peak (Overall Peak Hour) | 15:45-16:45 |
| Custom ID | |
| Tags | |

Summary

| Entry | Bailey Avenue | | | | | Eggert Road | | | | | | Bailey Avenue | | | | | | Eggert Road | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Left | Thru | Right | Crosswalk | Crosswalk | Left | Thru | Right | U-Turn | Crosswalk | Crosswalk | Left | Thru | Right | Crosswalk | Crosswalk | Left | Thru | Right | U-Turn | Crosswalk | Crosswalk | Total | |
| 2024-12-03 00:00:00 +0000 | 1 | 7 | 0 | 0 | 0 | 1 | 5 | 1 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 6 | 5 | 0 | 0 | 0 | 30 | |
| 2024-12-03 00:15:00 +0000 | 1 | 7 | 0 | 0 | 0 | 2 | 5 | 1 | 0 | 0 | 0 | 0 | 4 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 24 | |
| 2024-12-03 00:30:00 +0000 | 1 | 6 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 15 | |
| 2024-12-03 00:45:00 +0000 | 0 | 3 | 0 | 0 | 0 | 0 | 5 | 1 | 0 | 0 | 0 | 0 | 5 | 0 | 0 | 0 | 1 | 0 | 3 | 0 | 0 | 0 | 18 | |
| 2024-12-03 01:00:00 +0000 | 1 | 7 | 0 | 0 | 0 | 4 | 2 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 20 | |
| 2024-12-03 01:15:00 +0000 | 0 | 4 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 2 | 4 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 14 | |
| 2024-12-03 01:30:00 +0000 | 1 | 4 | 0 | 0 | 0 | 2 | 1 | 2 | 0 | 0 | 0 | 4 | 7 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 25 | |
| 2024-12-03 01:45:00 +0000 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 6 | |
| 2024-12-03 02:00:00 +0000 | 0 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 4 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 10 | |
| 2024-12-03 02:15:00 +0000 | 1 | 5 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 2 | 0 | 0 | 0 | 13 | |
| 2024-12-03 02:30:00 +0000 | 0 | 3 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 10 | |
| 2024-12-03 02:45:00 +0000 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | |
| 2024-12-03 03:00:00 +0000 | 1 | 3 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 9 | |
| 2024-12-03 03:15:00 +0000 | 0 | 0 | 1 | 0 | 0 | 2 | 2 | 0 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 11 | |
| 2024-12-03 03:30:00 +0000 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 4 | |
| 2024-12-03 03:45:00 +0000 | 0 | 2 | 0 | 0 | 0 | 2 | 2 | 1 | 0 | 0 | 0 | 1 | 2 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 11 | |
| 2024-12-03 04:00:00 +0000 | 0 | 3 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 8 | |
| 2024-12-03 04:15:00 +0000 | 0 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 2 | 5 | 0 | 0 | 0 | 1 | 2 | 1 | 0 | 0 | 0 | 15 | |
| 2024-12-03 04:30:00 +0000 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 3 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 9 | |
| 2024-12-03 04:45:00 +0000 | 0 | 2 | 0 | 0 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 3 | 12 | 1 | 0 | 0 | 2 | 4 | 1 | 0 | 0 | 0 | 29 | |
| 2024-12-03 05:00:00 +0000 | 3 | 2 | 0 | 0 | 0 | 0 | 3 | 4 | 0 | 0 | 0 | 3 | 7 | 1 | 0 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 27 | |
| 2024-12-03 05:15:00 +0000 | 1 | 3 | 0 | 0 | 0 | 0 | 4 | 2 | 0 | 0 | 0 | 0 | 3 | 1 | 0 | 0 | 2 | 7 | 5 | 0 | 0 | 0 | 28 | |
| 2024-12-03 05:30:00 +0000 | 0 | 7 | 0 | 0 | 0 | 0 | 6 | 1 | 0 | 0 | 0 | 0 | 10 | 2 | 0 | 0 | 3 | 9 | 6 | 0 | 0 | 0 | 44 | |
| 2024-12-03 05:45:00 +0000 | 0 | 6 | 0 | 0 | 0 | 0 | 11 | 2 | 0 | 0 | 0 | 10 | 10 | 0 | 0 | 0 | 0 | 10 | 13 | 0 | 0 | 0 | 62 | |
| 2024-12-03 06:00:00 +0000 | 2 | 17 | 1 | 0 | 0 | 2 | 12 | 4 | 0 | 0 | 0 | 6 | 16 | 1 | 0 | 0 | 2 | 8 | 5 | 0 | 0 | 0 | 76 | |
| 2024-12-03 06:15:00 +0000 | 1 | 13 | 0 | 0 | 0 | 3 | 11 | 4 | 0 | 0 | 0 | 9 | 16 | 3 | 0 | 0 | 2 | 20 | 11 | 0 | 0 | 0 | 93 | |
| 2024-12-03 06:30:00 +0000 | 2 | 24 | 1 | 0 | 0 | 1 | 16 | 3 | 0 | 0 | 0 | 8 | 12 | 3 | 0 | 0 | 3 | 20 | 18 | 0 | 0 | 0 | 111 | |
| 2024-12-03 06:45:00 +0000 | 3 | 29 | 3 | 0 | 0 | 1 | 19 | 8 | 0 | 0 | 0 | 13 | 28 | 6 | 0 | 0 | 4 | 32 | 23 | 0 | 0 | 0 | 169 | |
| 2024-12-03 07:00:00 +0000 | 2 | 25 | 2 | 0 | 0 | 2 | 25 | 8 | 0 | 0 | 0 | 5 | 32 | 1 | 0 | 0 | 5 | 25 | 17 | 0 | 0 | 0 | 149 | |
| 2024-12-03 07:15:00 +0000 | 3 | 37 | 4 | 0 | 0 | 4 | 20 | 11 | 0 | 0 | 0 | 11 | 25 | 2 | 0 | 0 | 2 | 43 | 25 | 0 | 0 | 0 | 187 | |
| 2024-12-03 07:30:00 +0000 | 10 | 36 | 4 | 0 | 0 | 11 | 46 | 19 | 0 | 0 | 0 | 13 | 30 | 5 | 0 | 0 | 3 | 70 | 44 | 0 | 0 | 0 | 291 | |
| 2024-12-03 07:45:00 +0000 | 9 | 55 | 4 | 0 | 0 | 6 | 48 | 20 | 0 | 0 | 0 | 11 | 43 | 2 | 0 | 0 | 8 | 54 | 22 | 0 | 0 | 0 | 282 | |
| 2024-12-03 08:00:00 +0000 | 4 | 60 | 5 | 0 | 0 | 8 | 27 | 20 | 0 | 0 | 0 | 11 | 47 | 3 | 0 | 0 | 6 | 49 | 28 | 0 | 0 | 0 | 268 | |
| 2024-12-03 08:15:00 +0000 | 9 | 47 | 1 | 0 | 0 | 9 | 36 | 10 | 0 | 0 | 0 | 12 | 37 | 5 | 0 | 0 | 5 | 45 | 18 | 0 | 0 | 0 | 234 | |
| 2024-12-03 08:30:00 +0000 | 3 | 39 | 3 | 0 | 0 | 6 | 29 | 12 | 0 | 0 | 0 | 14 | 51 | 10 | 0 | 0 | 12 | 58 | 25 | 0 | 0 | 0 | 262 | |
| 2024-12-03 08:45:00 +0000 | 8 | 73 | 4 | 0 | 0 | 18 | 47 | 20 | 0 | 0 | 0 | 17 | 61 | 4 | 0 | 0 | 10 | 44 | 29 | 0 | 0 | 0 | 335 | |
| 2024-12-03 09:00:00 +0000 | 8 | 52 | 9 | 0 | 0 | 8 | 43 | 12 | 0 | 0 | 0 | 13 | 45 | 11 | 0 | 0 | 6 | 35 | 22 | 0 | 0 | 0 | 264 | |
| 2024-12-03 09:15:00 +0000 | 17 | 50 | 5 | 0 | 0 | 5 | 42 | 16 | 0 | 0 | 0 | 15 | 56 | 14 | 0 | 0 | 6 | 46 | 22 | 0 | 0 | 0 | 294 | |
| 2024-12-03 09:30:00 +0000 | 12 | 42 | 5 | 0 | 0 | 6 | 37 | 30 | 0 | 0 | 0 | 10 | 78 | 6 | 0 | 0 | 7 | 42 | 12 | 0 | 0 | 0 | 287 | |
| 2024-12-03 09:45:00 +0000 | 15 | 48 | 8 | 0 | 0 | 8 | 53 | 22 | 0 | 0 | 0 | 13 | 53 | 8 | 0 | 0 | 7 | 54 | 22 | 0 | 0 | 0 | 311 | |
| 2024-12-03 10:00:00 +0000 | 15 | 51 | 9 | 0 | 0 | 8 | 38 | 23 | 0 | 0 | 0 | 17 | 63 | 4 | 0 | 0 | 8 | 51 | 23 | 0 | 0 | 0 | 310 | |
| 2024-12-03 10:15:00 +0000 | 15 | 41 | 10 | 0 | 0 | 2 | 48 | 22 | 0 | 0 | 0 | 13 | 64 | 7 | 0 | 0 | 8 | 42 | 17 | 0 | 0 | 0 | 289 | |
| 2024-12-03 10:30:00 +0000 | 12 | 55 | 2 | 0 | 0 | 3 | 53 | 20 | 0 | 0 | 0 | 13 | 46 | 3 | 0 | 0 | 10 | 44 | 17 | 0 | 0 | 0 | 278 | |
| 2024-12-03 10:45:00 +0000 | 10 | 57 | 5 | 0 | 0 | 4 | 50 | 32 | 0 | 0 | 0 | 28 | 80 | 2 | 0 | 0 | 4 | 42 | 18 | 0 | 0 | 0 | 332 | |
| 2024-12-03 11:00:00 +0000 | 14 | 53 | 4 | 0 | 0 | 9 | 39 | 29 | 0 | 0 | 0 | 11 | 47 | 6 | 0 | 0 | 10 | 37 | 20 | 0 | 0 | 0 | 279 | |
| 2024-12-03 11:15:00 +0000 | 17 | 68 | 7 | 0 | 0 | 9 | 55 | 27 | 0 | 0 | 0 | 21 | 72 | 11 | 0 | 0 | 12 | 47 | 23 | 0 | 0 | 0 | 369 | |
| 2024-12-03 11:30:00 +0000 | 13 | 43 | 8 | 0 | 0 | 9 | 60 | 31 | 0 | 0 | 0 | 15 | 61 | 9 | 0 | 0 | 8 | 49 | 23 | 0 | 0 | 0 | 329 | |
| 2024-12-03 11:45:00 +0000 | 20 | 91 | 6 | 0 | 0 | 13 | 60 | 22 | 0 | 0 | 0 | 27 | 61 | 8 | 0 | 0 | 17 | 59 | 18 | 0 | 0 | 0 | 402 | |
| 2024-12-03 12:00:00 +0000 | 13 | 77 | 4 | 0 | 0 | 10 | 51 | 27 | 0 | 0 | 0 | 24 | 98 | 5 | 0 | 0 | 9 | 46 | 21 | 0 | 0 | 0 | 385 | |
| 2024-12-03 12:15:00 +0000 | 17 | 87 | 7 | 0 | 0 | 5 | 53 | 28 | 0 | 0 | 0 | 19 | 74 | 6 | 0 | 0 | 9 | 39 | 25 | 0 | 0 | 0 | 369 | |
| 2024-12-03 12:30:00 +0000 | 20 | 68 | 8 | 0 | 0 | 11 | 52 | 30 | 0 | 0 | 0 | 22 | 76 | 8 | 0 | 0 | 11 | 55 | 25 | 0 | 0 | 0 | 386 | |
| 2024-12-03 12:45:00 +0000 | 17 | 62 | 17 | 0 | 0 | 11 | 36 | 30 | 0 | 0 | 0 | 31 | 95 | 6 | 0 | 0 | 14 | 51 | 23 | 0 | 0 | 0 | 393 | |
| 2024-12-03 13:00:00 +0000 | 16 | 65 | 3 | 0 | 0 | 13 | 29 | 25 | 0 | 0 | 0 | 28 | 68 | 5 | 0 | 0 | 9 | 42 | 22 | 0 | 0 | 0 | 325 | |
| 2024-12-03 13:15:00 +0000 | 24 | 75 | 14 | 0 | 0 | 7 | 48 | 20 | 0 | 0 | 0 | 14 | 74 | 8 | 0 | 0 | 10 | 51 | 22 | 0 | 0 | 0 | 367 | |
| 2024-12-03 13:30:00 +0000 | 27 | 70 | 12 | 0 | 0 | 4 | 52 | 29 | 0 | 0 | 0 | 17 | 57 | 6 | 0 | 0 | 10 | 59 | 24 | 0 | 0 | 0 | 367 | |
| 2024-12-03 13:45:00 +0000 | 13 | 81 | 8 | 0 | 0 | 11 | 52 | 27 | 0 | 0 | 0 | 25 | 79 | 6 | 0 | 0 | 11 | 58 | 32 | 0 | 0 | 0 | 403 | |
| 2024-12-03 14:00:00 +0000 | 29 | 80 | 7 | 0 | 0 | 7 | 54 | 27 | 0 | 0 | 0 | 24 | 61 | 9 | 0 | 0 | 6 | 55 | 23 | 0 | 0 | 0 | 382 | |
| 2024-12-03 14:15:00 +0000 | 25 | 86 | 8 | 0 | 0 | 13 | 53 | 35 | 0 | 0 | 0 | 19 | 50 | 3 | 0 | 0 | 11 | 59 | 22 | 0 | 0 | 0 | 384 | |
| 2024-12-03 14:30:00 +0000 | 25 | 77 | 11 | 0 | 0 | 13 | 64 | 20 | 0 | 0 | 0 | 28 | 81 | 11 | 0 | 0 | 19 | 57 | 19 | 0 | 0 | 0 | 425 | |
| 2024-12-03 14:45:00 +0000 | 23 | 90 | 8 | 0 | 0 | 11 | 54 | 25 | 0 | 0 | 0 | 28 | 86 | 6 | 0 | 0 | 11 | 44 | 26 | 0 | 0 | 0 | 412 | |
| 2024-12-03 15:00:00 +0000 | 22 | 64 | 9 | 0 | 0 | 11 | 68 | 31 | 0 | 0 | 0 | 31 | 77 | 6 | 0 | 0 | 15 | 66 | 26 | 0 | 0 | 0 | 426 | |
| 2024-12-03 15:15:00 +0000 | 32 | 98 | 11 | 0 | 0 | 9 | 57 | 32 | 0 | 0 | 0 | 42 | 93 | 8 | 0 | 0 | 16 | 60 | 17 | 0 | 0 | 0 | 475 | |
| 2024-12-03 15:30:00 +0000 | 16 | 89 | 11 | 0 | 0 | 9 | 67 | 27 | 0 | 0 | 0 | 42 | 88 | 11 | 0 | 0 | 11 | 66 | 20 | 0 | 0 | 0 | 457 | |
| 2024-12-03 15:45:00 +0000 | 20 | 84 | 13 | 0 | 0 | 13 | 73 | 30 | 0 | 0 | 0 | 43 | 103 | 14 | 0 | 0 | 10 | 67 | 26 | 0 | 0 | 0 | 496 | |
| 2024-12-03 16:00:00 +0000 | 28 | 86 | 15 | 0 | 0 | 11 | 77 | 27 | 0 | 0 | 0 | 27 | 85 | 9 | 0 | 0 | 10 | 66 | 23 | 0 | 0 | 0 | 464 | |
| 2024-12-03 16:15:00 +0000 | 25 | 83 | 11 | 0 | 0 | 10 | 87 | 27 | 0 | 0 | 0 | 30 | 82 | 9 | 0 | 0 | 9 | 73 | 29 | 0 | 0 | 0 | 475 | Lights HV |
| 2024-12-03 16:30:00 +0000 | 32 | 70 | 12 | 0 | 0 | 7 | 71 | 35 | 0 | 0 | 0 | 29 | 92 | 11 | 0 | 0 | 9 | 72 | 21 | 0 | 0 | 0 | 461 | 461 0 |
| 2024-12-03 16:45:00 +0000 | 25 | 91 | 12 | 0 | 0 | 14 | 80 | 28 | 0 | 0 | 0 | 29 | 91 | 14 | 0 | 0 | 9 | 70 | 22 | 0 | 0 | 0 | 485 | 483 2 |
| 2024-12-03 17:00:00 +0000 | 30 | 77 | 12 | 0 | 0 | 7 | 78 | 27 | 0 | 0 | 0 | 27 | 85 | 13 | 0 | 0 | 9 | 73 | 30 | 0 | 0 | 0 | 468 | 465 3 |
| 2024-12-03 17:15:00 +0000 | 33 | 89 | 10 | 0 | 0 | 11 | 65 | 29 | 0 | 0 | 0 | 25 | 82 | 13 | 0 | 0 | 9 | 58 | 28 | 0 | 0 | 0 | 452 | 449 3 |
| | | | | | | | | | | | | | | | | | | | | | PHF | | 0.961856 | |
| | | | | | | | | | | | | | | | | | | | | | HV | | 0.4% | |
| 2024-12-03 17:30:00 +0000 | 20 | 72 | 6 | 0 | 0 | 11 | 68 | 20 | 1 | 0 | 0 | 20 | 79 | 10 | 0 | 0 | 11 | 56 | 19 | 0 | 0 | 0 | 393 | |
| 2024-12-03 17:45:00 +0000 | 19 | 82 | 8 | 0 | 0 | 11 | 76 | 43 | 0 | 0 | 0 | 14 | 85 | 6 | 0 | 0 | 8 | 59 | 14 | 0 | 0 | 0 | 425 | |
| 2024-12-03 18:00:00 +0000 | 21 | 59 | 6 | 0 | 0 | 13 | 57 | 24 | 0 | 0 | 0 | 17 | 90 | 10 | 0 | 0 | 14 | 52 | 23 | 0 | 0 | 0 | 386 | |
| 2024-12-03 18:15:00 +0000 | 24 | 76 | 9 | 0 | 0 | 13 | 43 | 20 | 0 | 0 | 0 | 21 | 62 | 10 | 0 | 0 | 6 | 53 | 20 | 0 | 0 | 0 | 357 | |
| 2024-12-03 18:30:00 +0000 | 20 | 69 | 6 | 0 | 0 | 12 | 44 | 15 | 0 | 0 | 0 | 16 | 50 | 9 | 0 | 0 | 10 | 46 | 14 | 0 | 0 | 0 | 311 | |
| 2024-12-03 18:45:00 +0000 | 23 | 63 | 6 | 0 | 0 | 10 | 36 | 17 | 0 | 0 | 0 | 15 | 52 | 7 | 0 | 0 | 3 | 40 | 20 | 0 | 0 | 0 | 292 | |
| 2024-12-03 19:00:00 +0000 | 16 | 71 | 8 | 0 | 0 | 6 | 38 | 12 | 0 | 0 | 0 | 15 | 52 | 9 | 0 | 0 | 12 | 47 | 21 | 0 | 0 | 0 | 307 | |
| 2024-12-03 19:15:00 +0000 | 20 | 65 | 5 | 0 | 0 | 6 | 38 | 15 | 0 | 0 | 0 | 8 | 50 | 13 | 0 | 0 | 4 | 39 | 10 | 0 | 0 | 0 | 273 | |
| 2024-12-03 19:30:00 +0000 | 22 | 47 | 4 | 0 | 0 | 16 | 23 | 16 | 0 | 0 | 0 | 12 | 45 | 7 | 0 | 0 | 2 | 41 | 18 | 0 | 0 | 0 | 253 | |
| 2024-12-03 19:45:00 +0000 | 14 | 59 | 7 | 0 | 0 | 4 | 23 | 11 | 0 | 0 | 0 | 15 | 49 | 6 | 0 | 0 | 6 | 29 | 10 | 0 | 0 | 0 | 233 | |
| 2024-12-03 20:00:00 +0000 | 8 | 61 | 6 | 0 | 0 | 7 | 16 | 10 | 0 | 0 | 0 | 7 | 32 | 5 | 0 | 0 | 4 | 38 | 16 | 0 | 0 | 0 | 210 | |
| 2024-12-03 20:15:00 +0000 | 13 | 66 | 1 | 0 | 0 | 4 | 25 | 12 | 0 | 0 | 0 | 8 | 40 | 4 | 0 | 0 | 2 | 28 | 6 | 0 | 0 | 0 | 209 | |
| 2024-12-03 20:30:00 +0000 | 15 | 48 | 2 | 0 | 0 | 6 | 16 | 5 | 0 | 0 | 0 | 10 | 38 | 2 | 0 | 0 | 3 | 24 | 13 | 0 | 0 | 0 | 182 | |
| 2024-12-03 20:45:00 +0000 | 14 | 45 | 6 | 0 | 0 | 2 | 14 | 9 | 0 | 0 | 0 | 8 | 28 | 3 | 0 | 0 | 2 | 18 | 10 | 0 | 0 | 0 | 159 | |
| 2024-12-03 21:00:00 +0000 | 7 | 49 | 7 | 0 | 0 | 7 | 27 | 9 | 0 | 0 | 0 | 3 | 19 | 3 | 0 | 0 | 5 | 25 | 11 | 0 | 0 | 0 | 172 | |
| 2024-12-03 21:15:00 +0000 | 8 | 37 | 5 | 0 | 0 | 8 | 9 | 5 | 0 | 0 | 0 | 2 | 28 | 5 | 0 | 0 | 1 | 15 | 3 | 0 | 0 | 0 | 126 | |
| 2024-12-03 21:30:00 +0000 | 10 | 42 | 0 | 0 | 0 | 5 | 13 | 3 | 0 | 0 | 0 | 2 | 26 | 5 | 0 | 0 | 2 | 15 | 8 | 0 | 0 | 0 | 131 | |
| 2024-12-03 21:45:00 +0000 | 5 | 20 | 2 | 0 | 0 | 9 | 12 | 7 | 0 | 0 | 0 | 8 | 24 | 3 | 0 | 0 | 2 | 14 | 6 | 0 | 0 | 0 | 112 | |
| 2024-12-03 22:00:00 +0000 | 5 | 38 | 3 | 0 | 0 | 5 | 13 | 8 | 0 | 0 | 0 | 4 | 15 | 1 | 0 | 0 | 2 | 10 | 9 | 0 | 0 | 0 | 113 | |
| 2024-12-03 22:15:00 +0000 | 6 | 29 | 1 | 0 | 0 | 4 | 9 | 0 | 0 | 0 | 0 | 3 | 24 | 5 | 0 | 0 | 0 | 13 | 5 | 0 | 0 | 0 | 99 | |
| 2024-12-03 22:30:00 +0000 | 1 | 26 | 1 | 0 | 0 | 8 | 16 | 2 | 0 | 0 | 0 | 4 | 18 | 1 | 0 | 0 | 2 | 14 | 5 | 0 | 0 | 0 | 98 | |
| 2024-12-03 22:45:00 +0000 | 2 | 13 | 1 | 0 | 0 | 1 | 7 | 1 | 0 | 0 | 0 | 7 | 12 | 1 | 0 | 0 | 0 | 6 | 0 | 0 | 0 | 0 | 51 | |
| 2024-12-03 23:00:00 +0000 | 0 | 23 | 1 | 0 | 0 | 0 | 8 | 2 | 0 | 0 | 0 | 6 | 10 | 0 | 0 | 0 | 2 | 7 | 3 | 0 | 0 | 0 | 62 | |
| 2024-12-03 23:15:00 +0000 | 1 | 15 | 1 | 0 | 0 | 1 | 9 | 1 | 0 | 0 | 0 | 4 | 8 | 3 | 0 | 0 | 1 | 7 | 2 | 0 | 0 | 0 | 53 | |
| 2024-12-03 23:30:00 +0000 | 0 | 12 | 1 | 0 | 0 | 0 | 10 | 1 | 0 | 0 | 0 | 5 | 4 | 1 | 0 | 0 | 0 | 4 | 7 | 0 | 0 | 0 | 45 | |
| 2024-12-03 23:45:00 +0000 | 2 | 6 | 1 | 0 | 0 | 1 | 6 | 1 | 0 | 0 | 0 | 0 | 6 | 2 | 0 | 0 | 0 | 4 | 2 | 0 | 0 | 0 | 31 | |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/4/2023 0:00
End Time 2/4/2023 23:59
Location Maple Road @ Alberta Drive
Latitude ar 42.99087363,-78.81709853

All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00:00 | 14 | 9 | 2 | 0 | 0 | 0 | 0 | 160 | 35 | 0 | 0 | 0 | 42 | 15 | 48 | 0 | 0 | 0 | 36 | 117 | 6 | 1 | 0 | 0 | 485 |
| 12:15:00 | 14 | 2 | 4 | 0 | 0 | 0 | 2 | 171 | 33 | 0 | 0 | 0 | 40 | 19 | 55 | 0 | 0 | 0 | 61 | 115 | 8 | 0 | 0 | 0 | 524 |
| 12:30:00 | 12 | 15 | 0 | 0 | 0 | 0 | 0 | 157 | 43 | 0 | 0 | 0 | 23 | 16 | 52 | 0 | 0 | 0 | 29 | 124 | 8 | 0 | 0 | 0 | 479 |
| 12:45:00 | 16 | 6 | 3 | 0 | 0 | 0 | 3 | 173 | 46 | 0 | 0 | 0 | 46 | 9 | 57 | 0 | 0 | 0 | 48 | 128 | 12 | 0 | 0 | 0 | 547 |
| 13:00:00 | 8 | 11 | 2 | 0 | 0 | 0 | 2 | 146 | 44 | 0 | 0 | 0 | 41 | 13 | 52 | 0 | 0 | 0 | 44 | 136 | 13 | 0 | 0 | 0 | 512 |
| 13:15:00 | 10 | 8 | 2 | 0 | 0 | 0 | 2 | 168 | 41 | 0 | 0 | 0 | 35 | 18 | 71 | 0 | 0 | 0 | 37 | 118 | 8 | 0 | 0 | 0 | 518 |
| 13:30:00 | 6 | 6 | 2 | 0 | 0 | 0 | 2 | 168 | 37 | 0 | 0 | 0 | 50 | 19 | 64 | 0 | 0 | 0 | 51 | 129 | 14 | 0 | 0 | 0 | 548 |
| 13:45:00 | 12 | 21 | 5 | 0 | 0 | 0 | 1 | 173 | 39 | 0 | 0 | 0 | 34 | 17 | 60 | 0 | 0 | 0 | 46 | 130 | 14 | 0 | 0 | 0 | 552 |
| 14:00:00 | 14 | 11 | 4 | 0 | 0 | 0 | 2 | 186 | 55 | 0 | 0 | 0 | 41 | 11 | 62 | 0 | 0 | 0 | 49 | 109 | 14 | 0 | 0 | 0 | 558 |
| 14:15:00 | 15 | 12 | 3 | 0 | 0 | 0 | 2 | 160 | 51 | 0 | 0 | 0 | 42 | 15 | 65 | 0 | 0 | 0 | 39 | 118 | 9 | 0 | 0 | 0 | 531 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.980735 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 14:30:00 | 15 | 5 | 0 | 0 | 0 | 0 | 1 | 194 | 44 | 0 | 0 | 0 | 38 | 16 | 61 | 0 | 0 | 0 | 56 | 113 | 10 | 0 | 0 | 0 | 553 |
| 14:45:00 | 13 | 8 | 6 | 0 | 0 | 0 | 0 | 147 | 46 | 0 | 0 | 0 | 40 | 15 | 58 | 0 | 0 | 0 | 51 | 127 | 10 | 0 | 0 | 0 | 521 |

Lights

Summary

| | |
|---|---|
| Bin Size | 15 minutes |
| Aggregatio | Median |
| Time Zone | America/New_York |
| Start Time | ######## |
| End Time | ######## |
| Location | Maple Road @ Alberta Drive |
| Latitude an | 42.99087363,-78.81709853 |

All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 3:00 PM | 7 | 16 | 5 | 0 | 0 | 0 | 2 | 142 | 31 | 0 | 0 | 0 | 33 | 15 | 47 | 0 | 0 | 0 | 36 | 121 | 10 | 0 | 0 | 0 | 465 |
| 3:15 PM | 12 | 10 | 3 | 0 | 0 | 0 | 2 | 163 | 32 | 0 | 0 | 0 | 32 | 14 | 42 | 0 | 0 | 0 | 35 | 128 | 8 | 0 | 0 | 0 | 481 |
| 3:30 PM | 16 | 6 | 5 | 0 | 0 | 0 | 0 | 182 | 25 | 0 | 0 | 0 | 24 | 21 | 46 | 0 | 0 | 0 | 49 | 110 | 6 | 0 | 0 | 0 | 490 |
| 3:45 PM | 6 | 7 | 2 | 0 | 0 | 0 | 0 | 196 | 34 | 0 | 0 | 0 | 26 | 16 | 41 | 0 | 0 | 0 | 45 | 123 | 14 | 0 | 0 | 0 | 510 |
| 4:00 PM | 15 | 7 | 7 | 0 | 0 | 0 | 1 | 199 | 39 | 0 | 0 | 0 | 29 | 13 | 58 | 0 | 0 | 0 | 36 | 114 | 8 | 0 | 0 | 0 | 526 |
| 4:15 PM | 13 | 7 | 8 | 0 | 0 | 0 | 3 | 187 | 37 | 0 | 0 | 0 | 41 | 19 | 61 | 0 | 0 | 0 | 39 | 121 | 17 | 0 | 0 | 0 | 553 |
| 4:30 PM | 12 | 11 | 3 | 0 | 0 | 0 | 1 | 205 | 42 | 0 | 0 | 0 | 31 | 13 | 49 | 0 | 0 | 0 | 40 | 119 | 8 | 0 | 0 | 0 | 534 |
| 4:45 PM | 17 | 11 | 5 | 0 | 0 | 0 | 1 | 190 | 29 | 0 | 0 | 0 | 32 | 8 | 61 | 0 | 0 | 0 | 46 | 132 | 9 | 0 | 0 | 0 | 541 |
| 5:00 PM | 15 | 9 | 3 | 0 | 0 | 0 | 1 | 241 | 45 | 0 | 0 | 0 | 41 | 24 | 48 | 0 | 0 | 0 | 41 | 109 | 4 | 0 | 0 | 0 | 581 |
| 5:15 PM | 4 | 5 | 4 | 0 | 0 | 0 | 2 | 188 | 49 | 0 | 0 | 0 | 19 | 24 | 55 | 0 | 0 | 0 | 41 | 114 | 5 | 0 | 0 | 0 | 510 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.950516 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 17:30:00 | 9 | 3 | 3 | 0 | 0 | 0 | 3 | 167 | 26 | 0 | 0 | 0 | 43 | 11 | 42 | 0 | 0 | 0 | 38 | 128 | 9 | 0 | 0 | 0 | 482 |
| 17:45:00 | 9 | 7 | 3 | 0 | 0 | 0 | 6 | 78 | 25 | 0 | 0 | 0 | 27 | 9 | 34 | 0 | 0 | 0 | 25 | 121 | 3 | 0 | 0 | 0 | 347 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/2/2023 0:00
End Time 2/2/2023 23:59
Location North Bailey Avenue and Meyer Road
Latitude ar 42.99368334,-78.81459879
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 3:00 PM | 11 | 153 | 8 | 0 | 0 | 0 | 19 | 2 | 0 | 0 | 0 | 0 | 1 | 125 | 3 | 0 | 0 | 0 | 14 | 3 | 14 | 0 | 0 | 0 | 353 |
| 3:15 PM | 12 | 146 | 12 | 0 | 0 | 0 | 26 | 1 | 2 | 0 | 0 | 0 | 3 | 127 | 3 | 0 | 0 | 0 | 11 | 4 | 11 | 0 | 0 | 0 | 358 |
| 3:30 PM | 13 | 136 | 19 | 0 | 0 | 0 | 24 | 10 | 1 | 0 | 0 | 0 | 3 | 130 | 11 | 0 | 0 | 0 | 13 | 7 | 13 | 0 | 0 | 0 | 380 |
| 3:45 PM | 13 | 161 | 14 | 0 | 0 | 0 | 49 | 7 | 0 | 0 | 0 | 0 | 4 | 157 | 12 | 0 | 0 | 0 | 8 | 7 | 19 | 0 | 0 | 0 | 451 |
| 4:00 PM | 11 | 170 | 20 | 0 | 0 | 0 | 24 | 7 | 0 | 0 | 0 | 0 | 4 | 155 | 9 | 0 | 0 | 0 | 15 | 4 | 30 | 0 | 0 | 0 | 449 |
| 4:15 PM | 16 | 163 | 22 | 0 | 0 | 0 | 23 | 12 | 0 | 0 | 0 | 0 | 4 | 145 | 7 | 0 | 0 | 0 | 15 | 7 | 18 | 0 | 0 | 0 | 432 |
| 4:30 PM | 18 | 165 | 18 | 0 | 0 | 0 | 32 | 9 | 1 | 0 | 0 | 0 | 9 | 155 | 9 | 0 | 0 | 0 | 18 | 5 | 28 | 0 | 0 | 0 | 467 |
| 4:45 PM | 12 | 171 | 24 | 0 | 0 | 0 | 29 | 4 | 2 | 0 | 0 | 0 | 4 | 150 | 8 | 0 | 0 | 0 | 13 | 8 | 24 | 0 | 0 | 0 | 449 |
| 5:00 PM | 21 | 160 | 29 | 0 | 0 | 0 | 31 | 4 | 1 | 0 | 0 | 0 | 8 | 163 | 6 | 0 | 0 | 0 | 19 | 11 | 23 | 0 | 0 | 0 | 476 |
| 5:15 PM | 14 | 160 | 19 | 0 | 0 | 0 | 31 | 7 | 3 | 0 | 0 | 0 | 8 | 160 | 5 | 0 | 0 | 0 | 10 | 7 | 24 | 0 | 0 | 0 | 448 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.966387 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 5:30 PM | 15 | 176 | 19 | 0 | 0 | 0 | 29 | 6 | 2 | 0 | 0 | 0 | 1 | 147 | 11 | 0 | 0 | 0 | 10 | 4 | 21 | 0 | 0 | 0 | 441 |
| 5:45 PM | 11 | 164 | 17 | 0 | 0 | 0 | 31 | 5 | 1 | 0 | 0 | 0 | 6 | 126 | 4 | 0 | 0 | 0 | 13 | 4 | 25 | 0 | 0 | 0 | 407 |

Time Zone America/New_York
Start Time 2/4/2023 0:00
End Time 2/4/2023 23:59
Location Maple Road @ Hillcrest Drive
Latitude ar 42.99081477,-78.81004432
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00:00 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 294 | 2 | 0 | 0 | 0 | 4 | 0 | 2 | 0 | 0 | 0 | 1 | 192 | 0 | 0 | 0 | 0 | 496 |
| 12:15:00 | 0 | 2 | 11 | 0 | 0 | 0 | 0 | 287 | 0 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 4 | 213 | 0 | 0 | 0 | 0 | 519 |
| 12:30:00 | 0 | 1 | 3 | 0 | 0 | 0 | 0 | 278 | 3 | 0 | 0 | 0 | 2 | 0 | 5 | 0 | 0 | 0 | 2 | 236 | 0 | 0 | 0 | 0 | 530 |
| 12:45:00 | 2 | 0 | 0 | 0 | 0 | 0 | 0 | 310 | 2 | 0 | 0 | 0 | 3 | 0 | 4 | 0 | 0 | 0 | 2 | 251 | 0 | 0 | 0 | 0 | 574 |
| 13:00:00 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 286 | 1 | 0 | 0 | 0 | 5 | 0 | 5 | 0 | 0 | 0 | 4 | 232 | 0 | 0 | 0 | 0 | 535 |
| 13:15:00 | 1 | 0 | 2 | 0 | 0 | 0 | 0 | 261 | 5 | 0 | 0 | 0 | 6 | 0 | 7 | 0 | 0 | 0 | 6 | 263 | 0 | 0 | 0 | 0 | 551 |
| 13:30:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 272 | 2 | 0 | 0 | 0 | 1 | 0 | 4 | 0 | 0 | 0 | 3 | 262 | 0 | 0 | 0 | 0 | 544 |
| 13:45:00 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 320 | 2 | 0 | 0 | 0 | 2 | 0 | 6 | 0 | 0 | 0 | 5 | 263 | 0 | 0 | 0 | 0 | 598 |
| 14:00:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 300 | 2 | 0 | 0 | 0 | 2 | 0 | 6 | 0 | 0 | 0 | 1 | 243 | 0 | 0 | 0 | 0 | 555 |
| 14:15:00 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 313 | 3 | 0 | 0 | 0 | 5 | 0 | 6 | 0 | 0 | 0 | 5 | 246 | 0 | 0 | 0 | 0 | 580 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.951923 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 14:30:00 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 293 | 1 | 0 | 0 | 0 | 4 | 0 | 6 | 0 | 0 | 0 | 4 | 265 | 0 | 0 | 0 | 0 | 574 |
| 14:45:00 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 279 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 6 | 257 | 0 | 0 | 0 | 0 | 546 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/2/2023 0:00
End Time 2/2/2023 23:59
Location Maple Road @ Hillcrest Drive
Latitude ar 42.99081477,-78.81004432

All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 15:00:00 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 273 | 5 | 0 | 0 | 0 | 7 | 0 | 5 | 0 | 0 | 0 | 1 | 240 | 0 | 0 | 0 | 0 | 533 |
| 15:15:00 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 292 | 2 | 0 | 0 | 0 | 2 | 0 | 3 | 0 | 0 | 0 | 5 | 246 | 0 | 0 | 0 | 0 | 554 |
| 15:30:00 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 325 | 9 | 0 | 0 | 0 | 7 | 0 | 4 | 0 | 0 | 0 | 3 | 217 | 0 | 0 | 0 | 0 | 568 |
| 15:45:00 | 0 | 7 | 55 | 0 | 0 | 0 | 0 | 341 | 3 | 0 | 0 | 0 | 6 | 0 | 9 | 0 | 0 | 0 | 7 | 218 | 0 | 0 | 0 | 0 | 646 |
| 16:00:00 | 1 | 0 | 21 | 0 | 0 | 0 | 0 | 323 | 7 | 0 | 0 | 0 | 8 | 0 | 8 | 0 | 0 | 0 | 3 | 216 | 0 | 0 | 0 | 0 | 587 |
| 16:15:00 | 1 | 0 | 14 | 0 | 0 | 0 | 0 | 342 | 1 | 0 | 0 | 0 | 8 | 0 | 6 | 0 | 0 | 0 | 4 | 260 | 0 | 0 | 0 | 0 | 636 |
| 16:30:00 | 1 | 0 | 14 | 0 | 0 | 0 | 0 | 334 | 6 | 0 | 0 | 0 | 11 | 0 | 5 | 0 | 0 | 0 | 3 | 254 | 0 | 0 | 0 | 0 | 628 |
| 16:45:00 | 1 | 0 | 6 | 0 | 0 | 0 | 0 | 334 | 4 | 0 | 0 | 0 | 6 | 0 | 9 | 0 | 0 | 0 | 3 | 257 | 0 | 0 | 0 | 0 | 620 |
| 17:00:00 | 0 | 0 | 4 | 0 | 0 | 0 | 0 | 409 | 2 | 0 | 0 | 0 | 9 | 0 | 8 | 0 | 0 | 0 | 3 | 258 | 0 | 0 | 0 | 0 | 693 |
| 17:15:00 | 3 | 0 | 3 | 0 | 0 | 0 | 0 | 387 | 7 | 0 | 0 | 0 | 7 | 0 | 10 | 0 | 0 | 0 | 9 | 222 | 0 | 0 | 0 | 0 | 648 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.929654 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 17:30:00 | 1 | 0 | 8 | 0 | 0 | 0 | 0 | 329 | 4 | 0 | 0 | 0 | 7 | 0 | 4 | 0 | 0 | 0 | 6 | 246 | 0 | 0 | 0 | 0 | 605 |
| 17:45:00 | 3 | 1 | 18 | 0 | 0 | 0 | 0 | 208 | 1 | 0 | 0 | 0 | 8 | 0 | 7 | 0 | 0 | 0 | 4 | 255 | 0 | 0 | 0 | 0 | 505 |

Aggregatio Median
Time Zone America/New_York
Start Time 2/4/2023 0:00
End Time 2/4/2023 23:59
Location Maple Road and Bowmart Pkwy
Latitude ar 42.99085401,-78.81192186
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00:00 | 19 | 0 | 31 | 0 | 0 | 0 | 34 | 237 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 165 | 36 | 0 | 0 | 0 | 0 | 522 |
| 12:15:00 | 23 | 0 | 34 | 0 | 0 | 0 | 36 | 251 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 187 | 32 | 0 | 0 | 0 | 0 | 563 |
| 12:30:00 | 32 | 0 | 38 | 0 | 0 | 0 | 39 | 231 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 198 | 25 | 0 | 0 | 0 | 0 | 563 |
| 12:45:00 | 37 | 0 | 28 | 0 | 0 | 0 | 38 | 266 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 225 | 25 | 0 | 0 | 0 | 0 | 619 |
| 13:00:00 | 29 | 0 | 47 | 0 | 0 | 0 | 41 | 235 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 189 | 27 | 0 | 0 | 0 | 0 | 568 |
| 13:15:00 | 29 | 0 | 41 | 0 | 0 | 0 | 30 | 231 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 235 | 18 | 0 | 0 | 0 | 0 | 584 |
| 13:30:00 | 32 | 0 | 40 | 0 | 0 | 0 | 42 | 231 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 218 | 16 | 0 | 0 | 0 | 0 | 579 |
| 13:45:00 | 39 | 0 | 54 | 0 | 0 | 0 | 46 | 274 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 215 | 28 | 0 | 0 | 0 | 0 | 656 |
| 14:00:00 | 29 | 0 | 49 | 0 | 0 | 0 | 36 | 256 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 197 | 21 | 0 | 0 | 0 | 0 | 588 |
| 14:15:00 | 27 | 0 | 47 | 0 | 0 | 0 | 34 | 259 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 205 | 18 | 0 | 0 | 0 | 0 | 590 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.919588 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 1% |
| 14:30:00 | 27 | 0 | 40 | 0 | 0 | 0 | 35 | 263 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 223 | 20 | 0 | 0 | 0 | 0 | 608 |
| 14:45:00 | 25 | 0 | 55 | 0 | 0 | 0 | 39 | 223 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 214 | 14 | 0 | 0 | 0 | 0 | 570 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/2/2023 0:00
End Time 2/2/2023 23:59
Location Maple Road and Bowmart Pkwy
Latitude ar 42.99085401,-78.81192186
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 15:00:00 | 24 | 0 | 33 | 0 | 0 | 0 | 38 | 235 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 210 | 16 | 0 | 0 | 0 | | 556 |
| 15:15:00 | 24 | 0 | 38 | 0 | 0 | 0 | 38 | 250 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 214 | 19 | 0 | 0 | 0 | | 583 |
| 15:30:00 | 17 | 0 | 33 | 0 | 0 | 0 | 51 | 269 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 198 | 9 | 0 | 0 | 0 | | 577 |
| 15:45:00 | 16 | 0 | 40 | 0 | 0 | 0 | 70 | 323 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 194 | 15 | 0 | 0 | 0 | | 658 |
| 16:00:00 | 35 | 0 | 29 | 0 | 0 | 0 | 47 | 276 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 184 | 23 | 0 | 0 | 0 | | 594 |
| 16:15:00 | 31 | 0 | 46 | 0 | 0 | 0 | 60 | 258 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 218 | 22 | 0 | 0 | 0 | | 635 |
| 16:30:00 | 21 | 0 | 48 | 0 | 0 | 0 | 52 | 308 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 208 | 17 | 0 | 0 | 0 | | 654 |
| 16:45:00 | 21 | 0 | 42 | 0 | 0 | 0 | 52 | 276 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 223 | 23 | 0 | 0 | 0 | | 637 |
| 17:00:00 | 21 | 0 | 60 | 0 | 0 | 0 | 54 | 338 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 198 | 21 | 0 | 0 | 0 | | 692 |
| 17:15:00 | 24 | 0 | 42 | 0 | 0 | 0 | 59 | 321 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 191 | 33 | 0 | 0 | 0 | | 670 |
| 17:30:00 | 43 | 0 | 51 | 0 | 0 | 0 | 52 | 258 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 217 | 23 | 0 | 0 | 0 | | 644 |
| 17:45:00 | 26 | 0 | 50 | 0 | 0 | 0 | 53 | 230 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 209 | 33 | 0 | 0 | 0 | | 601 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/4/2023 0:00
End Time 2/4/2023 23:59
Location Maple Road and North Bailey Avenue
Latitude ar 42.9908697,-78.81465235
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00:00 | 39 | 100 | 63 | 0 | 0 | 0 | 68 | 152 | 51 | 0 | 0 | 0 | 34 | 75 | 24 | 0 | 0 | 0 | 16 | 125 | 20 | 0 | 0 | 0 | 767 |
| 12:15:00 | 31 | 84 | 70 | 1 | 0 | 0 | 56 | 183 | 46 | 0 | 0 | 0 | 25 | 84 | 22 | 0 | 0 | 0 | 8 | 136 | 23 | 0 | 0 | 0 | 769 |
| 12:30:00 | 24 | 90 | 71 | 0 | 0 | 0 | 74 | 145 | 47 | 0 | 0 | 0 | 29 | 71 | 30 | 0 | 0 | 0 | 8 | 114 | 17 | 0 | 0 | 0 | 720 |
| 12:45:00 | 36 | 98 | 70 | 0 | 0 | 0 | 87 | 166 | 47 | 0 | 0 | 0 | 41 | 70 | 22 | 0 | 0 | 0 | 22 | 136 | 27 | 0 | 0 | 0 | 822 |
| 13:00:00 | 30 | 94 | 64 | 0 | 0 | 0 | 66 | 146 | 49 | 0 | 0 | 0 | 26 | 89 | 20 | 0 | 0 | 0 | 17 | 135 | 24 | 0 | 0 | 0 | 760 |
| 13:15:00 | 40 | 97 | 80 | 0 | 0 | 0 | 66 | 164 | 45 | 0 | 0 | 0 | 41 | 72 | 31 | 0 | 0 | 0 | 11 | 129 | 24 | 0 | 0 | 0 | 800 |
| 13:30:00 | 30 | 94 | 65 | 0 | 0 | 0 | 52 | 167 | 46 | 0 | 0 | 0 | 39 | 82 | 26 | 0 | 0 | 0 | 15 | 141 | 29 | 0 | 0 | 0 | 786 |
| 13:45:00 | 24 | 89 | 84 | 1 | 0 | 0 | 77 | 163 | 49 | 0 | 0 | 0 | 34 | 79 | 33 | 0 | 0 | 0 | 23 | 120 | 24 | 0 | 0 | 0 | 800 |
| 14:00:00 | 50 | 99 | 68 | 0 | 0 | 0 | 67 | 170 | 61 | 0 | 0 | 0 | 33 | 83 | 24 | 0 | 0 | 0 | 14 | 115 | 29 | 0 | 0 | 0 | 813 |
| 14:15:00 | 35 | 114 | 73 | 0 | 0 | 0 | 63 | 166 | 52 | 0 | 0 | 0 | 34 | 87 | 25 | 0 | 0 | 0 | 21 | 114 | 31 | 0 | 0 | 0 | 815 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.98589 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | 52 | 102 | 82 | 0 | 0 | 0 | 87 | 164 | 48 | 0 | 0 | 0 | 34 | 66 | 28 | 0 | 0 | 0 | 11 | 123 | 17 | 0 | 0 | 0 | 814 |
| 14:45:00 | 48 | 108 | 74 | 0 | 0 | 0 | 66 | 131 | 47 | 0 | 0 | 0 | 39 | 79 | 18 | 0 | 0 | 0 | 17 | 120 | 41 | 0 | 0 | 0 | 788 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/2/2023 0:00
End Time 2/2/2023 23:59
Location Maple Road and North Bailey Avenue
Latitude ar 42.9908697,-78.81465235
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 3:00 PM | 29 | 77 | 65 | 0 | 0 | 0 | 50 | 146 | 39 | 0 | 0 | 0 | 34 | 60 | 13 | 0 | 0 | 0 | 10 | 136 | 19 | 0 | 0 | 0 | 678 |
| 3:15 PM | 27 | 71 | 75 | 0 | 0 | 0 | 57 | 170 | 53 | 0 | 0 | 0 | 33 | 64 | 16 | 0 | 0 | 0 | 21 | 123 | 17 | 0 | 0 | 0 | 727 |
| 3:30 PM | 27 | 59 | 61 | 0 | 0 | 0 | 65 | 183 | 46 | 0 | 0 | 0 | 23 | 58 | 21 | 0 | 0 | 0 | 15 | 119 | 17 | 0 | 0 | 0 | 694 |
| 3:45 PM | 25 | 76 | 68 | 0 | 0 | 0 | 60 | 190 | 39 | 0 | 0 | 0 | 34 | 83 | 19 | 0 | 0 | 0 | 19 | 105 | 24 | 0 | 0 | 0 | 742 |
| 4:00 PM | 25 | 97 | 59 | 0 | 0 | 0 | 72 | 208 | 58 | 0 | 0 | 0 | 40 | 77 | 26 | 0 | 0 | 0 | 18 | 122 | 17 | 0 | 0 | 0 | 819 |
| 4:15 PM | 28 | 75 | 78 | 0 | 0 | 0 | 56 | 186 | 45 | 0 | 0 | 0 | 25 | 86 | 25 | 0 | 0 | 0 | 11 | 127 | 19 | 0 | 0 | 0 | 761 |
| 4:30 PM | 33 | 90 | 72 | 0 | 0 | 0 | 57 | 206 | 48 | 0 | 0 | 0 | 35 | 97 | 20 | 0 | 0 | 0 | 12 | 137 | 16 | 0 | 0 | 0 | 823 |
| 4:45 PM | 23 | 94 | 68 | 0 | 0 | 0 | 55 | 191 | 43 | 0 | 0 | 0 | 34 | 92 | 16 | 0 | 0 | 0 | 8 | 146 | 16 | 0 | 0 | 0 | 786 |
| 5:00 PM | 29 | 86 | 63 | 0 | 0 | 0 | 65 | 236 | 54 | 0 | 0 | 0 | 29 | 86 | 12 | 0 | 0 | 0 | 12 | 119 | 20 | 0 | 0 | 0 | 811 |
| 5:15 PM | 32 | 90 | 73 | 0 | 0 | 0 | 73 | 210 | 65 | 0 | 0 | 0 | 40 | 78 | 21 | 0 | 0 | 0 | 12 | 116 | 18 | 0 | 0 | 0 | 828 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.966282 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 17:30:00 | 30 | 86 | 65 | 1 | 0 | 0 | 64 | 185 | 51 | 0 | 0 | 0 | 38 | 76 | 22 | 0 | 0 | 0 | 11 | 136 | 22 | 0 | 0 | 0 | 787 |
| 17:45:00 | 32 | 95 | 66 | 0 | 0 | 0 | 58 | 165 | 45 | 0 | 0 | 0 | 50 | 61 | 22 | 0 | 0 | 0 | 5 | 140 | 18 | 0 | 0 | 0 | 757 |

Summary

| | |
|---|---|
| Bin Size | 15 minutes |
| Aggregation Metho | 100% |
| Time Zone | America/New_York |
| Start Time | 10/22/2022 0:00 |
| End Time | 10/22/2022 23:59 |
| Location | 05-53-179 Rt 62 @ Maple Rd |
| Latitude and Longi | 42.99092677,-78.82255213 |

All Vehicles

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00:00 | 20 | 201 | 59 | 0 | 0 | 0 | 82 | 72 | 69 | 3 | 0 | 0 | 65 | 231 | 12 | 7 | 0 | 0 | 5 | 77 | 36 | 0 | 0 | 0 | 939 |
| 12:15:00 | 24 | 186 | 74 | 3 | 0 | 0 | 77 | 80 | 71 | 0 | 0 | 0 | 50 | 221 | 12 | 0 | 0 | 0 | 12 | 98 | 32 | 0 | 0 | 0 | 940 |
| 12:30:00 | 17 | 226 | 68 | 1 | 0 | 0 | 59 | 68 | 66 | 2 | 0 | 0 | 80 | 298 | 12 | 4 | 0 | 0 | 13 | 76 | 49 | 0 | 0 | 0 | 1039 |
| 12:45:00 | 21 | 184 | 90 | 3 | 0 | 0 | 88 | 86 | 84 | 1 | 0 | 0 | 62 | 218 | 11 | 4 | 0 | 0 | 6 | 92 | 34 | 0 | 0 | 0 | 984 |
| 13:00:00 | 21 | 189 | 62 | 1 | 0 | 0 | 76 | 80 | 52 | 1 | 0 | 0 | 68 | 235 | 11 | 3 | 0 | 0 | 9 | 81 | 35 | 0 | 0 | 0 | 924 |
| 13:15:00 | 22 | 217 | 72 | 1 | 0 | 0 | 53 | 87 | 81 | 0 | 0 | 0 | 61 | 243 | 14 | 4 | 0 | 0 | 8 | 71 | 39 | 0 | 0 | 0 | 973 |
| 13:30:00 | 26 | 202 | 59 | 0 | 0 | 0 | 63 | 77 | 67 | 0 | 0 | 0 | 71 | 244 | 11 | 2 | 0 | 0 | 13 | 71 | 42 | 0 | 0 | 0 | 948 |
| 13:45:00 | 29 | 238 | 73 | 1 | 0 | 0 | 58 | 82 | 63 | 0 | 0 | 0 | 61 | 249 | 9 | 7 | 0 | 0 | 7 | 82 | 30 | 0 | 0 | 0 | 989 |
| 14:00:00 | 23 | 170 | 57 | 1 | 0 | 0 | 60 | 75 | 76 | 0 | 0 | 0 | 55 | 221 | 10 | 2 | 0 | 0 | 4 | 68 | 41 | 0 | 0 | 0 | 863 |
| 14:15:00 | 22 | 194 | 81 | 1 | 0 | 0 | 69 | 73 | 56 | 1 | 0 | 0 | 57 | 280 | 16 | 4 | 0 | 0 | 22 | 65 | 36 | 1 | 0 | 0 | 978 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.955005 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | 26 | 209 | 70 | 0 | 0 | 0 | 54 | 87 | 60 | 0 | 0 | 0 | 55 | 195 | 15 | 1 | 0 | 0 | 3 | 63 | 30 | 0 | 0 | 0 | 868 |
| 14:45:00 | 24 | 176 | 60 | 0 | 0 | 0 | 68 | 79 | 76 | 0 | 0 | 0 | 73 | 228 | 11 | 0 | 0 | 0 | 11 | 66 | 33 | 1 | 0 | 0 | 906 |

Summary

| | |
|---|---|
| Bin Size | 15 minutes |
| Aggregatio | 100% |
| Time Zone | America/New_York |
| Start Time | 10/20/2022 0:00 |
| End Time | 10/20/2022 23:59 |
| Location | 05-53-179 Rt 62 @ Maple Rd |
| Latitude ar | 42.99092677,-78.82255213 |

All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 3:00 PM | 26 | 178 | 52 | 1 | 0 | 0 | 40 | 70 | 51 | 0 | 0 | 0 | 42 | 209 | 12 | 2 | 0 | 0 | 10 | 50 | 22 | 0 | 0 | 0 | 765 |
| 3:15 PM | 19 | 146 | 46 | 1 | 0 | 0 | 61 | 87 | 63 | 0 | 0 | 0 | 50 | 149 | 11 | 2 | 0 | 0 | 15 | 65 | 31 | 0 | 0 | 0 | 746 |
| 3:30 PM | 27 | 196 | 46 | 0 | 0 | 0 | 55 | 72 | 79 | 0 | 0 | 0 | 65 | 194 | 11 | 2 | 0 | 0 | 9 | 66 | 28 | 0 | 0 | 0 | 850 |
| 3:45 PM | 35 | 164 | 44 | 1 | 0 | 0 | 53 | 92 | 71 | 1 | 0 | 0 | 47 | 217 | 14 | 6 | 0 | 0 | 10 | 65 | 23 | 0 | 0 | 0 | 843 |
| 4:00 PM | 16 | 185 | 51 | 1 | 0 | 0 | 69 | 79 | 82 | 0 | 0 | 0 | 49 | 201 | 13 | 7 | 0 | 0 | 14 | 61 | 43 | 0 | 0 | 0 | 871 |
| 4:15 PM | 27 | 187 | 36 | 0 | 0 | 0 | 61 | 95 | 75 | 0 | 0 | 0 | 51 | 238 | 11 | 4 | 0 | 0 | 7 | 63 | 28 | 0 | 0 | 0 | 883 |
| 4:30 PM | 29 | 184 | 66 | 1 | 0 | 0 | 62 | 100 | 65 | 0 | 0 | 0 | 60 | 196 | 22 | 2 | 0 | 0 | 10 | 69 | 31 | 0 | 0 | 0 | 897 |
| 4:45 PM | 23 | 182 | 61 | 0 | 0 | 0 | 62 | 101 | 67 | 0 | 0 | 0 | 46 | 211 | 16 | 0 | 0 | 0 | 11 | 70 | 40 | 0 | 0 | 0 | 890 |
| 5:00 PM | 25 | 189 | 54 | 0 | 0 | 0 | 58 | 92 | 74 | 0 | 0 | 0 | 55 | 217 | 7 | 6 | 0 | 0 | 10 | 68 | 32 | 0 | 0 | 0 | 887 |
| 5:15 PM | 28 | 195 | 67 | 0 | 0 | 0 | 60 | 86 | 71 | 1 | 0 | 0 | 65 | 201 | 14 | 6 | 0 | 0 | 13 | 64 | 37 | 0 | 0 | 0 | 908 |
| 5:30 PM | 27 | 166 | 61 | 1 | 0 | 0 | 62 | 104 | 77 | 0 | 0 | 0 | 68 | 209 | 9 | 5 | 0 | 0 | 10 | 65 | 36 | 0 | 0 | 0 | 900 |
| 5:45 PM | 34 | 164 | 56 | 2 | 0 | 0 | 61 | 73 | 60 | 0 | 0 | 0 | 54 | 220 | 17 | 4 | 0 | 0 | 8 | 72 | 36 | 1 | 0 | 0 | 862 |

Summary

| | |
|---|---|
| Bin Size | 15 minutes |
| Aggregation M | Median |
| Time Zone | America/New_York |
| Start Time | 2/4/2023 0:00 |
| End Time | 2/4/2023 23:59 |
| Location | 05-53-283 Rt 62 @ Glenalby & Romney |
| Latitude and L | 42.99749213,-78.82245963 |

All Vehicles

| Entry | North | | | | | | East | | | | | | South | | | | | | West | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Direction | Southbound | | | | | | Westbound | | | | | | Northbound | | | | | | Eastbound | | | | | | |
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00 PM | 19 | 197 | 59 | 0 | 0 | 0 | 38 | 30 | 33 | 0 | 0 | 0 | 33 | 186 | 5 | 1 | 0 | 0 | 11 | 18 | 13 | 0 | 0 | 0 | 643 |
| 12:15 PM | 9 | 245 | 57 | 0 | 0 | 0 | 36 | 19 | 42 | 0 | 0 | 0 | 25 | 193 | 4 | 2 | 0 | 0 | 1 | 23 | 10 | 0 | 0 | 0 | 666 |
| 12:30 PM | 14 | 210 | 58 | 0 | 0 | 0 | 51 | 12 | 37 | 0 | 0 | 0 | 33 | 214 | 9 | 1 | 0 | 0 | 8 | 24 | 8 | 0 | 0 | 0 | 679 |
| 12:45 PM | 10 | 200 | 58 | 0 | 0 | 0 | 54 | 20 | 45 | 0 | 0 | 0 | 39 | 180 | 8 | 5 | 0 | 0 | 9 | 42 | 11 | 0 | 0 | 0 | 681 |
| 1:00 PM | 7 | 223 | 59 | 0 | 0 | 0 | 37 | 22 | 41 | 0 | 0 | 0 | 35 | 183 | 14 | 3 | 0 | 0 | 11 | 29 | 8 | 0 | 0 | 0 | 672 |
| 1:15 PM | 11 | 220 | 56 | 0 | 0 | 0 | 45 | 19 | 41 | 0 | 0 | 0 | 21 | 196 | 10 | 0 | 0 | 0 | 4 | 27 | 9 | 0 | 0 | 0 | 659 |
| 1:30 PM | 13 | 254 | 53 | 0 | 0 | 0 | 49 | 21 | 37 | 0 | 0 | 0 | 33 | 191 | 11 | 2 | 0 | 0 | 8 | 26 | 14 | 0 | 0 | 0 | 712 |
| 1:45 PM | 9 | 182 | 50 | 1 | 0 | 0 | 47 | 24 | 49 | 0 | 0 | 0 | 36 | 200 | 18 | 4 | 0 | 0 | 6 | 22 | 9 | 0 | 0 | 0 | 657 |
| 2:00 PM | 6 | 244 | 51 | 0 | 0 | 0 | 50 | 17 | 50 | 0 | 0 | 0 | 33 | 216 | 8 | 0 | 0 | 0 | 7 | 18 | 8 | 0 | 0 | 0 | 708 |
| 2:15 PM | 8 | 186 | 47 | 0 | 0 | 0 | 31 | 25 | 44 | 0 | 0 | 0 | 46 | 198 | 8 | 0 | 0 | 0 | 9 | 20 | 10 | 0 | 0 | 0 | 632 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.951194 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 2:30 PM | 8 | 196 | 51 | 1 | 0 | 0 | 47 | 25 | 55 | 0 | 0 | 0 | 47 | 166 | 13 | 2 | 0 | 0 | 7 | 32 | 9 | 0 | 0 | 0 | 659 |
| 2:45 PM | 8 | 222 | 57 | 0 | 0 | 0 | 44 | 24 | 59 | 0 | 0 | 0 | 43 | 205 | 13 | 1 | 0 | 0 | 7 | 23 | 6 | 0 | 0 | 0 | 712 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/2/2023 0:00
End Time 2/2/2023 23:59
Location 05-53-283 Rt 62 @ Glenalby & Romney
Latitude ar 42.99749213,-78.82245963


All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 15:00:00 | 15 | 165 | 21 | 0 | 0 | 0 | 23 | 20 | 40 | 0 | 0 | 0 | 9 | 179 | 2 | 3 | 0 | 0 | 11 | 22 | 6 | 0 | 0 | 0 | 516 |
| 15:15:00 | 6 | 185 | 25 | 0 | 0 | 0 | 27 | 18 | 35 | 0 | 0 | 0 | 11 | 156 | 3 | 2 | 0 | 0 | 3 | 15 | 19 | 0 | 0 | 0 | 505 |
| 15:30:00 | 7 | 169 | 50 | 0 | 0 | 0 | 33 | 10 | 27 | 0 | 0 | 0 | 12 | 187 | 4 | 2 | 0 | 0 | 7 | 12 | 8 | 0 | 0 | 0 | 528 |
| 15:45:00 | 15 | 188 | 35 | 0 | 0 | 0 | 35 | 18 | 34 | 0 | 0 | 0 | 20 | 162 | 6 | 3 | 0 | 0 | 1 | 20 | 12 | 0 | 0 | 0 | 549 |
| 16:00:00 | 12 | 204 | 39 | 0 | 0 | 0 | 29 | 24 | 32 | 0 | 0 | 0 | 15 | 192 | 11 | 5 | 0 | 0 | 7 | 17 | 12 | 0 | 0 | 0 | 599 |
| 16:15:00 | 9 | 181 | 53 | 0 | 0 | 0 | 33 | 24 | 32 | 0 | 0 | 0 | 12 | 187 | 13 | 1 | 0 | 0 | 2 | 29 | 9 | 0 | 0 | 0 | 585 |
| 16:30:00 | 10 | 195 | 39 | 0 | 0 | 0 | 38 | 25 | 28 | 0 | 0 | 0 | 10 | 192 | 4 | 1 | 0 | 0 | 4 | 12 | 10 | 0 | 0 | 0 | 568 |
| 16:45:00 | 11 | 206 | 36 | 0 | 0 | 0 | 31 | 19 | 35 | 0 | 0 | 0 | 13 | 188 | 8 | 0 | 0 | 0 | 6 | 17 | 6 | 0 | 0 | 0 | 576 |
| 17:00:00 | 10 | 188 | 34 | 0 | 0 | 0 | 44 | 32 | 43 | 0 | 0 | 0 | 14 | 181 | 8 | 1 | 0 | 0 | 4 | 20 | 15 | 0 | 0 | 0 | 594 |
| 17:15:00 | 11 | 238 | 44 | 0 | 0 | 0 | 30 | 14 | 27 | 0 | 0 | 0 | 12 | 197 | 7 | 0 | 0 | 0 | 7 | 13 | 13 | 0 | 0 | 0 | 613 |
| 17:30:00 | 6 | 184 | 32 | 0 | 0 | 0 | 45 | 23 | 40 | 0 | 0 | 0 | 11 | 185 | 14 | 0 | 0 | 0 | 3 | 28 | 6 | 0 | 0 | 0 | 577 |
| 17:45:00 | 7 | 200 | 41 | 0 | 0 | 0 | 38 | 20 | 37 | 0 | 0 | 0 | 1 | 170 | 7 | 0 | 0 | 0 | 3 | 19 | 7 | 0 | 0 | 0 | 550 |

Summary
Bin Size 15 minutes
Aggregatio Median
Time Zone America/New_York
Start Time 2/4/2023 0:00
End Time 2/4/2023 23:59
Location North Bailey Avenue and Meyer Road
Latitude ar 42.99368334,-78.81459879
All Vehicles

| Entry Direction | North Southbound | | | | | | East Westbound | | | | | | South Northbound | | | | | | West Eastbound | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Start Time | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Right | Thru | Left | U-Turn | Peds CW | Peds CCW | Total |
| 12:00:00 | 22 | 185 | 14 | 0 | 0 | 0 | 30 | 4 | 0 | 0 | 0 | 0 | 5 | 151 | 9 | 0 | 0 | 0 | 11 | 8 | 14 | 0 | 0 | 0 | 453 |
| 12:15:00 | 6 | 171 | 15 | 0 | 0 | 0 | 29 | 5 | 0 | 0 | 0 | 0 | 3 | 158 | 6 | 0 | 0 | 0 | 11 | 8 | 12 | 0 | 0 | 0 | 424 |
| 12:30:00 | 15 | 176 | 11 | 0 | 0 | 0 | 30 | 4 | 0 | 0 | 0 | 0 | 6 | 158 | 7 | 0 | 0 | 0 | 14 | 10 | 24 | 0 | 0 | 0 | 455 |
| 12:45:00 | 10 | 191 | 11 | 0 | 0 | 0 | 29 | 4 | 3 | 0 | 0 | 0 | 2 | 165 | 4 | 0 | 0 | 0 | 16 | 7 | 17 | 0 | 0 | 0 | 459 |
| 13:00:00 | 15 | 182 | 12 | 0 | 0 | 0 | 30 | 1 | 1 | 0 | 0 | 0 | 3 | 170 | 7 | 0 | 0 | 0 | 12 | 9 | 11 | 0 | 0 | 0 | 453 |
| 13:15:00 | 22 | 193 | 17 | 0 | 0 | 0 | 33 | 3 | 3 | 0 | 0 | 0 | 2 | 168 | 6 | 0 | 0 | 0 | 18 | 6 | 18 | 0 | 0 | 0 | 489 |
| 13:30:00 | 14 | 195 | 20 | 0 | 0 | 0 | 28 | 2 | 1 | 0 | 0 | 0 | 2 | 158 | 7 | 0 | 0 | 0 | 19 | 9 | 25 | 0 | 0 | 0 | 480 |
| 13:45:00 | 13 | 165 | 7 | 0 | 0 | 0 | 31 | 3 | 1 | 0 | 0 | 0 | 3 | 162 | 7 | 0 | 0 | 0 | 13 | 7 | 20 | 0 | 0 | 0 | 432 |
| 14:00:00 | 12 | 214 | 13 | 0 | 0 | 0 | 27 | 5 | 2 | 0 | 0 | 0 | 2 | 168 | 6 | 0 | 0 | 0 | 13 | 5 | 15 | 0 | 0 | 0 | 482 |
| 14:15:00 | 19 | 202 | 18 | 0 | 0 | 0 | 23 | 1 | 3 | 0 | 0 | 0 | 3 | 164 | 5 | 0 | 0 | 0 | 15 | 3 | 15 | 0 | 0 | 0 | 471 |
| **PHF** | | | | | | | | | | | | | | | | | | | | | | | | | 0.967324 |
| **% HV** | | | | | | | | | | | | | | | | | | | | | | | | | 0% |
| 14:30:00 | 10 | 214 | 14 | 0 | 0 | 0 | 30 | 1 | 1 | 0 | 0 | 0 | 2 | 162 | 6 | 0 | 0 | 0 | 18 | 7 | 19 | 0 | 0 | 0 | 484 |
| 14:45:00 | 18 | 215 | 19 | 0 | 0 | 0 | 31 | 6 | 1 | 0 | 0 | 0 | 6 | 162 | 5 | 0 | 0 | 0 | 15 | 5 | 19 | 0 | 0 | 0 | 502 |

# Appendix D – Synchro Reports




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 4 | 0 | 9 | 478 | 11 | 679 | 0 | 1196 | 393 | 0 | 1378 | 0 |
| Future Volume (vph) | 4 | 0 | 9 | 478 | 11 | 679 | 0 | 1196 | 393 | 0 | 1378 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 250 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 0 | | 1 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 0.95 | 0.91 | 0.95 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | 0.884 | 0.850 | | | 0.850 | | | |
| Flt Protected | 0.950 | | | 0.950 | 0.990 | | | | | | | |
| Satd. Flow (prot) | 1787 | 0 | 1599 | 1698 | 1498 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Flt Permitted | 0.189 | | | 0.950 | 0.990 | | | | | | | |
| Satd. Flow (perm) | 356 | 0 | 1599 | 1698 | 1498 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 28 | | 58 | 58 | | | 409 | | | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 894 | | | 646 | | | 950 | | | 1161 | |
| Travel Time (s) | | 20.3 | | | 14.7 | | | 16.2 | | | 19.8 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 4 | 0 | 9 | 498 | 11 | 707 | 0 | 1246 | 409 | 0 | 1435 | 0 |
| Shared Lane Traffic (%) | | | | 16% | | 44% | | | | | | |
| Lane Group Flow (vph) | 4 | 0 | 9 | 418 | 402 | 396 | 0 | 1246 | 409 | 0 | 1435 | 0 |
| Turn Type | D.Pm | | Perm | Perm | NA | Perm | | NA | Perm | | NA | |
| Protected Phases | | | | | 3 | | | 1 | | | 1 | |
| Permitted Phases | 3 | | 3 | 3 | | 3 | | | 1 | | | |
| Detector Phase | 3 | | 3 | 3 | 3 | 3 | | 1 | 1 | | 1 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | | 6.0 | 6.0 | 6.0 | 6.0 | | 20.0 | 20.0 | | 20.0 | |
| Minimum Split (s) | 13.3 | | 13.3 | 13.3 | 13.3 | 13.3 | | 34.6 | 34.6 | | 34.6 | |
| Total Split (s) | 70.0 | | 70.0 | 70.0 | 70.0 | 70.0 | | 110.0 | 110.0 | | 110.0 | |
| Total Split (%) | 38.9% | | 38.9% | 38.9% | 38.9% | 38.9% | | 61.1% | 61.1% | | 61.1% | |
| Maximum Green (s) | 62.7 | | 62.7 | 62.7 | 62.7 | 62.7 | | 102.4 | 102.4 | | 102.4 | |
| Yellow Time (s) | 4.3 | | 4.3 | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 | | 4.3 | |
| All-Red Time (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.3 | 3.3 | | 3.3 | |
| Lost Time Adjust (s) | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |
| Total Lost Time (s) | 7.3 | | 7.3 | 7.3 | 7.3 | 7.3 | | 7.6 | 7.6 | | 7.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | |
| Recall Mode | None | | None | None | None | None | | C-Max | C-Max | | C-Max | |
| Walk Time (s) | | | | | | | | 7.0 | 7.0 | | 7.0 | |
| Flash Don't Walk (s) | | | | | | | | 20.0 | 20.0 | | 20.0 | |
| Pedestrian Calls (#/hr) | | | | | | | | 0 | 0 | | 0 | |
| Act Effct Green (s) | 53.8 | | 53.8 | 53.8 | 53.8 | 53.8 | | 111.3 | 111.3 | | 111.3 | |
| Actuated g/C Ratio | 0.30 | | 0.30 | 0.30 | 0.30 | 0.30 | | 0.62 | 0.62 | | 0.62 | |
| v/c Ratio | 0.04 | | 0.02 | 0.82 | 0.82 | 0.80 | | 0.39 | 0.36 | | 0.45 | |
| Control Delay (s/veh) | 41.3 | | 0.1 | 72.1 | 63.7 | 61.4 | | 17.5 | 3.0 | | 19.6 | |
| Queue Delay | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 41.3 | | 0.1 | 72.1 | 63.7 | 61.4 | | 17.5 | 3.0 | | 19.6 | |
| LOS | D | | A | E | E | E | | B | A | | B | |
| Approach Delay (s/veh) | | 12.8 | | | 65.8 | | | 14.0 | | | 19.6 | |
| Approach LOS | | B | | | E | | | B | | | B | |
| Queue Length 50th (ft) | 3 | | 0 | 482 | 423 | 393 | | 265 | 11 | | 324 | |
| Queue Length 95th (ft) | 14 | | 0 | 594 | 550 | 511 | | 340 | 51 | | 402 | |
| Internal Link Dist (ft) | | 814 | | | 566 | | | 870 | | | 1081 | |
| Turn Bay Length (ft) | | | | | | | | | 250 | | | |
| Base Capacity (vph) | 124 | | 575 | 591 | 559 | 566 | | 3176 | 1144 | | 3176 | |
| Starvation Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Spillback Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Storage Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Reduced v/c Ratio | 0.03 | | 0.02 | 0.71 | 0.72 | 0.70 | | 0.39 | 0.36 | | 0.45 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 60 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.82 | | | |
| Intersection Signal Delay (s/veh): 30.4 | | Intersection LOS: C | |
| Intersection Capacity Utilization 70.6% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 1: Niagara Falls Blvd & I-290 WB Ramp





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 0 | 422 | 0 | 0 | 386 | 0 | 1184 | 0 | 0 | 1214 | 483 |
| Future Volume (vph) | 0 | 0 | 422 | 0 | 0 | 386 | 0 | 1184 | 0 | 0 | 1214 | 483 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 200 |
| Storage Lanes | 0 | | 2 | 0 | | 1 | 0 | | 0 | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 0.88 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | | 0.865 | | | | | | 0.850 |
| Flt Protected | | | | | | | | | | | | |
| Satd. Flow (prot) | 0 | 0 | 2814 | 0 | 0 | 1611 | 0 | 5136 | 0 | 0 | 5136 | 1599 |
| Flt Permitted | | | | | | | | | | | | |
| Satd. Flow (perm) | 0 | 0 | 2814 | 0 | 0 | 1611 | 0 | 5136 | 0 | 0 | 5136 | 1599 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 92 | | | | | | | | | 454 |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 932 | | | 703 | | | 600 | | | 950 | |
| Travel Time (s) | | 21.2 | | | 16.0 | | | 10.2 | | | 16.2 | |
| Peak Hour Factor | 0.94 | 0.92 | 0.94 | 0.92 | 0.92 | 0.92 | 0.94 | 0.94 | 0.92 | 0.92 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 2% | 1% | 2% | 2% | 2% | 1% | 1% | 2% | 2% | 1% | 1% |
| Adj. Flow (vph) | 0 | 0 | 449 | 0 | 0 | 420 | 0 | 1260 | 0 | 0 | 1291 | 514 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 0 | 449 | 0 | 0 | 420 | 0 | 1260 | 0 | 0 | 1291 | 514 |
| Turn Type | | | Prot | | | Perm | | NA | | | NA | Perm |
| Protected Phases | | | 3 | | | | | 1 3 | | | 1 | |
| Permitted Phases | | | | | | 1 3 | | | | | | 1 |
| Detector Phase | | | 3 | | | 1 3 | | | | | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | | 15.0 | | | | | | | | 10.0 | 10.0 |
| Minimum Split (s) | | | 22.1 | | | | | | | | 26.5 | 26.5 |
| Total Split (s) | | | 70.0 | | | | | | | | 110.0 | 110.0 |
| Total Split (%) | | | 38.9% | | | | | | | | 61.1% | 61.1% |
| Maximum Green (s) | | | 62.9 | | | | | | | | 102.5 | 102.5 |
| Yellow Time (s) | | | 5.1 | | | | | | | | 4.3 | 4.3 |
| All-Red Time (s) | | | 2.0 | | | | | | | | 3.2 | 3.2 |
| Lost Time Adjust (s) | | | 0.0 | | | | | | | | 0.0 | 0.0 |
| Total Lost Time (s) | | | 7.1 | | | | | | | | 7.5 | 7.5 |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | | 3.0 | | | | | | | | 3.0 | 3.0 |
| Recall Mode | | | None | | | | | | | | C-Max | C-Max |
| Walk Time (s) | | | | | | | | | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | | | | | | | | | | 12.0 | 12.0 |
| Pedestrian Calls (#/hr) | | | | | | | | | | | 0 | 0 |
| Act Effct Green (s) | | | 31.4 | | | 180.0 | | 180.0 | | | 134.0 | 134.0 |
| Actuated g/C Ratio | | | 0.17 | | | 1.00 | | 1.00 | | | 0.74 | 0.74 |
| v/c Ratio | | | 0.79 | | | 0.26 | | 0.25 | | | 0.34 | 0.39 |
| Control Delay (s/veh) | | | 66.3 | | | 0.4 | | 0.1 | | | 7.5 | 1.5 |
| Queue Delay | | | 0.0 | | | 0.0 | | 0.0 | | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | | 66.3 | | | 0.4 | | 0.1 | | | 7.5 | 1.5 |
| LOS | | | E | | | A | | A | | | A | A |
| Approach Delay (s/veh) | | 66.3 | | | 0.4 | | | 0.1 | | | 5.8 | |
| Approach LOS | | E | | | A | | | A | | | A | |
| Queue Length 50th (ft) | | | 236 | | | 0 | | 0 | | | 137 | 18 |
| Queue Length 95th (ft) | | | 292 | | | 0 | | 0 | | | 154 | 13 |
| Internal Link Dist (ft) | | 852 | | | 623 | | | 520 | | | 870 | |
| Turn Bay Length (ft) | | | | | | | | | | | | 200 |
| Base Capacity (vph) | | | 1043 | | | 1611 | | 5136 | | | 3822 | 1306 |
| Starvation Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Spillback Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Storage Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Reduced v/c Ratio | | | 0.43 | | | 0.26 | | 0.25 | | | 0.34 | 0.39 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.79 | | | |
| Intersection Signal Delay (s/veh): 10.3 | | Intersection LOS: B | |
| Intersection Capacity Utilization 59.3% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 2: Niagara Falls Blvd & I-290 EB Ramp






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 123 | 64 | 15 | 31 | 57 | 718 | 25 | 1047 | 8 | 607 | 1084 | 104 |
| Future Volume (vph) | 123 | 64 | 15 | 31 | 57 | 718 | 25 | 1047 | 8 | 607 | 1084 | 104 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 100 | | 0 | 0 | | 225 | 130 | | 0 | 435 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 2 | 1 | | 0 | 2 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.88 | 1.00 | 0.91 | 0.91 | 0.97 | 0.91 | 0.91 |
| Frt | | 0.972 | | | | 0.850 | | 0.999 | | | 0.987 | |
| Flt Protected | 0.950 | | | | 0.983 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 1829 | 0 | 0 | 1849 | 2814 | 1787 | 5131 | 0 | 3467 | 5069 | 0 |
| Flt Permitted | 0.669 | | | | 0.851 | | 0.950 | | | 0.950 | | |
| Satd. Flow (perm) | 1259 | 1829 | 0 | 0 | 1601 | 2814 | 1787 | 5131 | 0 | 3467 | 5069 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 6 | | | | 198 | | 1 | | | 14 | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 853 | | | 2284 | | | 672 | | | 600 | |
| Travel Time (s) | | 19.4 | | | 51.9 | | | 11.5 | | | 10.2 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 127 | 66 | 15 | 32 | 59 | 740 | 26 | 1079 | 8 | 626 | 1118 | 107 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 127 | 81 | 0 | 0 | 91 | 740 | 26 | 1087 | 0 | 626 | 1225 | 0 |
| Turn Type | D.P+P | NA | | Perm | NA | pm+ov | Prot | NA | | Prot | NA | |
| Protected Phases | 7 | 7 8 | | | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 8 | | | 8 | | 8 | | | | | | |
| Detector Phase | 7 | 7 8 | | 8 | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | | | 4.1 | 4.1 | 5.0 | 5.0 | 20.0 | | 5.0 | 20.0 | |
| Minimum Split (s) | 12.7 | | | 12.3 | 12.3 | 12.5 | 11.6 | 32.6 | | 12.5 | 32.6 | |
| Total Split (s) | 25.0 | | | 30.0 | 30.0 | 60.0 | 20.0 | 65.0 | | 60.0 | 105.0 | |
| Total Split (%) | 13.9% | | | 16.7% | 16.7% | 33.3% | 11.1% | 36.1% | | 33.3% | 58.3% | |
| Maximum Green (s) | 17.5 | | | 21.8 | 21.8 | 52.5 | 13.7 | 58.5 | | 52.5 | 98.5 | |
| Yellow Time (s) | 3.6 | | | 4.3 | 4.3 | 3.6 | 4.3 | 4.3 | | 3.6 | 4.3 | |
| All-Red Time (s) | 3.9 | | | 3.9 | 3.9 | 3.9 | 2.0 | 2.2 | | 3.9 | 2.2 | |
| Lost Time Adjust (s) | 0.0 | | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 7.5 | | | | 8.2 | 7.5 | 6.3 | 6.5 | | 7.5 | 6.5 | |
| Lead/Lag | Lead | | | Lag | Lag | Lead | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 2.0 | | | 2.0 | 2.0 | 2.4 | 2.4 | 2.4 | | 2.4 | 2.4 | |
| Recall Mode | None | | | None | None | None | None | C-Max | | None | Max | |
| Walk Time (s) | | | | | | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | | | | | | | 19.0 | | | 19.0 | |
| Pedestrian Calls (#/hr) | | | | | | | | 0 | | | 0 | |
| Act Effct Green (s) | 30.0 | 37.5 | | | 14.6 | 61.9 | 7.5 | 81.9 | | 39.1 | 119.5 | |
| Actuated g/C Ratio | 0.17 | 0.21 | | | 0.08 | 0.34 | 0.04 | 0.46 | | 0.22 | 0.66 | |
| v/c Ratio | 0.50 | 0.21 | | | 0.71 | 0.67 | 0.35 | 0.47 | | 0.83 | 0.36 | |
| Control Delay (s/veh) | 66.4 | 53.8 | | | 107.2 | 38.3 | 96.0 | 12.4 | | 83.6 | 9.0 | |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.1 | 0.1 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 66.4 | 53.8 | | | 107.2 | 38.3 | 96.0 | 12.4 | | 83.6 | 9.1 | |
| LOS | E | D | | | F | D | F | B | | F | A | |
| Approach Delay (s/veh) | | 61.5 | | | 45.9 | | | 14.3 | | | 34.3 | |
| Approach LOS | | E | | | D | | | B | | | C | |
| Queue Length 50th (ft) | 129 | 74 | | | 107 | 318 | 32 | 87 | | 345 | 180 | |
| Queue Length 95th (ft) | 187 | 120 | | | 170 | 351 | m59 | 85 | | 371 | 204 | |
| Internal Link Dist (ft) | | 773 | | | 2204 | | | 592 | | | 520 | |
| Turn Bay Length (ft) | 100 | | | | | 225 | 130 | | | 435 | | |
| Base Capacity (vph) | 280 | 426 | | | 193 | 1292 | 136 | 2333 | | 1011 | 3369 | |
| Starvation Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 21 | 973 | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.45 | 0.19 | | | 0.47 | 0.57 | 0.19 | 0.47 | | 0.63 | 0.51 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 2:NBT, Start of Yellow | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.83 | | | |
| Intersection Signal Delay (s/veh): 32.6 | | Intersection LOS: C | |
| Intersection Capacity Utilization 70.3% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 3: Niagara Falls Blvd & Koenig Rd/Ridge Lea Rd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 14 | 9 | 10 | 113 | 7 | 197 | 5 | 8 | 931 | 108 | 1 | 157 |
| Future Volume (vph) | 14 | 9 | 10 | 113 | 7 | 197 | 5 | 8 | 931 | 108 | 1 | 157 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 0 | | 160 | | 110 | | 170 | | 300 |
| Storage Lanes | 0 | | 1 | 0 | | 1 | | 1 | | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | | 0.850 | | | | 0.850 | | |
| Flt Protected | | 0.971 | | | 0.955 | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1827 | 1599 | 0 | 1797 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Flt Permitted | | 0.318 | | | 0.720 | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 598 | 1599 | 0 | 1354 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 127 | | | 210 | | | | 127 | | |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | |
| Link Distance (ft) | | 671 | | | 580 | | | | 758 | | | |
| Travel Time (s) | | 15.3 | | | 13.2 | | | | 12.9 | | | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 15 | 10 | 11 | 120 | 7 | 210 | 5 | 9 | 990 | 115 | 1 | 167 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 25 | 11 | 0 | 127 | 210 | 0 | 14 | 990 | 115 | 0 | 168 |
| Turn Type | Perm | NA | Perm | Perm | NA | Perm | Prot | Prot | NA | Perm | Prot | Prot |
| Protected Phases | | 3 | | | 4 | | 5 | 5 | 2 | | 1 | 1 |
| Permitted Phases | 3 | | 3 | 4 | | 4 | | | | 2 | | |
| Detector Phase | 3 | 3 | 3 | 4 | 4 | 4 | 5 | 5 | 2 | 2 | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 3.0 | 6.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 3.0 |
| Minimum Split (s) | 23.8 | 23.8 | 23.8 | 24.6 | 24.6 | 24.6 | 10.8 | 10.8 | 23.8 | 23.8 | 10.8 | 10.8 |
| Total Split (s) | 40.0 | 40.0 | 40.0 | 45.0 | 45.0 | 45.0 | 20.0 | 20.0 | 65.0 | 65.0 | 30.0 | 30.0 |
| Total Split (%) | 22.2% | 22.2% | 22.2% | 25.0% | 25.0% | 25.0% | 11.1% | 11.1% | 36.1% | 36.1% | 16.7% | 16.7% |
| Maximum Green (s) | 34.2 | 34.2 | 34.2 | 38.4 | 38.4 | 38.4 | 14.2 | 14.2 | 59.2 | 59.2 | 24.2 | 24.2 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | 3.2 | 3.2 | 3.2 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 1.9 | 1.9 | 1.9 | 3.4 | 3.4 | 3.4 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 5.8 | 5.8 | | 6.6 | 6.6 | | 5.8 | 5.8 | 5.8 | | 5.8 |
| Lead/Lag | Lead | Lead | Lead | Lag | Lag | Lag | Lead | Lead | Lag | Lag | Lead | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | Max | Max | Max | Max | Max | Max | None | None | C-Max | C-Max | Min | Min |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | | | 11.0 | 11.0 | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | | |
| Act Effct Green (s) | | 34.2 | 34.2 | | 38.4 | 38.4 | | 7.0 | 62.5 | 62.5 | | 20.9 |
| Actuated g/C Ratio | | 0.19 | 0.19 | | 0.21 | 0.21 | | 0.04 | 0.35 | 0.35 | | 0.12 |
| v/c Ratio | | 0.22 | 0.03 | | 0.44 | 0.42 | | 0.20 | 0.56 | 0.18 | | 0.81 |
| Control Delay (s/veh) | | 67.7 | 0.1 | | 67.1 | 9.0 | | 93.2 | 56.9 | 11.7 | | 94.3 |
| Queue Delay | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 872 | 22 |
| Future Volume (vph) | 872 | 22 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.996 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5115 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5115 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 2 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 672 | |
| Travel Time (s) | 11.5 | |
| Peak Hour Factor | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 928 | 23 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 951 | 0 |
| Turn Type | NA | |
| Protected Phases | 6 | |
| Permitted Phases | | |
| Detector Phase | 6 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 23.4 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 41.7% | |
| Maximum Green (s) | 69.6 | |
| Yellow Time (s) | 3.5 | |
| All-Red Time (s) | 1.9 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 5.4 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | C-Max | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 11.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 84.0 | |
| Actuated g/C Ratio | 0.47 | |
| v/c Ratio | 0.40 | |
| Control Delay (s/veh) | 16.7 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 67.7 | 0.1 | | 67.1 | 9.0 | | 93.2 | 56.9 | 11.7 | | 94.3 |
| LOS | | E | A | | E | A | | F | E | B | | F |
| Approach Delay (s/veh) | | 47.1 | | | 30.9 | | | | 52.7 | | | |
| Approach LOS | | D | | | C | | | | D | | | |
| Queue Length 50th (ft) | | 25 | 0 | | 132 | 0 | | 15 | 393 | 38 | | 180 |
| Queue Length 95th (ft) | | 60 | 0 | | 207 | 75 | | m40 | 480 | m107 | | 250 |
| Internal Link Dist (ft) | | 591 | | | 500 | | | | 678 | | | |
| Turn Bay Length (ft) | | | 25 | | | 160 | | 110 | | 170 | | 300 |
| Base Capacity (vph) | | 113 | 406 | | 288 | 506 | | 140 | 1782 | 638 | | 240 |
| Starvation Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.22 | 0.03 | | 0.44 | 0.42 | | 0.10 | 0.56 | 0.18 | | 0.70 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 85 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.81 | | | |
| Intersection Signal Delay (s/veh): 39.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 62.3% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 4: Niagara Falls Blvd & Pier 1 Entrance/The Boulevard/Consumer Square





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 16.7 | |
| LOS | B | |
| Approach Delay (s/veh) | 28.3 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 223 | |
| Queue Length 95th (ft) | 313 | |
| Internal Link Dist (ft) | 592 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 2387 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.40 | |

Intersection Summary



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 44 | 62 | 21 | 133 | 90 | 143 | 2 | 27 | 758 | 49 | 153 | 827 |
| Future Volume (vph) | 44 | 62 | 21 | 133 | 90 | 143 | 2 | 27 | 758 | 49 | 153 | 827 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 100 | | 0 | | 120 | | 165 | 315 | |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 1 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 |
| Frt | | | 0.850 | | 0.908 | | | | | 0.850 | | 0.993 |
| Flt Protected | | 0.980 | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1844 | 1599 | 1787 | 1708 | 0 | 0 | 1787 | 5136 | 1599 | 1787 | 5100 |
| Flt Permitted | | 0.264 | | 0.606 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 497 | 1599 | 1140 | 1708 | 0 | 0 | 1787 | 5136 | 1599 | 1787 | 5100 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 63 | | 45 | | | | | 64 | | 5 |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | 40 |
| Link Distance (ft) | | 713 | | | 278 | | | | 1759 | | | 758 |
| Travel Time (s) | | 16.2 | | | 6.3 | | | | 30.0 | | | 12.9 |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 45 | 64 | 22 | 137 | 93 | 147 | 2 | 28 | 781 | 51 | 158 | 853 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 109 | 22 | 137 | 240 | 0 | 0 | 30 | 781 | 51 | 158 | 896 |
| Turn Type | Perm | NA | Perm | Perm | NA | | Prot | Prot | NA | Perm | Prot | NA |
| Protected Phases | | 4 | | | 8 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 4 | | 4 | 8 | | | | | | 2 | | |
| Detector Phase | 4 | 4 | 4 | 8 | 8 | | 5 | 5 | 2 | 2 | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 |
| Minimum Split (s) | 48.9 | 48.9 | 48.9 | 48.9 | 48.9 | | 11.7 | 11.7 | 40.0 | 40.0 | 11.7 | 31.7 |
| Total Split (s) | 60.0 | 60.0 | 60.0 | 60.0 | 60.0 | | 45.0 | 45.0 | 75.0 | 75.0 | 45.0 | 75.0 |
| Total Split (%) | 33.3% | 33.3% | 33.3% | 33.3% | 33.3% | | 25.0% | 25.0% | 41.7% | 41.7% | 25.0% | 41.7% |
| Maximum Green (s) | 53.1 | 53.1 | 53.1 | 53.1 | 53.1 | | 38.3 | 38.3 | 68.3 | 68.3 | 38.3 | 68.3 |
| Yellow Time (s) | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 3.7 | 3.7 | 3.7 | 3.7 | 3.7 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.9 | 6.9 | 6.9 | 6.9 | | | 6.7 | 6.7 | 6.7 | 6.7 | 6.7 |
| Lead/Lag | | | | | | | Lead | Lead | Lag | Lag | Lead | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | None | None | None | | None | None | C-Max | C-Max | None | C-Max |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | 7.0 | | 7.0 |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | 30.0 | 30.0 | | | | 24.0 | 24.0 | | 18.0 |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | | | | 0 | 0 | | 0 |
| Act Effct Green (s) | | 25.8 | 25.8 | 25.8 | 25.8 | | | 7.9 | 113.2 | 113.2 | 20.7 | 128.4 |
| Actuated g/C Ratio | | 0.14 | 0.14 | 0.14 | 0.14 | | | 0.04 | 0.63 | 0.63 | 0.12 | 0.71 |
| v/c Ratio | | 1.54 | 0.08 | 0.84 | 0.85 | | | 0.38 | 0.24 | 0.05 | 0.77 | 0.25 |
| Control Delay (s/veh) | | 345.3 | 0.5 | 110.8 | 84.4 | | | 81.6 | 25.9 | 13.6 | 118.5 | 2.5 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 42 |
| Future Volume (vph) | 42 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Peak Hour Factor | 0.97 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 43 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |
| Control Delay (s/veh) | |
| Queue Delay | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 345.3 | 0.5 | 110.8 | 84.4 | | | 81.6 | 25.9 | 13.6 | 118.5 | 2.5 |
| LOS | | F | A | F | F | | | F | C | B | F | A |
| Approach Delay (s/veh) | | 287.4 | | | 94.0 | | | | 27.1 | | | 19.9 |
| Approach LOS | | F | | | F | | | | C | | | B |
| Queue Length 50th (ft) | | ~179 | 0 | 159 | 231 | | | 36 | 158 | 0 | 198 | 20 |
| Queue Length 95th (ft) | | #288 | 0 | 234 | 320 | | | 76 | 312 | 46 | 264 | 26 |
| Internal Link Dist (ft) | | 633 | | | 198 | | | | 1679 | | | 678 |
| Turn Bay Length (ft) | | | 25 | 100 | | | | 120 | | 165 | 315 | |
| Base Capacity (vph) | | 146 | 516 | 336 | 535 | | | 380 | 3229 | 1029 | 380 | 3638 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.75 | 0.04 | 0.41 | 0.45 | | | 0.08 | 0.24 | 0.05 | 0.42 | 0.25 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 150 (83%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 1.54 | | | |
| Intersection Signal Delay (s/veh): 48.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 65.0% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| ~ Volume exceeds capacity, queue is theoretically infinite. | | | |
| Queue shown is maximum after two cycles. | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 5: Niagara Falls Blvd & Glenalby Rd/Romney Dr





| Lane Group | SBR |
|---|---|
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|

| Intersection | |
|---|---|
| Int Delay, s/veh | 1.2 |

| Movement | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | | | |
| Traffic Vol, veh/h | 1 | 0 | 13 | 9 | 0 | 33 | 2 | 0 | 1212 | 39 | 36 | 35 | 1073 | 11 |
| Future Vol, veh/h | 1 | 0 | 13 | 9 | 0 | 33 | 2 | 0 | 1212 | 39 | 36 | 35 | 1073 | 11 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Stop | Stop | Stop | Stop | Free | Free | Free | Free | Free | Free | Free | Free |
| RT Channelized | - | - | None | - | - | None | - | - | - | None | - | - | - | None |
| Storage Length | - | - | - | - | - | - | - | - | - | - | - | 105 | - | - |
| Veh in Median Storage, # | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Grade, % | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Peak Hour Factor | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 1 | 0 | 13 | 9 | 0 | 34 | 2 | 0 | 1237 | 40 | 37 | 36 | 1095 | 11 |

| Major/Minor | Minor2 | | | Minor1 | | | Major1 | | | | Major2 | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Conflicting Flow All | 1744 | 2526 | 553 | 1844 | 2512 | 638 | 807 | 1106 | 0 | 0 | 932 | 1277 | 0 | 0 |
| Stage 1 | 1245 | 1245 | - | 1261 | 1261 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 499 | 1281 | - | 583 | 1251 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy | 6.42 | 6.52 | 7.12 | 6.42 | 6.52 | 7.12 | 5.64 | 5.32 | - | - | 5.62 | 5.32 | - | - |
| Critical Hdwy Stg 1 | 7.32 | 5.52 | - | 7.32 | 5.52 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy Stg 2 | 6.72 | 5.52 | - | 6.72 | 5.52 | - | - | - | - | - | - | - | - | - |
| Follow-up Hdwy | 3.81 | 4.01 | 3.91 | 3.81 | 4.01 | 3.91 | 2.32 | 3.11 | - | - | 2.31 | 3.11 | - | - |
| Pot Cap-1 Maneuver | 92 | 28 | 410 | 80 | 28 | 361 | 562 | 351 | - | - | 483 | 290 | - | - |
| Stage 1 | 135 | 246 | - | 132 | 242 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 479 | 237 | - | 427 | 244 | - | - | - | - | - | - | - | - | - |
| Platoon blocked, % | | | | | | | | | - | - | | | - | - |
| Mov Cap-1 Maneuver | 66 | 22 | 410 | 61 | 22 | 361 | 544 | 544 | - | - | 350 | 350 | - | - |
| Mov Cap-2 Maneuver | 66 | 22 | - | 61 | 22 | - | - | - | - | - | - | - | - | - |
| Stage 1 | 107 | 195 | - | 131 | 241 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 433 | 235 | - | 327 | 194 | - | - | - | - | - | - | - | - | - |

| Approach | EB | WB | NB | SB |
|---|---|---|---|---|
| HCM Control Delay, s/v | 17.64 | 31.86 | 0.13 | 1.1 |
| HCM LOS | C | D | | |

| Minor Lane/Major Mvmt | NBL | NBT | NBR | EBLn1 | WBLn1 | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|
| Capacity (veh/h) | 8 | - | - | 299 | 176 | 350 | - | - |
| HCM Lane V/C Ratio | - | - | - | 0.048 | 0.243 | 0.207 | - | - |
| HCM Control Delay (s/veh) | 11.6 | 0.1 | - | 17.6 | 31.9 | 18 | - | - |
| HCM Lane LOS | B | A | - | C | D | C | - | - |
| HCM 95th %tile Q(veh) | 0 | - | - | 0.1 | 0.9 | 0.8 | - | - |




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 140 | 271 | 44 | 278 | 379 | 242 | 14 | 59 | 825 | 226 | 1 | 248 |
| Future Volume (vph) | 140 | 271 | 44 | 278 | 379 | 242 | 14 | 59 | 825 | 226 | 1 | 248 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 50 | | 50 | 400 | | 0 | | 300 | | 300 | | 350 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | | 1 | | 1 | | 2 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 0.91 | 0.97 |
| Frt | | 0.979 | | | | 0.850 | | | | 0.850 | | |
| Flt Protected | 0.950 | | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 1787 | 3499 | 0 | 1787 | 3574 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 3467 |
| Flt Permitted | 0.503 | | | 0.234 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 946 | 3499 | 0 | 440 | 3574 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 3467 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 9 | | | | 249 | | | | 233 | | |
| Link Speed (mph) | | 30 | | | 45 | | | | 40 | | | |
| Link Distance (ft) | | 1574 | | | 1441 | | | | 956 | | | |
| Travel Time (s) | | 35.8 | | | 21.8 | | | | 16.3 | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 144 | 279 | 45 | 287 | 391 | 249 | 14 | 61 | 851 | 233 | 1 | 256 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 144 | 324 | 0 | 287 | 391 | 249 | 0 | 75 | 851 | 233 | 0 | 257 |
| Turn Type | pm+pt | NA | | pm+pt | NA | Perm | Prot | Prot | NA | Perm | Prot | Prot |
| Protected Phases | 7 | 4 | | 3 | 8 | | 5 | 5 | 2 | | 1 | 1 |
| Permitted Phases | 4 | | | 8 | | 8 | | | | 2 | | |
| Detector Phase | 7 | 4 | | 3 | 8 | 8 | 5 | 5 | 2 | 2 | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 6.0 | | 3.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 3.0 |
| Minimum Split (s) | 17.5 | 48.8 | | 13.8 | 47.8 | 47.8 | 12.1 | 12.1 | 39.1 | 39.1 | 12.1 | 12.1 |
| Total Split (s) | 30.0 | 50.0 | | 35.0 | 55.0 | 55.0 | 20.0 | 20.0 | 65.0 | 65.0 | 30.0 | 30.0 |
| Total Split (%) | 16.7% | 27.8% | | 19.4% | 30.6% | 30.6% | 11.1% | 11.1% | 36.1% | 36.1% | 16.7% | 16.7% |
| Maximum Green (s) | 21.9 | 41.9 | | 26.9 | 46.9 | 46.9 | 13.1 | 13.1 | 58.1 | 58.1 | 23.1 | 23.1 |
| Yellow Time (s) | 3.8 | 3.8 | | 3.8 | 3.8 | 3.8 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 4.3 | 4.3 | | 4.3 | 4.3 | 4.3 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | 8.1 | 8.1 | | 8.1 | 8.1 | 8.1 | | 6.9 | 6.9 | 6.9 | | 6.9 |
| Lead/Lag | Lead | Lag | | Lead | Lag | Lag | Lead | Lead | Lag | Lag | Lead | Lead |
| Lead-Lag Optimize? | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | | 2.5 | 2.5 | 2.5 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | | None | None | None | None | None | C-Max | C-Max | None | None |
| Walk Time (s) | | 7.0 | | | 7.0 | 7.0 | | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | | 33.0 | | | 31.0 | 31.0 | | | 24.0 | 24.0 | | |
| Pedestrian Calls (#/hr) | | 0 | | | 0 | 0 | | | 0 | 0 | | |
| Act Effct Green (s) | 36.1 | 20.7 | | 54.2 | 31.1 | 31.1 | | 12.3 | 85.5 | 85.5 | | 18.0 |
| Actuated g/C Ratio | 0.20 | 0.12 | | 0.30 | 0.17 | 0.17 | | 0.07 | 0.48 | 0.48 | | 0.10 |
| v/c Ratio | 0.55 | 0.79 | | 0.88 | 0.63 | 0.52 | | 0.61 | 0.35 | 0.26 | | 0.74 |
| Control Delay (s/veh) | 55.9 | 89.2 | | 79.3 | 74.1 | 10.5 | | 102.0 | 31.3 | 4.1 | | 101.9 |
| Queue Delay | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 750 | 105 |
| Future Volume (vph) | 750 | 105 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.982 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5043 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5043 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 16 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 608 | |
| Travel Time (s) | 10.4 | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 773 | 108 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 881 | 0 |
| Turn Type | NA | |
| Protected Phases | 6 | |
| Permitted Phases | | |
| Detector Phase | 6 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 32.1 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 41.7% | |
| Maximum Green (s) | 68.1 | |
| Yellow Time (s) | 3.9 | |
| All-Red Time (s) | 3.0 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.9 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 2.4 | |
| Recall Mode | C-Max | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 17.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 91.2 | |
| Actuated g/C Ratio | 0.51 | |
| v/c Ratio | 0.34 | |
| Control Delay (s/veh) | 17.5 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 55.9 | 89.2 | | 79.3 | 74.1 | 10.5 | | 102.0 | 31.3 | 4.1 | | 101.9 |
| LOS | E | F | | E | E | B | | F | C | A | | F |
| Approach Delay (s/veh) | | 78.9 | | | 58.6 | | | | 30.4 | | | |
| Approach LOS | | E | | | E | | | | C | | | |
| Queue Length 50th (ft) | 129 | 194 | | 281 | 227 | 0 | | 88 | 232 | 0 | | 156 |
| Queue Length 95th (ft) | 186 | 245 | | #384 | 287 | 86 | | 146 | 298 | 57 | | 208 |
| Internal Link Dist (ft) | | 1494 | | | 1361 | | | | 876 | | | |
| Turn Bay Length (ft) | 50 | | | 400 | | | | 300 | | 300 | | 350 |
| Base Capacity (vph) | 326 | 821 | | 333 | 931 | 600 | | 140 | 2439 | 881 | | 444 |
| Starvation Cap Reductn | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Spillback Cap Reductn | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Storage Cap Reductn | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Reduced v/c Ratio | 0.44 | 0.39 | | 0.86 | 0.42 | 0.42 | | 0.54 | 0.35 | 0.26 | | 0.58 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 120 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.88 | | | |
| Intersection Signal Delay (s/veh): 45.5 | | Intersection LOS: D | |
| Intersection Capacity Utilization 72.3% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 7: Niagara Falls Blvd & Brighton Rd/Maple Rd





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 17.5 | |
| LOS | B | |
| Approach Delay (s/veh) | 36.5 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 141 | |
| Queue Length 95th (ft) | 167 | |
| Internal Link Dist (ft) | 528 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 2563 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.34 | |

| Intersection Summary |
|---|


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 4 | 1 | 7 | 23 | 4 | 25 | 2 | 7 | 969 | 25 | 13 | 22 |
| Future Volume (vph) | 4 | 1 | 7 | 23 | 4 | 25 | 2 | 7 | 969 | 25 | 13 | 22 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 125 | | 0 | | 330 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 |
| Frt | | 0.921 | | | 0.869 | | | | 0.996 | | | |
| Flt Protected | | 0.984 | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1705 | 0 | 1787 | 1635 | 0 | 0 | 1787 | 5115 | 0 | 0 | 1787 |
| Flt Permitted | | 0.877 | | | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 1519 | 0 | 1881 | 1635 | 0 | 0 | 1787 | 5115 | 0 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 7 | | | 27 | | | | 3 | | | |
| Link Speed (mph) | | 25 | | | 25 | | | | 40 | | | |
| Link Distance (ft) | | 642 | | | 490 | | | | 588 | | | |
| Travel Time (s) | | 17.5 | | | 13.4 | | | | 10.0 | | | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 4 | 1 | 7 | 24 | 4 | 27 | 2 | 7 | 1031 | 27 | 14 | 23 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 12 | 0 | 24 | 31 | 0 | 0 | 9 | 1058 | 0 | 0 | 37 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | Prot |
| Protected Phases | | 3 | | | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 |
| Minimum Split (s) | 39.2 | 39.2 | | 39.2 | 39.2 | | 9.3 | 9.3 | 31.3 | | 9.3 | 9.3 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 35.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 21.9% |
| Maximum Green (s) | 43.8 | 43.8 | | 43.8 | 43.8 | | 28.7 | 28.7 | 68.7 | | 28.7 | 28.7 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |
| Total Lost Time (s) | | 6.2 | | 6.2 | 6.2 | | | 6.3 | 6.3 | | | 6.3 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | 3.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | None |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | 26.0 | 26.0 | | 26.0 | 26.0 | | | | 18.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 6.5 | | 6.5 | 6.5 | | | 5.1 | 29.7 | | | 6.0 |
| Actuated g/C Ratio | | 0.15 | | 0.15 | 0.15 | | | 0.12 | 0.67 | | | 0.14 |
| v/c Ratio | | 0.05 | | 0.09 | 0.12 | | | 0.04 | 0.31 | | | 0.15 |
| Control Delay (s/veh) | | 16.7 | | 21.7 | 12.4 | | | 22.9 | 7.7 | | | 22.1 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 1061 | 15 |
| Future Volume (vph) | 1061 | 15 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.998 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5125 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5125 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 2 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 956 | |
| Travel Time (s) | 16.3 | |
| Peak Hour Factor | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 1129 | 16 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 1145 | 0 |
| Turn Type | NA | |
| Protected Phases | 2 | |
| Permitted Phases | | |
| Detector Phase | 2 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 33.3 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 46.9% | |
| Maximum Green (s) | 68.7 | |
| Yellow Time (s) | 4.0 | |
| All-Red Time (s) | 2.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.3 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | Min | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 20.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 32.1 | |
| Actuated g/C Ratio | 0.73 | |
| v/c Ratio | 0.31 | |
| Control Delay (s/veh) | 5.5 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 16.7 | | 21.7 | 12.4 | | | 22.9 | 7.7 | | | 22.1 |
| LOS | | B | | C | B | | | C | A | | | C |
| Approach Delay (s/veh) | | 16.7 | | | 16.5 | | | | 7.8 | | | |
| Approach LOS | | B | | | B | | | | A | | | |
| Queue Length 50th (ft) | | 1 | | 5 | 1 | | | 2 | 42 | | | 7 |
| Queue Length 95th (ft) | | 14 | | 26 | 22 | | | 14 | 126 | | | 34 |
| Internal Link Dist (ft) | | 562 | | | 410 | | | | 508 | | | |
| Turn Bay Length (ft) | | | | | | | | 125 | | | | 330 |
| Base Capacity (vph) | | 1392 | | 1723 | 1500 | | | 1220 | 5115 | | | 1220 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Reduced v/c Ratio | | 0.01 | | 0.01 | 0.02 | | | 0.01 | 0.21 | | | 0.03 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 44.1 | | | |
| Natural Cycle: 85 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.31 | | | |
| Intersection Signal Delay (s/veh): 7.2 | | Intersection LOS: A | |
| Intersection Capacity Utilization 44.5% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 8: Niagara Falls Blvd & Driveway 4/Boulevard Mall Driveway





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 5.5 | |
| LOS | A | |
| Approach Delay (s/veh) | 6.1 | |
| Approach LOS | A | |
| Queue Length 50th (ft) | 46 | |
| Queue Length 95th (ft) | 129 | |
| Internal Link Dist (ft) | 876 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 5125 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.22 | |

| Intersection Summary |
|---|

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 21 | 14 | 20 | 42 | 11 | 21 | 21 | 18 | 950 | 18 | 20 | 1081 |
| Future Volume (vph) | 21 | 14 | 20 | 42 | 11 | 21 | 21 | 18 | 950 | 18 | 20 | 1081 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 150 | | 0 | 250 | |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 |
| Frt | | 0.951 | | | 0.903 | | | | 0.997 | | | 0.996 |
| Flt Protected | | 0.981 | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1755 | 0 | 1787 | 1699 | 0 | 0 | 1787 | 5120 | 0 | 1787 | 5115 |
| Flt Permitted | | 0.861 | | 0.719 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 1540 | 0 | 1353 | 1699 | 0 | 0 | 1787 | 5120 | 0 | 1787 | 5115 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 18 | | | 22 | | | | 2 | | | 3 |
| Link Speed (mph) | | 30 | | | 25 | | | | 40 | | | 40 |
| Link Distance (ft) | | 538 | | | 562 | | | | 2182 | | | 588 |
| Travel Time (s) | | 12.2 | | | 15.3 | | | | 37.2 | | | 10.0 |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 22 | 15 | 21 | 44 | 12 | 22 | 22 | 19 | 1000 | 19 | 21 | 1138 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 58 | 0 | 44 | 34 | 0 | 0 | 41 | 1019 | 0 | 21 | 1166 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | NA |
| Protected Phases | | 3 | | | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 10.0 |
| Minimum Split (s) | 41.6 | 41.6 | | 41.6 | 41.6 | | 16.3 | 16.3 | 32.6 | | 16.3 | 32.6 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 75.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 46.9% |
| Maximum Green (s) | 43.4 | 43.4 | | 43.4 | 43.4 | | 28.4 | 28.4 | 68.4 | | 28.4 | 68.4 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.4 | 3.4 | | 3.4 | 3.4 | | 2.6 | 2.6 | 2.6 | | 2.6 | 2.6 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.6 | | 6.6 | 6.6 | | | 6.6 | 6.6 | | 6.6 | 6.6 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.5 | 3.5 | | 3.5 | 3.5 | | 2.0 | 2.0 | 4.0 | | 2.0 | 4.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | Min |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | 7.0 | | | 7.0 |
| Flash Don't Walk (s) | 28.0 | 28.0 | | 28.0 | 28.0 | | | | 19.0 | | | 19.0 |
| Pedestrian Calls (#/hr) | 5 | 5 | | 5 | 5 | | | | 5 | | | 5 |
| Act Effct Green (s) | | 11.8 | | 11.8 | 11.8 | | | 6.9 | 40.5 | | 6.8 | 35.7 |
| Actuated g/C Ratio | | 0.19 | | 0.19 | 0.19 | | | 0.11 | 0.64 | | 0.11 | 0.57 |
| v/c Ratio | | 0.19 | | 0.17 | 0.10 | | | 0.21 | 0.31 | | 0.11 | 0.40 |
| Control Delay (s/veh) | | 20.1 | | 26.3 | 15.0 | | | 37.1 | 10.7 | | 35.4 | 13.8 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 27 |
| Future Volume (vph) | 27 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Peak Hour Factor | 0.95 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 28 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |
| Control Delay (s/veh) | |
| Queue Delay | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 20.1 | | 26.3 | 15.0 | | | 37.1 | 10.7 | | 35.4 | 13.8 |
| LOS | | C | | C | B | | | D | B | | D | B |
| Approach Delay (s/veh) | | 20.1 | | | 21.4 | | | | 11.8 | | | 14.2 |
| Approach LOS | | C | | | C | | | | B | | | B |
| Queue Length 50th (ft) | | 13 | | 15 | 4 | | | 14 | 50 | | 7 | 108 |
| Queue Length 95th (ft) | | 49 | | 48 | 28 | | | 62 | 246 | | 37 | 269 |
| Internal Link Dist (ft) | | 458 | | | 482 | | | | 2102 | | | 508 |
| Turn Bay Length (ft) | | | | | | | | 150 | | | 250 | |
| Base Capacity (vph) | | 1154 | | 1010 | 1274 | | | 925 | 4746 | | 925 | 4741 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 13 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | | 0.05 | | 0.04 | 0.03 | | | 0.04 | 0.21 | | 0.02 | 0.25 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 63 | | | |
| Natural Cycle: 95 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.40 | | | |
| Intersection Signal Delay (s/veh): 13.5 | | Intersection LOS: B | |
| Intersection Capacity Utilization 51.1% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 9: Niagara Falls Blvd & Treadwell Rd/Driveway 2





| Lane Group | SBR |
|---|---|
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|




| Lane Group | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 328 | 672 | 0 | 2 | 283 | 714 | 39 | 0 | 528 | 56 | 34 | 158 |
| Future Volume (vph) | 328 | 672 | 0 | 2 | 283 | 714 | 39 | 0 | 528 | 56 | 34 | 158 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 370 | | 0 | | 300 | | 300 | 0 | | 0 | | 450 |
| Storage Lanes | 2 | | 0 | | 2 | | 1 | 0 | | 0 | | 2 |
| Taper Length (ft) | 25 | | | | 25 | | | 25 | | | | 25 |
| Lane Util. Factor | 0.97 | 0.91 | 0.91 | 0.91 | 0.97 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 | 0.97 |
| Ped Bike Factor | 1.00 | | | | 1.00 | | 0.98 | | | | | |
| Frt | | | | | | | 0.850 | | 0.986 | | | |
| Flt Protected | 0.950 | | | | 0.950 | | | | | | | 0.950 |
| Satd. Flow (prot) | 3467 | 5136 | 0 | 0 | 3467 | 5136 | 1599 | 0 | 5064 | 0 | 0 | 3467 |
| Flt Permitted | 0.950 | | | | 0.950 | | | | | | | 0.950 |
| Satd. Flow (perm) | 3463 | 5136 | 0 | 0 | 3465 | 5136 | 1575 | 0 | 5064 | 0 | 0 | 3467 |
| Right Turn on Red | | | Yes | | | | Yes | | | Yes | | |
| Satd. Flow (RTOR) | | | | | | | 119 | | 10 | | | |
| Link Speed (mph) | | 40 | | | | 40 | | | 40 | | | |
| Link Distance (ft) | | 623 | | | | 1468 | | | 379 | | | |
| Travel Time (s) | | 10.6 | | | | 25.0 | | | 6.5 | | | |
| Confl. Peds. (#/hr) | 2 | | 1 | | 1 | | 2 | | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 338 | 693 | 0 | 2 | 292 | 736 | 40 | 0 | 544 | 58 | 35 | 163 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 338 | 693 | 0 | 0 | 294 | 736 | 40 | 0 | 602 | 0 | 0 | 198 |
| Turn Type | Prot | NA | | Prot | Prot | NA | Perm | | NA | | Prot | Prot |
| Protected Phases | 3 | 8 | | 7 | 7 | 4 | | | 2 | | 1 | 1 |
| Permitted Phases | | | | | | | 4 | | | | | |
| Detector Phase | 3 | 8 | | 7 | 7 | 4 | 4 | | 2 | | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 6.0 | | 3.0 | 3.0 | 6.0 | 6.0 | | 10.0 | | 3.0 | 3.0 |
| Minimum Split (s) | 10.3 | 48.0 | | 10.3 | 10.3 | 48.0 | 48.0 | | 58.2 | | 12.3 | 12.3 |
| Total Split (s) | 37.0 | 48.0 | | 37.0 | 37.0 | 48.0 | 48.0 | | 68.0 | | 37.0 | 37.0 |
| Total Split (%) | 19.5% | 25.3% | | 19.5% | 19.5% | 25.3% | 25.3% | | 35.8% | | 19.5% | 19.5% |
| Maximum Green (s) | 29.7 | 40.7 | | 29.7 | 29.7 | 40.7 | 40.7 | | 59.8 | | 28.8 | 28.8 |
| Yellow Time (s) | 4.0 | 4.0 | | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.3 | 3.3 | | 3.3 | 3.3 | 3.3 | 3.3 | | 4.2 | | 4.2 | 4.2 |
| Lost Time Adjust (s) | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 |
| Total Lost Time (s) | 7.3 | 7.3 | | | 7.3 | 7.3 | 7.3 | | 8.2 | | | 8.2 |
| Lead/Lag | Lead | Lag | | Lead | Lead | Lag | Lag | | Lag | | Lead | Lead |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 2.0 | 4.0 | | 2.0 | 2.0 | 4.0 | 4.0 | | 4.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | None | None | | C-Min | | None | None |
| Walk Time (s) | | 7.0 | | | | 7.0 | 7.0 | | 7.0 | | | |
| Flash Don't Walk (s) | | 30.0 | | | | 30.0 | 30.0 | | 39.0 | | | |
| Pedestrian Calls (#/hr) | | 0 | | | | 2 | 2 | | 1 | | | |
| Act Effct Green (s) | 22.9 | 38.3 | | | 20.5 | 35.9 | 35.9 | | 85.0 | | | 15.2 |
| Actuated g/C Ratio | 0.12 | 0.20 | | | 0.11 | 0.19 | 0.19 | | 0.45 | | | 0.08 |
| v/c Ratio | 0.81 | 0.67 | | | 0.79 | 0.76 | 0.10 | | 0.27 | | | 0.71 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | ↑↑ | ↱ |
| Traffic Volume (vph) | 651 | 354 |
| Future Volume (vph) | 651 | 354 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 1.00 |
| Ped Bike Factor | | |
| Frt | | 0.850 |
| Flt Protected | | |
| Satd. Flow (prot) | 3574 | 1599 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3574 | 1599 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | | 365 |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 2182 | |
| Travel Time (s) | 37.2 | |
| Confl. Peds. (#/hr) | | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 671 | 365 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 671 | 365 |
| Turn Type | NA | Perm |
| Protected Phases | 6 | |
| Permitted Phases | | 6 |
| Detector Phase | 6 | 6 |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | 10.0 |
| Minimum Split (s) | 58.2 | 58.2 |
| Total Split (s) | 105.0 | 105.0 |
| Total Split (%) | 55.3% | 55.3% |
| Maximum Green (s) | 96.8 | 96.8 |
| Yellow Time (s) | 4.0 | 4.0 |
| All-Red Time (s) | 4.2 | 4.2 |
| Lost Time Adjust (s) | 0.0 | 0.0 |
| Total Lost Time (s) | 8.2 | 8.2 |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 4.0 | 4.0 |
| Recall Mode | C-Min | C-Min |
| Walk Time (s) | 7.0 | 7.0 |
| Flash Don't Walk (s) | 39.0 | 39.0 |
| Pedestrian Calls (#/hr) | 2 | 2 |
| Act Effct Green (s) | 108.4 | 108.4 |
| Actuated g/C Ratio | 0.57 | 0.57 |
| v/c Ratio | 0.33 | 0.34 |

| Lane Group | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | 96.7 | 73.0 | | | 97.6 | 78.1 | 0.5 | | 19.3 | | | 99.4 |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.2 | | | 0.0 |
| Total Delay (s/veh) | 96.7 | 73.0 | | | 97.6 | 78.1 | 0.5 | | 19.6 | | | 99.4 |
| LOS | F | E | | | F | E | A | | B | | | F |
| Approach Delay (s/veh) | | 80.8 | | | | 80.6 | | | 19.6 | | | |
| Approach LOS | | F | | | | F | | | B | | | |
| Queue Length 50th (ft) | 215 | 297 | | | 188 | 323 | 0 | | 86 | | | 126 |
| Queue Length 95th (ft) | 268 | 330 | | | 238 | 359 | 0 | | 62 | | | 171 |
| Internal Link Dist (ft) | | 543 | | | | 1388 | | | 299 | | | |
| Turn Bay Length (ft) | 370 | | | | 300 | | 300 | | | | | 450 |
| Base Capacity (vph) | 541 | 1128 | | | 541 | 1110 | 433 | | 2270 | | | 525 |
| Starvation Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | | 881 | | | 0 |
| Spillback Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | | 0 | | | 0 |
| Storage Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | | 0 | | | 0 |
| Reduced v/c Ratio | 0.62 | 0.61 | | | 0.54 | 0.66 | 0.09 | | 0.43 | | | 0.38 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 140 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.81 | | | |
| Intersection Signal Delay (s/veh): 55.3 | | Intersection LOS: E | |
| Intersection Capacity Utilization 67.0% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 10: Niagara Falls Blvd & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Control Delay (s/veh) | 23.1 | 2.9 |
| Queue Delay | 0.0 | 0.0 |
| Total Delay (s/veh) | 23.2 | 2.9 |
| LOS | C | A |
| Approach Delay (s/veh) | 29.4 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 227 | 0 |
| Queue Length 95th (ft) | 315 | 56 |
| Internal Link Dist (ft) | 2102 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 2041 | 1069 |
| Starvation Cap Reductn | 0 | 0 |
| Spillback Cap Reductn | 95 | 0 |
| Storage Cap Reductn | 0 | 0 |
| Reduced v/c Ratio | 0.34 | 0.34 |

| Intersection Summary |
|---|

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 1 | 242 | 169 | 46 | 298 | 71 | 2 | 153 | 699 | 41 | 3 | 90 |
| Future Volume (vph) | 1 | 242 | 169 | 46 | 298 | 71 | 2 | 153 | 699 | 41 | 3 | 90 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 100 | 200 | | 0 | | 250 | | 0 | | 0 |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 0.95 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 0.91 | 1.00 | 0.91 | 0.91 | 0.95 | 1.00 |
| Frt | | | 0.850 | | 0.971 | | | | 0.992 | | | |
| Flt Protected | | | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 3574 | 1599 | 1787 | 3471 | 0 | 0 | 1787 | 5095 | 0 | 0 | 1787 |
| Flt Permitted | | 0.953 | | 0.468 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 3406 | 1599 | 880 | 3471 | 0 | 0 | 1787 | 5095 | 0 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 165 | | 14 | | | | 5 | | | |
| Link Speed (mph) | | 30 | | | 35 | | | | 35 | | | |
| Link Distance (ft) | | 718 | | | 1535 | | | | 1665 | | | |
| Travel Time (s) | | 16.3 | | | 29.9 | | | | 32.4 | | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 1 | 247 | 172 | 47 | 304 | 72 | 2 | 156 | 713 | 42 | 3 | 92 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 248 | 172 | 47 | 376 | 0 | 0 | 158 | 755 | 0 | 0 | 95 |
| Turn Type | Perm | NA | Perm | Perm | NA | | Prot | Prot | NA | | Prot | Prot |
| Protected Phases | | 4 | | | 4 | | 1 | 1 | 2 | | 1 3 | 1 3 |
| Permitted Phases | 4 | | 4 | 4 | | | | | | | | |
| Detector Phase | 4 | 4 | 4 | 4 | 4 | | 1 | 1 | 2 | | 1 3 | 1 3 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 5.0 | | | |
| Minimum Split (s) | 43.1 | 43.1 | 43.1 | 43.1 | 43.1 | | 9.8 | 9.8 | 22.5 | | | |
| Total Split (s) | 54.0 | 54.0 | 54.0 | 54.0 | 54.0 | | 35.0 | 35.0 | 68.0 | | | |
| Total Split (%) | 28.4% | 28.4% | 28.4% | 28.4% | 28.4% | | 18.4% | 18.4% | 35.8% | | | |
| Maximum Green (s) | 46.9 | 46.9 | 46.9 | 46.9 | 46.9 | | 28.2 | 28.2 | 63.5 | | | |
| Yellow Time (s) | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | | 3.9 | 3.9 | 3.5 | | | |
| All-Red Time (s) | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | | 2.9 | 2.9 | 1.0 | | | |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | | |
| Total Lost Time (s) | | 7.1 | 7.1 | 7.1 | 7.1 | | | 6.8 | 4.5 | | | |
| Lead/Lag | Lag | Lag | Lag | Lag | Lag | | Lead | Lead | Lag | | | |
| Lead-Lag Optimize? | | | | | | | | | Yes | | | |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | 3.0 | | | |
| Recall Mode | None | None | None | None | None | | None | None | C-Max | | | |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | 29.0 | 29.0 | 29.0 | 29.0 | 29.0 | | | | 11.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 26.2 | 26.2 | 26.2 | 26.2 | | | 21.1 | 104.7 | | | 33.9 |
| Actuated g/C Ratio | | 0.14 | 0.14 | 0.14 | 0.14 | | | 0.11 | 0.55 | | | 0.18 |
| v/c Ratio | | 0.53 | 0.48 | 0.39 | 0.77 | | | 0.80 | 0.27 | | | 0.30 |
| Control Delay (s/veh) | | 79.6 | 14.3 | 82.4 | 86.4 | | | 109.1 | 24.3 | | | 36.5 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |

| Lane Group | SBT | SBR | Ø3 |
|---|---|---|---|
| Lane Configurations | | | |
| Traffic Volume (vph) | 795 | 32 | |
| Future Volume (vph) | 795 | 32 | |
| Ideal Flow (vphpl) | 1900 | 1900 | |
| Storage Length (ft) | | 0 | |
| Storage Lanes | | 0 | |
| Taper Length (ft) | | | |
| Lane Util. Factor | 0.95 | 0.95 | |
| Frt | 0.994 | | |
| Flt Protected | | | |
| Satd. Flow (prot) | 3553 | 0 | |
| Flt Permitted | | | |
| Satd. Flow (perm) | 3553 | 0 | |
| Right Turn on Red | | Yes | |
| Satd. Flow (RTOR) | 3 | | |
| Link Speed (mph) | 40 | | |
| Link Distance (ft) | 379 | | |
| Travel Time (s) | 6.5 | | |
| Peak Hour Factor | 0.98 | 0.98 | |
| Heavy Vehicles (%) | 1% | 1% | |
| Adj. Flow (vph) | 811 | 33 | |
| Shared Lane Traffic (%) | | | |
| Lane Group Flow (vph) | 844 | 0 | |
| Turn Type | NA | | |
| Protected Phases | 2 3 | | 3 |
| Permitted Phases | | | |
| Detector Phase | 2 3 | | |
| Switch Phase | | | |
| Minimum Initial (s) | | | 3.0 |
| Minimum Split (s) | | | 9.8 |
| Total Split (s) | | | 33.0 |
| Total Split (%) | | | 17% |
| Maximum Green (s) | | | 26.2 |
| Yellow Time (s) | | | 3.9 |
| All-Red Time (s) | | | 2.9 |
| Lost Time Adjust (s) | | | |
| Total Lost Time (s) | | | |
| Lead/Lag | | | Lead |
| Lead-Lag Optimize? | | | |
| Vehicle Extension (s) | | | 2.0 |
| Recall Mode | | | None |
| Walk Time (s) | | | |
| Flash Don't Walk (s) | | | |
| Pedestrian Calls (#/hr) | | | |
| Act Effct Green (s) | 124.3 | | |
| Actuated g/C Ratio | 0.65 | | |
| v/c Ratio | 0.36 | | |
| Control Delay (s/veh) | 13.2 | | |
| Queue Delay | 0.2 | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 79.6 | 14.3 | 82.4 | 86.4 | | | 109.1 | 24.3 | | | 36.5 |
| LOS | | E | B | F | F | | | F | C | | | D |
| Approach Delay (s/veh) | | 52.9 | | | 85.9 | | | | 38.9 | | | |
| Approach LOS | | D | | | F | | | | D | | | |
| Queue Length 50th (ft) | | 154 | 8 | 54 | 233 | | | 196 | 178 | | | 75 |
| Queue Length 95th (ft) | | 197 | 83 | 99 | 284 | | | 275 | 255 | | | 124 |
| Internal Link Dist (ft) | | 638 | | | 1455 | | | | 1585 | | | |
| Turn Bay Length (ft) | | | 100 | 200 | | | | 250 | | | | |
| Base Capacity (vph) | | 840 | 518 | 217 | 867 | | | 265 | 2810 | | | 511 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | | 0 |
| Reduced v/c Ratio | | 0.30 | 0.33 | 0.22 | 0.43 | | | 0.60 | 0.27 | | | 0.19 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBSB, Start of Yellow | | | |
| Natural Cycle: 90 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.80 | | | |
| Intersection Signal Delay (s/veh): 40.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 73.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 11: Niagara Falls Blvd & Eggert Rd





| Lane Group | SBT | SBR | Ø3 |
|---|---|---|---|
| Total Delay (s/veh) | 13.4 | | |
| LOS | B | | |
| Approach Delay (s/veh) | 15.7 | | |
| Approach LOS | B | | |
| Queue Length 50th (ft) | 285 | | |
| Queue Length 95th (ft) | 315 | | |
| Internal Link Dist (ft) | 299 | | |
| Turn Bay Length (ft) | | | |
| Base Capacity (vph) | 2576 | | |
| Starvation Cap Reductn | 897 | | |
| Spillback Cap Reductn | 0 | | |
| Storage Cap Reductn | 0 | | |
| Reduced v/c Ratio | 0.50 | | |

Intersection Summary





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 26 | 474 | 168 | 165 | 824 | 5 | 213 | 69 | 123 | 15 | 36 | 48 |
| Future Volume (vph) | 26 | 474 | 168 | 165 | 824 | 5 | 213 | 69 | 123 | 15 | 36 | 48 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 400 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.850 | | 0.999 | | | 0.904 | | | 0.914 | |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 5131 | 0 | 1787 | 1701 | 0 | 1787 | 1719 | 0 |
| Flt Permitted | 0.313 | | | 0.303 | | | 0.495 | | | 0.631 | | |
| Satd. Flow (perm) | 589 | 3574 | 1599 | 570 | 5131 | 0 | 931 | 1701 | 0 | 1187 | 1719 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 177 | | 1 | | | 84 | | | 51 | |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 25 | |
| Link Distance (ft) | | 1441 | | | 678 | | | 472 | | | 347 | |
| Travel Time (s) | | 21.8 | | | 10.3 | | | 9.2 | | | 9.5 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 27 | 499 | 177 | 174 | 867 | 5 | 224 | 73 | 129 | 16 | 38 | 51 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 27 | 499 | 177 | 174 | 872 | 0 | 224 | 202 | 0 | 16 | 89 | 0 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Permitted Phases | 2 | 2 | 2 | 6 | | | 8 | | | 4 | | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | | 5.0 | 10.0 | | 5.0 | 10.0 | |
| Minimum Split (s) | 10.0 | 27.6 | 27.6 | 10.0 | 27.6 | | 10.0 | 27.6 | | 10.0 | 27.6 | |
| Total Split (s) | 15.0 | 40.0 | 40.0 | 15.0 | 40.0 | | 15.0 | 20.0 | | 15.0 | 20.0 | |
| Total Split (%) | 16.7% | 44.4% | 44.4% | 16.7% | 44.4% | | 16.7% | 22.2% | | 16.7% | 22.2% | |
| Maximum Green (s) | 10.0 | 34.4 | 34.4 | 10.0 | 34.4 | | 10.0 | 14.4 | | 10.0 | 14.4 | |
| Yellow Time (s) | 3.0 | 3.6 | 3.6 | 3.0 | 3.6 | | 3.0 | 3.6 | | 3.0 | 3.6 | |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 5.0 | 5.6 | 5.6 | 5.0 | 5.6 | | 5.0 | 5.6 | | 5.0 | 5.6 | |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | | 3.0 | 4.0 | | 3.0 | 4.0 | |
| Minimum Gap (s) | 3.0 | 0.2 | 0.2 | 3.0 | 0.2 | | 3.0 | 0.2 | | 3.0 | 0.2 | |
| Time Before Reduce (s) | 0.0 | 7.0 | 7.0 | 0.0 | 7.0 | | 0.0 | 7.0 | | 0.0 | 7.0 | |
| Time To Reduce (s) | 0.0 | 0.5 | 0.5 | 0.0 | 0.5 | | 0.0 | 0.5 | | 0.0 | 0.5 | |
| Recall Mode | None | Min | Min | None | Min | | None | None | | None | None | |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | 15.0 | 15.0 | | 15.0 | | | 15.0 | | | 15.0 | |
| Pedestrian Calls (#/hr) | | 4 | 4 | | 2 | | | 4 | | | 2 | |
| Act Effct Green (s) | 22.4 | 15.3 | 15.3 | 29.5 | 25.4 | | 23.8 | 21.6 | | 15.9 | 12.3 | |
| Actuated g/C Ratio | 0.35 | 0.24 | 0.24 | 0.46 | 0.39 | | 0.37 | 0.33 | | 0.25 | 0.19 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | 0.08 | 0.59 | 0.34 | 0.41 | 0.43 | | 0.46 | 0.32 | | 0.05 | 0.24 | |
| Control Delay (s/veh) | 12.6 | 26.4 | 6.4 | 15.2 | 18.0 | | 18.2 | 12.6 | | 14.1 | 14.9 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Delay (s/veh) | 12.6 | 26.4 | 6.4 | 15.2 | 18.0 | | 18.2 | 12.6 | | 14.1 | 14.9 | |
| LOS | B | C | A | B | B | | B | B | | B | B | |
| Approach Delay (s/veh) | | 20.9 | | | 17.5 | | | 15.6 | | | 14.7 | |
| Approach LOS | | C | | | B | | | B | | | B | |
| Queue Length 50th (ft) | 6 | 94 | 0 | 40 | 80 | | 61 | 30 | | 4 | 13 | |
| Queue Length 95th (ft) | 23 | 170 | 47 | 98 | 187 | | 124 | 104 | | 16 | 51 | |
| Internal Link Dist (ft) | | 1361 | | | 598 | | | 392 | | | 267 | |
| Turn Bay Length (ft) | 200 | | 200 | 400 | | | | | | | | |
| Base Capacity (vph) | 435 | 1998 | 971 | 457 | 2869 | | 483 | 658 | | 469 | 471 | |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.06 | 0.25 | 0.18 | 0.38 | 0.30 | | 0.46 | 0.31 | | 0.03 | 0.19 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 90 | | | |
| Actuated Cycle Length: 64.7 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.59 | | | |
| Intersection Signal Delay (s/veh): 18.1 | | Intersection LOS: B | |
| Intersection Capacity Utilization 54.2% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 12: Alberta Dr/Driveway 5 & Maple Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 70 | 518 | 44 | 210 | 843 | 250 | 69 | 353 | 138 | 276 | 360 | 117 |
| Future Volume (vph) | 70 | 518 | 44 | 210 | 843 | 250 | 69 | 353 | 138 | 276 | 360 | 117 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | 430 | 350 | | 0 | 150 | | 150 | 500 | | 150 |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 1 | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.850 | | 0.966 | | | | 0.850 | | | 0.850 |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 4961 | 0 | 1787 | 1881 | 1599 | 1787 | 1881 | 1599 |
| Flt Permitted | 0.177 | | | 0.215 | | | 0.368 | | | 0.289 | | |
| Satd. Flow (perm) | 333 | 3574 | 1599 | 404 | 4961 | 0 | 692 | 1881 | 1599 | 544 | 1881 | 1599 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 227 | | 72 | | | | 209 | | | 209 |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 35 | |
| Link Distance (ft) | | 678 | | | 748 | | | 1712 | | | 1039 | |
| Travel Time (s) | | 10.3 | | | 11.3 | | | 33.4 | | | 20.2 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 72 | 534 | 45 | 216 | 869 | 258 | 71 | 364 | 142 | 285 | 371 | 121 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 72 | 534 | 45 | 216 | 1127 | 0 | 71 | 364 | 142 | 285 | 371 | 121 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | Perm | pm+pt | NA | Perm |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Permitted Phases | 2 | 2 | 2 | 6 | | | 8 | | 8 | 4 | | 4 |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | 8 | 7 | 4 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | 10.0 |
| Minimum Split (s) | 12.0 | 29.0 | 29.0 | 12.0 | 29.0 | | 12.0 | 29.0 | 29.0 | 12.0 | 29.0 | 29.0 |
| Total Split (s) | 15.0 | 35.0 | 35.0 | 30.0 | 50.0 | | 15.0 | 40.0 | 40.0 | 15.0 | 40.0 | 40.0 |
| Total Split (%) | 12.5% | 29.2% | 29.2% | 25.0% | 41.7% | | 12.5% | 33.3% | 33.3% | 12.5% | 33.3% | 33.3% |
| Maximum Green (s) | 8.0 | 30.0 | 30.0 | 23.0 | 45.0 | | 8.0 | 33.0 | 33.0 | 8.0 | 33.0 | 33.0 |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 4.0 | 2.0 | 2.0 | 4.0 | 2.0 | | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 7.0 | 5.0 | 5.0 | 7.0 | 5.0 | | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | 4.0 |
| Minimum Gap (s) | 3.0 | 0.2 | 0.2 | 3.0 | 0.2 | | 3.0 | 0.2 | 0.2 | 3.0 | 0.2 | 0.2 |
| Time Before Reduce (s) | 0.0 | 7.0 | 7.0 | 0.0 | 7.0 | | 0.0 | 7.0 | 7.0 | 0.0 | 7.0 | 7.0 |
| Time To Reduce (s) | 0.0 | 0.5 | 0.5 | 0.0 | 0.5 | | 0.0 | 0.5 | 0.5 | 0.0 | 0.5 | 0.5 |
| Recall Mode | None | Min | Min | None | Min | | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 15.0 | 15.0 | | 15.0 | | | 15.0 | 15.0 | | 15.0 | 15.0 |
| Pedestrian Calls (#/hr) | | 1 | 1 | | 0 | | | 1 | 1 | | 0 | 0 |
| Act Effct Green (s) | 26.2 | 20.8 | 20.8 | 38.4 | 30.1 | | 31.2 | 23.9 | 23.9 | 34.2 | 28.1 | 28.1 |
| Actuated g/C Ratio | 0.28 | 0.22 | 0.22 | 0.41 | 0.32 | | 0.34 | 0.26 | 0.26 | 0.37 | 0.30 | 0.30 |


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | 0.34 | 0.67 | 0.08 | 0.59 | 0.68 | | 0.22 | 0.75 | 0.25 | 0.92 | 0.65 | 0.19 |
| Control Delay (s/veh) | 23.2 | 38.4 | 0.3 | 25.2 | 29.2 | | 20.0 | 43.5 | 1.9 | 61.0 | 37.5 | 0.7 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 23.2 | 38.4 | 0.3 | 25.2 | 29.2 | | 20.0 | 43.5 | 1.9 | 61.0 | 37.5 | 0.7 |
| LOS | C | D | A | C | C | | B | D | A | E | D | A |
| Approach Delay (s/veh) | | 34.1 | | | 28.5 | | | 30.3 | | | 40.4 | |
| Approach LOS | | C | | | C | | | C | | | D | |
| Queue Length 50th (ft) | 25 | 150 | 0 | 81 | 207 | | 24 | 196 | 0 | 112 | 200 | 0 |
| Queue Length 95th (ft) | 57 | 242 | 0 | 150 | 288 | | 60 | 341 | 10 | #317 | 348 | 0 |
| Internal Link Dist (ft) | | 598 | | | 668 | | | 1632 | | | 959 | |
| Turn Bay Length (ft) | 250 | | 430 | 350 | | | 150 | | 150 | 500 | | 150 |
| Base Capacity (vph) | 225 | 1182 | 681 | 521 | 2498 | | 335 | 684 | 715 | 309 | 684 | 715 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.32 | 0.45 | 0.07 | 0.41 | 0.45 | | 0.21 | 0.53 | 0.20 | 0.92 | 0.54 | 0.17 |

**Intersection Summary**

Area Type: Other
Cycle Length: 120
Actuated Cycle Length: 93
Natural Cycle: 85
Control Type: Actuated-Uncoordinated
Maximum v/c Ratio: 0.92
Intersection Signal Delay (s/veh): 32.7 Intersection LOS: C
Intersection Capacity Utilization 81.6% ICU Level of Service D
Analysis Period (min) 15
# 95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 13: Bailey Ave & Maple Rd







| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Volume (vph) | 94 | 820 | 1243 | 217 | 192 | 87 |
| Future Volume (vph) | 94 | 820 | 1243 | 217 | 192 | 87 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | | 100 | 100 | 0 |
| Storage Lanes | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 0.91 | 0.91 | 1.00 | 1.00 |
| Frt | | | 0.978 | | | 0.850 |
| Flt Protected | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1787 | 3574 | 5023 | 0 | 1787 | 1599 |
| Flt Permitted | 0.105 | | | | 0.950 | |
| Satd. Flow (perm) | 198 | 3574 | 5023 | 0 | 1787 | 1599 |
| Right Turn on Red | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | 55 | | | 91 |
| Link Speed (mph) | | 35 | 45 | | 30 | |
| Link Distance (ft) | | 748 | 466 | | 1444 | |
| Travel Time (s) | | 14.6 | 7.1 | | 32.8 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 98 | 854 | 1295 | 226 | 200 | 91 |
| Shared Lane Traffic (%) | | | | | | |
| Lane Group Flow (vph) | 98 | 854 | 1521 | 0 | 200 | 91 |
| Turn Type | pm+pt | NA | NA | | Prot | Prot |
| Protected Phases | 5 | 2 | 6 | | 4 | 4 |
| Permitted Phases | 2 | | | | | |
| Detector Phase | 5 | 2 | 6 | | 4 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 5.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| Minimum Split (s) | 9.5 | 27.0 | 27.0 | | 27.0 | 27.0 |
| Total Split (s) | 15.0 | 95.0 | 80.0 | | 25.0 | 25.0 |
| Total Split (%) | 12.5% | 79.2% | 66.7% | | 20.8% | 20.8% |
| Maximum Green (s) | 10.5 | 90.0 | 75.0 | | 20.0 | 20.0 |
| Yellow Time (s) | 3.5 | 3.0 | 3.0 | | 3.0 | 3.0 |
| All-Red Time (s) | 1.0 | 2.0 | 2.0 | | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 4.5 | 5.0 | 5.0 | | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | | | |
| Lead-Lag Optimize? | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | None | Min | Min | | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 11.0 | 11.0 | | 11.0 | 11.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 0 | 0 |
| Act Effct Green (s) | 44.3 | 43.8 | 33.6 | | 13.1 | 13.1 |
| Actuated g/C Ratio | 0.66 | 0.65 | 0.50 | | 0.19 | 0.19 |
| v/c Ratio | 0.30 | 0.37 | 0.60 | | 0.58 | 0.24 |
| Control Delay (s/veh) | 6.8 | 6.0 | 14.0 | | 34.0 | 8.3 |
| Queue Delay | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 6.8 | 6.0 | 14.0 | | 34.0 | 8.3 |
| LOS | A | A | B | | C | A |
| Approach Delay (s/veh) | | 6.1 | 14.0 | | 26.0 | |
| Approach LOS | | A | B | | C | |
| Queue Length 50th (ft) | 12 | 68 | 158 | | 76 | 0 |
| Queue Length 95th (ft) | 32 | 125 | 250 | | 162 | 37 |
| Internal Link Dist (ft) | | 668 | 386 | | 1364 | |
| Turn Bay Length (ft) | 250 | | | | 100 | |
| Base Capacity (vph) | 389 | 3574 | 4882 | | 553 | 558 |
| Starvation Cap Reductn | 0 | 0 | 119 | | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | 0.25 | 0.24 | 0.32 | | 0.36 | 0.16 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 67.3 | | | |
| Natural Cycle: 65 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.60 | | | |
| Intersection Signal Delay (s/veh): 12.5 | | Intersection LOS: B | |
| Intersection Capacity Utilization 56.8% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 14: Maple Rd & Bowmart Parkway






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 991 | 18 | 19 | 1464 | 0 | 32 | 0 | 33 | 27 | 0 | 5 |
| Future Volume (vph) | 0 | 991 | 18 | 19 | 1464 | 0 | 32 | 0 | 33 | 27 | 0 | 5 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 150 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | 0 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.997 | | | | | | 0.932 | | | 0.850 | |
| Flt Protected | | | | 0.950 | | | | 0.976 | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3564 | 0 | 1787 | 3574 | 0 | 0 | 1711 | 0 | 1787 | 1599 | 0 |
| Flt Permitted | | | | 0.950 | | | | 0.841 | | 0.712 | | |
| Satd. Flow (perm) | 0 | 3564 | 0 | 1787 | 3574 | 0 | 0 | 1474 | 0 | 1339 | 1599 | 0 |
| Right Turn on Red | | | No | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | | | | 64 | | | 64 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 10 | |
| Link Distance (ft) | | 466 | | | 1563 | | | 418 | | | 259 | |
| Travel Time (s) | | 9.1 | | | 30.4 | | | 9.5 | | | 17.7 | |
| Peak Hour Factor | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 0 | 1066 | 19 | 20 | 1574 | 0 | 34 | 0 | 35 | 29 | 0 | 5 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 1085 | 0 | 20 | 1574 | 0 | 0 | 69 | 0 | 29 | 5 | 0 |
| Turn Type | | NA | | Prot | NA | | Perm | NA | | Perm | NA | |
| Protected Phases | | 2 | | 1 | 6 | | | 4 | | | 8 | |
| Permitted Phases | | | | | | | 4 | | | 8 | | |
| Detector Phase | | 2 | | 1 | 6 | | 4 | 4 | | 8 | 8 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | 5.0 | | 10.0 | 5.0 | | 5.0 | 5.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | | 27.0 | | 27.0 | 27.0 | | 27.0 | 27.0 | | 27.0 | 27.0 | |
| Total Split (s) | | 60.0 | | 20.0 | 80.0 | | 40.0 | 40.0 | | 40.0 | 40.0 | |
| Total Split (%) | | 50.0% | | 16.7% | 66.7% | | 33.3% | 33.3% | | 33.3% | 33.3% | |
| Maximum Green (s) | | 55.0 | | 15.0 | 75.0 | | 35.0 | 35.0 | | 35.0 | 35.0 | |
| Yellow Time (s) | | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | 5.0 | 5.0 | | | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | Lag | | Lead | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Gap (s) | | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | |
| Time Before Reduce (s) | | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Time To Reduce (s) | | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | |
| Recall Mode | | Min | | None | Min | | None | None | | None | None | |
| Walk Time (s) | | | | | 7.0 | | | | | | | |
| Flash Don't Walk (s) | | | | | 30.0 | | | | | | | |
| Pedestrian Calls (#/hr) | | | | | 0 | | | | | | | |
| Act Effct Green (s) | | 34.9 | | 10.5 | 37.3 | | | 9.5 | | 10.6 | 10.6 | |
| Actuated g/C Ratio | | 0.67 | | 0.20 | 0.72 | | | 0.18 | | 0.20 | 0.20 | |


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | | 0.45 | | 0.06 | 0.62 | | | 0.22 | | 0.11 | 0.01 | |
| Control Delay (s/veh) | | 8.0 | | 20.9 | 7.0 | | | 9.5 | | 21.7 | 0.0 | |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | |
| Total Delay (s/veh) | | 8.0 | | 20.9 | 7.0 | | | 9.5 | | 21.7 | 0.0 | |
| LOS | | A | | C | A | | | A | | C | A | |
| Approach Delay (s/veh) | | 8.0 | | | 7.1 | | | 9.5 | | | 18.5 | |
| Approach LOS | | A | | | A | | | A | | | B | |
| Queue Length 50th (ft) | | 80 | | 5 | 144 | | | 1 | | 8 | 0 | |
| Queue Length 95th (ft) | | 228 | | 24 | 200 | | | 33 | | 31 | 0 | |
| Internal Link Dist (ft) | | 386 | | | 1483 | | | 338 | | | 179 | |
| Turn Bay Length (ft) | | | | 150 | | | | | | | | |
| Base Capacity (vph) | | 3416 | | 542 | 3574 | | | 1046 | | 933 | 1133 | |
| Starvation Cap Reductn | | 118 | | 0 | 0 | | | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.33 | | 0.04 | 0.44 | | | 0.07 | | 0.03 | 0.00 | |

**Intersection Summary**

Area Type: Other
Cycle Length: 120
Actuated Cycle Length: 52.1
Natural Cycle: 85
Control Type: Actuated-Uncoordinated
Maximum v/c Ratio: 0.62
Intersection Signal Delay (s/veh): 7.7 Intersection LOS: A
Intersection Capacity Utilization 59.3% ICU Level of Service B
Analysis Period (min) 15

Splits and Phases: 15: Hillcrest Dr/Driveway 6 & Maple Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 293 | 600 | 79 | 190 | 854 | 222 | 98 | 333 | 116 | 181 | 438 | 499 |
| Future Volume (vph) | 293 | 600 | 79 | 190 | 854 | 222 | 98 | 333 | 116 | 181 | 438 | 499 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 100 | | 0 | 150 | | 150 | 200 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 1 | | 1 | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | 0.97 | 1.00 | | | | | | | | 0.99 |
| Frt | | | 0.850 | | | 0.850 | | | 0.850 | | | 0.850 |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 3574 | 1599 | 1787 | 1881 | 1599 | 1787 | 1881 | 1599 |
| Flt Permitted | 0.107 | | | 0.394 | | | 0.164 | | | 0.232 | | |
| Satd. Flow (perm) | 201 | 3574 | 1556 | 739 | 3574 | 1599 | 309 | 1881 | 1599 | 436 | 1881 | 1575 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 113 | | | 158 | | | 157 | | | 378 |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 45 | |
| Link Distance (ft) | | 1563 | | | 492 | | | 510 | | | 929 | |
| Travel Time (s) | | 23.7 | | | 7.5 | | | 9.9 | | | 14.1 | |
| Confl. Peds. (#/hr) | | | 3 | 3 | | | 2 | | | | | 2 |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 305 | 625 | 82 | 198 | 890 | 231 | 102 | 347 | 121 | 189 | 456 | 520 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 305 | 625 | 82 | 198 | 890 | 231 | 102 | 347 | 121 | 189 | 456 | 520 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm |
| Protected Phases | 1 | 6 | | 5 | 2 | | 7 | 4 | | 3 | 8 | |
| Permitted Phases | 6 | | 6 | 2 | | 2 | 4 | | 4 | 8 | | 8 |
| Detector Phase | 1 | 6 | 6 | 5 | 2 | 2 | 7 | 4 | 4 | 3 | 8 | 8 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 | 10.0 | 3.0 | 6.0 | 6.0 | 3.0 | 6.0 | 6.0 |
| Minimum Split (s) | 10.2 | 39.5 | 39.5 | 9.8 | 38.8 | 38.8 | 10.2 | 45.3 | 45.3 | 9.6 | 45.3 | 45.3 |
| Total Split (s) | 45.0 | 63.0 | 63.0 | 25.0 | 43.0 | 43.0 | 25.0 | 47.0 | 47.0 | 25.0 | 47.0 | 47.0 |
| Total Split (%) | 28.1% | 39.4% | 39.4% | 15.6% | 26.9% | 26.9% | 15.6% | 29.4% | 29.4% | 15.6% | 29.4% | 29.4% |
| Maximum Green (s) | 38.5 | 56.5 | 56.5 | 18.6 | 36.6 | 36.6 | 18.5 | 40.5 | 40.5 | 18.4 | 40.4 | 40.4 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 3.6 | 3.6 | 3.6 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 2.2 | 2.2 | 2.2 | 2.1 | 2.1 | 2.1 | 2.9 | 2.9 | 2.9 | 2.3 | 2.3 | 2.3 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 6.5 | 6.5 | 6.5 | 6.4 | 6.4 | 6.4 | 6.5 | 6.5 | 6.5 | 6.6 | 6.6 | 6.6 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 |
| Recall Mode | None | C-Max | C-Max | None | C-Max | C-Max | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 26.0 | 26.0 | | 25.0 | 25.0 | | 26.0 | 26.0 | | 26.0 | 26.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 3 | 3 | | 2 | 2 | | 2 | 2 |
| Act Effct Green (s) | 84.0 | 63.5 | 63.5 | 65.3 | 51.2 | 51.2 | 51.9 | 41.1 | 41.1 | 60.9 | 45.6 | 45.6 |
| Actuated g/C Ratio | 0.53 | 0.40 | 0.40 | 0.41 | 0.32 | 0.32 | 0.32 | 0.26 | 0.26 | 0.38 | 0.29 | 0.29 |
| v/c Ratio | 0.83 | 0.44 | 0.12 | 0.50 | 0.78 | 0.37 | 0.51 | 0.72 | 0.23 | 0.64 | 0.85 | 0.72 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | 55.7 | 37.6 | 2.4 | 26.7 | 48.8 | 10.8 | 40.3 | 63.6 | 3.3 | 42.9 | 69.5 | 19.7 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 55.7 | 37.6 | 2.4 | 26.7 | 48.8 | 10.8 | 40.3 | 63.6 | 3.3 | 42.9 | 69.5 | 19.7 |
| LOS | E | D | A | C | D | B | D | E | A | D | E | B |
| Approach Delay (s/veh) | | 40.2 | | | 38.9 | | | 46.6 | | | 42.9 | |
| Approach LOS | | D | | | D | | | D | | | D | |
| Queue Length 50th (ft) | 233 | 257 | 0 | 81 | 498 | 34 | 67 | 327 | 0 | 130 | 442 | 132 |
| Queue Length 95th (ft) | 336 | 331 | 17 | 109 | #666 | 80 | 110 | 457 | 23 | 192 | #653 | 291 |
| Internal Link Dist (ft) | | 1483 | | | 412 | | | 430 | | | 849 | |
| Turn Bay Length (ft) | 200 | | 200 | 100 | | | 150 | | 150 | 200 | | |
| Base Capacity (vph) | 487 | 1419 | 686 | 444 | 1144 | 619 | 285 | 492 | 534 | 325 | 536 | 719 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.63 | 0.44 | 0.12 | 0.45 | 0.78 | 0.37 | 0.36 | 0.71 | 0.23 | 0.58 | 0.85 | 0.72 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 117 (73%), Referenced to phase 2:WBTL and 6:EBTL, Start of Yellow | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.85 | | | |
| Intersection Signal Delay (s/veh): 41.5 | | Intersection LOS: D | |
| Intersection Capacity Utilization 90.3% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 16: Sweet Home Rd & Maple Rd







| Lane Group | EBU | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | |
| Traffic Volume (vph) | 2 | 12 | 794 | 887 | 236 | 37 | 137 |
| Future Volume (vph) | 2 | 12 | 794 | 887 | 236 | 37 | 137 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 100 | | | 115 | 0 | 0 |
| Storage Lanes | | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | |
| Lane Util. Factor | 0.95 | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 |
| Frt | | | | | 0.850 | | 0.850 |
| Flt Protected | | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1787 | 3574 | 3574 | 1599 | 1787 | 1599 |
| Flt Permitted | | 0.303 | | | | 0.950 | |
| Satd. Flow (perm) | 0 | 570 | 3574 | 3574 | 1599 | 1787 | 1599 |
| Right Turn on Red | | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | | | | | 136 |
| Link Speed (mph) | | | 45 | 45 | | 45 | |
| Link Distance (ft) | | | 3286 | 644 | | 265 | |
| Travel Time (s) | | | 49.8 | 9.8 | | 4.0 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 2 | 13 | 827 | 924 | 246 | 39 | 143 |
| Shared Lane Traffic (%) | | | | | | | |
| Lane Group Flow (vph) | 0 | 15 | 827 | 924 | 246 | 39 | 143 |
| Turn Type | Perm | Perm | NA | NA | custom | Prot | Perm |
| Protected Phases | | | 2 | 6 | 8 6 | 8 | |
| Permitted Phases | 2 | 2 | | | 8 | | 8 |
| Detector Phase | 2 | 2 | 2 | 6 | 8 6 | 8 | 8 |
| Switch Phase | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | 10.0 | | 6.0 | 6.0 |
| Minimum Split (s) | 35.3 | 35.3 | 35.3 | 35.3 | | 13.9 | 13.9 |
| Total Split (s) | 100.0 | 100.0 | 100.0 | 100.0 | | 60.0 | 60.0 |
| Total Split (%) | 62.5% | 62.5% | 62.5% | 62.5% | | 37.5% | 37.5% |
| Maximum Green (s) | 93.7 | 93.7 | 93.7 | 93.7 | | 53.8 | 53.8 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | | 1.9 | 1.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.3 | 6.3 | 6.3 | | 6.2 | 6.2 |
| Lead/Lag | | | | | | | |
| Lead-Lag Optimize? | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | C-Min | C-Min | C-Min | C-Min | | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | | | |
| Flash Don't Walk (s) | 22.0 | 22.0 | 22.0 | 22.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | | | |
| Act Effct Green (s) | | 135.3 | 135.3 | 135.3 | 160.0 | 12.2 | 12.2 |
| Actuated g/C Ratio | | 0.85 | 0.85 | 0.85 | 1.00 | 0.08 | 0.08 |
| v/c Ratio | | 0.03 | 0.27 | 0.31 | 0.15 | 0.29 | 0.58 |
| Control Delay (s/veh) | | 0.9 | 0.9 | 2.8 | 0.2 | 74.0 | 21.5 |
| Queue Delay | | 0.0 | 0.0 | 0.2 | 0.0 | 0.0 | 0.0 |

| Lane Group | EBU | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 0.9 | 0.9 | 3.0 | 0.2 | 74.0 | 21.5 |
| LOS | | A | A | A | A | E | C |
| Approach Delay (s/veh) | | | 0.9 | 2.4 | | 32.7 | |
| Approach LOS | | | A | A | | C | |
| Queue Length 50th (ft) | | 1 | 21 | 82 | 0 | 39 | 7 |
| Queue Length 95th (ft) | | m2 | 28 | 108 | 0 | 80 | 78 |
| Internal Link Dist (ft) | | | 3206 | 564 | | 185 | |
| Turn Bay Length (ft) | | 100 | | | 115 | | |
| Base Capacity (vph) | | 482 | 3022 | 3022 | 1599 | 600 | 627 |
| Starvation Cap Reductn | | 0 | 0 | 1180 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.03 | 0.27 | 0.50 | 0.15 | 0.07 | 0.23 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 121 (76%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.58 | | | |
| Intersection Signal Delay (s/veh): 4.3 | | Intersection LOS: A | |
| Intersection Capacity Utilization 43.4% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 17: Maple Rd & Millersprt Hwy SB Rmps






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 83 | 871 | 0 | 0 | 1040 | 15 | 56 | 2 | 560 | 0 | 0 | 0 |
| Future Volume (vph) | 83 | 871 | 0 | 0 | 1040 | 15 | 56 | 2 | 560 | 0 | 0 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 0 | 1 | | 0 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | | | 0.998 | | | 0.851 | | | | |
| Flt Protected | 0.950 | | | | | | 0.950 | | | | | |
| Satd. Flow (prot) | 1787 | 3574 | 0 | 0 | 3567 | 0 | 1787 | 1601 | 0 | 0 | 0 | 0 |
| Flt Permitted | 0.175 | | | | | | 0.950 | | | | | |
| Satd. Flow (perm) | 329 | 3574 | 0 | 0 | 3567 | 0 | 1787 | 1601 | 0 | 0 | 0 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | 1 | | | 105 | | | | |
| Link Speed (mph) | | 45 | | | 45 | | | 45 | | | 45 | |
| Link Distance (ft) | | 644 | | | 547 | | | 1142 | | | 667 | |
| Travel Time (s) | | 9.8 | | | 8.3 | | | 17.3 | | | 10.1 | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 88 | 927 | 0 | 0 | 1106 | 16 | 60 | 2 | 596 | 0 | 0 | 0 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 88 | 927 | 0 | 0 | 1122 | 0 | 60 | 598 | 0 | 0 | 0 | 0 |
| Turn Type | Perm | NA | | | NA | | Perm | NA | | | | |
| Protected Phases | | 2 | | | 6 | | | 4 | | | | |
| Permitted Phases | 2 | | | | | | 4 | | | | | |
| Detector Phase | 2 | 2 | | | 6 | | 4 | 4 | | | | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 20.0 | 20.0 | | | 20.0 | | 6.0 | 6.0 | | | | |
| Minimum Split (s) | 29.0 | 29.0 | | | 29.0 | | 23.0 | 23.0 | | | | |
| Total Split (s) | 90.0 | 90.0 | | | 90.0 | | 70.0 | 70.0 | | | | |
| Total Split (%) | 56.3% | 56.3% | | | 56.3% | | 43.8% | 43.8% | | | | |
| Maximum Green (s) | 84.0 | 84.0 | | | 84.0 | | 63.8 | 63.8 | | | | |
| Yellow Time (s) | 4.3 | 4.3 | | | 4.3 | | 4.3 | 4.3 | | | | |
| All-Red Time (s) | 1.7 | 1.7 | | | 1.7 | | 1.9 | 1.9 | | | | |
| Lost Time Adjust (s) | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | | | | |
| Total Lost Time (s) | 6.0 | 6.0 | | | 6.0 | | 6.2 | 6.2 | | | | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | | 3.0 | | 3.0 | 3.0 | | | | |
| Recall Mode | C-Max | C-Max | | | C-Max | | None | None | | | | |
| Walk Time (s) | 7.0 | 7.0 | | | 7.0 | | | | | | | |
| Flash Don't Walk (s) | 16.0 | 16.0 | | | 16.0 | | | | | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | 0 | | | | | | | |
| Act Effct Green (s) | 90.4 | 90.4 | | | 90.4 | | 57.4 | 57.4 | | | | |
| Actuated g/C Ratio | 0.57 | 0.57 | | | 0.57 | | 0.36 | 0.36 | | | | |
| v/c Ratio | 0.48 | 0.46 | | | 0.56 | | 0.09 | 0.93 | | | | |
| Control Delay (s/veh) | 34.4 | 22.4 | | | 24.4 | | 32.3 | 62.3 | | | | |
| Queue Delay | 0.0 | 0.5 | | | 0.0 | | 0.0 | 0.0 | | | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 34.4 | 23.0 | | | 24.4 | | 32.3 | 62.3 | | | | |
| LOS | C | C | | | C | | C | E | | | | |
| Approach Delay (s/veh) | | 24.0 | | | 24.4 | | | 59.6 | | | | |
| Approach LOS | | C | | | C | | | E | | | | |
| Queue Length 50th (ft) | 71 | 389 | | | 396 | | 40 | 506 | | | | |
| Queue Length 95th (ft) | 138 | 457 | | | 488 | | 72 | #690 | | | | |
| Internal Link Dist (ft) | | 564 | | | 467 | | | 1062 | | | 587 | |
| Turn Bay Length (ft) | 150 | | | | | | | | | | | |
| Base Capacity (vph) | 185 | 2019 | | | 2015 | | 712 | 701 | | | | |
| Starvation Cap Reductn | 0 | 629 | | | 0 | | 0 | 0 | | | | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Storage Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Reduced v/c Ratio | 0.48 | 0.67 | | | 0.56 | | 0.08 | 0.85 | | | | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 80 (50%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 70 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.93 | | | |
| Intersection Signal Delay (s/veh): 32.5 | | Intersection LOS: C | |
| Intersection Capacity Utilization 95.8% | | ICU Level of Service F | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 18: Millersprt Hwy NB Rmps & Maple Rd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT | NWR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 40 | 820 | 181 | 0 | 970 | 116 | 187 | 240 | 6 | 108 | 206 | 37 |
| Future Volume (vph) | 40 | 820 | 181 | 0 | 970 | 116 | 187 | 240 | 6 | 108 | 206 | 37 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 450 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Frt | | | 0.850 | | 0.984 | | | 0.998 | | | 0.984 | |
| Flt Protected | 0.950 | | | | | | | 0.979 | | | 0.985 | |
| Satd. Flow (prot) | 1787 | 5136 | 1599 | 0 | 5053 | 0 | 0 | 3492 | 0 | 0 | 3464 | 0 |
| Flt Permitted | 0.187 | | | | | | | 0.979 | | | 0.985 | |
| Satd. Flow (perm) | 352 | 5136 | 1599 | 0 | 5053 | 0 | 0 | 3492 | 0 | 0 | 3464 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 187 | | 26 | | | 1 | | | 11 | |
| Link Speed (mph) | | 40 | | | 40 | | | 30 | | | 30 | |
| Link Distance (ft) | | 1892 | | | 623 | | | 1712 | | | 718 | |
| Travel Time (s) | | 32.3 | | | 10.6 | | | 38.9 | | | 16.3 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 41 | 845 | 187 | 0 | 1000 | 120 | 193 | 247 | 6 | 111 | 212 | 38 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 41 | 845 | 187 | 0 | 1120 | 0 | 0 | 446 | 0 | 0 | 361 | 0 |
| Turn Type | Perm | NA | Perm | | NA | | Split | NA | | Split | NA | |
| Protected Phases | | 1 | | | 1 | | 3 | 3 | | 4 | 4 | |
| Permitted Phases | 1 | | 1 | | | | | | | | | |
| Detector Phase | 1 | 1 | 1 | | 1 | | 3 | 3 | | 4 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 15.0 | 15.0 | 15.0 | | 15.0 | | 6.0 | 6.0 | | 6.0 | 6.0 | |
| Minimum Split (s) | 50.0 | 50.0 | 50.0 | | 50.0 | | 70.9 | 70.9 | | 70.9 | 70.9 | |
| Total Split (s) | 45.0 | 45.0 | 45.0 | | 45.0 | | 25.0 | 25.0 | | 25.0 | 25.0 | |
| Total Split (%) | 47.4% | 47.4% | 47.4% | | 47.4% | | 26.3% | 26.3% | | 26.3% | 26.3% | |
| Maximum Green (s) | 37.0 | 37.0 | 37.0 | | 37.0 | | 16.1 | 16.1 | | 16.1 | 16.1 | |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.6 | 3.6 | | 3.6 | 3.6 | |
| All-Red Time (s) | 4.0 | 4.0 | 4.0 | | 4.0 | | 5.3 | 5.3 | | 5.3 | 5.3 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Lost Time (s) | 8.0 | 8.0 | 8.0 | | 8.0 | | | 8.9 | | | 8.9 | |
| Lead/Lag | | | | | | | Lead | Lead | | Lag | Lag | |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | | Yes | Yes | |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.5 | 3.5 | | 3.5 | 3.5 | |
| Recall Mode | Min | Min | Min | | Min | | None | None | | None | None | |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | | 7.0 | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | | 35.0 | | | | | 55.0 | 55.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | | 0 | | | | | 0 | 0 | |
| Act Effct Green (s) | 36.2 | 36.2 | 36.2 | | 36.2 | | | 15.2 | | | 14.2 | |
| Actuated g/C Ratio | 0.40 | 0.40 | 0.40 | | 0.40 | | | 0.17 | | | 0.16 | |
| v/c Ratio | 0.29 | 0.42 | 0.25 | | 0.56 | | | 0.77 | | | 0.66 | |
| Control Delay (s/veh) | 27.2 | 21.1 | 3.9 | | 22.5 | | | 46.5 | | | 41.9 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT | NWR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 27.2 | 21.1 | 3.9 | | 22.5 | | | 46.5 | | | 41.9 | |
| LOS | C | C | A | | C | | | D | | | D | |
| Approach Delay (s/veh) | | 18.3 | | | 22.5 | | | 46.5 | | | 41.9 | |
| Approach LOS | | B | | | C | | | D | | | D | |
| Queue Length 50th (ft) | 16 | 131 | 0 | | 181 | | | 134 | | | 103 | |
| Queue Length 95th (ft) | 47 | 169 | 41 | | 229 | | | #191 | | | 151 | |
| Internal Link Dist (ft) | | 1812 | | | 543 | | | 1632 | | | 638 | |
| Turn Bay Length (ft) | 200 | | 450 | | | | | | | | | |
| Base Capacity (vph) | 142 | 2083 | 759 | | 2065 | | | 617 | | | 620 | |
| Starvation Cap Reductn | 0 | 0 | 0 | | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | 0 | 0 | 0 | | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | 0 | 0 | 0 | | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | 0.29 | 0.41 | 0.25 | | 0.54 | | | 0.72 | | | 0.58 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 95 | | | |
| Actuated Cycle Length: 91.5 | | | |
| Natural Cycle: 195 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.77 | | | |
| Intersection Signal Delay (s/veh): 26.9 | | Intersection LOS: C | |
| Intersection Capacity Utilization 77.0% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 19: Eggert Rd & Sheridan Dr



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 25 | 129 | 685 | 43 | 8 | 55 | 987 | 67 | 36 | 66 | 18 | 130 |
| Future Volume (vph) | 25 | 129 | 685 | 43 | 8 | 55 | 987 | 67 | 36 | 66 | 18 | 130 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 235 | | 0 | | 240 | | 0 | 0 | | 100 | 0 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 0 | | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.991 | | | | 0.990 | | | 0.977 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | | 0.985 | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5089 | 0 | 0 | 1787 | 5084 | 0 | 0 | 3440 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | | 0.780 | | 0.451 |
| Satd. Flow (perm) | 0 | 1787 | 5089 | 0 | 0 | 1787 | 5084 | 0 | 0 | 2724 | 0 | 848 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 9 | | | | 8 | | | 11 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1468 | | | | 969 | | | 165 | | |
| Travel Time (s) | | | 25.0 | | | | 16.5 | | | 3.8 | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 26 | 134 | 714 | 45 | 8 | 57 | 1028 | 70 | 38 | 69 | 19 | 135 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 160 | 759 | 0 | 0 | 65 | 1098 | 0 | 0 | 126 | 0 | 135 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 6.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 10.0 | 10.0 | 29.2 | | 10.0 | 10.0 | 43.2 | | 22.5 | 22.5 | | 11.0 |
| Total Split (s) | 39.0 | 39.0 | 87.0 | | 20.0 | 20.0 | 68.0 | | 33.0 | 33.0 | | 20.0 |
| Total Split (%) | 24.4% | 24.4% | 54.4% | | 12.5% | 12.5% | 42.5% | | 20.6% | 20.6% | | 12.5% |
| Maximum Green (s) | 32.8 | 32.8 | 80.8 | | 13.8 | 13.8 | 61.8 | | 26.1 | 26.1 | | 14.0 |
| Yellow Time (s) | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | | 3.2 |
| All-Red Time (s) | 2.6 | 2.6 | 2.6 | | 2.6 | 2.6 | 2.6 | | 3.3 | 3.3 | | 2.8 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | | 6.9 | | 6.0 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | Min | Min | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | | | |
| Flash Don't Walk (s) | | | 16.0 | | | | 15.0 | | | | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | | | |
| Act Effct Green (s) | | 19.6 | 97.7 | | | 11.2 | 86.7 | | | 12.2 | | 35.3 |
| Actuated g/C Ratio | | 0.12 | 0.61 | | | 0.07 | 0.54 | | | 0.08 | | 0.22 |
| v/c Ratio | | 0.73 | 0.24 | | | 0.52 | 0.40 | | | 0.58 | | 0.48 |
| Control Delay (s/veh) | | 86.3 | 16.0 | | | 102.4 | 9.4 | | | 75.2 | | 56.9 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |




| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 105 | 163 |
| Future Volume (vph) | 105 | 163 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.909 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1710 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1710 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 49 | |
| Link Speed (mph) | 35 | |
| Link Distance (ft) | 3326 | |
| Travel Time (s) | 64.8 | |
| Peak Hour Factor | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 109 | 170 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 279 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 43.9 | |
| Total Split (s) | 53.0 | |
| Total Split (%) | 33.1% | |
| Maximum Green (s) | 46.1 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.9 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 27.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 34.4 | |
| Actuated g/C Ratio | 0.22 | |
| v/c Ratio | 0.69 | |
| Control Delay (s/veh) | 55.5 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 86.3 | 16.0 | | | 102.4 | 9.4 | | | 75.2 | | 56.9 |
| LOS | | F | B | | | F | A | | | E | | E |
| Approach Delay (s/veh) | | | 28.2 | | | | 14.6 | | | 75.2 | | |
| Approach LOS | | | C | | | | B | | | E | | |
| Queue Length 50th (ft) | | 164 | 132 | | | 71 | 86 | | | 62 | | 120 |
| Queue Length 95th (ft) | | 237 | 193 | | | m126 | 94 | | | 98 | | 174 |
| Internal Link Dist (ft) | | | 1388 | | | | 889 | | | 85 | | |
| Turn Bay Length (ft) | | 235 | | | | 240 | | | | | | |
| Base Capacity (vph) | | 366 | 3111 | | | 158 | 2757 | | | 453 | | 286 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Reduced v/c Ratio | | 0.44 | 0.24 | | | 0.41 | 0.40 | | | 0.28 | | 0.47 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 28 (18%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.73 | | | |
| Intersection Signal Delay (s/veh): 28.8 | | Intersection LOS: C | |
| Intersection Capacity Utilization 71.4% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |


Splits and Phases: 20: Alberta Dr & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 55.5 | |
| LOS | E | |
| Approach Delay (s/veh) | 56.0 | |
| Approach LOS | E | |
| Queue Length 50th (ft) | 226 | |
| Queue Length 95th (ft) | 309 | |
| Internal Link Dist (ft) | 3246 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 527 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.53 | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 20 | 109 | 721 | 55 | 9 | 115 | 916 | 109 | 95 | 371 | 88 | 118 |
| Future Volume (vph) | 20 | 109 | 721 | 55 | 9 | 115 | 916 | 109 | 95 | 371 | 88 | 118 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 230 | | 0 | | 270 | | 0 | 190 | | 0 | 240 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.989 | | | | 0.984 | | | 0.971 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5079 | 0 | 0 | 1787 | 5053 | 0 | 1787 | 3471 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.310 | | | 0.205 |
| Satd. Flow (perm) | 0 | 1787 | 5079 | 0 | 0 | 1787 | 5053 | 0 | 583 | 3471 | 0 | 386 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 8 | | | | 14 | | | 16 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 969 | | | | 1628 | | | 537 | | |
| Travel Time (s) | | | 16.5 | | | | 27.8 | | | 12.2 | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 20 | 111 | 736 | 56 | 9 | 117 | 935 | 111 | 97 | 379 | 90 | 120 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 131 | 792 | 0 | 0 | 126 | 1046 | 0 | 97 | 469 | 0 | 120 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | pm+pt | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 10.0 | 10.0 | 43.5 | | 10.0 | 10.0 | 43.5 | | 10.0 | 41.0 | | 10.0 |
| Total Split (s) | 30.0 | 30.0 | 52.0 | | 38.0 | 38.0 | 60.0 | | 29.0 | 41.0 | | 29.0 |
| Total Split (%) | 18.8% | 18.8% | 32.5% | | 23.8% | 23.8% | 37.5% | | 18.1% | 25.6% | | 18.1% |
| Maximum Green (s) | 23.6 | 23.6 | 45.5 | | 31.6 | 31.6 | 53.5 | | 22.3 | 34.3 | | 22.3 |
| Yellow Time (s) | 3.6 | 3.6 | 3.9 | | 3.6 | 3.6 | 3.9 | | 3.6 | 3.6 | | 3.6 |
| All-Red Time (s) | 2.8 | 2.8 | 2.6 | | 2.8 | 2.8 | 2.6 | | 3.1 | 3.1 | | 3.1 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.4 | 6.5 | | | 6.4 | 6.5 | | 6.7 | 6.7 | | 6.7 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lead | Lag | | Lead |
| Lead-Lag Optimize? | | | Yes | | Yes | Yes | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | 7.0 | | |
| Flash Don't Walk (s) | | | 21.0 | | | | 21.0 | | | 24.4 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | 0 | | |
| Act Effct Green (s) | | 17.0 | 76.6 | | | 16.6 | 76.2 | | 38.4 | 26.7 | | 42.6 |
| Actuated g/C Ratio | | 0.11 | 0.48 | | | 0.10 | 0.48 | | 0.24 | 0.17 | | 0.27 |
| v/c Ratio | | 0.69 | 0.33 | | | 0.68 | 0.43 | | 0.43 | 0.79 | | 0.54 |
| Control Delay (s/veh) | | 105.8 | 20.0 | | | 123.3 | 10.3 | | 46.3 | 71.7 | | 50.1 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |




| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 335 | 88 |
| Future Volume (vph) | 335 | 88 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 280 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 0.95 |
| Frt | 0.969 | |
| Flt Protected | | |
| Satd. Flow (prot) | 3463 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3463 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 19 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 495 | |
| Travel Time (s) | 11.3 | |
| Peak Hour Factor | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 342 | 90 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 432 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 41.0 | |
| Total Split (s) | 41.0 | |
| Total Split (%) | 25.6% | |
| Maximum Green (s) | 34.3 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.1 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.7 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 23.6 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 28.8 | |
| Actuated g/C Ratio | 0.18 | |
| v/c Ratio | 0.68 | |
| Control Delay (s/veh) | 63.5 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 105.8 | 20.0 | | | 123.3 | 10.3 | | 46.3 | 71.7 | | 50.1 |
| LOS | | F | B | | | F | B | | D | E | | D |
| Approach Delay (s/veh) | | | 32.1 | | | | 22.5 | | | 67.3 | | |
| Approach LOS | | | C | | | | C | | | E | | |
| Queue Length 50th (ft) | | 144 | 110 | | | 140 | 61 | | 76 | 242 | | 95 |
| Queue Length 95th (ft) | | 219 | 128 | | | 215 | 75 | | 115 | 295 | | 138 |
| Internal Link Dist (ft) | | | 889 | | | | 1548 | | | 457 | | |
| Turn Bay Length (ft) | | 230 | | | | 270 | | | 190 | | | 240 |
| Base Capacity (vph) | | 263 | 2436 | | | 352 | 2415 | | 337 | 756 | | 309 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.50 | 0.33 | | | 0.36 | 0.43 | | 0.29 | 0.62 | | 0.39 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 4 (3%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.79 | | | |
| Intersection Signal Delay (s/veh): 39.7 | | Intersection LOS: D | |
| Intersection Capacity Utilization 68.8% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 21: Bailey Ave & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 63.5 | |
| LOS | E | |
| Approach Delay (s/veh) | 60.6 | |
| Approach LOS | E | |
| Queue Length 50th (ft) | 214 | |
| Queue Length 95th (ft) | 263 | |
| Internal Link Dist (ft) | 415 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 763 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.57 | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 8 | 156 | 761 | 21 | 20 | 49 | 946 | 122 | 27 | 264 | 40 | 103 |
| Future Volume (vph) | 8 | 156 | 761 | 21 | 20 | 49 | 946 | 122 | 27 | 264 | 40 | 103 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 200 | | 0 | | 190 | | 0 | 85 | | 0 | 305 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.996 | | | | 0.983 | | | 0.980 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5115 | 0 | 0 | 1787 | 5048 | 0 | 1787 | 1844 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.494 | | | 0.182 |
| Satd. Flow (perm) | 0 | 1787 | 5115 | 0 | 0 | 1787 | 5048 | 0 | 929 | 1844 | 0 | 342 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 3 | | | | 17 | | | 4 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1628 | | | | 2376 | | | 1485 | | |
| Travel Time (s) | | | 27.8 | | | | 40.5 | | | 33.8 | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 8 | 159 | 777 | 21 | 20 | 50 | 965 | 124 | 28 | 269 | 41 | 105 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 167 | 798 | 0 | 0 | 70 | 1089 | 0 | 28 | 310 | 0 | 105 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 6.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 12.2 | 12.2 | 43.2 | | 12.2 | 12.2 | 43.2 | | 42.0 | 42.0 | | 12.1 |
| Total Split (s) | 21.0 | 21.0 | 60.0 | | 31.0 | 31.0 | 70.0 | | 42.0 | 42.0 | | 27.0 |
| Total Split (%) | 13.1% | 13.1% | 37.5% | | 19.4% | 19.4% | 43.8% | | 26.3% | 26.3% | | 16.9% |
| Maximum Green (s) | 14.8 | 14.8 | 53.8 | | 24.8 | 24.8 | 63.8 | | 34.9 | 34.9 | | 19.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | 3.9 | | 3.2 | 3.2 | | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | 2.3 | | 3.9 | 3.9 | | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | 7.1 | 7.1 | | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | | Yes | Yes | | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | | | 17.0 | | | | 18.0 | | 27.0 | 27.0 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | 0 | 0 | | |
| Act Effct Green (s) | | 23.3 | 76.7 | | | 11.6 | 65.1 | | 31.9 | 31.9 | | 52.2 |
| Actuated g/C Ratio | | 0.15 | 0.48 | | | 0.07 | 0.41 | | 0.20 | 0.20 | | 0.33 |
| v/c Ratio | | 0.64 | 0.33 | | | 0.54 | 0.53 | | 0.15 | 0.84 | | 0.46 |
| Control Delay (s/veh) | | 76.6 | 43.3 | | | 86.2 | 38.1 | | 51.9 | 79.5 | | 42.9 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |




| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 252 | 128 |
| Future Volume (vph) | 252 | 128 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.949 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1785 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1785 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 19 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 1504 | |
| Travel Time (s) | 34.2 | |
| Peak Hour Factor | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 257 | 131 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 388 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 44.1 | |
| Total Split (s) | 69.0 | |
| Total Split (%) | 43.1% | |
| Maximum Green (s) | 61.9 | |
| Yellow Time (s) | 3.2 | |
| All-Red Time (s) | 3.9 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 7.1 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 30.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 52.2 | |
| Actuated g/C Ratio | 0.33 | |
| v/c Ratio | 0.65 | |
| Control Delay (s/veh) | 48.1 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 76.6 | 43.3 | | | 86.2 | 38.1 | | 51.9 | 79.5 | | 42.9 |
| LOS | | E | D | | | F | D | | D | E | | D |
| Approach Delay (s/veh) | | | 49.1 | | | | 41.0 | | | 77.2 | | |
| Approach LOS | | | D | | | | D | | | E | | |
| Queue Length 50th (ft) | | 172 | 199 | | | 72 | 310 | | 24 | 312 | | 79 |
| Queue Length 95th (ft) | | 257 | 367 | | | 125 | 413 | | 52 | 399 | | 113 |
| Internal Link Dist (ft) | | | 1548 | | | | 2296 | | | 1405 | | |
| Turn Bay Length (ft) | | 200 | | | | 190 | | | 85 | | | 305 |
| Base Capacity (vph) | | 259 | 2453 | | | 276 | 2182 | | 210 | 420 | | 291 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.64 | 0.33 | | | 0.25 | 0.50 | | 0.13 | 0.74 | | 0.36 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 133 (83%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 110 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.84 | | | |
| Intersection Signal Delay (s/veh): 48.8 | | Intersection LOS: D | |
| Intersection Capacity Utilization 78.3% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 22: Sweet Home Rd & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 48.1 | |
| LOS | D | |
| Approach Delay (s/veh) | 47.0 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 332 | |
| Queue Length 95th (ft) | 396 | |
| Internal Link Dist (ft) | 1424 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 710 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.55 | |

| Intersection Summary |
|---|

| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 3 | 237 | 663 | 26 | 162 | 714 | 85 | 38 | 402 | 120 | 92 | 697 |
| Future Volume (vph) | 3 | 237 | 663 | 26 | 162 | 714 | 85 | 38 | 402 | 120 | 92 | 697 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 315 | | 0 | 330 | | 0 | 110 | | 155 | 105 | |
| Storage Lanes | | 1 | | 0 | 1 | | 0 | 1 | | 1 | 1 | |
| Taper Length (ft) | | 25 | | | 25 | | | 25 | | | 25 | |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 |
| Frt | | | 0.994 | | | 0.984 | | | | 0.850 | | |
| Flt Protected | | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1787 | 5105 | 0 | 1787 | 5053 | 0 | 1787 | 3574 | 1599 | 1787 | 3574 |
| Flt Permitted | | 0.950 | | | 0.950 | | | 0.250 | | | 0.377 | |
| Satd. Flow (perm) | 0 | 1787 | 5105 | 0 | 1787 | 5053 | 0 | 470 | 3574 | 1599 | 709 | 3574 |
| Right Turn on Red | | | | Yes | | | Yes | | | Yes | | |
| Satd. Flow (RTOR) | | | 4 | | | 13 | | | | 124 | | |
| Link Speed (mph) | | | 40 | | | 40 | | | 30 | | | 30 |
| Link Distance (ft) | | | 2376 | | | 4032 | | | 1401 | | | 981 |
| Travel Time (s) | | | 40.5 | | | 68.7 | | | 31.8 | | | 22.3 |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 3 | 244 | 684 | 27 | 167 | 736 | 88 | 39 | 414 | 124 | 95 | 719 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 247 | 711 | 0 | 167 | 824 | 0 | 39 | 414 | 124 | 95 | 719 |
| Turn Type | Prot | Prot | NA | | Prot | NA | | pm+pt | NA | Perm | pm+pt | NA |
| Protected Phases | 1 | 1 | 6 | | 5 | 2 | | 3 | 8 | | 7 | 4 |
| Permitted Phases | | | | | | | | 8 | | 8 | 4 | |
| Detector Phase | 1 | 1 | 6 | | 5 | 2 | | 3 | 8 | 8 | 7 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | | 10.0 | 10.0 | | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 |
| Minimum Split (s) | 16.2 | 16.2 | 43.2 | | 16.2 | 44.2 | | 10.1 | 45.0 | 45.0 | 10.1 | 45.0 |
| Total Split (s) | 30.0 | 30.0 | 45.0 | | 30.0 | 45.0 | | 35.0 | 45.0 | 45.0 | 35.0 | 45.0 |
| Total Split (%) | 19.4% | 19.4% | 29.0% | | 19.4% | 29.0% | | 22.6% | 29.0% | 29.0% | 22.6% | 29.0% |
| Maximum Green (s) | 23.8 | 23.8 | 38.8 | | 23.8 | 38.8 | | 27.9 | 37.9 | 37.9 | 27.9 | 37.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | 6.2 | 6.2 | | 7.1 | 7.1 | 7.1 | 7.1 | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lag | | Lead | Lag | Lag | Lead | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | None | None | Min | | None | Min | | None | None | None | None | None |
| Walk Time (s) | | | 7.0 | | | 7.0 | | | 7.0 | 7.0 | | 7.0 |
| Flash Don't Walk (s) | | | 30.0 | | | 31.0 | | | 30.0 | 30.0 | | 30.0 |
| Pedestrian Calls (#/hr) | | | 0 | | | 0 | | | 0 | 0 | | 0 |
| Act Effct Green (s) | | 21.6 | 30.7 | | 16.5 | 25.6 | | 34.0 | 26.9 | 26.9 | 41.0 | 33.2 |
| Actuated g/C Ratio | | 0.19 | 0.28 | | 0.15 | 0.23 | | 0.31 | 0.24 | 0.24 | 0.37 | 0.30 |
| v/c Ratio | | 0.72 | 0.50 | | 0.63 | 0.70 | | 0.17 | 0.48 | 0.26 | 0.27 | 0.68 |
| Control Delay (s/veh) | | 57.4 | 36.8 | | 58.5 | 43.4 | | 24.2 | 38.8 | 7.8 | 24.5 | 39.9 |
| Queue Delay | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 304 |
| Future Volume (vph) | 304 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 285 |
| Storage Lanes | 1 |
| Taper Length (ft) | |
| Lane Util. Factor | 1.00 |
| Frt | 0.850 |
| Flt Protected | |
| Satd. Flow (prot) | 1599 |
| Flt Permitted | |
| Satd. Flow (perm) | 1599 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | 313 |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Peak Hour Factor | 0.97 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 313 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 313 |
| Turn Type | Prot |
| Protected Phases | 4 |
| Permitted Phases | |
| Detector Phase | 4 |
| Switch Phase | |
| Minimum Initial (s) | 10.0 |
| Minimum Split (s) | 45.0 |
| Total Split (s) | 45.0 |
| Total Split (%) | 29.0% |
| Maximum Green (s) | 37.9 |
| Yellow Time (s) | 3.2 |
| All-Red Time (s) | 3.9 |
| Lost Time Adjust (s) | 0.0 |
| Total Lost Time (s) | 7.1 |
| Lead/Lag | Lag |
| Lead-Lag Optimize? | Yes |
| Vehicle Extension (s) | 3.0 |
| Recall Mode | None |
| Walk Time (s) | 7.0 |
| Flash Don't Walk (s) | 30.0 |
| Pedestrian Calls (#/hr) | 0 |
| Act Effct Green (s) | 33.2 |
| Actuated g/C Ratio | 0.30 |
| v/c Ratio | 0.45 |
| Control Delay (s/veh) | 5.9 |
| Queue Delay | 0.0 |

| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 57.4 | 36.8 | | 58.5 | 43.4 | | 24.2 | 38.8 | 7.8 | 24.5 | 39.9 |
| LOS | | E | D | | E | D | | C | D | A | C | D |
| Approach Delay (s/veh) | | | 42.1 | | | 46.0 | | | 31.1 | | | 29.2 |
| Approach LOS | | | D | | | D | | | C | | | C |
| Queue Length 50th (ft) | | 174 | 161 | | 121 | 208 | | 18 | 137 | 0 | 44 | 255 |
| Queue Length 95th (ft) | | #318 | 234 | | 203 | 272 | | 43 | 205 | 49 | 86 | 354 |
| Internal Link Dist (ft) | | | 2296 | | | 3952 | | | 1321 | | | 901 |
| Turn Bay Length (ft) | | 315 | | | 330 | | | 110 | | 155 | 105 | |
| Base Capacity (vph) | | 394 | 1842 | | 394 | 1829 | | 528 | 1258 | 643 | 562 | 1258 |
| Starvation Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.63 | 0.39 | | 0.42 | 0.45 | | 0.07 | 0.33 | 0.19 | 0.17 | 0.57 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 155 | | | |
| Actuated Cycle Length: 111.4 | | | |
| Natural Cycle: 120 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.72 | | | |
| Intersection Signal Delay (s/veh): 37.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 73.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |


Splits and Phases: 23: Millersport Hwy & Sheridan Dr





| Lane Group | SBR |
|---|---|
| Total Delay (s/veh) | 5.9 |
| LOS | A |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | 0 |
| Queue Length 95th (ft) | 68 |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | 285 |
| Base Capacity (vph) | 765 |
| Starvation Cap Reductn | 0 |
| Spillback Cap Reductn | 0 |
| Storage Cap Reductn | 0 |
| Reduced v/c Ratio | 0.41 |

| Intersection Summary |
|---|





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 37 | 344 | 4 | 2 | 415 | 18 | 0 | 25 | 4 | 42 | 29 | 45 |
| Future Volume (vph) | 37 | 344 | 4 | 2 | 415 | 18 | 0 | 25 | 4 | 42 | 29 | 45 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.999 | | | 0.994 | | | 0.982 | | | 0.948 | |
| Flt Protected | | 0.995 | | | | | | | | | 0.982 | |
| Satd. Flow (prot) | 0 | 3553 | 0 | 0 | 3553 | 0 | 0 | 1847 | 0 | 0 | 1751 | 0 |
| Flt Permitted | | 0.892 | | | 0.954 | | | | | | 0.867 | |
| Satd. Flow (perm) | 0 | 3185 | 0 | 0 | 3389 | 0 | 0 | 1847 | 0 | 0 | 1546 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 3 | | | 16 | | | 4 | | | 46 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 25 | |
| Link Distance (ft) | | 1535 | | | 1128 | | | 417 | | | 659 | |
| Travel Time (s) | | 29.9 | | | 22.0 | | | 9.5 | | | 18.0 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 39 | 358 | 4 | 2 | 432 | 19 | 0 | 26 | 4 | 44 | 30 | 47 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 401 | 0 | 0 | 453 | 0 | 0 | 30 | 0 | 0 | 121 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | | NA | | Perm | NA | |
| Protected Phases | | 1 | | | 1 | | | 2 | | | 2 | |
| Permitted Phases | 1 | | | 1 | | | 2 | | | 2 | | |
| Detector Phase | 1 | 1 | | 1 | 1 | | 2 | 2 | | 2 | 2 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 25.0 | 25.0 | | 25.0 | 25.0 | | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | 30.0 | 30.0 | | 30.0 | 30.0 | | 23.0 | 23.0 | | 23.0 | 23.0 | |
| Total Split (s) | 45.0 | 45.0 | | 45.0 | 45.0 | | 15.0 | 15.0 | | 15.0 | 15.0 | |
| Total Split (%) | 75.0% | 75.0% | | 75.0% | 75.0% | | 25.0% | 25.0% | | 25.0% | 25.0% | |
| Maximum Green (s) | 40.0 | 40.0 | | 40.0 | 40.0 | | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Yellow Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | | 5.0 | | | 5.0 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | None | None | | None | None | |
| Walk Time (s) | | | | | | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | | | | | 11.0 | 11.0 | | 11.0 | 11.0 | |
| Pedestrian Calls (#/hr) | | | | | | | 0 | 0 | | 0 | 0 | |
| Act Effct Green (s) | | 29.0 | | | 29.0 | | | 10.0 | | | 10.0 | |
| Actuated g/C Ratio | | 0.64 | | | 0.64 | | | 0.22 | | | 0.22 | |
| v/c Ratio | | 0.20 | | | 0.21 | | | 0.07 | | | 0.32 | |
| Control Delay (s/veh) | | 5.0 | | | 4.8 | | | 13.2 | | | 12.8 | |
| Queue Delay | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Delay (s/veh) | | 5.0 | | | 4.8 | | | 13.2 | | | 12.8 | |
| LOS | | A | | | A | | | B | | | B | |
| Approach Delay (s/veh) | | 5.0 | | | 4.8 | | | 13.2 | | | 12.8 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Approach LOS | | A | | | A | | | B | | | B | |
| Queue Length 50th (ft) | | 23 | | | 25 | | | 5 | | | 16 | |
| Queue Length 95th (ft) | | 40 | | | 43 | | | 20 | | | 49 | |
| Internal Link Dist (ft) | | 1455 | | | 1048 | | | 337 | | | 579 | |
| Turn Bay Length (ft) | | | | | | | | | | | | |
| Base Capacity (vph) | | 3185 | | | 3389 | | | 413 | | | 379 | |
| Starvation Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | | 0.13 | | | 0.13 | | | 0.07 | | | 0.32 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 60 | | | |
| Actuated Cycle Length: 45 | | | |
| Natural Cycle: 55 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.32 | | | |
| Intersection Signal Delay (s/veh): 6.1 | | Intersection LOS: A | |
| Intersection Capacity Utilization 60.0% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 24: Alberta Dr & Eggert Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 36 | 273 | 101 | 39 | 294 | 119 | 110 | 350 | 51 | 120 | 327 | 46 |
| Future Volume (vph) | 36 | 273 | 101 | 39 | 294 | 119 | 110 | 350 | 51 | 120 | 327 | 46 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 150 | | 0 | 110 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 0.95 | 0.95 |
| Frt | | 0.963 | | | 0.961 | | | 0.981 | | | 0.981 | |
| Flt Protected | | 0.996 | | | 0.996 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3428 | 0 | 0 | 3421 | 0 | 1787 | 1845 | 0 | 1787 | 3506 | 0 |
| Flt Permitted | | 0.877 | | | 0.882 | | 0.522 | | | 0.363 | | |
| Satd. Flow (perm) | 0 | 3019 | 0 | 0 | 3030 | 0 | 982 | 1845 | 0 | 683 | 3506 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 59 | | | 68 | | | 11 | | | 23 | |
| Link Speed (mph) | | 30 | | | 30 | | | 30 | | | 30 | |
| Link Distance (ft) | | 1128 | | | 580 | | | 922 | | | 349 | |
| Travel Time (s) | | 25.6 | | | 13.2 | | | 21.0 | | | 7.9 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 38 | 284 | 105 | 41 | 306 | 124 | 115 | 365 | 53 | 125 | 341 | 48 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 427 | 0 | 0 | 471 | 0 | 115 | 418 | 0 | 125 | 389 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | | 4 | | | 8 | | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 4 | | | 8 | | | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | | 10.0 | 10.0 | | 5.0 | 10.0 | | 5.0 | 10.0 | |
| Minimum Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 10.0 | 37.0 | | 10.0 | 37.0 | |
| Total Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 11.0 | 37.0 | | 11.0 | 37.0 | |
| Total Split (%) | 40.0% | 40.0% | | 40.0% | 40.0% | | 13.8% | 46.3% | | 13.8% | 46.3% | |
| Maximum Green (s) | 27.0 | 27.0 | | 27.0 | 27.0 | | 6.0 | 32.0 | | 6.0 | 32.0 | |
| Yellow Time (s) | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| All-Red Time (s) | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | | | | | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | | Yes | Yes | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | None | None | | None | None | |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | 20.0 | 20.0 | | 20.0 | 20.0 | | | 25.0 | | | 25.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Act Effct Green (s) | | 14.1 | | | 14.1 | | 21.8 | 17.3 | | 21.8 | 17.3 | |
| Actuated g/C Ratio | | 0.28 | | | 0.28 | | 0.43 | 0.34 | | 0.43 | 0.34 | |
| v/c Ratio | | 0.48 | | | 0.53 | | 0.22 | 0.65 | | 0.29 | 0.32 | |
| Control Delay (s/veh) | | 16.6 | | | 17.0 | | 7.8 | 20.1 | | 8.6 | 13.0 | |
| Queue Delay | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 16.6 | | | 17.0 | | 7.8 | 20.1 | | 8.6 | 13.0 | |
| LOS | | B | | | B | | A | C | | A | B | |
| Approach Delay (s/veh) | | 16.6 | | | 17.0 | | | 17.5 | | | 11.9 | |
| Approach LOS | | B | | | B | | | B | | | B | |
| Queue Length 50th (ft) | | 48 | | | 53 | | 15 | 103 | | 16 | 42 | |
| Queue Length 95th (ft) | | 104 | | | 114 | | 43 | 213 | | 46 | 83 | |
| Internal Link Dist (ft) | | 1048 | | | 500 | | | 842 | | | 269 | |
| Turn Bay Length (ft) | | | | | | | 150 | | | 110 | | |
| Base Capacity (vph) | | 1772 | | | 1782 | | 527 | 1244 | | 436 | 2365 | |
| Starvation Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.24 | | | 0.26 | | 0.22 | 0.34 | | 0.29 | 0.16 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 80 | | | |
| Actuated Cycle Length: 50.4 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.65 | | | |
| Intersection Signal Delay (s/veh): 15.7 | | Intersection LOS: B | |
| Intersection Capacity Utilization 69.7% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 25: Bailey Ave & Eggert Rd




| Intersection | |
|---|---|
| Int Delay, s/veh | 3.5 |

| Movement | EBL | EBR | NBL | NBT | SBT | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 20 | 201 | 147 | 694 | 561 | 11 |
| Future Vol, veh/h | 20 | 201 | 147 | 694 | 561 | 11 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Free | Free | Free | Free |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | 180 | 0 | 165 | - | - | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 98 | 98 | 98 | 98 | 98 | 98 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 20 | 205 | 150 | 708 | 572 | 11 |

| Major/Minor | Minor2 | | Major1 | | Major2 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 1586 | 578 | 584 | 0 | - | 0 |
| Stage 1 | 578 | - | - | - | - | - |
| Stage 2 | 1008 | - | - | - | - | - |
| Critical Hdwy | 6.41 | 6.21 | 4.11 | - | - | - |
| Critical Hdwy Stg 1 | 5.41 | - | - | - | - | - |
| Critical Hdwy Stg 2 | 5.41 | - | - | - | - | - |
| Follow-up Hdwy | 3.509 | 3.309 | 2.209 | - | - | - |
| Pot Cap-1 Maneuver | 120 | 517 | 996 | - | - | - |
| Stage 1 | 563 | - | - | - | - | - |
| Stage 2 | 354 | - | - | - | - | - |
| Platoon blocked, % | | | | - | - | - |
| Mov Cap-1 Maneuver | 102 | 517 | 996 | - | - | - |
| Mov Cap-2 Maneuver | 102 | - | - | - | - | - |
| Stage 1 | 478 | - | - | - | - | - |
| Stage 2 | 354 | - | - | - | - | - |

| Approach | EB | NB | SB |
|---|---|---|---|
| HCM Control Delay, s/v | 19.41 | 1.62 | 0 |
| HCM LOS | C | | |

| Minor Lane/Major Mvmt | NBL | NBT | EBLn1 | EBLn2 | SBT | SBR |
|---|---|---|---|---|---|---|
| Capacity (veh/h) | 996 | - | 102 | 517 | - | - |
| HCM Lane V/C Ratio | 0.151 | - | 0.201 | 0.396 | - | - |
| HCM Control Delay (s/veh) | 9.3 | - | 49.1 | 16.5 | - | - |
| HCM Lane LOS | A | - | E | C | - | - |
| HCM 95th %tile Q(veh) | 0.5 | - | 0.7 | 1.9 | - | - |




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 99 | 31 | 60 | 7 | 24 | 123 | 28 | 628 | 29 | 90 | 656 | 65 |
| Future Volume (vph) | 99 | 31 | 60 | 7 | 24 | 123 | 28 | 628 | 29 | 90 | 656 | 65 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 70 | 170 | | 0 | 150 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 1 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.957 | | | | 0.850 | | 0.993 | | | 0.986 | |
| Flt Protected | | 0.975 | | | 0.989 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 1755 | 0 | 0 | 1860 | 1599 | 1787 | 1868 | 0 | 1787 | 1855 | 0 |
| Flt Permitted | | 0.820 | | | 0.921 | | 0.259 | | | 0.304 | | |
| Satd. Flow (perm) | 0 | 1476 | 0 | 0 | 1733 | 1599 | 487 | 1868 | 0 | 572 | 1855 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 24 | | | | 127 | | 5 | | | 12 | |
| Link Speed (mph) | | 30 | | | 30 | | | 35 | | | 35 | |
| Link Distance (ft) | | 710 | | | 507 | | | 1039 | | | 1225 | |
| Travel Time (s) | | 16.1 | | | 11.5 | | | 20.2 | | | 23.9 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 102 | 32 | 62 | 7 | 25 | 127 | 29 | 647 | 30 | 93 | 676 | 67 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 196 | 0 | 0 | 32 | 127 | 29 | 677 | 0 | 93 | 743 | 0 |
| Turn Type | Perm | NA | | Perm | NA | Perm | Perm | NA | | Perm | NA | |
| Protected Phases | | 4 | | | 8 | | | 2 | | | 6 | |
| Permitted Phases | 4 | | | 8 | | 8 | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | 8 | 2 | 2 | | 6 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | | 10.0 | 10.0 | 10.0 | 30.0 | 30.0 | | 30.0 | 30.0 | |
| Minimum Split (s) | 27.2 | 27.2 | | 23.0 | 23.0 | 23.0 | 35.6 | 35.6 | | 35.6 | 35.6 | |
| Total Split (s) | 25.0 | 25.0 | | 25.0 | 25.0 | 25.0 | 65.0 | 65.0 | | 65.0 | 65.0 | |
| Total Split (%) | 27.8% | 27.8% | | 27.8% | 27.8% | 27.8% | 72.2% | 72.2% | | 72.2% | 72.2% | |
| Maximum Green (s) | 19.8 | 19.8 | | 19.8 | 19.8 | 19.8 | 59.4 | 59.4 | | 59.4 | 59.4 | |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | 3.2 | 3.6 | 3.6 | | 3.6 | 3.6 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.2 | | | 5.2 | 5.2 | 5.6 | 5.6 | | 5.6 | 5.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | None | None | | None | None | None | Min | Min | | Min | Min | |
| Walk Time (s) | 7.0 | 7.0 | | | | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | 15.0 | 15.0 | | | | | | | | 15.0 | 15.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | | | | | | 0 | 0 | |
| Act Effct Green (s) | | 12.8 | | | 12.8 | 12.8 | 33.9 | 33.9 | | 33.9 | 33.9 | |
| Actuated g/C Ratio | | 0.22 | | | 0.22 | 0.22 | 0.59 | 0.59 | | 0.59 | 0.59 | |
| v/c Ratio | | 0.57 | | | 0.08 | 0.28 | 0.10 | 0.62 | | 0.28 | 0.68 | |
| Control Delay (s/veh) | | 25.4 | | | 19.8 | 6.5 | 7.0 | 11.0 | | 9.2 | 12.4 | |
| Queue Delay | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 25.4 | | | 19.8 | 6.5 | 7.0 | 11.0 | | 9.2 | 12.4 | |
| LOS | | C | | | B | A | A | B | | A | B | |
| Approach Delay (s/veh) | | 25.4 | | | 9.2 | | | 10.9 | | | 12.0 | |
| Approach LOS | | C | | | A | | | B | | | B | |
| Queue Length 50th (ft) | | 47 | | | 8 | 0 | 3 | 118 | | 12 | 136 | |
| Queue Length 95th (ft) | | 131 | | | 32 | 38 | 17 | 279 | | 46 | 326 | |
| Internal Link Dist (ft) | | 630 | | | 427 | | | 959 | | | 1145 | |
| Turn Bay Length (ft) | | | | | | 70 | 170 | | | 150 | | |
| Base Capacity (vph) | | 533 | | | 608 | 643 | 465 | 1785 | | 546 | 1773 | |
| Starvation Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.37 | | | 0.05 | 0.20 | 0.06 | 0.38 | | 0.17 | 0.42 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 90 | | | |
| Actuated Cycle Length: 57.8 | | | |
| Natural Cycle: 65 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.68 | | | |
| Intersection Signal Delay (s/veh): 12.7 | | Intersection LOS: B | |
| Intersection Capacity Utilization 94.6% | | ICU Level of Service F | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 27: Bailey Ave & Meyer Rd




| Intersection | |
|---|---|
| Int Delay, s/veh | 4.8 |

| Movement | EBT | EBR | WBL | WBT | NBL | NBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 4 | 163 | 6 | 2 | 153 | 2 |
| Future Vol, veh/h | 4 | 163 | 6 | 2 | 153 | 2 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Stop | Stop |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | - | - | - | - | 0 | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 97 | 97 | 97 | 97 | 97 | 97 |
| Heavy Vehicles, % | 0 | 0 | 0 | 0 | 0 | 0 |
| Mvmt Flow | 4 | 168 | 6 | 2 | 158 | 2 |

| Major/Minor | Major1 | | Major2 | | Minor1 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 0 | 0 | 172 | 0 | 103 | 88 |
| Stage 1 | - | - | - | - | 88 | - |
| Stage 2 | - | - | - | - | 14 | - |
| Critical Hdwy | - | - | 4.1 | - | 6.4 | 6.2 |
| Critical Hdwy Stg 1 | - | - | - | - | 5.4 | - |
| Critical Hdwy Stg 2 | - | - | - | - | 5.4 | - |
| Follow-up Hdwy | - | - | 2.2 | - | 3.5 | 3.3 |
| Pot Cap-1 Maneuver | - | - | 1417 | - | 901 | 976 |
| Stage 1 | - | - | - | - | 940 | - |
| Stage 2 | - | - | - | - | 1014 | - |
| Platoon blocked, % | - | - | | - | | |
| Mov Cap-1 Maneuver | - | - | 1417 | - | 897 | 976 |
| Mov Cap-2 Maneuver | - | - | - | - | 897 | - |
| Stage 1 | - | - | - | - | 940 | - |
| Stage 2 | - | - | - | - | 1009 | - |

| Approach | EB | WB | NB |
|---|---|---|---|
| HCM Control Delay, s/v | 0 | 5.66 | 9.88 |
| HCM LOS | | | A |

| Minor Lane/Major Mvmt | NBLn1 | EBT | EBR | WBL | WBT |
|---|---|---|---|---|---|
| Capacity (veh/h) | 898 | - | - | 1350 | - |
| HCM Lane V/C Ratio | 0.178 | - | - | 0.004 | - |
| HCM Control Delay (s/veh) | 9.9 | - | - | 7.6 | 0 |
| HCM Lane LOS | A | - | - | A | A |
| HCM 95th %tile Q(veh) | 0.6 | - | - | 0 | - |




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 6 | 0 | 19 | 524 | 14 | 528 | 0 | 1207 | 417 | 0 | 1602 | 0 |
| Future Volume (vph) | 6 | 0 | 19 | 524 | 14 | 528 | 0 | 1207 | 417 | 0 | 1602 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 250 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 0 | | 1 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 0.95 | 0.91 | 0.95 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | 0.921 | 0.850 | | | 0.850 | | | |
| Flt Protected | 0.950 | | | 0.950 | 0.979 | | | | | | | |
| Satd. Flow (prot) | 1787 | 0 | 1599 | 1698 | 1544 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Flt Permitted | 0.196 | | | 0.950 | 0.979 | | | | | | | |
| Satd. Flow (perm) | 369 | 0 | 1599 | 1698 | 1544 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 28 | | 34 | 55 | | | 439 | | | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 240 | | | 646 | | | 950 | | | 468 | |
| Travel Time (s) | | 5.5 | | | 14.7 | | | 16.2 | | | 8.0 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 6 | 0 | 20 | 552 | 15 | 556 | 0 | 1271 | 439 | 0 | 1686 | 0 |
| Shared Lane Traffic (%) | | | | 30% | | 36% | | | | | | |
| Lane Group Flow (vph) | 6 | 0 | 20 | 386 | 381 | 356 | 0 | 1271 | 439 | 0 | 1686 | 0 |
| Turn Type | D.Pm | | Perm | Perm | NA | Perm | | NA | Perm | | NA | |
| Protected Phases | | | | | 3 | | | 1 | | | 1 | |
| Permitted Phases | 3 | | 3 | 3 | | 3 | | | 1 | | | |
| Detector Phase | 3 | | 3 | 3 | 3 | 3 | | 1 | 1 | | 1 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | | 6.0 | 6.0 | 6.0 | 6.0 | | 20.0 | 20.0 | | 20.0 | |
| Minimum Split (s) | 13.3 | | 13.3 | 13.3 | 13.3 | 13.3 | | 34.6 | 34.6 | | 34.6 | |
| Total Split (s) | 70.0 | | 70.0 | 70.0 | 70.0 | 70.0 | | 110.0 | 110.0 | | 110.0 | |
| Total Split (%) | 38.9% | | 38.9% | 38.9% | 38.9% | 38.9% | | 61.1% | 61.1% | | 61.1% | |
| Maximum Green (s) | 62.7 | | 62.7 | 62.7 | 62.7 | 62.7 | | 102.4 | 102.4 | | 102.4 | |
| Yellow Time (s) | 4.3 | | 4.3 | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 | | 4.3 | |
| All-Red Time (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.3 | 3.3 | | 3.3 | |
| Lost Time Adjust (s) | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |
| Total Lost Time (s) | 7.3 | | 7.3 | 7.3 | 7.3 | 7.3 | | 7.6 | 7.6 | | 7.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | |
| Recall Mode | None | | None | None | None | None | | C-Max | C-Max | | C-Max | |
| Walk Time (s) | | | | | | | | 7.0 | 7.0 | | 7.0 | |
| Flash Don't Walk (s) | | | | | | | | 20.0 | 20.0 | | 20.0 | |
| Pedestrian Calls (#/hr) | | | | | | | | 0 | 0 | | 0 | |
| Act Effct Green (s) | 51.1 | | 51.1 | 51.1 | 51.1 | 51.1 | | 114.0 | 114.0 | | 114.0 | |
| Actuated g/C Ratio | 0.28 | | 0.28 | 0.28 | 0.28 | 0.28 | | 0.63 | 0.63 | | 0.63 | |
| v/c Ratio | 0.06 | | 0.04 | 0.80 | 0.82 | 0.76 | | 0.39 | 0.37 | | 0.52 | |
| Control Delay (s/veh) | 43.2 | | 7.5 | 72.0 | 69.1 | 59.1 | | 21.2 | 5.3 | | 19.7 | |
| Queue Delay | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 43.2 | | 7.5 | 72.0 | 69.1 | 59.1 | | 21.2 | 5.3 | | 19.7 | |
| LOS | D | | A | E | E | E | | C | A | | B | |
| Approach Delay (s/veh) | | 15.8 | | | 66.9 | | | 17.1 | | | 19.7 | |
| Approach LOS | | B | | | E | | | B | | | B | |
| Queue Length 50th (ft) | 5 | | 0 | 446 | 427 | 348 | | 289 | 48 | | 387 | |
| Queue Length 95th (ft) | 18 | | 16 | 541 | 535 | 447 | | 363 | 99 | | 500 | |
| Internal Link Dist (ft) | | 160 | | | 566 | | | 870 | | | 388 | |
| Turn Bay Length (ft) | | | | | | | | | 250 | | | |
| Base Capacity (vph) | 128 | | 575 | 591 | 559 | 564 | | 3253 | 1173 | | 3253 | |
| Starvation Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Spillback Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Storage Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Reduced v/c Ratio | 0.05 | | 0.03 | 0.65 | 0.68 | 0.63 | | 0.39 | 0.37 | | 0.52 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 60 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.82 | | | |
| Intersection Signal Delay (s/veh): 30.4 | | Intersection LOS: C | |
| Intersection Capacity Utilization 74.7% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 1: Niagara Falls Blvd





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 0 | 639 | 0 | 0 | 242 | 0 | 1370 | 597 | 0 | 1502 | 500 |
| Future Volume (vph) | 0 | 0 | 639 | 0 | 0 | 242 | 0 | 1370 | 597 | 0 | 1502 | 500 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 200 |
| Storage Lanes | 0 | | 2 | 0 | | 1 | 0 | | 0 | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 0.88 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | | 0.865 | | 0.954 | | | | 0.850 |
| Flt Protected | | | | | | | | | | | | |
| Satd. Flow (prot) | 0 | 0 | 2814 | 0 | 0 | 1627 | 0 | 4899 | 0 | 0 | 5136 | 1599 |
| Flt Permitted | | | | | | | | | | | | |
| Satd. Flow (perm) | 0 | 0 | 2814 | 0 | 0 | 1627 | 0 | 4899 | 0 | 0 | 5136 | 1599 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 48 | | | | | | | | | 380 |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 374 | | | 614 | | | 600 | | | 950 | |
| Travel Time (s) | | 8.5 | | | 14.0 | | | 10.2 | | | 16.2 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 0 | 0 | 659 | 0 | 0 | 249 | 0 | 1412 | 615 | 0 | 1548 | 515 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 0 | 659 | 0 | 0 | 249 | 0 | 2027 | 0 | 0 | 1548 | 515 |
| Turn Type | | | Perm | | | Perm | | NA | | | NA | Perm |
| Protected Phases | | | | | | | | 1 3 | | | 1 | |
| Permitted Phases | | | 3 | | | 1 3 | | | | | | 1 |
| Detector Phase | | | 3 | | | 1 3 | | 1 3 | | | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | | 15.0 | | | | | | | | 10.0 | 10.0 |
| Minimum Split (s) | | | 25.1 | | | | | | | | 26.5 | 26.5 |
| Total Split (s) | | | 70.0 | | | | | | | | 110.0 | 110.0 |
| Total Split (%) | | | 38.9% | | | | | | | | 61.1% | 61.1% |
| Maximum Green (s) | | | 62.9 | | | | | | | | 102.5 | 102.5 |
| Yellow Time (s) | | | 5.1 | | | | | | | | 4.3 | 4.3 |
| All-Red Time (s) | | | 2.0 | | | | | | | | 3.2 | 3.2 |
| Lost Time Adjust (s) | | | 0.0 | | | | | | | | 0.0 | 0.0 |
| Total Lost Time (s) | | | 7.1 | | | | | | | | 7.5 | 7.5 |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | | 3.0 | | | | | | | | 3.0 | 3.0 |
| Recall Mode | | | None | | | | | | | | C-Max | C-Max |
| Walk Time (s) | | | | | | | | | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | | | | | | | | | | 12.0 | 12.0 |
| Pedestrian Calls (#/hr) | | | | | | | | | | | 0 | 0 |
| Act Effct Green (s) | | | 62.9 | | | 180.0 | | 180.0 | | | 102.5 | 102.5 |
| Actuated g/C Ratio | | | 0.35 | | | 1.00 | | 1.00 | | | 0.57 | 0.57 |
| v/c Ratio | | | 0.65 | | | 0.15 | | 0.41 | | | 0.53 | 0.48 |
| Control Delay (s/veh) | | | 49.0 | | | 0.2 | | 0.8 | | | 27.9 | 7.1 |
| Queue Delay | | | 0.0 | | | 0.0 | | 0.0 | | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | | 49.0 | | | 0.2 | | 0.8 | | | 27.9 | 7.1 |
| LOS | | | D | | | A | | A | | | C | A |
| Approach Delay (s/veh) | | 49.0 | | | 0.2 | | | 0.8 | | | 22.7 | |
| Approach LOS | | D | | | A | | | A | | | C | |
| Queue Length 50th (ft) | | | 348 | | | 0 | | 24 | | | 521 | 217 |
| Queue Length 95th (ft) | | | 428 | | | 0 | | 0 | | | 573 | 61 |
| Internal Link Dist (ft) | | 294 | | | 534 | | | 520 | | | 870 | |
| Turn Bay Length (ft) | | | | | | | | | | | | 200 |
| Base Capacity (vph) | | | 1014 | | | 1627 | | 4899 | | | 2924 | 1074 |
| Starvation Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Spillback Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Storage Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Reduced v/c Ratio | | | 0.65 | | | 0.15 | | 0.41 | | | 0.53 | 0.48 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 60 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.65 | | | |
| Intersection Signal Delay (s/veh): 16.2 | | Intersection LOS: B | |
| Intersection Capacity Utilization 67.3% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 2: Niagara Falls Blvd







| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 116 | 82 | 16 | 25 | 63 | 730 | 43 | 1144 | 13 | 651 | 1187 | 58 |
| Future Volume (vph) | 116 | 82 | 16 | 25 | 63 | 730 | 43 | 1144 | 13 | 651 | 1187 | 58 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 100 | | 0 | 0 | | 225 | 130 | | 0 | 435 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 2 | 1 | | 0 | 2 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.88 | 1.00 | 0.91 | 0.91 | 0.97 | 0.91 | 0.91 |
| Frt | | 0.975 | | | | 0.850 | | 0.998 | | | 0.993 | |
| Flt Protected | 0.950 | | | | 0.986 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 1834 | 0 | 0 | 1855 | 2814 | 1787 | 5125 | 0 | 3467 | 5100 | 0 |
| Flt Permitted | 0.627 | | | | 0.892 | | 0.950 | | | 0.950 | | |
| Satd. Flow (perm) | 1180 | 1834 | 0 | 0 | 1678 | 2814 | 1787 | 5125 | 0 | 3467 | 5100 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 5 | | | | 204 | | 1 | | | 6 | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 853 | | | 2284 | | | 672 | | | 600 | |
| Travel Time (s) | | 19.4 | | | 51.9 | | | 11.5 | | | 10.2 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.97 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 121 | 85 | 17 | 26 | 66 | 760 | 45 | 1192 | 14 | 671 | 1236 | 60 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 121 | 102 | 0 | 0 | 92 | 760 | 45 | 1206 | 0 | 671 | 1296 | 0 |
| Turn Type | D.P+P | NA | | Perm | NA | pm+ov | Prot | NA | | Prot | NA | |
| Protected Phases | 7 | 7 8 | | | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 8 | | | 8 | | 8 | | | | | | |
| Detector Phase | 7 | 7 8 | | 8 | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | | | 5.0 | 5.0 | 5.0 | 5.0 | 20.0 | | 5.0 | 20.0 | |
| Minimum Split (s) | 12.7 | | | 24.3 | 24.3 | 12.5 | 11.6 | 32.6 | | 12.5 | 34.3 | |
| Total Split (s) | 25.0 | | | 30.0 | 30.0 | 65.0 | 20.0 | 60.0 | | 65.0 | 105.0 | |
| Total Split (%) | 13.9% | | | 16.7% | 16.7% | 36.1% | 11.1% | 33.3% | | 36.1% | 58.3% | |
| Maximum Green (s) | 17.5 | | | 24.7 | 24.7 | 57.5 | 13.7 | 53.5 | | 57.5 | 98.5 | |
| Yellow Time (s) | 3.6 | | | 4.3 | 4.3 | 3.6 | 4.3 | 4.3 | | 3.6 | 4.3 | |
| All-Red Time (s) | 3.9 | | | 1.0 | 1.0 | 3.9 | 2.0 | 2.2 | | 3.9 | 2.2 | |
| Lost Time Adjust (s) | 0.0 | | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 7.5 | | | | 5.3 | 7.5 | 6.3 | 6.5 | | 7.5 | 6.5 | |
| Lead/Lag | Lead | | | Lag | Lag | Lead | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 2.0 | | | 3.0 | 3.0 | 2.4 | 2.4 | 2.4 | | 2.4 | 2.4 | |
| Recall Mode | None | | | Max | Max | Max | None | Max | | Max | C-Max | |
| Walk Time (s) | | | | 7.0 | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | | | 11.0 | 11.0 | | | 19.0 | | | 19.0 | |
| Pedestrian Calls (#/hr) | | | | 0 | 0 | | | 0 | | | 0 | |
| Act Effct Green (s) | 40.0 | 47.5 | | | 28.5 | 91.3 | 9.3 | 53.5 | | 57.5 | 105.3 | |
| Actuated g/C Ratio | 0.22 | 0.26 | | | 0.16 | 0.51 | 0.05 | 0.30 | | 0.32 | 0.59 | |
| v/c Ratio | 0.39 | 0.21 | | | 0.35 | 0.50 | 0.49 | 0.79 | | 0.61 | 0.43 | |
| Control Delay (s/veh) | 56.7 | 50.4 | | | 73.0 | 22.1 | 105.0 | 28.5 | | 76.7 | 12.0 | |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.1 | | 1.4 | 0.2 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 56.7 | 50.4 | | | 73.0 | 22.1 | 105.0 | 28.6 | | 78.1 | 12.1 | |
| LOS | E | D | | | E | C | F | C | | E | B | |
| Approach Delay (s/veh) | | 53.8 | | | 27.6 | | | 31.3 | | | 34.7 | |
| Approach LOS | | D | | | C | | | C | | | C | |
| Queue Length 50th (ft) | 114 | 90 | | | 99 | 243 | 56 | 104 | | 393 | 205 | |
| Queue Length 95th (ft) | 178 | 147 | | | 167 | 319 | m103 | 113 | | 463 | 227 | |
| Internal Link Dist (ft) | | 773 | | | 2204 | | | 592 | | | 520 | |
| Turn Bay Length (ft) | 100 | | | | | 225 | 130 | | | 435 | | |
| Base Capacity (vph) | 344 | 462 | | | 265 | 1527 | 136 | 1523 | | 1107 | 2984 | |
| Starvation Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 10 | | 247 | 673 | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.35 | 0.22 | | | 0.35 | 0.50 | 0.33 | 0.80 | | 0.78 | 0.56 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 6:SBT, Start of Yellow | | | |
| Natural Cycle: 95 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.79 | | | |
| Intersection Signal Delay (s/veh): 33.3 | | Intersection LOS: C | |
| Intersection Capacity Utilization 72.3% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 3: Niagara Falls Blvd & Koenig Rd/Ridge Lea Rd





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 20 | 10 | 24 | 176 | 5 | 260 | 9 | 16 | 1026 | 112 | 258 | 1062 |
| Future Volume (vph) | 20 | 10 | 24 | 176 | 5 | 260 | 9 | 16 | 1026 | 112 | 258 | 1062 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 0 | | 160 | | 110 | | 170 | 300 | |
| Storage Lanes | 0 | | 1 | 0 | | 1 | | 1 | | 1 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 |
| Ped Bike Factor | | | | | | | | | | 0.99 | | |
| Frt | | | 0.850 | | | 0.850 | | | | 0.850 | | 0.994 |
| Flt Protected | | 0.967 | | | 0.954 | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1819 | 1599 | 0 | 1795 | 1599 | 0 | 1787 | 5136 | 1599 | 1787 | 5105 |
| Flt Permitted | | 0.182 | | | 0.709 | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 342 | 1599 | 0 | 1334 | 1599 | 0 | 1787 | 5136 | 1575 | 1787 | 5105 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 92 | | | 271 | | | | 92 | | 4 |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | 40 |
| Link Distance (ft) | | 800 | | | 1099 | | | | 758 | | | 672 |
| Travel Time (s) | | 18.2 | | | 25.0 | | | | 12.9 | | | 11.5 |
| Confl. Peds. (#/hr) | | | | | | | | | | 1 | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 21 | 10 | 25 | 183 | 5 | 271 | 9 | 17 | 1069 | 117 | 269 | 1106 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 31 | 25 | 0 | 188 | 271 | 0 | 26 | 1069 | 117 | 269 | 1151 |
| Turn Type | Perm | NA | Perm | Perm | NA | Perm | Prot | Prot | NA | Perm | Prot | NA |
| Protected Phases | | 3 | | | 4 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 3 | | 3 | 4 | | 4 | | | | 2 | | |
| Detector Phase | 3 | 3 | 3 | 4 | 4 | 4 | 5 | 5 | 2 | 2 | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 3.0 | 6.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 |
| Minimum Split (s) | 23.8 | 23.8 | 23.8 | 24.6 | 24.6 | 24.6 | 10.8 | 10.8 | 23.8 | 23.8 | 10.8 | 23.8 |
| Total Split (s) | 30.0 | 30.0 | 30.0 | 55.0 | 55.0 | 55.0 | 25.0 | 25.0 | 65.0 | 65.0 | 30.0 | 70.0 |
| Total Split (%) | 16.7% | 16.7% | 16.7% | 30.6% | 30.6% | 30.6% | 13.9% | 13.9% | 36.1% | 36.1% | 16.7% | 38.9% |
| Maximum Green (s) | 24.2 | 24.2 | 24.2 | 48.4 | 48.4 | 48.4 | 19.2 | 19.2 | 59.2 | 59.2 | 24.2 | 64.2 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | 3.2 | 3.2 | 3.2 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 1.9 | 1.9 | 1.9 | 3.4 | 3.4 | 3.4 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 5.8 | 5.8 | | 6.6 | 6.6 | | 5.8 | 5.8 | 5.8 | 5.8 | 5.8 |
| Lead/Lag | Lead | Lead | Lead | Lag | Lag | Lag | Lead | Lead | Lag | Lag | Lead | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | None | None | None | None | None | None | None | None | C-Max | C-Max | None | C-Max |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | 7.0 | 7.0 | | 7.0 |
| Flash Don't Walk (s) | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | | | 11.0 | 11.0 | | 11.0 |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 |
| Act Effct Green (s) | | 20.2 | 20.2 | | 31.1 | 31.1 | | 8.1 | 70.1 | 70.1 | 37.6 | 104.4 |
| Actuated g/C Ratio | | 0.11 | 0.11 | | 0.17 | 0.17 | | 0.05 | 0.39 | 0.39 | 0.21 | 0.58 |
| v/c Ratio | | 0.82 | 0.10 | | 0.82 | 0.54 | | 0.33 | 0.53 | 0.17 | 0.72 | 0.39 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 43 |
| Future Volume (vph) | 43 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Ped Bike Factor | |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | |
| Peak Hour Factor | 0.96 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 45 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 174.1 | 0.8 | | 96.9 | 9.8 | | 124.6 | 44.9 | 9.6 | 83.4 | 7.4 |
| Queue Delay | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | | 174.1 | 0.8 | | 96.9 | 9.8 | | 124.6 | 44.9 | 9.6 | 83.4 | 7.4 |
| LOS | | F | A | | F | A | | F | D | A | F | A |
| Approach Delay (s/veh) | | 96.7 | | | 45.5 | | | | 43.2 | | | 21.8 |
| Approach LOS | | F | | | D | | | | D | | | C |
| Queue Length 50th (ft) | | 35 | 0 | | 217 | 0 | | 32 | 449 | 54 | 224 | 57 |
| Queue Length 95th (ft) | | #103 | 0 | | 296 | 82 | | m70 | 516 | 24 | #491 | 258 |
| Internal Link Dist (ft) | | 720 | | | 1019 | | | | 678 | | | 592 |
| Turn Bay Length (ft) | | | 25 | | | 160 | | 110 | | 170 | 300 | |
| Base Capacity (vph) | | 45 | 294 | | 358 | 628 | | 190 | 2000 | 669 | 373 | 2962 |
| Starvation Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 316 |
| Spillback Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 4 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.69 | 0.09 | | 0.53 | 0.43 | | 0.14 | 0.54 | 0.17 | 0.72 | 0.43 |

| Intersection Summary | |
|---|---|
| Area Type: | Other |
| Cycle Length: 180 | |
| Actuated Cycle Length: 180 | |
| Offset: 153 (85%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | |
| Natural Cycle: 95 | |
| Control Type: Actuated-Coordinated | |
| Maximum v/c Ratio: 0.82 | |
| Intersection Signal Delay (s/veh): 34.8 | Intersection LOS: C |
| Intersection Capacity Utilization 66.0% | ICU Level of Service C |
| Analysis Period (min) 15 | |
| # 95th percentile volume exceeds capacity, queue may be longer. | |
| Queue shown is maximum after two cycles. | |
| m Volume for 95th percentile queue is metered by upstream signal. | |

Splits and Phases: 4: Niagara Falls Blvd & Pier 1 Entrance/The Boulevard/Consumer Square





| Lane Group | SBR |
|---|---|
| Control Delay (s/veh) | |
| Queue Delay | |
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 41 | 86 | 30 | 180 | 87 | 177 | 6 | 45 | 805 | 148 | 1 | 201 |
| Future Volume (vph) | 41 | 86 | 30 | 180 | 87 | 177 | 6 | 45 | 805 | 148 | 1 | 201 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 100 | | 0 | | 120 | | 165 | | 315 |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | 0.900 | | | | | 0.850 | | |
| Flt Protected | | 0.984 | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1851 | 1599 | 1787 | 1693 | 0 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Flt Permitted | | 0.368 | | 0.574 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 692 | 1599 | 1080 | 1693 | 0 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 63 | | 57 | | | | | 123 | | |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | |
| Link Distance (ft) | | 868 | | | 278 | | | | 1759 | | | |
| Travel Time (s) | | 19.7 | | | 6.3 | | | | 30.0 | | | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 43 | 91 | 32 | 189 | 92 | 186 | 6 | 47 | 847 | 156 | 1 | 212 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 134 | 32 | 189 | 278 | 0 | 0 | 53 | 847 | 156 | 0 | 213 |
| Turn Type | Perm | NA | Perm | Perm | NA | | Prot | Prot | NA | Perm | Prot | Prot |
| Protected Phases | | 4 | | | 8 | | 5 | 5 | 2 | | 1 | 1 |
| Permitted Phases | 4 | | 4 | 8 | | | | | | 2 | | |
| Detector Phase | 4 | 4 | 4 | 8 | 8 | | 5 | 5 | 2 | 2 | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 3.0 |
| Minimum Split (s) | 48.9 | 48.9 | 48.9 | 48.9 | 48.9 | | 11.7 | 11.7 | 40.0 | 40.0 | 11.7 | 11.7 |
| Total Split (s) | 60.0 | 60.0 | 60.0 | 60.0 | 60.0 | | 45.0 | 45.0 | 75.0 | 75.0 | 45.0 | 45.0 |
| Total Split (%) | 33.3% | 33.3% | 33.3% | 33.3% | 33.3% | | 25.0% | 25.0% | 41.7% | 41.7% | 25.0% | 25.0% |
| Maximum Green (s) | 53.1 | 53.1 | 53.1 | 53.1 | 53.1 | | 38.3 | 38.3 | 68.3 | 68.3 | 38.3 | 38.3 |
| Yellow Time (s) | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 3.7 | 3.7 | 3.7 | 3.7 | 3.7 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.9 | 6.9 | 6.9 | 6.9 | | | 6.7 | 6.7 | 6.7 | | 6.7 |
| Lead/Lag | | | | | | | Lead | Lead | Lag | Lag | Lead | Lead |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | None | None | None | | None | None | C-Max | C-Max | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | 30.0 | 30.0 | | | | 24.0 | 24.0 | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | | | | 0 | 0 | | |
| Act Effct Green (s) | | 33.7 | 33.7 | 33.7 | 33.7 | | | 10.1 | 99.9 | 99.9 | | 26.2 |
| Actuated g/C Ratio | | 0.19 | 0.19 | 0.19 | 0.19 | | | 0.06 | 0.56 | 0.56 | | 0.15 |
| v/c Ratio | | 1.04 | 0.09 | 0.94 | 0.77 | | | 0.53 | 0.30 | 0.17 | | 0.82 |
| Control Delay (s/veh) | | 158.2 | 0.8 | 117.4 | 65.5 | | | 84.2 | 39.5 | 23.3 | | 108.2 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 866 | 36 |
| Future Volume (vph) | 866 | 36 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.994 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5105 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5105 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 4 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 758 | |
| Travel Time (s) | 12.9 | |
| Peak Hour Factor | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 912 | 38 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 950 | 0 |
| Turn Type | NA | |
| Protected Phases | 6 | |
| Permitted Phases | | |
| Detector Phase | 6 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 31.7 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 41.7% | |
| Maximum Green (s) | 68.3 | |
| Yellow Time (s) | 4.3 | |
| All-Red Time (s) | 2.4 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.7 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 2.4 | |
| Recall Mode | C-Max | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 18.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 118.4 | |
| Actuated g/C Ratio | 0.66 | |
| v/c Ratio | 0.28 | |
| Control Delay (s/veh) | 6.8 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 158.2 | 0.8 | 117.4 | 65.5 | | | 84.2 | 39.5 | 23.3 | | 108.2 |
| LOS | | F | A | F | E | | | F | D | C | | F |
| Approach Delay (s/veh) | | 127.9 | | | 86.5 | | | | 39.3 | | | |
| Approach LOS | | F | | | F | | | | D | | | |
| Queue Length 50th (ft) | | ~170 | 0 | 222 | 249 | | | 62 | 249 | 45 | | 248 |
| Queue Length 95th (ft) | | #265 | 4 | 304 | 333 | | | 115 | 394 | 150 | | 352 |
| Internal Link Dist (ft) | | 788 | | | 198 | | | | 1679 | | | |
| Turn Bay Length (ft) | | | 25 | 100 | | | | 120 | | 165 | | 315 |
| Base Capacity (vph) | | 204 | 516 | 318 | 539 | | | 380 | 2849 | 941 | | 380 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.66 | 0.06 | 0.59 | 0.52 | | | 0.14 | 0.30 | 0.17 | | 0.56 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 150 (83%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 1.04 | | | |
| Intersection Signal Delay (s/veh): 46.5 | | Intersection LOS: D | |
| Intersection Capacity Utilization 71.7% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| ~ Volume exceeds capacity, queue is theoretically infinite. | | | |
| Queue shown is maximum after two cycles. | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 5: Niagara Falls Blvd & Glenalby Rd/Romney Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 6.8 | |
| LOS | A | |
| Approach Delay (s/veh) | 25.4 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 60 | |
| Queue Length 95th (ft) | 124 | |
| Internal Link Dist (ft) | 678 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 3359 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.28 | |

| Intersection Summary |
|---|

| Intersection | |
|---|---|
| Int Delay, s/veh | 4.3 |

| Movement | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | | | |
| Traffic Vol, veh/h | 0 | 2 | 16 | 13 | 0 | 59 | 1 | 1 | 1480 | 47 | 50 | 39 | 1243 | 17 |
| Future Vol, veh/h | 0 | 2 | 16 | 13 | 0 | 59 | 1 | 1 | 1480 | 47 | 50 | 39 | 1243 | 17 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Stop | Stop | Stop | Stop | Free | Free | Free | Free | Free | Free | Free | Free |
| RT Channelized | - | - | None | - | - | None | - | - | - | None | - | - | - | None |
| Storage Length | - | - | - | - | - | - | - | - | - | - | - | 105 | - | - |
| Veh in Median Storage, # | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Grade, % | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Peak Hour Factor | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 0 | 2 | 16 | 13 | 0 | 60 | 1 | 1 | 1510 | 48 | 51 | 40 | 1268 | 17 |

| Major/Minor | Minor2 | | | Minor1 | | | Major1 | | | | Major2 | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Conflicting Flow All | 2067 | 3021 | 643 | 2228 | 3006 | 779 | 939 | 1286 | 0 | 0 | 1137 | 1558 | 0 | 0 |
| Stage 1 | 1459 | 1459 | - | 1538 | 1538 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 608 | 1562 | - | 690 | 1467 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy | 6.42 | 6.52 | 7.12 | 6.42 | 6.52 | 7.12 | 5.64 | 5.32 | - | - | 5.62 | 5.32 | - | - |
| Critical Hdwy Stg 1 | 7.32 | 5.52 | - | 7.32 | 5.52 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy Stg 2 | 6.72 | 5.52 | - | 6.72 | 5.52 | - | - | - | - | - | - | - | - | - |
| Follow-up Hdwy | 3.81 | 4.01 | 3.91 | 3.81 | 4.01 | 3.91 | 2.32 | 3.11 | - | - | 2.31 | 3.11 | - | - |
| Pot Cap-1 Maneuver | 58 | 13 | 359 | 46 | 13 | 292 | 475 | 287 | - | - | 372 | 211 | - | - |
| Stage 1 | 96 | 194 | - | 84 | 177 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 412 | 173 | - | 367 | 192 | - | - | - | - | - | - | - | - | - |
| Platoon blocked, % | | | | | | | | | - | - | | | - | - |
| Mov Cap-1 Maneuver | 29 | 8 | 359 | 23 | 9 | 292 | 351 | 351 | - | - | 251 | 251 | - | - |
| Mov Cap-2 Maneuver | 29 | 8 | - | 23 | 9 | - | - | - | - | - | - | - | - | - |
| Stage 1 | 61 | 124 | - | 83 | 176 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 324 | 171 | - | 220 | 123 | - | - | - | - | - | - | - | - | - |

| Approach | EB | WB | NB | SB |
|---|---|---|---|---|
| HCM Control Delay, s/v | 83.74 | 118.97 | 0.26 | 1.8 |
| HCM LOS | F | F | | |

| Minor Lane/Major Mvmt | NBL | NBT | NBR | EBLn1 | WBLn1 | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|
| Capacity (veh/h) | 7 | - | - | 63 | 94 | 251 | - | - |
| HCM Lane V/C Ratio | 0.003 | - | - | 0.29 | 0.778 | 0.362 | - | - |
| HCM Control Delay (s/veh) | 15.3 | 0.2 | - | 83.7 | 119 | 27.2 | - | - |
| HCM Lane LOS | C | A | - | F | F | D | - | - |
| HCM 95th %tile Q(veh) | 0 | - | - | 1 | 4.1 | 1.6 | - | - |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBU | NBL | NBT | NBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 1 | 149 | 286 | 46 | 1 | 262 | 307 | 250 | 15 | 46 | 994 | 244 |
| Future Volume (vph) | 1 | 149 | 286 | 46 | 1 | 262 | 307 | 250 | 15 | 46 | 994 | 244 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 50 | | 50 | | 400 | | 0 | | 300 | | 300 |
| Storage Lanes | | 1 | | 1 | | 1 | | 1 | | 1 | | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | | 25 | | |
| Lane Util. Factor | 0.95 | 1.00 | 0.95 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 |
| Ped Bike Factor | | 1.00 | 1.00 | | | 1.00 | | 0.98 | | | | |
| Frt | | | 0.979 | | | | | 0.850 | | | | 0.850 |
| Flt Protected | | 0.950 | | | | 0.950 | | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 1787 | 3491 | 0 | 0 | 1787 | 3574 | 1599 | 0 | 1787 | 5136 | 1599 |
| Flt Permitted | | 0.558 | | | | 0.221 | | | | 0.950 | | |
| Satd. Flow (perm) | 0 | 1047 | 3491 | 0 | 0 | 415 | 3574 | 1573 | 0 | 1787 | 5136 | 1599 |
| Right Turn on Red | | | | Yes | | | | Yes | | | | Yes |
| Satd. Flow (RTOR) | | | 9 | | | | | 260 | | | | 254 |
| Link Speed (mph) | | | 30 | | | | 45 | | | | 40 | |
| Link Distance (ft) | | | 1574 | | | | 1441 | | | | 956 | |
| Travel Time (s) | | | 35.8 | | | | 21.8 | | | | 16.3 | |
| Confl. Peds. (#/hr) | | 3 | | 4 | | 4 | | 3 | | | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 1 | 155 | 298 | 48 | 1 | 273 | 320 | 260 | 16 | 48 | 1035 | 254 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 156 | 346 | 0 | 0 | 274 | 320 | 260 | 0 | 64 | 1035 | 254 |
| Turn Type | pm+pt | pm+pt | NA | | pm+pt | pm+pt | NA | Perm | Prot | Prot | NA | Perm |
| Protected Phases | 7 | 7 | 4 | | 3 | 3 | 8 | | 5 | 5 | 2 | |
| Permitted Phases | 4 | 4 | | | 8 | 8 | | 8 | | | | 2 |
| Detector Phase | 7 | 7 | 4 | | 3 | 3 | 8 | 8 | 5 | 5 | 2 | 2 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 6.0 | | 3.0 | 3.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 |
| Minimum Split (s) | 13.8 | 13.8 | 48.1 | | 13.8 | 13.8 | 47.8 | 47.8 | 12.1 | 12.1 | 39.1 | 39.1 |
| Total Split (s) | 30.0 | 30.0 | 50.0 | | 35.0 | 35.0 | 55.0 | 55.0 | 20.0 | 20.0 | 65.0 | 65.0 |
| Total Split (%) | 16.7% | 16.7% | 27.8% | | 19.4% | 19.4% | 30.6% | 30.6% | 11.1% | 11.1% | 36.1% | 36.1% |
| Maximum Green (s) | 21.9 | 21.9 | 41.9 | | 26.9 | 26.9 | 46.9 | 46.9 | 13.1 | 13.1 | 58.1 | 58.1 |
| Yellow Time (s) | 3.8 | 3.8 | 3.8 | | 3.8 | 3.8 | 3.8 | 3.8 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 | 4.3 | 4.3 | 3.0 | 3.0 | 3.0 | 3.0 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 8.1 | 8.1 | | | 8.1 | 8.1 | 8.1 | | 6.9 | 6.9 | 6.9 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | Lag | Lead | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | | 2.5 | 2.5 | 2.5 | 2.5 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | None | | None | None | None | None | None | None | C-Max | C-Max |
| Walk Time (s) | | | 7.0 | | | | 7.0 | 7.0 | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | | 33.0 | | | | 31.0 | 31.0 | | | 24.0 | 24.0 |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | 0 | | | 0 | 0 |
| Act Effct Green (s) | | 38.2 | 21.9 | | | 54.8 | 30.9 | 30.9 | | 11.2 | 83.3 | 83.3 |
| Actuated g/C Ratio | | 0.21 | 0.12 | | | 0.30 | 0.17 | 0.17 | | 0.06 | 0.46 | 0.46 |
| v/c Ratio | | 0.54 | 0.80 | | | 0.86 | 0.52 | 0.54 | | 0.58 | 0.44 | 0.29 |

| Lane Group | SBU | SBL | SBT | SBR |
|---|---|---|---|---|
| Lane Configurations | | | | |
| Traffic Volume (vph) | 3 | 270 | 804 | 100 |
| Future Volume (vph) | 3 | 270 | 804 | 100 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 350 | | 0 |
| Storage Lanes | | 2 | | 0 |
| Taper Length (ft) | | 25 | | |
| Lane Util. Factor | 0.91 | 0.97 | 0.91 | 0.91 |
| Ped Bike Factor | | | | |
| Frt | | | 0.983 | |
| Flt Protected | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3467 | 5048 | 0 |
| Flt Permitted | | 0.950 | | |
| Satd. Flow (perm) | 0 | 3467 | 5048 | 0 |
| Right Turn on Red | | | | Yes |
| Satd. Flow (RTOR) | | | 14 | |
| Link Speed (mph) | | | 40 | |
| Link Distance (ft) | | | 608 | |
| Travel Time (s) | | | 10.4 | |
| Confl. Peds. (#/hr) | | | | |
| Peak Hour Factor | 0.94 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 3 | 281 | 838 | 104 |
| Shared Lane Traffic (%) | | | | |
| Lane Group Flow (vph) | 0 | 284 | 942 | 0 |
| Turn Type | Prot | Prot | NA | |
| Protected Phases | 1 | 1 | 6 | |
| Permitted Phases | | | | |
| Detector Phase | 1 | 1 | 6 | |
| Switch Phase | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | |
| Minimum Split (s) | 12.1 | 12.1 | 32.1 | |
| Total Split (s) | 30.0 | 30.0 | 75.0 | |
| Total Split (%) | 16.7% | 16.7% | 41.7% | |
| Maximum Green (s) | 23.1 | 23.1 | 68.1 | |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | |
| All-Red Time (s) | 3.0 | 3.0 | 3.0 | |
| Lost Time Adjust (s) | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 6.9 | 6.9 | |
| Lead/Lag | Lead | Lead | Lag | |
| Lead-Lag Optimize? | Yes | Yes | Yes | |
| Vehicle Extension (s) | 2.4 | 2.4 | 2.4 | |
| Recall Mode | None | None | C-Max | |
| Walk Time (s) | | | 7.0 | |
| Flash Don't Walk (s) | | | 17.0 | |
| Pedestrian Calls (#/hr) | | | 0 | |
| Act Effct Green (s) | | 19.4 | 91.6 | |
| Actuated g/C Ratio | | 0.11 | 0.51 | |
| v/c Ratio | | 0.76 | 0.37 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBU | NBL | NBT | NBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 54.4 | 88.8 | | | 75.3 | 70.8 | 10.6 | | 101.4 | 34.5 | 4.2 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | | 54.4 | 88.8 | | | 75.3 | 70.8 | 10.6 | | 101.4 | 34.5 | 4.2 |
| LOS | | D | F | | | E | E | B | | F | C | A |
| Approach Delay (s/veh) | | | 78.1 | | | | 53.9 | | | | 32.0 | |
| Approach LOS | | | E | | | | D | | | | C | |
| Queue Length 50th (ft) | | 139 | 207 | | | 263 | 181 | 0 | | 75 | 304 | 0 |
| Queue Length 95th (ft) | | 197 | 260 | | | #357 | 236 | 88 | | 130 | 385 | 60 |
| Internal Link Dist (ft) | | | 1494 | | | | 1361 | | | | 876 | |
| Turn Bay Length (ft) | | 50 | | | | 400 | | | | 300 | | 300 |
| Base Capacity (vph) | | 344 | 819 | | | 331 | 931 | 602 | | 135 | 2378 | 877 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.45 | 0.42 | | | 0.83 | 0.34 | 0.43 | | 0.47 | 0.44 | 0.29 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.86 | | | |
| Intersection Signal Delay (s/veh): 44.6 | | Intersection LOS: D | |
| Intersection Capacity Utilization 79.0% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 7: Niagara Falls Blvd & Brighton Rd/Maple Rd





| Lane Group | SBU | SBL | SBT | SBR |
|---|---|---|---|---|
| Control Delay (s/veh) | | 93.9 | 21.7 | |
| Queue Delay | | 0.0 | 0.0 | |
| Total Delay (s/veh) | | 93.9 | 21.7 | |
| LOS | | F | C | |
| Approach Delay (s/veh) | | | 38.5 | |
| Approach LOS | | | D | |
| Queue Length 50th (ft) | | 175 | 184 | |
| Queue Length 95th (ft) | | 198 | 224 | |
| Internal Link Dist (ft) | | | 528 | |
| Turn Bay Length (ft) | | 350 | | |
| Base Capacity (vph) | | 449 | 2575 | |
| Starvation Cap Reductn | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | 0 | |
| Storage Cap Reductn | | 0 | 0 | |
| Reduced v/c Ratio | | 0.63 | 0.37 | |

| Intersection Summary |
|---|




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 9 | 2 | 15 | 30 | 7 | 36 | 1 | 6 | 1116 | 25 | 16 | 41 |
| Future Volume (vph) | 9 | 2 | 15 | 30 | 7 | 36 | 1 | 6 | 1116 | 25 | 16 | 41 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 125 | | 0 | | 330 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 |
| Ped Bike Factor | | 0.99 | | 1.00 | | | | | | | | |
| Frt | | 0.922 | | | 0.874 | | | | 0.997 | | | |
| Flt Protected | | 0.983 | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1692 | 0 | 1787 | 1644 | 0 | 0 | 1787 | 5120 | 0 | 0 | 1787 |
| Flt Permitted | | 0.867 | | 0.800 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 1492 | 0 | 1503 | 1644 | 0 | 0 | 1787 | 5120 | 0 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 15 | | | 37 | | | | 3 | | | |
| Link Speed (mph) | | 25 | | | 25 | | | | 40 | | | |
| Link Distance (ft) | | 642 | | | 490 | | | | 588 | | | |
| Travel Time (s) | | 17.5 | | | 13.4 | | | | 10.0 | | | |
| Confl. Peds. (#/hr) | | | 1 | 1 | | | | | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 9 | 2 | 15 | 31 | 7 | 37 | 1 | 6 | 1151 | 26 | 16 | 42 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 26 | 0 | 31 | 44 | 0 | 0 | 7 | 1177 | 0 | 0 | 58 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | Prot |
| Protected Phases | | 3 | | | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 |
| Minimum Split (s) | 39.2 | 39.2 | | 39.2 | 39.2 | | 9.3 | 9.3 | 33.3 | | 9.3 | 9.3 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 35.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 21.9% |
| Maximum Green (s) | 43.8 | 43.8 | | 43.8 | 43.8 | | 28.7 | 28.7 | 68.7 | | 28.7 | 28.7 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |
| Total Lost Time (s) | | 6.2 | | 6.2 | 6.2 | | | 6.3 | 6.3 | | | 6.3 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | 3.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | None |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | 26.0 | 26.0 | | 26.0 | 26.0 | | | | 20.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 6.9 | | 6.9 | 6.9 | | | 5.1 | 28.6 | | | 6.9 |
| Actuated g/C Ratio | | 0.14 | | 0.14 | 0.14 | | | 0.10 | 0.57 | | | 0.14 |
| v/c Ratio | | 0.12 | | 0.15 | 0.17 | | | 0.04 | 0.40 | | | 0.24 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 1018 | 24 |
| Future Volume (vph) | 1018 | 24 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Ped Bike Factor | | |
| Frt | 0.997 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5120 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5120 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 3 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 956 | |
| Travel Time (s) | 16.3 | |
| Confl. Peds. (#/hr) | | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 1049 | 25 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 1074 | 0 |
| Turn Type | NA | |
| Protected Phases | 2 | |
| Permitted Phases | | |
| Detector Phase | 2 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 33.3 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 46.9% | |
| Maximum Green (s) | 68.7 | |
| Yellow Time (s) | 4.0 | |
| All-Red Time (s) | 2.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.3 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | Min | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 20.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 34.1 | |
| Actuated g/C Ratio | 0.68 | |
| v/c Ratio | 0.31 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 17.8 | | 25.8 | 13.2 | | | 26.4 | 10.4 | | | 25.6 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |
| Total Delay (s/veh) | | 17.8 | | 25.8 | 13.2 | | | 26.4 | 10.4 | | | 25.6 |
| LOS | | B | | C | B | | | C | B | | | C |
| Approach Delay (s/veh) | | 17.8 | | | 18.4 | | | | 10.5 | | | |
| Approach LOS | | B | | | B | | | | B | | | |
| Queue Length 50th (ft) | | 3 | | 9 | 2 | | | 2 | 98 | | | 17 |
| Queue Length 95th (ft) | | 24 | | 34 | 28 | | | 13 | 154 | | | 51 |
| Internal Link Dist (ft) | | 562 | | | 410 | | | | 508 | | | |
| Turn Bay Length (ft) | | | | | | | | 125 | | | | 330 |
| Base Capacity (vph) | | 1270 | | 1277 | 1403 | | | 1084 | 5120 | | | 1084 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Reduced v/c Ratio | | 0.02 | | 0.02 | 0.03 | | | 0.01 | 0.23 | | | 0.05 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 50.3 | | | |
| Natural Cycle: 85 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.40 | | | |
| Intersection Signal Delay (s/veh): 9.1 | | Intersection LOS: A | |
| Intersection Capacity Utilization 50.0% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 8: Niagara Falls Blvd & Driveway 4/Boulevard Mall Driveway





| Lane Group | SBT | SBR |
|---|---|---|
| Control Delay (s/veh) | 5.8 | |
| Queue Delay | 0.0 | |
| Total Delay (s/veh) | 5.8 | |
| LOS | A | |
| Approach Delay (s/veh) | 6.8 | |
| Approach LOS | A | |
| Queue Length 50th (ft) | 43 | |
| Queue Length 95th (ft) | 121 | |
| Internal Link Dist (ft) | 876 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 5120 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.21 | |

Intersection Summary

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 23 | 15 | 19 | 33 | 15 | 36 | 25 | 28 | 1046 | 48 | 26 | 1036 |
| Future Volume (vph) | 23 | 15 | 19 | 33 | 15 | 36 | 25 | 28 | 1046 | 48 | 26 | 1036 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 150 | | 0 | 250 | |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 |
| Ped Bike Factor | | 0.99 | | 0.99 | | | | 1.00 | | | | 1.00 |
| Frt | | 0.954 | | | 0.893 | | | | 0.993 | | | 0.995 |
| Flt Protected | | 0.980 | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1747 | 0 | 1787 | 1680 | 0 | 0 | 1787 | 5100 | 0 | 1787 | 5104 |
| Flt Permitted | | 0.844 | | 0.719 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 1504 | 0 | 1342 | 1680 | 0 | 0 | 1781 | 5100 | 0 | 1787 | 5104 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 16 | | | 37 | | | | 5 | | | 4 |
| Link Speed (mph) | | 30 | | | 25 | | | | 40 | | | 40 |
| Link Distance (ft) | | 538 | | | 562 | | | | 2182 | | | 588 |
| Travel Time (s) | | 12.2 | | | 15.3 | | | | 37.2 | | | 10.0 |
| Confl. Peds. (#/hr) | | | 6 | 6 | | | | 5 | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 24 | 15 | 20 | 34 | 15 | 37 | 26 | 29 | 1078 | 49 | 27 | 1068 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 59 | 0 | 34 | 52 | 0 | 0 | 55 | 1127 | 0 | 27 | 1106 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | NA |
| Protected Phases | | 3 | | | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 10.0 |
| Minimum Split (s) | 41.6 | 41.6 | | 41.6 | 41.6 | | 16.3 | 16.3 | 31.3 | | 16.3 | 33.3 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 75.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 46.9% |
| Maximum Green (s) | 43.4 | 43.4 | | 43.4 | 43.4 | | 28.7 | 28.7 | 68.7 | | 28.7 | 68.7 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 |
| All-Red Time (s) | 3.4 | 3.4 | | 3.4 | 3.4 | | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.6 | | 6.6 | 6.6 | | | 6.3 | 6.3 | | 6.3 | 6.3 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 3.5 | 3.5 | | 3.5 | 3.5 | | 2.0 | 2.0 | 4.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | Min |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | | | | 7.0 |
| Flash Don't Walk (s) | 26.0 | 26.0 | | 26.0 | 26.0 | | | | | | | 20.0 |
| Pedestrian Calls (#/hr) | 5 | 5 | | 5 | 5 | | | | | | | 0 |
| Act Effct Green (s) | | 11.3 | | 11.3 | 11.3 | | | 7.4 | 33.4 | | 6.3 | 30.0 |
| Actuated g/C Ratio | | 0.20 | | 0.20 | 0.20 | | | 0.13 | 0.58 | | 0.11 | 0.52 |
| v/c Ratio | | 0.19 | | 0.13 | 0.14 | | | 0.24 | 0.38 | | 0.14 | 0.41 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 37 |
| Future Volume (vph) | 37 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Ped Bike Factor | |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | 5 |
| Peak Hour Factor | 0.97 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 38 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 19.1 | | 23.5 | 12.4 | | | 33.1 | 11.8 | | 34.8 | 14.4 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Delay (s/veh) | | 19.1 | | 23.5 | 12.4 | | | 33.1 | 11.8 | | 34.8 | 14.4 |
| LOS | | B | | C | B | | | C | B | | C | B |
| Approach Delay (s/veh) | | 19.1 | | | 16.8 | | | | 12.8 | | | 14.9 |
| Approach LOS | | B | | | B | | | | B | | | B |
| Queue Length 50th (ft) | | 11 | | 9 | 4 | | | 15 | 54 | | 8 | 99 |
| Queue Length 95th (ft) | | 48 | | 38 | 33 | | | 71 | 242 | | 44 | 248 |
| Internal Link Dist (ft) | | 458 | | | 482 | | | | 2102 | | | 508 |
| Turn Bay Length (ft) | | | | | | | | 150 | | | 250 | |
| Base Capacity (vph) | | 1200 | | 1068 | 1344 | | | 1037 | 4780 | | 1037 | 4784 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | | 0.05 | | 0.03 | 0.04 | | | 0.05 | 0.24 | | 0.03 | 0.23 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 57.2 | | | |
| Natural Cycle: 95 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.41 | | | |
| Intersection Signal Delay (s/veh): 14.0 | | Intersection LOS: B | |
| Intersection Capacity Utilization 53.9% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 9: Niagara Falls Blvd & Treadwell Rd/Driveway 2





| Lane Group | SBR |
|---|---|
| Control Delay (s/veh) | |
| Queue Delay | |
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 2 | 339 | 591 | 0 | 3 | 229 | 668 | 52 | 0 | 558 | 59 | 35 |
| Future Volume (vph) | 2 | 339 | 591 | 0 | 3 | 229 | 668 | 52 | 0 | 558 | 59 | 35 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 370 | | 0 | | 300 | | 300 | 0 | | 0 | |
| Storage Lanes | | 2 | | 0 | | 2 | | 1 | 0 | | 0 | |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | |
| Lane Util. Factor | 0.91 | 0.97 | 0.91 | 0.91 | 0.91 | 0.97 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 |
| Ped Bike Factor | | 1.00 | | | | 1.00 | | 0.98 | | | | |
| Frt | | | | | | | | 0.850 | | 0.986 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | | | | |
| Satd. Flow (prot) | 0 | 3467 | 5136 | 0 | 0 | 3467 | 5136 | 1599 | 0 | 5064 | 0 | 0 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | | | | |
| Satd. Flow (perm) | 0 | 3463 | 5136 | 0 | 0 | 3465 | 5136 | 1575 | 0 | 5064 | 0 | 0 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | | | | | | 119 | | 10 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 40 | | |
| Link Distance (ft) | | | 623 | | | | 1468 | | | 379 | | |
| Travel Time (s) | | | 10.6 | | | | 25.0 | | | 6.5 | | |
| Confl. Peds. (#/hr) | | 2 | | 1 | | 1 | | 2 | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 2 | 349 | 609 | 0 | 3 | 236 | 689 | 54 | 0 | 575 | 61 | 36 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 351 | 609 | 0 | 0 | 239 | 689 | 54 | 0 | 636 | 0 | 0 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | Perm | | NA | | Prot |
| Protected Phases | 3 | 3 | 8 | | 7 | 7 | 4 | | | 2 | | 1 |
| Permitted Phases | | | | | | | | 4 | | | | |
| Detector Phase | 3 | 3 | 8 | | 7 | 7 | 4 | 4 | | 2 | | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 6.0 | | 3.0 | 3.0 | 6.0 | 6.0 | | 10.0 | | 3.0 |
| Minimum Split (s) | 10.3 | 10.3 | 48.0 | | 10.3 | 10.3 | 48.0 | 48.0 | | 58.2 | | 12.3 |
| Total Split (s) | 37.0 | 37.0 | 48.0 | | 37.0 | 37.0 | 48.0 | 48.0 | | 68.0 | | 37.0 |
| Total Split (%) | 19.5% | 19.5% | 25.3% | | 19.5% | 19.5% | 25.3% | 25.3% | | 35.8% | | 19.5% |
| Maximum Green (s) | 29.7 | 29.7 | 40.7 | | 29.7 | 29.7 | 40.7 | 40.7 | | 59.8 | | 28.8 |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 4.0 |
| All-Red Time (s) | 3.3 | 3.3 | 3.3 | | 3.3 | 3.3 | 3.3 | 3.3 | | 4.2 | | 4.2 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | | |
| Total Lost Time (s) | | 7.3 | 7.3 | | | 7.3 | 7.3 | 7.3 | | 8.2 | | |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | Lag | | Lag | | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | | Yes | | Yes |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | | 2.0 | 2.0 | 4.0 | 4.0 | | 4.0 | | 2.0 |
| Recall Mode | None | None | None | | None | None | None | None | | C-Min | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | 7.0 | | 7.0 | | |
| Flash Don't Walk (s) | | | 30.0 | | | | 30.0 | 30.0 | | 39.0 | | |
| Pedestrian Calls (#/hr) | | | 1 | | | | 2 | 2 | | 0 | | |
| Act Effct Green (s) | | 25.3 | 41.8 | | | 17.5 | 34.0 | 34.0 | | 81.6 | | |
| Actuated g/C Ratio | | 0.13 | 0.22 | | | 0.09 | 0.18 | 0.18 | | 0.43 | | |
| v/c Ratio | | 0.76 | 0.54 | | | 0.75 | 0.75 | 0.14 | | 0.29 | | |




| Lane Group | SBL | SBT | SBR |
|---|---|---|---|
| Lane Configurations | | | |
| Traffic Volume (vph) | 209 | 507 | 376 |
| Future Volume (vph) | 209 | 507 | 376 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 |
| Storage Length (ft) | 450 | | 0 |
| Storage Lanes | 2 | | 1 |
| Taper Length (ft) | 25 | | |
| Lane Util. Factor | 0.97 | 0.95 | 1.00 |
| Ped Bike Factor | | | |
| Frt | | | 0.850 |
| Flt Protected | 0.950 | | |
| Satd. Flow (prot) | 3467 | 3574 | 1599 |
| Flt Permitted | 0.950 | | |
| Satd. Flow (perm) | 3467 | 3574 | 1599 |
| Right Turn on Red | | | Yes |
| Satd. Flow (RTOR) | | | 388 |
| Link Speed (mph) | | 40 | |
| Link Distance (ft) | | 2182 | |
| Travel Time (s) | | 37.2 | |
| Confl. Peds. (#/hr) | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% |
| Adj. Flow (vph) | 215 | 523 | 388 |
| Shared Lane Traffic (%) | | | |
| Lane Group Flow (vph) | 251 | 523 | 388 |
| Turn Type | Prot | NA | Perm |
| Protected Phases | 1 | 6 | |
| Permitted Phases | | | 6 |
| Detector Phase | 1 | 6 | 6 |
| Switch Phase | | | |
| Minimum Initial (s) | 3.0 | 10.0 | 10.0 |
| Minimum Split (s) | 12.3 | 58.2 | 58.2 |
| Total Split (s) | 37.0 | 105.0 | 105.0 |
| Total Split (%) | 19.5% | 55.3% | 55.3% |
| Maximum Green (s) | 28.8 | 96.8 | 96.8 |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 |
| All-Red Time (s) | 4.2 | 4.2 | 4.2 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 8.2 | 8.2 | 8.2 |
| Lead/Lag | Lead | | |
| Lead-Lag Optimize? | Yes | | |
| Vehicle Extension (s) | 2.0 | 4.0 | 4.0 |
| Recall Mode | None | C-Min | C-Min |
| Walk Time (s) | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 39.0 | 39.0 |
| Pedestrian Calls (#/hr) | | 2 | 2 |
| Act Effct Green (s) | 18.1 | 107.9 | 107.9 |
| Actuated g/C Ratio | 0.10 | 0.57 | 0.57 |
| v/c Ratio | 0.76 | 0.26 | 0.36 |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 90.3 | 67.0 | | | 98.6 | 79.2 | 0.8 | | 22.3 | | |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.3 | | |
| Total Delay (s/veh) | | 90.3 | 67.0 | | | 98.6 | 79.2 | 0.8 | | 22.5 | | |
| LOS | | F | E | | | F | E | A | | C | | |
| Approach Delay (s/veh) | | | 75.5 | | | | 79.6 | | | 22.5 | | |
| Approach LOS | | | E | | | | E | | | C | | |
| Queue Length 50th (ft) | | 221 | 249 | | | 153 | 303 | 0 | | 198 | | |
| Queue Length 95th (ft) | | 274 | 280 | | | 200 | 339 | 0 | | 122 | | |
| Internal Link Dist (ft) | | | 543 | | | | 1388 | | | 299 | | |
| Turn Bay Length (ft) | | 370 | | | | 300 | | 300 | | | | |
| Base Capacity (vph) | | 545 | 1175 | | | 541 | 1101 | 430 | | 2181 | | |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 844 | | |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | | |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | | |
| Reduced v/c Ratio | | 0.64 | 0.52 | | | 0.44 | 0.63 | 0.13 | | 0.48 | | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow, Master Intersection | | | |
| Natural Cycle: 140 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.76 | | | |
| Intersection Signal Delay (s/veh): 54.1 | | Intersection LOS: D | |
| Intersection Capacity Utilization 68.7% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 10: Niagara Falls Blvd & Sheridan Dr





| Lane Group | SBL | SBT | SBR |
|---|---|---|---|
| Control Delay (s/veh) | 98.6 | 22.2 | 2.9 |
| Queue Delay | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 98.6 | 22.2 | 2.9 |
| LOS | F | C | A |
| Approach Delay (s/veh) | | 32.3 | |
| Approach LOS | | C | |
| Queue Length 50th (ft) | 160 | 171 | 0 |
| Queue Length 95th (ft) | 208 | 242 | 57 |
| Internal Link Dist (ft) | | 2102 | |
| Turn Bay Length (ft) | 450 | | |
| Base Capacity (vph) | 525 | 2035 | 1077 |
| Starvation Cap Reductn | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 16 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.48 | 0.26 | 0.36 |

Intersection Summary



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 191 | 134 | 48 | 178 | 75 | 2 | 101 | 694 | 56 | 73 | 639 |
| Future Volume (vph) | 0 | 191 | 134 | 48 | 178 | 75 | 2 | 101 | 694 | 56 | 73 | 639 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 100 | 200 | | 0 | | 250 | | 0 | 0 | |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 0 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 |
| Ped Bike Factor | | | | | 1.00 | | | | | | | |
| Frt | | | 0.850 | | 0.955 | | | | 0.989 | | | 0.991 |
| Flt Protected | | | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 3505 | 1568 | 1752 | 3334 | 0 | 0 | 1752 | 4981 | 0 | 1752 | 3473 |
| Flt Permitted | | | | 0.498 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 3505 | 1568 | 919 | 3334 | 0 | 0 | 1752 | 4981 | 0 | 1752 | 3473 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 144 | | 33 | | | | 7 | | | 5 |
| Link Speed (mph) | | 30 | | | 35 | | | | 35 | | | 40 |
| Link Distance (ft) | | 718 | | | 1535 | | | | 1665 | | | 379 |
| Travel Time (s) | | 16.3 | | | 29.9 | | | | 32.4 | | | 6.5 |
| Confl. Peds. (#/hr) | 1 | | | | | 1 | | | | | | |
| Peak Hour Factor | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 |
| Heavy Vehicles (%) | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% |
| Adj. Flow (vph) | 0 | 205 | 144 | 52 | 191 | 81 | 2 | 109 | 746 | 60 | 78 | 687 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 205 | 144 | 52 | 272 | 0 | 0 | 111 | 806 | 0 | 78 | 729 |
| Turn Type | | NA | Perm | Perm | NA | | Prot | Prot | NA | | Prot | NA |
| Protected Phases | | 4 | | | 4 | | 1 | 1 | 2 | | 1 3 | 2 3 |
| Permitted Phases | | | 4 | 4 | | | | | | | | |
| Detector Phase | | 4 | 4 | 4 | 4 | | 1 | 1 | 2 | | 1 3 | 2 3 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | | |
| Minimum Split (s) | | 43.1 | 43.1 | 43.1 | 43.1 | | 9.8 | 9.8 | 35.8 | | | |
| Total Split (s) | | 54.0 | 54.0 | 54.0 | 54.0 | | 35.0 | 35.0 | 68.0 | | | |
| Total Split (%) | | 28.4% | 28.4% | 28.4% | 28.4% | | 18.4% | 18.4% | 35.8% | | | |
| Maximum Green (s) | | 46.9 | 46.9 | 46.9 | 46.9 | | 28.2 | 28.2 | 61.2 | | | |
| Yellow Time (s) | | 3.2 | 3.2 | 3.2 | 3.2 | | 3.9 | 3.9 | 3.9 | | | |
| All-Red Time (s) | | 3.9 | 3.9 | 3.9 | 3.9 | | 2.9 | 2.9 | 2.9 | | | |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | | |
| Total Lost Time (s) | | 7.1 | 7.1 | 7.1 | 7.1 | | | 6.8 | 6.8 | | | |
| Lead/Lag | | Lag | Lag | Lag | Lag | | Lead | Lead | Lag | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | 4.0 | | | |
| Recall Mode | | None | None | None | None | | None | None | C-Min | | | |
| Walk Time (s) | | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | | 29.0 | 29.0 | 29.0 | 29.0 | | | | 22.0 | | | |
| Pedestrian Calls (#/hr) | | 0 | 0 | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 19.0 | 19.0 | 19.0 | 19.0 | | | 16.4 | 115.4 | | 28.1 | 133.9 |
| Actuated g/C Ratio | | 0.10 | 0.10 | 0.10 | 0.10 | | | 0.09 | 0.61 | | 0.15 | 0.70 |
| v/c Ratio | | 0.59 | 0.50 | 0.57 | 0.75 | | | 0.74 | 0.27 | | 0.30 | 0.30 |



| Lane Group | SBR | Ø3 |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 39 | |
| Future Volume (vph) | 39 | |
| Ideal Flow (vphpl) | 1900 | |
| Storage Length (ft) | 0 | |
| Storage Lanes | 0 | |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | |
| Ped Bike Factor | | |
| Frt | | |
| Flt Protected | | |
| Satd. Flow (prot) | 0 | |
| Flt Permitted | | |
| Satd. Flow (perm) | 0 | |
| Right Turn on Red | Yes | |
| Satd. Flow (RTOR) | | |
| Link Speed (mph) | | |
| Link Distance (ft) | | |
| Travel Time (s) | | |
| Confl. Peds. (#/hr) | | |
| Peak Hour Factor | 0.93 | |
| Heavy Vehicles (%) | 3% | |
| Adj. Flow (vph) | 42 | |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 0 | |
| Turn Type | | |
| Protected Phases | | 3 |
| Permitted Phases | | |
| Detector Phase | | |
| Switch Phase | | |
| Minimum Initial (s) | | 3.0 |
| Minimum Split (s) | | 9.8 |
| Total Split (s) | | 33.0 |
| Total Split (%) | | 17% |
| Maximum Green (s) | | 26.2 |
| Yellow Time (s) | | 3.9 |
| All-Red Time (s) | | 2.9 |
| Lost Time Adjust (s) | | |
| Total Lost Time (s) | | |
| Lead/Lag | | Lead |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | | 2.0 |
| Recall Mode | | None |
| Walk Time (s) | | |
| Flash Don't Walk (s) | | |
| Pedestrian Calls (#/hr) | | |
| Act Effct Green (s) | | |
| Actuated g/C Ratio | | |
| v/c Ratio | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 88.0 | 16.1 | 104.1 | 85.7 | | | 110.8 | 18.8 | | 61.2 | 3.7 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.2 |
| Total Delay (s/veh) | | 88.0 | 16.1 | 104.1 | 85.7 | | | 110.8 | 18.8 | | 61.2 | 3.9 |
| LOS | | F | B | F | F | | | F | B | | E | A |
| Approach Delay (s/veh) | | 58.3 | | | 88.7 | | | | 29.9 | | | 9.4 |
| Approach LOS | | E | | | F | | | | C | | | A |
| Queue Length 50th (ft) | | 131 | 0 | 63 | 155 | | | 138 | 165 | | 97 | 6 |
| Queue Length 95th (ft) | | 174 | 73 | 115 | 205 | | | 207 | 239 | | 130 | 264 |
| Internal Link Dist (ft) | | 638 | | | 1455 | | | | 1585 | | | 299 |
| Turn Bay Length (ft) | | | 100 | 200 | | | | 250 | | | | |
| Base Capacity (vph) | | 865 | 495 | 226 | 847 | | | 260 | 3028 | | 501 | 2713 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 | 971 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | | 0.24 | 0.29 | 0.23 | 0.32 | | | 0.43 | 0.27 | | 0.16 | 0.42 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBSB, Start of Yellow | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.75 | | | |
| Intersection Signal Delay (s/veh): 35.1 | | Intersection LOS: D | |
| Intersection Capacity Utilization 61.1% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 11: Niagara Falls Blvd & Eggert Rd





| Lane Group | SBR | Ø3 |
|---|---|---|
| Control Delay (s/veh) | | |
| Queue Delay | | |
| Total Delay (s/veh) | | |
| LOS | | |
| Approach Delay (s/veh) | | |
| Approach LOS | | |
| Queue Length 50th (ft) | | |
| Queue Length 95th (ft) | | |
| Internal Link Dist (ft) | | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | | |
| Starvation Cap Reductn | | |
| Spillback Cap Reductn | | |
| Storage Cap Reductn | | |
| Reduced v/c Ratio | | |

| Intersection Summary |
|---|





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 51 | 486 | 185 | 182 | 687 | 7 | 251 | 62 | 167 | 14 | 50 | 47 |
| Future Volume (vph) | 51 | 486 | 185 | 182 | 687 | 7 | 251 | 62 | 167 | 14 | 50 | 47 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 400 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | 1.00 | | 0.98 | 1.00 | 1.00 | | 1.00 | 0.99 | | 1.00 | 0.99 | |
| Frt | | | 0.850 | | 0.999 | | | 0.891 | | | 0.927 | |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 5129 | 0 | 1787 | 1658 | 0 | 1787 | 1731 | 0 |
| Flt Permitted | 0.371 | | | 0.290 | | | 0.482 | | | 0.613 | | |
| Satd. Flow (perm) | 697 | 3574 | 1571 | 544 | 5129 | 0 | 905 | 1658 | 0 | 1151 | 1731 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 189 | | 2 | | | 121 | | | 42 | |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 25 | |
| Link Distance (ft) | | 1441 | | | 678 | | | 472 | | | 208 | |
| Travel Time (s) | | 21.8 | | | 10.3 | | | 9.2 | | | 5.7 | |
| Confl. Peds. (#/hr) | 2 | | 4 | 4 | | 2 | 2 | | 2 | 2 | | 2 |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 52 | 496 | 189 | 186 | 701 | 7 | 256 | 63 | 170 | 14 | 51 | 48 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 52 | 496 | 189 | 186 | 708 | 0 | 256 | 233 | 0 | 14 | 99 | 0 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Permitted Phases | 2 | 2 | 2 | 6 | | | 8 | | | 4 | | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 5.0 | | 5.0 | 10.0 | | 5.0 | 5.0 | |
| Minimum Split (s) | 10.0 | 27.6 | 27.6 | 10.0 | 27.6 | | 10.0 | 27.6 | | 10.0 | 27.6 | |
| Total Split (s) | 15.0 | 45.0 | 45.0 | 15.0 | 45.0 | | 15.0 | 25.0 | | 15.0 | 25.0 | |
| Total Split (%) | 15.0% | 45.0% | 45.0% | 15.0% | 45.0% | | 15.0% | 25.0% | | 15.0% | 25.0% | |
| Maximum Green (s) | 10.0 | 40.0 | 40.0 | 10.0 | 40.0 | | 10.0 | 20.0 | | 10.0 | 20.0 | |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Gap (s) | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | |
| Time Before Reduce (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Time To Reduce (s) | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | |
| Recall Mode | None | Min | Min | None | Min | | None | None | | None | None | |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | 15.0 | 15.0 | | 15.0 | | | 15.0 | | | 15.0 | |
| Pedestrian Calls (#/hr) | | 4 | 4 | | 2 | | | 4 | | | 2 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Act Effct Green (s) | 23.1 | 15.2 | 15.2 | 28.3 | 22.9 | | 22.3 | 20.8 | | 15.6 | 10.4 | |
| Actuated g/C Ratio | 0.37 | 0.24 | 0.24 | 0.45 | 0.36 | | 0.35 | 0.33 | | 0.25 | 0.16 | |
| v/c Ratio | 0.13 | 0.58 | 0.36 | 0.43 | 0.38 | | 0.55 | 0.37 | | 0.04 | 0.31 | |
| Control Delay (s/veh) | 12.4 | 25.5 | 6.3 | 15.1 | 19.1 | | 20.3 | 11.3 | | 13.9 | 18.7 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Delay (s/veh) | 12.4 | 25.5 | 6.3 | 15.1 | 19.1 | | 20.3 | 11.3 | | 13.9 | 18.7 | |
| LOS | B | C | A | B | B | | C | B | | B | B | |
| Approach Delay (s/veh) | | 19.6 | | | 18.2 | | | 16.0 | | | 18.1 | |
| Approach LOS | | B | | | B | | | B | | | B | |
| Queue Length 50th (ft) | 10 | 89 | 0 | 40 | 83 | | 70 | 28 | | 3 | 20 | |
| Queue Length 95th (ft) | 36 | 166 | 48 | 103 | 152 | | 140 | 106 | | 14 | 61 | |
| Internal Link Dist (ft) | | 1361 | | | 598 | | | 392 | | | 128 | |
| Turn Bay Length (ft) | 200 | | 200 | 400 | | | | | | | | |
| Base Capacity (vph) | 464 | 2374 | 1107 | 449 | 3407 | | 465 | 698 | | 450 | 610 | |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.11 | 0.21 | 0.17 | 0.41 | 0.21 | | 0.55 | 0.33 | | 0.03 | 0.16 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 100 | | | |
| Actuated Cycle Length: 63.2 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.58 | | | |
| Intersection Signal Delay (s/veh): 18.2 | | Intersection LOS: B | |
| Intersection Capacity Utilization 57.2% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 12: Alberta Dr/Driveway 5 & Maple Rd





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 113 | 490 | 73 | 208 | 666 | 259 | 108 | 331 | 140 | 1 | 290 | 396 |
| Future Volume (vph) | 113 | 490 | 73 | 208 | 666 | 259 | 108 | 331 | 140 | 1 | 290 | 396 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | 430 | 350 | | 0 | 150 | | 150 | | 500 | |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 1 | | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | 0.98 | 1.00 | | | 1.00 | | | | | |
| Frt | | | 0.850 | | 0.958 | | | | 0.850 | | | |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 4920 | 0 | 1787 | 1881 | 1599 | 0 | 1787 | 1881 |
| Flt Permitted | 0.204 | | | 0.236 | | | 0.476 | | | | 0.250 | |
| Satd. Flow (perm) | 384 | 3574 | 1564 | 444 | 4920 | 0 | 895 | 1881 | 1599 | 0 | 470 | 1881 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | |
| Satd. Flow (RTOR) | | | 218 | | 86 | | | | 218 | | | |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | | 35 |
| Link Distance (ft) | | 678 | | | 748 | | | 1795 | | | | 1039 |
| Travel Time (s) | | 10.3 | | | 11.3 | | | 35.0 | | | | 20.2 |
| Confl. Peds. (#/hr) | | | 1 | 1 | | | 1 | | | | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 115 | 500 | 74 | 212 | 680 | 264 | 110 | 338 | 143 | 1 | 296 | 404 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 115 | 500 | 74 | 212 | 944 | 0 | 110 | 338 | 143 | 0 | 297 | 404 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | Perm | pm+pt | pm+pt | NA |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 7 | 4 |
| Permitted Phases | 2 | | 2 | 6 | | | 8 | | 8 | 4 | 4 | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | 8 | 7 | 7 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | | 5.0 | 10.0 | 10.0 | 5.0 | 5.0 | 10.0 |
| Minimum Split (s) | 10.0 | 38.0 | 38.0 | 10.0 | 38.0 | | 10.0 | 38.0 | 38.0 | 10.0 | 10.0 | 38.0 |
| Total Split (s) | 15.0 | 30.0 | 30.0 | 25.0 | 40.0 | | 15.0 | 35.0 | 35.0 | 25.0 | 25.0 | 45.0 |
| Total Split (%) | 13.0% | 26.1% | 26.1% | 21.7% | 34.8% | | 13.0% | 30.4% | 30.4% | 21.7% | 21.7% | 39.1% |
| Maximum Green (s) | 10.0 | 24.0 | 24.0 | 20.0 | 34.0 | | 10.0 | 29.0 | 29.0 | 20.0 | 20.0 | 39.0 |
| Yellow Time (s) | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | | 3.0 | 4.0 | 4.0 | 3.0 | 3.0 | 4.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 6.0 | 6.0 | 5.0 | 6.0 | | 5.0 | 6.0 | 6.0 | | 5.0 | 6.0 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | Lag | Lead | Lead | Lag |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 |
| Minimum Gap (s) | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 |
| Time Before Reduce (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 |
| Time To Reduce (s) | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 |
| Recall Mode | None | None | None | None | None | | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | 7.0 | | | 7.0 |
| Flash Don't Walk (s) | | 25.0 | 25.0 | | 25.0 | | | 25.0 | 25.0 | | | 25.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 1 | | | 0 | 0 | | | 1 |



| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 139 |
| Future Volume (vph) | 139 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 150 |
| Storage Lanes | 1 |
| Taper Length (ft) | |
| Lane Util. Factor | 1.00 |
| Ped Bike Factor | 0.99 |
| Frt | 0.850 |
| Flt Protected | |
| Satd. Flow (prot) | 1599 |
| Flt Permitted | |
| Satd. Flow (perm) | 1578 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | 171 |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | 1 |
| Peak Hour Factor | 0.98 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 142 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 142 |
| Turn Type | Perm |
| Protected Phases | |
| Permitted Phases | 4 |
| Detector Phase | 4 |
| Switch Phase | |
| Minimum Initial (s) | 10.0 |
| Minimum Split (s) | 38.0 |
| Total Split (s) | 45.0 |
| Total Split (%) | 39.1% |
| Maximum Green (s) | 39.0 |
| Yellow Time (s) | 4.0 |
| All-Red Time (s) | 2.0 |
| Lost Time Adjust (s) | 0.0 |
| Total Lost Time (s) | 6.0 |
| Lead/Lag | Lag |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | 4.0 |
| Minimum Gap (s) | 0.2 |
| Time Before Reduce (s) | 7.0 |
| Time To Reduce (s) | 0.5 |
| Recall Mode | None |
| Walk Time (s) | 7.0 |
| Flash Don't Walk (s) | 25.0 |
| Pedestrian Calls (#/hr) | 1 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Act Effct Green (s) | 30.1 | 19.6 | 19.6 | 38.6 | 24.5 | | 32.8 | 22.6 | 22.6 | | 46.1 | 34.0 |
| Actuated g/C Ratio | 0.31 | 0.20 | 0.20 | 0.40 | 0.25 | | 0.34 | 0.23 | 0.23 | | 0.48 | 0.35 |
| v/c Ratio | 0.45 | 0.69 | 0.15 | 0.56 | 0.72 | | 0.28 | 0.77 | 0.26 | | 0.64 | 0.61 |
| Control Delay (s/veh) | 25.9 | 42.7 | 0.7 | 26.0 | 33.6 | | 18.2 | 48.4 | 1.7 | | 23.6 | 32.9 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Delay (s/veh) | 25.9 | 42.7 | 0.7 | 26.0 | 33.6 | | 18.2 | 48.4 | 1.7 | | 23.6 | 32.9 |
| LOS | C | D | A | C | C | | B | D | A | | C | C |
| Approach Delay (s/veh) | | 35.4 | | | 32.2 | | | 31.5 | | | | 24.6 |
| Approach LOS | | D | | | C | | | C | | | | C |
| Queue Length 50th (ft) | 44 | 153 | 0 | 87 | 182 | | 36 | 197 | 0 | | 110 | 214 |
| Queue Length 95th (ft) | 89 | 240 | 0 | 154 | 249 | | 78 | 335 | 6 | | 200 | 359 |
| Internal Link Dist (ft) | | 598 | | | 668 | | | 1715 | | | | 959 |
| Turn Bay Length (ft) | 250 | | 430 | 350 | | | 150 | | 150 | | 500 | |
| Base Capacity (vph) | 272 | 915 | 562 | 471 | 1840 | | 409 | 582 | 645 | | 505 | 783 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | 0.42 | 0.55 | 0.13 | 0.45 | 0.51 | | 0.27 | 0.58 | 0.22 | | 0.59 | 0.52 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 115 | | | |
| Actuated Cycle Length: 96.5 | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.77 | | | |
| Intersection Signal Delay (s/veh): 30.8 | | Intersection LOS: C | |
| Intersection Capacity Utilization 77.4% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 13: Bailey Ave & Maple Rd





| Lane Group | SBR |
|---|---|
| Act Effct Green (s) | 34.0 |
| Actuated g/C Ratio | 0.35 |
| v/c Ratio | 0.21 |
| Control Delay (s/veh) | 3.1 |
| Queue Delay | 0.0 |
| Total Delay (s/veh) | 3.1 |
| LOS | A |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | 0 |
| Queue Length 95th (ft) | 28 |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | 150 |
| Base Capacity (vph) | 756 |
| Starvation Cap Reductn | 0 |
| Spillback Cap Reductn | 0 |
| Storage Cap Reductn | 0 |
| Reduced v/c Ratio | 0.19 |

Intersection Summary





| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Volume (vph) | 83 | 835 | 1020 | 158 | 190 | 127 |
| Future Volume (vph) | 83 | 835 | 1020 | 158 | 190 | 127 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | | 100 | 100 | 0 |
| Storage Lanes | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 0.91 | 0.91 | 1.00 | 1.00 |
| Frt | | | 0.980 | | | 0.850 |
| Flt Protected | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1787 | 3574 | 5033 | 0 | 1787 | 1599 |
| Flt Permitted | 0.950 | | | | 0.950 | |
| Satd. Flow (perm) | 1787 | 3574 | 5033 | 0 | 1787 | 1599 |
| Right Turn on Red | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | 46 | | | 138 |
| Link Speed (mph) | | 35 | 45 | | 30 | |
| Link Distance (ft) | | 748 | 466 | | 1444 | |
| Travel Time (s) | | 14.6 | 7.1 | | 32.8 | |
| Peak Hour Factor | 0.92 | 0.92 | 0.92 | 0.92 | 0.92 | 0.92 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 90 | 908 | 1109 | 172 | 207 | 138 |
| Shared Lane Traffic (%) | | | | | | |
| Lane Group Flow (vph) | 90 | 908 | 1281 | 0 | 207 | 138 |
| Turn Type | Prot | NA | NA | | Prot | custom |
| Protected Phases | 5 | 2 | 6 | | 4 | 4 |
| Permitted Phases | | | | | | 6 |
| Detector Phase | 5 | 2 | 6 | | 4 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| Minimum Split (s) | 9.0 | 27.0 | 27.0 | | 27.0 | 27.0 |
| Total Split (s) | 15.0 | 95.0 | 80.0 | | 25.0 | 25.0 |
| Total Split (%) | 12.5% | 79.2% | 66.7% | | 20.8% | 20.8% |
| Maximum Green (s) | 10.0 | 90.0 | 75.0 | | 20.0 | 20.0 |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | | | |
| Lead-Lag Optimize? | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | Min | Min | Min | | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 11.0 | 11.0 | | 11.0 | 11.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 0 | 0 |
| Act Effct Green (s) | 8.6 | 39.1 | 25.4 | | 12.8 | 43.3 |
| Actuated g/C Ratio | 0.14 | 0.63 | 0.41 | | 0.21 | 0.70 |
| v/c Ratio | 0.37 | 0.40 | 0.62 | | 0.56 | 0.12 |
| Control Delay (s/veh) | 31.9 | 6.6 | 15.6 | | 30.2 | 0.9 |
| Queue Delay | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 31.9 | 6.6 | 15.6 | | 30.2 | 0.9 |
| LOS | C | A | B | | C | A |
| Approach Delay (s/veh) | | 8.8 | 15.6 | | 18.4 | |
| Approach LOS | | A | B | | B | |
| Queue Length 50th (ft) | 31 | 74 | 128 | | 71 | 0 |
| Queue Length 95th (ft) | 83 | 133 | 198 | | 149 | 11 |
| Internal Link Dist (ft) | | 668 | 386 | | 1364 | |
| Turn Bay Length (ft) | 250 | | | | 100 | |
| Base Capacity (vph) | 295 | 3574 | 5010 | | 591 | 1338 |
| Starvation Cap Reductn | 0 | 0 | 21 | | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | 0.31 | 0.25 | 0.26 | | 0.35 | 0.10 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 62.2 | | | |
| Natural Cycle: 65 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.62 | | | |
| Intersection Signal Delay (s/veh): 13.4 | | Intersection LOS: B | |
| Intersection Capacity Utilization 50.9% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 14: Maple Rd & Bowmart Parkway







| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 1014 | 14 | 9 | 1205 | 0 | 22 | 0 | 10 | 0 | 1 | 2 |
| Future Volume (vph) | 0 | 1014 | 14 | 9 | 1205 | 0 | 22 | 0 | 10 | 0 | 1 | 2 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 150 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | 0 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.998 | | | | | | 0.956 | | | 0.900 | |
| Flt Protected | | | | 0.950 | | | | 0.967 | | | | |
| Satd. Flow (prot) | 0 | 3567 | 0 | 1787 | 3574 | 0 | 0 | 1739 | 0 | 1881 | 1693 | 0 |
| Flt Permitted | | | | 0.950 | | | | | | | | |
| Satd. Flow (perm) | 0 | 3567 | 0 | 1787 | 3574 | 0 | 0 | 1798 | 0 | 1881 | 1693 | 0 |
| Right Turn on Red | | | No | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | | | | 59 | | | 2 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 10 | |
| Link Distance (ft) | | 466 | | | 1563 | | | 418 | | | 259 | |
| Travel Time (s) | | 9.1 | | | 30.4 | | | 9.5 | | | 17.7 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 0 | 1067 | 15 | 9 | 1268 | 0 | 23 | 0 | 11 | 0 | 1 | 2 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 1082 | 0 | 9 | 1268 | 0 | 0 | 34 | 0 | 0 | 3 | 0 |
| Turn Type | | NA | | Prot | NA | | Perm | NA | | Perm | NA | |
| Protected Phases | | 2 | | 1 | 6 | | | 4 | | | 8 | |
| Permitted Phases | | | | | | | 4 | | | 8 | | |
| Detector Phase | | 2 | | 1 | 6 | | 4 | 4 | | 8 | 8 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Minimum Split (s) | | 27.0 | | 9.5 | 27.0 | | 27.0 | 27.0 | | 42.0 | 42.0 | |
| Total Split (s) | | 60.0 | | 20.0 | 80.0 | | 40.0 | 40.0 | | 40.0 | 40.0 | |
| Total Split (%) | | 50.0% | | 16.7% | 66.7% | | 33.3% | 33.3% | | 33.3% | 33.3% | |
| Maximum Green (s) | | 55.0 | | 15.5 | 75.0 | | 35.0 | 35.0 | | 35.0 | 35.0 | |
| Yellow Time (s) | | 3.0 | | 3.5 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | | 2.0 | | 1.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | 4.5 | 5.0 | | | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | Lag | | Lead | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | 4.0 | | 3.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Gap (s) | | 0.2 | | 3.0 | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | |
| Time Before Reduce (s) | | 7.0 | | 0.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Time To Reduce (s) | | 0.5 | | 0.0 | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | |
| Recall Mode | | Min | | None | Min | | None | None | | None | None | |
| Walk Time (s) | | | | | 7.0 | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | | | 30.0 | | | | | 30.0 | 30.0 | |
| Pedestrian Calls (#/hr) | | | | | 0 | | | | | 0 | 0 | |
| Act Effct Green (s) | | 35.7 | | 6.1 | 37.5 | | | 6.9 | | | 6.9 | |
| Actuated g/C Ratio | | 0.83 | | 0.14 | 0.87 | | | 0.16 | | | 0.16 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | | 0.37 | | 0.04 | 0.41 | | | 0.10 | | | 0.01 | |
| Control Delay (s/veh) | | 4.6 | | 20.2 | 2.7 | | | 4.6 | | | 16.7 | |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | | 0.0 | |
| Total Delay (s/veh) | | 4.6 | | 20.2 | 2.7 | | | 4.6 | | | 16.7 | |
| LOS | | A | | C | A | | | A | | | B | |
| Approach Delay (s/veh) | | 4.6 | | | 2.9 | | | 4.6 | | | 16.7 | |
| Approach LOS | | A | | | A | | | A | | | B | |
| Queue Length 50th (ft) | | 0 | | 2 | 0 | | | 0 | | | 0 | |
| Queue Length 95th (ft) | | 182 | | 13 | 115 | | | 12 | | | 6 | |
| Internal Link Dist (ft) | | 386 | | | 1483 | | | 338 | | | 179 | |
| Turn Bay Length (ft) | | | | 150 | | | | | | | | |
| Base Capacity (vph) | | 3567 | | 666 | 3574 | | | 1523 | | | 1426 | |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | | 0.30 | | 0.01 | 0.35 | | | 0.02 | | | 0.00 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 43 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.41 | | | |
| Intersection Signal Delay (s/veh): 3.7 | | Intersection LOS: A | |
| Intersection Capacity Utilization 50.1% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 15: Hillcrest Dr/Driveway 6 & Maple Rd







| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 298 | 565 | 76 | 68 | 660 | 98 | 95 | 241 | 75 | 151 | 261 | 359 |
| Future Volume (vph) | 298 | 565 | 76 | 68 | 660 | 98 | 95 | 241 | 75 | 151 | 261 | 359 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 100 | | 0 | 150 | | 150 | 200 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 1 | | 1 | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | 0.97 | 1.00 | | | 1.00 | | | | | 0.99 |
| Frt | | | 0.850 | | | 0.850 | | | 0.850 | | | 0.850 |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 3574 | 1599 | 1787 | 1881 | 1599 | 1787 | 1881 | 1599 |
| Flt Permitted | 0.268 | | | 0.435 | | | 0.350 | | | 0.302 | | |
| Satd. Flow (perm) | 504 | 3574 | 1557 | 816 | 3574 | 1599 | 657 | 1881 | 1599 | 568 | 1881 | 1576 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 132 | | | 185 | | | 187 | | | 366 |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 45 | |
| Link Distance (ft) | | 1563 | | | 492 | | | 510 | | | 929 | |
| Travel Time (s) | | 23.7 | | | 7.5 | | | 9.9 | | | 14.1 | |
| Confl. Peds. (#/hr) | | | 3 | 3 | | | 2 | | | | | 2 |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 304 | 577 | 78 | 69 | 673 | 100 | 97 | 246 | 77 | 154 | 266 | 366 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 304 | 577 | 78 | 69 | 673 | 100 | 97 | 246 | 77 | 154 | 266 | 366 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm |
| Protected Phases | 1 | 6 | | 5 | 2 | | 7 | 4 | | 3 | 8 | |
| Permitted Phases | 6 | | 6 | 2 | | 2 | 4 | | 4 | 8 | | 8 |
| Detector Phase | 1 | 6 | 6 | 5 | 2 | 2 | 7 | 4 | 4 | 3 | 8 | 8 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 | 10.0 | 3.0 | 6.0 | 6.0 | 3.0 | 6.0 | 6.0 |
| Minimum Split (s) | 9.8 | 39.8 | 39.8 | 9.8 | 38.8 | 38.8 | 9.6 | 40.6 | 40.6 | 9.6 | 40.6 | 40.6 |
| Total Split (s) | 34.0 | 58.0 | 58.0 | 20.0 | 44.0 | 44.0 | 20.0 | 42.0 | 42.0 | 20.0 | 42.0 | 42.0 |
| Total Split (%) | 24.3% | 41.4% | 41.4% | 14.3% | 31.4% | 31.4% | 14.3% | 30.0% | 30.0% | 14.3% | 30.0% | 30.0% |
| Maximum Green (s) | 27.2 | 51.2 | 51.2 | 13.2 | 37.2 | 37.2 | 13.4 | 35.4 | 35.4 | 13.4 | 35.4 | 35.4 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.3 | 2.3 | 2.3 | 2.3 | 2.3 | 2.3 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 | 6.6 | 6.6 | 6.6 | 6.6 | 6.6 | 6.6 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 |
| Recall Mode | None | C-Max | C-Max | None | C-Max | C-Max | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 26.0 | 26.0 | | 25.0 | 25.0 | | 27.0 | 27.0 | | 27.0 | 27.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 3 | 3 | | 0 | 0 | | 0 | 0 |
| Act Effct Green (s) | 82.4 | 70.9 | 70.9 | 63.6 | 56.6 | 56.6 | 35.3 | 25.4 | 25.4 | 40.0 | 27.7 | 27.7 |
| Actuated g/C Ratio | 0.59 | 0.51 | 0.51 | 0.45 | 0.40 | 0.40 | 0.25 | 0.18 | 0.18 | 0.29 | 0.20 | 0.20 |
| v/c Ratio | 0.65 | 0.32 | 0.09 | 0.17 | 0.47 | 0.13 | 0.40 | 0.72 | 0.17 | 0.57 | 0.72 | 0.60 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | 22.7 | 23.2 | 0.4 | 14.1 | 31.9 | 3.6 | 37.7 | 65.5 | 0.9 | 43.1 | 62.9 | 8.6 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 22.7 | 23.2 | 0.4 | 14.1 | 31.9 | 3.6 | 37.7 | 65.5 | 0.9 | 43.1 | 62.9 | 8.6 |
| LOS | C | C | A | B | C | A | D | E | A | D | E | A |
| Approach Delay (s/veh) | | 21.2 | | | 27.1 | | | 47.2 | | | 33.7 | |
| Approach LOS | | C | | | C | | | D | | | C | |
| Queue Length 50th (ft) | 132 | 164 | 0 | 18 | 241 | 6 | 64 | 215 | 0 | 105 | 228 | 0 |
| Queue Length 95th (ft) | 228 | 251 | 3 | 34 | 370 | 27 | 97 | 283 | 0 | 146 | 306 | 83 |
| Internal Link Dist (ft) | | 1483 | | | 412 | | | 430 | | | 849 | |
| Turn Bay Length (ft) | 200 | | 200 | 100 | | | 150 | | 150 | 200 | | |
| Base Capacity (vph) | 546 | 1811 | 854 | 498 | 1444 | 756 | 290 | 475 | 544 | 283 | 476 | 671 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.56 | 0.32 | 0.09 | 0.14 | 0.47 | 0.13 | 0.33 | 0.52 | 0.14 | 0.54 | 0.56 | 0.55 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 140 | | | |
| Actuated Cycle Length: 140 | | | |
| Offset: 84 (60%), Referenced to phase 2:WBTL and 6:EBTL, Start of Yellow | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.72 | | | |
| Intersection Signal Delay (s/veh): 29.8 | | Intersection LOS: C | |
| Intersection Capacity Utilization 78.1% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 16: Sweet Home Rd & Maple Rd






| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Volume (vph) | 11 | 647 | 679 | 178 | 14 | 104 |
| Future Volume (vph) | 11 | 647 | 679 | 178 | 14 | 104 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 100 | | | 115 | 0 | 0 |
| Storage Lanes | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 |
| Frt | | | | 0.850 | | 0.850 |
| Flt Protected | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1770 | 3539 | 3539 | 1583 | 1770 | 1583 |
| Flt Permitted | 0.377 | | | | 0.950 | |
| Satd. Flow (perm) | 702 | 3539 | 3539 | 1583 | 1770 | 1583 |
| Right Turn on Red | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | | | | 111 |
| Link Speed (mph) | | 45 | 45 | | 45 | |
| Link Distance (ft) | | 3286 | 644 | | 265 | |
| Travel Time (s) | | 49.8 | 9.8 | | 4.0 | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Adj. Flow (vph) | 12 | 688 | 722 | 189 | 15 | 111 |
| Shared Lane Traffic (%) | | | | | | |
| Lane Group Flow (vph) | 12 | 688 | 722 | 189 | 15 | 111 |
| Turn Type | Perm | NA | NA | custom | Prot | Perm |
| Protected Phases | | 2 | 6 | 8 6 | 8 | |
| Permitted Phases | 2 | | | 6 | | 8 |
| Detector Phase | 2 | 2 | 6 | 8 6 | 8 | 8 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | | 6.0 | 6.0 |
| Minimum Split (s) | 35.3 | 35.3 | 35.3 | | 13.2 | 13.2 |
| Total Split (s) | 80.0 | 80.0 | 80.0 | | 60.0 | 60.0 |
| Total Split (%) | 57.1% | 57.1% | 57.1% | | 42.9% | 42.9% |
| Maximum Green (s) | 73.7 | 73.7 | 73.7 | | 53.8 | 53.8 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | | 1.9 | 1.9 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 6.3 | 6.3 | 6.3 | | 6.2 | 6.2 |
| Lead/Lag | | | | | | |
| Lead-Lag Optimize? | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | C-Max | C-Max | C-Max | | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | | | |
| Flash Don't Walk (s) | 22.0 | 22.0 | 22.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | | | |
| Act Effct Green (s) | 119.8 | 119.8 | 119.8 | 140.0 | 7.7 | 7.7 |
| Actuated g/C Ratio | 0.86 | 0.86 | 0.86 | 1.00 | 0.06 | 0.06 |
| v/c Ratio | 0.02 | 0.23 | 0.24 | 0.12 | 0.15 | 0.58 |
| Control Delay (s/veh) | 0.4 | 1.1 | 1.2 | 0.2 | 65.1 | 22.8 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 0.4 | 1.1 | 1.2 | 0.2 | 65.1 | 22.8 |

| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| LOS | A | A | A | A | E | C |
| Approach Delay (s/veh) | | 1.1 | 1.0 | | 27.8 | |
| Approach LOS | | A | A | | C | |
| Queue Length 50th (ft) | 0 | 3 | 15 | 0 | 13 | 0 |
| Queue Length 95th (ft) | m1 | 10 | 17 | 0 | 37 | 60 |
| Internal Link Dist (ft) | | 3206 | 564 | | 185 | |
| Turn Bay Length (ft) | 100 | | | 115 | | |
| Base Capacity (vph) | 600 | 3027 | 3027 | 1583 | 680 | 676 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.02 | 0.23 | 0.24 | 0.12 | 0.02 | 0.16 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 140 | | | |
| Actuated Cycle Length: 140 | | | |
| Offset: 59 (42%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.58 | | | |
| Intersection Signal Delay (s/veh): 3.0 | | Intersection LOS: A | |
| Intersection Capacity Utilization 35.6% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 17: Maple Rd & Millersprt Hwy SB Rmps



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 62 | 526 | 0 | 0 | 822 | 6 | 38 | 1 | 335 | 0 | 0 | 0 |
| Future Volume (vph) | 62 | 526 | 0 | 0 | 822 | 6 | 38 | 1 | 335 | 0 | 0 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 0 | 1 | | 0 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | | | 0.999 | | | 0.850 | | | | |
| Flt Protected | 0.950 | | | | | | 0.950 | | | | | |
| Satd. Flow (prot) | 1787 | 3574 | 0 | 0 | 3571 | 0 | 1787 | 1599 | 0 | 0 | 0 | 0 |
| Flt Permitted | 0.313 | | | | | | 0.950 | | | | | |
| Satd. Flow (perm) | 589 | 3574 | 0 | 0 | 3571 | 0 | 1787 | 1599 | 0 | 0 | 0 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | 1 | | | 275 | | | | |
| Link Speed (mph) | | 45 | | | 45 | | | 45 | | | 45 | |
| Link Distance (ft) | | 644 | | | 547 | | | 161 | | | 257 | |
| Travel Time (s) | | 9.8 | | | 8.3 | | | 2.4 | | | 3.9 | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 66 | 560 | 0 | 0 | 874 | 6 | 40 | 1 | 356 | 0 | 0 | 0 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 66 | 560 | 0 | 0 | 880 | 0 | 40 | 357 | 0 | 0 | 0 | 0 |
| Turn Type | Perm | NA | | | NA | | Perm | NA | | | | |
| Protected Phases | | 2 | | | 6 | | | 4 | | | | |
| Permitted Phases | 2 | | | | | | 4 | | | | | |
| Detector Phase | 2 | 2 | | | 6 | | 4 | 4 | | | | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 20.0 | 20.0 | | | 20.0 | | 6.0 | 6.0 | | | | |
| Minimum Split (s) | 29.0 | 29.0 | | | 29.0 | | 23.0 | 23.0 | | | | |
| Total Split (s) | 80.0 | 80.0 | | | 80.0 | | 60.0 | 60.0 | | | | |
| Total Split (%) | 57.1% | 57.1% | | | 57.1% | | 42.9% | 42.9% | | | | |
| Maximum Green (s) | 74.0 | 74.0 | | | 74.0 | | 53.8 | 53.8 | | | | |
| Yellow Time (s) | 4.3 | 4.3 | | | 4.3 | | 4.3 | 4.3 | | | | |
| All-Red Time (s) | 1.7 | 1.7 | | | 1.7 | | 1.9 | 1.9 | | | | |
| Lost Time Adjust (s) | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | | | | |
| Total Lost Time (s) | 6.0 | 6.0 | | | 6.0 | | 6.2 | 6.2 | | | | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | | 3.0 | | 3.0 | 3.0 | | | | |
| Recall Mode | C-Max | C-Max | | | C-Max | | None | None | | | | |
| Walk Time (s) | 7.0 | 7.0 | | | 7.0 | | | | | | | |
| Flash Don't Walk (s) | 16.0 | 16.0 | | | 16.0 | | | | | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | 0 | | | | | | | |
| Act Effct Green (s) | 112.4 | 112.4 | | | 112.4 | | 15.4 | 15.4 | | | | |
| Actuated g/C Ratio | 0.80 | 0.80 | | | 0.80 | | 0.11 | 0.11 | | | | |
| v/c Ratio | 0.14 | 0.20 | | | 0.31 | | 0.21 | 0.85 | | | | |
| Control Delay (s/veh) | 1.8 | 1.1 | | | 4.6 | | 54.9 | 33.2 | | | | |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | | | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 1.8 | 1.1 | | | 4.6 | | 54.9 | 33.2 | | | | |
| LOS | A | A | | | A | | D | C | | | | |
| Approach Delay (s/veh) | | 1.2 | | | 4.6 | | | 35.4 | | | | |
| Approach LOS | | A | | | A | | | D | | | | |
| Queue Length 50th (ft) | 3 | 12 | | | 86 | | 34 | 73 | | | | |
| Queue Length 95th (ft) | 9 | 26 | | | 178 | | 65 | 179 | | | | |
| Internal Link Dist (ft) | | 564 | | | 467 | | | 81 | | | 177 | |
| Turn Bay Length (ft) | 150 | | | | | | | | | | | |
| Base Capacity (vph) | 473 | 2870 | | | 2868 | | 686 | 783 | | | | |
| Starvation Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Storage Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Reduced v/c Ratio | 0.14 | 0.20 | | | 0.31 | | 0.06 | 0.46 | | | | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 140 | | | |
| Actuated Cycle Length: 140 | | | |
| Offset: 43 (31%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 55 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.85 | | | |
| Intersection Signal Delay (s/veh): 9.9 | | Intersection LOS: A | |
| Intersection Capacity Utilization 75.5% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 18: Millersprt Hwy NB Rmps & Maple Rd



| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 1 | 63 | 881 | 152 | 0 | 865 | 123 | 122 | 145 | 12 | 131 | 148 |
| Future Volume (vph) | 1 | 63 | 881 | 152 | 0 | 865 | 123 | 122 | 145 | 12 | 131 | 148 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 200 | | 450 | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Lanes | | 1 | | 1 | 0 | | 0 | 0 | | 0 | 0 | |
| Taper Length (ft) | | 25 | | | 25 | | | 25 | | | 25 | |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Ped Bike Factor | | 1.00 | | 0.99 | | 1.00 | | | 1.00 | | | 1.00 |
| Frt | | | | 0.850 | | 0.981 | | | 0.993 | | | 0.980 |
| Flt Protected | | 0.950 | | | | | | | 0.979 | | | 0.980 |
| Satd. Flow (prot) | 0 | 1770 | 5085 | 1583 | 0 | 4980 | 0 | 0 | 3438 | 0 | 0 | 3393 |
| Flt Permitted | | 0.218 | | | | | | | 0.979 | | | 0.980 |
| Satd. Flow (perm) | 0 | 406 | 5085 | 1562 | 0 | 4980 | 0 | 0 | 3437 | 0 | 0 | 3392 |
| Right Turn on Red | | | | Yes | | | Yes | | | Yes | | |
| Satd. Flow (RTOR) | | | | 170 | | 32 | | | 4 | | | 15 |
| Link Speed (mph) | | | 40 | | | 40 | | | 30 | | | 30 |
| Link Distance (ft) | | | 1892 | | | 623 | | | 1712 | | | 718 |
| Travel Time (s) | | | 32.3 | | | 10.6 | | | 38.9 | | | 16.3 |
| Confl. Peds. (#/hr) | | 2 | | 2 | 2 | | 2 | 3 | | 2 | 2 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Adj. Flow (vph) | 1 | 66 | 927 | 160 | 0 | 911 | 129 | 128 | 153 | 13 | 138 | 156 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 67 | 927 | 160 | 0 | 1040 | 0 | 0 | 294 | 0 | 0 | 339 |
| Turn Type | Perm | Perm | NA | Perm | | NA | | Split | NA | | Split | NA |
| Protected Phases | | | 1 | | | 1 | | 3 | 3 | | 4 | 4 |
| Permitted Phases | 1 | 1 | | 1 | | | | | | | | |
| Detector Phase | 1 | 1 | 1 | 1 | | 1 | | 3 | 3 | | 4 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 15.0 | 15.0 | 15.0 | 15.0 | | 15.0 | | 6.0 | 6.0 | | 6.0 | 6.0 |
| Minimum Split (s) | 50.0 | 50.0 | 50.0 | 50.0 | | 50.0 | | 70.9 | 70.9 | | 70.9 | 70.9 |
| Total Split (s) | 45.0 | 45.0 | 45.0 | 45.0 | | 45.0 | | 25.0 | 25.0 | | 25.0 | 25.0 |
| Total Split (%) | 47.4% | 47.4% | 47.4% | 47.4% | | 47.4% | | 26.3% | 26.3% | | 26.3% | 26.3% |
| Maximum Green (s) | 37.0 | 37.0 | 37.0 | 37.0 | | 37.0 | | 16.1 | 16.1 | | 16.1 | 16.1 |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.6 | 3.6 | | 3.6 | 3.6 |
| All-Red Time (s) | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 5.3 | 5.3 | | 5.3 | 5.3 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 |
| Total Lost Time (s) | | 8.0 | 8.0 | 8.0 | | 8.0 | | | 8.9 | | | 8.9 |
| Lead/Lag | | | | | | | | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.5 | 3.5 | | 3.5 | 3.5 |
| Recall Mode | Min | Min | Min | Min | | Min | | None | None | | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | | 7.0 | | | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | 35.0 | | 35.0 | | | | | 55.0 | 55.0 |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | | 0 | | | | | 0 | 0 |
| Act Effct Green (s) | | 35.9 | 35.9 | 35.9 | | 35.9 | | | 13.0 | | | 13.7 |
| Actuated g/C Ratio | | 0.41 | 0.41 | 0.41 | | 0.41 | | | 0.15 | | | 0.15 |
| v/c Ratio | | 0.41 | 0.45 | 0.22 | | 0.51 | | | 0.58 | | | 0.63 |
| Control Delay (s/veh) | | 29.8 | 20.5 | 3.5 | | 20.6 | | | 40.2 | | | 39.7 |




| Lane Group | NWR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 43 |
| Future Volume (vph) | 43 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.95 |
| Ped Bike Factor | |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | 3 |
| Peak Hour Factor | 0.95 |
| Adj. Flow (vph) | 45 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |
| Control Delay (s/veh) | |

| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Queue Delay | | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 |
| Total Delay (s/veh) | | 29.8 | 20.5 | 3.5 | | 20.6 | | | 40.2 | | | 39.7 |
| LOS | | C | C | A | | C | | | D | | | D |
| Approach Delay (s/veh) | | | 18.7 | | | 20.6 | | | 40.2 | | | 39.7 |
| Approach LOS | | | B | | | C | | | D | | | D |
| Queue Length 50th (ft) | | 26 | 136 | 0 | | 153 | | | 82 | | | 91 |
| Queue Length 95th (ft) | | 73 | 188 | 34 | | 210 | | | 126 | | | 141 |
| Internal Link Dist (ft) | | | 1812 | | | 543 | | | 1632 | | | 638 |
| Turn Bay Length (ft) | | 200 | | 450 | | | | | | | | |
| Base Capacity (vph) | | 170 | 2138 | 755 | | 2113 | | | 632 | | | 633 |
| Starvation Cap Reductn | | 0 | 0 | 0 | | 0 | | | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | | 0 | | | 0 | | | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | | 0 | | | 0 | | | 0 |
| Reduced v/c Ratio | | 0.39 | 0.43 | 0.21 | | 0.49 | | | 0.47 | | | 0.54 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 95 | | | |
| Actuated Cycle Length: 88.5 | | | |
| Natural Cycle: 195 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.63 | | | |
| Intersection Signal Delay (s/veh): 24.1 | | Intersection LOS: C | |
| Intersection Capacity Utilization 82.4% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 19: Eggert Rd & Sheridan Dr





| Lane Group | NWR |
|---|---|
| Queue Delay | |
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 33 | 147 | 791 | 87 | 9 | 64 | 936 | 98 | 66 | 91 | 37 | 131 |
| Future Volume (vph) | 33 | 147 | 791 | 87 | 9 | 64 | 936 | 98 | 66 | 91 | 37 | 131 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 235 | | 0 | | 240 | | 0 | 0 | | 100 | 0 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 0 | | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.985 | | | | 0.986 | | | 0.971 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | | 0.983 | | 0.950 |
| Satd. Flow (prot) | 0 | 1752 | 4960 | 0 | 0 | 1752 | 4965 | 0 | 0 | 3345 | 0 | 1752 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | | 0.740 | | 0.408 |
| Satd. Flow (perm) | 0 | 1752 | 4960 | 0 | 0 | 1752 | 4965 | 0 | 0 | 2518 | 0 | 753 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 17 | | | | 13 | | | 15 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1468 | | | | 969 | | | 165 | | |
| Travel Time (s) | | | 25.0 | | | | 16.5 | | | 3.8 | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% |
| Adj. Flow (vph) | 34 | 153 | 824 | 91 | 9 | 67 | 975 | 102 | 69 | 95 | 39 | 136 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 187 | 915 | 0 | 0 | 76 | 1077 | 0 | 0 | 203 | 0 | 136 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 6.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 11.2 | 11.2 | 22.5 | | 11.2 | 11.2 | 43.2 | | 22.5 | 22.5 | | 11.0 |
| Total Split (s) | 39.0 | 39.0 | 87.0 | | 20.0 | 20.0 | 68.0 | | 33.0 | 33.0 | | 20.0 |
| Total Split (%) | 24.4% | 24.4% | 54.4% | | 12.5% | 12.5% | 42.5% | | 20.6% | 20.6% | | 12.5% |
| Maximum Green (s) | 32.8 | 32.8 | 80.8 | | 13.8 | 13.8 | 61.8 | | 26.1 | 26.1 | | 14.0 |
| Yellow Time (s) | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | | 3.2 |
| All-Red Time (s) | 2.6 | 2.6 | 2.6 | | 2.6 | 2.6 | 2.6 | | 3.3 | 3.3 | | 2.8 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | | 6.9 | | 6.0 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | | | | | | | | | Yes | Yes | | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | | | | | 7.0 | | | | | |
| Flash Don't Walk (s) | | | | | | | 30.0 | | | | | |
| Pedestrian Calls (#/hr) | | | | | | | 0 | | | | | |
| Act Effct Green (s) | | 22.3 | 89.1 | | | 12.3 | 79.0 | | | 17.4 | | 40.3 |
| Actuated g/C Ratio | | 0.14 | 0.56 | | | 0.08 | 0.49 | | | 0.11 | | 0.25 |
| v/c Ratio | | 0.77 | 0.33 | | | 0.57 | 0.44 | | | 0.71 | | 0.47 |
| Control Delay (s/veh) | | 85.7 | 20.6 | | | 103.4 | 11.4 | | | 76.7 | | 52.4 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |




| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 132 | 192 |
| Future Volume (vph) | 132 | 192 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.911 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1680 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1680 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 46 | |
| Link Speed (mph) | 35 | |
| Link Distance (ft) | 3326 | |
| Travel Time (s) | 64.8 | |
| Peak Hour Factor | 0.96 | 0.96 |
| Heavy Vehicles (%) | 3% | 3% |
| Adj. Flow (vph) | 138 | 200 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 338 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 24.9 | |
| Total Split (s) | 53.0 | |
| Total Split (%) | 33.1% | |
| Maximum Green (s) | 46.1 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.9 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 11.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 39.4 | |
| Actuated g/C Ratio | 0.25 | |
| v/c Ratio | 0.75 | |
| Control Delay (s/veh) | 58.2 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 85.7 | 20.6 | | | 103.4 | 11.4 | | | 76.7 | | 52.4 |
| LOS | | F | C | | | F | B | | | E | | D |
| Approach Delay (s/veh) | | | 31.7 | | | | 17.5 | | | 76.7 | | |
| Approach LOS | | | C | | | | B | | | E | | |
| Queue Length 50th (ft) | | 191 | 182 | | | 83 | 91 | | | 101 | | 116 |
| Queue Length 95th (ft) | | 269 | 262 | | | m142 | 102 | | | 144 | | 165 |
| Internal Link Dist (ft) | | | 1388 | | | | 889 | | | 85 | | |
| Turn Bay Length (ft) | | 235 | | | | 240 | | | | | | |
| Base Capacity (vph) | | 359 | 2811 | | | 159 | 2462 | | | 423 | | 293 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Reduced v/c Ratio | | 0.52 | 0.33 | | | 0.48 | 0.44 | | | 0.48 | | 0.46 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 28 (18%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 90 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.77 | | | |
| Intersection Signal Delay (s/veh): 33.2 | | Intersection LOS: C | |
| Intersection Capacity Utilization 76.4% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |


Splits and Phases: 20: Alberta Dr & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 58.2 | |
| LOS | E | |
| Approach Delay (s/veh) | 56.6 | |
| Approach LOS | E | |
| Queue Length 50th (ft) | 288 | |
| Queue Length 95th (ft) | 374 | |
| Internal Link Dist (ft) | 3246 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 524 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.65 | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 31 | 171 | 771 | 52 | 19 | 132 | 873 | 123 | 106 | 359 | 80 | 169 |
| Future Volume (vph) | 31 | 171 | 771 | 52 | 19 | 132 | 873 | 123 | 106 | 359 | 80 | 169 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 230 | | 0 | | 270 | | 0 | 190 | | 0 | 240 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.990 | | | | 0.981 | | | 0.973 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5084 | 0 | 0 | 1787 | 5038 | 0 | 1787 | 3478 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.383 | | | 0.189 |
| Satd. Flow (perm) | 0 | 1787 | 5084 | 0 | 0 | 1787 | 5038 | 0 | 720 | 3478 | 0 | 356 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 7 | | | | 18 | | | 15 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 969 | | | | 1628 | | | 537 | | |
| Travel Time (s) | | | 16.5 | | | | 27.8 | | | 12.2 | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 32 | 176 | 795 | 54 | 20 | 136 | 900 | 127 | 109 | 370 | 82 | 174 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 208 | 849 | 0 | 0 | 156 | 1027 | 0 | 109 | 452 | 0 | 174 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | pm+pt | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 10.0 | 10.0 | 43.5 | | 10.0 | 10.0 | 43.5 | | 10.0 | 41.0 | | 10.0 |
| Total Split (s) | 30.0 | 30.0 | 54.0 | | 38.0 | 38.0 | 62.0 | | 27.0 | 41.0 | | 27.0 |
| Total Split (%) | 18.8% | 18.8% | 33.8% | | 23.8% | 23.8% | 38.8% | | 16.9% | 25.6% | | 16.9% |
| Maximum Green (s) | 23.3 | 23.3 | 47.5 | | 31.6 | 31.6 | 55.5 | | 20.3 | 34.3 | | 20.3 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.6 | 3.6 | 3.9 | | 3.6 | 3.6 | | 3.6 |
| All-Red Time (s) | 2.8 | 2.8 | 2.6 | | 2.8 | 2.8 | 2.6 | | 3.1 | 3.1 | | 3.1 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.7 | 6.5 | | | 6.4 | 6.5 | | 6.7 | 6.7 | | 6.7 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lead | Lag | | Lead |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | 7.0 | | |
| Flash Don't Walk (s) | | | 21.0 | | | | 21.0 | | | 24.4 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | 0 | | |
| Act Effct Green (s) | | 24.3 | 70.7 | | | 19.3 | 65.4 | | 38.3 | 25.8 | | 49.1 |
| Actuated g/C Ratio | | 0.15 | 0.44 | | | 0.12 | 0.41 | | 0.24 | 0.16 | | 0.31 |
| v/c Ratio | | 0.77 | 0.38 | | | 0.73 | 0.50 | | 0.43 | 0.79 | | 0.64 |
| Control Delay (s/veh) | | 104.9 | 21.9 | | | 108.1 | 25.6 | | 43.9 | 72.5 | | 51.5 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |




| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 337 | 78 |
| Future Volume (vph) | 337 | 78 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 280 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 0.95 |
| Frt | 0.972 | |
| Flt Protected | | |
| Satd. Flow (prot) | 3474 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3474 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 16 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 495 | |
| Travel Time (s) | 11.3 | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 347 | 80 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 427 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 41.0 | |
| Total Split (s) | 41.0 | |
| Total Split (%) | 25.6% | |
| Maximum Green (s) | 34.3 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.1 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.7 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 23.6 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 31.2 | |
| Actuated g/C Ratio | 0.20 | |
| v/c Ratio | 0.62 | |
| Control Delay (s/veh) | 60.1 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 104.9 | 21.9 | | | 108.1 | 25.6 | | 43.9 | 72.5 | | 51.5 |
| LOS | | F | C | | | F | C | | D | E | | D |
| Approach Delay (s/veh) | | | 38.2 | | | | 36.5 | | | 66.9 | | |
| Approach LOS | | | D | | | | D | | | E | | |
| Queue Length 50th (ft) | | 230 | 123 | | | 166 | 320 | | 84 | 235 | | 139 |
| Queue Length 95th (ft) | | 320 | 144 | | | 172 | 434 | | 121 | 286 | | 185 |
| Internal Link Dist (ft) | | | 889 | | | | 1548 | | | 457 | | |
| Turn Bay Length (ft) | | 230 | | | | 270 | | | 190 | | | 240 |
| Base Capacity (vph) | | 290 | 2250 | | | 352 | 2122 | | 341 | 757 | | 298 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.72 | 0.38 | | | 0.44 | 0.48 | | 0.32 | 0.60 | | 0.58 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 4 (3%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.79 | | | |
| Intersection Signal Delay (s/veh): 45.8 | | Intersection LOS: D | |
| Intersection Capacity Utilization 74.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 21: Bailey Ave & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 60.1 | |
| LOS | E | |
| Approach Delay (s/veh) | 57.6 | |
| Approach LOS | E | |
| Queue Length 50th (ft) | 210 | |
| Queue Length 95th (ft) | 254 | |
| Internal Link Dist (ft) | 415 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 779 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.55 | |

| Intersection Summary |
|---|




| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 10 | 172 | 777 | 19 | 18 | 27 | 837 | 86 | 32 | 169 | 22 | 124 |
| Future Volume (vph) | 10 | 172 | 777 | 19 | 18 | 27 | 837 | 86 | 32 | 169 | 22 | 124 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 200 | | 0 | | 190 | | 0 | 85 | | 0 | 305 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.996 | | | | 0.986 | | | 0.983 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5115 | 0 | 0 | 1787 | 5064 | 0 | 1787 | 1849 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.586 | | | 0.268 |
| Satd. Flow (perm) | 0 | 1787 | 5115 | 0 | 0 | 1787 | 5064 | 0 | 1102 | 1849 | 0 | 504 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 2 | | | | 13 | | | 4 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1628 | | | | 2376 | | | 1485 | | |
| Travel Time (s) | | | 27.8 | | | | 40.5 | | | 33.8 | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 10 | 176 | 793 | 19 | 18 | 28 | 854 | 88 | 33 | 172 | 22 | 127 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 186 | 812 | 0 | 0 | 46 | 942 | 0 | 33 | 194 | 0 | 127 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 25.0 | | 6.0 | 6.0 | 25.0 | | 12.0 | 12.0 | | 5.0 |
| Minimum Split (s) | 12.2 | 12.2 | 43.2 | | 12.2 | 12.2 | 43.2 | | 42.0 | 42.0 | | 12.1 |
| Total Split (s) | 21.0 | 21.0 | 60.0 | | 31.0 | 31.0 | 70.0 | | 42.0 | 42.0 | | 27.0 |
| Total Split (%) | 13.1% | 13.1% | 37.5% | | 19.4% | 19.4% | 43.8% | | 26.3% | 26.3% | | 16.9% |
| Maximum Green (s) | 14.8 | 14.8 | 53.8 | | 24.8 | 24.8 | 63.8 | | 34.9 | 34.9 | | 19.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | 3.9 | | 3.2 | 3.2 | | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | 2.3 | | 3.9 | 3.9 | | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | 7.1 | 7.1 | | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | | Yes | Yes | | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | | | 17.0 | | | | 18.0 | | 27.0 | 27.0 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | 0 | 0 | | |
| Act Effct Green (s) | | 27.6 | 88.9 | | | 9.5 | 68.4 | | 21.8 | 21.8 | | 44.5 |
| Actuated g/C Ratio | | 0.17 | 0.56 | | | 0.06 | 0.43 | | 0.14 | 0.14 | | 0.28 |
| v/c Ratio | | 0.60 | 0.29 | | | 0.43 | 0.43 | | 0.22 | 0.76 | | 0.48 |
| Control Delay (s/veh) | | 58.1 | 34.5 | | | 84.3 | 33.8 | | 62.8 | 83.6 | | 49.0 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 144 | 133 |
| Future Volume (vph) | 144 | 133 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.928 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1746 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1746 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 34 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 1504 | |
| Travel Time (s) | 34.2 | |
| Peak Hour Factor | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 147 | 136 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 283 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 12.0 | |
| Minimum Split (s) | 44.1 | |
| Total Split (s) | 69.0 | |
| Total Split (%) | 43.1% | |
| Maximum Green (s) | 61.9 | |
| Yellow Time (s) | 3.2 | |
| All-Red Time (s) | 3.9 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 7.1 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 30.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 44.5 | |
| Actuated g/C Ratio | 0.28 | |
| v/c Ratio | 0.55 | |
| Control Delay (s/veh) | 46.0 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 58.1 | 34.5 | | | 84.3 | 33.8 | | 62.8 | 83.6 | | 49.0 |
| LOS | | E | C | | | F | C | | E | F | | D |
| Approach Delay (s/veh) | | | 38.9 | | | | 36.1 | | | 80.6 | | |
| Approach LOS | | | D | | | | D | | | F | | |
| Queue Length 50th (ft) | | 180 | 230 | | | 47 | 245 | | 31 | 195 | | 104 |
| Queue Length 95th (ft) | | 268 | 332 | | | 92 | 334 | | 65 | 274 | | 147 |
| Internal Link Dist (ft) | | | 1548 | | | | 2296 | | | 1405 | | |
| Turn Bay Length (ft) | | 200 | | | | 190 | | | 85 | | | 305 |
| Base Capacity (vph) | | 308 | 2843 | | | 276 | 2228 | | 240 | 406 | | 301 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.60 | 0.29 | | | 0.17 | 0.42 | | 0.14 | 0.48 | | 0.42 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 133 (83%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 110 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.76 | | | |
| Intersection Signal Delay (s/veh): 42.7 | | Intersection LOS: D | |
| Intersection Capacity Utilization 78.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 22: Sweet Home Rd & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 46.0 | |
| LOS | D | |
| Approach Delay (s/veh) | 47.0 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 224 | |
| Queue Length 95th (ft) | 289 | |
| Internal Link Dist (ft) | 1424 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 696 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.41 | |

| Intersection Summary |
|---|




| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 2 | 246 | 638 | 19 | 21 | 71 | 611 | 51 | 53 | 403 | 108 | 96 |
| Future Volume (vph) | 2 | 246 | 638 | 19 | 21 | 71 | 611 | 51 | 53 | 403 | 108 | 96 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 315 | | 0 | | 330 | | 0 | 110 | | 155 | 105 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 1.00 | 1.00 |
| Frt | | | 0.996 | | | | 0.988 | | | | 0.850 | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1752 | 5016 | 0 | 0 | 1752 | 4975 | 0 | 1752 | 3505 | 1568 | 1752 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.538 | | | 0.360 |
| Satd. Flow (perm) | 0 | 1752 | 5016 | 0 | 0 | 1752 | 4975 | 0 | 992 | 3505 | 1568 | 664 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 3 | | | | 8 | | | | 124 | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 2376 | | | | 4032 | | | 1401 | | |
| Travel Time (s) | | | 40.5 | | | | 68.7 | | | 31.8 | | |
| Peak Hour Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Heavy Vehicles (%) | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% |
| Adj. Flow (vph) | 2 | 246 | 638 | 19 | 21 | 71 | 611 | 51 | 53 | 403 | 108 | 96 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 248 | 657 | 0 | 0 | 92 | 662 | 0 | 53 | 403 | 108 | 96 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | pm+pt | NA | Perm | pm+pt |
| Protected Phases | 1 | 1 | 6 | | 5 | 5 | 2 | | 3 | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | 8 | 4 |
| Detector Phase | 1 | 1 | 6 | | 5 | 5 | 2 | | 3 | 8 | 8 | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | | 10.0 | 10.0 | 10.0 | | 3.0 | 10.0 | 10.0 | 3.0 |
| Minimum Split (s) | 16.2 | 16.2 | 43.2 | | 16.2 | 16.2 | 43.2 | | 10.1 | 44.1 | 44.1 | 10.1 |
| Total Split (s) | 30.0 | 30.0 | 37.0 | | 30.0 | 30.0 | 37.0 | | 33.0 | 45.0 | 45.0 | 33.0 |
| Total Split (%) | 20.7% | 20.7% | 25.5% | | 20.7% | 20.7% | 25.5% | | 22.8% | 31.0% | 31.0% | 22.8% |
| Maximum Green (s) | 23.8 | 23.8 | 30.8 | | 23.8 | 23.8 | 30.8 | | 25.9 | 37.9 | 37.9 | 25.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | 3.9 | | 3.2 | 3.2 | 3.2 | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | 2.3 | | 3.9 | 3.9 | 3.9 | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | 7.1 | 7.1 | 7.1 | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lead | Lag | Lag | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | None | None | Min | | None | None | Min | | None | None | None | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | 18.0 | | | | 17.0 | | | 28.0 | 28.0 | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | 0 | 0 | |
| Act Effct Green (s) | | 19.9 | 31.5 | | | 11.8 | 19.2 | | 24.9 | 17.5 | 17.5 | 31.2 |
| Actuated g/C Ratio | | 0.21 | 0.34 | | | 0.13 | 0.20 | | 0.27 | 0.19 | 0.19 | 0.33 |
| v/c Ratio | | 0.66 | 0.39 | | | 0.42 | 0.65 | | 0.16 | 0.62 | 0.27 | 0.29 |
| Control Delay (s/veh) | | 45.4 | 26.7 | | | 47.9 | 37.9 | | 22.6 | 40.7 | 7.0 | 23.6 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 357 | 286 |
| Future Volume (vph) | 357 | 286 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 285 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 1.00 |
| Frt | | 0.850 |
| Flt Protected | | |
| Satd. Flow (prot) | 3505 | 1568 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3505 | 1568 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | | 286 |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 981 | |
| Travel Time (s) | 22.3 | |
| Peak Hour Factor | 1.00 | 1.00 |
| Heavy Vehicles (%) | 3% | 3% |
| Adj. Flow (vph) | 357 | 286 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 357 | 286 |
| Turn Type | NA | Perm |
| Protected Phases | 4 | |
| Permitted Phases | | 4 |
| Detector Phase | 4 | 4 |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | 10.0 |
| Minimum Split (s) | 44.1 | 44.1 |
| Total Split (s) | 45.0 | 45.0 |
| Total Split (%) | 31.0% | 31.0% |
| Maximum Green (s) | 37.9 | 37.9 |
| Yellow Time (s) | 3.2 | 3.2 |
| All-Red Time (s) | 3.9 | 3.9 |
| Lost Time Adjust (s) | 0.0 | 0.0 |
| Total Lost Time (s) | 7.1 | 7.1 |
| Lead/Lag | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 |
| Recall Mode | None | None |
| Walk Time (s) | 7.0 | 7.0 |
| Flash Don't Walk (s) | 30.0 | 30.0 |
| Pedestrian Calls (#/hr) | 0 | 0 |
| Act Effct Green (s) | 23.2 | 23.2 |
| Actuated g/C Ratio | 0.25 | 0.25 |
| v/c Ratio | 0.41 | 0.47 |
| Control Delay (s/veh) | 33.8 | 7.0 |
| Queue Delay | 0.0 | 0.0 |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 45.4 | 26.7 | | | 47.9 | 37.9 | | 22.6 | 40.7 | 7.0 | 23.6 |
| LOS | | D | C | | | D | D | | C | D | A | C |
| Approach Delay (s/veh) | | | 31.8 | | | | 39.1 | | | 32.5 | | |
| Approach LOS | | | C | | | | D | | | C | | |
| Queue Length 50th (ft) | | 134 | 112 | | | 52 | 132 | | 20 | 117 | 0 | 38 |
| Queue Length 95th (ft) | | 260 | 180 | | | 116 | 200 | | 50 | 190 | 36 | 81 |
| Internal Link Dist (ft) | | | 2296 | | | | 3952 | | | 1321 | | |
| Turn Bay Length (ft) | | 315 | | | | 330 | | | 110 | | 155 | 105 |
| Base Capacity (vph) | | 456 | 1775 | | | 456 | 1684 | | 582 | 1455 | 723 | 554 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.54 | 0.37 | | | 0.20 | 0.39 | | 0.09 | 0.28 | 0.15 | 0.17 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 145 | | | |
| Actuated Cycle Length: 93.7 | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.66 | | | |
| Intersection Signal Delay (s/veh): 31.4 | | Intersection LOS: C | |
| Intersection Capacity Utilization 69.9% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 23: Millersport Hwy & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 33.8 | 7.0 |
| LOS | C | A |
| Approach Delay (s/veh) | 22.1 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 98 | 0 |
| Queue Length 95th (ft) | 161 | 67 |
| Internal Link Dist (ft) | 901 | |
| Turn Bay Length (ft) | | 285 |
| Base Capacity (vph) | 1455 | 818 |
| Starvation Cap Reductn | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 |
| Storage Cap Reductn | 0 | 0 |
| Reduced v/c Ratio | 0.25 | 0.35 |


Intersection Summary


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 42 | 320 | 4 | 8 | 289 | 17 | 4 | 20 | 4 | 47 | 41 | 45 |
| Future Volume (vph) | 42 | 320 | 4 | 8 | 289 | 17 | 4 | 20 | 4 | 47 | 41 | 45 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | | | | | | 1.00 | | | 1.00 | |
| Frt | | 0.998 | | | 0.992 | | | 0.981 | | | 0.954 | |
| Flt Protected | | 0.994 | | | 0.999 | | | 0.993 | | | 0.983 | |
| Satd. Flow (prot) | 0 | 3443 | 0 | 0 | 3440 | 0 | 0 | 1776 | 0 | 0 | 1713 | 0 |
| Flt Permitted | | 0.890 | | | 0.944 | | | 0.943 | | | 0.871 | |
| Satd. Flow (perm) | 0 | 3083 | 0 | 0 | 3251 | 0 | 0 | 1686 | 0 | 0 | 1516 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 4 | | | 18 | | | 4 | | | 37 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 25 | |
| Link Distance (ft) | | 1535 | | | 1128 | | | 417 | | | 659 | |
| Travel Time (s) | | 29.9 | | | 22.0 | | | 9.5 | | | 18.0 | |
| Confl. Peds. (#/hr) | | | | | | | | | 5 | 5 | | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% |
| Adj. Flow (vph) | 44 | 337 | 4 | 8 | 304 | 18 | 4 | 21 | 4 | 49 | 43 | 47 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 385 | 0 | 0 | 330 | 0 | 0 | 29 | 0 | 0 | 139 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | Perm | NA | | Perm | NA | |
| Protected Phases | | 1 | | | 1 | | | 2 | | | 2 | |
| Permitted Phases | 1 | | | 1 | | | 2 | | | 2 | | |
| Detector Phase | 1 | 1 | | 1 | 1 | | 2 | 2 | | 2 | 2 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 15.0 | 15.0 | | 15.0 | 15.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Split (s) | 21.0 | 21.0 | | 21.0 | 21.0 | | 27.0 | 27.0 | | 27.0 | 27.0 | |
| Total Split (s) | 45.0 | 45.0 | | 45.0 | 45.0 | | 15.0 | 15.0 | | 15.0 | 15.0 | |
| Total Split (%) | 75.0% | 75.0% | | 75.0% | 75.0% | | 25.0% | 25.0% | | 25.0% | 25.0% | |
| Maximum Green (s) | 40.0 | 40.0 | | 40.0 | 40.0 | | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Yellow Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | | 5.0 | | | 5.0 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | Min | Min | | Min | Min | |
| Walk Time (s) | | | | | | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | | | | | 15.0 | 15.0 | | 15.0 | 15.0 | |
| Pedestrian Calls (#/hr) | | | | | | | 0 | 0 | | 0 | 0 | |
| Act Effct Green (s) | | 15.1 | | | 15.1 | | | 7.5 | | | 7.5 | |
| Actuated g/C Ratio | | 0.46 | | | 0.46 | | | 0.23 | | | 0.23 | |
| v/c Ratio | | 0.27 | | | 0.22 | | | 0.07 | | | 0.37 | |
| Control Delay (s/veh) | | 6.3 | | | 5.8 | | | 9.3 | | | 11.1 | |
| Queue Delay | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Delay (s/veh) | | 6.3 | | | 5.8 | | | 9.3 | | | 11.1 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| LOS | | A | | | A | | | A | | | B | |
| Approach Delay (s/veh) | | 6.3 | | | 5.8 | | | 9.3 | | | 11.1 | |
| Approach LOS | | A | | | A | | | A | | | B | |
| Queue Length 50th (ft) | | 18 | | | 14 | | | 3 | | | 14 | |
| Queue Length 95th (ft) | | 39 | | | 32 | | | 14 | | | 42 | |
| Internal Link Dist (ft) | | 1455 | | | 1048 | | | 337 | | | 579 | |
| Turn Bay Length (ft) | | | | | | | | | | | | |
| Base Capacity (vph) | | 3083 | | | 3251 | | | 519 | | | 490 | |
| Starvation Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | | 0.12 | | | 0.10 | | | 0.06 | | | 0.28 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 60 | | | |
| Actuated Cycle Length: 32.7 | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.37 | | | |
| Intersection Signal Delay (s/veh): 7.0 | | Intersection LOS: A | |
| Intersection Capacity Utilization 51.7% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 24: Alberta Dr & Eggert Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 40 | 204 | 79 | 38 | 236 | 133 | 75 | 341 | 36 | 121 | 304 | 42 |
| Future Volume (vph) | 40 | 204 | 79 | 38 | 236 | 133 | 75 | 341 | 36 | 121 | 304 | 42 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 150 | | 0 | 110 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 0.95 | 0.95 |
| Frt | | 0.963 | | | 0.951 | | | 0.986 | | | 0.982 | |
| Flt Protected | | 0.994 | | | 0.995 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3421 | 0 | 0 | 3382 | 0 | 1787 | 1855 | 0 | 1787 | 3510 | 0 |
| Flt Permitted | | 0.843 | | | 0.881 | | 0.515 | | | 0.330 | | |
| Satd. Flow (perm) | 0 | 2902 | 0 | 0 | 2995 | 0 | 969 | 1855 | 0 | 621 | 3510 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 59 | | | 112 | | | 8 | | | 23 | |
| Link Speed (mph) | | 30 | | | 30 | | | 30 | | | 30 | |
| Link Distance (ft) | | 1128 | | | 580 | | | 922 | | | 349 | |
| Travel Time (s) | | 25.6 | | | 13.2 | | | 21.0 | | | 7.9 | |
| Peak Hour Factor | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 47 | 237 | 92 | 44 | 274 | 155 | 87 | 397 | 42 | 141 | 353 | 49 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 376 | 0 | 0 | 473 | 0 | 87 | 439 | 0 | 141 | 402 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | | 4 | | | 8 | | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 4 | | | 8 | | | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | | 10.0 | 10.0 | | 5.0 | 10.0 | | 5.0 | 10.0 | |
| Minimum Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 10.0 | 37.0 | | 10.0 | 37.0 | |
| Total Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 11.0 | 37.0 | | 11.0 | 37.0 | |
| Total Split (%) | 40.0% | 40.0% | | 40.0% | 40.0% | | 13.8% | 46.3% | | 13.8% | 46.3% | |
| Maximum Green (s) | 27.0 | 27.0 | | 27.0 | 27.0 | | 6.0 | 32.0 | | 6.0 | 32.0 | |
| Yellow Time (s) | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| All-Red Time (s) | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | | | | | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | | Yes | Yes | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | None | None | | None | None | |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | 20.0 | 20.0 | | 20.0 | 20.0 | | | 25.0 | | | 25.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Act Effct Green (s) | | 13.8 | | | 13.8 | | 22.4 | 17.9 | | 23.6 | 20.4 | |
| Actuated g/C Ratio | | 0.27 | | | 0.27 | | 0.44 | 0.35 | | 0.47 | 0.40 | |
| v/c Ratio | | 0.45 | | | 0.53 | | 0.16 | 0.66 | | 0.32 | 0.28 | |
| Control Delay (s/veh) | | 16.5 | | | 15.7 | | 7.1 | 20.1 | | 8.6 | 11.5 | |
| Queue Delay | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 16.5 | | | 15.7 | | 7.1 | 20.1 | | 8.6 | 11.5 | |
| LOS | | B | | | B | | A | C | | A | B | |
| Approach Delay (s/veh) | | 16.5 | | | 15.7 | | | 18.0 | | | 10.8 | |
| Approach LOS | | B | | | B | | | B | | | B | |
| Queue Length 50th (ft) | | 41 | | | 47 | | 11 | 109 | | 18 | 43 | |
| Queue Length 95th (ft) | | 87 | | | 100 | | 32 | 209 | | 48 | 80 | |
| Internal Link Dist (ft) | | 1048 | | | 500 | | | 842 | | | 269 | |
| Turn Bay Length (ft) | | | | | | | 150 | | | 110 | | |
| Base Capacity (vph) | | 1691 | | | 1767 | | 532 | 1249 | | 437 | 2365 | |
| Starvation Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.22 | | | 0.27 | | 0.16 | 0.35 | | 0.32 | 0.17 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 80 | | | |
| Actuated Cycle Length: 50.7 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.66 | | | |
| Intersection Signal Delay (s/veh): 15.1 | | Intersection LOS: B | |
| Intersection Capacity Utilization 64.7% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 25: Bailey Ave & Eggert Rd




| Intersection | |
|---|---|
| Int Delay, s/veh | 5.8 |

| Movement | EBL | EBR | NBL | NBT | SBT | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 28 | 253 | 192 | 639 | 656 | 23 |
| Future Vol, veh/h | 28 | 253 | 192 | 639 | 656 | 23 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Free | Free | Free | Free |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | 180 | 0 | 165 | - | - | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 96 | 96 | 96 | 96 | 96 | 96 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 29 | 264 | 200 | 666 | 683 | 24 |

| Major/Minor | Minor2 | | Major1 | | Major2 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 1761 | 695 | 707 | 0 | - | 0 |
| Stage 1 | 695 | - | - | - | - | - |
| Stage 2 | 1066 | - | - | - | - | - |
| Critical Hdwy | 6.41 | 6.21 | 4.11 | - | - | - |
| Critical Hdwy Stg 1 | 5.41 | - | - | - | - | - |
| Critical Hdwy Stg 2 | 5.41 | - | - | - | - | - |
| Follow-up Hdwy | 3.509 | 3.309 | 2.209 | - | - | - |
| Pot Cap-1 Maneuver | 93 | 444 | 896 | - | - | - |
| Stage 1 | 497 | - | - | - | - | - |
| Stage 2 | 333 | - | - | - | - | - |
| Platoon blocked, % | | | | - | - | - |
| Mov Cap-1 Maneuver | 73 | 444 | 896 | - | - | - |
| Mov Cap-2 Maneuver | 73 | - | - | - | - | - |
| Stage 1 | 386 | - | - | - | - | - |
| Stage 2 | 333 | - | - | - | - | - |

| Approach | EB | NB | SB |
|---|---|---|---|
| HCM Control Delay, s/v | 30.31 | 2.35 | 0 |
| HCM LOS | D | | |

| Minor Lane/Major Mvmt | NBL | NBT | EBLn1 | EBLn2 | SBT | SBR |
|---|---|---|---|---|---|---|
| Capacity (veh/h) | 896 | - | 73 | 444 | - | - |
| HCM Lane V/C Ratio | 0.223 | - | 0.402 | 0.594 | - | - |
| HCM Control Delay (s/veh) | 10.2 | - | 84.7 | 24.3 | - | - |
| HCM Lane LOS | B | - | F | C | - | - |
| HCM 95th %tile Q(veh) | 0.9 | - | 1.6 | 3.8 | - | - |




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 75 | 24 | 60 | 7 | 11 | 109 | 25 | 652 | 10 | 58 | 776 | 58 |
| Future Volume (vph) | 75 | 24 | 60 | 7 | 11 | 109 | 25 | 652 | 10 | 58 | 776 | 58 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 70 | 170 | | 0 | 150 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 1 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.949 | | | | 0.850 | | 0.998 | | | 0.990 | |
| Flt Protected | | 0.977 | | | 0.981 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 1744 | 0 | 0 | 1845 | 1599 | 1787 | 1877 | 0 | 1787 | 1862 | 0 |
| Flt Permitted | | 0.841 | | | 0.869 | | 0.203 | | | 0.316 | | |
| Satd. Flow (perm) | 0 | 1501 | 0 | 0 | 1635 | 1599 | 382 | 1877 | 0 | 594 | 1862 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 31 | | | | 112 | | 2 | | | 9 | |
| Link Speed (mph) | | 30 | | | 30 | | | 35 | | | 35 | |
| Link Distance (ft) | | 710 | | | 507 | | | 1039 | | | 1225 | |
| Travel Time (s) | | 16.1 | | | 11.5 | | | 20.2 | | | 23.9 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 77 | 25 | 62 | 7 | 11 | 112 | 26 | 672 | 10 | 60 | 800 | 60 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 164 | 0 | 0 | 18 | 112 | 26 | 682 | 0 | 60 | 860 | 0 |
| Turn Type | Perm | NA | | Perm | NA | Perm | Perm | NA | | Perm | NA | |
| Protected Phases | | 4 | | | 8 | | | 2 | | | 6 | |
| Permitted Phases | 4 | | | 8 | | 8 | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | 8 | 2 | 2 | | 6 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | | 5.0 | 5.0 | 5.0 | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | 33.0 | 33.0 | | 23.0 | 23.0 | 23.0 | 23.0 | 23.0 | | 32.0 | 32.0 | |
| Total Split (s) | 25.0 | 25.0 | | 25.0 | 25.0 | 25.0 | 65.0 | 65.0 | | 65.0 | 65.0 | |
| Total Split (%) | 27.8% | 27.8% | | 27.8% | 27.8% | 27.8% | 72.2% | 72.2% | | 72.2% | 72.2% | |
| Maximum Green (s) | 19.8 | 19.8 | | 19.8 | 19.8 | 19.8 | 59.4 | 59.4 | | 59.4 | 59.4 | |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | 3.2 | 3.6 | 3.6 | | 3.6 | 3.6 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.2 | | | 5.2 | 5.2 | 5.6 | 5.6 | | 5.6 | 5.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | None | None | | None | None | None | Min | Min | | Min | Min | |
| Walk Time (s) | 7.0 | 7.0 | | | | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | 15.0 | 15.0 | | | | | | | | 15.0 | 15.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | | | | | | 0 | 0 | |
| Act Effct Green (s) | | 11.2 | | | 11.2 | 11.2 | 35.5 | 35.5 | | 35.5 | 35.5 | |
| Actuated g/C Ratio | | 0.19 | | | 0.19 | 0.19 | 0.61 | 0.61 | | 0.61 | 0.61 | |
| v/c Ratio | | 0.52 | | | 0.06 | 0.28 | 0.11 | 0.60 | | 0.17 | 0.76 | |
| Control Delay (s/veh) | | 26.0 | | | 23.8 | 8.1 | 6.5 | 9.7 | | 6.6 | 13.5 | |
| Queue Delay | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 26.0 | | | 23.8 | 8.1 | 6.5 | 9.7 | | 6.6 | 13.5 | |
| LOS | | C | | | C | A | A | A | | A | B | |
| Approach Delay (s/veh) | | 26.0 | | | 10.3 | | | 9.6 | | | 13.1 | |
| Approach LOS | | C | | | B | | | A | | | B | |
| Queue Length 50th (ft) | | 36 | | | 5 | 0 | 3 | 113 | | 7 | 167 | |
| Queue Length 95th (ft) | | 125 | | | 26 | 41 | 15 | 265 | | 27 | 399 | |
| Internal Link Dist (ft) | | 630 | | | 427 | | | 959 | | | 1145 | |
| Turn Bay Length (ft) | | | | | | 70 | 170 | | | 150 | | |
| Base Capacity (vph) | | 565 | | | 594 | 653 | 352 | 1731 | | 548 | 1718 | |
| Starvation Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.29 | | | 0.03 | 0.17 | 0.07 | 0.39 | | 0.11 | 0.50 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 90 | | | |
| Actuated Cycle Length: 58.3 | | | |
| Natural Cycle: 75 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.76 | | | |
| Intersection Signal Delay (s/veh): 12.7 | | Intersection LOS: B | |
| Intersection Capacity Utilization 73.0% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 27: Bailey Ave & Meyer Rd




| Intersection | |
|---|---|
| Int Delay, s/veh | 4.7 |

| Movement | EBT | EBR | WBL | WBT | NBL | NBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 2 | 116 | 2 | 7 | 117 | 1 |
| Future Vol, veh/h | 2 | 116 | 2 | 7 | 117 | 1 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Stop | Stop |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | - | - | - | - | 0 | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 82 | 82 | 82 | 82 | 82 | 82 |
| Heavy Vehicles, % | 3 | 3 | 3 | 3 | 3 | 3 |
| Mvmt Flow | 2 | 141 | 2 | 9 | 143 | 1 |

| Major/Minor | Major1 | | Major2 | | Minor1 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 0 | 0 | 144 | 0 | 87 | 73 |
| Stage 1 | - | - | - | - | 73 | - |
| Stage 2 | - | - | - | - | 13 | - |
| Critical Hdwy | - | - | 4.13 | - | 6.43 | 6.23 |
| Critical Hdwy Stg 1 | - | - | - | - | 5.43 | - |
| Critical Hdwy Stg 2 | - | - | - | - | 5.43 | - |
| Follow-up Hdwy | - | - | 2.227 | - | 3.527 | 3.327 |
| Pot Cap-1 Maneuver | - | - | 1432 | - | 912 | 986 |
| Stage 1 | - | - | - | - | 947 | - |
| Stage 2 | - | - | - | - | 1007 | - |
| Platoon blocked, % | - | - | | - | | |
| Mov Cap-1 Maneuver | - | - | 1432 | - | 910 | 986 |
| Mov Cap-2 Maneuver | - | - | - | - | 910 | - |
| Stage 1 | - | - | - | - | 947 | - |
| Stage 2 | - | - | - | - | 1005 | - |

| Approach | EB | WB | NB |
|---|---|---|---|
| HCM Control Delay, s/v | 0 | 1.67 | 9.69 |
| HCM LOS | | | A |

| Minor Lane/Major Mvmt | NBLn1 | EBT | EBR | WBL | WBT |
|---|---|---|---|---|---|
| Capacity (veh/h) | 911 | - | - | 400 | - |
| HCM Lane V/C Ratio | 0.158 | - | - | 0.002 | - |
| HCM Control Delay (s/veh) | 9.7 | - | - | 7.5 | 0 |
| HCM Lane LOS | A | - | - | A | A |
| HCM 95th %tile Q(veh) | 0.6 | - | - | 0 | - |





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 4 | 0 | 9 | 536 | 1 | 679 | 0 | 1256 | 413 | 0 | 1406 | 0 |
| Future Volume (vph) | 4 | 0 | 9 | 536 | 1 | 679 | 0 | 1256 | 413 | 0 | 1406 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 250 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 0 | | 1 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 0.95 | 0.91 | 0.95 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | 0.894 | 0.850 | | | 0.850 | | | |
| Flt Protected | 0.950 | | | 0.950 | 0.986 | | | | | | | |
| Satd. Flow (prot) | 1787 | 0 | 1599 | 1698 | 1509 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Flt Permitted | 0.176 | | | 0.950 | 0.986 | | | | | | | |
| Satd. Flow (perm) | 331 | 0 | 1599 | 1698 | 1509 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 28 | | 50 | 50 | | | 430 | | | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 894 | | | 646 | | | 950 | | | 1161 | |
| Travel Time (s) | | 20.3 | | | 14.7 | | | 16.2 | | | 19.8 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 4 | 0 | 9 | 558 | 1 | 707 | 0 | 1308 | 430 | 0 | 1465 | 0 |
| Shared Lane Traffic (%) | | | | 22% | | 42% | | | | | | |
| Lane Group Flow (vph) | 4 | 0 | 9 | 435 | 421 | 410 | 0 | 1308 | 430 | 0 | 1465 | 0 |
| Turn Type | D.Pm | | Perm | Perm | NA | Perm | | NA | Perm | | NA | |
| Protected Phases | | | | | 3 | | | 1 | | | 1 | |
| Permitted Phases | 3 | | 3 | 3 | | 3 | | | 1 | | | |
| Detector Phase | 3 | | 3 | 3 | 3 | 3 | | 1 | 1 | | 1 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | | 6.0 | 6.0 | 6.0 | 6.0 | | 20.0 | 20.0 | | 20.0 | |
| Minimum Split (s) | 13.3 | | 13.3 | 13.3 | 13.3 | 13.3 | | 34.6 | 34.6 | | 34.6 | |
| Total Split (s) | 70.0 | | 70.0 | 70.0 | 70.0 | 70.0 | | 110.0 | 110.0 | | 110.0 | |
| Total Split (%) | 38.9% | | 38.9% | 38.9% | 38.9% | 38.9% | | 61.1% | 61.1% | | 61.1% | |
| Maximum Green (s) | 62.7 | | 62.7 | 62.7 | 62.7 | 62.7 | | 102.4 | 102.4 | | 102.4 | |
| Yellow Time (s) | 4.3 | | 4.3 | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 | | 4.3 | |
| All-Red Time (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.3 | 3.3 | | 3.3 | |
| Lost Time Adjust (s) | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |
| Total Lost Time (s) | 7.3 | | 7.3 | 7.3 | 7.3 | 7.3 | | 7.6 | 7.6 | | 7.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | |
| Recall Mode | None | | None | None | None | None | | C-Max | C-Max | | C-Max | |
| Walk Time (s) | | | | | | | | 7.0 | 7.0 | | 7.0 | |
| Flash Don't Walk (s) | | | | | | | | 20.0 | 20.0 | | 20.0 | |
| Pedestrian Calls (#/hr) | | | | | | | | 0 | 0 | | 0 | |
| Act Effct Green (s) | 55.4 | | 55.4 | 55.4 | 55.4 | 55.4 | | 109.7 | 109.7 | | 109.7 | |
| Actuated g/C Ratio | 0.31 | | 0.31 | 0.31 | 0.31 | 0.31 | | 0.61 | 0.61 | | 0.61 | |
| v/c Ratio | 0.04 | | 0.02 | 0.83 | 0.84 | 0.82 | | 0.42 | 0.38 | | 0.47 | |
| Control Delay (s/veh) | 40.8 | | 0.1 | 71.9 | 66.5 | 63.5 | | 19.3 | 3.3 | | 20.6 | |
| Queue Delay | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 40.8 | | 0.1 | 71.9 | 66.5 | 63.5 | | 19.3 | 3.3 | | 20.6 | |
| LOS | D | | A | E | E | E | | B | A | | C | |
| Approach Delay (s/veh) | | 12.6 | | | 67.3 | | | 15.3 | | | 20.6 | |
| Approach LOS | | B | | | E | | | B | | | C | |
| Queue Length 50th (ft) | 3 | | 0 | 497 | 453 | 416 | | 298 | 18 | | 346 | |
| Queue Length 95th (ft) | 14 | | 0 | 625 | 595 | 547 | | 354 | 59 | | 412 | |
| Internal Link Dist (ft) | | 814 | | | 566 | | | 870 | | | 1081 | |
| Turn Bay Length (ft) | | | | | | | | | 250 | | | |
| Base Capacity (vph) | 115 | | 575 | 591 | 558 | 561 | | 3130 | 1142 | | 3130 | |
| Starvation Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Spillback Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Storage Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Reduced v/c Ratio | 0.03 | | 0.02 | 0.74 | 0.75 | 0.73 | | 0.42 | 0.38 | | 0.47 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 60 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.84 | | | |
| Intersection Signal Delay (s/veh): 31.7 | | Intersection LOS: C | |
| Intersection Capacity Utilization 72.5% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 1: Niagara Falls Blvd & I-290 WB Ramp






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 0 | 494 | 0 | 0 | 382 | 0 | 1184 | 0 | 0 | 1299 | 483 |
| Future Volume (vph) | 0 | 0 | 494 | 0 | 0 | 382 | 0 | 1184 | 0 | 0 | 1299 | 483 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 200 |
| Storage Lanes | 0 | | 2 | 0 | | 1 | 0 | | 0 | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 0.88 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | | 0.865 | | | | | | 0.850 |
| Flt Protected | | | | | | | | | | | | |
| Satd. Flow (prot) | 0 | 0 | 2814 | 0 | 0 | 1611 | 0 | 5136 | 0 | 0 | 5136 | 1599 |
| Flt Permitted | | | | | | | | | | | | |
| Satd. Flow (perm) | 0 | 0 | 2814 | 0 | 0 | 1611 | 0 | 5136 | 0 | 0 | 5136 | 1599 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 73 | | | | | | | | | 425 |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 932 | | | 703 | | | 600 | | | 950 | |
| Travel Time (s) | | 21.2 | | | 16.0 | | | 10.2 | | | 16.2 | |
| Peak Hour Factor | 0.94 | 0.92 | 0.94 | 0.92 | 0.92 | 0.92 | 0.94 | 0.94 | 0.92 | 0.92 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 2% | 1% | 2% | 2% | 2% | 1% | 1% | 2% | 2% | 1% | 1% |
| Adj. Flow (vph) | 0 | 0 | 526 | 0 | 0 | 415 | 0 | 1260 | 0 | 0 | 1382 | 514 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 0 | 526 | 0 | 0 | 415 | 0 | 1260 | 0 | 0 | 1382 | 514 |
| Turn Type | | | Prot | | | Perm | | NA | | | NA | Perm |
| Protected Phases | | | 3 | | | | | 1 3 | | | 1 | |
| Permitted Phases | | | | | | 1 3 | | | | | | 1 |
| Detector Phase | | | 3 | | | 1 3 | | | | | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | | 15.0 | | | | | | | | 10.0 | 10.0 |
| Minimum Split (s) | | | 22.1 | | | | | | | | 26.5 | 26.5 |
| Total Split (s) | | | 70.0 | | | | | | | | 110.0 | 110.0 |
| Total Split (%) | | | 38.9% | | | | | | | | 61.1% | 61.1% |
| Maximum Green (s) | | | 62.9 | | | | | | | | 102.5 | 102.5 |
| Yellow Time (s) | | | 5.1 | | | | | | | | 4.3 | 4.3 |
| All-Red Time (s) | | | 2.0 | | | | | | | | 3.2 | 3.2 |
| Lost Time Adjust (s) | | | 0.0 | | | | | | | | 0.0 | 0.0 |
| Total Lost Time (s) | | | 7.1 | | | | | | | | 7.5 | 7.5 |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | | 3.0 | | | | | | | | 3.0 | 3.0 |
| Recall Mode | | | None | | | | | | | | C-Max | C-Max |
| Walk Time (s) | | | | | | | | | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | | | | | | | | | | 12.0 | 12.0 |
| Pedestrian Calls (#/hr) | | | | | | | | | | | 0 | 0 |
| Act Effct Green (s) | | | 37.7 | | | 180.0 | | 180.0 | | | 127.7 | 127.7 |
| Actuated g/C Ratio | | | 0.21 | | | 1.00 | | 1.00 | | | 0.71 | 0.71 |
| v/c Ratio | | | 0.81 | | | 0.26 | | 0.25 | | | 0.38 | 0.41 |
| Control Delay (s/veh) | | | 68.2 | | | 0.4 | | 0.1 | | | 10.3 | 2.3 |
| Queue Delay | | | 0.0 | | | 0.0 | | 0.0 | | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | | 68.2 | | | 0.4 | | 0.1 | | | 10.3 | 2.3 |
| LOS | | | E | | | A | | A | | | B | A |
| Approach Delay (s/veh) | | 68.2 | | | 0.4 | | | 0.1 | | | 8.1 | |
| Approach LOS | | E | | | A | | | A | | | A | |
| Queue Length 50th (ft) | | | 298 | | | 0 | | 0 | | | 160 | 30 |
| Queue Length 95th (ft) | | | 352 | | | 0 | | 0 | | | 243 | 29 |
| Internal Link Dist (ft) | | 852 | | | 623 | | | 520 | | | 870 | |
| Turn Bay Length (ft) | | | | | | | | | | | | 200 |
| Base Capacity (vph) | | | 1030 | | | 1611 | | 5136 | | | 3644 | 1258 |
| Starvation Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Spillback Cap Reductn | | | 5 | | | 0 | | 0 | | | 10 | 0 |
| Storage Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Reduced v/c Ratio | | | 0.51 | | | 0.26 | | 0.25 | | | 0.38 | 0.41 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.81 | | | |
| Intersection Signal Delay (s/veh): 12.6 | | Intersection LOS: B | |
| Intersection Capacity Utilization 59.0% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 2: Niagara Falls Blvd & I-290 EB Ramp




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 123 | 64 | 15 | 91 | 57 | 859 | 25 | 1131 | 64 | 760 | 1237 | 104 |
| Future Volume (vph) | 123 | 64 | 15 | 91 | 57 | 859 | 25 | 1131 | 64 | 760 | 1237 | 104 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 100 | | 0 | 0 | | 225 | 130 | | 0 | 435 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 2 | 1 | | 0 | 2 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.88 | 1.00 | 0.91 | 0.91 | 0.97 | 0.91 | 0.91 |
| Frt | | 0.972 | | | | 0.850 | | 0.992 | | | 0.988 | |
| Flt Protected | 0.950 | | | | 0.970 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 1829 | 0 | 0 | 1825 | 2814 | 1787 | 5095 | 0 | 3467 | 5074 | 0 |
| Flt Permitted | 0.461 | | | | 0.765 | | 0.950 | | | 0.950 | | |
| Satd. Flow (perm) | 867 | 1829 | 0 | 0 | 1439 | 2814 | 1787 | 5095 | 0 | 3467 | 5074 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 6 | | | | 167 | | 5 | | | 12 | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 853 | | | 2284 | | | 672 | | | 600 | |
| Travel Time (s) | | 19.4 | | | 51.9 | | | 11.5 | | | 10.2 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 127 | 66 | 15 | 94 | 59 | 886 | 26 | 1166 | 66 | 784 | 1275 | 107 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 127 | 81 | 0 | 0 | 153 | 886 | 26 | 1232 | 0 | 784 | 1382 | 0 |
| Turn Type | D.P+P | NA | | Perm | NA | pm+ov | Prot | NA | | Prot | NA | |
| Protected Phases | 7 | 7 8 | | | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 8 | | | 8 | | 8 | | | | | | |
| Detector Phase | 7 | 7 8 | | 8 | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | | | 4.1 | 4.1 | 5.0 | 5.0 | 20.0 | | 5.0 | 20.0 | |
| Minimum Split (s) | 12.7 | | | 12.3 | 12.3 | 12.5 | 11.6 | 32.6 | | 12.5 | 32.6 | |
| Total Split (s) | 25.0 | | | 30.0 | 30.0 | 60.0 | 20.0 | 65.0 | | 60.0 | 105.0 | |
| Total Split (%) | 13.9% | | | 16.7% | 16.7% | 33.3% | 11.1% | 36.1% | | 33.3% | 58.3% | |
| Maximum Green (s) | 17.5 | | | 21.8 | 21.8 | 52.5 | 13.7 | 58.5 | | 52.5 | 98.5 | |
| Yellow Time (s) | 3.6 | | | 4.3 | 4.3 | 3.6 | 4.3 | 4.3 | | 3.6 | 4.3 | |
| All-Red Time (s) | 3.9 | | | 3.9 | 3.9 | 3.9 | 2.0 | 2.2 | | 3.9 | 2.2 | |
| Lost Time Adjust (s) | 0.0 | | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 7.5 | | | | 8.2 | 7.5 | 6.3 | 6.5 | | 7.5 | 6.5 | |
| Lead/Lag | Lead | | | Lag | Lag | Lead | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 2.0 | | | 2.0 | 2.0 | 2.4 | 2.4 | 2.4 | | 2.4 | 2.4 | |
| Recall Mode | None | | | None | None | None | None | C-Max | | None | Max | |
| Walk Time (s) | | | | | | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | | | | | | | 19.0 | | | 19.0 | |
| Pedestrian Calls (#/hr) | | | | | | | | 0 | | | 0 | |
| Act Effct Green (s) | 36.6 | 44.1 | | | 21.6 | 76.9 | 7.5 | 67.3 | | 47.1 | 112.9 | |
| Actuated g/C Ratio | 0.20 | 0.25 | | | 0.12 | 0.43 | 0.04 | 0.37 | | 0.26 | 0.63 | |
| v/c Ratio | 0.51 | 0.18 | | | 0.89 | 0.68 | 0.35 | 0.65 | | 0.86 | 0.43 | |
| Control Delay (s/veh) | 62.0 | 49.4 | | | 120.2 | 35.5 | 99.4 | 12.8 | | 70.9 | 11.4 | |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 1.2 | 0.2 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 62.0 | 49.4 | | | 120.2 | 35.5 | 99.4 | 12.8 | | 72.0 | 11.6 | |
| LOS | E | D | | | F | D | F | B | | E | B | |
| Approach Delay (s/veh) | | 57.1 | | | 48.0 | | | 14.6 | | | 33.5 | |
| Approach LOS | | E | | | D | | | B | | | C | |
| Queue Length 50th (ft) | 120 | 69 | | | 178 | 380 | 32 | 72 | | 364 | 228 | |
| Queue Length 95th (ft) | 186 | 119 | | | #325 | 456 | m53 | 88 | | 468 | 247 | |
| Internal Link Dist (ft) | | 773 | | | 2204 | | | 592 | | | 520 | |
| Turn Bay Length (ft) | 100 | | | | | 225 | 130 | | | 435 | | |
| Base Capacity (vph) | 281 | 433 | | | 180 | 1377 | 136 | 1908 | | 1011 | 3185 | |
| Starvation Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 21 | | 80 | 784 | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.45 | 0.19 | | | 0.85 | 0.64 | 0.19 | 0.65 | | 0.84 | 0.58 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 2:NBT, Start of Yellow | | | |
| Natural Cycle: 90 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.89 | | | |
| Intersection Signal Delay (s/veh): 32.7 | | Intersection LOS: C | |
| Intersection Capacity Utilization 78.2% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 3: Niagara Falls Blvd & Koenig Rd/Ridge Lea Rd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 14 | 9 | 10 | 113 | 7 | 197 | 5 | 8 | 1067 | 108 | 1 | 157 |
| Future Volume (vph) | 14 | 9 | 10 | 113 | 7 | 197 | 5 | 8 | 1067 | 108 | 1 | 157 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 0 | | 160 | | 110 | | 170 | | 300 |
| Storage Lanes | 0 | | 1 | 0 | | 1 | | 1 | | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | | 0.850 | | | | 0.850 | | |
| Flt Protected | | 0.971 | | | 0.955 | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1827 | 1599 | 0 | 1797 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Flt Permitted | | 0.318 | | | 0.720 | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 598 | 1599 | 0 | 1354 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 127 | | | 210 | | | | 127 | | |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | |
| Link Distance (ft) | | 671 | | | 580 | | | | 758 | | | |
| Travel Time (s) | | 15.3 | | | 13.2 | | | | 12.9 | | | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 15 | 10 | 11 | 120 | 7 | 210 | 5 | 9 | 1135 | 115 | 1 | 167 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 25 | 11 | 0 | 127 | 210 | 0 | 14 | 1135 | 115 | 0 | 168 |
| Turn Type | Perm | NA | Perm | Perm | NA | Perm | Prot | Prot | NA | Perm | Prot | Prot |
| Protected Phases | | 3 | | | 4 | | 5 | 5 | 2 | | 1 | 1 |
| Permitted Phases | 3 | | 3 | 4 | | 4 | | | | 2 | | |
| Detector Phase | 3 | 3 | 3 | 4 | 4 | 4 | 5 | 5 | 2 | 2 | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 3.0 | 6.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 3.0 |
| Minimum Split (s) | 23.8 | 23.8 | 23.8 | 24.6 | 24.6 | 24.6 | 10.8 | 10.8 | 23.8 | 23.8 | 10.8 | 10.8 |
| Total Split (s) | 40.0 | 40.0 | 40.0 | 45.0 | 45.0 | 45.0 | 20.0 | 20.0 | 65.0 | 65.0 | 30.0 | 30.0 |
| Total Split (%) | 22.2% | 22.2% | 22.2% | 25.0% | 25.0% | 25.0% | 11.1% | 11.1% | 36.1% | 36.1% | 16.7% | 16.7% |
| Maximum Green (s) | 34.2 | 34.2 | 34.2 | 38.4 | 38.4 | 38.4 | 14.2 | 14.2 | 59.2 | 59.2 | 24.2 | 24.2 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | 3.2 | 3.2 | 3.2 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 1.9 | 1.9 | 1.9 | 3.4 | 3.4 | 3.4 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 5.8 | 5.8 | | 6.6 | 6.6 | | 5.8 | 5.8 | 5.8 | | 5.8 |
| Lead/Lag | Lead | Lead | Lead | Lag | Lag | Lag | Lead | Lead | Lag | Lag | Lead | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | Max | Max | Max | Max | Max | Max | None | None | C-Max | C-Max | Min | Min |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | | | 11.0 | 11.0 | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | | |
| Act Effct Green (s) | | 34.2 | 34.2 | | 38.4 | 38.4 | | 7.0 | 62.5 | 62.5 | | 20.9 |
| Actuated g/C Ratio | | 0.19 | 0.19 | | 0.21 | 0.21 | | 0.04 | 0.35 | 0.35 | | 0.12 |
| v/c Ratio | | 0.22 | 0.03 | | 0.44 | 0.42 | | 0.20 | 0.64 | 0.18 | | 0.81 |
| Control Delay (s/veh) | | 67.7 | 0.1 | | 67.1 | 9.0 | | 111.4 | 55.9 | 9.1 | | 95.8 |
| Queue Delay | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 1009 | 22 |
| Future Volume (vph) | 1009 | 22 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.997 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5120 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5120 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 2 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 672 | |
| Travel Time (s) | 11.5 | |
| Peak Hour Factor | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 1073 | 23 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 1096 | 0 |
| Turn Type | NA | |
| Protected Phases | 6 | |
| Permitted Phases | | |
| Detector Phase | 6 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 23.4 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 41.7% | |
| Maximum Green (s) | 69.6 | |
| Yellow Time (s) | 3.5 | |
| All-Red Time (s) | 1.9 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 5.4 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | C-Max | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 11.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 84.0 | |
| Actuated g/C Ratio | 0.47 | |
| v/c Ratio | 0.46 | |
| Control Delay (s/veh) | 16.7 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 67.7 | 0.1 | | 67.1 | 9.0 | | 111.4 | 55.9 | 9.1 | | 95.8 |
| LOS | | E | A | | E | A | | F | E | A | | F |
| Approach Delay (s/veh) | | 47.1 | | | 30.9 | | | | 52.3 | | | |
| Approach LOS | | D | | | C | | | | D | | | |
| Queue Length 50th (ft) | | 25 | 0 | | 132 | 0 | | 13 | 490 | 50 | | 145 |
| Queue Length 95th (ft) | | 60 | 0 | | 207 | 75 | | m0 | 547 | m76 | | m253 |
| Internal Link Dist (ft) | | 591 | | | 500 | | | | 678 | | | |
| Turn Bay Length (ft) | | | 25 | | | 160 | | 110 | | 170 | | 300 |
| Base Capacity (vph) | | 113 | 406 | | 288 | 506 | | 140 | 1782 | 638 | | 240 |
| Starvation Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.22 | 0.03 | | 0.44 | 0.42 | | 0.10 | 0.64 | 0.18 | | 0.70 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 85 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.81 | | | |
| Intersection Signal Delay (s/veh): 38.8 | | Intersection LOS: D | |
| Intersection Capacity Utilization 64.9% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 4: Niagara Falls Blvd & Pier 1 Entrance/The Boulevard/Consumer Square





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 16.7 | |
| LOS | B | |
| Approach Delay (s/veh) | 27.2 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 148 | |
| Queue Length 95th (ft) | 350 | |
| Internal Link Dist (ft) | 592 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 2389 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.46 | |

Intersection Summary

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 44 | 62 | 21 | 150 | 90 | 168 | 2 | 27 | 856 | 60 | 173 | 940 |
| Future Volume (vph) | 44 | 62 | 21 | 150 | 90 | 168 | 2 | 27 | 856 | 60 | 173 | 940 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 100 | | 0 | | 120 | | 165 | 315 | |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 1 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 |
| Frt | | | 0.850 | | 0.902 | | | | | 0.850 | | 0.994 |
| Flt Protected | | 0.980 | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1844 | 1599 | 1787 | 1697 | 0 | 0 | 1787 | 5136 | 1599 | 1787 | 5105 |
| Flt Permitted | | 0.233 | | 0.616 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 438 | 1599 | 1159 | 1697 | 0 | 0 | 1787 | 5136 | 1599 | 1787 | 5105 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 63 | | 53 | | | | | 64 | | 4 |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | 40 |
| Link Distance (ft) | | 713 | | | 278 | | | | 1759 | | | 758 |
| Travel Time (s) | | 16.2 | | | 6.3 | | | | 30.0 | | | 12.9 |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 45 | 64 | 22 | 155 | 93 | 173 | 2 | 28 | 882 | 62 | 178 | 969 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 109 | 22 | 155 | 266 | 0 | 0 | 30 | 882 | 62 | 178 | 1012 |
| Turn Type | Perm | NA | Perm | Perm | NA | | Prot | Prot | NA | Perm | Prot | NA |
| Protected Phases | | 4 | | | 8 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 4 | | 4 | 8 | | | | | | 2 | | |
| Detector Phase | 4 | 4 | 4 | 8 | 8 | | 5 | 5 | 2 | 2 | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 |
| Minimum Split (s) | 48.9 | 48.9 | 48.9 | 48.9 | 48.9 | | 11.7 | 11.7 | 40.0 | 40.0 | 11.7 | 31.7 |
| Total Split (s) | 60.0 | 60.0 | 60.0 | 60.0 | 60.0 | | 45.0 | 45.0 | 75.0 | 75.0 | 45.0 | 75.0 |
| Total Split (%) | 33.3% | 33.3% | 33.3% | 33.3% | 33.3% | | 25.0% | 25.0% | 41.7% | 41.7% | 25.0% | 41.7% |
| Maximum Green (s) | 53.1 | 53.1 | 53.1 | 53.1 | 53.1 | | 38.3 | 38.3 | 68.3 | 68.3 | 38.3 | 68.3 |
| Yellow Time (s) | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 3.7 | 3.7 | 3.7 | 3.7 | 3.7 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.9 | 6.9 | 6.9 | 6.9 | | | 6.7 | 6.7 | 6.7 | 6.7 | 6.7 |
| Lead/Lag | | | | | | | Lead | Lead | Lag | Lag | Lead | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | None | None | None | | None | None | C-Max | C-Max | None | C-Max |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | 7.0 | | 7.0 |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | 30.0 | 30.0 | | | | 24.0 | 24.0 | | 18.0 |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | | | | 0 | 0 | | 0 |
| Act Effct Green (s) | | 28.2 | 28.2 | 28.2 | 28.2 | | | 7.9 | 108.8 | 108.8 | 22.7 | 125.9 |
| Actuated g/C Ratio | | 0.16 | 0.16 | 0.16 | 0.16 | | | 0.04 | 0.60 | 0.60 | 0.13 | 0.70 |
| v/c Ratio | | 1.60 | 0.07 | 0.86 | 0.86 | | | 0.38 | 0.28 | 0.06 | 0.79 | 0.28 |
| Control Delay (s/veh) | | 372.5 | 0.5 | 109.5 | 82.3 | | | 78.1 | 36.1 | 21.1 | 117.6 | 2.6 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 42 |
| Future Volume (vph) | 42 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Peak Hour Factor | 0.97 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 43 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |
| Control Delay (s/veh) | |
| Queue Delay | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 372.5 | 0.5 | 109.5 | 82.3 | | | 78.1 | 36.1 | 21.1 | 117.6 | 2.6 |
| LOS | | F | A | F | F | | | E | D | C | F | A |
| Approach Delay (s/veh) | | 310.0 | | | 92.3 | | | | 36.5 | | | 19.8 |
| Approach LOS | | F | | | F | | | | D | | | B |
| Queue Length 50th (ft) | | ~183 | 0 | 181 | 251 | | | 36 | 265 | 12 | 218 | 22 |
| Queue Length 95th (ft) | | #291 | 0 | m254 | m340 | | | m73 | 394 | 67 | 294 | 36 |
| Internal Link Dist (ft) | | 633 | | | 198 | | | | 1679 | | | 678 |
| Turn Bay Length (ft) | | | 25 | 100 | | | | 120 | | 165 | 315 | |
| Base Capacity (vph) | | 129 | 516 | 341 | 537 | | | 380 | 3103 | 991 | 380 | 3573 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.84 | 0.04 | 0.45 | 0.50 | | | 0.08 | 0.28 | 0.06 | 0.47 | 0.28 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 150 (83%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 1.60 | | | |
| Intersection Signal Delay (s/veh): 51.0 | | Intersection LOS: D | |
| Intersection Capacity Utilization 69.5% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| ~ Volume exceeds capacity, queue is theoretically infinite. | | | |
| Queue shown is maximum after two cycles. | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 5: Niagara Falls Blvd & Glenalby Rd/Romney Dr





| Lane Group | SBR |
|---|---|
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|

| Intersection | |
|---|---|
| Int Delay, s/veh | 25.2 |

| Movement | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | | | |
| Traffic Vol, veh/h | 1 | 0 | 13 | 63 | 0 | 49 | 2 | 0 | 1352 | 74 | 36 | 57 | 1163 | 11 |
| Future Vol, veh/h | 1 | 0 | 13 | 63 | 0 | 49 | 2 | 0 | 1352 | 74 | 36 | 57 | 1163 | 11 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Stop | Stop | Stop | Stop | Free | Free | Free | Free | Free | Free | Free | Free |
| RT Channelized | - | - | None | - | - | None | - | - | - | None | - | - | - | None |
| Storage Length | - | - | - | - | - | - | - | - | - | - | - | 105 | - | - |
| Veh in Median Storage, # | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Grade, % | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Peak Hour Factor | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 1 | 0 | 13 | 64 | 0 | 50 | 2 | 0 | 1380 | 76 | 37 | 58 | 1187 | 11 |

| Major/Minor | Minor2 | | | Minor1 | | | Major1 | | | | Major2 | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Conflicting Flow All | 1938 | 2841 | 599 | 2086 | 2809 | 728 | 875 | 1198 | 0 | 0 | 1062 | 1455 | 0 | 0 |
| Stage 1 | 1382 | 1382 | - | 1421 | 1421 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 556 | 1459 | - | 664 | 1388 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy | 6.42 | 6.52 | 7.12 | 6.42 | 6.52 | 7.12 | 5.64 | 5.32 | - | - | 5.62 | 5.32 | - | - |
| Critical Hdwy Stg 1 | 7.32 | 5.52 | - | 7.32 | 5.52 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy Stg 2 | 6.72 | 5.52 | - | 6.72 | 5.52 | - | - | - | - | - | - | - | - | - |
| Follow-up Hdwy | 3.81 | 4.01 | 3.91 | 3.81 | 4.01 | 3.91 | 2.32 | 3.11 | - | - | 2.31 | 3.11 | - | - |
| Pot Cap-1 Maneuver | 70 | 17 | 383 | ~ 57 | 18 | 316 | 516 | 316 | - | - | 409 | 237 | - | - |
| Stage 1 | 108 | 211 | - | 102 | 202 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 443 | 194 | - | 381 | 210 | - | - | - | - | - | - | - | - | - |
| Platoon blocked, % | | | | | | | | | - | - | | | - | - |
| Mov Cap-1 Maneuver | 38 | 11 | 383 | ~ 35 | 12 | 316 | 498 | 498 | - | - | 269 | 269 | - | - |
| Mov Cap-2 Maneuver | 38 | 11 | - | ~ 35 | 12 | - | - | - | - | - | - | - | - | - |
| Stage 1 | 70 | 137 | - | 101 | 201 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 371 | 193 | - | 238 | 136 | - | - | - | - | - | - | - | - | - |

| Approach | EB | WB | NB | SB |
|---|---|---|---|---|
| HCM Control Delay, s/v | 21.5 | $ 609.79 | 0.15 | 1.87 |
| HCM LOS | C | F | | |

| Minor Lane/Major Mvmt | NBL | NBT | NBR | EBLn1 | WBLn1 | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|
| Capacity (veh/h) | 7 | - | - | 232 | 58 | 269 | - | - |
| HCM Lane V/C Ratio | - | - | - | 0.061 | 1.978 | 0.352 | - | - |
| HCM Control Delay (s/veh) | 12.3 | 0.1 | - | 21.5 | $ 609.8 | 25.5 | - | - |
| HCM Lane LOS | B | A | - | C | F | D | - | - |
| HCM 95th %tile Q(veh) | 0 | - | - | 0.2 | 11 | 1.5 | - | - |

| Notes | | | |
|---|---|---|---|
| ~: Volume exceeds capacity | $: Delay exceeds 300s | +: Computation Not Defined | *: All major volume in platoon |


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 167 | 320 | 77 | 345 | 399 | 289 | 14 | 92 | 917 | 268 | 1 | 291 |
| Future Volume (vph) | 167 | 320 | 77 | 345 | 399 | 289 | 14 | 92 | 917 | 268 | 1 | 291 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 50 | | 50 | 400 | | 0 | | 300 | | 300 | | 350 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | | 1 | | 1 | | 2 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 0.91 | 0.97 |
| Frt | | 0.971 | | | | 0.850 | | | | 0.850 | | |
| Flt Protected | 0.950 | | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 1787 | 3471 | 0 | 1787 | 3574 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 3467 |
| Flt Permitted | 0.474 | | | 0.186 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 892 | 3471 | 0 | 350 | 3574 | 1599 | 0 | 1787 | 5136 | 1599 | 0 | 3467 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 15 | | | | 292 | | | | 276 | | |
| Link Speed (mph) | | 30 | | | 45 | | | | 40 | | | |
| Link Distance (ft) | | 1574 | | | 1441 | | | | 956 | | | |
| Travel Time (s) | | 35.8 | | | 21.8 | | | | 16.3 | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 172 | 330 | 79 | 356 | 411 | 298 | 14 | 95 | 945 | 276 | 1 | 300 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 172 | 409 | 0 | 356 | 411 | 298 | 0 | 109 | 945 | 276 | 0 | 301 |
| Turn Type | pm+pt | NA | | pm+pt | NA | Perm | Prot | Prot | NA | Perm | Prot | Prot |
| Protected Phases | 7 | 4 | | 3 | 8 | | 5 | 5 | 2 | | 1 | 1 |
| Permitted Phases | 4 | | | 8 | | 8 | | | | 2 | | |
| Detector Phase | 7 | 4 | | 3 | 8 | 8 | 5 | 5 | 2 | 2 | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 6.0 | | 3.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 3.0 |
| Minimum Split (s) | 17.5 | 48.8 | | 13.8 | 47.8 | 47.8 | 12.1 | 12.1 | 39.1 | 39.1 | 12.1 | 12.1 |
| Total Split (s) | 30.0 | 50.0 | | 35.0 | 55.0 | 55.0 | 20.0 | 20.0 | 65.0 | 65.0 | 30.0 | 30.0 |
| Total Split (%) | 16.7% | 27.8% | | 19.4% | 30.6% | 30.6% | 11.1% | 11.1% | 36.1% | 36.1% | 16.7% | 16.7% |
| Maximum Green (s) | 21.9 | 41.9 | | 26.9 | 46.9 | 46.9 | 13.1 | 13.1 | 58.1 | 58.1 | 23.1 | 23.1 |
| Yellow Time (s) | 3.8 | 3.8 | | 3.8 | 3.8 | 3.8 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 4.3 | 4.3 | | 4.3 | 4.3 | 4.3 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | 8.1 | 8.1 | | 8.1 | 8.1 | 8.1 | | 6.9 | 6.9 | 6.9 | | 6.9 |
| Lead/Lag | Lead | Lag | | Lead | Lag | Lag | Lead | Lead | Lag | Lag | Lead | Lead |
| Lead-Lag Optimize? | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | | 2.5 | 2.5 | 2.5 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | | None | None | None | None | None | C-Max | C-Max | None | None |
| Walk Time (s) | | 7.0 | | | 7.0 | 7.0 | | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | | 33.0 | | | 31.0 | 31.0 | | | 24.0 | 24.0 | | |
| Pedestrian Calls (#/hr) | | 0 | | | 0 | 0 | | | 0 | 0 | | |
| Act Effct Green (s) | 42.1 | 25.0 | | 59.3 | 34.9 | 34.9 | | 16.7 | 77.8 | 77.8 | | 20.3 |
| Actuated g/C Ratio | 0.23 | 0.14 | | 0.33 | 0.19 | 0.19 | | 0.09 | 0.43 | 0.43 | | 0.11 |
| v/c Ratio | 0.59 | 0.83 | | 1.08 | 0.59 | 0.55 | | 0.66 | 0.43 | 0.33 | | 0.77 |
| Control Delay (s/veh) | 53.1 | 86.6 | | 119.2 | 70.0 | 10.5 | | 97.0 | 37.3 | 4.6 | | 105.4 |
| Queue Delay | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 822 | 134 |
| Future Volume (vph) | 822 | 134 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.979 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5028 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5028 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 20 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 608 | |
| Travel Time (s) | 10.4 | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 847 | 138 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 985 | 0 |
| Turn Type | NA | |
| Protected Phases | 6 | |
| Permitted Phases | | |
| Detector Phase | 6 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 32.1 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 41.7% | |
| Maximum Green (s) | 68.1 | |
| Yellow Time (s) | 3.9 | |
| All-Red Time (s) | 3.0 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.9 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 2.4 | |
| Recall Mode | C-Max | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 17.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 81.3 | |
| Actuated g/C Ratio | 0.45 | |
| v/c Ratio | 0.43 | |
| Control Delay (s/veh) | 20.7 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 53.1 | 86.6 | | 119.2 | 70.0 | 10.5 | | 97.0 | 37.3 | 4.6 | | 105.4 |
| LOS | D | F | | F | E | B | | F | D | A | | F |
| Approach Delay (s/veh) | | 76.7 | | | 69.8 | | | | 35.4 | | | |
| Approach LOS | | E | | | E | | | | D | | | |
| Queue Length 50th (ft) | 151 | 242 | | ~386 | 236 | 6 | | 126 | 283 | 0 | | 189 |
| Queue Length 95th (ft) | 209 | 296 | | #593 | 295 | 99 | | 195 | 361 | 64 | | 243 |
| Internal Link Dist (ft) | | 1494 | | | 1361 | | | | 876 | | | |
| Turn Bay Length (ft) | 50 | | | 400 | | | | 300 | | 300 | | 350 |
| Base Capacity (vph) | 341 | 819 | | 329 | 931 | 632 | | 169 | 2219 | 847 | | 453 |
| Starvation Cap Reductn | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Spillback Cap Reductn | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Storage Cap Reductn | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 |
| Reduced v/c Ratio | 0.50 | 0.50 | | 1.08 | 0.44 | 0.47 | | 0.64 | 0.43 | 0.33 | | 0.66 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 120 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 1.08 | | | |
| Intersection Signal Delay (s/veh): 51.2 | | Intersection LOS: D | |
| Intersection Capacity Utilization 81.5% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| ~ Volume exceeds capacity, queue is theoretically infinite. | | | |
| Queue shown is maximum after two cycles. | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 7: Niagara Falls Blvd & Brighton Rd/Maple Rd





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 20.7 | |
| LOS | C | |
| Approach Delay (s/veh) | 40.5 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 159 | |
| Queue Length 95th (ft) | 185 | |
| Internal Link Dist (ft) | 528 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 2282 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.43 | |

Intersection Summary


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 4 | 1 | 7 | 73 | 4 | 75 | 2 | 7 | 1074 | 70 | 13 | 75 |
| Future Volume (vph) | 4 | 1 | 7 | 73 | 4 | 75 | 2 | 7 | 1074 | 70 | 13 | 75 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 125 | | 0 | | 330 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 |
| Frt | | 0.921 | | | 0.857 | | | | 0.991 | | | |
| Flt Protected | | 0.984 | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1705 | 0 | 1787 | 1612 | 0 | 0 | 1787 | 5089 | 0 | 0 | 1787 |
| Flt Permitted | | 0.879 | | 0.750 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 1523 | 0 | 1411 | 1612 | 0 | 0 | 1787 | 5089 | 0 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 7 | | | 80 | | | | 8 | | | |
| Link Speed (mph) | | 25 | | | 25 | | | | 40 | | | |
| Link Distance (ft) | | 642 | | | 490 | | | | 588 | | | |
| Travel Time (s) | | 17.5 | | | 13.4 | | | | 10.0 | | | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 4 | 1 | 7 | 78 | 4 | 80 | 2 | 7 | 1143 | 74 | 14 | 80 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 12 | 0 | 78 | 84 | 0 | 0 | 9 | 1217 | 0 | 0 | 94 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | Prot |
| Protected Phases | | 3 | | | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 |
| Minimum Split (s) | 39.2 | 39.2 | | 39.2 | 39.2 | | 9.3 | 9.3 | 31.3 | | 9.3 | 9.3 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 35.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 21.9% |
| Maximum Green (s) | 43.8 | 43.8 | | 43.8 | 43.8 | | 28.7 | 28.7 | 68.7 | | 28.7 | 28.7 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |
| Total Lost Time (s) | | 6.2 | | 6.2 | 6.2 | | | 6.3 | 6.3 | | | 6.3 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | 3.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | None |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | 26.0 | 26.0 | | 26.0 | 26.0 | | | | 18.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 9.0 | | 9.0 | 9.0 | | | 5.1 | 27.2 | | | 8.7 |
| Actuated g/C Ratio | | 0.15 | | 0.15 | 0.15 | | | 0.08 | 0.44 | | | 0.14 |
| v/c Ratio | | 0.05 | | 0.38 | 0.27 | | | 0.06 | 0.54 | | | 0.37 |
| Control Delay (s/veh) | | 19.8 | | 32.0 | 10.6 | | | 32.5 | 14.7 | | | 31.2 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 1184 | 15 |
| Future Volume (vph) | 1184 | 15 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.998 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5125 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5125 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 1 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 956 | |
| Travel Time (s) | 16.3 | |
| Peak Hour Factor | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 1260 | 16 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 1276 | 0 |
| Turn Type | NA | |
| Protected Phases | 2 | |
| Permitted Phases | | |
| Detector Phase | 2 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 33.3 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 46.9% | |
| Maximum Green (s) | 68.7 | |
| Yellow Time (s) | 4.0 | |
| All-Red Time (s) | 2.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.3 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | Min | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 20.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 37.3 | |
| Actuated g/C Ratio | 0.61 | |
| v/c Ratio | 0.41 | |
| Control Delay (s/veh) | 7.5 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 19.8 | | 32.0 | 10.6 | | | 32.5 | 14.7 | | | 31.2 |
| LOS | | B | | C | B | | | C | B | | | C |
| Approach Delay (s/veh) | | 19.8 | | | 20.9 | | | | 14.9 | | | |
| Approach LOS | | B | | | C | | | | B | | | |
| Queue Length 50th (ft) | | 2 | | 26 | 1 | | | 3 | 121 | | | 32 |
| Queue Length 95th (ft) | | 16 | | 75 | 39 | | | 18 | 198 | | | 86 |
| Internal Link Dist (ft) | | 562 | | | 410 | | | | 508 | | | |
| Turn Bay Length (ft) | | | | | | | | 125 | | | | 330 |
| Base Capacity (vph) | | 1135 | | 1049 | 1219 | | | 871 | 4946 | | | 871 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Reduced v/c Ratio | | 0.01 | | 0.07 | 0.07 | | | 0.01 | 0.25 | | | 0.11 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 61.2 | | | |
| Natural Cycle: 85 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.54 | | | |
| Intersection Signal Delay (s/veh): 12.4 | | Intersection LOS: B | |
| Intersection Capacity Utilization 53.0% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 8: Niagara Falls Blvd & Driveway 4/Boulevard Mall Driveway





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 7.5 | |
| LOS | A | |
| Approach Delay (s/veh) | 9.1 | |
| Approach LOS | A | |
| Queue Length 50th (ft) | 65 | |
| Queue Length 95th (ft) | 175 | |
| Internal Link Dist (ft) | 876 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 4981 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.26 | |

| Intersection Summary |
|---|



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 21 | 14 | 20 | 92 | 11 | 71 | 21 | 18 | 1054 | 62 | 74 | 1207 |
| Future Volume (vph) | 21 | 14 | 20 | 92 | 11 | 71 | 21 | 18 | 1054 | 62 | 74 | 1207 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 150 | | 0 | 250 | |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 |
| Frt | | 0.951 | | | 0.871 | | | | 0.992 | | | 0.997 |
| Flt Protected | | 0.981 | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1755 | 0 | 1787 | 1639 | 0 | 0 | 1787 | 5095 | 0 | 1787 | 5120 |
| Flt Permitted | | 0.860 | | 0.719 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 1539 | 0 | 1353 | 1639 | 0 | 0 | 1787 | 5095 | 0 | 1787 | 5120 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 18 | | | 75 | | | | 7 | | | 2 |
| Link Speed (mph) | | 30 | | | 25 | | | | 40 | | | 40 |
| Link Distance (ft) | | 538 | | | 562 | | | | 2182 | | | 588 |
| Travel Time (s) | | 12.2 | | | 15.3 | | | | 37.2 | | | 10.0 |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 22 | 15 | 21 | 97 | 12 | 75 | 22 | 19 | 1109 | 65 | 78 | 1271 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 58 | 0 | 97 | 87 | 0 | 0 | 41 | 1174 | 0 | 78 | 1299 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | NA |
| Protected Phases | | 3 | | | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 10.0 |
| Minimum Split (s) | 41.6 | 41.6 | | 41.6 | 41.6 | | 16.3 | 16.3 | 32.6 | | 16.3 | 32.6 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 75.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 46.9% |
| Maximum Green (s) | 43.4 | 43.4 | | 43.4 | 43.4 | | 28.4 | 28.4 | 68.4 | | 28.4 | 68.4 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.4 | 3.4 | | 3.4 | 3.4 | | 2.6 | 2.6 | 2.6 | | 2.6 | 2.6 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.6 | | 6.6 | 6.6 | | | 6.6 | 6.6 | | 6.6 | 6.6 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.5 | 3.5 | | 3.5 | 3.5 | | 2.0 | 2.0 | 4.0 | | 2.0 | 4.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | Min |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | 7.0 | | | 7.0 |
| Flash Don't Walk (s) | 28.0 | 28.0 | | 28.0 | 28.0 | | | | 19.0 | | | 19.0 |
| Pedestrian Calls (#/hr) | 5 | 5 | | 5 | 5 | | | | 5 | | | 5 |
| Act Effct Green (s) | | 14.5 | | 14.5 | 14.5 | | | 6.9 | 32.7 | | 8.9 | 37.3 |
| Actuated g/C Ratio | | 0.20 | | 0.20 | 0.20 | | | 0.09 | 0.44 | | 0.12 | 0.50 |
| v/c Ratio | | 0.18 | | 0.37 | 0.23 | | | 0.25 | 0.52 | | 0.36 | 0.50 |
| Control Delay (s/veh) | | 21.9 | | 32.4 | 10.7 | | | 42.5 | 17.9 | | 41.0 | 15.2 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 27 |
| Future Volume (vph) | 27 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Peak Hour Factor | 0.95 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 28 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |
| Control Delay (s/veh) | |
| Queue Delay | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 21.9 | | 32.4 | 10.7 | | | 42.5 | 17.9 | | 41.0 | 15.2 |
| LOS | | C | | C | B | | | D | B | | D | B |
| Approach Delay (s/veh) | | 21.9 | | | 22.1 | | | | 18.7 | | | 16.7 |
| Approach LOS | | C | | | C | | | | B | | | B |
| Queue Length 50th (ft) | | 15 | | 38 | 4 | | | 17 | 131 | | 31 | 141 |
| Queue Length 95th (ft) | | 53 | | 99 | 44 | | | 65 | 287 | | 103 | 307 |
| Internal Link Dist (ft) | | 458 | | | 482 | | | | 2102 | | | 508 |
| Turn Bay Length (ft) | | | | | | | | 150 | | | 250 | |
| Base Capacity (vph) | | 996 | | 870 | 1081 | | | 752 | 4542 | | 752 | 4564 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 81 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | | 0.06 | | 0.11 | 0.08 | | | 0.05 | 0.26 | | 0.10 | 0.29 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 73.9 | | | |
| Natural Cycle: 95 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.52 | | | |
| Intersection Signal Delay (s/veh): 18.0 | | Intersection LOS: B | |
| Intersection Capacity Utilization 55.1% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 9: Niagara Falls Blvd & Treadwell Rd/Driveway 2





| Lane Group | SBR |
|---|---|
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|




| Lane Group | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 376 | 684 | 0 | 2 | 305 | 736 | 58 | 0 | 607 | 65 | 34 | 169 |
| Future Volume (vph) | 376 | 684 | 0 | 2 | 305 | 736 | 58 | 0 | 607 | 65 | 34 | 169 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 370 | | 0 | | 300 | | 300 | 0 | | 0 | | 450 |
| Storage Lanes | 2 | | 0 | | 2 | | 1 | 0 | | 0 | | 2 |
| Taper Length (ft) | 25 | | | | 25 | | | 25 | | | | 25 |
| Lane Util. Factor | 0.97 | 0.91 | 0.91 | 0.91 | 0.97 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 | 0.97 |
| Ped Bike Factor | 1.00 | | | | 1.00 | | 0.98 | | | | | |
| Frt | | | | | | | 0.850 | | 0.985 | | | |
| Flt Protected | 0.950 | | | | 0.950 | | | | | | | 0.950 |
| Satd. Flow (prot) | 3467 | 5136 | 0 | 0 | 3467 | 5136 | 1599 | 0 | 5059 | 0 | 0 | 3467 |
| Flt Permitted | 0.950 | | | | 0.950 | | | | | | | 0.950 |
| Satd. Flow (perm) | 3463 | 5136 | 0 | 0 | 3465 | 5136 | 1575 | 0 | 5059 | 0 | 0 | 3467 |
| Right Turn on Red | | | Yes | | | | Yes | | | Yes | | |
| Satd. Flow (RTOR) | | | | | | | 119 | | 10 | | | |
| Link Speed (mph) | | 40 | | | | 40 | | | 40 | | | |
| Link Distance (ft) | | 623 | | | | 1468 | | | 379 | | | |
| Travel Time (s) | | 10.6 | | | | 25.0 | | | 6.5 | | | |
| Confl. Peds. (#/hr) | 2 | | 1 | | 1 | | 2 | | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 388 | 705 | 0 | 2 | 314 | 759 | 60 | 0 | 626 | 67 | 35 | 174 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 388 | 705 | 0 | 0 | 316 | 759 | 60 | 0 | 693 | 0 | 0 | 209 |
| Turn Type | Prot | NA | | Prot | Prot | NA | Perm | | NA | | Prot | Prot |
| Protected Phases | 3 | 8 | | 7 | 7 | 4 | | | 2 | | 1 | 1 |
| Permitted Phases | | | | | | | 4 | | | | | |
| Detector Phase | 3 | 8 | | 7 | 7 | 4 | 4 | | 2 | | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 6.0 | | 3.0 | 3.0 | 6.0 | 6.0 | | 10.0 | | 3.0 | 3.0 |
| Minimum Split (s) | 10.3 | 48.0 | | 10.3 | 10.3 | 48.0 | 48.0 | | 58.2 | | 12.3 | 12.3 |
| Total Split (s) | 37.0 | 48.0 | | 37.0 | 37.0 | 48.0 | 48.0 | | 68.0 | | 37.0 | 37.0 |
| Total Split (%) | 19.5% | 25.3% | | 19.5% | 19.5% | 25.3% | 25.3% | | 35.8% | | 19.5% | 19.5% |
| Maximum Green (s) | 29.7 | 40.7 | | 29.7 | 29.7 | 40.7 | 40.7 | | 59.8 | | 28.8 | 28.8 |
| Yellow Time (s) | 4.0 | 4.0 | | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.3 | 3.3 | | 3.3 | 3.3 | 3.3 | 3.3 | | 4.2 | | 4.2 | 4.2 |
| Lost Time Adjust (s) | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 |
| Total Lost Time (s) | 7.3 | 7.3 | | | 7.3 | 7.3 | 7.3 | | 8.2 | | | 8.2 |
| Lead/Lag | Lead | Lag | | Lead | Lead | Lag | Lag | | Lag | | Lead | Lead |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 2.0 | 4.0 | | 2.0 | 2.0 | 4.0 | 4.0 | | 4.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | None | None | | C-Min | | None | None |
| Walk Time (s) | | 7.0 | | | | 7.0 | 7.0 | | 7.0 | | | |
| Flash Don't Walk (s) | | 30.0 | | | | 30.0 | 30.0 | | 39.0 | | | |
| Pedestrian Calls (#/hr) | | 0 | | | | 2 | 2 | | 1 | | | |
| Act Effct Green (s) | 25.5 | 40.9 | | | 21.7 | 37.0 | 37.0 | | 80.6 | | | 15.8 |
| Actuated g/C Ratio | 0.13 | 0.22 | | | 0.11 | 0.19 | 0.19 | | 0.42 | | | 0.08 |
| v/c Ratio | 0.83 | 0.64 | | | 0.80 | 0.76 | 0.15 | | 0.32 | | | 0.73 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | ↑↑ | ↱ |
| Traffic Volume (vph) | 773 | 442 |
| Future Volume (vph) | 773 | 442 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 1.00 |
| Ped Bike Factor | | |
| Frt | | 0.850 |
| Flt Protected | | |
| Satd. Flow (prot) | 3574 | 1599 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3574 | 1599 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | | 456 |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 2182 | |
| Travel Time (s) | 37.2 | |
| Confl. Peds. (#/hr) | | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 797 | 456 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 797 | 456 |
| Turn Type | NA | Perm |
| Protected Phases | 6 | |
| Permitted Phases | | 6 |
| Detector Phase | 6 | 6 |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | 10.0 |
| Minimum Split (s) | 58.2 | 58.2 |
| Total Split (s) | 105.0 | 105.0 |
| Total Split (%) | 55.3% | 55.3% |
| Maximum Green (s) | 96.8 | 96.8 |
| Yellow Time (s) | 4.0 | 4.0 |
| All-Red Time (s) | 4.2 | 4.2 |
| Lost Time Adjust (s) | 0.0 | 0.0 |
| Total Lost Time (s) | 8.2 | 8.2 |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 4.0 | 4.0 |
| Recall Mode | C-Min | C-Min |
| Walk Time (s) | 7.0 | 7.0 |
| Flash Don't Walk (s) | 39.0 | 39.0 |
| Pedestrian Calls (#/hr) | 2 | 2 |
| Act Effct Green (s) | 104.6 | 104.6 |
| Actuated g/C Ratio | 0.55 | 0.55 |
| v/c Ratio | 0.40 | 0.42 |

| Lane Group | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | 95.7 | 70.2 | | | 97.2 | 77.2 | 0.8 | | 20.7 | | | 99.2 |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.2 | | | 0.0 |
| Total Delay (s/veh) | 95.7 | 70.2 | | | 97.2 | 77.2 | 0.8 | | 20.9 | | | 99.2 |
| LOS | F | E | | | F | E | A | | C | | | F |
| Approach Delay (s/veh) | | 79.2 | | | | 78.8 | | | 20.9 | | | |
| Approach LOS | | E | | | | E | | | C | | | |
| Queue Length 50th (ft) | 247 | 298 | | | 202 | 334 | 0 | | 98 | | | 134 |
| Queue Length 95th (ft) | 301 | 329 | | | 253 | 367 | 0 | | 76 | | | 179 |
| Internal Link Dist (ft) | | 543 | | | | 1388 | | | 299 | | | |
| Turn Bay Length (ft) | 370 | | | | 300 | | 300 | | | | | 450 |
| Base Capacity (vph) | 547 | 1159 | | | 541 | 1119 | 436 | | 2152 | | | 525 |
| Starvation Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | | 709 | | | 0 |
| Spillback Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | | 0 | | | 0 |
| Storage Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | | 0 | | | 0 |
| Reduced v/c Ratio | 0.71 | 0.61 | | | 0.58 | 0.68 | 0.14 | | 0.48 | | | 0.40 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 140 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.83 | | | |
| Intersection Signal Delay (s/veh): 53.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 70.8% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 10: Niagara Falls Blvd & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Control Delay (s/veh) | 26.6 | 3.2 |
| Queue Delay | 0.1 | 0.0 |
| Total Delay (s/veh) | 26.7 | 3.2 |
| LOS | C | A |
| Approach Delay (s/veh) | 29.7 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 296 | 0 |
| Queue Length 95th (ft) | 406 | 63 |
| Internal Link Dist (ft) | 2102 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 1987 | 1091 |
| Starvation Cap Reductn | 0 | 0 |
| Spillback Cap Reductn | 287 | 0 |
| Storage Cap Reductn | 0 | 0 |
| Reduced v/c Ratio | 0.47 | 0.42 |

| Intersection Summary |
|---|

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 1 | 242 | 169 | 46 | 298 | 92 | 2 | 153 | 753 | 41 | 3 | 107 |
| Future Volume (vph) | 1 | 242 | 169 | 46 | 298 | 92 | 2 | 153 | 753 | 41 | 3 | 107 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 100 | 200 | | 0 | | 250 | | 0 | | 0 |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 0.95 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 0.91 | 1.00 | 0.91 | 0.91 | 0.95 | 1.00 |
| Frt | | | 0.850 | | 0.965 | | | | 0.992 | | | |
| Flt Protected | | | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 3574 | 1599 | 1787 | 3449 | 0 | 0 | 1787 | 5095 | 0 | 0 | 1787 |
| Flt Permitted | | 0.953 | | 0.474 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 3406 | 1599 | 892 | 3449 | 0 | 0 | 1787 | 5095 | 0 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 165 | | 21 | | | | 5 | | | |
| Link Speed (mph) | | 30 | | | 35 | | | | 35 | | | |
| Link Distance (ft) | | 718 | | | 1535 | | | | 1665 | | | |
| Travel Time (s) | | 16.3 | | | 29.9 | | | | 32.4 | | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 1 | 247 | 172 | 47 | 304 | 94 | 2 | 156 | 768 | 42 | 3 | 109 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 248 | 172 | 47 | 398 | 0 | 0 | 158 | 810 | 0 | 0 | 112 |
| Turn Type | Perm | NA | Perm | Perm | NA | | Prot | Prot | NA | | Prot | Prot |
| Protected Phases | | 4 | | | 4 | | 1 | 1 | 2 | | 1 3 | 1 3 |
| Permitted Phases | 4 | | 4 | 4 | | | | | | | | |
| Detector Phase | 4 | 4 | 4 | 4 | 4 | | 1 | 1 | 2 | | 1 3 | 1 3 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 5.0 | | | |
| Minimum Split (s) | 43.1 | 43.1 | 43.1 | 43.1 | 43.1 | | 9.8 | 9.8 | 22.5 | | | |
| Total Split (s) | 54.0 | 54.0 | 54.0 | 54.0 | 54.0 | | 35.0 | 35.0 | 68.0 | | | |
| Total Split (%) | 28.4% | 28.4% | 28.4% | 28.4% | 28.4% | | 18.4% | 18.4% | 35.8% | | | |
| Maximum Green (s) | 46.9 | 46.9 | 46.9 | 46.9 | 46.9 | | 28.2 | 28.2 | 63.5 | | | |
| Yellow Time (s) | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | | 3.9 | 3.9 | 3.5 | | | |
| All-Red Time (s) | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | | 2.9 | 2.9 | 1.0 | | | |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | | |
| Total Lost Time (s) | | 7.1 | 7.1 | 7.1 | 7.1 | | | 6.8 | 4.5 | | | |
| Lead/Lag | Lag | Lag | Lag | Lag | Lag | | Lead | Lead | Lag | | | |
| Lead-Lag Optimize? | | | | | | | | | Yes | | | |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | 3.0 | | | |
| Recall Mode | None | None | None | None | None | | None | None | C-Max | | | |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | 29.0 | 29.0 | 29.0 | 29.0 | 29.0 | | | | 11.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 27.2 | 27.2 | 27.2 | 27.2 | | | 21.1 | 102.0 | | | 35.7 |
| Actuated g/C Ratio | | 0.14 | 0.14 | 0.14 | 0.14 | | | 0.11 | 0.54 | | | 0.19 |
| v/c Ratio | | 0.51 | 0.47 | 0.37 | 0.78 | | | 0.80 | 0.30 | | | 0.33 |
| Control Delay (s/veh) | | 78.2 | 13.9 | 80.3 | 84.8 | | | 109.1 | 26.2 | | | 38.4 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |

| Lane Group | SBT | SBR | Ø3 |
|---|---|---|---|
| Lane Configurations | | | |
| Traffic Volume (vph) | 952 | 32 | |
| Future Volume (vph) | 952 | 32 | |
| Ideal Flow (vphpl) | 1900 | 1900 | |
| Storage Length (ft) | | 0 | |
| Storage Lanes | | 0 | |
| Taper Length (ft) | | | |
| Lane Util. Factor | 0.95 | 0.95 | |
| Frt | 0.995 | | |
| Flt Protected | | | |
| Satd. Flow (prot) | 3556 | 0 | |
| Flt Permitted | | | |
| Satd. Flow (perm) | 3556 | 0 | |
| Right Turn on Red | | Yes | |
| Satd. Flow (RTOR) | 3 | | |
| Link Speed (mph) | 40 | | |
| Link Distance (ft) | 379 | | |
| Travel Time (s) | 6.5 | | |
| Peak Hour Factor | 0.98 | 0.98 | |
| Heavy Vehicles (%) | 1% | 1% | |
| Adj. Flow (vph) | 971 | 33 | |
| Shared Lane Traffic (%) | | | |
| Lane Group Flow (vph) | 1004 | 0 | |
| Turn Type | NA | | |
| Protected Phases | 2 3 | | 3 |
| Permitted Phases | | | |
| Detector Phase | 2 3 | | |
| Switch Phase | | | |
| Minimum Initial (s) | | | 3.0 |
| Minimum Split (s) | | | 9.8 |
| Total Split (s) | | | 33.0 |
| Total Split (%) | | | 17% |
| Maximum Green (s) | | | 26.2 |
| Yellow Time (s) | | | 3.9 |
| All-Red Time (s) | | | 2.9 |
| Lost Time Adjust (s) | | | |
| Total Lost Time (s) | | | |
| Lead/Lag | | | Lead |
| Lead-Lag Optimize? | | | |
| Vehicle Extension (s) | | | 2.0 |
| Recall Mode | | | None |
| Walk Time (s) | | | |
| Flash Don't Walk (s) | | | |
| Pedestrian Calls (#/hr) | | | |
| Act Effct Green (s) | 123.3 | | |
| Actuated g/C Ratio | 0.65 | | |
| v/c Ratio | 0.43 | | |
| Control Delay (s/veh) | 12.7 | | |
| Queue Delay | 0.2 | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 78.2 | 13.9 | 80.3 | 84.8 | | | 109.1 | 26.2 | | | 38.4 |
| LOS | | E | B | F | F | | | F | C | | | D |
| Approach Delay (s/veh) | | 51.9 | | | 84.3 | | | | 39.7 | | | |
| Approach LOS | | D | | | F | | | | D | | | |
| Queue Length 50th (ft) | | 153 | 8 | 54 | 243 | | | 196 | 199 | | | 88 |
| Queue Length 95th (ft) | | 195 | 82 | 99 | 294 | | | 275 | 285 | | | 161 |
| Internal Link Dist (ft) | | 638 | | | 1455 | | | | 1585 | | | |
| Turn Bay Length (ft) | | | 100 | 200 | | | | 250 | | | | |
| Base Capacity (vph) | | 840 | 518 | 220 | 867 | | | 265 | 2737 | | | 511 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 5 | | | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | | 0 |
| Reduced v/c Ratio | | 0.30 | 0.33 | 0.21 | 0.46 | | | 0.60 | 0.30 | | | 0.22 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBSB, Start of Yellow | | | |
| Natural Cycle: 90 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.80 | | | |
| Intersection Signal Delay (s/veh): 39.0 | | Intersection LOS: D | |
| Intersection Capacity Utilization 78.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 11: Niagara Falls Blvd & Eggert Rd





| Lane Group | SBT | SBR | Ø3 |
|---|---|---|---|
| Total Delay (s/veh) | 13.0 | | |
| LOS | B | | |
| Approach Delay (s/veh) | 15.5 | | |
| Approach LOS | B | | |
| Queue Length 50th (ft) | 361 | | |
| Queue Length 95th (ft) | 410 | | |
| Internal Link Dist (ft) | 299 | | |
| Turn Bay Length (ft) | | | |
| Base Capacity (vph) | 2527 | | |
| Starvation Cap Reductn | 693 | | |
| Spillback Cap Reductn | 0 | | |
| Storage Cap Reductn | 0 | | |
| Reduced v/c Ratio | 0.55 | | |

Intersection Summary




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 26 | 563 | 206 | 314 | 973 | 5 | 262 | 69 | 236 | 15 | 36 | 48 |
| Future Volume (vph) | 26 | 563 | 206 | 314 | 973 | 5 | 262 | 69 | 236 | 15 | 36 | 48 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 400 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.850 | | 0.999 | | | 0.884 | | | 0.914 | |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 5131 | 0 | 1787 | 1663 | 0 | 1787 | 1719 | 0 |
| Flt Permitted | 0.266 | | | 0.251 | | | 0.495 | | | 0.566 | | |
| Satd. Flow (perm) | 500 | 3574 | 1599 | 472 | 5131 | 0 | 931 | 1663 | 0 | 1065 | 1719 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 217 | | 1 | | | 162 | | | 51 | |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 25 | |
| Link Distance (ft) | | 1441 | | | 678 | | | 472 | | | 347 | |
| Travel Time (s) | | 21.8 | | | 10.3 | | | 9.2 | | | 9.5 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 27 | 593 | 217 | 331 | 1024 | 5 | 276 | 73 | 248 | 16 | 38 | 51 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 27 | 593 | 217 | 331 | 1029 | 0 | 276 | 321 | 0 | 16 | 89 | 0 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Permitted Phases | 2 | 2 | 2 | 6 | | | 8 | | | 4 | | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | | 5.0 | 10.0 | | 5.0 | 10.0 | |
| Minimum Split (s) | 10.0 | 27.6 | 27.6 | 10.0 | 27.6 | | 10.0 | 27.6 | | 10.0 | 27.6 | |
| Total Split (s) | 15.0 | 40.0 | 40.0 | 15.0 | 40.0 | | 15.0 | 20.0 | | 15.0 | 20.0 | |
| Total Split (%) | 16.7% | 44.4% | 44.4% | 16.7% | 44.4% | | 16.7% | 22.2% | | 16.7% | 22.2% | |
| Maximum Green (s) | 10.0 | 34.4 | 34.4 | 10.0 | 34.4 | | 10.0 | 14.4 | | 10.0 | 14.4 | |
| Yellow Time (s) | 3.0 | 3.6 | 3.6 | 3.0 | 3.6 | | 3.0 | 3.6 | | 3.0 | 3.6 | |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 5.0 | 5.6 | 5.6 | 5.0 | 5.6 | | 5.0 | 5.6 | | 5.0 | 5.6 | |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | | 3.0 | 4.0 | | 3.0 | 4.0 | |
| Minimum Gap (s) | 3.0 | 0.2 | 0.2 | 3.0 | 0.2 | | 3.0 | 0.2 | | 3.0 | 0.2 | |
| Time Before Reduce (s) | 0.0 | 7.0 | 7.0 | 0.0 | 7.0 | | 0.0 | 7.0 | | 0.0 | 7.0 | |
| Time To Reduce (s) | 0.0 | 0.5 | 0.5 | 0.0 | 0.5 | | 0.0 | 0.5 | | 0.0 | 0.5 | |
| Recall Mode | None | Min | Min | None | Min | | None | None | | None | None | |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | 15.0 | 15.0 | | 15.0 | | | 15.0 | | | 15.0 | |
| Pedestrian Calls (#/hr) | | 4 | 4 | | 2 | | | 4 | | | 2 | |
| Act Effct Green (s) | 24.4 | 17.4 | 17.4 | 32.5 | 28.4 | | 23.9 | 21.7 | | 15.9 | 12.3 | |
| Actuated g/C Ratio | 0.36 | 0.26 | 0.26 | 0.48 | 0.42 | | 0.35 | 0.32 | | 0.23 | 0.18 | |


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | 0.09 | 0.65 | 0.38 | 0.79 | 0.48 | | 0.60 | 0.50 | | 0.05 | 0.25 | |
| Control Delay (s/veh) | 12.3 | 27.2 | 5.8 | 30.4 | 17.9 | | 22.9 | 13.2 | | 15.3 | 15.7 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Delay (s/veh) | 12.3 | 27.2 | 5.8 | 30.4 | 17.9 | | 22.9 | 13.2 | | 15.3 | 15.7 | |
| LOS | B | C | A | C | B | | C | B | | B | B | |
| Approach Delay (s/veh) | | 21.2 | | | 21.0 | | | 17.7 | | | 15.6 | |
| Approach LOS | | C | | | C | | | B | | | B | |
| Queue Length 50th (ft) | 6 | 117 | 0 | 84 | 98 | | 83 | 46 | | 4 | 14 | |
| Queue Length 95th (ft) | 22 | 203 | 51 | #248 | 223 | | 163 | 153 | | 17 | 53 | |
| Internal Link Dist (ft) | | 1361 | | | 598 | | | 392 | | | 267 | |
| Turn Bay Length (ft) | 200 | | 200 | 400 | | | | | | | | |
| Base Capacity (vph) | 408 | 1897 | 950 | 429 | 2724 | | 462 | 672 | | 429 | 450 | |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.07 | 0.31 | 0.23 | 0.77 | 0.38 | | 0.60 | 0.48 | | 0.04 | 0.20 | |

**Intersection Summary**

Area Type: Other
Cycle Length: 90
Actuated Cycle Length: 67.8
Natural Cycle: 80
Control Type: Actuated-Uncoordinated
Maximum v/c Ratio: 0.79
Intersection Signal Delay (s/veh): 20.2 Intersection LOS: C
Intersection Capacity Utilization 67.6% ICU Level of Service C
Analysis Period (min) 15
# 95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 12: Alberta Dr/Driveway 5 & Maple Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 116 | 677 | 67 | 251 | 1035 | 291 | 103 | 395 | 146 | 300 | 396 | 177 |
| Future Volume (vph) | 116 | 677 | 67 | 251 | 1035 | 291 | 103 | 395 | 146 | 300 | 396 | 177 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | 430 | 350 | | 0 | 150 | | 150 | 500 | | 150 |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 1 | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.850 | | 0.967 | | | | 0.850 | | | 0.850 |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 4966 | 0 | 1787 | 1881 | 1599 | 1787 | 1881 | 1599 |
| Flt Permitted | 0.150 | | | 0.134 | | | 0.237 | | | 0.226 | | |
| Satd. Flow (perm) | 282 | 3574 | 1599 | 252 | 4966 | 0 | 446 | 1881 | 1599 | 425 | 1881 | 1599 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 227 | | 68 | | | | 209 | | | 209 |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 35 | |
| Link Distance (ft) | | 678 | | | 748 | | | 1712 | | | 1039 | |
| Travel Time (s) | | 10.3 | | | 11.3 | | | 33.4 | | | 20.2 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 120 | 698 | 69 | 259 | 1067 | 300 | 106 | 407 | 151 | 309 | 408 | 182 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 120 | 698 | 69 | 259 | 1367 | 0 | 106 | 407 | 151 | 309 | 408 | 182 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | Perm | pm+pt | NA | Perm |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Permitted Phases | 2 | 2 | 2 | 6 | | | 8 | | 8 | 4 | | 4 |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | 8 | 7 | 4 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | 10.0 |
| Minimum Split (s) | 12.0 | 29.0 | 29.0 | 12.0 | 29.0 | | 12.0 | 29.0 | 29.0 | 12.0 | 29.0 | 29.0 |
| Total Split (s) | 15.0 | 35.0 | 35.0 | 30.0 | 50.0 | | 15.0 | 40.0 | 40.0 | 15.0 | 40.0 | 40.0 |
| Total Split (%) | 12.5% | 29.2% | 29.2% | 25.0% | 41.7% | | 12.5% | 33.3% | 33.3% | 12.5% | 33.3% | 33.3% |
| Maximum Green (s) | 8.0 | 30.0 | 30.0 | 23.0 | 45.0 | | 8.0 | 33.0 | 33.0 | 8.0 | 33.0 | 33.0 |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| All-Red Time (s) | 4.0 | 2.0 | 2.0 | 4.0 | 2.0 | | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 7.0 | 5.0 | 5.0 | 7.0 | 5.0 | | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | 4.0 |
| Minimum Gap (s) | 3.0 | 0.2 | 0.2 | 3.0 | 0.2 | | 3.0 | 0.2 | 0.2 | 3.0 | 0.2 | 0.2 |
| Time Before Reduce (s) | 0.0 | 7.0 | 7.0 | 0.0 | 7.0 | | 0.0 | 7.0 | 7.0 | 0.0 | 7.0 | 7.0 |
| Time To Reduce (s) | 0.0 | 0.5 | 0.5 | 0.0 | 0.5 | | 0.0 | 0.5 | 0.5 | 0.0 | 0.5 | 0.5 |
| Recall Mode | None | Min | Min | None | Min | | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 15.0 | 15.0 | | 15.0 | | | 15.0 | 15.0 | | 15.0 | 15.0 |
| Pedestrian Calls (#/hr) | | 1 | 1 | | 0 | | | 1 | 1 | | 0 | 0 |
| Act Effct Green (s) | 32.5 | 26.6 | 26.6 | 46.4 | 34.8 | | 35.3 | 27.5 | 27.5 | 36.1 | 27.9 | 27.9 |
| Actuated g/C Ratio | 0.31 | 0.25 | 0.25 | 0.44 | 0.33 | | 0.34 | 0.26 | 0.26 | 0.34 | 0.27 | 0.27 |


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | 0.60 | 0.77 | 0.12 | 0.74 | 0.81 | | 0.43 | 0.83 | 0.26 | 1.23 | 0.82 | 0.31 |
| Control Delay (s/veh) | 35.1 | 44.1 | 0.4 | 36.2 | 34.6 | | 26.8 | 52.4 | 2.3 | 160.1 | 51.3 | 4.4 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 35.1 | 44.1 | 0.4 | 36.2 | 34.6 | | 26.8 | 52.4 | 2.3 | 160.1 | 51.3 | 4.4 |
| LOS | D | D | A | D | C | | C | D | A | F | D | A |
| Approach Delay (s/veh) | | 39.5 | | | 34.8 | | | 36.9 | | | 79.2 | |
| Approach LOS | | D | | | C | | | D | | | E | |
| Queue Length 50th (ft) | 47 | 235 | 0 | 113 | 298 | | 44 | 258 | 0 | ~175 | 259 | 0 |
| Queue Length 95th (ft) | #113 | 338 | 0 | 212 | 369 | | 91 | #437 | 15 | #386 | #439 | 38 |
| Internal Link Dist (ft) | | 598 | | | 668 | | | 1632 | | | 959 | |
| Turn Bay Length (ft) | 250 | | 430 | 350 | | | 150 | | 150 | 500 | | 150 |
| Base Capacity (vph) | 204 | 1039 | 626 | 457 | 2205 | | 255 | 601 | 654 | 251 | 601 | 654 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.59 | 0.67 | 0.11 | 0.57 | 0.62 | | 0.42 | 0.68 | 0.23 | 1.23 | 0.68 | 0.28 |

**Intersection Summary**

Area Type: Other
Cycle Length: 120
Actuated Cycle Length: 104.9
Natural Cycle: 85
Control Type: Actuated-Uncoordinated
Maximum v/c Ratio: 1.23
Intersection Signal Delay (s/veh): 46.0 Intersection LOS: D
Intersection Capacity Utilization 92.0% ICU Level of Service F
Analysis Period (min) 15
~ Volume exceeds capacity, queue is theoretically infinite.
Queue shown is maximum after two cycles.
# 95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 13: Bailey Ave & Maple Rd







| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Volume (vph) | 111 | 976 | 1493 | 245 | 239 | 107 |
| Future Volume (vph) | 111 | 976 | 1493 | 245 | 239 | 107 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | | 100 | 100 | 0 |
| Storage Lanes | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 0.91 | 0.91 | 1.00 | 1.00 |
| Frt | | | 0.979 | | | 0.850 |
| Flt Protected | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1787 | 3574 | 5028 | 0 | 1787 | 1599 |
| Flt Permitted | 0.085 | | | | 0.950 | |
| Satd. Flow (perm) | 160 | 3574 | 5028 | 0 | 1787 | 1599 |
| Right Turn on Red | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | 50 | | | 111 |
| Link Speed (mph) | | 35 | 45 | | 30 | |
| Link Distance (ft) | | 748 | 466 | | 1444 | |
| Travel Time (s) | | 14.6 | 7.1 | | 32.8 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 116 | 1017 | 1555 | 255 | 249 | 111 |
| Shared Lane Traffic (%) | | | | | | |
| Lane Group Flow (vph) | 116 | 1017 | 1810 | 0 | 249 | 111 |
| Turn Type | pm+pt | NA | NA | | Prot | Prot |
| Protected Phases | 5 | 2 | 6 | | 4 | 4 |
| Permitted Phases | 2 | | | | | |
| Detector Phase | 5 | 2 | 6 | | 4 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 5.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| Minimum Split (s) | 9.5 | 27.0 | 27.0 | | 27.0 | 27.0 |
| Total Split (s) | 15.0 | 95.0 | 80.0 | | 25.0 | 25.0 |
| Total Split (%) | 12.5% | 79.2% | 66.7% | | 20.8% | 20.8% |
| Maximum Green (s) | 10.5 | 90.0 | 75.0 | | 20.0 | 20.0 |
| Yellow Time (s) | 3.5 | 3.0 | 3.0 | | 3.0 | 3.0 |
| All-Red Time (s) | 1.0 | 2.0 | 2.0 | | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 4.5 | 5.0 | 5.0 | | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | | | |
| Lead-Lag Optimize? | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | None | Min | Min | | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 11.0 | 11.0 | | 11.0 | 11.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 0 | 0 |
| Act Effct Green (s) | 56.8 | 56.3 | 42.4 | | 16.8 | 16.8 |
| Actuated g/C Ratio | 0.68 | 0.68 | 0.51 | | 0.20 | 0.20 |
| v/c Ratio | 0.40 | 0.42 | 0.70 | | 0.69 | 0.27 |
| Control Delay (s/veh) | 11.7 | 6.8 | 16.8 | | 44.2 | 8.9 |
| Queue Delay | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 11.7 | 6.8 | 16.9 | | 44.2 | 8.9 |
| LOS | B | A | B | | D | A |
| Approach Delay (s/veh) | | 7.3 | 16.9 | | 33.3 | |
| Approach LOS | | A | B | | C | |
| Queue Length 50th (ft) | 19 | 114 | 253 | | 121 | 0 |
| Queue Length 95th (ft) | 56 | 157 | 320 | | #259 | 46 |
| Internal Link Dist (ft) | | 668 | 386 | | 1364 | |
| Turn Bay Length (ft) | 250 | | | | 100 | |
| Base Capacity (vph) | 320 | 3461 | 4457 | | 441 | 478 |
| Starvation Cap Reductn | 0 | 0 | 487 | | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | 0.36 | 0.29 | 0.46 | | 0.56 | 0.23 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 83.4 | | | |
| Natural Cycle: 65 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.70 | | | |
| Intersection Signal Delay (s/veh): 15.4 | | Intersection LOS: B | |
| Intersection Capacity Utilization 65.8% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 14: Maple Rd & Bowmart Parkway







| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 1152 | 18 | 19 | 1746 | 0 | 32 | 0 | 33 | 27 | 0 | 5 |
| Future Volume (vph) | 0 | 1152 | 18 | 19 | 1746 | 0 | 32 | 0 | 33 | 27 | 0 | 5 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 150 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | 0 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.998 | | | | | | 0.932 | | | 0.850 | |
| Flt Protected | | | | 0.950 | | | | 0.976 | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3567 | 0 | 1787 | 3574 | 0 | 0 | 1711 | 0 | 1787 | 1599 | 0 |
| Flt Permitted | | | | 0.950 | | | | 0.841 | | 0.903 | | |
| Satd. Flow (perm) | 0 | 3567 | 0 | 1787 | 3574 | 0 | 0 | 1474 | 0 | 1699 | 1599 | 0 |
| Right Turn on Red | | | No | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | | | | 64 | | | 64 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 10 | |
| Link Distance (ft) | | 466 | | | 1563 | | | 418 | | | 259 | |
| Travel Time (s) | | 9.1 | | | 30.4 | | | 9.5 | | | 17.7 | |
| Peak Hour Factor | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 0 | 1239 | 19 | 20 | 1877 | 0 | 34 | 0 | 35 | 29 | 0 | 5 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 1258 | 0 | 20 | 1877 | 0 | 0 | 69 | 0 | 29 | 5 | 0 |
| Turn Type | | NA | | Prot | NA | | Perm | NA | | Perm | NA | |
| Protected Phases | | 2 | | 1 | 6 | | | 4 | | | 8 | |
| Permitted Phases | | | | | | | 4 | | | 8 | | |
| Detector Phase | | 2 | | 1 | 6 | | 4 | 4 | | 8 | 8 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | 5.0 | | 10.0 | 5.0 | | 5.0 | 5.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | | 27.0 | | 27.0 | 27.0 | | 27.0 | 27.0 | | 27.0 | 27.0 | |
| Total Split (s) | | 60.0 | | 20.0 | 80.0 | | 40.0 | 40.0 | | 40.0 | 40.0 | |
| Total Split (%) | | 50.0% | | 16.7% | 66.7% | | 33.3% | 33.3% | | 33.3% | 33.3% | |
| Maximum Green (s) | | 55.0 | | 15.0 | 75.0 | | 35.0 | 35.0 | | 35.0 | 35.0 | |
| Yellow Time (s) | | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | 5.0 | 5.0 | | | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | Lag | | Lead | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Gap (s) | | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | |
| Time Before Reduce (s) | | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Time To Reduce (s) | | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | |
| Recall Mode | | Min | | None | Min | | None | None | | None | None | |
| Walk Time (s) | | | | | 7.0 | | | | | | | |
| Flash Don't Walk (s) | | | | | 30.0 | | | | | | | |
| Pedestrian Calls (#/hr) | | | | | 0 | | | | | | | |
| Act Effct Green (s) | | 40.0 | | 10.6 | 45.3 | | | 9.6 | | 10.8 | 10.8 | |
| Actuated g/C Ratio | | 0.67 | | 0.18 | 0.76 | | | 0.16 | | 0.18 | 0.18 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | | 0.53 | | 0.06 | 0.70 | | | 0.24 | | 0.10 | 0.01 | |
| Control Delay (s/veh) | | 10.3 | | 25.7 | 7.6 | | | 11.0 | | 25.7 | 0.0 | |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | |
| Total Delay (s/veh) | | 10.3 | | 25.7 | 7.6 | | | 11.0 | | 25.7 | 0.0 | |
| LOS | | B | | C | A | | | B | | C | A | |
| Approach Delay (s/veh) | | 10.3 | | | 7.8 | | | 11.0 | | | 22.0 | |
| Approach LOS | | B | | | A | | | B | | | C | |
| Queue Length 50th (ft) | | 99 | | 6 | 203 | | | 2 | | 10 | 0 | |
| Queue Length 95th (ft) | | 285 | | 26 | 292 | | | 34 | | 33 | 0 | |
| Internal Link Dist (ft) | | 386 | | | 1483 | | | 338 | | | 179 | |
| Turn Bay Length (ft) | | | | 150 | | | | | | | | |
| Base Capacity (vph) | | 3093 | | 474 | 3574 | | | 938 | | 1053 | 1015 | |
| Starvation Cap Reductn | | 344 | | 0 | 0 | | | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.46 | | 0.04 | 0.53 | | | 0.07 | | 0.03 | 0.00 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 60 | | | |
| Natural Cycle: 85 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.70 | | | |
| Intersection Signal Delay (s/veh): 9.0 | | Intersection LOS: A | |
| Intersection Capacity Utilization 67.1% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 15: Hillcrest Dr/Driveway 6 & Maple Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 375 | 740 | 91 | 209 | 987 | 260 | 120 | 382 | 154 | 231 | 468 | 620 |
| Future Volume (vph) | 375 | 740 | 91 | 209 | 987 | 260 | 120 | 382 | 154 | 231 | 468 | 620 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 100 | | 0 | 150 | | 150 | 200 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 1 | | 1 | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | 0.97 | 1.00 | | | | | | | | 0.99 |
| Frt | | | 0.850 | | | 0.850 | | | 0.850 | | | 0.850 |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 3574 | 1599 | 1787 | 1881 | 1599 | 1787 | 1881 | 1599 |
| Flt Permitted | 0.083 | | | 0.324 | | | 0.132 | | | 0.160 | | |
| Satd. Flow (perm) | 156 | 3574 | 1556 | 608 | 3574 | 1599 | 248 | 1881 | 1599 | 301 | 1881 | 1575 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 113 | | | 161 | | | 157 | | | 438 |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 45 | |
| Link Distance (ft) | | 1563 | | | 492 | | | 510 | | | 929 | |
| Travel Time (s) | | 23.7 | | | 7.5 | | | 9.9 | | | 14.1 | |
| Confl. Peds. (#/hr) | | | 3 | 3 | | | 2 | | | | | 2 |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 391 | 771 | 95 | 218 | 1028 | 271 | 125 | 398 | 160 | 241 | 488 | 646 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 391 | 771 | 95 | 218 | 1028 | 271 | 125 | 398 | 160 | 241 | 488 | 646 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm |
| Protected Phases | 1 | 6 | | 5 | 2 | | 7 | 4 | | 3 | 8 | |
| Permitted Phases | 6 | | 6 | 2 | | 2 | 4 | | 4 | 8 | | 8 |
| Detector Phase | 1 | 6 | 6 | 5 | 2 | 2 | 7 | 4 | 4 | 3 | 8 | 8 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 | 10.0 | 3.0 | 6.0 | 6.0 | 3.0 | 6.0 | 6.0 |
| Minimum Split (s) | 10.2 | 39.5 | 39.5 | 9.8 | 38.8 | 38.8 | 10.2 | 45.3 | 45.3 | 9.6 | 45.3 | 45.3 |
| Total Split (s) | 45.0 | 63.0 | 63.0 | 25.0 | 43.0 | 43.0 | 25.0 | 47.0 | 47.0 | 25.0 | 47.0 | 47.0 |
| Total Split (%) | 28.1% | 39.4% | 39.4% | 15.6% | 26.9% | 26.9% | 15.6% | 29.4% | 29.4% | 15.6% | 29.4% | 29.4% |
| Maximum Green (s) | 38.5 | 56.5 | 56.5 | 18.6 | 36.6 | 36.6 | 18.5 | 40.5 | 40.5 | 18.4 | 40.4 | 40.4 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 3.6 | 3.6 | 3.6 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 2.2 | 2.2 | 2.2 | 2.1 | 2.1 | 2.1 | 2.9 | 2.9 | 2.9 | 2.3 | 2.3 | 2.3 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 6.5 | 6.5 | 6.5 | 6.4 | 6.4 | 6.4 | 6.5 | 6.5 | 6.5 | 6.6 | 6.6 | 6.6 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 |
| Recall Mode | None | C-Max | C-Max | None | C-Max | C-Max | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 26.0 | 26.0 | | 25.0 | 25.0 | | 26.0 | 26.0 | | 26.0 | 26.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 3 | 3 | | 2 | 2 | | 2 | 2 |
| Act Effct Green (s) | 81.5 | 60.1 | 60.1 | 56.9 | 41.8 | 41.8 | 53.6 | 41.4 | 41.4 | 63.9 | 46.7 | 46.7 |
| Actuated g/C Ratio | 0.51 | 0.38 | 0.38 | 0.36 | 0.26 | 0.26 | 0.34 | 0.26 | 0.26 | 0.40 | 0.29 | 0.29 |
| v/c Ratio | 0.94 | 0.57 | 0.15 | 0.67 | 1.10 | 0.51 | 0.63 | 0.82 | 0.30 | 0.85 | 0.89 | 0.84 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | 77.7 | 42.4 | 3.9 | 42.8 | 108.2 | 16.5 | 45.3 | 70.6 | 8.3 | 60.8 | 73.2 | 27.6 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 77.7 | 42.4 | 3.9 | 42.8 | 108.2 | 16.5 | 45.3 | 70.6 | 8.3 | 60.8 | 73.2 | 27.6 |
| LOS | E | D | A | D | F | B | D | E | A | E | E | C |
| Approach Delay (s/veh) | | 50.4 | | | 82.4 | | | 51.4 | | | 49.6 | |
| Approach LOS | | D | | | F | | | D | | | D | |
| Queue Length 50th (ft) | 349 | 338 | 0 | 87 | ~669 | 64 | 83 | 398 | 2 | 171 | 488 | 231 |
| Queue Length 95th (ft) | #507 | 421 | 29 | 170 | #862 | 145 | 132 | #566 | 63 | #313 | #757 | #493 |
| Internal Link Dist (ft) | | 1483 | | | 412 | | | 430 | | | 849 | |
| Turn Bay Length (ft) | 200 | | 200 | 100 | | | 150 | | 150 | 200 | | |
| Base Capacity (vph) | 471 | 1341 | 654 | 366 | 934 | 536 | 270 | 486 | 530 | 290 | 549 | 769 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.83 | 0.57 | 0.15 | 0.60 | 1.10 | 0.51 | 0.46 | 0.82 | 0.30 | 0.83 | 0.89 | 0.84 |

| Intersection Summary | |
|---|---|
| Area Type: | Other |
| Cycle Length: 160 | |
| Actuated Cycle Length: 160 | |
| Offset: 117 (73%), Referenced to phase 2:WBTL and 6:EBTL, Start of Yellow | |
| Natural Cycle: 135 | |
| Control Type: Actuated-Coordinated | |
| Maximum v/c Ratio: 1.10 | |
| Intersection Signal Delay (s/veh): 60.4 | Intersection LOS: E |
| Intersection Capacity Utilization 102.6% | ICU Level of Service G |
| Analysis Period (min) 15 | |
| ~ Volume exceeds capacity, queue is theoretically infinite. | |
| Queue shown is maximum after two cycles. | |
| # 95th percentile volume exceeds capacity, queue may be longer. | |
| Queue shown is maximum after two cycles. | |

Splits and Phases: 16: Sweet Home Rd & Maple Rd






| Lane Group | EBU | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | |
| Traffic Volume (vph) | 2 | 44 | 826 | 954 | 236 | 37 | 151 |
| Future Volume (vph) | 2 | 44 | 826 | 954 | 236 | 37 | 151 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 100 | | | 115 | 0 | 0 |
| Storage Lanes | | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | |
| Lane Util. Factor | 0.95 | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 |
| Frt | | | | | 0.850 | | 0.850 |
| Flt Protected | | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1787 | 3574 | 3574 | 1599 | 1787 | 1599 |
| Flt Permitted | | 0.281 | | | | 0.950 | |
| Satd. Flow (perm) | 0 | 529 | 3574 | 3574 | 1599 | 1787 | 1599 |
| Right Turn on Red | | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | | | | | 115 |
| Link Speed (mph) | | | 45 | 45 | | 45 | |
| Link Distance (ft) | | | 3286 | 644 | | 265 | |
| Travel Time (s) | | | 49.8 | 9.8 | | 4.0 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 2 | 46 | 860 | 994 | 246 | 39 | 157 |
| Shared Lane Traffic (%) | | | | | | | |
| Lane Group Flow (vph) | 0 | 48 | 860 | 994 | 246 | 39 | 157 |
| Turn Type | Perm | Perm | NA | NA | custom | Prot | Perm |
| Protected Phases | | | 2 | 6 | 8 6 | 8 | |
| Permitted Phases | 2 | 2 | | | 8 | | 8 |
| Detector Phase | 2 | 2 | 2 | 6 | 8 6 | 8 | 8 |
| Switch Phase | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | 10.0 | | 6.0 | 6.0 |
| Minimum Split (s) | 35.3 | 35.3 | 35.3 | 35.3 | | 13.9 | 13.9 |
| Total Split (s) | 100.0 | 100.0 | 100.0 | 100.0 | | 60.0 | 60.0 |
| Total Split (%) | 62.5% | 62.5% | 62.5% | 62.5% | | 37.5% | 37.5% |
| Maximum Green (s) | 93.7 | 93.7 | 93.7 | 93.7 | | 53.8 | 53.8 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | | 1.9 | 1.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.3 | 6.3 | 6.3 | | 6.2 | 6.2 |
| Lead/Lag | | | | | | | |
| Lead-Lag Optimize? | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | C-Min | C-Min | C-Min | C-Min | | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | | | |
| Flash Don't Walk (s) | 22.0 | 22.0 | 22.0 | 22.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | | | |
| Act Effct Green (s) | | 136.1 | 136.1 | 136.1 | 160.0 | 11.4 | 11.4 |
| Actuated g/C Ratio | | 0.85 | 0.85 | 0.85 | 1.00 | 0.07 | 0.07 |
| v/c Ratio | | 0.11 | 0.28 | 0.33 | 0.15 | 0.31 | 0.71 |
| Control Delay (s/veh) | | 1.4 | 1.1 | 2.7 | 0.2 | 74.9 | 39.7 |
| Queue Delay | | 0.0 | 0.0 | 0.2 | 0.0 | 0.0 | 0.0 |

| Lane Group | EBU | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 1.4 | 1.1 | 3.0 | 0.2 | 74.9 | 39.7 |
| LOS | | A | A | A | A | E | D |
| Approach Delay (s/veh) | | | 1.1 | 2.4 | | 46.7 | |
| Approach LOS | | | A | A | | D | |
| Queue Length 50th (ft) | | 2 | 20 | 79 | 0 | 40 | 43 |
| Queue Length 95th (ft) | | m6 | 37 | 133 | 0 | 78 | 121 |
| Internal Link Dist (ft) | | | 3206 | 564 | | 185 | |
| Turn Bay Length (ft) | | 100 | | | 115 | | |
| Base Capacity (vph) | | 450 | 3040 | 3040 | 1599 | 600 | 613 |
| Starvation Cap Reductn | | 0 | 0 | 1135 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.11 | 0.28 | 0.52 | 0.15 | 0.07 | 0.26 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 121 (76%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.71 | | | |
| Intersection Signal Delay (s/veh): 5.6 | | Intersection LOS: A | |
| Intersection Capacity Utilization 58.0% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 17: Maple Rd & Millersprt Hwy SB Rmps




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 83 | 909 | 0 | 0 | 1082 | 15 | 56 | 2 | 560 | 0 | 0 | 0 |
| Future Volume (vph) | 83 | 909 | 0 | 0 | 1082 | 15 | 56 | 2 | 560 | 0 | 0 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 0 | 1 | | 0 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | | | 0.998 | | | 0.851 | | | | |
| Flt Protected | 0.950 | | | | | | 0.950 | | | | | |
| Satd. Flow (prot) | 1787 | 3574 | 0 | 0 | 3567 | 0 | 1787 | 1601 | 0 | 0 | 0 | 0 |
| Flt Permitted | 0.161 | | | | | | 0.950 | | | | | |
| Satd. Flow (perm) | 303 | 3574 | 0 | 0 | 3567 | 0 | 1787 | 1601 | 0 | 0 | 0 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | 1 | | | 95 | | | | |
| Link Speed (mph) | | 45 | | | 45 | | | 45 | | | 45 | |
| Link Distance (ft) | | 644 | | | 547 | | | 1142 | | | 667 | |
| Travel Time (s) | | 9.8 | | | 8.3 | | | 17.3 | | | 10.1 | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 88 | 967 | 0 | 0 | 1151 | 16 | 60 | 2 | 596 | 0 | 0 | 0 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 88 | 967 | 0 | 0 | 1167 | 0 | 60 | 598 | 0 | 0 | 0 | 0 |
| Turn Type | Perm | NA | | | NA | | Perm | NA | | | | |
| Protected Phases | | 2 | | | 6 | | | 4 | | | | |
| Permitted Phases | 2 | | | | | | 4 | | | | | |
| Detector Phase | 2 | 2 | | | 6 | | 4 | 4 | | | | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 20.0 | 20.0 | | | 20.0 | | 6.0 | 6.0 | | | | |
| Minimum Split (s) | 29.0 | 29.0 | | | 29.0 | | 23.0 | 23.0 | | | | |
| Total Split (s) | 90.0 | 90.0 | | | 90.0 | | 70.0 | 70.0 | | | | |
| Total Split (%) | 56.3% | 56.3% | | | 56.3% | | 43.8% | 43.8% | | | | |
| Maximum Green (s) | 84.0 | 84.0 | | | 84.0 | | 63.8 | 63.8 | | | | |
| Yellow Time (s) | 4.3 | 4.3 | | | 4.3 | | 4.3 | 4.3 | | | | |
| All-Red Time (s) | 1.7 | 1.7 | | | 1.7 | | 1.9 | 1.9 | | | | |
| Lost Time Adjust (s) | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | | | | |
| Total Lost Time (s) | 6.0 | 6.0 | | | 6.0 | | 6.2 | 6.2 | | | | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | | 3.0 | | 3.0 | 3.0 | | | | |
| Recall Mode | C-Max | C-Max | | | C-Max | | None | None | | | | |
| Walk Time (s) | 7.0 | 7.0 | | | 7.0 | | | | | | | |
| Flash Don't Walk (s) | 16.0 | 16.0 | | | 16.0 | | | | | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | 0 | | | | | | | |
| Act Effct Green (s) | 89.9 | 89.9 | | | 89.9 | | 57.9 | 57.9 | | | | |
| Actuated g/C Ratio | 0.56 | 0.56 | | | 0.56 | | 0.36 | 0.36 | | | | |
| v/c Ratio | 0.52 | 0.48 | | | 0.58 | | 0.09 | 0.93 | | | | |
| Control Delay (s/veh) | 36.1 | 20.8 | | | 25.2 | | 32.1 | 63.4 | | | | |
| Queue Delay | 0.0 | 0.5 | | | 0.0 | | 0.0 | 0.0 | | | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 36.1 | 21.3 | | | 25.2 | | 32.1 | 63.4 | | | | |
| LOS | D | C | | | C | | C | E | | | | |
| Approach Delay (s/veh) | | 22.6 | | | 25.2 | | | 60.5 | | | | |
| Approach LOS | | C | | | C | | | E | | | | |
| Queue Length 50th (ft) | 71 | 401 | | | 425 | | 40 | 512 | | | | |
| Queue Length 95th (ft) | 120 | 467 | | | 517 | | 72 | #722 | | | | |
| Internal Link Dist (ft) | | 564 | | | 467 | | | 1062 | | | 587 | |
| Turn Bay Length (ft) | 150 | | | | | | | | | | | |
| Base Capacity (vph) | 170 | 2008 | | | 2004 | | 712 | 695 | | | | |
| Starvation Cap Reductn | 0 | 583 | | | 0 | | 0 | 0 | | | | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Storage Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Reduced v/c Ratio | 0.52 | 0.68 | | | 0.58 | | 0.08 | 0.86 | | | | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 80 (50%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.93 | | | |
| Intersection Signal Delay (s/veh): 32.3 | | Intersection LOS: C | |
| Intersection Capacity Utilization 97.0% | | ICU Level of Service F | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 18: Millersprt Hwy NB Rmps & Maple Rd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT | NWR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 40 | 882 | 181 | 0 | 1089 | 116 | 108 | 206 | 37 | 187 | 240 | 6 |
| Future Volume (vph) | 40 | 882 | 181 | 0 | 1089 | 116 | 108 | 206 | 37 | 187 | 240 | 6 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 450 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Frt | | | 0.850 | | 0.986 | | | 0.984 | | | 0.998 | |
| Flt Protected | 0.950 | | | | | | | 0.985 | | | 0.979 | |
| Satd. Flow (prot) | 1787 | 5136 | 1599 | 0 | 5064 | 0 | 0 | 3464 | 0 | 0 | 3492 | 0 |
| Flt Permitted | 0.151 | | | | | | | 0.985 | | | 0.979 | |
| Satd. Flow (perm) | 284 | 5136 | 1599 | 0 | 5064 | 0 | 0 | 3464 | 0 | 0 | 3492 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 187 | | 22 | | | 11 | | | 1 | |
| Link Speed (mph) | | 40 | | | 40 | | | 30 | | | 30 | |
| Link Distance (ft) | | 1892 | | | 623 | | | 1712 | | | 718 | |
| Travel Time (s) | | 32.3 | | | 10.6 | | | 38.9 | | | 16.3 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 41 | 909 | 187 | 0 | 1123 | 120 | 111 | 212 | 38 | 193 | 247 | 6 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 41 | 909 | 187 | 0 | 1243 | 0 | 0 | 361 | 0 | 0 | 446 | 0 |
| Turn Type | Perm | NA | Perm | | NA | | Split | NA | | Split | NA | |
| Protected Phases | | 1 | | | 1 | | 3 | 3 | | 4 | 4 | |
| Permitted Phases | 1 | | 1 | | | | | | | | | |
| Detector Phase | 1 | 1 | 1 | | 1 | | 3 | 3 | | 4 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 15.0 | 15.0 | 15.0 | | 15.0 | | 6.0 | 6.0 | | 6.0 | 6.0 | |
| Minimum Split (s) | 50.0 | 50.0 | 50.0 | | 50.0 | | 70.9 | 70.9 | | 70.9 | 70.9 | |
| Total Split (s) | 45.0 | 45.0 | 45.0 | | 45.0 | | 25.0 | 25.0 | | 25.0 | 25.0 | |
| Total Split (%) | 47.4% | 47.4% | 47.4% | | 47.4% | | 26.3% | 26.3% | | 26.3% | 26.3% | |
| Maximum Green (s) | 37.0 | 37.0 | 37.0 | | 37.0 | | 16.1 | 16.1 | | 16.1 | 16.1 | |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.6 | 3.6 | | 3.6 | 3.6 | |
| All-Red Time (s) | 4.0 | 4.0 | 4.0 | | 4.0 | | 5.3 | 5.3 | | 5.3 | 5.3 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Lost Time (s) | 8.0 | 8.0 | 8.0 | | 8.0 | | | 8.9 | | | 8.9 | |
| Lead/Lag | | | | | | | Lead | Lead | | Lag | Lag | |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | | Yes | Yes | |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.5 | 3.5 | | 3.5 | 3.5 | |
| Recall Mode | Min | Min | Min | | Min | | None | None | | None | None | |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | | 7.0 | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | | 35.0 | | | | | 55.0 | 55.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | | 0 | | | | | 0 | 0 | |
| Act Effct Green (s) | 37.0 | 37.0 | 37.0 | | 37.0 | | | 14.2 | | | 15.3 | |
| Actuated g/C Ratio | 0.40 | 0.40 | 0.40 | | 0.40 | | | 0.15 | | | 0.17 | |
| v/c Ratio | 0.36 | 0.44 | 0.25 | | 0.61 | | | 0.66 | | | 0.77 | |
| Control Delay (s/veh) | 32.0 | 21.4 | 3.9 | | 23.4 | | | 42.2 | | | 47.1 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT | NWR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 32.0 | 21.4 | 3.9 | | 23.4 | | | 42.2 | | | 47.1 | |
| LOS | C | C | A | | C | | | D | | | D | |
| Approach Delay (s/veh) | | 18.9 | | | 23.4 | | | 42.2 | | | 47.1 | |
| Approach LOS | | B | | | C | | | D | | | D | |
| Queue Length 50th (ft) | 17 | 143 | 0 | | 209 | | | 103 | | | 134 | |
| Queue Length 95th (ft) | 52 | 183 | 41 | | 261 | | | 151 | | | #191 | |
| Internal Link Dist (ft) | | 1812 | | | 543 | | | 1632 | | | 638 | |
| Turn Bay Length (ft) | 200 | | 450 | | | | | | | | | |
| Base Capacity (vph) | 113 | 2058 | 752 | | 2043 | | | 613 | | | 609 | |
| Starvation Cap Reductn | 0 | 0 | 0 | | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | 0 | 0 | 0 | | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | 0 | 0 | 0 | | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | 0.36 | 0.44 | 0.25 | | 0.61 | | | 0.59 | | | 0.73 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 95 | | | |
| Actuated Cycle Length: 92.4 | | | |
| Natural Cycle: 195 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.77 | | | |
| Intersection Signal Delay (s/veh): 27.2 | | Intersection LOS: C | |
| Intersection Capacity Utilization 77.0% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 19: Eggert Rd & Sheridan Dr




| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 25 | 148 | 691 | 43 | 8 | 55 | 1009 | 190 | 36 | 66 | 18 | 221 |
| Future Volume (vph) | 25 | 148 | 691 | 43 | 8 | 55 | 1009 | 190 | 36 | 66 | 18 | 221 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 235 | | 0 | | 240 | | 0 | 0 | | 100 | 0 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 0 | | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.991 | | | | 0.976 | | | 0.977 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | | 0.985 | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5089 | 0 | 0 | 1787 | 5012 | 0 | 0 | 3440 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | | 0.762 | | 0.453 |
| Satd. Flow (perm) | 0 | 1787 | 5089 | 0 | 0 | 1787 | 5012 | 0 | 0 | 2661 | 0 | 852 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 9 | | | | 28 | | | 11 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1468 | | | | 969 | | | 165 | | |
| Travel Time (s) | | | 25.0 | | | | 16.5 | | | 3.8 | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 26 | 154 | 720 | 45 | 8 | 57 | 1051 | 198 | 38 | 69 | 19 | 230 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 180 | 765 | 0 | 0 | 65 | 1249 | 0 | 0 | 126 | 0 | 230 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 6.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 10.0 | 10.0 | 29.2 | | 10.0 | 10.0 | 43.2 | | 22.5 | 22.5 | | 11.0 |
| Total Split (s) | 39.0 | 39.0 | 87.0 | | 20.0 | 20.0 | 68.0 | | 33.0 | 33.0 | | 20.0 |
| Total Split (%) | 24.4% | 24.4% | 54.4% | | 12.5% | 12.5% | 42.5% | | 20.6% | 20.6% | | 12.5% |
| Maximum Green (s) | 32.8 | 32.8 | 80.8 | | 13.8 | 13.8 | 61.8 | | 26.1 | 26.1 | | 14.0 |
| Yellow Time (s) | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | | 3.2 |
| All-Red Time (s) | 2.6 | 2.6 | 2.6 | | 2.6 | 2.6 | 2.6 | | 3.3 | 3.3 | | 2.8 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | | 6.9 | | 6.0 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | Min | Min | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | | | |
| Flash Don't Walk (s) | | | 16.0 | | | | 15.0 | | | | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | | | |
| Act Effct Green (s) | | 21.4 | 90.8 | | | 11.2 | 77.9 | | | 12.4 | | 42.3 |
| Actuated g/C Ratio | | 0.13 | 0.57 | | | 0.07 | 0.49 | | | 0.08 | | 0.26 |
| v/c Ratio | | 0.76 | 0.26 | | | 0.52 | 0.51 | | | 0.58 | | 0.64 |
| Control Delay (s/veh) | | 85.7 | 19.4 | | | 101.7 | 13.1 | | | 75.4 | | 57.4 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 105 | 223 |
| Future Volume (vph) | 105 | 223 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.898 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1689 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1689 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 67 | |
| Link Speed (mph) | 35 | |
| Link Distance (ft) | 3326 | |
| Travel Time (s) | 64.8 | |
| Peak Hour Factor | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 109 | 232 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 341 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 43.9 | |
| Total Split (s) | 53.0 | |
| Total Split (%) | 33.1% | |
| Maximum Green (s) | 46.1 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.9 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 27.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 41.4 | |
| Actuated g/C Ratio | 0.26 | |
| v/c Ratio | 0.70 | |
| Control Delay (s/veh) | 50.2 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 85.7 | 19.4 | | | 101.7 | 13.1 | | | 75.4 | | 57.4 |
| LOS | | F | B | | | F | B | | | E | | E |
| Approach Delay (s/veh) | | | 32.0 | | | | 17.5 | | | 75.4 | | |
| Approach LOS | | | C | | | | B | | | E | | |
| Queue Length 50th (ft) | | 184 | 152 | | | 71 | 109 | | | 62 | | 202 |
| Queue Length 95th (ft) | | 261 | 204 | | | m124 | 123 | | | 98 | | 279 |
| Internal Link Dist (ft) | | | 1388 | | | | 889 | | | 85 | | |
| Turn Bay Length (ft) | | 235 | | | | 240 | | | | | | |
| Base Capacity (vph) | | 366 | 2911 | | | 158 | 2455 | | | 443 | | 359 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Reduced v/c Ratio | | 0.49 | 0.26 | | | 0.41 | 0.51 | | | 0.28 | | 0.64 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 28 (18%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.76 | | | |
| Intersection Signal Delay (s/veh): 31.5 | | Intersection LOS: C | |
| Intersection Capacity Utilization 79.4% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 20: Alberta Dr & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 50.2 | |
| LOS | D | |
| Approach Delay (s/veh) | 53.1 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 262 | |
| Queue Length 95th (ft) | 366 | |
| Internal Link Dist (ft) | 3246 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 539 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.63 | |

| Intersection Summary |
|---|


| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 20 | 127 | 770 | 77 | 9 | 136 | 978 | 130 | 117 | 407 | 102 | 142 |
| Future Volume (vph) | 20 | 127 | 770 | 77 | 9 | 136 | 978 | 130 | 117 | 407 | 102 | 142 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 230 | | 0 | | 270 | | 0 | 190 | | 0 | 240 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.986 | | | | 0.982 | | | 0.970 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5064 | 0 | 0 | 1787 | 5043 | 0 | 1787 | 3467 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.250 | | | 0.182 |
| Satd. Flow (perm) | 0 | 1787 | 5064 | 0 | 0 | 1787 | 5043 | 0 | 470 | 3467 | 0 | 342 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 10 | | | | 16 | | | 18 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 969 | | | | 1628 | | | 537 | | |
| Travel Time (s) | | | 16.5 | | | | 27.8 | | | 12.2 | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 20 | 130 | 786 | 79 | 9 | 139 | 998 | 133 | 119 | 415 | 104 | 145 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 150 | 865 | 0 | 0 | 148 | 1131 | 0 | 119 | 519 | 0 | 145 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | pm+pt | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 10.0 | 10.0 | 43.5 | | 10.0 | 10.0 | 43.5 | | 10.0 | 41.0 | | 10.0 |
| Total Split (s) | 30.0 | 30.0 | 52.0 | | 38.0 | 38.0 | 60.0 | | 29.0 | 41.0 | | 29.0 |
| Total Split (%) | 18.8% | 18.8% | 32.5% | | 23.8% | 23.8% | 37.5% | | 18.1% | 25.6% | | 18.1% |
| Maximum Green (s) | 23.6 | 23.6 | 45.5 | | 31.6 | 31.6 | 53.5 | | 22.3 | 34.3 | | 22.3 |
| Yellow Time (s) | 3.6 | 3.6 | 3.9 | | 3.6 | 3.6 | 3.9 | | 3.6 | 3.6 | | 3.6 |
| All-Red Time (s) | 2.8 | 2.8 | 2.6 | | 2.8 | 2.8 | 2.6 | | 3.1 | 3.1 | | 3.1 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.4 | 6.5 | | | 6.4 | 6.5 | | 6.7 | 6.7 | | 6.7 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lead | Lag | | Lead |
| Lead-Lag Optimize? | | | Yes | | Yes | Yes | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | 7.0 | | |
| Flash Don't Walk (s) | | | 21.0 | | | | 21.0 | | | 24.4 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | 0 | | |
| Act Effct Green (s) | | 18.7 | 70.9 | | | 18.6 | 70.8 | | 42.0 | 29.0 | | 46.6 |
| Actuated g/C Ratio | | 0.12 | 0.44 | | | 0.12 | 0.44 | | 0.26 | 0.18 | | 0.29 |
| v/c Ratio | | 0.72 | 0.38 | | | 0.71 | 0.51 | | 0.52 | 0.81 | | 0.61 |
| Control Delay (s/veh) | | 98.1 | 24.7 | | | 117.2 | 13.6 | | 46.6 | 70.5 | | 50.3 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 369 | 127 |
| Future Volume (vph) | 369 | 127 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 280 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 0.95 |
| Frt | 0.962 | |
| Flt Protected | | |
| Satd. Flow (prot) | 3438 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3438 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 27 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 495 | |
| Travel Time (s) | 11.3 | |
| Peak Hour Factor | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 377 | 130 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 507 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 41.0 | |
| Total Split (s) | 41.0 | |
| Total Split (%) | 25.6% | |
| Maximum Green (s) | 34.3 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.1 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.7 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 23.6 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 31.3 | |
| Actuated g/C Ratio | 0.20 | |
| v/c Ratio | 0.73 | |
| Control Delay (s/veh) | 63.1 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 98.1 | 24.7 | | | 117.2 | 13.6 | | 46.6 | 70.5 | | 50.3 |
| LOS | | F | C | | | F | B | | D | E | | D |
| Approach Delay (s/veh) | | | 35.6 | | | | 25.6 | | | 66.0 | | |
| Approach LOS | | | D | | | | C | | | E | | |
| Queue Length 50th (ft) | | 161 | 148 | | | 165 | 72 | | 91 | 267 | | 113 |
| Queue Length 95th (ft) | | 245 | 173 | | | 219 | 459 | | 131 | 320 | | 156 |
| Internal Link Dist (ft) | | | 889 | | | | 1548 | | | 457 | | |
| Turn Bay Length (ft) | | 230 | | | | 270 | | | 190 | | | 240 |
| Base Capacity (vph) | | 266 | 2248 | | | 352 | 2242 | | 330 | 765 | | 309 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.56 | 0.38 | | | 0.42 | 0.50 | | 0.36 | 0.68 | | 0.47 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 4 (3%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.81 | | | |
| Intersection Signal Delay (s/veh): 41.9 | | Intersection LOS: D | |
| Intersection Capacity Utilization 74.2% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 21: Bailey Ave & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 63.1 | |
| LOS | E | |
| Approach Delay (s/veh) | 60.3 | |
| Approach LOS | E | |
| Queue Length 50th (ft) | 251 | |
| Queue Length 95th (ft) | 300 | |
| Internal Link Dist (ft) | 415 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 778 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.65 | |

Intersection Summary



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 8 | 169 | 814 | 21 | 20 | 49 | 1040 | 185 | 27 | 264 | 40 | 150 |
| Future Volume (vph) | 8 | 169 | 814 | 21 | 20 | 49 | 1040 | 185 | 27 | 264 | 40 | 150 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 200 | | 0 | | 190 | | 0 | 85 | | 0 | 305 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.996 | | | | 0.977 | | | 0.980 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5115 | 0 | 0 | 1787 | 5018 | 0 | 1787 | 1844 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.523 | | | 0.176 |
| Satd. Flow (perm) | 0 | 1787 | 5115 | 0 | 0 | 1787 | 5018 | 0 | 984 | 1844 | 0 | 331 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 2 | | | | 26 | | | 4 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1628 | | | | 2376 | | | 1485 | | |
| Travel Time (s) | | | 27.8 | | | | 40.5 | | | 33.8 | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 8 | 172 | 831 | 21 | 20 | 50 | 1061 | 189 | 28 | 269 | 41 | 153 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 180 | 852 | 0 | 0 | 70 | 1250 | 0 | 28 | 310 | 0 | 153 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 6.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 12.2 | 12.2 | 43.2 | | 12.2 | 12.2 | 43.2 | | 42.0 | 42.0 | | 12.1 |
| Total Split (s) | 21.0 | 21.0 | 60.0 | | 31.0 | 31.0 | 70.0 | | 42.0 | 42.0 | | 27.0 |
| Total Split (%) | 13.1% | 13.1% | 37.5% | | 19.4% | 19.4% | 43.8% | | 26.3% | 26.3% | | 16.9% |
| Maximum Green (s) | 14.8 | 14.8 | 53.8 | | 24.8 | 24.8 | 63.8 | | 34.9 | 34.9 | | 19.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | 3.9 | | 3.2 | 3.2 | | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | 2.3 | | 3.9 | 3.9 | | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | 7.1 | 7.1 | | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | | Yes | Yes | | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | | | 17.0 | | | | 18.0 | | 27.0 | 27.0 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | 0 | 0 | | |
| Act Effct Green (s) | | 23.7 | 73.3 | | | 11.6 | 61.3 | | 31.5 | 31.5 | | 55.5 |
| Actuated g/C Ratio | | 0.15 | 0.46 | | | 0.07 | 0.38 | | 0.20 | 0.20 | | 0.35 |
| v/c Ratio | | 0.68 | 0.36 | | | 0.54 | 0.65 | | 0.15 | 0.85 | | 0.57 |
| Control Delay (s/veh) | | 75.7 | 46.1 | | | 86.2 | 42.3 | | 52.3 | 81.4 | | 44.1 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |



| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 252 | 148 |
| Future Volume (vph) | 252 | 148 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.944 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1776 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1776 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 22 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 1504 | |
| Travel Time (s) | 34.2 | |
| Peak Hour Factor | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 257 | 151 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 408 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 44.1 | |
| Total Split (s) | 69.0 | |
| Total Split (%) | 43.1% | |
| Maximum Green (s) | 61.9 | |
| Yellow Time (s) | 3.2 | |
| All-Red Time (s) | 3.9 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 7.1 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 30.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 55.5 | |
| Actuated g/C Ratio | 0.35 | |
| v/c Ratio | 0.65 | |
| Control Delay (s/veh) | 45.4 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 75.7 | 46.1 | | | 86.2 | 42.3 | | 52.3 | 81.4 | | 44.1 |
| LOS | | E | D | | | F | D | | D | F | | D |
| Approach Delay (s/veh) | | | 51.3 | | | | 44.7 | | | 79.0 | | |
| Approach LOS | | | D | | | | D | | | E | | |
| Queue Length 50th (ft) | | 193 | 215 | | | 72 | 393 | | 24 | 312 | | 114 |
| Queue Length 95th (ft) | | #386 | 391 | | | 125 | 454 | | 53 | 407 | | 154 |
| Internal Link Dist (ft) | | | 1548 | | | | 2296 | | | 1405 | | |
| Turn Bay Length (ft) | | 200 | | | | 190 | | | 85 | | | 305 |
| Base Capacity (vph) | | 264 | 2345 | | | 276 | 2077 | | 220 | 415 | | 300 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.68 | 0.36 | | | 0.25 | 0.60 | | 0.13 | 0.75 | | 0.51 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 133 (83%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 110 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.85 | | | |
| Intersection Signal Delay (s/veh): 50.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 83.5% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |


Splits and Phases: 22: Sweet Home Rd & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 45.4 | |
| LOS | D | |
| Approach Delay (s/veh) | 45.1 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 340 | |
| Queue Length 95th (ft) | 406 | |
| Internal Link Dist (ft) | 1424 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 714 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.57 | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 3 | 247 | 774 | 36 | 162 | 772 | 85 | 44 | 402 | 120 | 92 | 704 |
| Future Volume (vph) | 3 | 247 | 774 | 36 | 162 | 772 | 85 | 44 | 402 | 120 | 92 | 704 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 315 | | 0 | 330 | | 0 | 110 | | 155 | 105 | |
| Storage Lanes | | 1 | | 0 | 1 | | 0 | 1 | | 1 | 1 | |
| Taper Length (ft) | | 25 | | | 25 | | | 25 | | | 25 | |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 |
| Frt | | | 0.993 | | | 0.985 | | | | 0.850 | | |
| Flt Protected | | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1787 | 5100 | 0 | 1787 | 5059 | 0 | 1787 | 3574 | 1599 | 1787 | 3574 |
| Flt Permitted | | 0.950 | | | 0.950 | | | 0.235 | | | 0.372 | |
| Satd. Flow (perm) | 0 | 1787 | 5100 | 0 | 1787 | 5059 | 0 | 442 | 3574 | 1599 | 700 | 3574 |
| Right Turn on Red | | | | Yes | | | Yes | | | Yes | | |
| Satd. Flow (RTOR) | | | 4 | | | 12 | | | | 124 | | |
| Link Speed (mph) | | | 40 | | | 40 | | | 30 | | | 30 |
| Link Distance (ft) | | | 2376 | | | 4032 | | | 1401 | | | 981 |
| Travel Time (s) | | | 40.5 | | | 68.7 | | | 31.8 | | | 22.3 |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 3 | 255 | 798 | 37 | 167 | 796 | 88 | 45 | 414 | 124 | 95 | 726 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 258 | 835 | 0 | 167 | 884 | 0 | 45 | 414 | 124 | 95 | 726 |
| Turn Type | Prot | Prot | NA | | Prot | NA | | pm+pt | NA | Perm | pm+pt | NA |
| Protected Phases | 1 | 1 | 6 | | 5 | 2 | | 3 | 8 | | 7 | 4 |
| Permitted Phases | | | | | | | | 8 | | 8 | 4 | |
| Detector Phase | 1 | 1 | 6 | | 5 | 2 | | 3 | 8 | 8 | 7 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | | 10.0 | 10.0 | | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 |
| Minimum Split (s) | 16.2 | 16.2 | 43.2 | | 16.2 | 44.2 | | 10.1 | 45.0 | 45.0 | 10.1 | 45.0 |
| Total Split (s) | 30.0 | 30.0 | 45.0 | | 30.0 | 45.0 | | 35.0 | 45.0 | 45.0 | 35.0 | 45.0 |
| Total Split (%) | 19.4% | 19.4% | 29.0% | | 19.4% | 29.0% | | 22.6% | 29.0% | 29.0% | 22.6% | 29.0% |
| Maximum Green (s) | 23.8 | 23.8 | 38.8 | | 23.8 | 38.8 | | 27.9 | 37.9 | 37.9 | 27.9 | 37.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | 6.2 | 6.2 | | 7.1 | 7.1 | 7.1 | 7.1 | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lag | | Lead | Lag | Lag | Lead | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | None | None | Min | | None | Min | | None | None | None | None | None |
| Walk Time (s) | | | 7.0 | | | 7.0 | | | 7.0 | 7.0 | | 7.0 |
| Flash Don't Walk (s) | | | 30.0 | | | 31.0 | | | 30.0 | 30.0 | | 30.0 |
| Pedestrian Calls (#/hr) | | | 0 | | | 0 | | | 0 | 0 | | 0 |
| Act Effct Green (s) | | 22.7 | 33.9 | | 16.7 | 27.8 | | 35.1 | 27.7 | 27.7 | 41.8 | 33.8 |
| Actuated g/C Ratio | | 0.20 | 0.29 | | 0.14 | 0.24 | | 0.30 | 0.24 | 0.24 | 0.36 | 0.29 |
| v/c Ratio | | 0.74 | 0.56 | | 0.65 | 0.72 | | 0.20 | 0.48 | 0.26 | 0.27 | 0.69 |
| Control Delay (s/veh) | | 59.9 | 37.7 | | 61.5 | 44.4 | | 25.8 | 40.3 | 7.9 | 25.7 | 42.1 |
| Queue Delay | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 363 |
| Future Volume (vph) | 363 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 285 |
| Storage Lanes | 1 |
| Taper Length (ft) | |
| Lane Util. Factor | 1.00 |
| Frt | 0.850 |
| Flt Protected | |
| Satd. Flow (prot) | 1599 |
| Flt Permitted | |
| Satd. Flow (perm) | 1599 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | 373 |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Peak Hour Factor | 0.97 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 374 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 374 |
| Turn Type | Prot |
| Protected Phases | 4 |
| Permitted Phases | |
| Detector Phase | 4 |
| Switch Phase | |
| Minimum Initial (s) | 10.0 |
| Minimum Split (s) | 45.0 |
| Total Split (s) | 45.0 |
| Total Split (%) | 29.0% |
| Maximum Green (s) | 37.9 |
| Yellow Time (s) | 3.2 |
| All-Red Time (s) | 3.9 |
| Lost Time Adjust (s) | 0.0 |
| Total Lost Time (s) | 7.1 |
| Lead/Lag | Lag |
| Lead-Lag Optimize? | Yes |
| Vehicle Extension (s) | 3.0 |
| Recall Mode | None |
| Walk Time (s) | 7.0 |
| Flash Don't Walk (s) | 30.0 |
| Pedestrian Calls (#/hr) | 0 |
| Act Effct Green (s) | 33.8 |
| Actuated g/C Ratio | 0.29 |
| v/c Ratio | 0.51 |
| Control Delay (s/veh) | 6.3 |
| Queue Delay | 0.0 |

| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 59.9 | 37.7 | | 61.5 | 44.4 | | 25.8 | 40.3 | 7.9 | 25.7 | 42.1 |
| LOS | | E | D | | E | D | | C | D | A | C | D |
| Approach Delay (s/veh) | | | 43.0 | | | 47.1 | | | 32.3 | | | 29.6 |
| Approach LOS | | | D | | | D | | | C | | | C |
| Queue Length 50th (ft) | | 194 | 203 | | 127 | 234 | | 21 | 142 | 0 | 46 | 268 |
| Queue Length 95th (ft) | | #355 | 279 | | 209 | 296 | | 49 | 212 | 50 | 89 | 372 |
| Internal Link Dist (ft) | | | 2296 | | | 3952 | | | 1321 | | | 901 |
| Turn Bay Length (ft) | | 315 | | | 330 | | | 110 | | 155 | 105 | |
| Base Capacity (vph) | | 379 | 1765 | | 379 | 1756 | | 507 | 1206 | 622 | 544 | 1206 |
| Starvation Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.68 | 0.47 | | 0.44 | 0.50 | | 0.09 | 0.34 | 0.20 | 0.17 | 0.60 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 155 | | | |
| Actuated Cycle Length: 115.6 | | | |
| Natural Cycle: 120 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.74 | | | |
| Intersection Signal Delay (s/veh): 38.4 | | Intersection LOS: D | |
| Intersection Capacity Utilization 78.6% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |


Splits and Phases: 23: Millersport Hwy & Sheridan Dr





| Lane Group | SBR |
|---|---|
| Total Delay (s/veh) | 6.3 |
| LOS | A |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | 1 |
| Queue Length 95th (ft) | 78 |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | 285 |
| Base Capacity (vph) | 787 |
| Starvation Cap Reductn | 0 |
| Spillback Cap Reductn | 0 |
| Storage Cap Reductn | 0 |
| Reduced v/c Ratio | 0.48 |

| Intersection Summary |
|---|





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 37 | 375 | 4 | 2 | 437 | 18 | 0 | 25 | 4 | 42 | 29 | 45 |
| Future Volume (vph) | 37 | 375 | 4 | 2 | 437 | 18 | 0 | 25 | 4 | 42 | 29 | 45 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.999 | | | 0.994 | | | 0.982 | | | 0.948 | |
| Flt Protected | | 0.996 | | | | | | | | | 0.982 | |
| Satd. Flow (prot) | 0 | 3556 | 0 | 0 | 3553 | 0 | 0 | 1847 | 0 | 0 | 1751 | 0 |
| Flt Permitted | | 0.894 | | | 0.954 | | | | | | 0.867 | |
| Satd. Flow (perm) | 0 | 3192 | 0 | 0 | 3389 | 0 | 0 | 1847 | 0 | 0 | 1546 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 3 | | | 15 | | | 4 | | | 46 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 25 | |
| Link Distance (ft) | | 1535 | | | 1128 | | | 417 | | | 659 | |
| Travel Time (s) | | 29.9 | | | 22.0 | | | 9.5 | | | 18.0 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 39 | 391 | 4 | 2 | 455 | 19 | 0 | 26 | 4 | 44 | 30 | 47 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 434 | 0 | 0 | 476 | 0 | 0 | 30 | 0 | 0 | 121 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | | NA | | Perm | NA | |
| Protected Phases | | 1 | | | 1 | | | 2 | | | 2 | |
| Permitted Phases | 1 | | | 1 | | | 2 | | | 2 | | |
| Detector Phase | 1 | 1 | | 1 | 1 | | 2 | 2 | | 2 | 2 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 25.0 | 25.0 | | 25.0 | 25.0 | | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | 30.0 | 30.0 | | 30.0 | 30.0 | | 23.0 | 23.0 | | 23.0 | 23.0 | |
| Total Split (s) | 45.0 | 45.0 | | 45.0 | 45.0 | | 15.0 | 15.0 | | 15.0 | 15.0 | |
| Total Split (%) | 75.0% | 75.0% | | 75.0% | 75.0% | | 25.0% | 25.0% | | 25.0% | 25.0% | |
| Maximum Green (s) | 40.0 | 40.0 | | 40.0 | 40.0 | | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Yellow Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | | 5.0 | | | 5.0 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | None | None | | None | None | |
| Walk Time (s) | | | | | | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | | | | | 11.0 | 11.0 | | 11.0 | 11.0 | |
| Pedestrian Calls (#/hr) | | | | | | | 0 | 0 | | 0 | 0 | |
| Act Effct Green (s) | | 29.0 | | | 29.0 | | | 10.0 | | | 10.0 | |
| Actuated g/C Ratio | | 0.64 | | | 0.64 | | | 0.22 | | | 0.22 | |
| v/c Ratio | | 0.21 | | | 0.22 | | | 0.07 | | | 0.32 | |
| Control Delay (s/veh) | | 5.0 | | | 4.9 | | | 13.2 | | | 12.8 | |
| Queue Delay | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Delay (s/veh) | | 5.0 | | | 4.9 | | | 13.2 | | | 12.8 | |
| LOS | | A | | | A | | | B | | | B | |
| Approach Delay (s/veh) | | 5.0 | | | 4.9 | | | 13.2 | | | 12.8 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Approach LOS | | A | | | A | | | B | | | B | |
| Queue Length 50th (ft) | | 25 | | | 27 | | | 5 | | | 16 | |
| Queue Length 95th (ft) | | 42 | | | 45 | | | 20 | | | 49 | |
| Internal Link Dist (ft) | | 1455 | | | 1048 | | | 337 | | | 579 | |
| Turn Bay Length (ft) | | | | | | | | | | | | |
| Base Capacity (vph) | | 3192 | | | 3389 | | | 413 | | | 379 | |
| Starvation Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | | 0.14 | | | 0.14 | | | 0.07 | | | 0.32 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 60 | | | |
| Actuated Cycle Length: 45 | | | |
| Natural Cycle: 55 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.32 | | | |
| Intersection Signal Delay (s/veh): 6.1 | | Intersection LOS: A | |
| Intersection Capacity Utilization 60.8% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 24: Alberta Dr & Eggert Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 36 | 273 | 122 | 39 | 294 | 119 | 121 | 395 | 51 | 120 | 386 | 46 |
| Future Volume (vph) | 36 | 273 | 122 | 39 | 294 | 119 | 121 | 395 | 51 | 120 | 386 | 46 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 150 | | 0 | 110 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 0.95 | 0.95 |
| Frt | | 0.958 | | | 0.961 | | | 0.983 | | | 0.984 | |
| Flt Protected | | 0.996 | | | 0.996 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3410 | 0 | 0 | 3421 | 0 | 1787 | 1849 | 0 | 1787 | 3517 | 0 |
| Flt Permitted | | 0.880 | | | 0.879 | | 0.488 | | | 0.318 | | |
| Satd. Flow (perm) | 0 | 3013 | 0 | 0 | 3019 | 0 | 918 | 1849 | 0 | 598 | 3517 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 79 | | | 68 | | | 10 | | | 19 | |
| Link Speed (mph) | | 30 | | | 30 | | | 30 | | | 30 | |
| Link Distance (ft) | | 1128 | | | 580 | | | 922 | | | 349 | |
| Travel Time (s) | | 25.6 | | | 13.2 | | | 21.0 | | | 7.9 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 38 | 284 | 127 | 41 | 306 | 124 | 126 | 411 | 53 | 125 | 402 | 48 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 449 | 0 | 0 | 471 | 0 | 126 | 464 | 0 | 125 | 450 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | | 4 | | | 8 | | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 4 | | | 8 | | | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | | 10.0 | 10.0 | | 5.0 | 10.0 | | 5.0 | 10.0 | |
| Minimum Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 10.0 | 37.0 | | 10.0 | 37.0 | |
| Total Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 11.0 | 37.0 | | 11.0 | 37.0 | |
| Total Split (%) | 40.0% | 40.0% | | 40.0% | 40.0% | | 13.8% | 46.3% | | 13.8% | 46.3% | |
| Maximum Green (s) | 27.0 | 27.0 | | 27.0 | 27.0 | | 6.0 | 32.0 | | 6.0 | 32.0 | |
| Yellow Time (s) | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| All-Red Time (s) | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | | | | | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | | Yes | Yes | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | None | None | | None | None | |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | 20.0 | 20.0 | | 20.0 | 20.0 | | | 25.0 | | | 25.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Act Effct Green (s) | | 14.5 | | | 14.5 | | 23.4 | 18.9 | | 23.4 | 18.9 | |
| Actuated g/C Ratio | | 0.28 | | | 0.28 | | 0.44 | 0.36 | | 0.44 | 0.36 | |
| v/c Ratio | | 0.51 | | | 0.53 | | 0.24 | 0.69 | | 0.30 | 0.35 | |
| Control Delay (s/veh) | | 17.1 | | | 18.0 | | 7.9 | 20.9 | | 8.7 | 13.2 | |
| Queue Delay | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 17.1 | | | 18.0 | | 7.9 | 20.9 | | 8.7 | 13.2 | |
| LOS | | B | | | B | | A | C | | A | B | |
| Approach Delay (s/veh) | | 17.1 | | | 18.0 | | | 18.1 | | | 12.2 | |
| Approach LOS | | B | | | B | | | B | | | B | |
| Queue Length 50th (ft) | | 51 | | | 56 | | 17 | 120 | | 16 | 51 | |
| Queue Length 95th (ft) | | 114 | | | 123 | | 46 | 243 | | 46 | 97 | |
| Internal Link Dist (ft) | | 1048 | | | 500 | | | 842 | | | 269 | |
| Turn Bay Length (ft) | | | | | | | 150 | | | 110 | | |
| Base Capacity (vph) | | 1728 | | | 1726 | | 516 | 1210 | | 414 | 2302 | |
| Starvation Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.26 | | | 0.27 | | 0.24 | 0.38 | | 0.30 | 0.20 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 80 | | | |
| Actuated Cycle Length: 52.6 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.69 | | | |
| Intersection Signal Delay (s/veh): 16.2 | | Intersection LOS: B | |
| Intersection Capacity Utilization 72.8% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 25: Bailey Ave & Eggert Rd




| Intersection | |
|---|---|
| Int Delay, s/veh | 6.2 |

| Movement | EBL | EBR | NBL | NBT | SBT | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 26 | 226 | 213 | 847 | 773 | 11 |
| Future Vol, veh/h | 26 | 226 | 213 | 847 | 773 | 11 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Free | Free | Free | Free |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | 180 | 0 | 165 | - | - | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 98 | 98 | 98 | 98 | 98 | 98 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 27 | 231 | 217 | 864 | 789 | 11 |

| Major/Minor | Minor2 | | Major1 | | Major2 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 2093 | 794 | 800 | 0 | - | 0 |
| Stage 1 | 794 | - | - | - | - | - |
| Stage 2 | 1299 | - | - | - | - | - |
| Critical Hdwy | 6.41 | 6.21 | 4.11 | - | - | - |
| Critical Hdwy Stg 1 | 5.41 | - | - | - | - | - |
| Critical Hdwy Stg 2 | 5.41 | - | - | - | - | - |
| Follow-up Hdwy | 3.509 | 3.309 | 2.209 | - | - | - |
| Pot Cap-1 Maneuver | 58 | 389 | 827 | - | - | - |
| Stage 1 | 447 | - | - | - | - | - |
| Stage 2 | 257 | - | - | - | - | - |
| Platoon blocked, % | | | | - | - | - |
| Mov Cap-1 Maneuver | 43 | 389 | 827 | - | - | - |
| Mov Cap-2 Maneuver | 43 | - | - | - | - | - |
| Stage 1 | 329 | - | - | - | - | - |
| Stage 2 | 257 | - | - | - | - | - |

| Approach | EB | NB | SB |
|---|---|---|---|
| HCM Control Delay, s/v | 42.6 | 2.19 | 0 |
| HCM LOS | E | | |

| Minor Lane/Major Mvmt | NBL | NBT | EBLn1 | EBLn2 | SBT | SBR |
|---|---|---|---|---|---|---|
| Capacity (veh/h) | 827 | - | 43 | 389 | - | - |
| HCM Lane V/C Ratio | 0.263 | - | 0.622 | 0.592 | - | - |
| HCM Control Delay (s/veh) | 10.9 | - | 179.9 | 26.8 | - | - |
| HCM Lane LOS | B | - | F | D | - | - |
| HCM 95th %tile Q(veh) | 1.1 | - | 2.3 | 3.7 | - | - |




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 141 | 43 | 66 | 12 | 38 | 151 | 54 | 726 | 36 | 135 | 881 | 125 |
| Future Volume (vph) | 141 | 43 | 66 | 12 | 38 | 151 | 54 | 726 | 36 | 135 | 881 | 125 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 70 | 170 | | 0 | 150 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 1 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.964 | | | | 0.850 | | 0.993 | | | 0.981 | |
| Flt Protected | | 0.973 | | | 0.988 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 1765 | 0 | 0 | 1859 | 1599 | 1787 | 1868 | 0 | 1787 | 1845 | 0 |
| Flt Permitted | | 0.797 | | | 0.922 | | 0.100 | | | 0.249 | | |
| Satd. Flow (perm) | 0 | 1445 | 0 | 0 | 1734 | 1599 | 188 | 1868 | 0 | 468 | 1845 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 18 | | | | 156 | | 6 | | | 17 | |
| Link Speed (mph) | | 30 | | | 30 | | | 35 | | | 35 | |
| Link Distance (ft) | | 710 | | | 507 | | | 1039 | | | 1225 | |
| Travel Time (s) | | 16.1 | | | 11.5 | | | 20.2 | | | 23.9 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 145 | 44 | 68 | 12 | 39 | 156 | 56 | 748 | 37 | 139 | 908 | 129 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 257 | 0 | 0 | 51 | 156 | 56 | 785 | 0 | 139 | 1037 | 0 |
| Turn Type | Perm | NA | | Perm | NA | Perm | Perm | NA | | Perm | NA | |
| Protected Phases | | 4 | | | 8 | | | 2 | | | 6 | |
| Permitted Phases | 4 | | | 8 | | 8 | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | 8 | 2 | 2 | | 6 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | | 10.0 | 10.0 | 10.0 | 30.0 | 30.0 | | 30.0 | 30.0 | |
| Minimum Split (s) | 27.2 | 27.2 | | 23.0 | 23.0 | 23.0 | 35.6 | 35.6 | | 35.6 | 35.6 | |
| Total Split (s) | 25.0 | 25.0 | | 25.0 | 25.0 | 25.0 | 65.0 | 65.0 | | 65.0 | 65.0 | |
| Total Split (%) | 27.8% | 27.8% | | 27.8% | 27.8% | 27.8% | 72.2% | 72.2% | | 72.2% | 72.2% | |
| Maximum Green (s) | 19.8 | 19.8 | | 19.8 | 19.8 | 19.8 | 59.4 | 59.4 | | 59.4 | 59.4 | |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | 3.2 | 3.6 | 3.6 | | 3.6 | 3.6 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.2 | | | 5.2 | 5.2 | 5.6 | 5.6 | | 5.6 | 5.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | None | None | | None | None | None | Min | Min | | Min | Min | |
| Walk Time (s) | 7.0 | 7.0 | | | | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | 15.0 | 15.0 | | | | | | | | 15.0 | 15.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | | | | | | 0 | 0 | |
| Act Effct Green (s) | | 16.8 | | | 16.8 | 16.8 | 48.6 | 48.6 | | 48.6 | 48.6 | |
| Actuated g/C Ratio | | 0.22 | | | 0.22 | 0.22 | 0.63 | 0.63 | | 0.63 | 0.63 | |
| v/c Ratio | | 0.78 | | | 0.13 | 0.33 | 0.47 | 0.66 | | 0.47 | 0.88 | |
| Control Delay (s/veh) | | 46.3 | | | 28.3 | 7.5 | 23.3 | 12.1 | | 13.9 | 22.4 | |
| Queue Delay | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 46.3 | | | 28.3 | 7.5 | 23.3 | 12.1 | | 13.9 | 22.4 | |
| LOS | | D | | | C | A | C | B | | B | C | |
| Approach Delay (s/veh) | | 46.3 | | | 12.6 | | | 12.9 | | | 21.4 | |
| Approach LOS | | D | | | B | | | B | | | C | |
| Queue Length 50th (ft) | | 118 | | | 22 | 0 | 14 | 230 | | 34 | 397 | |
| Queue Length 95th (ft) | | #251 | | | 54 | 48 | 58 | 341 | | 82 | #651 | |
| Internal Link Dist (ft) | | 630 | | | 427 | | | 959 | | | 1145 | |
| Turn Bay Length (ft) | | | | | | 70 | 170 | | | 150 | | |
| Base Capacity (vph) | | 404 | | | 469 | 546 | 146 | 1456 | | 364 | 1441 | |
| Starvation Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.64 | | | 0.11 | 0.29 | 0.38 | 0.54 | | 0.38 | 0.72 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 90 | | | |
| Actuated Cycle Length: 76.7 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.88 | | | |
| Intersection Signal Delay (s/veh): 20.4 | | Intersection LOS: C | |
| Intersection Capacity Utilization 113.4% | | ICU Level of Service H | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 27: Bailey Ave & Meyer Rd



| Intersection | |
|---|---|
| Int Delay, s/veh | 5.5 |

| Movement | EBT | EBR | WBL | WBT | NBL | NBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 23 | 206 | 30 | 8 | 194 | 20 |
| Future Vol, veh/h | 23 | 206 | 30 | 8 | 194 | 20 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Stop | Stop |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | - | - | - | - | 0 | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 97 | 97 | 97 | 97 | 97 | 97 |
| Heavy Vehicles, % | 0 | 0 | 0 | 0 | 0 | 0 |
| Mvmt Flow | 24 | 212 | 31 | 8 | 200 | 21 |

| Major/Minor | Major1 | | Major2 | | Minor1 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 0 | 0 | 236 | 0 | 200 | 130 |
| Stage 1 | - | - | - | - | 130 | - |
| Stage 2 | - | - | - | - | 70 | - |
| Critical Hdwy | - | - | 4.1 | - | 6.4 | 6.2 |
| Critical Hdwy Stg 1 | - | - | - | - | 5.4 | - |
| Critical Hdwy Stg 2 | - | - | - | - | 5.4 | - |
| Follow-up Hdwy | - | - | 2.2 | - | 3.5 | 3.3 |
| Pot Cap-1 Maneuver | - | - | 1343 | - | 793 | 925 |
| Stage 1 | - | - | - | - | 901 | - |
| Stage 2 | - | - | - | - | 958 | - |
| Platoon blocked, % | - | - | | - | | |
| Mov Cap-1 Maneuver | - | - | 1343 | - | 775 | 925 |
| Mov Cap-2 Maneuver | - | - | - | - | 775 | - |
| Stage 1 | - | - | - | - | 901 | - |
| Stage 2 | - | - | - | - | 936 | - |

| Approach | EB | WB | NB |
|---|---|---|---|
| HCM Control Delay, s/v | 0 | 6.11 | 11.35 |
| HCM LOS | | | B |


| Minor Lane/Major Mvmt | NBLn1 | EBT | EBR | WBL | WBT |
|---|---|---|---|---|---|
| Capacity (veh/h) | 787 | - | - | 1337 | - |
| HCM Lane V/C Ratio | 0.28 | - | - | 0.023 | - |
| HCM Control Delay (s/veh) | 11.3 | - | - | 7.7 | 0 |
| HCM Lane LOS | B | - | - | A | A |
| HCM 95th %tile Q(veh) | 1.2 | - | - | 0.1 | - |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 6 | 0 | 19 | 577 | 14 | 528 | 0 | 1266 | 437 | 0 | 1634 | 0 |
| Future Volume (vph) | 6 | 0 | 19 | 577 | 14 | 528 | 0 | 1266 | 437 | 0 | 1634 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 250 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 0 | | 1 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 0.95 | 0.91 | 0.95 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | 0.931 | 0.850 | | | 0.850 | | | |
| Flt Protected | 0.950 | | | 0.950 | 0.975 | | | | | | | |
| Satd. Flow (prot) | 1787 | 0 | 1599 | 1698 | 1554 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Flt Permitted | 0.189 | | | 0.950 | 0.975 | | | | | | | |
| Satd. Flow (perm) | 356 | 0 | 1599 | 1698 | 1554 | 1519 | 0 | 5136 | 1599 | 0 | 5136 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 28 | | 26 | 47 | | | 460 | | | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 240 | | | 646 | | | 950 | | | 468 | |
| Travel Time (s) | | 5.5 | | | 14.7 | | | 16.2 | | | 8.0 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 6 | 0 | 20 | 607 | 15 | 556 | 0 | 1333 | 460 | 0 | 1720 | 0 |
| Shared Lane Traffic (%) | | | | 33% | | 33% | | | | | | |
| Lane Group Flow (vph) | 6 | 0 | 20 | 407 | 398 | 373 | 0 | 1333 | 460 | 0 | 1720 | 0 |
| Turn Type | D.Pm | | Perm | Perm | NA | Perm | | NA | Perm | | NA | |
| Protected Phases | | | | | 3 | | | 1 | | | 1 | |
| Permitted Phases | 3 | | 3 | 3 | | 3 | | | 1 | | | |
| Detector Phase | 3 | | 3 | 3 | 3 | 3 | | 1 | 1 | | 1 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | | 6.0 | 6.0 | 6.0 | 6.0 | | 20.0 | 20.0 | | 20.0 | |
| Minimum Split (s) | 13.3 | | 13.3 | 13.3 | 13.3 | 13.3 | | 34.6 | 34.6 | | 34.6 | |
| Total Split (s) | 70.0 | | 70.0 | 70.0 | 70.0 | 70.0 | | 110.0 | 110.0 | | 110.0 | |
| Total Split (%) | 38.9% | | 38.9% | 38.9% | 38.9% | 38.9% | | 61.1% | 61.1% | | 61.1% | |
| Maximum Green (s) | 62.7 | | 62.7 | 62.7 | 62.7 | 62.7 | | 102.4 | 102.4 | | 102.4 | |
| Yellow Time (s) | 4.3 | | 4.3 | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 | | 4.3 | |
| All-Red Time (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.3 | 3.3 | | 3.3 | |
| Lost Time Adjust (s) | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |
| Total Lost Time (s) | 7.3 | | 7.3 | 7.3 | 7.3 | 7.3 | | 7.6 | 7.6 | | 7.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | |
| Recall Mode | None | | None | None | None | None | | C-Max | C-Max | | C-Max | |
| Walk Time (s) | | | | | | | | 7.0 | 7.0 | | 7.0 | |
| Flash Don't Walk (s) | | | | | | | | 20.0 | 20.0 | | 20.0 | |
| Pedestrian Calls (#/hr) | | | | | | | | 0 | 0 | | 0 | |
| Act Effct Green (s) | 53.2 | | 53.2 | 53.2 | 53.2 | 53.2 | | 111.9 | 111.9 | | 111.9 | |
| Actuated g/C Ratio | 0.30 | | 0.30 | 0.30 | 0.30 | 0.30 | | 0.62 | 0.62 | | 0.62 | |
| v/c Ratio | 0.06 | | 0.04 | 0.81 | 0.83 | 0.78 | | 0.42 | 0.39 | | 0.54 | |
| Control Delay (s/veh) | 42.2 | | 7.5 | 71.4 | 70.2 | 61.0 | | 23.0 | 5.5 | | 21.1 | |
| Queue Delay | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 42.2 | | 7.5 | 71.4 | 70.2 | 61.0 | | 23.0 | 5.5 | | 21.1 | |
| LOS | D | | A | E | E | E | | C | A | | C | |
| Approach Delay (s/veh) | | 15.5 | | | 67.7 | | | 18.5 | | | 21.1 | |
| Approach LOS | | B | | | E | | | B | | | C | |
| Queue Length 50th (ft) | 5 | | 0 | 466 | 452 | 373 | | 331 | 60 | | 419 | |
| Queue Length 95th (ft) | 18 | | 16 | 576 | 575 | 485 | | 389 | 102 | | 514 | |
| Internal Link Dist (ft) | | 160 | | | 566 | | | 870 | | | 388 | |
| Turn Bay Length (ft) | | | | | | | | | 250 | | | |
| Base Capacity (vph) | 124 | | 575 | 591 | 558 | 559 | | 3194 | 1168 | | 3194 | |
| Starvation Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Spillback Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Storage Cap Reductn | 0 | | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | |
| Reduced v/c Ratio | 0.05 | | 0.03 | 0.69 | 0.71 | 0.67 | | 0.42 | 0.39 | | 0.54 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 60 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.83 | | | |
| Intersection Signal Delay (s/veh): 31.7 | | Intersection LOS: C | |
| Intersection Capacity Utilization 76.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 1: Niagara Falls Blvd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 0 | 748 | 0 | 0 | 240 | 0 | 1535 | 668 | 0 | 1602 | 500 |
| Future Volume (vph) | 0 | 0 | 748 | 0 | 0 | 240 | 0 | 1535 | 668 | 0 | 1602 | 500 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 200 |
| Storage Lanes | 0 | | 2 | 0 | | 1 | 0 | | 0 | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 0.88 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | | 0.865 | | 0.954 | | | | 0.850 |
| Flt Protected | | | | | | | | | | | | |
| Satd. Flow (prot) | 0 | 0 | 2814 | 0 | 0 | 1627 | 0 | 4899 | 0 | 0 | 5136 | 1599 |
| Flt Permitted | | | | | | | | | | | | |
| Satd. Flow (perm) | 0 | 0 | 2814 | 0 | 0 | 1627 | 0 | 4899 | 0 | 0 | 5136 | 1599 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 37 | | | | | | | | | 356 |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 374 | | | 614 | | | 600 | | | 950 | |
| Travel Time (s) | | 8.5 | | | 14.0 | | | 10.2 | | | 16.2 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 0 | 0 | 771 | 0 | 0 | 247 | 0 | 1582 | 689 | 0 | 1652 | 515 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 0 | 771 | 0 | 0 | 247 | 0 | 2271 | 0 | 0 | 1652 | 515 |
| Turn Type | | | Perm | | | Perm | | NA | | | NA | Perm |
| Protected Phases | | | | | | | | 1 3 | | | 1 | |
| Permitted Phases | | | 3 | | | 1 3 | | | | | | 1 |
| Detector Phase | | | 3 | | | 1 3 | | 1 3 | | | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | | 15.0 | | | | | | | | 10.0 | 10.0 |
| Minimum Split (s) | | | 25.1 | | | | | | | | 26.5 | 26.5 |
| Total Split (s) | | | 70.0 | | | | | | | | 110.0 | 110.0 |
| Total Split (%) | | | 38.9% | | | | | | | | 61.1% | 61.1% |
| Maximum Green (s) | | | 62.9 | | | | | | | | 102.5 | 102.5 |
| Yellow Time (s) | | | 5.1 | | | | | | | | 4.3 | 4.3 |
| All-Red Time (s) | | | 2.0 | | | | | | | | 3.2 | 3.2 |
| Lost Time Adjust (s) | | | 0.0 | | | | | | | | 0.0 | 0.0 |
| Total Lost Time (s) | | | 7.1 | | | | | | | | 7.5 | 7.5 |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | | 3.0 | | | | | | | | 3.0 | 3.0 |
| Recall Mode | | | None | | | | | | | | C-Max | C-Max |
| Walk Time (s) | | | | | | | | | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | | | | | | | | | | 12.0 | 12.0 |
| Pedestrian Calls (#/hr) | | | | | | | | | | | 0 | 0 |
| Act Effct Green (s) | | | 62.9 | | | 180.0 | | 180.0 | | | 102.5 | 102.5 |
| Actuated g/C Ratio | | | 0.35 | | | 1.00 | | 1.00 | | | 0.57 | 0.57 |
| v/c Ratio | | | 0.77 | | | 0.15 | | 0.46 | | | 0.56 | 0.48 |
| Control Delay (s/veh) | | | 55.4 | | | 0.2 | | 0.3 | | | 28.9 | 7.8 |
| Queue Delay | | | 1.6 | | | 0.0 | | 0.0 | | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | | 56.9 | | | 0.2 | | 0.3 | | | 28.9 | 7.8 |
| LOS | | | E | | | A | | A | | | C | A |
| Approach Delay (s/veh) | | 56.9 | | | 0.2 | | | 0.3 | | | 23.9 | |
| Approach LOS | | E | | | A | | | A | | | C | |
| Queue Length 50th (ft) | | | 442 | | | 0 | | 0 | | | 572 | 213 |
| Queue Length 95th (ft) | | | 534 | | | 0 | | 0 | | | 627 | 137 |
| Internal Link Dist (ft) | | 294 | | | 534 | | | 520 | | | 870 | |
| Turn Bay Length (ft) | | | | | | | | | | | | 200 |
| Base Capacity (vph) | | | 1007 | | | 1627 | | 4899 | | | 2924 | 1063 |
| Starvation Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Spillback Cap Reductn | | | 103 | | | 0 | | 0 | | | 0 | 0 |
| Storage Cap Reductn | | | 0 | | | 0 | | 0 | | | 0 | 0 |
| Reduced v/c Ratio | | | 0.85 | | | 0.15 | | 0.46 | | | 0.56 | 0.48 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 1:NBSB, Start of Yellow | | | |
| Natural Cycle: 60 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.77 | | | |
| Intersection Signal Delay (s/veh): 17.7 | | Intersection LOS: B | |
| Intersection Capacity Utilization 72.0% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 2: Niagara Falls Blvd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 116 | 82 | 16 | 86 | 63 | 873 | 43 | 1238 | 75 | 812 | 1348 | 58 |
| Future Volume (vph) | 116 | 82 | 16 | 86 | 63 | 873 | 43 | 1238 | 75 | 812 | 1348 | 58 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 100 | | 0 | 0 | | 225 | 130 | | 0 | 435 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 2 | 1 | | 0 | 2 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.88 | 1.00 | 0.91 | 0.91 | 0.97 | 0.91 | 0.91 |
| Frt | | 0.975 | | | | 0.850 | | 0.991 | | | 0.994 | |
| Flt Protected | 0.950 | | | | 0.972 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 1834 | 0 | 0 | 1829 | 2814 | 1787 | 5089 | 0 | 3467 | 5105 | 0 |
| Flt Permitted | 0.448 | | | | 0.765 | | 0.950 | | | 0.950 | | |
| Satd. Flow (perm) | 843 | 1834 | 0 | 0 | 1439 | 2814 | 1787 | 5089 | 0 | 3467 | 5105 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 5 | | | | 177 | | 5 | | | 6 | |
| Link Speed (mph) | | 30 | | | 30 | | | 40 | | | 40 | |
| Link Distance (ft) | | 853 | | | 2284 | | | 672 | | | 600 | |
| Travel Time (s) | | 19.4 | | | 51.9 | | | 11.5 | | | 10.2 | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.97 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 121 | 85 | 17 | 90 | 66 | 909 | 45 | 1290 | 78 | 837 | 1404 | 60 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 121 | 102 | 0 | 0 | 156 | 909 | 45 | 1368 | 0 | 837 | 1464 | 0 |
| Turn Type | D.P+P | NA | | Perm | NA | pm+ov | Prot | NA | | Prot | NA | |
| Protected Phases | 7 | 7 8 | | | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 8 | | | 8 | | 8 | | | | | | |
| Detector Phase | 7 | 7 8 | | 8 | 8 | 1 | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | | | 5.0 | 5.0 | 5.0 | 5.0 | 20.0 | | 5.0 | 20.0 | |
| Minimum Split (s) | 12.7 | | | 24.3 | 24.3 | 12.5 | 11.6 | 32.6 | | 12.5 | 34.3 | |
| Total Split (s) | 25.0 | | | 30.0 | 30.0 | 65.0 | 20.0 | 60.0 | | 65.0 | 105.0 | |
| Total Split (%) | 13.9% | | | 16.7% | 16.7% | 36.1% | 11.1% | 33.3% | | 36.1% | 58.3% | |
| Maximum Green (s) | 17.5 | | | 24.7 | 24.7 | 57.5 | 13.7 | 53.5 | | 57.5 | 98.5 | |
| Yellow Time (s) | 3.6 | | | 4.3 | 4.3 | 3.6 | 4.3 | 4.3 | | 3.6 | 4.3 | |
| All-Red Time (s) | 3.9 | | | 1.0 | 1.0 | 3.9 | 2.0 | 2.2 | | 3.9 | 2.2 | |
| Lost Time Adjust (s) | 0.0 | | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 7.5 | | | | 5.3 | 7.5 | 6.3 | 6.5 | | 7.5 | 6.5 | |
| Lead/Lag | Lead | | | Lag | Lag | Lead | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 2.0 | | | 3.0 | 3.0 | 2.4 | 2.4 | 2.4 | | 2.4 | 2.4 | |
| Recall Mode | None | | | Max | Max | Max | None | Max | | Max | C-Max | |
| Walk Time (s) | | | | 7.0 | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | | | 11.0 | 11.0 | | | 19.0 | | | 19.0 | |
| Pedestrian Calls (#/hr) | | | | 0 | 0 | | | 0 | | | 0 | |
| Act Effct Green (s) | 40.0 | 47.5 | | | 28.5 | 91.3 | 9.3 | 53.5 | | 57.5 | 105.3 | |
| Actuated g/C Ratio | 0.22 | 0.26 | | | 0.16 | 0.51 | 0.05 | 0.30 | | 0.32 | 0.59 | |
| v/c Ratio | 0.47 | 0.21 | | | 0.69 | 0.60 | 0.49 | 0.90 | | 0.76 | 0.49 | |
| Control Delay (s/veh) | 58.9 | 50.4 | | | 87.9 | 26.9 | 104.0 | 30.5 | | 79.2 | 11.8 | |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.1 | | 8.8 | 0.2 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 58.9 | 50.4 | | | 87.9 | 26.9 | 104.0 | 30.6 | | 87.9 | 12.0 | |
| LOS | E | D | | | F | C | F | C | | F | B | |
| Approach Delay (s/veh) | | 55.0 | | | 35.8 | | | 32.9 | | | 39.6 | |
| Approach LOS | | E | | | D | | | C | | | D | |
| Queue Length 50th (ft) | 114 | 90 | | | 177 | 348 | 56 | 97 | | 500 | 246 | |
| Queue Length 95th (ft) | 178 | 147 | | | #304 | 443 | m93 | 128 | | 575 | 253 | |
| Internal Link Dist (ft) | | 773 | | | 2204 | | | 592 | | | 520 | |
| Turn Bay Length (ft) | 100 | | | | | 225 | 130 | | | 435 | | |
| Base Capacity (vph) | 295 | 462 | | | 227 | 1513 | 136 | 1516 | | 1107 | 2987 | |
| Starvation Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 6 | | 239 | 650 | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.41 | 0.22 | | | 0.69 | 0.60 | 0.33 | 0.91 | | 0.96 | 0.63 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 6:SBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.90 | | | |
| Intersection Signal Delay (s/veh): 37.6 | | Intersection LOS: D | |
| Intersection Capacity Utilization 80.5% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 3: Niagara Falls Blvd & Koenig Rd/Ridge Lea Rd




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 20 | 10 | 24 | 176 | 5 | 260 | 9 | 16 | 1176 | 112 | 258 | 1239 |
| Future Volume (vph) | 20 | 10 | 24 | 176 | 5 | 260 | 9 | 16 | 1176 | 112 | 258 | 1239 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 0 | | 160 | | 110 | | 170 | 300 | |
| Storage Lanes | 0 | | 1 | 0 | | 1 | | 1 | | 1 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 |
| Ped Bike Factor | | | | | | | | | | 0.99 | | |
| Frt | | | 0.850 | | | 0.850 | | | | 0.850 | | 0.995 |
| Flt Protected | | 0.967 | | | 0.954 | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1819 | 1599 | 0 | 1795 | 1599 | 0 | 1787 | 5136 | 1599 | 1787 | 5110 |
| Flt Permitted | | 0.182 | | | 0.709 | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 342 | 1599 | 0 | 1334 | 1599 | 0 | 1787 | 5136 | 1575 | 1787 | 5110 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 92 | | | 271 | | | | 92 | | 3 |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | 40 |
| Link Distance (ft) | | 800 | | | 1099 | | | | 758 | | | 672 |
| Travel Time (s) | | 18.2 | | | 25.0 | | | | 12.9 | | | 11.5 |
| Confl. Peds. (#/hr) | | | | | | | | | | 1 | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 21 | 10 | 25 | 183 | 5 | 271 | 9 | 17 | 1225 | 117 | 269 | 1291 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 31 | 25 | 0 | 188 | 271 | 0 | 26 | 1225 | 117 | 269 | 1336 |
| Turn Type | Perm | NA | Perm | Perm | NA | Perm | Prot | Prot | NA | Perm | Prot | NA |
| Protected Phases | | 3 | | | 4 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 3 | | 3 | 4 | | 4 | | | | 2 | | |
| Detector Phase | 3 | 3 | 3 | 4 | 4 | 4 | 5 | 5 | 2 | 2 | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 3.0 | 6.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 |
| Minimum Split (s) | 23.8 | 23.8 | 23.8 | 24.6 | 24.6 | 24.6 | 10.8 | 10.8 | 23.8 | 23.8 | 10.8 | 23.8 |
| Total Split (s) | 30.0 | 30.0 | 30.0 | 55.0 | 55.0 | 55.0 | 25.0 | 25.0 | 65.0 | 65.0 | 30.0 | 70.0 |
| Total Split (%) | 16.7% | 16.7% | 16.7% | 30.6% | 30.6% | 30.6% | 13.9% | 13.9% | 36.1% | 36.1% | 16.7% | 38.9% |
| Maximum Green (s) | 24.2 | 24.2 | 24.2 | 48.4 | 48.4 | 48.4 | 19.2 | 19.2 | 59.2 | 59.2 | 24.2 | 64.2 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | 3.2 | 3.2 | 3.2 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 1.9 | 1.9 | 1.9 | 3.4 | 3.4 | 3.4 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 | 1.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 5.8 | 5.8 | | 6.6 | 6.6 | | 5.8 | 5.8 | 5.8 | 5.8 | 5.8 |
| Lead/Lag | Lead | Lead | Lead | Lag | Lag | Lag | Lead | Lead | Lag | Lag | Lead | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | None | None | None | None | None | None | None | None | C-Max | C-Max | None | C-Max |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | 7.0 | 7.0 | | 7.0 |
| Flash Don't Walk (s) | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | 11.0 | | | 11.0 | 11.0 | | 11.0 |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 |
| Act Effct Green (s) | | 20.2 | 20.2 | | 31.1 | 31.1 | | 8.1 | 70.1 | 70.1 | 37.6 | 104.4 |
| Actuated g/C Ratio | | 0.11 | 0.11 | | 0.17 | 0.17 | | 0.05 | 0.39 | 0.39 | 0.21 | 0.58 |
| v/c Ratio | | 0.82 | 0.10 | | 0.82 | 0.54 | | 0.33 | 0.61 | 0.17 | 0.72 | 0.45 |

| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 43 |
| Future Volume (vph) | 43 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Ped Bike Factor | |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | |
| Peak Hour Factor | 0.96 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 45 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 174.1 | 0.8 | | 96.9 | 9.8 | | 122.4 | 41.0 | 5.2 | 80.8 | 8.3 |
| Queue Delay | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | | 174.1 | 0.8 | | 96.9 | 9.8 | | 122.4 | 41.0 | 5.2 | 80.8 | 8.3 |
| LOS | | F | A | | F | A | | F | D | A | F | A |
| Approach Delay (s/veh) | | 96.7 | | | 45.5 | | | | 39.5 | | | 20.5 |
| Approach LOS | | F | | | D | | | | D | | | C |
| Queue Length 50th (ft) | | 35 | 0 | | 217 | 0 | | 32 | 531 | 49 | 221 | 76 |
| Queue Length 95th (ft) | | #103 | 0 | | 296 | 82 | | m68 | 590 | m13 | #477 | 324 |
| Internal Link Dist (ft) | | 720 | | | 1019 | | | | 678 | | | 592 |
| Turn Bay Length (ft) | | | 25 | | | 160 | | 110 | | 170 | 300 | |
| Base Capacity (vph) | | 45 | 294 | | 358 | 628 | | 190 | 2000 | 669 | 373 | 2964 |
| Starvation Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 208 |
| Spillback Cap Reductn | | 0 | 0 | | 0 | 1 | | 0 | 25 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | 0 | 0 | | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.69 | 0.09 | | 0.53 | 0.43 | | 0.14 | 0.62 | 0.17 | 0.72 | 0.48 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 153 (85%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 95 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.82 | | | |
| Intersection Signal Delay (s/veh): 32.5 | | Intersection LOS: C | |
| Intersection Capacity Utilization 68.9% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 4: Niagara Falls Blvd & Pier 1 Entrance/The Boulevard/Consumer Square





| Lane Group | SBR |
|---|---|
| Control Delay (s/veh) | |
| Queue Delay | |
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 41 | 86 | 30 | 204 | 87 | 212 | 6 | 45 | 922 | 161 | 1 | 223 |
| Future Volume (vph) | 41 | 86 | 30 | 204 | 87 | 212 | 6 | 45 | 922 | 161 | 1 | 223 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 25 | 100 | | 0 | | 120 | | 165 | | 315 |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 |
| Frt | | | 0.850 | | 0.894 | | | | | 0.850 | | |
| Flt Protected | | 0.984 | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1851 | 1599 | 1787 | 1682 | 0 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Flt Permitted | | 0.361 | | 0.590 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 679 | 1599 | 1110 | 1682 | 0 | 0 | 1787 | 5136 | 1599 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 63 | | 69 | | | | | 116 | | |
| Link Speed (mph) | | 30 | | | 30 | | | | 40 | | | |
| Link Distance (ft) | | 868 | | | 278 | | | | 1759 | | | |
| Travel Time (s) | | 19.7 | | | 6.3 | | | | 30.0 | | | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 43 | 91 | 32 | 215 | 92 | 223 | 6 | 47 | 971 | 169 | 1 | 235 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 134 | 32 | 215 | 315 | 0 | 0 | 53 | 971 | 169 | 0 | 236 |
| Turn Type | Perm | NA | Perm | Perm | NA | | Prot | Prot | NA | Perm | Prot | Prot |
| Protected Phases | | 4 | | | 8 | | 5 | 5 | 2 | | 1 | 1 |
| Permitted Phases | 4 | | 4 | 8 | | | | | | 2 | | |
| Detector Phase | 4 | 4 | 4 | 8 | 8 | | 5 | 5 | 2 | 2 | 1 | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | 10.0 | 3.0 | 3.0 |
| Minimum Split (s) | 48.9 | 48.9 | 48.9 | 48.9 | 48.9 | | 11.7 | 11.7 | 40.0 | 40.0 | 11.7 | 11.7 |
| Total Split (s) | 60.0 | 60.0 | 60.0 | 60.0 | 60.0 | | 45.0 | 45.0 | 75.0 | 75.0 | 45.0 | 45.0 |
| Total Split (%) | 33.3% | 33.3% | 33.3% | 33.3% | 33.3% | | 25.0% | 25.0% | 41.7% | 41.7% | 25.0% | 25.0% |
| Maximum Green (s) | 53.1 | 53.1 | 53.1 | 53.1 | 53.1 | | 38.3 | 38.3 | 68.3 | 68.3 | 38.3 | 38.3 |
| Yellow Time (s) | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 3.7 | 3.7 | 3.7 | 3.7 | 3.7 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.9 | 6.9 | 6.9 | 6.9 | | | 6.7 | 6.7 | 6.7 | | 6.7 |
| Lead/Lag | | | | | | | Lead | Lead | Lag | Lag | Lead | Lead |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | None | None | None | | None | None | C-Max | C-Max | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | 30.0 | 30.0 | | | | 24.0 | 24.0 | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | 0 | | | | 0 | 0 | | |
| Act Effct Green (s) | | 37.7 | 37.7 | 37.7 | 37.7 | | | 10.1 | 93.5 | 93.5 | | 28.5 |
| Actuated g/C Ratio | | 0.21 | 0.21 | 0.21 | 0.21 | | | 0.06 | 0.52 | 0.52 | | 0.16 |
| v/c Ratio | | 0.94 | 0.08 | 0.93 | 0.78 | | | 0.53 | 0.36 | 0.19 | | 0.84 |
| Control Delay (s/veh) | | 130.7 | 0.7 | 109.4 | 62.3 | | | 81.3 | 51.2 | 31.8 | | 112.8 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 988 | 36 |
| Future Volume (vph) | 988 | 36 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Frt | 0.995 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5110 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5110 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 3 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 758 | |
| Travel Time (s) | 12.9 | |
| Peak Hour Factor | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 1040 | 38 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 1078 | 0 |
| Turn Type | NA | |
| Protected Phases | 6 | |
| Permitted Phases | | |
| Detector Phase | 6 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 31.7 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 41.7% | |
| Maximum Green (s) | 68.3 | |
| Yellow Time (s) | 4.3 | |
| All-Red Time (s) | 2.4 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.7 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 2.4 | |
| Recall Mode | C-Max | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 18.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 114.4 | |
| Actuated g/C Ratio | 0.64 | |
| v/c Ratio | 0.33 | |
| Control Delay (s/veh) | 8.6 | |
| Queue Delay | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 130.7 | 0.7 | 109.4 | 62.3 | | | 81.3 | 51.2 | 31.8 | | 112.8 |
| LOS | | F | A | F | E | | | F | D | C | | F |
| Approach Delay (s/veh) | | 105.7 | | | 81.4 | | | | 49.8 | | | |
| Approach LOS | | F | | | F | | | | D | | | |
| Queue Length 50th (ft) | | 158 | 0 | 251 | 277 | | | 63 | 352 | 86 | | 282 |
| Queue Length 95th (ft) | | #249 | 3 | m336 | 363 | | | 116 | 462 | 172 | | 391 |
| Internal Link Dist (ft) | | 788 | | | 198 | | | | 1679 | | | |
| Turn Bay Length (ft) | | | 25 | 100 | | | | 120 | | 165 | | 315 |
| Base Capacity (vph) | | 200 | 516 | 327 | 544 | | | 380 | 2667 | 886 | | 380 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.67 | 0.06 | 0.66 | 0.58 | | | 0.14 | 0.36 | 0.19 | | 0.62 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 150 (83%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 105 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.94 | | | |
| Intersection Signal Delay (s/veh): 48.7 | | Intersection LOS: D | |
| Intersection Capacity Utilization 77.3% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |

Splits and Phases: 5: Niagara Falls Blvd & Glenalby Rd/Romney Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 8.6 | |
| LOS | A | |
| Approach Delay (s/veh) | 27.3 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 90 | |
| Queue Length 95th (ft) | 140 | |
| Internal Link Dist (ft) | 678 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 3247 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.33 | |

Intersection Summary

| Intersection | |
|---|---|
| Int Delay, s/veh | 552.7 |

| Movement | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | | | |
| Traffic Vol, veh/h | 0 | 2 | 16 | 119 | 0 | 53 | 1 | 1 | 1651 | 90 | 50 | 65 | 1347 | 17 |
| Future Vol, veh/h | 0 | 2 | 16 | 119 | 0 | 53 | 1 | 1 | 1651 | 90 | 50 | 65 | 1347 | 17 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Stop | Stop | Stop | Stop | Free | Free | Free | Free | Free | Free | Free | Free |
| RT Channelized | - | - | None | - | - | None | - | - | - | None | - | - | - | None |
| Storage Length | - | - | - | - | - | - | - | - | - | - | - | 105 | - | - |
| Veh in Median Storage, # | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Grade, % | - | 0 | - | - | 0 | - | - | - | 0 | - | - | - | 0 | - |
| Peak Hour Factor | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 | 98 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 0 | 2 | 16 | 121 | 0 | 54 | 1 | 1 | 1685 | 92 | 51 | 66 | 1374 | 17 |

| Major/Minor | Minor2 | | | Minor1 | | | Major1 | | | | Major2 | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Conflicting Flow All | 2296 | 3398 | 696 | 2520 | 3361 | 888 | 1016 | 1392 | 0 | 0 | 1297 | 1777 | 0 | 0 |
| Stage 1 | 1618 | 1618 | - | 1735 | 1735 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 678 | 1781 | - | 786 | 1627 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy | 6.42 | 6.52 | 7.12 | 6.42 | 6.52 | 7.12 | 5.64 | 5.32 | - | - | 5.62 | 5.32 | - | - |
| Critical Hdwy Stg 1 | 7.32 | 5.52 | - | 7.32 | 5.52 | - | - | - | - | - | - | - | - | - |
| Critical Hdwy Stg 2 | 6.72 | 5.52 | - | 6.72 | 5.52 | - | - | - | - | - | - | - | - | - |
| Follow-up Hdwy | 3.81 | 4.01 | 3.91 | 3.81 | 4.01 | 3.91 | 2.32 | 3.11 | - | - | 2.31 | 3.11 | - | - |
| Pot Cap-1 Maneuver | 42 | 7 | 331 | ~ 30 | 8 | 248 | 430 | 254 | - | - | 303 | 164 | - | - |
| Stage 1 | 74 | 162 | - | ~ 61 | 142 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 374 | 135 | - | 321 | 161 | - | - | - | - | - | - | - | - | - |
| Platoon blocked, % | | | | | | | | | - | - | | | - | - |
| Mov Cap-1 Maneuver | 12 | 3 | 331 | ~ 5 | 3 | 248 | 314 | 314 | - | - | 189 | 189 | - | - |
| Mov Cap-2 Maneuver | 12 | 3 | - | ~ 5 | 3 | - | - | - | - | - | - | - | - | - |
| Stage 1 | 28 | 62 | - | ~ 60 | 141 | - | - | - | - | - | - | - | - | - |
| Stage 2 | 289 | 133 | - | ~ 112 | 61 | - | - | - | - | - | - | - | - | - |

| Approach | EB | WB | NB | SB |
|---|---|---|---|---|
| HCM Control Delay, $/3 | $ 347.54 | $ 10889.82 | 0.32 | 3.95 |
| HCM LOS | F | F | | |

| Minor Lane/Major Mvmt | NBL | NBT | NBR | EBLn1 | WBLn1 | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|
| Capacity (veh/h) | 5 | - | - | 23 | 8 | 189 | - | - |
| HCM Lane V/C Ratio | 0.003 | - | - | 0.783 | 23.086 | 0.62 | - | - |
| HCM Control Delay (s/veh) | 16.5 | 0.3 | - | $ 347.5 | $ 10889.8 | 50.8 | - | - |
| HCM Lane LOS | C | A | - | F | F | F | - | - |
| HCM 95th %tile Q(veh) | 0 | - | - | 2.3 | 23.8 | 3.5 | - | - |

| Notes | | | |
|---|---|---|---|
| ~: Volume exceeds capacity | $: Delay exceeds 300s | +: Computation Not Defined | *: All major volume in platoon |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBU | NBL | NBT | NBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 1 | 178 | 338 | 81 | 1 | 323 | 325 | 293 | 15 | 85 | 1100 | 292 |
| Future Volume (vph) | 1 | 178 | 338 | 81 | 1 | 323 | 325 | 293 | 15 | 85 | 1100 | 292 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 50 | | 50 | | 400 | | 0 | | 300 | | 300 |
| Storage Lanes | | 1 | | 1 | | 1 | | 1 | | 1 | | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | | 25 | | |
| Lane Util. Factor | 0.95 | 1.00 | 0.95 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 0.91 | 1.00 | 0.91 | 1.00 |
| Ped Bike Factor | | 1.00 | 1.00 | | | 1.00 | | 0.98 | | | | |
| Frt | | | 0.971 | | | | | 0.850 | | | | 0.850 |
| Flt Protected | | 0.950 | | | | 0.950 | | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 1787 | 3459 | 0 | 0 | 1787 | 3574 | 1599 | 0 | 1787 | 5136 | 1599 |
| Flt Permitted | | 0.548 | | | | 0.175 | | | | 0.950 | | |
| Satd. Flow (perm) | 0 | 1028 | 3459 | 0 | 0 | 328 | 3574 | 1573 | 0 | 1787 | 5136 | 1599 |
| Right Turn on Red | | | | Yes | | | | Yes | | | | Yes |
| Satd. Flow (RTOR) | | | 15 | | | | | 281 | | | | 278 |
| Link Speed (mph) | | | 30 | | | | 45 | | | | 40 | |
| Link Distance (ft) | | | 1574 | | | | 1441 | | | | 956 | |
| Travel Time (s) | | | 35.8 | | | | 21.8 | | | | 16.3 | |
| Confl. Peds. (#/hr) | | 3 | | 4 | | 4 | | 3 | | | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 1 | 185 | 352 | 84 | 1 | 336 | 339 | 305 | 16 | 89 | 1146 | 304 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 186 | 436 | 0 | 0 | 337 | 339 | 305 | 0 | 105 | 1146 | 304 |
| Turn Type | pm+pt | pm+pt | NA | | pm+pt | pm+pt | NA | Perm | Prot | Prot | NA | Perm |
| Protected Phases | 7 | 7 | 4 | | 3 | 3 | 8 | | 5 | 5 | 2 | |
| Permitted Phases | 4 | 4 | | | 8 | 8 | | 8 | | | | 2 |
| Detector Phase | 7 | 7 | 4 | | 3 | 3 | 8 | 8 | 5 | 5 | 2 | 2 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 6.0 | | 3.0 | 3.0 | 6.0 | 6.0 | 3.0 | 3.0 | 10.0 | 10.0 |
| Minimum Split (s) | 13.8 | 13.8 | 48.1 | | 13.8 | 13.8 | 47.8 | 47.8 | 12.1 | 12.1 | 39.1 | 39.1 |
| Total Split (s) | 30.0 | 30.0 | 50.0 | | 35.0 | 35.0 | 55.0 | 55.0 | 20.0 | 20.0 | 65.0 | 65.0 |
| Total Split (%) | 16.7% | 16.7% | 27.8% | | 19.4% | 19.4% | 30.6% | 30.6% | 11.1% | 11.1% | 36.1% | 36.1% |
| Maximum Green (s) | 21.9 | 21.9 | 41.9 | | 26.9 | 26.9 | 46.9 | 46.9 | 13.1 | 13.1 | 58.1 | 58.1 |
| Yellow Time (s) | 3.8 | 3.8 | 3.8 | | 3.8 | 3.8 | 3.8 | 3.8 | 3.9 | 3.9 | 3.9 | 3.9 |
| All-Red Time (s) | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 | 4.3 | 4.3 | 3.0 | 3.0 | 3.0 | 3.0 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 8.1 | 8.1 | | | 8.1 | 8.1 | 8.1 | | 6.9 | 6.9 | 6.9 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | Lag | Lead | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | 2.0 | | 2.5 | 2.5 | 2.5 | 2.5 | 2.4 | 2.4 | 2.4 | 2.4 |
| Recall Mode | None | None | None | | None | None | None | None | None | None | C-Max | C-Max |
| Walk Time (s) | | | 7.0 | | | | 7.0 | 7.0 | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | | 33.0 | | | | 31.0 | 31.0 | | | 24.0 | 24.0 |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | 0 | | | 0 | 0 |
| Act Effct Green (s) | | 44.3 | 26.5 | | | 60.2 | 35.2 | 35.2 | | 16.1 | 75.1 | 75.1 |
| Actuated g/C Ratio | | 0.25 | 0.15 | | | 0.33 | 0.20 | 0.20 | | 0.09 | 0.42 | 0.42 |
| v/c Ratio | | 0.57 | 0.84 | | | 1.04 | 0.48 | 0.57 | | 0.66 | 0.54 | 0.37 |

| Lane Group | SBU | SBL | SBT | SBR |
|---|---|---|---|---|
| Lane Configurations | | | | |
| Traffic Volume (vph) | 3 | 316 | 880 | 131 |
| Future Volume (vph) | 3 | 316 | 880 | 131 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 350 | | 0 |
| Storage Lanes | | 2 | | 0 |
| Taper Length (ft) | | 25 | | |
| Lane Util. Factor | 0.91 | 0.97 | 0.91 | 0.91 |
| Ped Bike Factor | | | | |
| Frt | | | 0.981 | |
| Flt Protected | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3467 | 5038 | 0 |
| Flt Permitted | | 0.950 | | |
| Satd. Flow (perm) | 0 | 3467 | 5038 | 0 |
| Right Turn on Red | | | | Yes |
| Satd. Flow (RTOR) | | | 18 | |
| Link Speed (mph) | | | 40 | |
| Link Distance (ft) | | | 608 | |
| Travel Time (s) | | | 10.4 | |
| Confl. Peds. (#/hr) | | | | |
| Peak Hour Factor | 0.94 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 3 | 329 | 917 | 136 |
| Shared Lane Traffic (%) | | | | |
| Lane Group Flow (vph) | 0 | 332 | 1053 | 0 |
| Turn Type | Prot | Prot | NA | |
| Protected Phases | 1 | 1 | 6 | |
| Permitted Phases | | | | |
| Detector Phase | 1 | 1 | 6 | |
| Switch Phase | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | |
| Minimum Split (s) | 12.1 | 12.1 | 32.1 | |
| Total Split (s) | 30.0 | 30.0 | 75.0 | |
| Total Split (%) | 16.7% | 16.7% | 41.7% | |
| Maximum Green (s) | 23.1 | 23.1 | 68.1 | |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | |
| All-Red Time (s) | 3.0 | 3.0 | 3.0 | |
| Lost Time Adjust (s) | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 6.9 | 6.9 | |
| Lead/Lag | Lead | Lead | Lag | |
| Lead-Lag Optimize? | Yes | Yes | Yes | |
| Vehicle Extension (s) | 2.4 | 2.4 | 2.4 | |
| Recall Mode | None | None | C-Max | |
| Walk Time (s) | | | 7.0 | |
| Flash Don't Walk (s) | | | 17.0 | |
| Pedestrian Calls (#/hr) | | | 0 | |
| Act Effct Green (s) | | 21.9 | 80.8 | |
| Actuated g/C Ratio | | 0.12 | 0.45 | |
| v/c Ratio | | 0.79 | 0.46 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBU | NBL | NBT | NBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 51.0 | 86.3 | | | 107.7 | 66.7 | 13.0 | | 98.1 | 41.7 | 6.8 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | | 51.0 | 86.3 | | | 107.7 | 66.7 | 13.0 | | 98.1 | 41.7 | 6.8 |
| LOS | | D | F | | | F | E | B | | F | D | A |
| Approach Delay (s/veh) | | | 75.8 | | | | 64.1 | | | | 38.7 | |
| Approach LOS | | | E | | | | E | | | | D | |
| Queue Length 50th (ft) | | 162 | 259 | | | ~342 | 190 | 24 | | 122 | 372 | 18 |
| Queue Length 95th (ft) | | 222 | 314 | | | #545 | 241 | 122 | | 189 | 468 | 98 |
| Internal Link Dist (ft) | | | 1494 | | | | 1361 | | | | 876 | |
| Turn Bay Length (ft) | | 50 | | | | 400 | | | | 300 | | 300 |
| Base Capacity (vph) | | 368 | 816 | | | 327 | 931 | 617 | | 164 | 2141 | 828 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.51 | 0.53 | | | 1.03 | 0.36 | 0.49 | | 0.64 | 0.54 | 0.37 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 180 | | | |
| Actuated Cycle Length: 180 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 1.04 | | | |
| Intersection Signal Delay (s/veh): 50.8 | | Intersection LOS: D | |
| Intersection Capacity Utilization 88.0% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |
| ~ Volume exceeds capacity, queue is theoretically infinite. | | | |
| Queue shown is maximum after two cycles. | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 7: Niagara Falls Blvd & Brighton Rd/Maple Rd





| Lane Group | SBU | SBL | SBT | SBR |
|---|---|---|---|---|
| Control Delay (s/veh) | | 97.4 | 27.0 | |
| Queue Delay | | 0.0 | 0.0 | |
| Total Delay (s/veh) | | 97.4 | 27.0 | |
| LOS | | F | C | |
| Approach Delay (s/veh) | | | 43.9 | |
| Approach LOS | | | D | |
| Queue Length 50th (ft) | | 210 | 213 | |
| Queue Length 95th (ft) | | 227 | 256 | |
| Internal Link Dist (ft) | | | 528 | |
| Turn Bay Length (ft) | | 350 | | |
| Base Capacity (vph) | | 463 | 2271 | |
| Starvation Cap Reductn | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | 0 | |
| Storage Cap Reductn | | 0 | 0 | |
| Reduced v/c Ratio | | 0.72 | 0.46 | |

Intersection Summary


| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 9 | 2 | 15 | 83 | 7 | 89 | 1 | 6 | 1236 | 77 | 16 | 93 |
| Future Volume (vph) | 9 | 2 | 15 | 83 | 7 | 89 | 1 | 6 | 1236 | 77 | 16 | 93 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 125 | | 0 | | 330 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | | 25 |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 |
| Ped Bike Factor | | 0.99 | | 1.00 | | | | | | | | |
| Frt | | 0.922 | | | 0.861 | | | | 0.991 | | | |
| Flt Protected | | 0.983 | | 0.950 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (prot) | 0 | 1692 | 0 | 1787 | 1620 | 0 | 0 | 1787 | 5089 | 0 | 0 | 1787 |
| Flt Permitted | | 0.864 | | 0.740 | | | | 0.950 | | | | 0.950 |
| Satd. Flow (perm) | 0 | 1487 | 0 | 1390 | 1620 | 0 | 0 | 1787 | 5089 | 0 | 0 | 1787 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 15 | | | 92 | | | | 7 | | | |
| Link Speed (mph) | | 25 | | | 25 | | | | 40 | | | |
| Link Distance (ft) | | 642 | | | 490 | | | | 588 | | | |
| Travel Time (s) | | 17.5 | | | 13.4 | | | | 10.0 | | | |
| Confl. Peds. (#/hr) | | | 1 | 1 | | | | | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 9 | 2 | 15 | 86 | 7 | 92 | 1 | 6 | 1274 | 79 | 16 | 96 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 26 | 0 | 86 | 99 | 0 | 0 | 7 | 1353 | 0 | 0 | 112 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | Prot |
| Protected Phases | | 3 | | | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 1 | 1 | 6 | | 5 | 5 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 |
| Minimum Split (s) | 39.2 | 39.2 | | 39.2 | 39.2 | | 9.3 | 9.3 | 33.3 | | 9.3 | 9.3 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 35.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 21.9% |
| Maximum Green (s) | 43.8 | 43.8 | | 43.8 | 43.8 | | 28.7 | 28.7 | 68.7 | | 28.7 | 28.7 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| All-Red Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |
| Total Lost Time (s) | | 6.2 | | 6.2 | 6.2 | | | 6.3 | 6.3 | | | 6.3 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | 3.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | None |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | 26.0 | 26.0 | | 26.0 | 26.0 | | | | 20.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 10.0 | | 10.0 | 10.0 | | | 5.1 | 29.7 | | | 10.0 |
| Actuated g/C Ratio | | 0.14 | | 0.14 | 0.14 | | | 0.07 | 0.43 | | | 0.14 |
| v/c Ratio | | 0.11 | | 0.43 | 0.32 | | | 0.05 | 0.62 | | | 0.44 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 1139 | 24 |
| Future Volume (vph) | 1139 | 24 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.91 | 0.91 |
| Ped Bike Factor | | |
| Frt | 0.997 | |
| Flt Protected | | |
| Satd. Flow (prot) | 5120 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 5120 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 2 | |
| Link Speed (mph) | 40 | |
| Link Distance (ft) | 956 | |
| Travel Time (s) | 16.3 | |
| Confl. Peds. (#/hr) | | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 1174 | 25 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 1199 | 0 |
| Turn Type | NA | |
| Protected Phases | 2 | |
| Permitted Phases | | |
| Detector Phase | 2 | |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | |
| Minimum Split (s) | 33.3 | |
| Total Split (s) | 75.0 | |
| Total Split (%) | 46.9% | |
| Maximum Green (s) | 68.7 | |
| Yellow Time (s) | 4.0 | |
| All-Red Time (s) | 2.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.3 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | Yes | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | Min | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 20.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 44.3 | |
| Actuated g/C Ratio | 0.64 | |
| v/c Ratio | 0.37 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBU | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 20.4 | | 37.0 | 11.7 | | | 37.4 | 17.0 | | | 35.7 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 |
| Total Delay (s/veh) | | 20.4 | | 37.0 | 11.7 | | | 37.4 | 17.0 | | | 35.7 |
| LOS | | C | | D | B | | | D | B | | | D |
| Approach Delay (s/veh) | | 20.4 | | | 23.5 | | | | 17.1 | | | |
| Approach LOS | | C | | | C | | | | B | | | |
| Queue Length 50th (ft) | | 4 | | 33 | 3 | | | 3 | 150 | | | 43 |
| Queue Length 95th (ft) | | 28 | | 90 | 46 | | | 17 | 247 | | | 109 |
| Internal Link Dist (ft) | | 562 | | | 410 | | | | 508 | | | |
| Turn Bay Length (ft) | | | | | | | | 125 | | | | 330 |
| Base Capacity (vph) | | 983 | | 914 | 1097 | | | 770 | 4740 | | | 770 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | | 0 |
| Reduced v/c Ratio | | 0.03 | | 0.09 | 0.09 | | | 0.01 | 0.29 | | | 0.15 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 69.2 | | | |
| Natural Cycle: 85 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.62 | | | |
| Intersection Signal Delay (s/veh): 14.0 | | Intersection LOS: B | |
| Intersection Capacity Utilization 58.4% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 8: Niagara Falls Blvd & Driveway 4/Boulevard Mall Driveway





| Lane Group | SBT | SBR |
|---|---|---|
| Control Delay (s/veh) | 7.0 | |
| Queue Delay | 0.0 | |
| Total Delay (s/veh) | 7.0 | |
| LOS | A | |
| Approach Delay (s/veh) | 9.4 | |
| Approach LOS | A | |
| Queue Length 50th (ft) | 64 | |
| Queue Length 95th (ft) | 168 | |
| Internal Link Dist (ft) | 876 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 4768 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.25 | |

Intersection Summary

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 23 | 15 | 19 | 86 | 15 | 89 | 25 | 28 | 1164 | 98 | 79 | 1159 |
| Future Volume (vph) | 23 | 15 | 19 | 86 | 15 | 89 | 25 | 28 | 1164 | 98 | 79 | 1159 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | | 150 | | 0 | 250 | |
| Storage Lanes | 0 | | 0 | 1 | | 0 | | 1 | | 0 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.91 |
| Ped Bike Factor | | 0.99 | | 0.99 | | | | 1.00 | | | | 1.00 |
| Frt | | 0.954 | | | 0.871 | | | | 0.988 | | | 0.995 |
| Flt Protected | | 0.980 | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 1747 | 0 | 1787 | 1639 | 0 | 0 | 1787 | 5074 | 0 | 1787 | 5105 |
| Flt Permitted | | 0.838 | | 0.719 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 1493 | 0 | 1342 | 1639 | 0 | 0 | 1782 | 5074 | 0 | 1787 | 5105 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | 16 | | | 92 | | | | 11 | | | 4 |
| Link Speed (mph) | | 30 | | | 25 | | | | 40 | | | 40 |
| Link Distance (ft) | | 538 | | | 562 | | | | 2182 | | | 588 |
| Travel Time (s) | | 12.2 | | | 15.3 | | | | 37.2 | | | 10.0 |
| Confl. Peds. (#/hr) | | | 6 | 6 | | | | 5 | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 24 | 15 | 20 | 89 | 15 | 92 | 26 | 29 | 1200 | 101 | 81 | 1195 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 59 | 0 | 89 | 107 | 0 | 0 | 55 | 1301 | 0 | 81 | 1233 |
| Turn Type | Perm | NA | | Perm | NA | | Prot | Prot | NA | | Prot | NA |
| Protected Phases | | 3 | | | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Permitted Phases | 3 | | | 3 | | | | | | | | |
| Detector Phase | 3 | 3 | | 3 | 3 | | 5 | 5 | 2 | | 1 | 6 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 10.0 |
| Minimum Split (s) | 41.6 | 41.6 | | 41.6 | 41.6 | | 16.3 | 16.3 | 31.3 | | 16.3 | 33.3 |
| Total Split (s) | 50.0 | 50.0 | | 50.0 | 50.0 | | 35.0 | 35.0 | 75.0 | | 35.0 | 75.0 |
| Total Split (%) | 31.3% | 31.3% | | 31.3% | 31.3% | | 21.9% | 21.9% | 46.9% | | 21.9% | 46.9% |
| Maximum Green (s) | 43.4 | 43.4 | | 43.4 | 43.4 | | 28.7 | 28.7 | 68.7 | | 28.7 | 68.7 |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 |
| All-Red Time (s) | 3.4 | 3.4 | | 3.4 | 3.4 | | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.6 | | 6.6 | 6.6 | | | 6.3 | 6.3 | | 6.3 | 6.3 |
| Lead/Lag | | | | | | | Lead | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 3.5 | 3.5 | | 3.5 | 3.5 | | 2.0 | 2.0 | 4.0 | | 2.0 | 2.0 |
| Recall Mode | None | None | | None | None | | None | None | Min | | None | Min |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | | | | | 7.0 |
| Flash Don't Walk (s) | 26.0 | 26.0 | | 26.0 | 26.0 | | | | | | | 20.0 |
| Pedestrian Calls (#/hr) | 5 | 5 | | 5 | 5 | | | | | | | 0 |
| Act Effct Green (s) | | 14.1 | | 14.1 | 14.1 | | | 7.7 | 35.5 | | 9.0 | 36.6 |
| Actuated g/C Ratio | | 0.19 | | 0.19 | 0.19 | | | 0.10 | 0.47 | | 0.12 | 0.48 |
| v/c Ratio | | 0.20 | | 0.36 | 0.28 | | | 0.31 | 0.55 | | 0.38 | 0.50 |




| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 37 |
| Future Volume (vph) | 37 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.91 |
| Ped Bike Factor | |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | 5 |
| Peak Hour Factor | 0.97 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 38 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 24.6 | | 34.4 | 11.3 | | | 43.5 | 17.1 | | 42.7 | 15.6 |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Delay (s/veh) | | 24.6 | | 34.4 | 11.3 | | | 43.5 | 17.1 | | 42.7 | 15.6 |
| LOS | | C | | C | B | | | D | B | | D | B |
| Approach Delay (s/veh) | | 24.6 | | | 21.8 | | | | 18.2 | | | 17.3 |
| Approach LOS | | C | | | C | | | | B | | | B |
| Queue Length 50th (ft) | | 17 | | 36 | 6 | | | 23 | 146 | | 34 | 131 |
| Queue Length 95th (ft) | | 58 | | 98 | 51 | | | 82 | 313 | | 109 | 282 |
| Internal Link Dist (ft) | | 458 | | | 482 | | | | 2102 | | | 508 |
| Turn Bay Length (ft) | | | | | | | | 150 | | | 250 | |
| Base Capacity (vph) | | 949 | | 847 | 1069 | | | 746 | 4465 | | 746 | 4491 |
| Starvation Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 118 |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | | 0.06 | | 0.11 | 0.10 | | | 0.07 | 0.29 | | 0.11 | 0.28 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 75.8 | | | |
| Natural Cycle: 95 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.55 | | | |
| Intersection Signal Delay (s/veh): 18.2 | | Intersection LOS: B | |
| Intersection Capacity Utilization 58.3% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 9: Niagara Falls Blvd & Treadwell Rd/Driveway 2





| Lane Group | SBR |
|---|---|
| Control Delay (s/veh) | |
| Queue Delay | |
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 2 | 447 | 603 | 0 | 3 | 249 | 688 | 69 | 0 | 641 | 68 | 35 |
| Future Volume (vph) | 2 | 447 | 603 | 0 | 3 | 249 | 688 | 69 | 0 | 641 | 68 | 35 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 370 | | 0 | | 300 | | 300 | 0 | | 0 | |
| Storage Lanes | | 2 | | 0 | | 2 | | 1 | 0 | | 0 | |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | |
| Lane Util. Factor | 0.91 | 0.97 | 0.91 | 0.91 | 0.91 | 0.97 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 |
| Ped Bike Factor | | 1.00 | | | | 1.00 | | 0.98 | | | | |
| Frt | | | | | | | | 0.850 | | 0.986 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | | | | |
| Satd. Flow (prot) | 0 | 3467 | 5136 | 0 | 0 | 3467 | 5136 | 1599 | 0 | 5064 | 0 | 0 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | | | | |
| Satd. Flow (perm) | 0 | 3463 | 5136 | 0 | 0 | 3465 | 5136 | 1575 | 0 | 5064 | 0 | 0 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | | | | | | 119 | | 10 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 40 | | |
| Link Distance (ft) | | | 623 | | | | 1468 | | | 379 | | |
| Travel Time (s) | | | 10.6 | | | | 25.0 | | | 6.5 | | |
| Confl. Peds. (#/hr) | | 2 | | 1 | | 1 | | 2 | | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 2 | 461 | 622 | 0 | 3 | 257 | 709 | 71 | 0 | 661 | 70 | 36 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 463 | 622 | 0 | 0 | 260 | 709 | 71 | 0 | 731 | 0 | 0 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | Perm | | NA | | Prot |
| Protected Phases | 3 | 3 | 8 | | 7 | 7 | 4 | | | 2 | | 1 |
| Permitted Phases | | | | | | | | 4 | | | | |
| Detector Phase | 3 | 3 | 8 | | 7 | 7 | 4 | 4 | | 2 | | 1 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 6.0 | | 3.0 | 3.0 | 6.0 | 6.0 | | 10.0 | | 3.0 |
| Minimum Split (s) | 10.3 | 10.3 | 48.0 | | 10.3 | 10.3 | 48.0 | 48.0 | | 58.2 | | 12.3 |
| Total Split (s) | 37.0 | 37.0 | 48.0 | | 37.0 | 37.0 | 48.0 | 48.0 | | 68.0 | | 37.0 |
| Total Split (%) | 19.5% | 19.5% | 25.3% | | 19.5% | 19.5% | 25.3% | 25.3% | | 35.8% | | 19.5% |
| Maximum Green (s) | 29.7 | 29.7 | 40.7 | | 29.7 | 29.7 | 40.7 | 40.7 | | 59.8 | | 28.8 |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 4.0 |
| All-Red Time (s) | 3.3 | 3.3 | 3.3 | | 3.3 | 3.3 | 3.3 | 3.3 | | 4.2 | | 4.2 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.0 | | |
| Total Lost Time (s) | | 7.3 | 7.3 | | | 7.3 | 7.3 | 7.3 | | 8.2 | | |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | Lag | | Lag | | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | Yes | | Yes | | Yes |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | | 2.0 | 2.0 | 4.0 | 4.0 | | 4.0 | | 2.0 |
| Recall Mode | None | None | None | | None | None | None | None | | C-Min | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | 7.0 | | 7.0 | | |
| Flash Don't Walk (s) | | | 30.0 | | | | 30.0 | 30.0 | | 39.0 | | |
| Pedestrian Calls (#/hr) | | | 1 | | | | 2 | 2 | | 0 | | |
| Act Effct Green (s) | | 31.8 | 48.0 | | | 18.6 | 34.8 | 34.8 | | 73.7 | | |
| Actuated g/C Ratio | | 0.17 | 0.25 | | | 0.10 | 0.18 | 0.18 | | 0.39 | | |
| v/c Ratio | | 0.80 | 0.48 | | | 0.77 | 0.75 | 0.18 | | 0.37 | | |




| Lane Group | SBL | SBT | SBR |
|---|---|---|---|
| Lane Configurations | | | |
| Traffic Volume (vph) | 219 | 621 | 459 |
| Future Volume (vph) | 219 | 621 | 459 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 |
| Storage Length (ft) | 450 | | 0 |
| Storage Lanes | 2 | | 1 |
| Taper Length (ft) | 25 | | |
| Lane Util. Factor | 0.97 | 0.95 | 1.00 |
| Ped Bike Factor | | | |
| Frt | | | 0.850 |
| Flt Protected | 0.950 | | |
| Satd. Flow (prot) | 3467 | 3574 | 1599 |
| Flt Permitted | 0.950 | | |
| Satd. Flow (perm) | 3467 | 3574 | 1599 |
| Right Turn on Red | | | Yes |
| Satd. Flow (RTOR) | | | 445 |
| Link Speed (mph) | | 40 | |
| Link Distance (ft) | | 2182 | |
| Travel Time (s) | | 37.2 | |
| Confl. Peds. (#/hr) | | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% |
| Adj. Flow (vph) | 226 | 640 | 473 |
| Shared Lane Traffic (%) | | | |
| Lane Group Flow (vph) | 262 | 640 | 473 |
| Turn Type | Prot | NA | Perm |
| Protected Phases | 1 | 6 | |
| Permitted Phases | | | 6 |
| Detector Phase | 1 | 6 | 6 |
| Switch Phase | | | |
| Minimum Initial (s) | 3.0 | 10.0 | 10.0 |
| Minimum Split (s) | 12.3 | 58.2 | 58.2 |
| Total Split (s) | 37.0 | 105.0 | 105.0 |
| Total Split (%) | 19.5% | 55.3% | 55.3% |
| Maximum Green (s) | 28.8 | 96.8 | 96.8 |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 |
| All-Red Time (s) | 4.2 | 4.2 | 4.2 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 8.2 | 8.2 | 8.2 |
| Lead/Lag | Lead | | |
| Lead-Lag Optimize? | Yes | | |
| Vehicle Extension (s) | 2.0 | 4.0 | 4.0 |
| Recall Mode | None | C-Min | C-Min |
| Walk Time (s) | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 39.0 | 39.0 |
| Pedestrian Calls (#/hr) | | 2 | 2 |
| Act Effct Green (s) | 18.7 | 100.6 | 100.6 |
| Actuated g/C Ratio | 0.10 | 0.53 | 0.53 |
| v/c Ratio | 0.77 | 0.34 | 0.45 |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBU |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 86.5 | 61.1 | | | 98.5 | 78.7 | 1.1 | | 27.7 | | |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | 0.0 | | 0.3 | | |
| Total Delay (s/veh) | | 86.5 | 61.1 | | | 98.5 | 78.7 | 1.1 | | 28.0 | | |
| LOS | | F | E | | | F | E | A | | C | | |
| Approach Delay (s/veh) | | | 71.9 | | | | 78.3 | | | 28.0 | | |
| Approach LOS | | | E | | | | E | | | C | | |
| Queue Length 50th (ft) | | 291 | 244 | | | 166 | 312 | 0 | | 248 | | |
| Queue Length 95th (ft) | | 344 | 272 | | | 214 | 347 | 0 | | 330 | | |
| Internal Link Dist (ft) | | | 543 | | | | 1388 | | | 299 | | |
| Turn Bay Length (ft) | | 370 | | | | 300 | | 300 | | | | |
| Base Capacity (vph) | | 597 | 1304 | | | 541 | 1105 | 432 | | 1992 | | |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 636 | | |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | | |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | 0 | | 0 | | |
| Reduced v/c Ratio | | 0.78 | 0.48 | | | 0.48 | 0.64 | 0.16 | | 0.54 | | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow, Master Intersection | | | |
| Natural Cycle: 150 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.80 | | | |
| Intersection Signal Delay (s/veh): 53.3 | | Intersection LOS: D | |
| Intersection Capacity Utilization 74.7% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 10: Niagara Falls Blvd & Sheridan Dr





| Lane Group | SBL | SBT | SBR |
|---|---|---|---|
| Control Delay (s/veh) | 98.5 | 27.5 | 4.5 |
| Queue Delay | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 98.5 | 27.5 | 4.5 |
| LOS | F | C | A |
| Approach Delay (s/veh) | | 33.1 | |
| Approach LOS | | C | |
| Queue Length 50th (ft) | 167 | 237 | 17 |
| Queue Length 95th (ft) | 216 | 329 | 98 |
| Internal Link Dist (ft) | | 2102 | |
| Turn Bay Length (ft) | 450 | | |
| Base Capacity (vph) | 525 | 1933 | 1069 |
| Starvation Cap Reductn | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 24 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.50 | 0.34 | 0.44 |

Intersection Summary



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 191 | 134 | 48 | 178 | 90 | 2 | 101 | 745 | 56 | 87 | 767 |
| Future Volume (vph) | 0 | 191 | 134 | 48 | 178 | 90 | 2 | 101 | 745 | 56 | 87 | 767 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 100 | 200 | | 0 | | 250 | | 0 | 0 | |
| Storage Lanes | 0 | | 1 | 1 | | 0 | | 1 | | 0 | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | | 25 | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 |
| Ped Bike Factor | | | | | 1.00 | | | | | | | |
| Frt | | | 0.850 | | 0.949 | | | | 0.990 | | | 0.993 |
| Flt Protected | | | | 0.950 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (prot) | 0 | 3505 | 1568 | 1752 | 3311 | 0 | 0 | 1752 | 4986 | 0 | 1752 | 3480 |
| Flt Permitted | | | | 0.505 | | | | 0.950 | | | 0.950 | |
| Satd. Flow (perm) | 0 | 3505 | 1568 | 932 | 3311 | 0 | 0 | 1752 | 4986 | 0 | 1752 | 3480 |
| Right Turn on Red | | | Yes | | | Yes | | | | Yes | | |
| Satd. Flow (RTOR) | | | 144 | | 44 | | | | 7 | | | 4 |
| Link Speed (mph) | | 30 | | | 35 | | | | 35 | | | 40 |
| Link Distance (ft) | | 718 | | | 1535 | | | | 1665 | | | 379 |
| Travel Time (s) | | 16.3 | | | 29.9 | | | | 32.4 | | | 6.5 |
| Confl. Peds. (#/hr) | 1 | | | | | 1 | | | | | | |
| Peak Hour Factor | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 | 0.93 |
| Heavy Vehicles (%) | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% |
| Adj. Flow (vph) | 0 | 205 | 144 | 52 | 191 | 97 | 2 | 109 | 801 | 60 | 94 | 825 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 205 | 144 | 52 | 288 | 0 | 0 | 111 | 861 | 0 | 94 | 867 |
| Turn Type | | NA | Perm | Perm | NA | | Prot | Prot | NA | | Prot | NA |
| Protected Phases | | 4 | | | 4 | | 1 | 1 | 2 | | 1 3 | 2 3 |
| Permitted Phases | | | 4 | 4 | | | | | | | | |
| Detector Phase | | 4 | 4 | 4 | 4 | | 1 | 1 | 2 | | 1 3 | 2 3 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | 6.0 | 6.0 | 6.0 | 6.0 | | 3.0 | 3.0 | 10.0 | | | |
| Minimum Split (s) | | 43.1 | 43.1 | 43.1 | 43.1 | | 9.8 | 9.8 | 35.8 | | | |
| Total Split (s) | | 54.0 | 54.0 | 54.0 | 54.0 | | 35.0 | 35.0 | 68.0 | | | |
| Total Split (%) | | 28.4% | 28.4% | 28.4% | 28.4% | | 18.4% | 18.4% | 35.8% | | | |
| Maximum Green (s) | | 46.9 | 46.9 | 46.9 | 46.9 | | 28.2 | 28.2 | 61.2 | | | |
| Yellow Time (s) | | 3.2 | 3.2 | 3.2 | 3.2 | | 3.9 | 3.9 | 3.9 | | | |
| All-Red Time (s) | | 3.9 | 3.9 | 3.9 | 3.9 | | 2.9 | 2.9 | 2.9 | | | |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | | |
| Total Lost Time (s) | | 7.1 | 7.1 | 7.1 | 7.1 | | | 6.8 | 6.8 | | | |
| Lead/Lag | | Lag | Lag | Lag | Lag | | Lead | Lead | Lag | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | 4.0 | | | |
| Recall Mode | | None | None | None | None | | None | None | C-Min | | | |
| Walk Time (s) | | 7.0 | 7.0 | 7.0 | 7.0 | | | | 7.0 | | | |
| Flash Don't Walk (s) | | 29.0 | 29.0 | 29.0 | 29.0 | | | | 22.0 | | | |
| Pedestrian Calls (#/hr) | | 0 | 0 | 0 | 0 | | | | 0 | | | |
| Act Effct Green (s) | | 19.8 | 19.8 | 19.8 | 19.8 | | | 16.4 | 112.9 | | 29.8 | 133.1 |
| Actuated g/C Ratio | | 0.10 | 0.10 | 0.10 | 0.10 | | | 0.09 | 0.59 | | 0.16 | 0.70 |
| v/c Ratio | | 0.56 | 0.49 | 0.54 | 0.75 | | | 0.74 | 0.29 | | 0.34 | 0.36 |

| Lane Group | SBR | Ø3 |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 39 | |
| Future Volume (vph) | 39 | |
| Ideal Flow (vphpl) | 1900 | |
| Storage Length (ft) | 0 | |
| Storage Lanes | 0 | |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | |
| Ped Bike Factor | | |
| Frt | | |
| Flt Protected | | |
| Satd. Flow (prot) | 0 | |
| Flt Permitted | | |
| Satd. Flow (perm) | 0 | |
| Right Turn on Red | Yes | |
| Satd. Flow (RTOR) | | |
| Link Speed (mph) | | |
| Link Distance (ft) | | |
| Travel Time (s) | | |
| Confl. Peds. (#/hr) | | |
| Peak Hour Factor | 0.93 | |
| Heavy Vehicles (%) | 3% | |
| Adj. Flow (vph) | 42 | |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 0 | |
| Turn Type | | |
| Protected Phases | | 3 |
| Permitted Phases | | |
| Detector Phase | | |
| Switch Phase | | |
| Minimum Initial (s) | | 3.0 |
| Minimum Split (s) | | 9.8 |
| Total Split (s) | | 33.0 |
| Total Split (%) | | 17% |
| Maximum Green (s) | | 26.2 |
| Yellow Time (s) | | 3.9 |
| All-Red Time (s) | | 2.9 |
| Lost Time Adjust (s) | | |
| Total Lost Time (s) | | |
| Lead/Lag | | Lead |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | | 2.0 |
| Recall Mode | | None |
| Walk Time (s) | | |
| Flash Don't Walk (s) | | |
| Pedestrian Calls (#/hr) | | |
| Act Effct Green (s) | | |
| Actuated g/C Ratio | | |
| v/c Ratio | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBU | NBL | NBT | NBR | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | | 86.3 | 15.5 | 99.6 | 81.9 | | | 110.8 | 20.5 | | 70.9 | 3.3 |
| Queue Delay | | 0.0 | 0.0 | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.2 |
| Total Delay (s/veh) | | 86.3 | 15.5 | 99.6 | 81.9 | | | 110.8 | 20.5 | | 70.9 | 3.4 |
| LOS | | F | B | F | F | | | F | C | | E | A |
| Approach Delay (s/veh) | | 57.1 | | | 84.6 | | | | 30.8 | | | 10.0 |
| Approach LOS | | E | | | F | | | | C | | | B |
| Queue Length 50th (ft) | | 130 | 0 | 63 | 159 | | | 138 | 186 | | 122 | 244 |
| Queue Length 95th (ft) | | 172 | 72 | 114 | 208 | | | 207 | 269 | | 189 | 156 |
| Internal Link Dist (ft) | | 638 | | | 1455 | | | | 1585 | | | 299 |
| Turn Bay Length (ft) | | | 100 | 200 | | | | 250 | | | | |
| Base Capacity (vph) | | 865 | 495 | 230 | 850 | | | 260 | 2966 | | 501 | 2674 |
| Starvation Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 | 797 |
| Spillback Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 127 | | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | 0 | | | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | | 0.24 | 0.29 | 0.23 | 0.34 | | | 0.43 | 0.30 | | 0.19 | 0.46 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 190 | | | |
| Actuated Cycle Length: 190 | | | |
| Offset: 0 (0%), Referenced to phase 2:NBSB, Start of Yellow | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.75 | | | |
| Intersection Signal Delay (s/veh): 33.7 | | Intersection LOS: C | |
| Intersection Capacity Utilization 64.6% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |


Splits and Phases: 11: Niagara Falls Blvd & Eggert Rd





| Lane Group | SBR | Ø3 |
|---|---|---|
| Control Delay (s/veh) | | |
| Queue Delay | | |
| Total Delay (s/veh) | | |
| LOS | | |
| Approach Delay (s/veh) | | |
| Approach LOS | | |
| Queue Length 50th (ft) | | |
| Queue Length 95th (ft) | | |
| Internal Link Dist (ft) | | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | | |
| Starvation Cap Reductn | | |
| Spillback Cap Reductn | | |
| Storage Cap Reductn | | |
| Reduced v/c Ratio | | |

| Intersection Summary |
|---|





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 51 | 582 | 226 | 313 | 818 | 7 | 309 | 62 | 301 | 14 | 50 | 47 |
| Future Volume (vph) | 51 | 582 | 226 | 313 | 818 | 7 | 309 | 62 | 301 | 14 | 50 | 47 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 400 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | 1.00 | | 0.98 | 1.00 | 1.00 | | 1.00 | 0.99 | | 1.00 | 0.99 | |
| Frt | | | 0.850 | | 0.999 | | | 0.876 | | | 0.927 | |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 5129 | 0 | 1787 | 1628 | 0 | 1787 | 1731 | 0 |
| Flt Permitted | 0.323 | | | 0.237 | | | 0.484 | | | 0.541 | | |
| Satd. Flow (perm) | 607 | 3574 | 1571 | 445 | 5129 | 0 | 908 | 1628 | 0 | 1017 | 1731 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 231 | | 1 | | | 219 | | | 42 | |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 25 | |
| Link Distance (ft) | | 1441 | | | 678 | | | 472 | | | 208 | |
| Travel Time (s) | | 21.8 | | | 10.3 | | | 9.2 | | | 5.7 | |
| Confl. Peds. (#/hr) | 2 | | 4 | 4 | | 2 | 2 | | 2 | 2 | | 2 |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 52 | 594 | 231 | 319 | 835 | 7 | 315 | 63 | 307 | 14 | 51 | 48 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 52 | 594 | 231 | 319 | 842 | 0 | 315 | 370 | 0 | 14 | 99 | 0 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Permitted Phases | 2 | 2 | 2 | 6 | | | 8 | | | 4 | | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | | 7 | 4 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 5.0 | | 5.0 | 10.0 | | 5.0 | 5.0 | |
| Minimum Split (s) | 10.0 | 27.6 | 27.6 | 10.0 | 27.6 | | 10.0 | 27.6 | | 10.0 | 27.6 | |
| Total Split (s) | 15.0 | 45.0 | 45.0 | 15.0 | 45.0 | | 15.0 | 25.0 | | 15.0 | 25.0 | |
| Total Split (%) | 15.0% | 45.0% | 45.0% | 15.0% | 45.0% | | 15.0% | 25.0% | | 15.0% | 25.0% | |
| Maximum Green (s) | 10.0 | 40.0 | 40.0 | 10.0 | 40.0 | | 10.0 | 20.0 | | 10.0 | 20.0 | |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Gap (s) | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | |
| Time Before Reduce (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Time To Reduce (s) | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | |
| Recall Mode | None | Min | Min | None | Min | | None | None | | None | None | |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | | 15.0 | 15.0 | | 15.0 | | | 15.0 | | | 15.0 | |
| Pedestrian Calls (#/hr) | | 4 | 4 | | 2 | | | 4 | | | 2 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Act Effct Green (s) | 24.9 | 17.1 | 17.1 | 30.7 | 25.3 | | 22.3 | 20.8 | | 15.7 | 10.4 | |
| Actuated g/C Ratio | 0.38 | 0.26 | 0.26 | 0.47 | 0.39 | | 0.34 | 0.32 | | 0.24 | 0.16 | |
| v/c Ratio | 0.14 | 0.64 | 0.40 | 0.77 | 0.43 | | 0.70 | 0.56 | | 0.04 | 0.32 | |
| Control Delay (s/veh) | 12.1 | 26.1 | 5.8 | 28.8 | 19.0 | | 27.0 | 12.2 | | 14.9 | 19.6 | |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Delay (s/veh) | 12.1 | 26.1 | 5.8 | 28.8 | 19.0 | | 27.0 | 12.2 | | 14.9 | 19.6 | |
| LOS | B | C | A | C | B | | C | B | | B | B | |
| Approach Delay (s/veh) | | 19.9 | | | 21.7 | | | 19.0 | | | 19.0 | |
| Approach LOS | | B | | | C | | | B | | | B | |
| Queue Length 50th (ft) | 10 | 111 | 0 | 75 | 102 | | 95 | 42 | | 4 | 21 | |
| Queue Length 95th (ft) | 35 | 200 | 51 | #258 | 182 | | 184 | 157 | | 15 | 63 | |
| Internal Link Dist (ft) | | 1361 | | | 598 | | | 392 | | | 128 | |
| Turn Bay Length (ft) | 200 | | 200 | 400 | | | | | | | | |
| Base Capacity (vph) | 442 | 2273 | 1083 | 421 | 3263 | | 448 | 727 | | 416 | 587 | |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | 0.12 | 0.26 | 0.21 | 0.76 | 0.26 | | 0.70 | 0.51 | | 0.03 | 0.17 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 100 | | | |
| Actuated Cycle Length: 65.6 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.77 | | | |
| Intersection Signal Delay (s/veh): 20.4 | | Intersection LOS: C | |
| Intersection Capacity Utilization 70.0% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 12: Alberta Dr/Driveway 5 & Maple Rd





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 162 | 660 | 97 | 244 | 833 | 295 | 143 | 374 | 149 | 1 | 316 | 436 |
| Future Volume (vph) | 162 | 660 | 97 | 244 | 833 | 295 | 143 | 374 | 149 | 1 | 316 | 436 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | 430 | 350 | | 0 | 150 | | 150 | | 500 | |
| Storage Lanes | 1 | | 1 | 1 | | 0 | 1 | | 1 | | 1 | |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | 0.98 | 1.00 | | | 1.00 | | | | | |
| Frt | | | 0.850 | | 0.961 | | | | 0.850 | | | |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 4935 | 0 | 1787 | 1881 | 1599 | 0 | 1787 | 1881 |
| Flt Permitted | 0.172 | | | 0.142 | | | 0.338 | | | | 0.177 | |
| Satd. Flow (perm) | 324 | 3574 | 1564 | 267 | 4935 | 0 | 636 | 1881 | 1599 | 0 | 333 | 1881 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | |
| Satd. Flow (RTOR) | | | 218 | | 79 | | | | 218 | | | |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | | 35 |
| Link Distance (ft) | | 678 | | | 748 | | | 1795 | | | | 1039 |
| Travel Time (s) | | 10.3 | | | 11.3 | | | 35.0 | | | | 20.2 |
| Confl. Peds. (#/hr) | | | 1 | 1 | | | 1 | | | | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 165 | 673 | 99 | 249 | 850 | 301 | 146 | 382 | 152 | 1 | 322 | 445 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 165 | 673 | 99 | 249 | 1151 | 0 | 146 | 382 | 152 | 0 | 323 | 445 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | | pm+pt | NA | Perm | pm+pt | pm+pt | NA |
| Protected Phases | 5 | 2 | | 1 | 6 | | 3 | 8 | | 7 | 7 | 4 |
| Permitted Phases | 2 | | 2 | 6 | | | 8 | | 8 | 4 | 4 | |
| Detector Phase | 5 | 2 | 2 | 1 | 6 | | 3 | 8 | 8 | 7 | 7 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 10.0 | 10.0 | 5.0 | 10.0 | | 5.0 | 10.0 | 10.0 | 5.0 | 5.0 | 10.0 |
| Minimum Split (s) | 10.0 | 38.0 | 38.0 | 10.0 | 38.0 | | 10.0 | 38.0 | 38.0 | 10.0 | 10.0 | 38.0 |
| Total Split (s) | 15.0 | 30.0 | 30.0 | 25.0 | 40.0 | | 15.0 | 35.0 | 35.0 | 25.0 | 25.0 | 45.0 |
| Total Split (%) | 13.0% | 26.1% | 26.1% | 21.7% | 34.8% | | 13.0% | 30.4% | 30.4% | 21.7% | 21.7% | 39.1% |
| Maximum Green (s) | 10.0 | 24.0 | 24.0 | 20.0 | 34.0 | | 10.0 | 29.0 | 29.0 | 20.0 | 20.0 | 39.0 |
| Yellow Time (s) | 3.0 | 4.0 | 4.0 | 3.0 | 4.0 | | 3.0 | 4.0 | 4.0 | 3.0 | 3.0 | 4.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 6.0 | 6.0 | 5.0 | 6.0 | | 5.0 | 6.0 | 6.0 | | 5.0 | 6.0 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | | Lead | Lag | Lag | Lead | Lead | Lag |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 |
| Minimum Gap (s) | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 |
| Time Before Reduce (s) | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 |
| Time To Reduce (s) | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 |
| Recall Mode | None | None | None | None | None | | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | | | 7.0 | 7.0 | | | 7.0 |
| Flash Don't Walk (s) | | 25.0 | 25.0 | | 25.0 | | | 25.0 | 25.0 | | | 25.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 1 | | | 0 | 0 | | | 1 |



| Lane Group | SBR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 205 |
| Future Volume (vph) | 205 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 150 |
| Storage Lanes | 1 |
| Taper Length (ft) | |
| Lane Util. Factor | 1.00 |
| Ped Bike Factor | 0.99 |
| Frt | 0.850 |
| Flt Protected | |
| Satd. Flow (prot) | 1599 |
| Flt Permitted | |
| Satd. Flow (perm) | 1578 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | 171 |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | 1 |
| Peak Hour Factor | 0.98 |
| Heavy Vehicles (%) | 1% |
| Adj. Flow (vph) | 209 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 209 |
| Turn Type | Perm |
| Protected Phases | |
| Permitted Phases | 4 |
| Detector Phase | 4 |
| Switch Phase | |
| Minimum Initial (s) | 10.0 |
| Minimum Split (s) | 38.0 |
| Total Split (s) | 45.0 |
| Total Split (%) | 39.1% |
| Maximum Green (s) | 39.0 |
| Yellow Time (s) | 4.0 |
| All-Red Time (s) | 2.0 |
| Lost Time Adjust (s) | 0.0 |
| Total Lost Time (s) | 6.0 |
| Lead/Lag | Lag |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | 4.0 |
| Minimum Gap (s) | 0.2 |
| Time Before Reduce (s) | 7.0 |
| Time To Reduce (s) | 0.5 |
| Recall Mode | None |
| Walk Time (s) | 7.0 |
| Flash Don't Walk (s) | 25.0 |
| Pedestrian Calls (#/hr) | 1 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBU | SBL | SBT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Act Effct Green (s) | 34.2 | 23.2 | 23.2 | 44.1 | 29.2 | | 36.3 | 25.6 | 25.6 | | 50.1 | 34.4 |
| Actuated g/C Ratio | 0.32 | 0.22 | 0.22 | 0.42 | 0.28 | | 0.34 | 0.24 | 0.24 | | 0.47 | 0.33 |
| v/c Ratio | 0.68 | 0.86 | 0.19 | 0.73 | 0.81 | | 0.45 | 0.84 | 0.27 | | 0.79 | 0.73 |
| Control Delay (s/veh) | 38.4 | 53.2 | 0.8 | 36.3 | 38.5 | | 22.4 | 56.0 | 2.2 | | 35.6 | 39.8 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Delay (s/veh) | 38.4 | 53.2 | 0.8 | 36.3 | 38.5 | | 22.4 | 56.0 | 2.2 | | 35.6 | 39.8 |
| LOS | D | D | A | D | D | | C | E | A | | D | D |
| Approach Delay (s/veh) | | 45.0 | | | 38.1 | | | 36.8 | | | | 31.7 |
| Approach LOS | | D | | | D | | | D | | | | C |
| Queue Length 50th (ft) | 75 | 247 | 0 | 119 | 265 | | 56 | 256 | 0 | | 139 | 271 |
| Queue Length 95th (ft) | #162 | #363 | 0 | 204 | 320 | | 100 | #415 | 12 | | #279 | 403 |
| Internal Link Dist (ft) | | 598 | | | 668 | | | 1715 | | | | 959 |
| Turn Bay Length (ft) | 250 | | 430 | 350 | | | 150 | | 150 | | 500 | |
| Base Capacity (vph) | 245 | 823 | 528 | 406 | 1665 | | 332 | 524 | 602 | | 437 | 704 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | 0.67 | 0.82 | 0.19 | 0.61 | 0.69 | | 0.44 | 0.73 | 0.25 | | 0.74 | 0.63 |

**Intersection Summary**

Area Type: Other
Cycle Length: 115
Actuated Cycle Length: 105.6
Natural Cycle: 100
Control Type: Actuated-Uncoordinated
Maximum v/c Ratio: 0.86
Intersection Signal Delay (s/veh): 37.9 Intersection LOS: D
Intersection Capacity Utilization 87.6% ICU Level of Service E
Analysis Period (min) 15
# 95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.


Splits and Phases: 13: Bailey Ave & Maple Rd





| Lane Group | SBR |
|---|---|
| Act Effct Green (s) | 34.4 |
| Actuated g/C Ratio | 0.33 |
| v/c Ratio | 0.33 |
| Control Delay (s/veh) | 8.3 |
| Queue Delay | 0.0 |
| Total Delay (s/veh) | 8.3 |
| LOS | A |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | 18 |
| Queue Length 95th (ft) | 74 |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | 150 |
| Base Capacity (vph) | 698 |
| Starvation Cap Reductn | 0 |
| Spillback Cap Reductn | 0 |
| Storage Cap Reductn | 0 |
| Reduced v/c Ratio | 0.30 |

| Intersection Summary |
|---|





| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Volume (vph) | 100 | 992 | 1221 | 180 | 235 | 146 |
| Future Volume (vph) | 100 | 992 | 1221 | 180 | 235 | 146 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 250 | | | 100 | 100 | 0 |
| Storage Lanes | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 0.91 | 0.91 | 1.00 | 1.00 |
| Frt | | | 0.981 | | | 0.850 |
| Flt Protected | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1787 | 3574 | 5038 | 0 | 1787 | 1599 |
| Flt Permitted | 0.950 | | | | 0.950 | |
| Satd. Flow (perm) | 1787 | 3574 | 5038 | 0 | 1787 | 1599 |
| Right Turn on Red | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | 43 | | | 159 |
| Link Speed (mph) | | 35 | 45 | | 30 | |
| Link Distance (ft) | | 748 | 466 | | 1444 | |
| Travel Time (s) | | 14.6 | 7.1 | | 32.8 | |
| Peak Hour Factor | 0.92 | 0.92 | 0.92 | 0.92 | 0.92 | 0.92 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 109 | 1078 | 1327 | 196 | 255 | 159 |
| Shared Lane Traffic (%) | | | | | | |
| Lane Group Flow (vph) | 109 | 1078 | 1523 | 0 | 255 | 159 |
| Turn Type | Prot | NA | NA | | Prot | custom |
| Protected Phases | 5 | 2 | 6 | | 4 | 4 |
| Permitted Phases | | | | | | 6 |
| Detector Phase | 5 | 2 | 6 | | 4 | 4 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 4.0 | 4.0 | 4.0 | | 4.0 | 4.0 |
| Minimum Split (s) | 9.0 | 27.0 | 27.0 | | 27.0 | 27.0 |
| Total Split (s) | 15.0 | 95.0 | 80.0 | | 25.0 | 25.0 |
| Total Split (%) | 12.5% | 79.2% | 66.7% | | 20.8% | 20.8% |
| Maximum Green (s) | 10.0 | 90.0 | 75.0 | | 20.0 | 20.0 |
| Yellow Time (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 5.0 | 5.0 | 5.0 | | 5.0 | 5.0 |
| Lead/Lag | Lead | | Lag | | | |
| Lead-Lag Optimize? | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | Min | Min | Min | | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 11.0 | 11.0 | | 11.0 | 11.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 0 | 0 |
| Act Effct Green (s) | 9.4 | 47.9 | 33.5 | | 16.7 | 55.3 |
| Actuated g/C Ratio | 0.13 | 0.64 | 0.45 | | 0.22 | 0.74 |
| v/c Ratio | 0.49 | 0.47 | 0.67 | | 0.64 | 0.13 |
| Control Delay (s/veh) | 41.8 | 7.9 | 17.6 | | 35.9 | 0.7 |
| Queue Delay | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |

| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 41.8 | 7.9 | 17.6 | | 35.9 | 0.7 |
| LOS | D | A | B | | D | A |
| Approach Delay (s/veh) | | 11.0 | 17.6 | | 22.4 | |
| Approach LOS | | B | B | | C | |
| Queue Length 50th (ft) | 48 | 121 | 195 | | 108 | 0 |
| Queue Length 95th (ft) | 111 | 175 | 256 | | 209 | 11 |
| Internal Link Dist (ft) | | 668 | 386 | | 1364 | |
| Turn Bay Length (ft) | 250 | | | | 100 | |
| Base Capacity (vph) | 244 | 3574 | 4782 | | 488 | 1294 |
| Starvation Cap Reductn | 0 | 0 | 173 | | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | | 0 | 0 |
| Reduced v/c Ratio | 0.45 | 0.30 | 0.33 | | 0.52 | 0.12 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 74.9 | | | |
| Natural Cycle: 65 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.67 | | | |
| Intersection Signal Delay (s/veh): 15.7 | | Intersection LOS: B | |
| Intersection Capacity Utilization 58.7% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 14: Maple Rd & Bowmart Parkway







| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 0 | 1178 | 14 | 9 | 1436 | 0 | 22 | 0 | 10 | 0 | 1 | 2 |
| Future Volume (vph) | 0 | 1178 | 14 | 9 | 1436 | 0 | 22 | 0 | 10 | 0 | 1 | 2 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 150 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 0 | | 0 | 1 | | 0 | 0 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.998 | | | | | | 0.956 | | | 0.900 | |
| Flt Protected | | | | 0.950 | | | | 0.967 | | | | |
| Satd. Flow (prot) | 0 | 3567 | 0 | 1787 | 3574 | 0 | 0 | 1739 | 0 | 1881 | 1693 | 0 |
| Flt Permitted | | | | 0.950 | | | | | | | | |
| Satd. Flow (perm) | 0 | 3567 | 0 | 1787 | 3574 | 0 | 0 | 1798 | 0 | 1881 | 1693 | 0 |
| Right Turn on Red | | | No | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | | | | 59 | | | 2 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 10 | |
| Link Distance (ft) | | 466 | | | 1563 | | | 418 | | | 259 | |
| Travel Time (s) | | 9.1 | | | 30.4 | | | 9.5 | | | 17.7 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 0 | 1240 | 15 | 9 | 1512 | 0 | 23 | 0 | 11 | 0 | 1 | 2 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 1255 | 0 | 9 | 1512 | 0 | 0 | 34 | 0 | 0 | 3 | 0 |
| Turn Type | | NA | | Prot | NA | | Perm | NA | | Perm | NA | |
| Protected Phases | | 2 | | 1 | 6 | | | 4 | | | 8 | |
| Permitted Phases | | | | | | | 4 | | | 8 | | |
| Detector Phase | | 2 | | 1 | 6 | | 4 | 4 | | 8 | 8 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Minimum Split (s) | | 27.0 | | 9.5 | 27.0 | | 27.0 | 27.0 | | 42.0 | 42.0 | |
| Total Split (s) | | 60.0 | | 20.0 | 80.0 | | 40.0 | 40.0 | | 40.0 | 40.0 | |
| Total Split (%) | | 50.0% | | 16.7% | 66.7% | | 33.3% | 33.3% | | 33.3% | 33.3% | |
| Maximum Green (s) | | 55.0 | | 15.5 | 75.0 | | 35.0 | 35.0 | | 35.0 | 35.0 | |
| Yellow Time (s) | | 3.0 | | 3.5 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | | 2.0 | | 1.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | 4.5 | 5.0 | | | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | Lag | | Lead | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | | 4.0 | | 3.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Gap (s) | | 0.2 | | 3.0 | 0.2 | | 0.2 | 0.2 | | 0.2 | 0.2 | |
| Time Before Reduce (s) | | 7.0 | | 0.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Time To Reduce (s) | | 0.5 | | 0.0 | 0.5 | | 0.5 | 0.5 | | 0.5 | 0.5 | |
| Recall Mode | | Min | | None | Min | | None | None | | None | None | |
| Walk Time (s) | | | | | 7.0 | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | | | 30.0 | | | | | 30.0 | 30.0 | |
| Pedestrian Calls (#/hr) | | | | | 0 | | | | | 0 | 0 | |
| Act Effct Green (s) | | 38.3 | | 6.1 | 40.0 | | | 7.0 | | | 7.0 | |
| Actuated g/C Ratio | | 0.84 | | 0.13 | 0.88 | | | 0.15 | | | 0.15 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| v/c Ratio | | 0.42 | | 0.04 | 0.48 | | | 0.10 | | | 0.01 | |
| Control Delay (s/veh) | | 4.7 | | 22.3 | 3.0 | | | 4.7 | | | 18.3 | |
| Queue Delay | | 0.0 | | 0.0 | 0.0 | | | 0.0 | | | 0.0 | |
| Total Delay (s/veh) | | 4.7 | | 22.3 | 3.0 | | | 4.7 | | | 18.3 | |
| LOS | | A | | C | A | | | A | | | B | |
| Approach Delay (s/veh) | | 4.7 | | | 3.1 | | | 4.7 | | | 18.3 | |
| Approach LOS | | A | | | A | | | A | | | B | |
| Queue Length 50th (ft) | | 0 | | 2 | 0 | | | 0 | | | 0 | |
| Queue Length 95th (ft) | | 223 | | 14 | 151 | | | 13 | | | 7 | |
| Internal Link Dist (ft) | | 386 | | | 1483 | | | 338 | | | 179 | |
| Turn Bay Length (ft) | | | | 150 | | | | | | | | |
| Base Capacity (vph) | | 3514 | | 638 | 3574 | | | 1462 | | | 1366 | |
| Starvation Cap Reductn | | 3 | | 0 | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | | 0.36 | | 0.01 | 0.42 | | | 0.02 | | | 0.00 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 120 | | | |
| Actuated Cycle Length: 45.4 | | | |
| Natural Cycle: 90 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.48 | | | |
| Intersection Signal Delay (s/veh): 3.8 | | Intersection LOS: A | |
| Intersection Capacity Utilization 56.5% | | ICU Level of Service B | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 15: Hillcrest Dr/Driveway 6 & Maple Rd







| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 377 | 700 | 87 | 80 | 747 | 123 | 111 | 278 | 104 | 186 | 282 | 442 |
| Future Volume (vph) | 377 | 700 | 87 | 80 | 747 | 123 | 111 | 278 | 104 | 186 | 282 | 442 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 200 | | 200 | 100 | | 0 | 150 | | 150 | 200 | | 0 |
| Storage Lanes | 1 | | 1 | 1 | | 1 | 1 | | 1 | 1 | | 1 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | 0.97 | 1.00 | | | 1.00 | | | | | 0.99 |
| Frt | | | 0.850 | | | 0.850 | | | 0.850 | | | 0.850 |
| Flt Protected | 0.950 | | | 0.950 | | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 1787 | 3574 | 1599 | 1787 | 3574 | 1599 | 1787 | 1881 | 1599 | 1787 | 1881 | 1599 |
| Flt Permitted | 0.175 | | | 0.380 | | | 0.329 | | | 0.255 | | |
| Satd. Flow (perm) | 329 | 3574 | 1557 | 713 | 3574 | 1599 | 618 | 1881 | 1599 | 480 | 1881 | 1576 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | 132 | | | 185 | | | 187 | | | 418 |
| Link Speed (mph) | | 45 | | | 45 | | | 35 | | | 45 | |
| Link Distance (ft) | | 1563 | | | 492 | | | 510 | | | 929 | |
| Travel Time (s) | | 23.7 | | | 7.5 | | | 9.9 | | | 14.1 | |
| Confl. Peds. (#/hr) | | | 3 | 3 | | | 2 | | | | | 2 |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 385 | 714 | 89 | 82 | 762 | 126 | 113 | 284 | 106 | 190 | 288 | 451 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 385 | 714 | 89 | 82 | 762 | 126 | 113 | 284 | 106 | 190 | 288 | 451 |
| Turn Type | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm | pm+pt | NA | Perm |
| Protected Phases | 1 | 6 | | 5 | 2 | | 7 | 4 | | 3 | 8 | |
| Permitted Phases | 6 | | 6 | 2 | | 2 | 4 | | 4 | 8 | | 8 |
| Detector Phase | 1 | 6 | 6 | 5 | 2 | 2 | 7 | 4 | 4 | 3 | 8 | 8 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 10.0 | 10.0 | 3.0 | 10.0 | 10.0 | 3.0 | 6.0 | 6.0 | 3.0 | 6.0 | 6.0 |
| Minimum Split (s) | 9.8 | 39.8 | 39.8 | 9.8 | 38.8 | 38.8 | 9.6 | 40.6 | 40.6 | 9.6 | 40.6 | 40.6 |
| Total Split (s) | 34.0 | 58.0 | 58.0 | 20.0 | 44.0 | 44.0 | 20.0 | 42.0 | 42.0 | 20.0 | 42.0 | 42.0 |
| Total Split (%) | 24.3% | 41.4% | 41.4% | 14.3% | 31.4% | 31.4% | 14.3% | 30.0% | 30.0% | 14.3% | 30.0% | 30.0% |
| Maximum Green (s) | 27.2 | 51.2 | 51.2 | 13.2 | 37.2 | 37.2 | 13.4 | 35.4 | 35.4 | 13.4 | 35.4 | 35.4 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| All-Red Time (s) | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 | 2.3 | 2.3 | 2.3 | 2.3 | 2.3 | 2.3 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 | 6.6 | 6.6 | 6.6 | 6.6 | 6.6 | 6.6 |
| Lead/Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag | Lead | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 | 2.0 | 4.0 | 4.0 |
| Recall Mode | None | C-Max | C-Max | None | C-Max | C-Max | None | None | None | None | None | None |
| Walk Time (s) | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 | | 7.0 | 7.0 |
| Flash Don't Walk (s) | | 26.0 | 26.0 | | 25.0 | 25.0 | | 27.0 | 27.0 | | 27.0 | 27.0 |
| Pedestrian Calls (#/hr) | | 0 | 0 | | 3 | 3 | | 0 | 0 | | 0 | 0 |
| Act Effct Green (s) | 79.6 | 65.2 | 65.2 | 53.0 | 45.4 | 45.4 | 38.0 | 27.5 | 27.5 | 42.8 | 29.9 | 29.9 |
| Actuated g/C Ratio | 0.57 | 0.47 | 0.47 | 0.38 | 0.32 | 0.32 | 0.27 | 0.20 | 0.20 | 0.31 | 0.21 | 0.21 |
| v/c Ratio | 0.82 | 0.43 | 0.11 | 0.25 | 0.66 | 0.20 | 0.44 | 0.77 | 0.23 | 0.71 | 0.72 | 0.68 |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Control Delay (s/veh) | 38.9 | 27.4 | 1.4 | 17.3 | 42.7 | 4.7 | 37.3 | 66.7 | 1.1 | 49.3 | 61.2 | 11.4 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 38.9 | 27.4 | 1.4 | 17.3 | 42.7 | 4.7 | 37.3 | 66.7 | 1.1 | 49.3 | 61.2 | 11.4 |
| LOS | D | C | A | B | D | A | D | E | A | D | E | B |
| Approach Delay (s/veh) | | 29.2 | | | 35.6 | | | 46.3 | | | 34.6 | |
| Approach LOS | | C | | | D | | | D | | | C | |
| Queue Length 50th (ft) | 211 | 224 | 0 | 25 | 328 | 7 | 73 | 248 | 0 | 128 | 246 | 24 |
| Queue Length 95th (ft) | #408 | 322 | 11 | 42 | 424 | 37 | 111 | 329 | 0 | 178 | 334 | 130 |
| Internal Link Dist (ft) | | 1483 | | | 412 | | | 430 | | | 849 | |
| Turn Bay Length (ft) | 200 | | 200 | 100 | | | 150 | | 150 | 200 | | |
| Base Capacity (vph) | 484 | 1664 | 795 | 399 | 1159 | 643 | 292 | 475 | 544 | 273 | 475 | 710 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.80 | 0.43 | 0.11 | 0.21 | 0.66 | 0.20 | 0.39 | 0.60 | 0.19 | 0.70 | 0.61 | 0.64 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 140 | | | |
| Actuated Cycle Length: 140 | | | |
| Offset: 84 (60%), Referenced to phase 2:WBTL and 6:EBTL, Start of Yellow | | | |
| Natural Cycle: 110 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.82 | | | |
| Intersection Signal Delay (s/veh): 34.7 | | Intersection LOS: C | |
| Intersection Capacity Utilization 88.8% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 16: Sweet Home Rd & Maple Rd






| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Volume (vph) | 37 | 673 | 730 | 178 | 14 | 113 |
| Future Volume (vph) | 37 | 673 | 730 | 178 | 14 | 113 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 100 | | | 115 | 0 | 0 |
| Storage Lanes | 1 | | | 1 | 1 | 1 |
| Taper Length (ft) | 25 | | | | 25 | |
| Lane Util. Factor | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 |
| Frt | | | | 0.850 | | 0.850 |
| Flt Protected | 0.950 | | | | 0.950 | |
| Satd. Flow (prot) | 1770 | 3539 | 3539 | 1583 | 1770 | 1583 |
| Flt Permitted | 0.357 | | | | 0.950 | |
| Satd. Flow (perm) | 665 | 3539 | 3539 | 1583 | 1770 | 1583 |
| Right Turn on Red | | | | Yes | | Yes |
| Satd. Flow (RTOR) | | | | | | 120 |
| Link Speed (mph) | | 45 | 45 | | 45 | |
| Link Distance (ft) | | 3286 | 644 | | 265 | |
| Travel Time (s) | | 49.8 | 9.8 | | 4.0 | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Adj. Flow (vph) | 39 | 716 | 777 | 189 | 15 | 120 |
| Shared Lane Traffic (%) | | | | | | |
| Lane Group Flow (vph) | 39 | 716 | 777 | 189 | 15 | 120 |
| Turn Type | Perm | NA | NA | custom | Prot | Perm |
| Protected Phases | | 2 | 6 | 8 6 | 8 | |
| Permitted Phases | 2 | | | 6 | | 8 |
| Detector Phase | 2 | 2 | 6 | 8 6 | 8 | 8 |
| Switch Phase | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | | 6.0 | 6.0 |
| Minimum Split (s) | 35.3 | 35.3 | 35.3 | | 13.2 | 13.2 |
| Total Split (s) | 80.0 | 80.0 | 80.0 | | 60.0 | 60.0 |
| Total Split (%) | 57.1% | 57.1% | 57.1% | | 42.9% | 42.9% |
| Maximum Green (s) | 73.7 | 73.7 | 73.7 | | 53.8 | 53.8 |
| Yellow Time (s) | 4.3 | 4.3 | 4.3 | | 4.3 | 4.3 |
| All-Red Time (s) | 2.0 | 2.0 | 2.0 | | 1.9 | 1.9 |
| Lost Time Adjust (s) | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 |
| Total Lost Time (s) | 6.3 | 6.3 | 6.3 | | 6.2 | 6.2 |
| Lead/Lag | | | | | | |
| Lead-Lag Optimize? | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 |
| Recall Mode | C-Max | C-Max | C-Max | | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | | | |
| Flash Don't Walk (s) | 22.0 | 22.0 | 22.0 | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | | | |
| Act Effct Green (s) | 119.7 | 119.7 | 119.7 | 140.0 | 7.8 | 7.8 |
| Actuated g/C Ratio | 0.86 | 0.86 | 0.86 | 1.00 | 0.06 | 0.06 |
| v/c Ratio | 0.07 | 0.24 | 0.26 | 0.12 | 0.15 | 0.60 |
| Control Delay (s/veh) | 0.5 | 1.0 | 1.1 | 0.2 | 64.9 | 22.7 |
| Queue Delay | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Delay (s/veh) | 0.5 | 1.0 | 1.1 | 0.2 | 64.9 | 22.7 |

| Lane Group | EBL | EBT | WBT | WBR | SBL | SBR |
|---|---|---|---|---|---|---|
| LOS | A | A | A | A | E | C |
| Approach Delay (s/veh) | | 1.0 | 0.9 | | 27.4 | |
| Approach LOS | | A | A | | C | |
| Queue Length 50th (ft) | 0 | 3 | 16 | 0 | 13 | 0 |
| Queue Length 95th (ft) | m2 | 11 | 18 | 0 | 36 | 62 |
| Internal Link Dist (ft) | | 3206 | 564 | | 185 | |
| Turn Bay Length (ft) | 100 | | | 115 | | |
| Base Capacity (vph) | 568 | 3025 | 3025 | 1583 | 680 | 682 |
| Starvation Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | 0 | 0 | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | 0.07 | 0.24 | 0.26 | 0.12 | 0.02 | 0.18 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 140 | | | |
| Actuated Cycle Length: 140 | | | |
| Offset: 59 (42%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.60 | | | |
| Intersection Signal Delay (s/veh): 2.9 | | Intersection LOS: A | |
| Intersection Capacity Utilization 46.2% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

m Volume for 95th percentile queue is metered by upstream signal.

Splits and Phases: 17: Maple Rd & Millersprt Hwy SB Rmps



| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 62 | 550 | 0 | 0 | 855 | 6 | 38 | 1 | 335 | 0 | 0 | 0 |
| Future Volume (vph) | 62 | 550 | 0 | 0 | 855 | 6 | 38 | 1 | 335 | 0 | 0 | 0 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 150 | | 0 | 0 | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Lanes | 1 | | 0 | 0 | | 0 | 1 | | 0 | 0 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 0.95 | 1.00 | 1.00 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | | | 0.999 | | | 0.850 | | | | |
| Flt Protected | 0.950 | | | | | | 0.950 | | | | | |
| Satd. Flow (prot) | 1787 | 3574 | 0 | 0 | 3571 | 0 | 1787 | 1599 | 0 | 0 | 0 | 0 |
| Flt Permitted | 0.299 | | | | | | 0.950 | | | | | |
| Satd. Flow (perm) | 562 | 3574 | 0 | 0 | 3571 | 0 | 1787 | 1599 | 0 | 0 | 0 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | | | | 1 | | | 258 | | | | |
| Link Speed (mph) | | 45 | | | 45 | | | 45 | | | 45 | |
| Link Distance (ft) | | 644 | | | 547 | | | 161 | | | 257 | |
| Travel Time (s) | | 9.8 | | | 8.3 | | | 2.4 | | | 3.9 | |
| Peak Hour Factor | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 | 0.94 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 66 | 585 | 0 | 0 | 910 | 6 | 40 | 1 | 356 | 0 | 0 | 0 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 66 | 585 | 0 | 0 | 916 | 0 | 40 | 357 | 0 | 0 | 0 | 0 |
| Turn Type | Perm | NA | | | NA | | Perm | NA | | | | |
| Protected Phases | | 2 | | | 6 | | | 4 | | | | |
| Permitted Phases | 2 | | | | | | 4 | | | | | |
| Detector Phase | 2 | 2 | | | 6 | | 4 | 4 | | | | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 20.0 | 20.0 | | | 20.0 | | 6.0 | 6.0 | | | | |
| Minimum Split (s) | 29.0 | 29.0 | | | 29.0 | | 23.0 | 23.0 | | | | |
| Total Split (s) | 80.0 | 80.0 | | | 80.0 | | 60.0 | 60.0 | | | | |
| Total Split (%) | 57.1% | 57.1% | | | 57.1% | | 42.9% | 42.9% | | | | |
| Maximum Green (s) | 74.0 | 74.0 | | | 74.0 | | 53.8 | 53.8 | | | | |
| Yellow Time (s) | 4.3 | 4.3 | | | 4.3 | | 4.3 | 4.3 | | | | |
| All-Red Time (s) | 1.7 | 1.7 | | | 1.7 | | 1.9 | 1.9 | | | | |
| Lost Time Adjust (s) | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | | | | |
| Total Lost Time (s) | 6.0 | 6.0 | | | 6.0 | | 6.2 | 6.2 | | | | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | | 3.0 | | 3.0 | 3.0 | | | | |
| Recall Mode | C-Max | C-Max | | | C-Max | | None | None | | | | |
| Walk Time (s) | 7.0 | 7.0 | | | 7.0 | | | | | | | |
| Flash Don't Walk (s) | 16.0 | 16.0 | | | 16.0 | | | | | | | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | 0 | | | | | | | |
| Act Effct Green (s) | 111.1 | 111.1 | | | 111.1 | | 16.7 | 16.7 | | | | |
| Actuated g/C Ratio | 0.79 | 0.79 | | | 0.79 | | 0.12 | 0.12 | | | | |
| v/c Ratio | 0.15 | 0.21 | | | 0.32 | | 0.19 | 0.85 | | | | |
| Control Delay (s/veh) | 2.2 | 1.4 | | | 5.2 | | 53.1 | 35.7 | | | | |
| Queue Delay | 0.0 | 0.0 | | | 0.0 | | 0.0 | 0.0 | | | | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | 2.2 | 1.4 | | | 5.2 | | 53.1 | 35.7 | | | | |
| LOS | A | A | | | A | | D | D | | | | |
| Approach Delay (s/veh) | | 1.5 | | | 5.2 | | | 37.5 | | | | |
| Approach LOS | | A | | | A | | | D | | | | |
| Queue Length 50th (ft) | 3 | 14 | | | 98 | | 34 | 91 | | | | |
| Queue Length 95th (ft) | 11 | 35 | | | 196 | | 64 | 195 | | | | |
| Internal Link Dist (ft) | | 564 | | | 467 | | | 81 | | | 177 | |
| Turn Bay Length (ft) | 150 | | | | | | | | | | | |
| Base Capacity (vph) | 445 | 2836 | | | 2834 | | 686 | 773 | | | | |
| Starvation Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Spillback Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Storage Cap Reductn | 0 | 0 | | | 0 | | 0 | 0 | | | | |
| Reduced v/c Ratio | 0.15 | 0.21 | | | 0.32 | | 0.06 | 0.46 | | | | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 140 | | | |
| Actuated Cycle Length: 140 | | | |
| Offset: 43 (31%), Referenced to phase 2:EBTL and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 55 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.85 | | | |
| Intersection Signal Delay (s/veh): 10.5 | | Intersection LOS: B | |
| Intersection Capacity Utilization 76.5% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 18: Millersprt Hwy NB Rmps & Maple Rd



| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 1 | 63 | 947 | 152 | 0 | 974 | 123 | 131 | 148 | 43 | 122 | 145 |
| Future Volume (vph) | 1 | 63 | 947 | 152 | 0 | 974 | 123 | 131 | 148 | 43 | 122 | 145 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 200 | | 450 | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Lanes | | 1 | | 1 | 0 | | 0 | 0 | | 0 | 0 | |
| Taper Length (ft) | | 25 | | | 25 | | | 25 | | | 25 | |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 1.00 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Ped Bike Factor | | 1.00 | | 0.99 | | 1.00 | | | 1.00 | | | 1.00 |
| Frt | | | | 0.850 | | 0.983 | | | 0.980 | | | 0.993 |
| Flt Protected | | 0.950 | | | | | | | 0.980 | | | 0.979 |
| Satd. Flow (prot) | 0 | 1770 | 5085 | 1583 | 0 | 4991 | 0 | 0 | 3392 | 0 | 0 | 3439 |
| Flt Permitted | | 0.182 | | | | | | | 0.980 | | | 0.979 |
| Satd. Flow (perm) | 0 | 339 | 5085 | 1562 | 0 | 4991 | 0 | 0 | 3391 | 0 | 0 | 3438 |
| Right Turn on Red | | | | Yes | | | Yes | | | Yes | | |
| Satd. Flow (RTOR) | | | | 170 | | 27 | | | 15 | | | 4 |
| Link Speed (mph) | | | 40 | | | 40 | | | 30 | | | 30 |
| Link Distance (ft) | | | 1892 | | | 623 | | | 1712 | | | 718 |
| Travel Time (s) | | | 32.3 | | | 10.6 | | | 38.9 | | | 16.3 |
| Confl. Peds. (#/hr) | | 2 | | 2 | 2 | | 2 | 3 | | 2 | 2 | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Adj. Flow (vph) | 1 | 66 | 997 | 160 | 0 | 1025 | 129 | 138 | 156 | 45 | 128 | 153 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 67 | 997 | 160 | 0 | 1154 | 0 | 0 | 339 | 0 | 0 | 294 |
| Turn Type | Perm | Perm | NA | Perm | | NA | | Split | NA | | Split | NA |
| Protected Phases | | | 1 | | | 1 | | 3 | 3 | | 4 | 4 |
| Permitted Phases | 1 | 1 | | 1 | | | | | | | | |
| Detector Phase | 1 | 1 | 1 | 1 | | 1 | | 3 | 3 | | 4 | 4 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 15.0 | 15.0 | 15.0 | 15.0 | | 15.0 | | 6.0 | 6.0 | | 6.0 | 6.0 |
| Minimum Split (s) | 50.0 | 50.0 | 50.0 | 50.0 | | 50.0 | | 70.9 | 70.9 | | 70.9 | 70.9 |
| Total Split (s) | 45.0 | 45.0 | 45.0 | 45.0 | | 45.0 | | 25.0 | 25.0 | | 25.0 | 25.0 |
| Total Split (%) | 47.4% | 47.4% | 47.4% | 47.4% | | 47.4% | | 26.3% | 26.3% | | 26.3% | 26.3% |
| Maximum Green (s) | 37.0 | 37.0 | 37.0 | 37.0 | | 37.0 | | 16.1 | 16.1 | | 16.1 | 16.1 |
| Yellow Time (s) | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.6 | 3.6 | | 3.6 | 3.6 |
| All-Red Time (s) | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 5.3 | 5.3 | | 5.3 | 5.3 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 |
| Total Lost Time (s) | | 8.0 | 8.0 | 8.0 | | 8.0 | | | 8.9 | | | 8.9 |
| Lead/Lag | | | | | | | | Lead | Lead | | Lag | Lag |
| Lead-Lag Optimize? | | | | | | | | Yes | Yes | | Yes | Yes |
| Vehicle Extension (s) | 4.0 | 4.0 | 4.0 | 4.0 | | 4.0 | | 3.5 | 3.5 | | 3.5 | 3.5 |
| Recall Mode | Min | Min | Min | Min | | Min | | None | None | | None | None |
| Walk Time (s) | 7.0 | 7.0 | 7.0 | 7.0 | | 7.0 | | | | | 7.0 | 7.0 |
| Flash Don't Walk (s) | 35.0 | 35.0 | 35.0 | 35.0 | | 35.0 | | | | | 55.0 | 55.0 |
| Pedestrian Calls (#/hr) | 0 | 0 | 0 | 0 | | 0 | | | | | 0 | 0 |
| Act Effct Green (s) | | 37.1 | 37.1 | 37.1 | | 37.1 | | | 13.8 | | | 13.0 |
| Actuated g/C Ratio | | 0.41 | 0.41 | 0.41 | | 0.41 | | | 0.15 | | | 0.14 |
| v/c Ratio | | 0.48 | 0.47 | 0.21 | | 0.56 | | | 0.64 | | | 0.59 |
| Control Delay (s/veh) | | 35.4 | 20.7 | 3.5 | | 21.4 | | | 40.2 | | | 40.6 |




| Lane Group | NWR |
|---|---|
| Lane Configurations | |
| Traffic Volume (vph) | 12 |
| Future Volume (vph) | 12 |
| Ideal Flow (vphpl) | 1900 |
| Storage Length (ft) | 0 |
| Storage Lanes | 0 |
| Taper Length (ft) | |
| Lane Util. Factor | 0.95 |
| Ped Bike Factor | |
| Frt | |
| Flt Protected | |
| Satd. Flow (prot) | 0 |
| Flt Permitted | |
| Satd. Flow (perm) | 0 |
| Right Turn on Red | Yes |
| Satd. Flow (RTOR) | |
| Link Speed (mph) | |
| Link Distance (ft) | |
| Travel Time (s) | |
| Confl. Peds. (#/hr) | 3 |
| Peak Hour Factor | 0.95 |
| Adj. Flow (vph) | 13 |
| Shared Lane Traffic (%) | |
| Lane Group Flow (vph) | 0 |
| Turn Type | |
| Protected Phases | |
| Permitted Phases | |
| Detector Phase | |
| Switch Phase | |
| Minimum Initial (s) | |
| Minimum Split (s) | |
| Total Split (s) | |
| Total Split (%) | |
| Maximum Green (s) | |
| Yellow Time (s) | |
| All-Red Time (s) | |
| Lost Time Adjust (s) | |
| Total Lost Time (s) | |
| Lead/Lag | |
| Lead-Lag Optimize? | |
| Vehicle Extension (s) | |
| Recall Mode | |
| Walk Time (s) | |
| Flash Don't Walk (s) | |
| Pedestrian Calls (#/hr) | |
| Act Effct Green (s) | |
| Actuated g/C Ratio | |
| v/c Ratio | |
| Control Delay (s/veh) | |

| Lane Group | EBU | EBL | EBT | EBR | WBL | WBT | WBR | SEL | SET | SER | NWL | NWT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Queue Delay | | 0.0 | 0.0 | 0.0 | | 0.0 | | | 0.0 | | | 0.0 |
| Total Delay (s/veh) | | 35.4 | 20.7 | 3.5 | | 21.4 | | | 40.2 | | | 40.6 |
| LOS | | D | C | A | | C | | | D | | | D |
| Approach Delay (s/veh) | | | 19.3 | | | 21.4 | | | 40.2 | | | 40.6 |
| Approach LOS | | | B | | | C | | | D | | | D |
| Queue Length 50th (ft) | | 28 | 149 | 0 | | 176 | | | 91 | | | 82 |
| Queue Length 95th (ft) | | #84 | 204 | 34 | | 238 | | | 141 | | | 126 |
| Internal Link Dist (ft) | | | 1812 | | | 543 | | | 1632 | | | 638 |
| Turn Bay Length (ft) | | 200 | | 450 | | | | | | | | |
| Base Capacity (vph) | | 140 | 2101 | 745 | | 2078 | | | 622 | | | 621 |
| Starvation Cap Reductn | | 0 | 0 | 0 | | 0 | | | 0 | | | 0 |
| Spillback Cap Reductn | | 0 | 0 | 0 | | 0 | | | 0 | | | 0 |
| Storage Cap Reductn | | 0 | 0 | 0 | | 0 | | | 0 | | | 0 |
| Reduced v/c Ratio | | 0.48 | 0.47 | 0.21 | | 0.56 | | | 0.55 | | | 0.47 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 95 | | | |
| Actuated Cycle Length: 89.8 | | | |
| Natural Cycle: 195 | | | |
| Control Type: Semi Act-Uncoord | | | |
| Maximum v/c Ratio: 0.64 | | | |
| Intersection Signal Delay (s/veh): 24.5 | | Intersection LOS: C | |
| Intersection Capacity Utilization 84.5% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |

# 95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 19: Eggert Rd & Sheridan Dr





| Lane Group | NWR |
|---|---|
| Queue Delay | |
| Total Delay (s/veh) | |
| LOS | |
| Approach Delay (s/veh) | |
| Approach LOS | |
| Queue Length 50th (ft) | |
| Queue Length 95th (ft) | |
| Internal Link Dist (ft) | |
| Turn Bay Length (ft) | |
| Base Capacity (vph) | |
| Starvation Cap Reductn | |
| Spillback Cap Reductn | |
| Storage Cap Reductn | |
| Reduced v/c Ratio | |

| Intersection Summary |
|---|




| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 33 | 170 | 799 | 87 | 9 | 64 | 957 | 219 | 66 | 91 | 37 | 235 |
| Future Volume (vph) | 33 | 170 | 799 | 87 | 9 | 64 | 957 | 219 | 66 | 91 | 37 | 235 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 235 | | 0 | | 240 | | 0 | 0 | | 100 | 0 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 0 | | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 0.95 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.985 | | | | 0.972 | | | 0.971 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | | 0.983 | | 0.950 |
| Satd. Flow (prot) | 0 | 1752 | 4960 | 0 | 0 | 1752 | 4895 | 0 | 0 | 3345 | 0 | 1752 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | | 0.732 | | 0.415 |
| Satd. Flow (perm) | 0 | 1752 | 4960 | 0 | 0 | 1752 | 4895 | 0 | 0 | 2491 | 0 | 766 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 17 | | | | 38 | | | 15 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1468 | | | | 969 | | | 165 | | |
| Travel Time (s) | | | 25.0 | | | | 16.5 | | | 3.8 | | |
| Peak Hour Factor | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 | 0.96 |
| Heavy Vehicles (%) | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% |
| Adj. Flow (vph) | 34 | 177 | 832 | 91 | 9 | 67 | 997 | 228 | 69 | 95 | 39 | 245 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 211 | 923 | 0 | 0 | 76 | 1225 | 0 | 0 | 203 | 0 | 245 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 6.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 11.2 | 11.2 | 22.5 | | 11.2 | 11.2 | 43.2 | | 22.5 | 22.5 | | 11.0 |
| Total Split (s) | 39.0 | 39.0 | 87.0 | | 20.0 | 20.0 | 68.0 | | 33.0 | 33.0 | | 20.0 |
| Total Split (%) | 24.4% | 24.4% | 54.4% | | 12.5% | 12.5% | 42.5% | | 20.6% | 20.6% | | 12.5% |
| Maximum Green (s) | 32.8 | 32.8 | 80.8 | | 13.8 | 13.8 | 61.8 | | 26.1 | 26.1 | | 14.0 |
| Yellow Time (s) | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | 3.6 | | 3.6 | 3.6 | | 3.2 |
| All-Red Time (s) | 2.6 | 2.6 | 2.6 | | 2.6 | 2.6 | 2.6 | | 3.3 | 3.3 | | 2.8 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | | 6.9 | | 6.0 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | | | | | | | | | Yes | Yes | | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | | | | | 7.0 | | | | | |
| Flash Don't Walk (s) | | | | | | | 30.0 | | | | | |
| Pedestrian Calls (#/hr) | | | | | | | 0 | | | | | |
| Act Effct Green (s) | | 24.5 | 81.4 | | | 12.1 | 69.0 | | | 18.0 | | 48.1 |
| Actuated g/C Ratio | | 0.15 | 0.51 | | | 0.08 | 0.43 | | | 0.11 | | 0.30 |
| v/c Ratio | | 0.79 | 0.36 | | | 0.58 | 0.57 | | | 0.70 | | 0.66 |
| Control Delay (s/veh) | | 85.1 | 24.8 | | | 107.5 | 17.9 | | | 75.4 | | 54.1 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 132 | 216 |
| Future Volume (vph) | 132 | 216 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.907 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1673 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1673 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 52 | |
| Link Speed (mph) | 35 | |
| Link Distance (ft) | 3326 | |
| Travel Time (s) | 64.8 | |
| Peak Hour Factor | 0.96 | 0.96 |
| Heavy Vehicles (%) | 3% | 3% |
| Adj. Flow (vph) | 138 | 225 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 363 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 24.9 | |
| Total Split (s) | 53.0 | |
| Total Split (%) | 33.1% | |
| Maximum Green (s) | 46.1 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.3 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.9 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 11.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 47.2 | |
| Actuated g/C Ratio | 0.30 | |
| v/c Ratio | 0.69 | |
| Control Delay (s/veh) | 49.0 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 85.1 | 24.8 | | | 107.5 | 17.9 | | | 75.4 | | 54.1 |
| LOS | | F | C | | | F | B | | | E | | D |
| Approach Delay (s/veh) | | | 36.0 | | | | 23.2 | | | 75.4 | | |
| Approach LOS | | | D | | | | C | | | E | | |
| Queue Length 50th (ft) | | 216 | 213 | | | 83 | 116 | | | 101 | | 204 |
| Queue Length 95th (ft) | | 296 | 261 | | | m139 | 256 | | | 143 | | 292 |
| Internal Link Dist (ft) | | | 1388 | | | | 889 | | | 85 | | |
| Turn Bay Length (ft) | | 235 | | | | 240 | | | | | | |
| Base Capacity (vph) | | 359 | 2643 | | | 157 | 2177 | | | 418 | | 373 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | | 0 | | 0 |
| Reduced v/c Ratio | | 0.59 | 0.35 | | | 0.48 | 0.56 | | | 0.49 | | 0.66 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 28 (18%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 90 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.79 | | | |
| Intersection Signal Delay (s/veh): 36.1 | | Intersection LOS: D | |
| Intersection Capacity Utilization 82.3% | | ICU Level of Service E | |
| Analysis Period (min) 15 | | | |
| m Volume for 95th percentile queue is metered by upstream signal. | | | |


Splits and Phases: 20: Alberta Dr & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 49.0 | |
| LOS | D | |
| Approach Delay (s/veh) | 51.0 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 284 | |
| Queue Length 95th (ft) | 406 | |
| Internal Link Dist (ft) | 3246 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 553 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.66 | |

| Intersection Summary |
|---|



| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 31 | 191 | 826 | 77 | 19 | 152 | 934 | 143 | 127 | 394 | 94 | 195 |
| Future Volume (vph) | 31 | 191 | 826 | 77 | 19 | 152 | 934 | 143 | 127 | 394 | 94 | 195 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 230 | | 0 | | 270 | | 0 | 190 | | 0 | 240 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 0.95 | 1.00 |
| Frt | | | 0.987 | | | | 0.980 | | | 0.971 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5069 | 0 | 0 | 1787 | 5033 | 0 | 1787 | 3471 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.306 | | | 0.167 |
| Satd. Flow (perm) | 0 | 1787 | 5069 | 0 | 0 | 1787 | 5033 | 0 | 576 | 3471 | 0 | 314 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 10 | | | | 19 | | | 17 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 969 | | | | 1628 | | | 537 | | |
| Travel Time (s) | | | 16.5 | | | | 27.8 | | | 12.2 | | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 32 | 197 | 852 | 79 | 20 | 157 | 963 | 147 | 131 | 406 | 97 | 201 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 229 | 931 | 0 | 0 | 177 | 1110 | 0 | 131 | 503 | 0 | 201 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | pm+pt | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 3 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 3.0 | 3.0 | 10.0 | | 3.0 | 3.0 | 10.0 | | 3.0 | 6.0 | | 3.0 |
| Minimum Split (s) | 10.0 | 10.0 | 43.5 | | 10.0 | 10.0 | 43.5 | | 10.0 | 41.0 | | 10.0 |
| Total Split (s) | 30.0 | 30.0 | 54.0 | | 38.0 | 38.0 | 62.0 | | 27.0 | 41.0 | | 27.0 |
| Total Split (%) | 18.8% | 18.8% | 33.8% | | 23.8% | 23.8% | 38.8% | | 16.9% | 25.6% | | 16.9% |
| Maximum Green (s) | 23.3 | 23.3 | 47.5 | | 31.6 | 31.6 | 55.5 | | 20.3 | 34.3 | | 20.3 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.6 | 3.6 | 3.9 | | 3.6 | 3.6 | | 3.6 |
| All-Red Time (s) | 2.8 | 2.8 | 2.6 | | 2.8 | 2.8 | 2.6 | | 3.1 | 3.1 | | 3.1 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.7 | 6.5 | | | 6.4 | 6.5 | | 6.7 | 6.7 | | 6.7 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lead | Lag | | Lead |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | 7.0 | | |
| Flash Don't Walk (s) | | | 21.0 | | | | 21.0 | | | 24.4 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | 0 | | |
| Act Effct Green (s) | | 24.9 | 64.9 | | | 21.1 | 60.8 | | 41.9 | 28.2 | | 53.4 |
| Actuated g/C Ratio | | 0.16 | 0.41 | | | 0.13 | 0.38 | | 0.26 | 0.18 | | 0.33 |
| v/c Ratio | | 0.82 | 0.45 | | | 0.75 | 0.58 | | 0.52 | 0.80 | | 0.71 |
| Control Delay (s/veh) | | 98.4 | 26.7 | | | 108.7 | 26.3 | | 43.9 | 71.2 | | 51.8 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |




| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 374 | 120 |
| Future Volume (vph) | 374 | 120 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 280 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 0.95 |
| Frt | 0.964 | |
| Flt Protected | | |
| Satd. Flow (prot) | 3446 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3446 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 25 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 495 | |
| Travel Time (s) | 11.3 | |
| Peak Hour Factor | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 386 | 124 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 510 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 6.0 | |
| Minimum Split (s) | 41.0 | |
| Total Split (s) | 41.0 | |
| Total Split (%) | 25.6% | |
| Maximum Green (s) | 34.3 | |
| Yellow Time (s) | 3.6 | |
| All-Red Time (s) | 3.1 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 6.7 | |
| Lead/Lag | Lag | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 23.6 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 34.0 | |
| Actuated g/C Ratio | 0.21 | |
| v/c Ratio | 0.68 | |
| Control Delay (s/veh) | 59.3 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 98.4 | 26.7 | | | 108.7 | 26.3 | | 43.9 | 71.2 | | 51.8 |
| LOS | | F | C | | | F | C | | D | E | | D |
| Approach Delay (s/veh) | | | 40.9 | | | | 37.6 | | | 65.6 | | |
| Approach LOS | | | D | | | | D | | | E | | |
| Queue Length 50th (ft) | | 248 | 162 | | | 165 | 376 | | 97 | 260 | | 156 |
| Queue Length 95th (ft) | | #406 | 192 | | | 220 | 460 | | 136 | 313 | | 204 |
| Internal Link Dist (ft) | | | 889 | | | | 1548 | | | 457 | | |
| Turn Bay Length (ft) | | 230 | | | | 270 | | | 190 | | | 240 |
| Base Capacity (vph) | | 287 | 2071 | | | 352 | 1985 | | 328 | 758 | | 304 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.80 | 0.45 | | | 0.50 | 0.56 | | 0.40 | 0.66 | | 0.66 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 4 (3%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.82 | | | |
| Intersection Signal Delay (s/veh): 47.0 | | Intersection LOS: D | |
| Intersection Capacity Utilization 80.4% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 21: Bailey Ave & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 59.3 | |
| LOS | E | |
| Approach Delay (s/veh) | 57.2 | |
| Approach LOS | E | |
| Queue Length 50th (ft) | 248 | |
| Queue Length 95th (ft) | 295 | |
| Internal Link Dist (ft) | 415 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 803 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.64 | |

| Intersection Summary |
|---|




| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 10 | 186 | 831 | 19 | 18 | 27 | 917 | 139 | 32 | 169 | 22 | 163 |
| Future Volume (vph) | 10 | 186 | 831 | 19 | 18 | 27 | 917 | 139 | 32 | 169 | 22 | 163 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 200 | | 0 | | 190 | | 0 | 85 | | 0 | 305 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 0 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | | 0.997 | | | | 0.980 | | | 0.983 | | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1787 | 5120 | 0 | 0 | 1787 | 5033 | 0 | 1787 | 1849 | 0 | 1787 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.577 | | | 0.268 |
| Satd. Flow (perm) | 0 | 1787 | 5120 | 0 | 0 | 1787 | 5033 | 0 | 1085 | 1849 | 0 | 504 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 2 | | | | 21 | | | 4 | | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 1628 | | | | 2376 | | | 1485 | | |
| Travel Time (s) | | | 27.8 | | | | 40.5 | | | 33.8 | | |
| Peak Hour Factor | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 10 | 190 | 848 | 19 | 18 | 28 | 936 | 142 | 33 | 172 | 22 | 166 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 200 | 867 | 0 | 0 | 46 | 1078 | 0 | 33 | 194 | 0 | 166 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | Perm | NA | | pm+pt |
| Protected Phases | 5 | 5 | 2 | | 1 | 1 | 6 | | | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | | 4 |
| Detector Phase | 5 | 5 | 2 | | 1 | 1 | 6 | | 8 | 8 | | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 6.0 | 6.0 | 25.0 | | 6.0 | 6.0 | 25.0 | | 12.0 | 12.0 | | 5.0 |
| Minimum Split (s) | 12.2 | 12.2 | 43.2 | | 12.2 | 12.2 | 43.2 | | 42.0 | 42.0 | | 12.1 |
| Total Split (s) | 21.0 | 21.0 | 60.0 | | 31.0 | 31.0 | 70.0 | | 42.0 | 42.0 | | 27.0 |
| Total Split (%) | 13.1% | 13.1% | 37.5% | | 19.4% | 19.4% | 43.8% | | 26.3% | 26.3% | | 16.9% |
| Maximum Green (s) | 14.8 | 14.8 | 53.8 | | 24.8 | 24.8 | 63.8 | | 34.9 | 34.9 | | 19.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | 3.9 | | 3.2 | 3.2 | | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | 2.3 | | 3.9 | 3.9 | | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | 7.1 | 7.1 | | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lag | Lag | | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | | Yes | Yes | | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 |
| Recall Mode | None | None | C-Min | | None | None | C-Min | | None | None | | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | 7.0 | 7.0 | | |
| Flash Don't Walk (s) | | | 17.0 | | | | 18.0 | | 27.0 | 27.0 | | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | 0 | 0 | | |
| Act Effct Green (s) | | 30.5 | 85.6 | | | 9.5 | 62.1 | | 21.8 | 21.8 | | 47.9 |
| Actuated g/C Ratio | | 0.19 | 0.54 | | | 0.06 | 0.39 | | 0.14 | 0.14 | | 0.30 |
| v/c Ratio | | 0.59 | 0.32 | | | 0.43 | 0.55 | | 0.22 | 0.76 | | 0.55 |
| Control Delay (s/veh) | | 54.7 | 37.8 | | | 84.3 | 39.7 | | 63.0 | 83.6 | | 48.6 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 144 | 150 |
| Future Volume (vph) | 144 | 150 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 0 |
| Storage Lanes | | 0 |
| Taper Length (ft) | | |
| Lane Util. Factor | 1.00 | 1.00 |
| Frt | 0.923 | |
| Flt Protected | | |
| Satd. Flow (prot) | 1736 | 0 |
| Flt Permitted | | |
| Satd. Flow (perm) | 1736 | 0 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | 38 | |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 1504 | |
| Travel Time (s) | 34.2 | |
| Peak Hour Factor | 0.98 | 0.98 |
| Heavy Vehicles (%) | 1% | 1% |
| Adj. Flow (vph) | 147 | 153 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 300 | 0 |
| Turn Type | NA | |
| Protected Phases | 4 | |
| Permitted Phases | | |
| Detector Phase | 4 | |
| Switch Phase | | |
| Minimum Initial (s) | 12.0 | |
| Minimum Split (s) | 44.1 | |
| Total Split (s) | 69.0 | |
| Total Split (%) | 43.1% | |
| Maximum Green (s) | 61.9 | |
| Yellow Time (s) | 3.2 | |
| All-Red Time (s) | 3.9 | |
| Lost Time Adjust (s) | 0.0 | |
| Total Lost Time (s) | 7.1 | |
| Lead/Lag | | |
| Lead-Lag Optimize? | | |
| Vehicle Extension (s) | 3.0 | |
| Recall Mode | None | |
| Walk Time (s) | 7.0 | |
| Flash Don't Walk (s) | 30.0 | |
| Pedestrian Calls (#/hr) | 0 | |
| Act Effct Green (s) | 47.9 | |
| Actuated g/C Ratio | 0.30 | |
| v/c Ratio | 0.55 | |
| Control Delay (s/veh) | 43.3 | |
| Queue Delay | 0.0 | |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 54.7 | 37.8 | | | 84.3 | 39.7 | | 63.0 | 83.6 | | 48.6 |
| LOS | | D | D | | | F | D | | E | F | | D |
| Approach Delay (s/veh) | | | 41.0 | | | | 41.5 | | | 80.6 | | |
| Approach LOS | | | D | | | | D | | | F | | |
| Queue Length 50th (ft) | | 195 | 302 | | | 47 | 307 | | 31 | 195 | | 135 |
| Queue Length 95th (ft) | | 304 | 362 | | | 92 | 412 | | 65 | 274 | | 179 |
| Internal Link Dist (ft) | | | 1548 | | | | 2296 | | | 1405 | | |
| Turn Bay Length (ft) | | 200 | | | | 190 | | | 85 | | | 305 |
| Base Capacity (vph) | | 340 | 2739 | | | 276 | 2090 | | 236 | 406 | | 321 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | | 0 |
| Reduced v/c Ratio | | 0.59 | 0.32 | | | 0.17 | 0.52 | | 0.14 | 0.48 | | 0.52 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 160 | | | |
| Actuated Cycle Length: 160 | | | |
| Offset: 133 (83%), Referenced to phase 2:EBT and 6:WBT, Start of Yellow | | | |
| Natural Cycle: 110 | | | |
| Control Type: Actuated-Coordinated | | | |
| Maximum v/c Ratio: 0.76 | | | |
| Intersection Signal Delay (s/veh): 45.0 | | Intersection LOS: D | |
| Intersection Capacity Utilization 80.6% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 22: Sweet Home Rd & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 43.3 | |
| LOS | D | |
| Approach Delay (s/veh) | 45.2 | |
| Approach LOS | D | |
| Queue Length 50th (ft) | 232 | |
| Queue Length 95th (ft) | 293 | |
| Internal Link Dist (ft) | 1424 | |
| Turn Bay Length (ft) | | |
| Base Capacity (vph) | 694 | |
| Starvation Cap Reductn | 0 | |
| Spillback Cap Reductn | 0 | |
| Storage Cap Reductn | 0 | |
| Reduced v/c Ratio | 0.43 | |

| Intersection Summary |
|---|


| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 2 | 256 | 717 | 29 | 21 | 71 | 655 | 51 | 59 | 403 | 108 | 96 |
| Future Volume (vph) | 2 | 256 | 717 | 29 | 21 | 71 | 655 | 51 | 59 | 403 | 108 | 96 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | | 315 | | 0 | | 330 | | 0 | 110 | | 155 | 105 |
| Storage Lanes | | 1 | | 0 | | 1 | | 0 | 1 | | 1 | 1 |
| Taper Length (ft) | | 25 | | | | 25 | | | 25 | | | 25 |
| Lane Util. Factor | 0.91 | 1.00 | 0.91 | 0.91 | 0.91 | 1.00 | 0.91 | 0.91 | 1.00 | 0.95 | 1.00 | 1.00 |
| Frt | | | 0.994 | | | | 0.989 | | | | 0.850 | |
| Flt Protected | | 0.950 | | | | 0.950 | | | 0.950 | | | 0.950 |
| Satd. Flow (prot) | 0 | 1752 | 5006 | 0 | 0 | 1752 | 4981 | 0 | 1752 | 3505 | 1568 | 1752 |
| Flt Permitted | | 0.950 | | | | 0.950 | | | 0.536 | | | 0.357 |
| Satd. Flow (perm) | 0 | 1752 | 5006 | 0 | 0 | 1752 | 4981 | 0 | 989 | 3505 | 1568 | 659 |
| Right Turn on Red | | | | Yes | | | | Yes | | | Yes | |
| Satd. Flow (RTOR) | | | 4 | | | | 8 | | | | 124 | |
| Link Speed (mph) | | | 40 | | | | 40 | | | 30 | | |
| Link Distance (ft) | | | 2376 | | | | 4032 | | | 1401 | | |
| Travel Time (s) | | | 40.5 | | | | 68.7 | | | 31.8 | | |
| Peak Hour Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Heavy Vehicles (%) | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% | 3% |
| Adj. Flow (vph) | 2 | 256 | 717 | 29 | 21 | 71 | 655 | 51 | 59 | 403 | 108 | 96 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 258 | 746 | 0 | 0 | 92 | 706 | 0 | 59 | 403 | 108 | 96 |
| Turn Type | Prot | Prot | NA | | Prot | Prot | NA | | pm+pt | NA | Perm | pm+pt |
| Protected Phases | 1 | 1 | 6 | | 5 | 5 | 2 | | 3 | 8 | | 7 |
| Permitted Phases | | | | | | | | | 8 | | 8 | 4 |
| Detector Phase | 1 | 1 | 6 | | 5 | 5 | 2 | | 3 | 8 | 8 | 7 |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | 10.0 | | 10.0 | 10.0 | 10.0 | | 3.0 | 10.0 | 10.0 | 3.0 |
| Minimum Split (s) | 16.2 | 16.2 | 43.2 | | 16.2 | 16.2 | 43.2 | | 10.1 | 44.1 | 44.1 | 10.1 |
| Total Split (s) | 30.0 | 30.0 | 37.0 | | 30.0 | 30.0 | 37.0 | | 33.0 | 45.0 | 45.0 | 33.0 |
| Total Split (%) | 20.7% | 20.7% | 25.5% | | 20.7% | 20.7% | 25.5% | | 22.8% | 31.0% | 31.0% | 22.8% |
| Maximum Green (s) | 23.8 | 23.8 | 30.8 | | 23.8 | 23.8 | 30.8 | | 25.9 | 37.9 | 37.9 | 25.9 |
| Yellow Time (s) | 3.9 | 3.9 | 3.9 | | 3.9 | 3.9 | 3.9 | | 3.2 | 3.2 | 3.2 | 3.2 |
| All-Red Time (s) | 2.3 | 2.3 | 2.3 | | 2.3 | 2.3 | 2.3 | | 3.9 | 3.9 | 3.9 | 3.9 |
| Lost Time Adjust (s) | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 |
| Total Lost Time (s) | | 6.2 | 6.2 | | | 6.2 | 6.2 | | 7.1 | 7.1 | 7.1 | 7.1 |
| Lead/Lag | Lead | Lead | Lag | | Lead | Lead | Lag | | Lead | Lag | Lag | Lead |
| Lead-Lag Optimize? | Yes | Yes | Yes | | Yes | Yes | Yes | | Yes | Yes | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 |
| Recall Mode | None | None | Min | | None | None | Min | | None | None | None | None |
| Walk Time (s) | | | 7.0 | | | | 7.0 | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | 18.0 | | | | 17.0 | | | 28.0 | 28.0 | |
| Pedestrian Calls (#/hr) | | | 0 | | | | 0 | | | 0 | 0 | |
| Act Effct Green (s) | | 20.9 | 33.6 | | | 11.8 | 20.4 | | 25.3 | 17.7 | 17.7 | 31.1 |
| Actuated g/C Ratio | | 0.22 | 0.35 | | | 0.12 | 0.21 | | 0.26 | 0.18 | 0.18 | 0.32 |
| v/c Ratio | | 0.68 | 0.42 | | | 0.43 | 0.66 | | 0.18 | 0.63 | 0.28 | 0.30 |
| Control Delay (s/veh) | | 46.4 | 26.8 | | | 49.2 | 38.4 | | 23.5 | 41.8 | 7.0 | 24.5 |
| Queue Delay | | 0.0 | 0.0 | | | 0.0 | 0.0 | | 0.0 | 0.0 | 0.0 | 0.0 |

| Lane Group | SBT | SBR |
|---|---|---|
| Lane Configurations | | |
| Traffic Volume (vph) | 361 | 326 |
| Future Volume (vph) | 361 | 326 |
| Ideal Flow (vphpl) | 1900 | 1900 |
| Storage Length (ft) | | 285 |
| Storage Lanes | | 1 |
| Taper Length (ft) | | |
| Lane Util. Factor | 0.95 | 1.00 |
| Frt | | 0.850 |
| Flt Protected | | |
| Satd. Flow (prot) | 3505 | 1568 |
| Flt Permitted | | |
| Satd. Flow (perm) | 3505 | 1568 |
| Right Turn on Red | | Yes |
| Satd. Flow (RTOR) | | 326 |
| Link Speed (mph) | 30 | |
| Link Distance (ft) | 981 | |
| Travel Time (s) | 22.3 | |
| Peak Hour Factor | 1.00 | 1.00 |
| Heavy Vehicles (%) | 3% | 3% |
| Adj. Flow (vph) | 361 | 326 |
| Shared Lane Traffic (%) | | |
| Lane Group Flow (vph) | 361 | 326 |
| Turn Type | NA | Perm |
| Protected Phases | 4 | |
| Permitted Phases | | 4 |
| Detector Phase | 4 | 4 |
| Switch Phase | | |
| Minimum Initial (s) | 10.0 | 10.0 |
| Minimum Split (s) | 44.1 | 44.1 |
| Total Split (s) | 45.0 | 45.0 |
| Total Split (%) | 31.0% | 31.0% |
| Maximum Green (s) | 37.9 | 37.9 |
| Yellow Time (s) | 3.2 | 3.2 |
| All-Red Time (s) | 3.9 | 3.9 |
| Lost Time Adjust (s) | 0.0 | 0.0 |
| Total Lost Time (s) | 7.1 | 7.1 |
| Lead/Lag | Lag | Lag |
| Lead-Lag Optimize? | Yes | Yes |
| Vehicle Extension (s) | 3.0 | 3.0 |
| Recall Mode | None | None |
| Walk Time (s) | 7.0 | 7.0 |
| Flash Don't Walk (s) | 30.0 | 30.0 |
| Pedestrian Calls (#/hr) | 0 | 0 |
| Act Effct Green (s) | 23.1 | 23.1 |
| Actuated g/C Ratio | 0.24 | 0.24 |
| v/c Ratio | 0.43 | 0.52 |
| Control Delay (s/veh) | 35.2 | 7.3 |
| Queue Delay | 0.0 | 0.0 |

| Lane Group | EBU | EBL | EBT | EBR | WBU | WBL | WBT | WBR | NBL | NBT | NBR | SBL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 46.4 | 26.8 | | | 49.2 | 38.4 | | 23.5 | 41.8 | 7.0 | 24.5 |
| LOS | | D | C | | | D | D | | C | D | A | C |
| Approach Delay (s/veh) | | | 31.8 | | | | 39.7 | | | 33.3 | | |
| Approach LOS | | | C | | | | D | | | C | | |
| Queue Length 50th (ft) | | 143 | 130 | | | 54 | 146 | | 24 | 121 | 0 | 40 |
| Queue Length 95th (ft) | | #279 | 205 | | | 116 | 214 | | 56 | 192 | 36 | 83 |
| Internal Link Dist (ft) | | | 2296 | | | | 3952 | | | 1321 | | |
| Turn Bay Length (ft) | | 315 | | | | 330 | | | 110 | | 155 | 105 |
| Base Capacity (vph) | | 444 | 1799 | | | 444 | 1639 | | 568 | 1415 | 706 | 540 |
| Starvation Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | 0 | 0 |
| Spillback Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | 0 | 0 |
| Storage Cap Reductn | | 0 | 0 | | | 0 | 0 | | 0 | 0 | 0 | 0 |
| Reduced v/c Ratio | | 0.58 | 0.41 | | | 0.21 | 0.43 | | 0.10 | 0.28 | 0.15 | 0.18 |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 145 | | | |
| Actuated Cycle Length: 96 | | | |
| Natural Cycle: 115 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.68 | | | |
| Intersection Signal Delay (s/veh): 31.7 | | Intersection LOS: C | |
| Intersection Capacity Utilization 73.8% | | ICU Level of Service D | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |


Splits and Phases: 23: Millersport Hwy & Sheridan Dr





| Lane Group | SBT | SBR |
|---|---|---|
| Total Delay (s/veh) | 35.2 | 7.3 |
| LOS | D | A |
| Approach Delay (s/veh) | 22.3 | |
| Approach LOS | C | |
| Queue Length 50th (ft) | 104 | 0 |
| Queue Length 95th (ft) | 166 | 74 |
| Internal Link Dist (ft) | 901 | |
| Turn Bay Length (ft) | | 285 |
| Base Capacity (vph) | 1415 | 827 |
| Starvation Cap Reductn | 0 | 0 |
| Spillback Cap Reductn | 0 | 0 |
| Storage Cap Reductn | 0 | 0 |
| Reduced v/c Ratio | 0.26 | 0.39 |

Intersection Summary





| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 42 | 349 | 4 | 8 | 305 | 17 | 4 | 20 | 4 | 47 | 41 | 45 |
| Future Volume (vph) | 42 | 349 | 4 | 8 | 305 | 17 | 4 | 20 | 4 | 47 | 41 | 45 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Ped Bike Factor | | | | | | | | 1.00 | | | 1.00 | |
| Frt | | 0.999 | | | 0.992 | | | 0.981 | | | 0.954 | |
| Flt Protected | | 0.995 | | | 0.999 | | | 0.993 | | | 0.983 | |
| Satd. Flow (prot) | 0 | 3450 | 0 | 0 | 3440 | 0 | 0 | 1776 | 0 | 0 | 1713 | 0 |
| Flt Permitted | | 0.892 | | | 0.944 | | | 0.943 | | | 0.871 | |
| Satd. Flow (perm) | 0 | 3093 | 0 | 0 | 3251 | 0 | 0 | 1686 | 0 | 0 | 1516 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 3 | | | 18 | | | 4 | | | 37 | |
| Link Speed (mph) | | 35 | | | 35 | | | 30 | | | 25 | |
| Link Distance (ft) | | 1535 | | | 1128 | | | 417 | | | 659 | |
| Travel Time (s) | | 29.9 | | | 22.0 | | | 9.5 | | | 18.0 | |
| Confl. Peds. (#/hr) | | | | | | | | | 5 | 5 | | |
| Peak Hour Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| Heavy Vehicles (%) | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% | 4% |
| Adj. Flow (vph) | 44 | 367 | 4 | 8 | 321 | 18 | 4 | 21 | 4 | 49 | 43 | 47 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 415 | 0 | 0 | 347 | 0 | 0 | 29 | 0 | 0 | 139 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | Perm | NA | | Perm | NA | |
| Protected Phases | | 1 | | | 1 | | | 2 | | | 2 | |
| Permitted Phases | 1 | | | 1 | | | 2 | | | 2 | | |
| Detector Phase | 1 | 1 | | 1 | 1 | | 2 | 2 | | 2 | 2 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 15.0 | 15.0 | | 15.0 | 15.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| Minimum Split (s) | 21.0 | 21.0 | | 21.0 | 21.0 | | 27.0 | 27.0 | | 27.0 | 27.0 | |
| Total Split (s) | 45.0 | 45.0 | | 45.0 | 45.0 | | 15.0 | 15.0 | | 15.0 | 15.0 | |
| Total Split (%) | 75.0% | 75.0% | | 75.0% | 75.0% | | 25.0% | 25.0% | | 25.0% | 25.0% | |
| Maximum Green (s) | 40.0 | 40.0 | | 40.0 | 40.0 | | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Yellow Time (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | | 5.0 | | | 5.0 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | Min | Min | | Min | Min | |
| Walk Time (s) | | | | | | | 7.0 | 7.0 | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | | | | | | | 15.0 | 15.0 | | 15.0 | 15.0 | |
| Pedestrian Calls (#/hr) | | | | | | | 0 | 0 | | 0 | 0 | |
| Act Effct Green (s) | | 15.2 | | | 15.2 | | | 7.6 | | | 7.6 | |
| Actuated g/C Ratio | | 0.46 | | | 0.46 | | | 0.23 | | | 0.23 | |
| v/c Ratio | | 0.29 | | | 0.23 | | | 0.07 | | | 0.37 | |
| Control Delay (s/veh) | | 6.4 | | | 5.8 | | | 9.4 | | | 11.2 | |
| Queue Delay | | 0.0 | | | 0.0 | | | 0.0 | | | 0.0 | |
| Total Delay (s/veh) | | 6.4 | | | 5.8 | | | 9.4 | | | 11.2 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| LOS | | A | | | A | | | A | | | B | |
| Approach Delay (s/veh) | | 6.4 | | | 5.8 | | | 9.4 | | | 11.2 | |
| Approach LOS | | A | | | A | | | A | | | B | |
| Queue Length 50th (ft) | | 20 | | | 15 | | | 3 | | | 14 | |
| Queue Length 95th (ft) | | 42 | | | 34 | | | 15 | | | 42 | |
| Internal Link Dist (ft) | | 1455 | | | 1048 | | | 337 | | | 579 | |
| Turn Bay Length (ft) | | | | | | | | | | | | |
| Base Capacity (vph) | | 3093 | | | 3251 | | | 518 | | | 489 | |
| Starvation Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | | 0 | | | 0 | |
| Reduced v/c Ratio | | 0.13 | | | 0.11 | | | 0.06 | | | 0.28 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 60 | | | |
| Actuated Cycle Length: 32.8 | | | |
| Natural Cycle: 50 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.37 | | | |
| Intersection Signal Delay (s/veh): 7.0 | | Intersection LOS: A | |
| Intersection Capacity Utilization 51.7% | | ICU Level of Service A | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 24: Alberta Dr & Eggert Rd






| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 40 | 204 | 95 | 38 | 236 | 133 | 85 | 381 | 36 | 121 | 360 | 42 |
| Future Volume (vph) | 40 | 204 | 95 | 38 | 236 | 133 | 85 | 381 | 36 | 121 | 360 | 42 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 0 | 150 | | 0 | 110 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 0 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 | 1.00 | 1.00 | 1.00 | 1.00 | 0.95 | 0.95 |
| Frt | | 0.958 | | | 0.951 | | | 0.987 | | | 0.984 | |
| Flt Protected | | 0.994 | | | 0.995 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 3404 | 0 | 0 | 3382 | 0 | 1787 | 1857 | 0 | 1787 | 3517 | 0 |
| Flt Permitted | | 0.846 | | | 0.879 | | 0.476 | | | 0.309 | | |
| Satd. Flow (perm) | 0 | 2897 | 0 | 0 | 2988 | 0 | 895 | 1857 | 0 | 581 | 3517 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 77 | | | 112 | | | 7 | | | 19 | |
| Link Speed (mph) | | 30 | | | 30 | | | 30 | | | 30 | |
| Link Distance (ft) | | 1128 | | | 580 | | | 922 | | | 349 | |
| Travel Time (s) | | 25.6 | | | 13.2 | | | 21.0 | | | 7.9 | |
| Peak Hour Factor | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 | 0.86 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 47 | 237 | 110 | 44 | 274 | 155 | 99 | 443 | 42 | 141 | 419 | 49 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 394 | 0 | 0 | 473 | 0 | 99 | 485 | 0 | 141 | 468 | 0 |
| Turn Type | Perm | NA | | Perm | NA | | pm+pt | NA | | pm+pt | NA | |
| Protected Phases | | 4 | | | 8 | | 5 | 2 | | 1 | 6 | |
| Permitted Phases | 4 | | | 8 | | | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | | 5 | 2 | | 1 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 10.0 | 10.0 | | 10.0 | 10.0 | | 5.0 | 10.0 | | 5.0 | 10.0 | |
| Minimum Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 10.0 | 37.0 | | 10.0 | 37.0 | |
| Total Split (s) | 32.0 | 32.0 | | 32.0 | 32.0 | | 11.0 | 37.0 | | 11.0 | 37.0 | |
| Total Split (%) | 40.0% | 40.0% | | 40.0% | 40.0% | | 13.8% | 46.3% | | 13.8% | 46.3% | |
| Maximum Green (s) | 27.0 | 27.0 | | 27.0 | 27.0 | | 6.0 | 32.0 | | 6.0 | 32.0 | |
| Yellow Time (s) | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | | 4.0 | 4.0 | |
| All-Red Time (s) | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | | 1.0 | 1.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.0 | | | 5.0 | | 5.0 | 5.0 | | 5.0 | 5.0 | |
| Lead/Lag | | | | | | | Lead | Lag | | Lead | Lag | |
| Lead-Lag Optimize? | | | | | | | Yes | Yes | | Yes | Yes | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | Min | Min | | Min | Min | | None | None | | None | None | |
| Walk Time (s) | 7.0 | 7.0 | | 7.0 | 7.0 | | | 7.0 | | | 7.0 | |
| Flash Don't Walk (s) | 20.0 | 20.0 | | 20.0 | 20.0 | | | 25.0 | | | 25.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | 0 | 0 | | | 0 | | | 0 | |
| Act Effct Green (s) | | 14.0 | | | 14.0 | | 24.5 | 20.1 | | 24.5 | 20.1 | |
| Actuated g/C Ratio | | 0.26 | | | 0.26 | | 0.46 | 0.38 | | 0.46 | 0.38 | |
| v/c Ratio | | 0.48 | | | 0.54 | | 0.19 | 0.69 | | 0.34 | 0.35 | |
| Control Delay (s/veh) | | 17.1 | | | 16.9 | | 7.1 | 20.4 | | 8.8 | 12.7 | |
| Queue Delay | | 0.0 | | | 0.0 | | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 17.1 | | | 16.9 | | 7.1 | 20.4 | | 8.8 | 12.7 | |
| LOS | | B | | | B | | A | C | | A | B | |
| Approach Delay (s/veh) | | 17.1 | | | 16.9 | | | 18.1 | | | 11.8 | |
| Approach LOS | | B | | | B | | | B | | | B | |
| Queue Length 50th (ft) | | 45 | | | 52 | | 13 | 127 | | 18 | 53 | |
| Queue Length 95th (ft) | | 94 | | | 107 | | 35 | 235 | | 47 | 93 | |
| Internal Link Dist (ft) | | 1048 | | | 500 | | | 842 | | | 269 | |
| Turn Bay Length (ft) | | | | | | | 150 | | | 110 | | |
| Base Capacity (vph) | | 1629 | | | 1694 | | 522 | 1210 | | 415 | 2294 | |
| Starvation Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.24 | | | 0.28 | | 0.19 | 0.40 | | 0.34 | 0.20 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 80 | | | |
| Actuated Cycle Length: 53.1 | | | |
| Natural Cycle: 80 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.69 | | | |
| Intersection Signal Delay (s/veh): 15.8 | | Intersection LOS: B | |
| Intersection Capacity Utilization 67.3% | | ICU Level of Service C | |
| Analysis Period (min) 15 | | | |

Splits and Phases: 25: Bailey Ave & Eggert Rd



| Intersection | |
|---|---|
| Int Delay, s/veh | 18.5 |


| Movement | EBL | EBR | NBL | NBT | SBT | SBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 35 | 281 | 257 | 790 | 907 | 23 |
| Future Vol, veh/h | 35 | 281 | 257 | 790 | 907 | 23 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Stop | Stop | Free | Free | Free | Free |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | 180 | 0 | 165 | - | - | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 96 | 96 | 96 | 96 | 96 | 96 |
| Heavy Vehicles, % | 1 | 1 | 1 | 1 | 1 | 1 |
| Mvmt Flow | 36 | 293 | 268 | 823 | 945 | 24 |

| Major/Minor | Minor2 | | Major1 | | Major2 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 2315 | 957 | 969 | 0 | - | 0 |
| Stage 1 | 957 | - | - | - | - | - |
| Stage 2 | 1358 | - | - | - | - | - |
| Critical Hdwy | 6.41 | 6.21 | 4.11 | - | - | - |
| Critical Hdwy Stg 1 | 5.41 | - | - | - | - | - |
| Critical Hdwy Stg 2 | 5.41 | - | - | - | - | - |
| Follow-up Hdwy | 3.509 | 3.309 | 2.209 | - | - | - |
| Pot Cap-1 Maneuver | 42 | 314 | 715 | - | - | - |
| Stage 1 | 375 | - | - | - | - | - |
| Stage 2 | 240 | - | - | - | - | - |
| Platoon blocked, % | | | | - | - | - |
| Mov Cap-1 Maneuver | ~ 26 | 314 | 715 | - | - | - |
| Mov Cap-2 Maneuver | ~ 26 | - | - | - | - | - |
| Stage 1 | 234 | - | - | - | - | - |
| Stage 2 | 240 | - | - | - | - | - |

| Approach | EB | NB | SB |
|---|---|---|---|
| HCM Control Delay, s/veh | $23.59 | 3.19 | 0 |
| HCM LOS | F | | |

| Minor Lane/Major Mvmt | NBL | NBT | EBLn1 | EBLn2 | SBT | SBR |
|---|---|---|---|---|---|---|
| Capacity (veh/h) | 715 | - | 26 | 314 | - | - |
| HCM Lane V/C Ratio | 0.374 | - | 1.39 | 0.932 | - | - |
| HCM Control Delay (s/veh) | 13 | - | $ 535.9 | 72.2 | - | - |
| HCM Lane LOS | B | - | F | F | - | - |
| HCM 95th %tile Q(veh) | 1.7 | - | 4.4 | 9.2 | - | - |

| Notes | | | |
|---|---|---|---|
| ~: Volume exceeds capacity | $: Delay exceeds 300s | +: Computation Not Defined | *: All major volume in platoon |




| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | | | | | | | |
| Traffic Volume (vph) | 124 | 38 | 67 | 11 | 22 | 131 | 51 | 750 | 17 | 124 | 1024 | 108 |
| Future Volume (vph) | 124 | 38 | 67 | 11 | 22 | 131 | 51 | 750 | 17 | 124 | 1024 | 108 |
| Ideal Flow (vphpl) | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 | 1900 |
| Storage Length (ft) | 0 | | 0 | 0 | | 70 | 170 | | 0 | 150 | | 0 |
| Storage Lanes | 0 | | 0 | 0 | | 1 | 1 | | 0 | 1 | | 0 |
| Taper Length (ft) | 25 | | | 25 | | | 25 | | | 25 | | |
| Lane Util. Factor | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Frt | | 0.961 | | | | 0.850 | | 0.997 | | | 0.986 | |
| Flt Protected | | 0.974 | | | 0.984 | | 0.950 | | | 0.950 | | |
| Satd. Flow (prot) | 0 | 1761 | 0 | 0 | 1851 | 1599 | 1787 | 1876 | 0 | 1787 | 1855 | 0 |
| Flt Permitted | | 0.812 | | | 0.900 | | 0.072 | | | 0.262 | | |
| Satd. Flow (perm) | 0 | 1468 | 0 | 0 | 1693 | 1599 | 135 | 1876 | 0 | 493 | 1855 | 0 |
| Right Turn on Red | | | Yes | | | Yes | | | Yes | | | Yes |
| Satd. Flow (RTOR) | | 21 | | | | 135 | | 3 | | | 12 | |
| Link Speed (mph) | | 30 | | | 30 | | | 35 | | | 35 | |
| Link Distance (ft) | | 710 | | | 507 | | | 1039 | | | 1225 | |
| Travel Time (s) | | 16.1 | | | 11.5 | | | 20.2 | | | 23.9 | |
| Peak Hour Factor | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 | 0.97 |
| Heavy Vehicles (%) | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% | 1% |
| Adj. Flow (vph) | 128 | 39 | 69 | 11 | 23 | 135 | 53 | 773 | 18 | 128 | 1056 | 111 |
| Shared Lane Traffic (%) | | | | | | | | | | | | |
| Lane Group Flow (vph) | 0 | 236 | 0 | 0 | 34 | 135 | 53 | 791 | 0 | 128 | 1167 | 0 |
| Turn Type | Perm | NA | | Perm | NA | Perm | Perm | NA | | Perm | NA | |
| Protected Phases | | 4 | | | 8 | | | 2 | | | 6 | |
| Permitted Phases | 4 | | | 8 | | 8 | 2 | | | 6 | | |
| Detector Phase | 4 | 4 | | 8 | 8 | 8 | 2 | 2 | | 6 | 6 | |
| Switch Phase | | | | | | | | | | | | |
| Minimum Initial (s) | 5.0 | 5.0 | | 5.0 | 5.0 | 5.0 | 10.0 | 10.0 | | 10.0 | 10.0 | |
| Minimum Split (s) | 33.0 | 33.0 | | 23.0 | 23.0 | 23.0 | 23.0 | 23.0 | | 32.0 | 32.0 | |
| Total Split (s) | 25.0 | 25.0 | | 25.0 | 25.0 | 25.0 | 65.0 | 65.0 | | 65.0 | 65.0 | |
| Total Split (%) | 27.8% | 27.8% | | 27.8% | 27.8% | 27.8% | 72.2% | 72.2% | | 72.2% | 72.2% | |
| Maximum Green (s) | 19.8 | 19.8 | | 19.8 | 19.8 | 19.8 | 59.4 | 59.4 | | 59.4 | 59.4 | |
| Yellow Time (s) | 3.2 | 3.2 | | 3.2 | 3.2 | 3.2 | 3.6 | 3.6 | | 3.6 | 3.6 | |
| All-Red Time (s) | 2.0 | 2.0 | | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | | 2.0 | 2.0 | |
| Lost Time Adjust (s) | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |
| Total Lost Time (s) | | 5.2 | | | 5.2 | 5.2 | 5.6 | 5.6 | | 5.6 | 5.6 | |
| Lead/Lag | | | | | | | | | | | | |
| Lead-Lag Optimize? | | | | | | | | | | | | |
| Vehicle Extension (s) | 3.0 | 3.0 | | 3.0 | 3.0 | 3.0 | 3.0 | 3.0 | | 3.0 | 3.0 | |
| Recall Mode | None | None | | None | None | None | Min | Min | | Min | Min | |
| Walk Time (s) | 7.0 | 7.0 | | | | | | | | 7.0 | 7.0 | |
| Flash Don't Walk (s) | 15.0 | 15.0 | | | | | | | | 15.0 | 15.0 | |
| Pedestrian Calls (#/hr) | 0 | 0 | | | | | | | | 0 | 0 | |
| Act Effct Green (s) | | 16.4 | | | 16.4 | 16.4 | 55.4 | 55.4 | | 55.4 | 55.4 | |
| Actuated g/C Ratio | | 0.20 | | | 0.20 | 0.20 | 0.67 | 0.67 | | 0.67 | 0.67 | |
| v/c Ratio | | 0.77 | | | 0.10 | 0.32 | 0.59 | 0.63 | | 0.39 | 0.94 | |
| Control Delay (s/veh) | | 47.2 | | | 29.2 | 7.9 | 41.1 | 11.0 | | 11.0 | 28.8 | |
| Queue Delay | | 0.0 | | | 0.0 | 0.0 | 0.0 | 0.0 | | 0.0 | 0.0 | |

| Lane Group | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Total Delay (s/veh) | | 47.2 | | | 29.2 | 7.9 | 41.1 | 11.0 | | 11.0 | 28.8 | |
| LOS | | D | | | C | A | D | B | | B | C | |
| Approach Delay (s/veh) | | 47.2 | | | 12.1 | | | 12.9 | | | 27.1 | |
| Approach LOS | | D | | | B | | | B | | | C | |
| Queue Length 50th (ft) | | 113 | | | 16 | 0 | 14 | 221 | | 28 | 504 | |
| Queue Length 95th (ft) | | #213 | | | 40 | 45 | #85 | 347 | | 69 | #905 | |
| Internal Link Dist (ft) | | 630 | | | 427 | | | 959 | | | 1145 | |
| Turn Bay Length (ft) | | | | | | 70 | 170 | | | 150 | | |
| Base Capacity (vph) | | 375 | | | 414 | 493 | 99 | 1378 | | 362 | 1365 | |
| Starvation Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Spillback Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Storage Cap Reductn | | 0 | | | 0 | 0 | 0 | 0 | | 0 | 0 | |
| Reduced v/c Ratio | | 0.63 | | | 0.08 | 0.27 | 0.54 | 0.57 | | 0.35 | 0.85 | |

| Intersection Summary | | | |
|---|---|---|---|
| Area Type: | Other | | |
| Cycle Length: 90 | | | |
| Actuated Cycle Length: 82.8 | | | |
| Natural Cycle: 100 | | | |
| Control Type: Actuated-Uncoordinated | | | |
| Maximum v/c Ratio: 0.94 | | | |
| Intersection Signal Delay (s/veh): 23.2 | | Intersection LOS: C | |
| Intersection Capacity Utilization 102.1% | | ICU Level of Service G | |
| Analysis Period (min) 15 | | | |
| # 95th percentile volume exceeds capacity, queue may be longer. | | | |
| Queue shown is maximum after two cycles. | | | |

Splits and Phases: 27: Bailey Ave & Meyer Rd



| Intersection | |
|---|---|
| Int Delay, s/veh | 5.1 |

| Movement | EBT | EBR | WBL | WBT | NBL | NBR |
|---|---|---|---|---|---|---|
| Lane Configurations | | | | | | |
| Traffic Vol, veh/h | 23 | 164 | 18 | 11 | 149 | 15 |
| Future Vol, veh/h | 23 | 164 | 18 | 11 | 149 | 15 |
| Conflicting Peds, #/hr | 0 | 0 | 0 | 0 | 0 | 0 |
| Sign Control | Free | Free | Free | Free | Stop | Stop |
| RT Channelized | - | None | - | None | - | None |
| Storage Length | - | - | - | - | 0 | - |
| Veh in Median Storage, # | 0 | - | - | 0 | 0 | - |
| Grade, % | 0 | - | - | 0 | 0 | - |
| Peak Hour Factor | 82 | 82 | 82 | 82 | 82 | 82 |
| Heavy Vehicles, % | 3 | 3 | 3 | 3 | 3 | 3 |
| Mvmt Flow | 28 | 200 | 22 | 13 | 182 | 18 |

| Major/Minor | Major1 | | Major2 | | Minor1 | |
|---|---|---|---|---|---|---|
| Conflicting Flow All | 0 | 0 | 228 | 0 | 185 | 128 |
| Stage 1 | - | - | - | - | 128 | - |
| Stage 2 | - | - | - | - | 57 | - |
| Critical Hdwy | - | - | 4.13 | - | 6.43 | 6.23 |
| Critical Hdwy Stg 1 | - | - | - | - | 5.43 | - |
| Critical Hdwy Stg 2 | - | - | - | - | 5.43 | - |
| Follow-up Hdwy | - | - | 2.227 | - | 3.527 | 3.327 |
| Pot Cap-1 Maneuver | - | - | 1334 | - | 802 | 919 |
| Stage 1 | - | - | - | - | 895 | - |
| Stage 2 | - | - | - | - | 963 | - |
| Platoon blocked, % | - | - | | - | | |
| Mov Cap-1 Maneuver | - | - | 1334 | - | 788 | 919 |
| Mov Cap-2 Maneuver | - | - | - | - | 788 | - |
| Stage 1 | - | - | - | - | 895 | - |
| Stage 2 | - | - | - | - | 947 | - |

| Approach | EB | WB | NB |
|---|---|---|---|
| HCM Control Delay, s/v | 0 | 4.81 | 11.01 |
| HCM LOS | | | B |

| Minor Lane/Major Mvmt | NBLn1 | EBT | EBR | WBL | WBT |
|---|---|---|---|---|---|
| Capacity (veh/h) | 799 | - | - | 1117 | - |
| HCM Lane V/C Ratio | 0.25 | - | - | 0.016 | - |
| HCM Control Delay (s/veh) | 11 | - | - | 7.7 | 0 |
| HCM Lane LOS | B | - | - | A | A |
| HCM 95th %tile Q(veh) | 1 | - | - | 0.1 | - |

# Mitigation Cost Backup

## SCOPING COST ESTIMATE

**Project: Niagara Falls Boulevard from Ridge Lea Road to Sheridan Road - Adaptive Signal Control**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 680 | Adaptive Signal Control | EA | $ 26,850.00 | 5 | $ 134,250.00 |
| | Maintenance & Support | EA | $ 2,100.00 | 5 | $ 10,500.00 |
| | | | | **Subtotal** | **$ 145,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 30,000 |
| | | | | **Construction Cost** | **$ 175,000** |

## SCOPING COST ESTIMATE

**Project: N Bailey / Ridge Lea Widening: From north end of CMAQ project to Niagara Falls Blvd**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 203 | Excavation - Roadway Widening | CY | $ 60.00 | 12,500 | $ 750,000.00 |
| 203 | Fill - Roadway Widening | CY | $ 60.00 | 7,550 | $ 453,000.00 |
| 209 | Erosion and Sediment Control (assume 2%) | LS | 2.0% | - | $ 262,410.00 |
| 304 | Subbase - Roadway Widening | CY | $ 100.00 | 5,100 | $ 510,000.00 |
| 404 | WMA Top - Road Overlay | TON | $ 150.00 | 2,700 | $ 405,000.00 |
| 404 | WMA Base and Binder - Roadway Widening | TON | $ 160.00 | 8,480 | $ 1,356,800.00 |
| 407 | Tack Coat | GAL | $ 10.00 | 4,600 | $ 46,000.00 |
| 490 | Production Milling | SY | $ 5.00 | 33,470 | $ 167,350.00 |
| 554 | Retaining Walls | SF | $ 100.00 | 29,080 | $ 2,908,000.00 |
| 555 | Box Culvert Extension | LS | $ 225,000.00 | 1 | $ 225,000.00 |
| 568 | Pedestrian Railing | LF | $ 150.00 | 3,635 | $ 545,250.00 |
| 603 | Storm Pipe | LF | $ 190.00 | 10,920 | $ 2,074,800.00 |
| 604 | Drainage Structures | EA | $ 8,600.00 | 52 | $ 447,200.00 |
| 605 | Underdrain | LF | $ 13.50 | 10,400 | $ 140,400.00 |
| 608 | Asphalt Driveways | SF | $ 22.00 | 27,600 | $ 607,200.00 |
| 608 | Concrete Sidewalks | SF | $ 20.00 | 48,780 | $ 975,600.00 |
| 609 | Concrete Curb | LF | $ 90.00 | 10,400 | $ 936,000.00 |
| 610 | Turf Establishment | SY | $ 17.50 | 13,870 | $ 242,725.00 |
| 611 | Tree Plantings | EA | $ 1,000.00 | 50 | $ 50,000.00 |
| 614 | Tree Removals | EA | $ 1,000.00 | 50 | $ 50,000.00 |
| 619 | Work Zone Traffic Control (assume 7%) | LS | 7.0% | - | $ 918,440.00 |
| 625 | Survey (assume 2%) | LS | 2.0% | - | $ 262,410.00 |
| 633 | Asphalt Spot Repairs | SY | $ 75.00 | 670 | $ 50,250.00 |
| 645 | Signage and Delineators (assume 1%) | LS | 1.0% | - | $ 131,210.00 |
| 663 | Hydrants | EA | $ 20,000.00 | 9 | $ 180,000.00 |
| 685 | Striping (assume 2%) | LS | 1.0% | - | $ 131,210.00 |
| | | | | **Subtotal** | **$ 14,827,000** |
| | Field Change | 5% | | + | $ 742,000 |
| | Contingencies | 30% | | + | $ 4,671,000 |
| | Mobilization | 4% | | + | $ 810,000 |
| | | | | **Subtotal** | **$ 21,050,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 3,350,000 |
| | | | | **Construction Cost** | **$ 24,400,000** |

## SCOPING COST ESTIMATE

**Project: Bowmart Parkway from Maple Road to Meyer Road - Resurfacsing**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 209 | Erosion and Sediment Control (assume 2%) | LS | 2.0% | - | $ 2,690.00 |
| 404 | WMA Top - Road Overlay | TON | $ 125.00 | 560 | $ 70,000.00 |
| 407 | Diluted Tack Coat | Gallon | $ 10.00 | 690 | $ 6,900.00 |
| 490 | Production Milling | SY | $ 5.00 | 6,810 | $ 34,050.00 |
| 619 | Work Zone Traffic Control (assume 6%) | LS | 6.0% | - | $ 8,080.00 |
| 625 | Survey (assume 2%) | LS | 2.0% | - | $ 2,690.00 |
| 633 | Asphalt Spot Repairs | SY | $ 75.00 | 140 | $ 10,500.00 |
| 645 | Signage and Delineators (assume 1%) | LS | 1.0% | - | $ 1,350.00 |
| 685 | Striping | LF | $ 2.00 | 6600 | $ 13,200.00 |
| | | | | **Subtotal** | **$ 150,000** |
| | Field Change | 5% | | + | $ 8,000 |
| | Contingencies | 30% | | + | $ 48,000 |
| | Mobilization | 4% | | + | $ 9,000 |
| | | | | **Subtotal** | **$ 215,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 40,000 |
| | | | | **Construction Cost** | **$ 255,000** |

## SCOPING COST ESTIMATE

**Project: Sheridan Drive from Niagara Falls Blvd to Millersport Highway - Revised Signal Timings and Coordination**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 680 | Traffic Signal Modification | EA | $ 2,000.00 | 4 | $ 8,000.00 |
| | | | | **Subtotal** | **$ 8,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 10,000 |
| | | | | **Construction Cost** | **$ 18,000** |

## SCOPING COST ESTIMATE

**Project: Maple Road at Sweethome - Updated Signal Timings, Striping and Signage**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 619 | Work Zone Traffic Control (assume 6%) | LS | 6.0% | - | $ 3,130.00 |
| 645 | No Turn on Red (Blank-Out overhead) | EA | $ 7,500.00 | 4 | $ 30,000.00 |
| 680 | Traffic Signal Modification | LS | $ 7,000.00 | 1 | $ 7,000.00 |
| 685 | Striping -Lines | LF | $ 2.00 | 6800 | $ 13,600.00 |
| 685 | Striping - Symbols | EA | $ 250.00 | 6 | $ 1,500.00 |
| | | | | **Subtotal** | **$ 56,000** |
| | Field Change | 5% | | + | $ 3,000 |
| | Contingencies | 30% | | + | $ 18,000 |
| | Mobilization | 4% | | + | $ 4,000 |
| | | | | **Subtotal** | **$ 81,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 20,000 |
| | | | | **Construction Cost** | **$ 101,000** |

## SCOPING COST ESTIMATE

**Project: Sherdan Drive at Sweethome - Updated Signal Timings, Striping and Signage**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 601 | Bike Boxes | SF | $ 15.65 | 300 | $ 4,695.00 |
| 619 | Work Zone Traffic Control (assume 6%) | LS | 6.0% | - | $ 3,120.00 |
| 645 | No Turn on Red (Blank-Out overhead) | EA | $ 7,500.00 | 4 | $ 30,000.00 |
| 680 | Traffic Signal Modification | LS | $ 7,000.00 | 1 | $ 7,000.00 |
| 685 | Striping | LF | $ 2.00 | 5190 | $ 10,380.00 |
| | | | | **Subtotal** | **$ 56,000** |
| | Field Change | 5% | | + | $ 3,000 |
| | Contingencies | 30% | | + | $ 18,000 |
| | Mobilization | 4% | | + | $ 4,000 |
| | | | | **Subtotal** | **$ 81,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 20,000 |
| | | | | **Construction Cost** | **$ 101,000** |

## SCOPING COST ESTIMATE

**Project: Emerson Drive and N Bailey Avenue Roundabout**
**2030 Construction**

| Item No. | Description | Units | Unit Cost | Qty | Amount |
|---|---|---|---|---|---|
| 203 | Excavation - Roadway | CY | $ 60.00 | 2,340 | $ 140,400.00 |
| 209 | Erosion and Sediment Control (assume 2%) | LS | 2.0% | - | $ 24,440.00 |
| 304 | Subbase - Roadway | CY | $ 100.00 | 1,200 | $ 120,000.00 |
| 404 | WMA Top - Road Overlay | TON | $ 125.00 | 300 | $ 37,500.00 |
| 404 | WMA Base and Binder - Roadway Widening | TON | $ 160.00 | 1,980 | $ 316,800.00 |
| 603 | Storm Pipe | LF | $ 185.00 | 1,060 | $ 196,100.00 |
| 604 | Drainage Structures | EA | $ 8,600.00 | 8 | $ 68,800.00 |
| 605 | Underdrain | LF | $ 14.00 | 1,060 | $ 14,840.00 |
| 608 | Concrete Sidewalks | SF | $ 28.00 | 5,100 | $ 142,800.00 |
| 609 | Concrete Curb | LF | $ 90.00 | 1,900 | $ 171,000.00 |
| 610 | Turf Establishment | SY | $ 15.00 | 800 | $ 12,000.00 |
| 611 | Tree Plantings | EA | $ 1,000.00 | 1 | $ 1,000.00 |
| 614 | Tree Removals | EA | $ 1,000.00 | 1 | $ 1,000.00 |
| 619 | Work Zone Traffic Control (assume 6%) | LS | 6.0% | - | $ 73,330.00 |
| 625 | Survey (assume 2%) | LS | 2.0% | - | $ 24,440.00 |
| 645 | Signage and Delineators (assume 1%) | LS | 1.0% | - | $ 12,220.00 |
| 685 | Striping (assume 2%) | LS | 1.0% | - | $ 12,220.00 |
| | | | | **Subtotal** | **$ 1,369,000** |
| | Field Change | 5% | | + | $ 69,000 |
| | Contingencies | 30% | | + | $ 432,000 |
| | Mobilization | 4% | | + | $ 75,000 |
| | | | | **Subtotal** | **$ 1,945,000** |
| | Inflation (3% compounded 5 years) | 15.9% | | + | $ 310,000 |
| | | | | **Construction Cost** | **$ 2,255,000** |

# APPENDIX D

## WATER & SEWER DATA

GROWTH PROJECTIONS – NEW SANITARY DEMAND TABLE

WATER SYSTEM DEMAND FIGURES

# APPENDIX D

**GROWTH PROJECTIONS – NEW SANITARY DEMAND TABLE**

## Growth Projections ("Full Build-Out") - New Sanitary Demand

**PREPARED FOR THE "BOULEVARD CENTRAL DISTRICT SDGEIS**

June 19, 2019 (DGEIS)

June 6, 2024 (SDGEIS)

| | | TRAFFIC ANALYSIS ZONE (TAZ) BOUNDARIES IN BCD STUDY AREA | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Date** | **Proposed Land Use** | **668** | **676** | **677** | **678** | **679** | **680** | **681** | **682** | **683** | **684** | **686** | **687** | **688** | **699** | **701** | **702** | **705** | **708** | **709** | Totals |
| **2024** | Total Dwelling Units (SDGEIS) | 0 | 78 | 494 | 1,140 | 0 | 43 | 50 | 1,551 | 269 | 50 | 115 | 385 | 118 | 20 | 0 | 200 | 320 | 90 | 0 | **4,921** |
| **2024** | Total Retail (SF) | 0 | 82,062 | 109,678 | 299,265 | 310,159 | 28,622 | 65,350 | 831,015 | 51,799 | 13,875 | 69,845 | 0 | 147,657 | 7,000 | 0 | 52,500 | 84,000 | 31,394 | 74,456 | 2,258,676 |
| **2024** | Total Office (SF) | 0 | 0 | 0 | 99,755 | 0 | 0 | 0 | 158,013 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 17,500 | 28,000 | 0 | 0 | 303,268 |
| | | | | | | | | | | | | | | | | | | | | **TOTAL SF (2024 SDGEIS)** | **2,561,944** |
| | 2024 SDGEIS Average Sewer Flow GPD | - | 17,983 | 81,184 | 199,130 | 24,813 | 8,585 | 12,603 | 306,585 | 43,535 | 8,378 | 22,453 | 56,448 | 29,084 | 3,493 | - | 34,933 | 55,893 | 15,667 | 5,957 | **926,723** |
| | 2024 SDGEIS Peak Sewer Flow GPD | - | 74,892 | 313,089 | 714,331 | 102,040 | 36,580 | 53,119 | 1,052,928 | 174,331 | 35,722 | 92,714 | 222,775 | 118,786 | 15,174 | - | 141,460 | 220,714 | 65,564 | 25,605 | **3,459,822** |
| | 2019 GEIS Average Flow GPD | 0 | 81,900 | 98,000 | 185,010 | 50,120 | 31,220 | 12,250 | 283,990 | 37,800 | 19,600 | 20,790 | 40,110 | 17,640 | 12,180 | 2,660 | 11,970 | 58,450 | 10,360 | 4,690 | 978,740 |
| | Net Change | - | (63,917) | (16,816) | 14,120 | (25,307) | (22,635) | 353 | 22,595 | 5,735 | (11,222) | 1,663 | 16,338 | 11,444 | (8,687) | (2,660) | 22,963 | (2,557) | 5,307 | 1,267 | **(52,017)** |
| | 2019 GEIS Peak Flow GPD | 0 | 242,748 | 290,467 | 548,361 | 148,553 | 36,308 | 36,308 | 841,733 | 112,037 | 58,093 | 61,621 | 118,884 | 52,284 | 36,101 | 7,884 | 35,479 | 173,243 | 30,707 | 13,901 | 2,844,712 |
| | Net Change | - | (167,856) | 22,622 | 165,970 | (46,513) | 272 | 16,811 | 211,195 | 62,294 | (22,371) | 31,093 | 103,891 | 66,502 | (20,927) | (7,884) | 105,981 | 47,471 | 34,857 | 11,704 | **615,110** |
| | Sewer Shed (RL-Ridge Lea, SH-Sheridan, H - Hartford) | RL | RL | RL | .5 RL; .5 H | RL | SH | RL | RL | H | H | H | H | RL | SH | SH | SH | SH | SH | SH | SH |

| | Ridge Lea | Hartford | Sheridan | ck |
|---|---|---|---|---|
| Ave Sewershed flow GPD | 571,817 | 230,378 | 124,528 | 926,723 |
| Peak Sewershed flow GPD | 2,072,019 | 882,706 | 505,097 | 3,459,822 |
| Ave Sewershed flow change GPD | (64,588) | 19,573 | (7,002) | (52,017) |
| Peak Sewershed flow change GPD | 185,745 | 257,890 | 171,474 | 615,110 |

# APPENDIX D

**WATER SYSTEM DEMAND FIGURES**





*Figure 1 – Pressure, Current Average Demand*





*Figure 2 – Pressure, Current Peak Demand*





*Figure 3 – Available Fire Flow, Current Peak Demand*





*Figure 4 – Pressure, Future Average Demand*





*Figure 5 – Pressure, Future Peak Demand*





*Figure 6 – Available Fire Flow, Future Peak Demand*





*Figure 7 – Available Fire Flow, Future Peak Demand with Mitigation*